

Parameter	Units	Allowable range	Calibrated values	
			TI	RTI
$M_{f,max}$	$\text{mm } ^\circ\text{C}^{-1} (6 \text{ h})^{-1}$	0.001–2.400	1.017 (2)	–
$M_{f,min}$	$\text{mm } ^\circ\text{C}^{-1} (6 \text{ h})^{-1}$	0.001–1.600	0.001 (4)	–
M_f	$\text{mm } ^\circ\text{C}^{-1} (6 \text{ h})^{-1}$	0.001–2.400	–	0.391 (4)
S_{cf}	fraction	0.800–1.000	0.869 (1)	–
$S_{sub,d}$	cm d^{-1}	0.001–0.100	–	0.068 (6)
$N_{mf,max}$	$\text{mm } ^\circ\text{C}^{-1} (6 \text{ h})^{-1}$	0.001–2.400	0.002 (6)	0.256 (8)
f_u	$\text{mm mb}^{-1} (6 \text{ h})^{-1}$	0.001–1.000	0.500 (7)	0.500 (10)
A_{TIPM}	fraction	0.001–1.000	1.000 (3)	0.992 (2)
L_{hc}	fraction	0.001–0.100	0.001 (5)	0.001 (9)
$K_v, \text{deciduous}$	fraction	0.200–1.000	–	0.969 (1)
$K_v, \text{evergreen}$	fraction	0.200–0.800	–	0.308 (7)
$L_{AI, \text{deciduous}}$	$\text{m}^2 \text{ m}^{-2}$	0.100–1.000	–	0.103 (5)
$L_{AI, \text{evergreen}}$	$\text{m}^2 \text{ m}^{-2}$	1.000–4.000	–	1.000 (3)