Hydrol. Earth Syst. Sci. Discuss., 10, 10565-10603, 2013 www.hydrol-earth-syst-sci-discuss.net/10/10565/2013 doi:10.5194/hessd-10-10565-2013 C Author(s) 2013. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Identifying sources and controlling factors of arsenic release in saline groundwater aguifers

C.-W. Liu¹, K.-L. Lu¹, Y.-H. Kao¹, C.-J. Wang¹, S.-K. Maji¹, and J.-F. Lee²

¹Department of Bioenvironmental Systems Engineering, National Taiwan University, 10617, ROC, Taipei, Taiwan

²National Synchrotron Radiation Research Center, 300, ROC, Hsinchu, Taiwan

Received: 21 July 2013 - Accepted: 4 August 2013 - Published: 16 August 2013

Correspondence to: C.-W. Liu (cwliu@ntu.edu.tw)

Published by Copernicus Publications on behalf of the European Geosciences Union.

10565

Abstract

maning

An integrated hydrogeochemical study is carried out to realize the occurrence of arsenic (As) in a saline aquifer. Saline groundwater was mostly concentrated in the uppermost aguifer and non-saline water was in the lower aguifer in the study area. High 5 As concentrations were found in both uppermost and lower aguifers. No correlation among salitation, well depth and As concentration was observed. Both reducing and oxidizing forms of Fe oxyhydroxides were identified in the magnetic fractions, which were concentrated by high gradient magnetic separation (HGMS) technique, revealing

that the redox cycling of Fe occurred in the subsurface. High levels of Fe, HCO_{2}^{-} , DOC and NH⁺₄ concentrations accompanying alkaline pH in the As-rich groundwater were consistent with the mechanism triggered by the microbial mediated reductive dissolution of Fe oxyhydroxides. A threshold value of $50 \,\mu g \, L^{-1}$. As concentration was used as an indicator for identification of active proceeding reductive dissolution of As-bearing Fe oxyhydroxides in the saline aquifer. Desorption behaviors of As were relevant to its

valence in the sediments and the co-existence of anions. Experimental and numerical results showed that additions of CI⁻ and SO²⁻, which represented the main anions of saline water, had minor effect on leaching sedimentary As. Although bicarbonate addition resulted in less As desorption than that of phosphate on a molar basis, the contribution of bicarbonate to the total release of As was greater than phosphate due to the much higher concentration of bicarbonate in groundwater and the associated

microbial mediation. Collectively, the chemical effect of saline water on the As-release to groundwater is mild in the coastal aquifer.

1 Introduction

Arsenic (As) in groundwater exerts a serious environmental issue, notably in south Asia where local residents rely heavily on groundwater for drinking and agricultural purposes (Mandal et al., 1996; Smedley and Kinniburgh, 2002; Rodriguez-Lado et al., 2008;

? hisher ? unclear

10566

Shamsudduha et al., 2009). Utilization of these water leads to a variety of chronic illnesses including skin lesions and cancers both externally and internally (Mandal et al., 1996). In Taiwan, blackfoot disease (BFD), an As-related disease, was first reported and regarded as an endemical disease in Chianan Plain due to intake of artesian As-

contained groundwater (Tseng, 1977). For Choushui River alluvial fan, a neighboring region of Chianan Plain, As-contaminated aguifers are also found and distributed in the coastal area with around 70% of monitoring wells exceeding the drinking water guality standard in Taiwan (0.01 mg L⁻¹) (Liu et al., 2006; Taiwan Sugar Company, 2006). For these two catchments, although high As concentrations were observed at different depths, major characteristics of groundwater as well as dominant release mechanism

selwont.

innobilized minerals? insoluble gr just minerals

whetare

of As were similar, particularly at the BFD endemic area (Wang et al., 2007; Lu et al., 2011).

In general, geogenic minerals such as Fe/Mn oxyhydroxides and As-bearing pyrite are the substantial compounds affecting the quantity of solid As in the subsurface (Smedley and Kinniburgh, 2002; Swartz et al., 2004; Drahota et al., 2009). Whereas suffering from either oxidizing or reducing condition, subsequent transformation of these minerals accompanying the congruent release of As into groundwater have been proposed and well documented (Nickson et al., 2000; Harvey et al., 2002; Swartz et al., 2004; Hasan et al., 2009; Nath et al., 2009). Ionic competition as well as the change ²⁰ of pH and *E*_H also influences the mobility of As (Kim et al., 2000; Su and Pulse, 2001; Appelo et al., 2002; Harvey et al., 2002). The reductive dissolution of Fe oxyhydroxides

- mediated by microorganisms is a plausible process responsible for the enrichment of As in reducing groundwater systems (Ravencroft et al., 2009). Regional surveys concerned with the partitioning of As within the subsurface in
- Choushui River alluvial fan have been conducted by many researchers (Liu et al., 2003a, 2006; Wang et al., 2007, 2011; Lu et al., 2010, 2011). Sedimentary As contents increase significantly with the decrease of particle sizes. The predominant As-hosting minerals are iron oxyhydroxides and As-bearing sulfides. Regarding with the aqueous phase, the enrichment of As in groundwater, mainly as As(III), is intimately involved with

10567

the redox processes. Initially, over-pumping results in the intrusion of air, causing the oxidation of immobilized minerals such as As-bearing pyrite, followed by the accumulation of Fe oxyhydroxides. Along with the gradual formation of reducing environment in the subsurface, the successive reductive dissolution of Fe oxyhydroxides is concurrent with the release of As into groundwater.

Saline water has high ionic concentrations, such as Na⁺, K⁺, Mg²⁺, HCO₃⁻, Cl⁻,

 SO_4^{2-} . The effect of ionic competition against the adsorption site of As onto the iron oxyhydroxides and the microbial interaction that may enhance the arsenic dissolved in the saline aquifer deserve further investigation.

Although several studies have been undertaken to investigate the distribution and occurrence of As in this area, the solid-phase influences on solution-phase arsenic concentrations as well as the effect derived from saline water remain unclear. Hence, the main purpose of this study is to comprehend the partition process of As in the saline sedimentary aquifer with respect to lithology, mineralogy, geochemistry and hydrochemistry. The association between Fe minerals and solid As is conducted and fractionated by high gradient magnetic separation (HGMS) technique. Leaching behaviors of As is performed by batch experiments and modeled by the geochemical code (PHREEQC) (Parkurst and Appelo, 1999) with variation of major anions in saline groundwater. The results of the study are valuable to realize the chemical effect of saline water on the As-release to groundwater in the coastal aquifer.

2 Materials and methods

2.1 Site description and sampling

The study area is located in the coastal area of the southern Choushui River alluvial fan, a major As-contaminated region in southwestern Taiwan (Fig. 1). The area is approximately 24 km² with 24 km from north to south and 1 km from east to west. The average 25

annual precipitation is 1417 mm, most of wich occurs over a five-month period from / h

10568

ugly style

June to October. The subtropical climate is hot and humid, and typhoons often sweep across the island, brining considerable precipitation in the summer. Due to demand and limited supply, groundwater is a vital water resource in this area. Substantial amounts of groundwater have been continuously extracted to meet aquacultural and agricultural

needs. The coastal land is below sea level (Water Resources Agency, 2010). When a typhoon sweeps through western Taiwan, seawater breaks through the embankment and flows inland. In typhoon situations, the flooded coastal area requires more than three days to drain (Water Resources Agency, 2010).

The array of monitoring wells comprised 21 shallow and 7 deep wells with depth ranging from 7 to 24 m and 38 to 110 m, respectively (Liu et al., 2003a). In this area, seasonal surveys of groundwater quality were undertaken by Tainan Hydraulics Laboratory from 1992 to 2004, and this study adopted the monitoring data for analyses (Tainan Hydraulic Laboratory, 1992–2004). To eliminate the fluctuations of seasonally measured groundwater quality, the time-averaged values of aqueous parameters were used to represent the hydrochemistry of local groundwater.

In addition, two boreholes, YL6-1 and YL7-1, located in around 10 m away from YL6 and YL7, respectively, which contained higher As concentrations than other monitoring wells. These two wells, located in the uppermost aquitards, were purposefully drilled for the investigation of lithological, mineralogical and geochemical characteristics of As-rich saline aquifer from the surface downwardly to a depth of 25 m (Fig. 1). A drill rig and a split-tube sampler with 50 mm O.D. PVC liner were used to collect sediment cores in 100 cm segment. The core-ends were sealed in the field with paraffin wax to minimize the exposure to the atmosphere. Furthermore, core samples were stored at 4° in polyethylene bags to reduce microbial activities before use.

no charges in state ?

10569

2.2 Analytical methods

in correct sentence

1

2.2.1 Aqueous phase

The field sampling methods used the NIEA code W103.50B set by the Taiwan Environment Protection Administration. At least 3 wellbore volumes of groundwater were purged before sampling. Dissolved oxygen (DO), temperature (*T*), pH and electrical conductivity (EC) were measured in a flow-through cell every 5 min during well purging. Cell sensors were calibrated with standard buffer solutions (all from Merck Co.), which have pH = 4.0, 7.0 and 10.0; EC = 1410 μ S cm⁻¹, in the field before measuring.

these parameters (APHA, 1998). Water samples were collected only after pH and EC
stabilized, and the fluctuations of pH and relative EC were less than 0.1 and 5%, respectively. After purging, a probe (MiniSonde manufactured by HydroLab, USA), which is 5 cm in diameter and 70 cm in length, including a data logger, a circulator and 3 sensors for DO, *T*, EC, and pH measurements, was lowered down to the screen position of the well casing and remained there for at least 10 min before water quality parameters
were recorded (Chen and Liu, 2003).

Water samples for metal and other cations' measurements were filtered by 0.45 μ m glass fiber papers and acidified with HNO₃ (Merck ultrapure grade) to pH 2. Samples, were then kept in ice boxes and delivered to the laboratory within 24 h. Dissolved ions concentrations were determined by conventional methods (APHA, 1998). The concentrations of major anions (Cl⁻, NO₃⁻ and SO₄²⁻) and cations (Na⁺, K⁺, Ca²⁺, Mg²⁺ and NH₄⁺) in groundwater samples were analyzed by Dionex DX-120 ion chromatography. Iron concentration was measured with inductively coupled plasma and atomic emission spectrometry (ICP-AES) (Varian, VISTA-MPX). Arsenic concentration was analyzed using an electro-thermal atomic absorption spectrometer (AAS, Perkin-Elmer AA100) and a hydride generation (HG) system (Perkin-Elmer FIAS100); 0.5% NaBH₄ in 0.25% NaOH and 1 MHCl were added to reduce arsenic to arsine. Four major As species, As(III), As(V), methylarsonic acid MMA and dimethylarsinic acid DMA, were separated using an anion column (Phenomenex, Macherey-Nagel, Germany; Nucleosil, 10 μ m,

250 mm × 4.6 mm), connected with an high performance liquid chromatograph (HPLC) (Perkin Elmer, Series 200), which was interfaced to an electro-thermal atomic absorption spectrometer (AAS) (Perkin-Elmer, AA 200) and a hydride generation (HG) system (Perkin-Elmer, FIAS 100) (Huang et al., 2003). The recovery rate of As(III) and As(V) vielded 100.7 ± 3.8 % and 97.2 ± 4.0 %, respectively. Dissolved organic carbon (DOC) was measured using the high temperature combustion method (APHA, 1998).

2.2.2 Solid phase

uslyskyle

winga

~

rept tion

Sediment samples were freeze-dried, ground and sieved to ensure representative sampling. The contents of As and Fe in the cores were determined following EPA 3050B. Main compositions in the core samples were determined by X-ray fluorescence (XRF) (Spectro, XEPOS). Percent abundance of total carbon was determined with a model 2400 CHN analyzer (VarioEL-III, Heraeus, Germany). Total organic carbon (OC) was then determined by subtracting the amount of carbon present as carbonate from the total amounts of carbon.

Preparation of different particle size fractions for mineralogical analysis was performed by dry sieving on freeze-dried samples. Density separation was conducted on freeze-dried samples for each of 6 depths (8, 10, 13, 15, 17 and 21 m for YL6-1 and 8, 10, 14, 17, 21 and 24 m for YL7-1) of two boreholes to guantify As associations as a function of Fe contents. The clay samples were dispersed in H_2O , and fine $(< 1 \,\mu m)$ and coarse clay $(1-2 \,\mu m)$ fractions were separated by centrifugation (Jackson, 1979). The silt was segregated from the sand by wet-sieving (53 µm sieve). The clay fractions were dialyzed against double distilled water (DDW) and then freeze-dried. Clays were separated into magnetic and non-magnetic fractions using high gradient magnetic separation (HGMS) technique (Schulze and Dixon, 1979). Total As and Fe contents in these fractions were also determined. Mineralogy of iron were determined by high-resolution X-ray photoelectron spectrometer (HR-XPS) (PHI Quantera SXM).

which was equipped with a K α X-ray beam at 3.8 kW generated from an AI rotating anode. Each spectrum was obtained by plotting the measured photoelectron intensity 10571

as a function of the binding energy (BE). Binding energies of photoelectrons were calibrated by the aliphatic adventitious hydrocarbon C (1s) peak at 284.6 eV.

Arsenic in the sediments used in leaching experiments was analyzed with X-ray absorption near-edge structure (XANES) spectra to determine arsenic speciation. X-ray absorption spectra (XAS) at the As K-edge (11867 eV) were collected at Wiggler 20 beamline BL-17C at National Synchrotron Radiation Research Center (NSRRC), Hsin-Chu, Taiwan. Beam line Wiggler 20 (17C), with energy ranging from 4 to 15 keV, employs a Si(111) double-crystal monochromator for energy scanning with a resolving power $(E/\Delta E)$ of 7000 and beam intensity of around $10^9 \sim 10^{10}$ photons per sec. All

samples were fixed onto an aluminum holder, sealed with Kapton tape and placed at 45° to the X-ray beam. Sample spectra were collected from -50 to +100 eV about the As K_{α} edge of 11867 eV and compared to XANES spectra of selected reference standards, including arsenate (Na₂HAsO₄ • 7H₂O) and arsenite (NaAsO₂). In addition, the Au L_3 -edge spectrum was monitored by the I_r chamber simultaneously with I_t and

 $I_{\rm f}$ chambers, serving as the reference to calibrate energy shift due to monochromator 15 drifts. Several scans were processed and averaged on each sample to improve the data quality of XAS spectra. The Athena program was used for standard background subtraction and edge-height normalization using AUTOBK algorithm (Ravel and Newville, 2005). 16hr

20 2.3 Batch desorption experiments

Batch experiments were performed to investigate the effect of major saline anions and phosphate ions on arsenic desorption from the sediment samples under atmospheric condition. In reference to local saline groundwater composition as well as those used in the literature, four kinds of anions in the local saline groundwater, including Cl⁻, 25 SO²⁻₄, HCO⁻₃ and PO³⁻₄, with varied concentrations, were selected to conduct leaching experiment to assess the competitive effects of various anions on As release. Except PO_4^{3-} , four levels of concentrations (0.001, 0.0(, 0.1 and 1 M) were used. These concentrations bracketed the highest and lowest concentrations of the respective anions

10572

was

unrealistically high for atleast KCOS

Skichtion of reduced Sediment

expected to be found in the local area. Phosphate generally has low concentration in groundwater due to strong bond of phosphate with clay minerals and metal hydroxides, particularly iron hydroxides, as well as its use in the biological cycle (Matthess, 1982). For phosphate, only three levels of concentrations (0.001, 0.01 and 0.1 M) were de-

signed. The supply of phosphorus concentration in the local groundwater of the study area was generally from the use of agrichemicals and household detergents.

The stock solutions of competitive anions were prepared in the laboratory by dissolving pre-weighted amount of reagents of NaCl, Na₂SO₄, NaHCO₃ and NaH₂PO₄, into DDW. The pH of these solutions was adjusted to around 7. For each of trial, 0.2 g of dried sediments, which were within the well screen range of either YL6-1 (16 m) or YL7-1 (18 m), was mixed with 3 mL of solution in a 50 mL centrifuge tube. The reaction flask was shaken at approximately 150 rpm by a reciprocal shaker lasting at least 30 days. After a specific period of shaking, an aliquot of the lechate was filtrated with 0.22 µm filter before analysis of As concentration.

5 2.4 Numerical simulation

The numerical program, PHREEQC (Parkurst and Appelo, 1999) was adopted to model the batch experiments of desorption processes of arsenic from the YL6-1 and YL7-1 core samples under various anionic concentrations. PHREEQC is based on the equilibrium chemistry of aqueous solutions interacting with minerals, gases, solid solutions, exchangers and sorption surfaces. These processes can be combined with equilibrium and/or chemical kinetic reactions. Several processes have been accounted for the basic calculation in the study, including equilibrated speciation, equilibrium phases, surface sorption and kinetic desorption that are mimic the batch experimental conditions.

10573

3 Results

Julin's

3.1 Description of groundwater quality

Table 1 lists the physicochemical data of groundwater samples. The pH of sampled wells was mostly above 7 and characterized as mild alkaline with the highest pH of 8.6 in YL14. Temperatures of all samples were uniform with an average of 26.0°. To classify the major ions for groundwater and summarize the main distinctions in hydrogeochemical composition between different water sources, Piper diagram was used. Plots of major ions on the Piper diagram showed that most samples, 12 out of 28 wells, were categorized into Group 4 of saline type, and 5, 7 and 4 samples were in Groups 1 (temporary hardness), 2 (alkali carbonate) and 3 (permanent hardness), respectively (Fig. 2). Local groundwaters were characterized as Na-Cl or Na-Mg-HCO₃ type. Notably, the Na-Cl type samples concentrated in the southern part in contrast to the Na-Mg-HCO₃ type in the northern part. High EC values accompanying well correlation between Na and Cl ($r^2 = 0.99$, p < 0.01) revealed the severe salination in groundwater (Liu et al., 2003a). The major causes of shallow groundwater salinization were the vertical infiltration of salt water from fish ponds farming and the seawater over flooding in the subsidence coastal area. Seawater intrusion plays a minor role on the local groundwater salinization due to aquifers are enclosed by the aquidard which does not directly contact the seawater (Liu et al., 2003b)

style

towhich extat

due to scanetar Areth where displacement

6

Referred to N species, NH⁺₄ was the deminant species (0.2 to 20.3 mgL⁻¹), indicating the presence of reducing condition in this region (Lu et al., 2011). Further signatures were evidenced by high levels of pH and HCO₃ concentrations (Stumm and Sulzberger, 1992). High but heterogeneous distribution of DOC concentrations was observed. High HCO₃ concentration may be originated from silicate weathering,

oxidation of organic carbon and carbonate dissolution (Mukherjee and Fryar, 2008). The Na-normalized Ca vs. HCO_3^- and Mg plots (Wang et al., 2012) suggest that the silicate weathering may be the main processes occurred during the Holocene trans-

meeningless forthis Listribution provide median

meaning? towards which direction?

gression. The weathering processes facilitated the formation of secondary clay minerals and Fe oxides, which provided sufficient sorption sites for the As enrichment of solid (Berg et al., 2008). Moreover, dissolved organic matter can be another active source for HCO3 in groundwater under reducing conditions. Arsenic concentrations also showed a heterogeneous distribution over the whole study area, spreading from 6.7 to 533.1 μ g L⁻¹, with the mean value of 89.2 μ g L⁻¹. According to the data, 25 out of 28 wells exceed the Taiwan Ilmitation of As concentration for drinking water (10 µgL⁻¹) and 12 out of 28 wells were above the concentration of 50.0 µg L⁻¹. Notably, electrical conductivity (EC) values varied heterogeneously but were higher in the shallow wells (YL1-YL21), spanning more than one order of magnitude among wells (Fig. 3a). The EC values of deep wells (YL22-YL28) were all less than 900 µs cm⁻¹ suggesting that the lower aquifer was not affected by saline water intrusion. But spallow salinized wells water, eg YL5 and YL16, did not necessarily contain higher As concentrations than those in the deeper wells water, eg)L22 and YL25. No correlations were found among EC, depth and As concentration (Fig. 3b). Iron concentrations were high, reaching up to $1140 \,\mu g L^{-1}$. Of all the sampled waters, 73% exceed the WHO guideline value of 300 µgL⁻¹ for Fe (WHO, 2002).

3.2 Lithological and geochemical characterization of saline sedimentary aquifer

The sedimentary sequence of alternating unconsolidated clays and sands from both boreholes exhibited dissimilar patterns, particularly at the top layer and screen range (Fig. 4). The sediments ranged in texture from gravel to clay and in color from grey - to black. The top layer for both boreholes consisted of various caps soil (0-3 m). At greater depths, the remaining silty sand and following sand showed grey to black in color. The gradual fining sequences of deposits of both boreholes were suggestive of deposition in a fluvial environment. The sediment is in grey to dark nature. The biostratigraphic analysis indicated that the formation age is the Holocene (Huang, 1996). Dark grey fine sand layers were also found in the shallow As affected aquifers of the

10575

 Hetao Bassin, Inner Mongolta, where groundwaters were anaerobic (Guo et al.; 2008). In contrast to silty sand interlayered with clay as the main composition of the screen range of YL6-1, the screen range of YL7-1 mainly comprised of sand, revealing the heterogeneous depositing process, even within a distance of 2.5 km. The observed
 fine-grained sediments in the upper layer (3–19 m) locally acted as aquitards, however,

they vary significantly on a regional scale. Geochemical profiles of both YL6-1 and YL7-1 were depicted with respect to total As, Fe and organic/inorganic carbon (OC/IC) contents (Fig. 4). The solid As ranged from 4.69 to 11.53 mg kg⁻¹ with mean value of 8.30 mg kg⁻¹ for YL6-1 and from 4.02 to

12.77 mg kg⁻¹ with mean value of 7.21 mg kg⁻¹ for YL7-1. The Fe contents varied from 3.0 to 4.1% and 2.5 to 4.6% with separate mean values of 3.6 and 3.5% for YL6-1 and YL7-1. There were no significant variation of As and Fe contents was observed in the core profile of YL6-1. However, contrary to the increasing trend of solid As within the screen range of YL7-1, the declining Fe amounts were measured. The As and Fe contents observed in other As-affected areas such as Bangladesh (BGS and DPHE, 2002). The amounts of OC and IC in both cores were comparable, generally less than 0.5% (Fig. 4).

Main-compositions of the analyzed sediments by XRF were Si, Al, Fe, K, Ca and Mg (Table 2). These results were similar to the previous studies in Bangladesh (Anawar et al., 2003; Swartz et al., 2004). Sulfur and manganese were the minor constituent elements, and their contents were less than 1300 and 300 mg kg⁻¹, respectively. Correlated relations between As with Fe ($r^2 = 0.46$, p < 0.05), Mn ($r^2 = 0.58$, p < 0.05) and S ($r^2 = 0.78$, p < 0.05) were observed in YL6-1 whereas no interrelations among these elements were observed in YL7-1, indicating the complex deposition process and in-

3.3 Analytical results of HGMS

The HGMS studies were operated specifically to concentrate Fe minerals from the sediments, and these separates exhibited different profiles of Fe and As in comparison

groundwoter

oryelber opeichised?

menningless any proof

according to KRG- analysis

too simple statement

medior

exements

pristine wrons in this context

Why as deposition process. Canibbe a hydrological hydrological process

untrected

with the pristine samples (without HGMS treatment) (Fig. 4). Among these separates, the average As contents reached 82.2 and 119.4 mg kg^{-1} with the mean Fe contents of 12.7 and 15.0% for YL6-1 and YL7-1, respectively. Arsenic contents in YL6-1 ranged from 50.3 to 90.6 mg kg⁻¹. However, ¥L7-1 showed the higher As contents, spreading ⁵ from 100.2 mg kg⁻¹ at the top to 210.7 mg kg⁻¹ at the bottom. In contrast to the samples without HGMS treatment, the As contents in the magnetic fractions increased about Len 10-fold, confirming the As-host ability of Fe minerals in the sediments.

In addition to determine the quantity of As and Fe in the magnetic fractions, the types of Fe minerals were characterized by HR-XPS, and the results were presented by two curves -(1) the experimental curve after smoothing using the spline method. and (2) the curve of the fitted components (Fig. 6). The iron signal was a doublet because of spin coupling, corresponding to $Fe2p_{3/2}$ (BE = 706-718 eV) and $Fe2p_{1/2}$ (BE = 723-732 eV). The Fe2p_{3/2} line can be fitted by four components with binding energies of about 709, 712, 714 and 717 eV, respectively (Fig. 6). The primary peak 15 (Fe2p_{3/2}) at 709.2-709.3 eV was characteristic of Fe(II) in FeO compounds (Fig. 6); that at 710.9-711.1 eV was characteristic of Fe(III) in Fe₂O₃ compounds (Fig. 6b, c, e and f); and that at 711.2-712.3 eV was characteristic of Fe(III) in FeOOH compounds (Fig. 6a and d). All analyzed samples contained both reducing and oxidizing forms of Fe oxyhydroxides, suggesting the redox cycling of Fe in the shallow aquifer.

20 3.4 Batch experiment of anions effects on As desorption

The valence of solid As in the selected sediments within the well screen range of YL6-1 (16 m) and YL7-1 (18 m) for leaching test was determined, comprising of As(III) and As(V) from XANES spectra. In contrast to the dominance of As(III) in YL6-1, As(V) was dominant in YL7-1, reflecting the complex deposition process (Fig. 6). Notably, ²⁵ the groundwater EC in YL6 (12129μScm⁻¹) was six times higher than that of in YL7 (2039 µS cm⁻¹), indicating these two sediment samples) under distinct aqueous geochemical environments The As decorption behaviors were certainly worthy of evaluation. The kinetics desorption of arsenic from both sediments were assessed by the

10577

are li Fferent

addition of different competitive anions with various concentration levels (Fig. 7). For sulfate and chloride, even at the highest loading of 1 M, no obvious elevated concentration of As was detected within the 75 days of extended experimental duration, implicating the negligible influence derived from seawater salination or arsenic desorp-

tion. For bicarbonate and phosphate, the desorbed fractions increased rapidly within 24 h, followed by gradual increase, and reached near equilibrium after about 30 days. Moreover, the increase in arsenic desorption was generally consistent with the elevated anionic concentrations. The predominance of As(V) in the aqueous phase (~99%) assemblage with the mixing of As(III) and As(V) as the sedimentary As can be in part ¹⁰ attributed to the imposed condition (under atmospheric environment).

For bicarbonate, the leached portions of As varied from 0.46 to 1.79 mgkg⁻¹ for YL6-1 and from 0.08 to 0.75 mg kg⁻¹ for YL7-1. As compared with the initial desorption concentration at 0.1 M for YL6-1, the desorption of As in YL7-1 was initiated while amending with 0.01 M of bicarbonate. Only half amount of As, however, was released in 15 the presence of the highest concentration (1 M) (Fig. 8). The great effect of bicarbonate

on YL6-1 than YL7-1 was due to formation of aqueous As-HCO3 complexes as well as competitive displacement of arsenic (Apello et al., 2002).

For phosphate, the leaching concentrations of As ranged from 0.91 to 1.83 mg kg⁻¹ for YL6-1 and 0.90 to 2.72 mg kg⁻¹ for YL7-1. Arsenic release was a function of phosphate added for low phosphate additions, but became insensitive at high phosphate

addition, particularly for YL6-1. Between the lowest (0.001 M) and highest (0.1 M) concentrations of phosphate, the fraction of arsenic desorbed increased only twice of magnitude in YL6-1 (Fig. 8a). With respect to YL7-1, the removal of As was proportional to the added anionic concentration (Fig. 8b). Besides, the equilibrium As concentrations observed at sets with 1 M bicarbonate, and 0.01 and 0.1 M phosphate were similar in YL6-1, revealing the limitation of leachable As. Consequently, the leaching behaviors

were different for the two cores, with either bicarbonate or phosphate. Furthermore, bicarbonate anions caused less desorption of arsenic than phosphate on a molar basis.

Fe - oryh.ox. be reducing except fes 04? fes 04? con it be in silicated silicated silicated silicated silicated silicated silicated

3.5 Numerical modeling of As desorption experiment

The experimental data of As desorption were modeled by the PHREEQC. Four types at anions including Cl⁻, SO_4^{2-} , HCO_2^- and PO_4^{3-} with the same varied concentrations in the batch experiment were simulated using the titration approach (Chen and An-

The

(1)

- derson, 2002). The initial arsenic contents of 8.5 and 9.9 mg kg^{-1} in core samples of YL6-1 and YL7-1, respectively, were assumed. The weight of core sample was 0.2 g and the specific area of the sediment was $15 \text{ m}^2 \text{ g}^{-1}$ (Maji et al., 2012). The surface complexation model for hydrous ferric oxide (Hfo) developed by Dzombark and Morel (1990) was adopted of which two types of sites could accommodate all experimental
- ¹⁰ data. These were the "strong" and "weak" sites and labeled as "s" and "w" in Table 3. The weak and strong adsorption site density were 0.005 and 0.2 molesites mole Hfo⁻¹. The thermodynamic data of As^{3+} , As^{5+} , SO_4^{2-} , HCO_3^- and PO_4^{3-} were listed in Table 3. Notably, no thermodynamic data available of Cl⁻ surface complexation reactions due to the chemically stable of Cl⁻ in nature. A first order reaction model was proposed to
- 15 represent the kinetic desorption of As as follows

$$\frac{\mathrm{d}C}{\mathrm{d}t} = -k_1 C$$

where *C* is the arsenic concentration, k_1 is the kinetic rate constant and is set to 0.05 and 0.1 for As³⁺ and As⁵⁺, respectively (Maji et al., 2007, 2011, 2013).

The simulated time dependent arsenic desorptions of YL6-1 and YL7-1 at various anionic (PO_4^{3-} , HCO_3^- , SO_4^{2-} and CI^-) concentrations were shown in Fig. 9. The simulated arsenic desorption curves and the amount of arsenic desorption of YL7-1 and YL6-1 by PO_4^{2-} were close to the experimental results, but were much less than the experimental data as competed by HCO_3^- . The laboratory arsenic desorption experiment used the in-situ core samples which contain both organic carbon and inorganic carbon. These carbons can be converted and utilized by microbes as energy sources and pro-

mote the iron oxyhydroxide dissolution accompanying with the desorption of arsenic.

10579

Moreover, dissolved As can complex with dissolved organic matter preventing adsorptive interaction between As and flocculated iron oxide in saline water (Waslenchuk and Windom, 1978). The simulated model considered the pure inorganic adsorption reaction which did not include the desorption enhanced by the microbial reaction and thus greatly underestimated the amount of arsenic desorption. For sulfate and chloride, the effect on the amount of arsenic desorption are minor which agree to the batch experimental results (Su and Pulse, 2001; Radu et al., 2005; Halima etal., 2009; Maji et al., 2013).

Notably, the sulfate ion slightly promoted the arsenic desorption whereas the chloride ion yielded less desorption of arsenic which may mildly reduce the aqueous arsenic concentrations. The comparison of the experimental and simulated amount of As desorption by PO_4^{3-} and HCO_3^{-} of YL6-1 and YL7-1 after 30 days are given in Table 4.

4 Discussion

4.1 Water quality related with As enrichment

Shallow groundwater samples were generally salinized by seawater flooding and salt water percolation from fish pond farming. Seawater intrusion shows small effect on aquifer salinization. Arsenic concentrations did not correlated with the well depth and the EC values suggesting that the effects of saline water on the arsenic release were complex. Among the collected water samples, high As concentration with increasing levels of HCO_3^- , NH_4^+ and Fe concentrations coupled with high pH (pH = 8) typically represented the onset of reducing dissolution of Fe oxyhydroxides concurrent with the mobility of As. Poor correlation between dissolved As and Fe concentrations in groundwater indeed reflected the complexity of geochemical reactions in the subsurface (Nickson et al., 2000; Harvey et al., 2002) and in part can be attributed to the mixing with saline water. Sulfate in saline groundwater may act as an electron acceptor and promotel **X**-precipitation of sulfide minerals. Formation of sulfide minerals restrained the

wor on s style, a sample in not salinized. The putters refer to salinization of the aquifer 25 25

not really

conditions

are

reductive

weak

Ly when?

10

liberated As in the anaerobic environment. The redox cyclic interactions of iron and sulfur resulted the low-As and high-Fe concentrations in saline water (Wang et al., 2011). Significant relation of aqueous As was only observed with DOC ($r^2 = 0.41$, p < 0.05) also as indicated by Harvey et al. (2002). The existence of organic carbon can trigger microbial activity, followed by the formation of reducing condition and release As via chemical and biological processes in the subsurface formation (Harvey et al., 2002; Sutton et al., 2009; Halima et al., 2009). Accordingly, these characteristics were consistent with the microbially mediated release of As via reductive dissolution of iron oxyhydroxides (Nickson et al., 2000; McArthur et al., 2001; Harvey et al., 2002; Rowland et al., 2008; Hasan et al., 2009; Nath et al., 2009).

Further assessment of groundwater quality was conducted on a basis of source water standard for As in Taiwan, $50 \,\mu\text{g L}^{-1}$. For the wells with As above $50 \,\mu\text{g L}^{-1}$, positive correlations were observed between As with Fe and DOC ($r^2 = 0.46$ and 0.41, p < 0.05). The other group wells, with the As below $50 \,\mu\text{g L}^{-1}$, showed poor relation

¹⁵ between As with Fe, even with DOC ($r^2 < 0.01$). Correlations among As, Fe and DOC concentrations were only significant via the categorization of As concentration with 50 µg L⁻¹, implicating that a threshold value of As concentration served as an indicator for identifying the active proceeding of reductive dissolution of As-bearing oxyhydroxides in the study area.

4.2 Implication from solid profiles of As, Fe and OC

Previous study has proposed that the quantity of As contents in the sediments was concentrated in the clay samples that were deposited during the Holocene transgression (Liu et al., 2003). Actually, the "clay minerals" fractionated from sediments, comprising of magnetic and non-magnetic fractions, were the main pool for As retention in this area. Irrespective with the poor relationship between As and Fe among the pristine sediments, significant and positive correlation was observed in the clay fractions

 $(r^2 = 0.50, p < 0.05)$. The direct source of As in groundwater is believed to be the chemically active As fraction in the sediments, i.e. Fe oxyhydroxides in this area (Lu et al.,

10581

2010). Hence, distinct difference of As contents within the screen range between two boreholes, particularly for the magnetic fraction, can be a potential factor affecting the heterogeneous distribution of As concentrations among these wells.

- In general, the distribution of major and trace elements in sediment was controlled by various factors such as sediment texture, source-rock mineralogy and geochemical processes (Abraham, 1998). According to the analytical data, although these two cores exhibited different soil color and types, average As and Fe contents for YL6-1 and YL7-1 were comparable (Table 2). Concomitant but gradual decrease of solid As, Fe and OC in the pristine samples (without HGMS treatment) of both boreholes was
- ¹⁰ observed within the screen range (Fig. 4). These geochemical profiles provided the direct evidence for the pathway relevant to microbial-mediated reductive dissolution of Fe minerals with concurrent decrease of OC contents, despite the variation of the trends were only moderate.

4.3 Effects of salination and anionic competition

¹⁵ Groundwater quality at the coastal shallow aquifer in this area was generally characterized as salination and As-contamination (Liu et al., 2003; Wang et al., 2007; Lu et al., 2010, 2011). In this study, saline water samples (Group 4) mainly distributed in the shallow depth and contained higher As concentration than other types. Actually, saline water intrusion provided excessive amounts of competition ions such as Cl⁻ and

SO²/₄ which can theoretically function as HCO³/₄ and PO³/₄ (Kim et al., 2000; Appelo et al., 2002). However, no obvious evidence showed direct connection between salination and As-contamination in the groundwater quality data, leaching experiment and numerical simulations. The competitive effect of salination on the motivation of As mobility has been suggested (Keon et al., 2001), it contributed only minor portion of As
 concentration in the batch experiments. However, the isotopic analyses show that the

high enrichment of ${}^{34}S_{[SO_4]}$ and ${}^{18}O_{[SO_4]}$ in saline groundwater caused by microbialmediated reaction of sulfate, and high ${}^{18}O$ enrichment factor ($\varepsilon_{[SO_{4-H_2O}]}$), suggesting A concentration is the resultant of all upstream processes

nonsense

10582

that sulfur disproportionation is also an important process during the reductive dissolu-tion of As-containing iron oxyhydroxides (Kao et al., 2011). Limited co-precipitation of ion-sulfide increased the rate of As liberation under anaerobic conditions.

- Since the high arsenic groundwater at Choushui River alluvial fan commonly has bicarbonate as the major anion, the role of competitive adsorption of bicarbonate should not be neglected. According to the results of batch experiments of Kim et al. (2000), bicarbonate solutions leached the greatest quantity of arsenic (1.2-1.6 mg kg⁻¹) from the aquifer materials (with a total arsenic concentration of 24.6 mg kg^{-1}), as compared to other solutions. Similar results were also observed herein. However, Radu et al. (2005)
- reported that the carbonate ions had small effect on competing with As for iron oxidecoated sand and resulted in only a slightly decrease in As adsorption. The cause of the major difference in the carbonate ions effect on the As desorption is that Kim et al. and our study used the in-situ core sample as the adsorbent whereas Radu et al. used the synthetic iron oxide-coated sand. The in-situ core sediment contained OC, IC and mi-
- cobials which can biogeochemically enhance the Fe oxyhydroxides dissolution and As 15 desorption (Liao et al., 2011). Our numerical simulation results, which only considered inorganic competition by carbonate ions, also show a much less desorption of As while comparing with the laboratory batch data. The vital role of microbial mediated desorption and mobilization of As in the groundwater is clearly evident. Varied equilibrium
- concentration between different amending sediments can be ascribed to the sources of adsorption host (Fuller et al., 1993; Wang et al., 2004). Moreover, desorption of arsenic by bicarbonate was easy assessable at YL7-1, but reached maximum values at YL6-1. Due to the observation of higher bicarbonate concentration than phosphate in the in-situ environment, the contribution of bicarbonate to the total arsenic leaching is greater than phosphate, especially for YL6-1.

As compared to bicarbonate, there was a significant elevation of arsenic concentration as increasing phosphate level. For YL6-1, suggesting that the desorption rate was high at low phosphate concentration. In contrast, the proportional increase of As was concurrent with the imposed phosphate concentration in YL7-1 (Fig. 8). Different

10583

valences of dominant As species in the sediment explained the desorption trends of phosphate between these sets (Fig. 7). Arsenate is generally susceptible to the presence of elevated concentration of phosphate. The strong ability of phosphate to inhabit the arsenate adsorption on iron oxyhydroxides has been verified (Dixit and Hering, 2003). The competition between PO_4^{3-} and $As(OH)_3$ is likely to be less significant than the PO_4^{3-} and AsO_4^{3-} (Smedley and Kinniburgh, 2002). Moreover, the YL7-1 solutions reached near-equilibrium faster than the YL6-1 solutions, which could reflect their lower particle size and its contribution to intra-particle diffusion (Ghosh et al., 2006).

5 Conclusions

- To comprehend the hydrogeochemical characteristics of As-contaminated saline aquifer in the coastal area of the southern Choushui River alluvial, detailed analyses were operated as a function of lithology, mineralogy, geochemistry and hydrochemistry. Leaching experiments and numerical simulations were also conducted to assess the competitive effect of various anions on As release. Groundwater was mostly as Na-Cl
- or Na-Mg-HCO₃ type dependent on the depth in this area. Saline water type was prevailing in the uppermost aquifers and non-saline water was in the lower aquifer. High level of As concentrations were found in both uppermost and lower aquifers. No direct evidence revealed the correlation among salination, As concentration and well depth.
- The analytical results evidenced that the clay fraction, especially for the magnetic fraction, acted as the principal pool of As in the sediment. Significant correlation of As with DOC and Fe concentrations only observed in groundwaters with a threshold of elevated As concentrations (> $50 \,\mu g L^{-1}$) which can serve as an indicator in the saline aquifer for active proceeding of reductive dissolution of Fe oxyhydroxides with microbially mediated degradation of organic matter. Concurrent decrease of solid As, Fe
- and OC contents observed within well screen area further supported the presence of actively reductive dissolution of As-bearing Fe minerals. The leaching behaviors of As among the posited sediments were closely dependent on its solid valence and the () hoppoven?

kinds of competitive anions. Contrary to YL6-1 as the dominance of As(III) in solid phase, the dominant As(V) in the sediment of YL7-1 was more liable to phosphate addition. Experimental and numerical results showed that the contributions of Cl⁻ and SO_4^{2-} to arsenic desorption were low as compared to those of bicarbonate and phos-

- but oxidation unler experimental conditions?
- phate. Although phosphate had a higher competitive potential than bicarbonate on an equal molar concentration of anions, the prevalence of bicarbonate and microbial mediated reactions in the subsurface contributed greater amount of dissolved As than phosphate. Collectively, the effect of saline water on the As-release to groundwater is mild in the coastal aquifer.
- Acknowledgements. The authors would like to thank the National Synchrotron Radiation Research Center for providing XANES analyses and the National Science Council of the Republic of China, Taiwan, for financially supporting this research under Contract No. NSC-95-2313-B-002-050-MY3.

References

30

- 15 Abraham, J.: Spatial distribution of major and trace elements in shallow reservoir sediments: an example from Lake Waco, Texas, Environ. Geol., 36, 349–363, 1998.
 - Allison, J. D., Brown, D. S., and Novo-Gradac, K. J.: MINTEQA2/PRODEFA2 a Geochemical Assessment Model for Environmental Systems, US Environmental Protection Agency, Athens, Georgia, 1990.
- Anawar, H. M., Akai, J., Komaki, K., Terao, H., Yoshioka, T., Ishizuka, T., Safiullah, S., and Kato, K.: Geochemical occurrence of arsenic in groundwater of Bangladesh: sources and mobilization processes, J. Geochem. Explor., 77, 109–131, 2003.
 - APHA: Standard Methods for the Examination of Water and Waste Water, 20th Edn., American Public Health Assoc, Washington, D.C., 413–426, 1998.
- Appelo, C. A. J., Van der Weiden, M. J. J., Tournassat, C., and Charlet, L.: Surface complexation of ferrous iron and carbonate on ferrihydrite and the mobilization of arsenic, Environ. Sci. Technol., 36, 3096–3103, 2002.
 - Berg, M., Trang, P. T. K., Stengel, C., Buschmann, J., Viet, P. H., Van Dan, N., Giger, W., and Stuben, D.: Hydrological and sedimentary controls leading to arsenic contamination of

10585

groundwater in the Hanoi Area, Vietnam: the impact of iron-arsenic ratios, peat, river bank deposits, and excessive groundwater abstraction, Chem. Geol., 249, 91–112, 2008.

- BGS and DPHE: Arsenic contamination in groundwater in Bangladesh, edited by: Kinniburgh, D. G. and Smedley, P. L., BGS Technical Report, Nottingham, 2002.
- 5 Chen, W. F. and Liu, T. K.: Dissolved oxygen and nitrate of groundwater in Choushui Fan-Delta, western Taiwan, Environ. Geol., 44, 731–737, 2003.
- Chen, Z. and Anderson, G.: Environmental Applications of Geochemical Modeling, Cambridge Press, 284 pp., 2002.
- Dixit, S. and Hering, J. G.: Comparison of arsenic(V) and arsenic(III) sorption onto iron oxide minerals: implications for arsenic mobility, Environ. Sci. Technol., 37, 4182–4189, 2003.
- Drahota, P., Rohovec, J., Filippi, M., Mihaljevic, M., Rychlovsky, P., Cerveny, V., and Pertold, Z.: Mineralogical and geochemical controls of arsenic speciation and mobility under different redox conditions in soil, sediment and water at the Mokrsko-West gold deposit, Czech Republic, Sci. Total. Environ., 407, 3372–3384, 2009.
- 15 Dzombak, D. A. and Morel, F. M. M.: Surface Complexation Modeling: Hydrous Ferric Oxide, John Wiley and Sons, New York, 1990.
 - Fuller, C. C., Davis, J. A., and Waychunas, G. A.: Surface chemistry of ferrihydrite, Part 2: Kinetics of arsenate adsorption and co-precipitation, Geochim. Cosmochim. Acta, 57, 2271–2282, 1993.
- 20 Ghosh, A., Eduardo Saez, A., and Ela, W.: Effect of pH, competitive anions and NOM on the leaching of arsenic from solid residuals, Sci. Total Environ., 363, 46–59, 2006.
 - Guo, H., Yang, S., Tang, X., Li, Y., and Shen, Z.: Groundwater geochemistry and its implications for arsenic mobilization in shallow aquifers of the Hetao Basin, Inner Mongolia, Sci. Total Environ., 393, 131–144, 2006.
- Halima, M. A., Majumder, R. K., Nessa, S. A., Hiroshiro, Y., Uddin, M. J., Shimada, J., and Jinno, K.: Hydrogeochemistry and arsenic contamination of groundwater in the Ganges Delta Plain, Bangladesh, J. Hazard. Mater., 164, 1335–1345, 2009.
 - Harvey, C. F., Swartz, C. H., Badruzzaman, A. B. M., Keon-Blute, N., Niedan, V., Brabander, D., Oates, P. M., Ashfaque, K. N., Islam, S., Hemond, H. F., and Ahmed, M. F.: Arsenic mobility and groundwater extraction in Bangladesh, Science, 298, 1602–1606, 2002.
- Hasan, M. A., Bhattacharya, P., Sracek, O., Ahmed, K. M., von Bromssen, M., and Jacks, G.: Geological controls on groundwater chemistry and arsenic mobilization: hydrogeochemical

study along an E–W transect in the Meghna basin, Bangladesh, J. Hydrol., 378, 105–118, 2009.

- Huang, C. Y.: Foraminiferal analysis and stratigraphic correlation on the subsurface geology of the Choushuichi alluvial fan, in: Conf. on Groundwater and Hydrogeology of Choushui River Alluvial Fan, Taipei, Taiwan, 8–9 February, Water Resources Bureau, Taipei, 5–66, 1996.
- Huang, Y. K., Lin, K. H., Chen, H. W., Chang, C. C., Liu, C. W., Yang, M. H., and Hsueh, Y. M.: As species contents at aquaculture farm and in farmed mouthbreeder (*Oreochromis mossambicus*) in BFD hyperendemic areas, Food Chem. Toxicol., 41, 1491–1500, 2003.

Jackson, M. L.: Soil Chemical Analysis, Advanced Course, 2nd Edn., University of Wisconsin, Madison, WI, 1979.

10

10

25

- Kao, Y. H., Wang, S. W., Liu, C. W., Wang, P. L., Wang, C. H., and Maji, S. K.: Biogeochemical cycling of arsenic in coastal salinized aquifers: evidence from sulfer isotope study, Sci. Total Environ., 409, 4818–4830, 2011.
- Keon, N. E., Swartz, C. H., Brabander, D. J., Harvey, C., and Hemond, H. F.: Validation of an arsenic sequential extraction method for evaluating mobility in sediments, Environ. Sci. Technol., 35, 2778–2784, 2001.
 - Kim, M. J., Nriagu, J., and Haack, S.: Carbonate ions and arsenic dissolution by groundwater, Environ. Sci. Technol., 34, 3094–3100, 2000.
 - Liao, V. H. C., Chu, Y. J., Su, Y. C., Lin, P. C., Hwang, Y. H., Liu, C. W., Liao, C. M., Chang, F. J.,
 - and Yu, C. W.: Assessing the mechanisms controlling the mobilization of arsenic in the arsenic contaminated shallow alluvial aquifer in the blackfoot disease endemic area, J. Hazard. Mater., 197, 397–403, 2011.
 - Liu, C. W., Lin, K. H., and Kuo, Y. M.: Application of factor analysis in the assessment of groundwater quality in a blackfoot disease area in Taiwan, Sci. Total Environ., 313, 77–89, 2003a.
- Liu, C. W., Lin, K. H., Chen, S. Z., and Jang, C. S.: Aquifer salinization in the Yun-Lin coastal area, Taiwan, J. Am. Water Resour. Assoc., 39, 817–827, 2003b.
 - Liu, C. W., Wang, S. W., Jang, C. S., and Lin, K. H.: Occurrence of arsenic in ground water in the Choushui River alluvial fan, Taiwan, J. Environ. Qual., 35, 68–75, 2006.
- Lu, K. L., Liu, C. W., Wang, S. W., Jang, C. S., Lin, K. H., Liao, V. H. C., Liao, C. M., and
 Chang, F. J.: Primary sink and source of geogenic arsenic in sedimentary aquifers in the southern Choushui River alluvial fan, Taiwan, Appl. Geochem., 25, 684–695, 2010.

- Lu, K. L., Liu, C. W., Wang, S. W., Jang, C. S., Lin, K. H., Liao, V. H. C., Liao, C. M., and Chang, F. J.: Assessing the characteristics of groundwater quality of arsenic contaminated aquifers in the blackfoot disease endemic area, J. Hazard. Mater., 185, 1458–1466, 2011.
- Maji, S. K., Pal, A., Pal, T., and Adak, A.: Sorption kinetics of arsenic on laterite soil in aqueous medium, J. Environ. Sci. Health A., 42, 989–996, 2007.
- Maji, S. K., Kao, Y. M., and Liu, C. W.: Arsenic removal from real arsenic-bearing groundwater by adsorption on iron-oxide-coated natural rock (IOCNR), Desalination, 280, 72–79, 2011.
- Maji, S. K., Kao, Y. H., Wang, C. J., Lu, G. S., Wu, J. J., and Liu, C. W.: Fixed bed adsorption of As(III) on iron-oxide-coated natural rock (IOCNR) and application to real arsenic-bearing groundwater, Chem. Eng. J., 203, 285–293, 2012.
- Maji, S. K., Wang, S. W., and Liu, C. W.: Arsenate removal from aqueous media on ironoxide-coated natural rock (IOCNR): a comprehensive batch study, Desalination Water Treat., doi:10.1080/19443994.2013.794551, in press, 2013.
- Mandal, B. K., Chowdhury, T. R., Samanta, G., Basu, G. K., Chowdhury, P. P., Chanda, C. R.,
- Lodh, D., Karan, N. K., Dhar, R. K., Tamil, D. K., Das, D., Saha, K. C., and Chakrabort, D.: Arsenic in groundwater in seven districts of West Bengal, India – the biggest arsenic calamity in the world, Curr. Sci., 70, 976–986, 1996.
 - Matthess, G.: The Properties of Groundwater, translated by: Harvey, J. C., Wiley, New York, 406 pp., 1982.
- McArthur, J. M., Ravenscroft, P., Safiulla, S., and Thirlwall, M. F.: Arsenic in groundwater: testing pollution mechanisms for sedimentary aquifers in Bangladesh, Water Resour. Res., 37, 109– 117, 2001.
 - Mukherjee, A. and Fryar, A. E.: Deeper groundwater chemistry and geochemical modeling of the arsenic affected western Bengal basin, West Bengal, India, Appl. Geochem., 23, 863– 894, 2008.
 - Nath, B., Chakraborty, S., Burnol, A., and Stuben, D.: Mobility of arsenic in the sub-surface environment: an integrated hydrogeochemical study and sorption model of the sandy aquifer materials, J. Hydrol., 364, 236–248, 2009.
- Nickson, R. T., McArthur, J. M., Ravenscroft, P., Burgess, W. G., and Ahmed, K. M.: Mechanism of arsenic release to groundwater, Bangladesh and West Bengal, Appl. Geochem., 15, 403–
- 413, 2000.

Parkurst, D. L. and Appelo, C. A. J.: User's guide to PHREEQC (version 2): a computer program for speciation, reaction path, 1-D transport, and inverse geochemical calculation, US Geol. Surv. Water Resour. Inv. Rep., 99-4259, Denver, CO, 312 pp., 1999.

Radu, T., Subacz, J. L., Phillippi, J. M., and Barnett, M. O.: Effect of dissolved carbonate on arsenic adsorption and mobility, Environ. Sci. Technol., 39, 7875–7882, 2005.

- Ravel, B. and Newville, M.: ATHENA, ARTEMIS, HEPHAESTUS: data analysis for X-ray absorption spectroscopy using IFEFFIT, J. Synchrotron Radiat., 12, 537–541, 2005.
- Ravenscroft, P., Brammer, H., and Tichards, K.: Arsenic Pollution: a Global Synthesis, Wiley-Blackwell, Chichester, UK, 588 pp., 2009.
- Rodriguez-Lado, L., Polya, D. A., Winkel, L., Berg, M., and Hegan, A.: Modelling arsenic hazard in groundwater in Cambodia: a geostastical approach using ancillary data, Appl. Geochem., 23, 3009–3018, 2008.
 - Rowland, H. A. L., Gault, A. G., Lythgoe, P., and Polya, D. A.: Geochemistry of aquifer sediments and arsenic-rich groundwaters from Kandal Province, Cambodia, Appl. Geochem., 23, 3029– 3046, 2008.

15

20

25

- Schulze, D. G. and Dixon, J. B.: High gradient magnetic separation of iron oxides and other magnetic minerals from soil clay, Soil Sci. Soc. Am. J., 43, 793–799, 1979.
- Sharnsudduha, M., Chandler, R. E., Taylor, R. G., and Ahmed, K. M.: Recent trends in groundwater levels in a highly seasonal hydrological system: the Ganges-Brahmaputra-Meghna Delta, Hydrol. Earth Syst. Sci., 13, 2373–2385, doi:10.5194/hess-13-2373-2009, 2009.
- Smedley, P. L. and Kinniburgh, D. G.: A review of the source, behavior, and distribution of arsenic in nature water. Appl. Geochem., 17, 517–568, 2002.
- Stumm, W. and Sulzberger, B.: The cycling of iron in nature environment: considerations based on laboratory studies of heterogeneous redox processes, Geochim. Cosmochim. Acta, 56, 3233–3257, 1992.
- Su, C. and Pulse, R. W.: Arsenate and arsenite removal by zerovalent iron: effects of phosphate, silicate, carbonate, borate, sulphate, chromate, molybdate and nitrate, relative to chloride, Environ. Sci. Technol., 35, 4562–4568, 2001.
- Sutton, N. A., van der Kraan, G. M., van Loosdrecht, M. C. M., Bruining, G. M. J., and Schotting, R. J.: Characterization of geochemical constituents and bacterial populations associated with As mobilization in deep and shallow tube wells in Bangladesh, Water Res., 43, 1720– 1730, 2009.

- Swartz, C. H., Blute, N. K., Badruzzman, B., Ali, A., Brabander, D., Jay, J., Besancon, J., Islam, S., Hemond, H. F., and Harvey, C. F.: Mobility of arsenic in a Bangladesh aquifer: inferences from geochemical profiles, leaching data, and mineralogical characterization, Geochim. Cosmochim. Acta, 68, 4539–4557, 2004.
- Tainan Hydraulic Laboratory: The Yun-Lin offshore industrial infrastructure complexes planning, development and monitoring report part I, vol. 6, groundwater level and quality measurements, Taiwan, ROC, National Cheng-Kung University, 1992–2004.
- Taiwan Sugar Company: Analysis and Evaluation of the Groundwater Quality Survey in Taiwan Area, Water Resource Bureau, Taiwan, 2006.
- ¹⁰ Tseng, W. P.: Effects and dose-response relationships of skin cancer and blackfoot disease with arsenic, Environ. Health Perspect., 19, 109–119, 1977.
 - van Geen, A., Rose, J., Thoral, S., Garnier, J. M., Zheng, Y., and Bottero, J. Y.: Decoupling of As and Fe release to Bangladesh groundwater under reducing conditions, Part II: Evidence from sediment incubations, Geochim. Cosmochim. Acta, 68, 3475–3486, 2004.
- 15 Wang, S. W., Liu, C. W., and Jang, C. S.: Factors responsible for high arsenic concentrations in two groundwater catchments in Taiwan, Appl. Geochem., 22, 460–467, 2007.
 - Wang, S. W., Kuo, Y. M., Kao, Y. H., Jang, C. S., Maji, S. K., Chang, F. J., and Liu, C. W.: Influence of hydrological and hydrogeochemical parameters on arsenic variation in shallow groundwater of southwestern Taiwan, J. Hydrol., 408, 286–295, 2011.
- Wang, S. W., Liu, C. W., Lu, K. L., and Lin, L. H.: Biogeochemical cycling of ferric oxyhydroxide affecting As partition in groundwater aquitard, Environ. Geochem. Health, 34, 467–479, 2012.
 - Wang, Y. X., Guo, H. M., Yan, S. L., Wang, R. F., and Li, Y. L.: Geochemical evolution of shallow groundwater systems and their vulnerability to contaminants: a case study at Datong Basin, Shanxi province, Chian, Science Press, Beijing, China, 102 pp., 2004.
- Shanxi province, Chian, Science Press, Beijing, China, 102 pp., 2004.
 Waslenchuk, D. G. and Windom, H. L: Factors controlling the estuarine chemistry of arsenic, Estuar. Coast. Mar. Sci., 7, 455–464, 1978.
 - Water Resources Agency: The integrated study of groundwater investigation and land subsidence prevention, Minster of Economical Affair, ROC, Taipei, 2010.
- 30 WHO: Guidelines for Drinking-water Quality, WHO Org., Geneva, 2002.

Table 1. Mean values of hydrogeochemical compositions of groundwater among monitoringwells in coastal area of Choushui River alluvial fan from 1992 to 2004.

No.	pН	Τ	EÇ	TDS	Ça ^{2*}	Mg ²	Na ⁺	K,	SO4-	CI-	NO;	NH ₄	HCO;	DOC	As	Fe
		(*)	(µS cm ⁻¹)	(mgL^{-1})	(mgL ⁻¹)	(mgL ⁻¹)	(mgL^{-1})	(mgL ⁻¹)	(mgL ⁻¹)	(mgL ⁻¹)	(mgl1)	(mgL ⁻¹)	(mgL ⁻¹)	(mgL ⁻¹)	(µgL ⁻¹)	(µg L ⁻¹)
YL 1	7.8	25.9	2410.8	1673.7	120.0	95.4	303 7	44.6	278.6	397 2	10	1.2	691.9	2.2	28.3	410
YL 2	7.6	25.4	34 987 9	26 427.1	230.4	625.5	5959 9	304.0	1090.8	10526.5	2.8	20.3	3151.3	2.7	21.5	730
YL 3	7.9	26.2	131270	10273.0	169.2	536.4	2165.0	142.8	153.8	3994.7	13	18.1	1726.8	2.2	103.1	440
YL 4	79	26 3	5797.4	4143.2	118.4	150.5	795.7	85.1	163.1	1541.6	0.5	11.8	914.3	1.8	77.6	450
YL 5	7.8	26.1	18236.5	14 080.5	164.2	314.3	2781.2	198.1	431.2	5558.5	26	15.9	1703.6	2.6	95	610
YL 6	8.1	25.6	121945	9216.5	46.3	164.2	2351.4	126.8	370.6	3610.1	2.0	14 0	630.9	5.2	175 4	330
YL 7	8.0	25.7	2038.9	1409.5	50.0	68.7	283 7	37 4	57.9	360.1	03	7.4	678.7	3.6	533.1	590
YL 8	7.7	26.7	24 176.9	19722.5	254.2	518.0	4409.2	171.7	1052.5	7594.3	0.7	2.2	2393.7	1.3	11.1	370
YL 9	8.3	26.4	3752.2	2803.1	14.0	22.7	810.9	51.8	188.2	820.4	2.0	87	523 4	17.4	477.5	930
YL 10	7.9	26 5	25730.7	20 4 20.2	198.6	431.4	4412.8	185.6	1131.5	7407.6	1.5	20	1760.7	1.6	93.0	370
YL 11	8.2	25 3	11732	797.1	26 2	27 4	2136	47.1	29 1	125.2	0.7	3.1	178.1	2.4	83.3	420
YL 12	7.9	26.0	13236.1	10053.9	201.4	276 3	2181.3	109.5	651.3	3894.9	1.5	4.1	1640.2	1.5	473	240
YL 13	7.6	26.4	17121.9	13099.2	250.3	243 3	2758.0	118.6	813.1	4862.2	0.7	3.4	1581.1	1.1	42.8	630
YL 14	8.6	26.3	1355 2	916.0	11.2	12.82	309.8	15.8	126.2	93 4	06	0.6	80.6	2.7	31.4	1180
YL 15	7.8	257	6483.2	5122.0	196.6	155.0	1052 6	41.1	355.0	1759.1	1.5	2.6	1216.4	2.3	1112	290
YL 16	7.5	25 6	1280.8	859.1	169.8	48.8	73.2	5.9	300.6	45.5	5.6	0.2	524.6	1.2	6.7	340
YL 17	78	26 2	1118.7	740.1	71.9	24.9	158.9	127	48 2	151 8	2.9	37	281 9	21	60.1	560
YL 18	7.6	26.6	1759.7	1207.0	171.6	84.9	121.3	20.3	449.4	157 5	0.9	0.4	777.4	1.2	195	410
YL 19	7.7	26.1	17370.3	12509.5	150.8	327.6	2904.5	144.8	507 8	5168.0	04	12.5	1724.8	2.1	36.9	1010
YL 20	77	25 9	1129.8	779 8	107 5	25 5	139.3	4.8	126 3	129.4	0.2	1.1	373.3	1.3	20.0	280
YL 21	7.8	26.5	1110.9	743.6	71.0	45.7	143.3	18.9	152 7	107 3	05	0.6	365.5	2.7	75	270
YL 22	8.0	25.7	554.9	350.0	42.7	22.1	49.3	4.9	46.3	6.4	0.3	2.2	197 9	18	226.1	370
YL 23	8.2	25.5	579.3	367.7	23.8	38.1	44.1	21.2	38.7	8.5	0.7	0.7	216.3	1.2	10.4	520
YL 24	8.0	25 5	546.5	358 2	49.6	15.1	54.2	2.4	16.3	27.9	05	0.6	186.2	1.7	188	290
YL 25	8.3	26 B	831.4	527.0	12.5	29.9	147.4	34.2	7.7	11.0	0.9	4.8	123.5	32	120.7	190
YL 26	8.1	26 6	434 8	277.2	31.8	76	63.5	3.2	3.9	6.6	0.4	0.8	111.1	16	36 5	380
YL 27	8.0	26.3	690.4	450.3	45.5	22.6	72.0	18.0	37.1	33.3	5.8	0.2	207.6	29	219	130
YL 28	7.7	25.9	753.0	488.2	44.6	19.0	90.2	14.8	16.1	48.0	6 0	0.5	189.4	3.1	66 3	260

Bore No	Depth (m)	Lithology color/type	Si %	A1 %	Fe %	K %	Ca %	Mg %	S mgkg ⁻¹	As mgkg ⁻¹	Mn mgkg ⁻¹
YL6-1	6.5	black /fine sand	37.6	10.2	4.0	2.8	1.3	0.5	1241.0	9.4	132.6
	8.5	black/silty clay	40.2	12.4	3.7	3.2	1.7	0.9	1245.0	11.5	203.7
	10.5	black/silty clay	37.1	10.4	3.0	2.8	1.5	0.5	821.3	7.0	101.7
	11.5	black/silty clay	40.7	13.9	4.1	3.5	1.7	1.1	988.4	9.4	225.9
	13.5	black/silty clay	39.4	11.4	3.5	2.9	1.8	0.7	794.9	6.8	159.0
	15.5	black/clay	39.5	12.7	4.0	3.3	1.6	0.9	887.7	8.5	208.0
	17.5	black/clay	40.2	13.7	4.0	3.5	1.5	1.0	933.5	10.1	179.6
	19.5	black/clay	35.6	11.3	3.4	3.0	1.2	0.6	475.0	5.7	99.3
	21.5	black/silty clay	37.9	12.1	3.5	3.1	1.4	0.9	824.0	9.2	163.3
	23.5	black/clay	37.7	10.5	3.2	2.9	1.3	0.6	513.1	4.7	94.7
YL7-1	6.5	dark grey/fine sand	38.1	10.3	2.8	2.7	1.7	0.5	433.2	4.6	127.9
	8.5	dark grey/fine sand	40.6	12.4	4.0	3.1	2.2	0.9	1225.0	8.0	204.8
	10.5	dark grey/siltyclay	40.8	13.7	4.2	3.4	1.9	1.1	815.5	4.7	234.9
	11.5	dark grey/silty clay	40.3	13.3	4.3	3.3	1.9	10	841.5	5.4	225.7
	15.5	dark grey/silty clay	40.6	14.6	4.3	3.8	1.6	12	757.9	9.3	260.0
	17.5	dark grey/silty clay	39.5	11.3	4.0	2,9	1.9	0.6	644.1	4.7	163.2
	18.5	dark grey/silty clay	39.9	13.7	3.6	3.5	1.6	1.3	1170.0	9.9	231.7
	21.5	dark grey/fine sand	40.6	13.1	2.5	3.4	1.2	0.6	185.2	11.6	187.0
	23.5	dark grey/fine sand	40.5	12.6	2.7	3.2	1.2	05	189.6	9.2	190.0

Table 2. Major elements (wt%), arsenic and manganese (mgkg⁻¹) contents in core samples.

Adsorption reaction	Log K
Arsenite	
$Hfo_sOH + H_3AsO_3 = Hfo_sH_2AsO_3 + H_2O$	5.41
$Hfo_wOH + H_3AsO_3 = Hfo_wH_2AsO_3 + H_2O$ Arsenate	5.41
$Hfo_sOH + H_3AsO_4 = Hfo_sH_2AsO_4 + H_2O$	8.61
$Hfo_wOH + H_3AsO_4 = Hfo_wH_2AsO_4 + H_2O$	8.61
$Hfo_sOH + H_3AsO_4 = Hfo_sHAsO_4^- + H_2O + H^+$	2.81
$Hfo_wOH + H_3AsO_4 = Hfo_wHAsO_4^- + H_2O + H^+$	2.81
$Hfo_sOH + H_3AsO_4 = Hfo_sOHAsO_4^{3-} + 3H^+$	-10.12
$Hfo_wOH + H_3AsO_4 = Hfo_wOHAsO_4^{3-} + 3H^+$	-10.12
Phosphate	
$H_{fo}sOH + PO_{4}^{3-} + 3H^{+} = H_{fo}sH_{2}PO_{4} + H_{2}O$	31.29
$Hfo_wOH + PO_4^{3-} + 3H^+ = Hfo_wH_2PO_4 + H_2O_4$	31.29
$Hfo_sOH + PO_4^{3-} + 2H^+ = Hfo_sHPO_4^- + H_2O$	25.39
$H_{fo}wOH + PO_{4}^{3-} + 2H^{+} = H_{fo}wHPO_{4}^{-} + H_{2}O$	25.39
$H_{fo}sOH + PO_{4}^{3-} + H^{+} = H_{fo}sPO_{4}^{2-} + H_{2}O$	17.72
Hfo wOH + PO_{4}^{3-} + H ⁺ = Hfo wPO_{4}^{2-} + H ₂ O	17.72
Sulfate	
$Hfo_wOH + SO_4^{2-} + H^+ = Hfo_wSO_4^- + H_2O$	7.78
Hfo wOH + SO $^{2-}$ = Hfo wOHSO $^{2-}$	0.79
Carbonate	
$Hfo_wOH + CO_2^{2-} + H^+ = Hfo_wCO_2^- + H_2O$	12.56
Hfo wOH + CO_2^{2-} + 2H ⁺ = Hfo wHCO ₂ + H ₂ O	20.62

Table 3. Thermodynamic data of surface complexation constants for arsenite, arsenate, phosphate, sulfate and carbonate (Allison et al., 1990; van Geen et al., 2004).

10593

 Table 4. Comparison of experimental and simulated amount of As desorption from core samples after 30 days.

Anion	Concentration (mole L^{-1})	Core type	Measured desorption (mgkg ⁻¹)	Simulated desorption desorption (mg kg ⁻¹)
PO ₄ ³⁻	0.1	YL6-1	1.8	2.41
		YL7-1	2.8	2.8
	0.01	YL6-1	1.75	0.74
		YL7-1	1.5	0.86
	0.001	YL6-1	0.8	0.031
		YL7-1	0.9	0.036
HCO_3^-	1	YL6-1	1.7	0.021
		YL7-1	0.7	0.024
	0.1	YL6-1	0.4	0.016
		YL7-1	0.5	0.019
	0.01	YL6-1	< 0.1	0.011
		YL7-1	0.1	0.012



Fig. 1. Location of study area in the portion of coastal area of Choushui River alluvial fan, Taiwan. Triangle and square symbols represented groundwater and core sampling wells, respectively. Offshore industrial complexes are man-made islands for oil refinery plants.



Fig. 2. Piper plot of sampled groundwaters in the littoral area of Choushui River alluvial fan.



Fig. 3. (a) Scatter plot of EC and well depth of YL1-YL28. **(b)** Three dimensional plot of EC, As concentration and well depth of YL1-YL28.

all and



Fig. 4. Geochemistry distribution of As, Fe, and organic and inorganic carbon contents along the depth in **(a)** YL6-1 and **(b)** YL7-1. Solid cross and diamond represented pristine samples (without HGMS treatment) and magnetic fractions, respectively. Hollow diamond represented non-magnetic fractions. For magnetic and non-magnetic fractions, only As and Fe contents were measured.



Fig. 5. Relationships of As between Fe, Mn and S in the solid phase of (a) YL6-1 and (b) YL7-1.



Fig. 6. Curve fitting data of the $Fe2p_{3/2}$ core level. (a) 13 m in YL6-1, (b) 15 m in YL6-1, (c) 8 m in YL7-1, (d) 10 m in YL7-1, (e) 14 m in YL7-1 and (f) 21 m in YL7-1. The solid line represents the experimental curve after smoothing and the dotted lines represent the fitted curve.



Fig. 7. Normalized As XANES spectra data of the sediments from YL6-1 (16 m) and YL7-1 (18 m) used in the leaching experiments. Reference As^{3+} and As^{5+} standard are NaAsO₂ and Na₂HASO₄ · 7H₂O.



10601

Fig. 8. Time dependent desorption of arsenic with bicarbonate at 0.01, 0.1 and 1 M and phosphate at 0.001, 0.01 and 0.1 M from (a) YL6-1 and (b) YL7-1.



Fig. 9. Simulated time dependent As desorption of YL6-1 and YL7-1 at various anionic concentrations (a) PO_4^{3-} (b) HCO_3^- (c) SO_4^{2-} (d) CI^- .