Hydrol. Earth Syst. Sci. Discuss., 11, 2177–2209, 2014 www.hydrol-earth-syst-sci-discuss.net/11/2177/2014/ doi:10.5194/hessd-11-2177-2014 © Author(s) 2014. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Dams on Mekong tributaries as significant contributors of hydrological alterations to the Tonle Sap Floodplain in Cambodia

M. E. Arias¹, T. Piman², H. Lauri³, T. A. Cochrane¹, and M. Kummu⁴

 ¹Department of Civil and Natural Resources Engineering, University of Canterbury, Christchurch, New Zealand
 ²Mekong River Commission, Vientiane, Lao
 ³EIA Finland Ltd., Espoo, Finland
 ⁴Water & Development Research Group, Aalto University, Aalto, Finland

Received: 24 January 2014 – Accepted: 6 February 2014 – Published: 18 February 2014

Correspondence to: T. A. Cochrane (tom.cochrane@canterbury.ac.nz)

Published by Copernicus Publications on behalf of the European Geosciences Union.



Abstract

River tributaries have a key role in the biophysical functioning of the Mekong Basin. Of particular attention are the Sesan, Srepok, and Sekong (3S) rivers, which contribute nearly a quarter of the total Mekong discharge. Forty two dams are proposed in the 3S, and once completed they will exceed the active storage of China's large dam cascade in the upper Mekong. Given their proximity to the lower Mekong floodplains, the 3S dams could alter the flood-pulse hydrology driving the productivity of downstream ecosystems. Therefore, the main objective of this study was to quantify how hydropower development in the 3S would alter the hydrology of the Tonle Sap floodplain, the largest wetland in the Mekong and home to one of the most productive inland fisheries in the world. We coupled results from four numerical models representing the basin's surface hydrology, water resources development, and floodplain hydrodynamics. The scale of alterations caused by hydropower in the 3S was compared with the basin's definite future development scenario (DF) driven by the upper

- ¹⁵ Mekong dam cascade. The DF or the 3S development scenarios could independently increase Tonle Sap's 30 day minimum water levels by 30 ± 5 cm and decrease annual water level fall rates by 0.30 ± 0.05 cm d⁻¹. When analyzed together (DF + 3S), these scenarios are likely to eliminate all baseline conditions (1986–2000) of extreme low water levels, a particularly important component of Tonle Sap's environmental flows.
- Given the ongoing trends and large economic incentives in the hydropower business in the region, there is a high possibility that most of the 3S hydropower potential will actually be exploited and that dams would be built even in locations where there is a high risk of ecological disruptions. Hence, retrofitting current designs and operations to promote sustainable hydropower practices that optimize multiple river services – rather
- than just maximize hydropower generation appear to be the most feasible alternative to mitigate hydropower-related disruptions in the Mekong.



1 Introduction

More than half of the world's greatest rivers have been altered by dams (Nilsson et al., 2005) and there is worldwide evidence showing that hydropower development causes significant hydrological and ecological disruptions to downstream freshwater ecosys-

- tems (Poff and Zimmermann, 2010). Understanding the cumulative impact of water resources infrastructure is important for sustainable development of river basins, and although hydrological alterations from dams have basin-wide implications, impact assessments typically concentrate on river segments directly upstream and downstream of single dam projects (Nilsson and Berggren, 2000). Impact assessments, however, became more aballanging when critical account further downstream under
- become more challenging when critical ecosystems occur further downstream under the influence of multiple dams as well as other water infrastructure components (e.g. irrigation, water supply, and flood control). The situation becomes even more complex in large rivers where the interests of upstream stakeholders differ from those downstream. Such is the case of the Mekong, a transboundary basin with a historically low
- ¹⁵ levels of hydrological regulation (i.e. fraction of annual water discharge that can be stored in reservoirs) that is comparable to other large tropical basins such as the Amazon and Congo (Lehner et al., 2011; Nilsson et al., 2005). Aggressive plans for multiple large hydropower schemes throughout the Mekong Basin for economic development, however, are expected to bring significant disruptions to the hydrological regime (Lauri
- et al., 2012; Piman et al., 2013b), compromising the geomorphology (Kummu et al., 2010; Walling, 2009), fish ecology (Ziv et al., 2012), and productivity of downstream floodplain ecosystems (Arias et al., 2014) that sustain the food security of millions of people.

The Mekong is the largest river and basin in Southeast Asia, covering an extension of 795 000 km² shared by six different countries: China, Myanmar, Thailand, Laos, Cambodia, and Vietnam (Fig. 1). Mean annual discharge in the Mekong at Kratie in Cambodia is 475 km³ or 14 500 m³ s⁻¹, varying from an average of less than 3000 m³ s⁻¹ during March–April, to nearly 40 000 m³ s⁻¹ during August–September (Adamson et al.,



2009). The Sesan, Srepok, and Sekong basins (collectively known as the 3S) cover an area of 78 650 km² distributed among Cambodia (33%), Laos (29%), and Vietnam (38%). Due to its relatively high rainfall precipitation (1100–3800 mm yr⁻¹), the 3S provides the largest flow contribution among Mekong tributaries, with an average discharge of 510 m³ s⁻¹ during March–April and 6133 m³ s⁻¹ during September. In general, the 3S contributes 23% of the annual Mekong discharge, compared to 16% generated in the upper Mekong in China (Adamson et al., 2009).

The Mekong River meets the Tonle Sap 300 km downstream from Stung Treng at the Cambodian capital, Phnom Penh. From October to May, water flows from the Tonle Sap river to the Mekong at a maximum daily discharge rate of $8300 \text{ m}^3 \text{ s}^{-1}$; when the wet

monsoon reaches the basin in May, the Mekong River rises to a higher level than the Tonle Sap, forcing the later to reverse its flow towards the Tonle Sap Lake. This phenomenon creates a floodplain that extends over 15 000 km² and stores up to 76.1 km³ of Mekong's annual flood-pulse (Kummu et al., 2014). Overall, 53.5% of the water en-

10

- tering the Tonle Sap system comes from the Mekong, 34 % from 11 tributaries in the Tonle Sap catchment, and 12.5 % directly from rainfall (Kummu et al., 2014).
 Hydropower development in the Mekong is occurring in three distinct regions. The first is the Lancang–Jiang cascade in the upper Mekong River in China (Fig. 1), a series of 6 dams (5 already built) with downstream hydrological alterations expected as
- far down as Kratie (Räsänen et al., 2012). The second focus of development is a series of 11 dams along the mainstream channel in the lower Mekong, only one of which is under construction, the Xayaburi dam in Lao. The lower Mekong mainstream dams have become very controversial due to their potential impacts on fisheries (Ziv et al., 2012) and their role in political affairs among the basin's countries (Grumbine and Xu,
- 25 2011; Grumbine et al., 2012; Stone, 2011). Despite generating a large amount of electricity, hydrological alterations caused by these mainstream (run-of-the-river) dams are expected to be low compared to other projects around the basin (Piman et al., 2013b). Of more concern in terms of hydrological alterations is the third region of development occurring in the Mekong tributaries, in particular in the 3S, where at least 42



dams are at some stage of development without much regional coordination or stakeholder consultation. Because of its proximity to the Tonle Sap and the rest of the lower Mekong floodplains, flow regulation in the 3S will most likely affect the floodplain's hydrological seasonality. Should the Tonle Sap hydrology be altered, however, serious consequences could happen to the ecological productivity that this floodplain wetland supports (Arias et al., 2014).

Thus far, existing dams are believed to have caused very little hydrological alterations in the lower Mekong (Adamson et al., 2009). There has been alterations to the frequency of extreme events beginning in the mid-1970s, but this is probably linked to changes to El Niño-Southern Oscillation (Delgado et al., 2012; Räsänen and Kummu,

- ¹⁰ changes to El Nino-Southern Oscillation (Delgado et al., 2012; Rasanen and Kummu, 2013). Several efforts and modeling tools have been developed to evaluate ongoing and future hydrological alterations in the Mekong (Johnston and Kummu, 2011). The primary focus of these studies have been the cumulative impact of multiple water in-frastructure development plans for the basin (Lauri et al., 2012; Piman et al., 2013b;
- ¹⁵ WB, 2004). Other studies have scrutinized alterations in particular regions of development such as the dam cascade in the upper Mekong River (Räsänen et al., 2012) and the 3S (Piman et al., 2013a; Ty et al., 2011), but linkages between development in these regions and impacts to the lower Mekong floodplains have not been assessed. Impact assessments of basin-wide alterations to the Tonle Sap, however, do exist and
- ²⁰ provide a good understanding of the general trends of future changes in the floodplain. Kummu and Sarkkula (2008) initially pointed out that the upstream development scenario from WB (2004) could increase Tonle Sap's dry season water levels by 15 cm and decrease wet season water levels by 36 cm, leading to a large reduction of seasonally inundated areas. Arias et al. (2012, 2013, 2014) demonstrated that hydropower-related
- alterations to the Tonle Sap's hydrology could cause major disruptions to existing floodplain habitats and their contribution to aquatic primary production.

Impacts of hydrological alterations in rivers and floodplains have been well documented for decades (Petts, 1980). Hundreds of studies provide evidence that hydrological alterations cause ecological disruptions in river and riparian systems (Poff and



Zimmermann, 2010), but most of these studies have been carried out in single river reaches in North America and Europe, where more than three quarters of rivers' discharge is regulated (Dynesius and Nilsson, 1994), and where sufficient time series exist to make statistical inference on pre-/post-dam alterations (FitzHugh, 2013; Poff

- ⁵ et al., 2007). Studies in these regions have evaluated impacts of dam development based on the scale of alterations to the magnitude, frequency, duration, timing, and rate of change of natural flow regimes required for the integrity of river and floodplain ecosystems (Poff et al., 1997). Based on these properties, a method to assess the impacts of hydrological alternations (IHA) to environmental flows was developed (Richter
- et al., 1997, 1996). This method defines 32 hydrological parameters and environmental flow components (EFC) and assesses the magnitude and statistical significance of alterations caused by flow regulation. Recent developments have been proposed to the IHA method, including the analysis of multivariate components among indicators of alterations (Gao et al., 2009) and ranking of alteration levels for specific EFCs (FitzHugh, 2013).

Most of the current construction of hydropower projects is happening in the (sub-) tropics in South America, Africa and Asia (Kareiva, 2012), where hydrological and ecological monitoring has not been carried out to the temporal span and resolution needed to comprehensively use the IHA method (which typically requires time

- ²⁰ series with at least 20 yr of daily measurements; The Nature Conservancy, 2009). Perhaps the only exceptions to this regional limitation include the Murray–Darling Basin in Australia (Kingsford, 2000) and the Paraná in Brazil (Agostinho et al., 2009), where hydrological alterations and corresponding ecological disruptions have been well documented. Despite the obvious limitations, applying the IHA method to tropical rivers
- ²⁵ under development brings interesting challenges and benefits. First, IHA can be used as a priori impact assessment tool to be applied on simulated scenarios of hydropower development in order to plan optimal and sustainable dam locations and operations. Furthermore, the tool can be used to compare the level of alterations between different projects and/or cascades, thus helping prioritize where sustainable hydropower



and basin management strategies are most needed. Moreover, the IHA tool could be used to evaluate the cumulative impacts of dam cascades at critical downstream river reaches and high-value ecosystems, instead of just focusing on nearby downstream impacts of a single dam. With these particular applications in mind, an assessment of budrelegies of a strategies in the Makeng would be an informative asses study not only

of hydrological alterations in the Mekong would be an informative case study not only for researchers and managers in the basin but also to others in (sub-)tropical rivers undergoing similar development and biophysical transitions.

The main objective of this study is to quantify how hydropower development in the tributaries of the lower Mekong would alter the hydrology of the Tonle Sap floodplain.

- ¹⁰ This was carried out by first validating a 2-D hydrodynamic model of the lower Mekong floodplains with historical water levels at the Tonle Sap. We then compared the expected hydrological alterations on the Tonle Sap caused by scenarios of 3S hydropower development and the most likely (definite) development scenario for the rest of the Mekong Basin by 2015. Once these two scenarios were analyzed separately, their cu-
- ¹⁵ mulative impact on hydrological parameters and environmental flows at the Tonle Sap floodplain were estimated. We conclude with a discussion of major implications of our findings as well as feasible alternatives to mitigate expected hydrological alteration and consequent ecological disruptions.

2 Methods

25

20 2.1 Modelling approach

This study integrates the results of four different sets of numerical models (Fig. 2). Basin hydrology and daily runoff flows were simulated in a daily time step using the Soil and Water Assessment Tool (SWAT) as described by Piman et al. (2013b). This SWAT model was calibrated for 28 different gauges upstream of Kratie. Subbasin runoff flows were then used as inputs to two different models of water resources development impacts. The first set of results came from simulations using the Integrated Quantity



and Quality Model (IQQM) that Piman et al. (2013b) applied to assess the impact of water regulation and abstraction in the Mekong. The second set of results were generated with the HEC-ResSim model presented by Piman et al. (2013a), which simulated the impact of hydropower development and operations in the 3S. Results from both

- IQQM and HEC-ResSim were used to compute daily river discharges in the Mekong at Kratie south of the 3S confluence (see location in Fig. 1). Water movement from this location down through the lower Mekong floodplains (including the Tonle Sap) was simulated with the 2-D EIA, a hydrodynamic model that solves the simplified Navier-Stokes and continuity equations numerically using a finite difference method (Koponen et al.,
- ¹⁰ 2010). The 2-D EIA lower Mekong application covers an area of 430 km by 570 km from Kratie to the Mekong Delta at a grid resolution of 1 km². An earlier version of this application was presented by Västilä et al. (2010). Daily water levels from the 2-D EIA model were extracted and validated at K. Luong where the main water gauge on the Tonle Sap is located (see Fig. 1). Simulated water levels were validated against historical measurements for the entire simulation period (1986–2000). Validation results were
- ¹⁵ cal measurements for the entire simulation period (1986–2000). Validation results were evaluated according to the linear correlation coefficient (r) between observed and simulated results, as well as the Nash–Sutcliffe efficiency coefficient (Nash and Sutcliffe, 1970).

2.2 Modeling scenarios

- A total of four scenarios were considered for this study (Table 1). A baseline scenario (BL) represented recent historical conditions (1986–2000) before major hydropower projects were built in the upper Mekong and the 3S. We were limited to this 15 yr time series because no continuous and reliable water level data exist for the Tonle Sap before this and because large dams began to be built after 2000. Two of the wettest and
- five of the driest years in the past seven centuries occurred during this baseline period (Räsänen et al., 2013), and therefore it was considered a good representation of the range of historical hydrological conditions and variability in the basin. Although 17 dams were already operational by the end of this period (including the Manwan dam in



China built in 1993), they were generally small and only accounted for 9.1 km^3 of active storage, in contrast to the approximately 38 km^3 that have been built since year 2000 (MRC, 2009). The first scenario of water resources development that was analyzed resembles the Definite Future (DF) scenario proposed by the Mekong River Commission

- (MRC; Piman et al., 2013b), which represents existing and on-going water resources infrastructure development up to the year of 2015. The DF scenario is primarily driven by the six dams in the Lancang–Jiang dam cascade in the upper Mekong in China, which provide an additional 23.2 km³ of active storage from baseline (Räsänen et al., 2012). The DF scenario in our study does not consider any proposed dams in the 3S.
- The second scenario of water resources development was based on the simulations of dams operations in the 3S presented by Piman et al. (2013a). This scenario represents a total of 42 dams at different development stages (existing, under construction, and proposed) in the 3S tributaries and sub-tributaries with 26.3 km³ of active storage. The last scenario analyzed represents the cumulative impact of both DF and 3S (DF + 3S)
- with an additional 49.5 km³ of active storage from baseline. All simulations were carried out on daily time steps for a period of 15 yr from 1 January 1986 to 31 December 2000.

2.3 Data analysis

Simulated water levels were used to calculate 30 hydrological parameters and corresponding alterations using the IHA Tool (The Nature Conservancy, 2009). This tool computes hydrologic parameters that are relevant to ecosystem processes and it calculates the level of alteration between baseline and post-alteration periods. Analyses were carried out by combining the BL scenario time series with each of the water development scenarios so that the first 15 yr defined the pre-alteration period and the second 15 yr represented the post-development period, as if all dams were built at once in 1 January 2001. Three different sets of analyses were carried out: DF scenario, 3S scenario, and DF + 3S. All analyses were carried out using non-parametric statistics. Data were analyzed according to calendar years (1 January to 31 December).



Environmental flow components were set according to commonly used parameters. The 75th percentile of water levels for each year was defined as the threshold between periods of low flow and high flow pulses. Small floods were defined as those with a peak above the 2 yr return period flood, whereas large flood events were defined as those 5 with a peak above the 10 yr flood. Extreme low flows were defined as those with an

⁵ with a peak above the 10 yr flood. Extreme low flows were defined as those with an initial low flow below the 10th percentile from daily records for each period.

Annual summary statistics were used to compare the magnitude of alterations between scenarios. All hydrologic parameters were analyzed with the Kruskal–Wallis test (Kruskal and Wallis, 1952) to determine if differences among the BL, DF, and 3S sce-

- ¹⁰ narios were significant to the 95th level. Once individual scenarios were compared, hydrological alterations were calculated for the DF and for the DF + 3S scenarios. Environmental flow components were estimated, exceedance probability charts plotted, and hydrological alteration factors were computed for all parameters according to the Range of Variability Approach (RVA; Richter et al., 1997). This approach consists on
- ¹⁵ dividing the data into 3 different categories (bounded by the 33rd and 67th percentiles), estimating the frequency at which values are expected to occur within each category, and then estimating the percent difference between the expected frequency and the simulated frequency for the impact scenarios.

In addition to the IHA analysis, changes in spatial flooding patterns were analyzed. Rasters representing cumulative flood duration were generated from the 2-D EIA model at the geographical extend of the Tonle Sap floodplain (15 000 km² approximately), and these were transformed into flood frequency rasters by normalizing flood duration according to the simulation's total length. Outputs from the impact scenarios were overlaid on the baseline raster in order to calculate and visualize spatial changes in flood regime.



3 Results

3.1 Baseline scenario validation

Prior to the analysis and comparison among scenarios, the simulated daily water levels at K. Luong were validated against historical measurements for the entire simulation ⁵ period (1986–2000). Overall, simulations of the baseline scenario show a tendency to overestimate historical records of daily water levels at low water levels, but this discrepancy disappears at water levels above approximately 7 m (Fig. 3). The linear correlation coefficient between the observed and simulated daily water levels was 0.97 and the Nash–Sutcliffe efficiency coefficient was 0.91.

10 3.2 Comparison between BL, DF, and 3S scenarios

Overall, similar scales and alteration trends between the DF and the 3S scenarios were found. Of the 30 hydrological parameters analyzed, 9 appeared to be significantly different (*p* ≤ 0.05) in either the DF or the 3S scenario when compared to the BL scenario (Table 2): April and May monthly water levels, water fall rate (that is, the difference between the annual minimum and maximum water levels divided by the duration between them), base flow index (that is, the 7 day minimum over the mean annual water level), and 1, 3, 7, 30, and 90 day minima. None of the parameters, however, appeared to be significantly different between the DF and the 3S scenario. Boxplots of some of the most representative parameters were prepared in order to demonstrate the general trends encountered in this comparison (Fig. 4). For instance, the 30 day minimum water level median was 1.52 m (range from 1.22 to 2.18 m) for the BL scenario, which is significantly different from 1.84 m (1.51 - 2.48) and 1.80 m (1.50 - 2.46 m) for the DF

is significantly different from 1.84 m (1.51–2.48) and 1.80 m (1.50–2.46 m) for the DF and 3S scenarios, respectively (Fig. 4a). Water level fall rate for the BL (median of 3.2 cmd⁻¹, range 3.0–3.6 cmd⁻¹) was also significantly different from DF (median of 2.8 cmd⁻¹, range 2.7–3.4 cmd⁻¹) and 3S (median of 2.9 cmd⁻¹, range 2.7–3.4 cmd⁻¹; Fig. 4b). In contrast, maximum annual water level from BL (median of 8.58 m, range of



7.42–9.67 m) was not found to be significantly different from either development scenarios (Fig. 4c).

3.3 Cumulative hydrological alteration from the DF + 3S scenario

15

The results of the simulations with the cumulative effects from the DF + 3S scenarios suggest that there could be significant impacts to the overall Tonle Sap flood regime. In terms of environmental flows, the cumulative impact of the DF + 3S scenario virtually eliminates all baseline extreme low flow conditions (Fig. 5); the frequency of these events is reduced from 11 to just 1 event in 15 yr. Moreover, the BL scenario shows that high flow pulses and floods occur every single year, but the frequency of these events decreases to 2 in every 3 yr.

Changes in the flood regime of the Tonle Sap will also be reflected in the probability of water level exceedance (Fig. 6). Greatest deviations occur at exceeding levels above 70%; for instance, 2.36 m corresponds to the 80% exceeding level in BL, but this increases to 2.62 and 2.80 m for the DF and the DF + 3S cases, respectively. Mild declines occur at the 20% exceedance level, but much milder changes were found for greatest (and less frequent) events.

Hydropower development through the Mekong and tributaries would alter multiple seasonal and annual hydrological parameters. Primarily, greatest alteration factors are expected during the dry season months, with large alteration factors for monthly water

- ²⁰ levels during April and May, as well as other parameters including the 1-day, 3-day, 7-day, 30-day, and 90 day minima (Table 3). The DF scenario decreases the frequency of occurrence of the baseline dry season parameters by 40–60 %, but the addition of the 3S hydropower network (DF + 3S) results in alteration factors of –100 % for all of these parameters (meaning that they are expected to be altered every year). Factors of alternative factors of parameters (for the parameters (for the parameters by 20 (20 % for the DF scenario)).
- alteration in annual rates of water rise/fall change by -33/-20% for the DF scenario, but the magnitude of alteration factors increase to -83 and -60% for the DF + 3S scenario (Table 4).



3.4 Changes in flood duration

Both DF and DF+3S scenarios could bring changes to the long-term spatial patterns of inundation throughout 51–60 % of the Tonle Sap Floodplain (Fig. 7). In general, areas that are marginally inundated and areas that are permanently inundated are likely to
⁵ expand, whereas areas that are seasonally inundated are likely to decrease. For instance, areas in the outermost class (inundated between 0.5–10 % of the time) expand by 177 km² (10.1 %) and 283 km² (16.1 %) as a result of the DF and the DF + 3S scenarios, respectively (Table 5). Moreover, largest area shifts occur in areas inundated 90–100 % of the time, which expand by 279 km² (5.7 %) and 424 km² (8.6 %) as a result of the DF and the DF + 3S scenarios, respectively. On the contrary, classes inundated 20–90 % shrink by 600 and 994 km² as a result of the DF and the DF + 3S scenarios, respectively.

4 Discussion

This study presents an important contribution to the assessment of water resources
management and development of the Mekong River Basin. We have combined multiple hydrological modeling tools – all of which have been previously validated for the basin – and simulated the specific and combined impact of water resources development in two regions of great hydrological contribution to the whole basin. Piman et al. (2013a) had already pointed out that the scale of hydropower development in the 3S was as large as the Lancang–Jiang dam cascade. In this study, we have taken a step further and shown that the corresponding hydrological alterations from the 3S hydropower projects are also as large; more importantly, we have demonstrated that the cumulative effect of development in the upper Mekong and the 3S will cause significant disruptions to the inundation patterns of the lower Mekong floodplains, in particular through an increase
in dry season water levels as well as a reduction in water level rise/fall rates.



Our study has assumed (intentionally) no changes in rainfall-runoff from one simulation to the other in order to solely explore the issue of water regulation in tributary dams. This assumption, however, is not a complete representation of changes to the basin's hydrological cycle, as there are other key factors such as climate change (Kingston 5 et al., 2011; Lauri et al., 2012), new irrigation schemes (Piman et al., 2013b), and land

- use/land cover changes (Costa-Cabral et al., 2007; Ishidaira et al., 2008) that are altering rainfall-runoff characteristics and thus simultaneously affecting the role of the 3S on the Tonle Sap hydrology. As Ty et al. (2012) pointed out for one of the 3S rivers (Srepok), these other factors could also cause alterations, particularly as a decrease in water availability during the dry season. This trend is opposite to the effects of hy-
- 10

in water availability during the dry season. This trend is opposite to the effects of hydropower in the 3S reported by Piman et al. (2013a), and therefore, there is a great need for detailed modelling studies that take into account all of these major drivers of hydrological alterations.

This study demonstrated the use of IHA tools to assess the impact of future scenarios of water resources development. Although this tool has been previously used for simulated scenarios by Gao et al. (2009), their scenarios represented hypothetical reservoirs and dam operations, whereas our study represented existing and proposed projects based on actual design characteristics. IHA tools have been used in the Mekong by Ty et al. (2011) and Thompson et al. (2013), but their applications focused

- on climate change and excluded the Tonle Sap flooding characteristics. Our study has actually made a first attempt at quantifying environmental flows for the Tonle Sap using the simulations of baseline conditions, and our estimates could help guiding environmental flows criteria based on specific biological needs of this system. As the validation results showed, however, our model scheme had a slight tendency to overestimate his-
- torical dry season water levels; for that reason, the reported magnitude of water levels defining extreme low flows need to be read with caution as they might actually be marginally higher than historical observations. We recommend that a closer analysis using long term observed water level records is carried out in order to more accurately define environmental flows and monitor ongoing alterations to these parameters.



Previous studies (Arias et al., 2012, 2014) also assessed the impacts of water resources development on water levels and flood duration at the Tonle Sap. These previous studies used three representative hydrological years (dry, average, and wet) in order to characterize multiyear variability, and in general it was found that hydrological alterations increased from wet to dry years. While results from this study still support this trend in representative years, we found that over a longer time series only al-

- terations on dry season water levels are expected to be recurrent. Furthermore, our estimates of dry season water level alterations for the DF scenario are consistent with values previously reported (Arias et al., 2012; MRC, 2010), whereas our estimates for
- the DF + 3S scenario (+47 and +61 cm for April and May, respectively) are considerably larger than any of the MRC future development scenarios previously reported (maximum of +33 cm in April and +39 cm in May; MRC, 2010). This difference highlights the significance of tributary dams to the hydrology of the entire basin and the importance of modeling their dimensions and operations in detail. Difference between
- the DF + 3S scenario and previous estimates could also be partially attributed to water abstraction for irrigation during the dry season, which were not considered in this study; yet, a previous comparison of alterations from hydropower dams vs. cumulative alterations of hydropower with irrigation did not show any major differences in the lower Mekong (Piman et al., 2013b). In order to more comprehensively address this issue,
- ²⁰ further modeling studies in the Mekong should compare the effects of hydropower with irrigation development.

Significant hydrological alterations are expected in the Tonle Sap and the rest of the lower Mekong floodplains if proposed hydropower development plans are to be formalized. Ongoing trends and large economic incentives in the hydropower business ²⁵ imply that most of the hydropower potential will actually be exploited and dams will be built even in locations where there is a high risk of disruptions to environmental flows. A clear evidence of this trend is the Xayaburi dam in the Mekong mainstream in Lao and the Lower Sesan 2 at the confluence of the 3S tributaries in Cambodia. Both of these dams have been already commissioned despite not only being highlighted



as having potentially large ecological impacts in the scientific literature (e.g. ICEM, 2010; Ziv et al., 2012) but also after rising much controversy in the international media. Under a likely, "development as usual" scenario, the most feasible alternative to mitigate disruptions in the Mekong consist on retrofitting current design and operation practices

- ⁵ in order to optimize river services rather than just maximize hydropower generation. In other words, seasonal and diurnal operation rules should also aim at minimizing hydrological alterations downstream in addition to meeting electricity demands. From a hydrological point of view, run-of-the-river designs or operations in which power is gained primarily from flow volume and not elevation head would yield much lesser
- alterations. In addition to hydrological considerations, there are other aspects such as sediment releases and fish passages that need to be implemented. These factors have not been widely considered in assessment studies in the Mekong (with the exception perhaps of Kummu et al., 2010 and Ziv et al., 2012) and should therefore be the subject of further research.

15 **5** Conclusions

This paper presented a study in which hydrological modeling and assessment tools were used to provide evidence of the expected hydrological alterations that hydropower development in the lower Mekong tributaries could bring to the Tonle Sap. Hydrological alterations caused by dams in the 3S were of similar magnitude as the DF scenario, which resembles water infrastructure development up to 2015 and particularly driven by China's Lancang–Jiang dam cascade in the upper Mekong. Definite future plans in combination with the full development of the 3S dam network will most likely cause significant and undocumented hydrological alterations to the Tonle Sap and the rest of the lower Mekong floodplains. The most significant alterations are in terms of water

²⁵ levels during the dry season (April and May) and rates of water level rise/drop; these hydrological parameters are crucial for biological factors such as tree seeds germination and fish migrations, and therefore major ecological disruptions are likely to follow.



Although there could be a decrease in wet season water levels in years of low flow from the Mekong, wet season disruptions are not recurrent in years of larger floods. Given the importance of the 3S to the rest of the lower Mekong, we recommend that more detail studies of drivers of hydrological change in the 3S are carried out, including irrigation, land use/land cover conversion, and climate change. Moreover, optimization

Irrigation, land use/land cover conversion, and climate change. Moreover, optimization of hydropower operations considering both electricity generation and environmental flows should be sought as a feasible alternative to be further studied and implemented in existing and proposed dams in this critical tributary.

Acknowledgements. Funding for University of Canterbury was provided by John D. and Catherine T. MacArthur Foundation through a project entitled "Critical Basin at Risk: Assessing and managing ecosystem pressures from development and climate change in the 3S basin".

References

10

- Adamson, P. T., Rutherfurd, I. D., Peel, M. C., and Conlan, I. A.: The hydrology of the Mekong River, in: The Mekong, available at: http://www.sciencedirect.com/science/
- ¹⁵ article/B9FBM-4Y59TWF-M/2/29840b78b5de4ee935ae707cd803a3b4, Academic Press, San Diego, 53–76, 2009.
 - Agostinho, A. A., Bonecker, C. C., and Gomes, L. C.: Effects of water quantity on connectivity: the case of the upper Paraná River floodplain, Ecohydrol. Hydrobiol., 9, 99–113, doi:10.2478/v10104-009-0040-x, 2009.
- Arias, M. E., Cochrane, T. A., Kummu, M., Killeen, T. J., Piman, T., and Caruso, B. S.: Quantifying changes in flooding and habitats in the Tonle Sap Lake (Cambodia) caused by water infrastructure development and climate change in the Mekong Basin, J. Environ. Manage., 112, 53–66, 2012.

Arias, M. E., Cochrane, T. A., Norton, D., Killeen, T. J., and Khon, P.: The flood pulse as the

- ²⁵ underlying driver of vegetation in the largest wetland and fishery of the Mekong Basin, Ambio, 42, 864–876, doi:10.1007/s13280-013-0424-4, 2013.
 - Arias, M. E., Cochrane, T. A., Kummu, M., Lauri, H., Koponen, J., Holtgrieve, G. W., and Piman, T.: Impacts of hydropower and climate change on drivers of ecological productivity of Southeast Asia's most important wetland, Ecol. Model., 272, 252–263, 2014.



Costa-Cabral, M. C., Richey, J. E., Goteti, G., Lettenmaier, D. P., Feldkötter, C., and Snidvongs, A.: Landscape structure and use, climate, and water movement in the Mekong River basin, Hydrol. Process., 22, 1731–1746, 2007.

Delgado, J. M., Merz, B., and Apel, H.: A climate-flood link for the lower Mekong River, Hydrol. Earth Syst. Sci., 16, 1533–1541, doi:10.5194/hess-16-1533-2012, 2012.

- Earth Syst. Sci., 16, 1533–1541, doi:10.5194/hess-16-1533-2012, 2012.
 Dynesius, M. and Nilsson, C.: Fragmentation and flow regulation of river systems in the northern third of the world, Science, 266, 753–762, doi:10.1126/science.266.5186.753, 1994.
 EitzHugh, T. W.: EECAM: a method for assessing alteration of onvironmental flow components.
 - FitzHugh, T. W.: EFCAM: a method for assessing alteration of environmental flow components, River Res. Appl., doi:10.1002/rra.2681, in press, 2013.
- Gao, Y., Vogel, R. M., Kroll, C. N., Poff, N. L., and Olden, J. D.: Development of representative indicators of hydrologic alteration, J. Hydrol., 374, 136–147, doi:10.1016/j.jhydrol.2009.06.009, 2009.
 - Grumbine, R. E. and Xu, J.: Mekong hydropower development, Science, 332, 178–179, doi:10.1126/science.1200990, 2011.
- ¹⁵ Grumbine, R. E., Dore, J., and Xu, J.: Mekong hydropower: drivers of change and governance challenges, Front. Ecol. Environ., 10, 91–98, doi:10.1890/110146, 2012.
 - ICEM: MRC Strategic Environmental Assessment Hydropower of on the Mekong mainstream, available at: http://icem.com.au/portfolio-items/ mrc-sea-of-hydropower-on-the-mekong-mainstream-reports-series/ (last access: 12 February 2014), 2010.

20

25

- Ishidaira, H., Ishikawa, Y., Funada, S., and Takeuchi, K.: Estimating the evolution of vegetation cover and its hydrological impact in the Mekong River basin in the 21st century, Hydrol. Process., 22, 1395–1405, 2008.
- Johnston, R. and Kummu, M.: Water resource models in the Mekong Basin: a review, Water Resour. Manage., 26, 1–27, doi:10.1007/s11269-011-9925-8, 2011.
- Kareiva, P. M.: Dam choices: analyses for multiple needs, P. Natl. Acad. Sci. USA, 109, 5553– 5554, 2012.
- Kingsford, R. T.: Ecological impacts of dams, water diversions and river management on floodplain wetlands in Australia, Austral. Ecol., 25, 109–127, 2000.
- ³⁰ Kingston, D. G., Thompson, J. R., and Kite, G.: Uncertainty in climate change projections of discharge for the Mekong River Basin, Hydrol. Earth Syst. Sci., 15, 1459–1471, doi:10.5194/hess-15-1459-2011, 2011.



- Koponen, J., Kummu, M., Lauri, H., Virtanen, M., Inkala, A., and Sarkkula, J.: 3D Modelling User Guide, Final Report, MRC Information Knowledge Management Programme/Finnish Environment Institute (SYKE)/EIA Centre of Finland Ltd., Helsinki, Finland, 2010.
- Kruskal, W. H. and Wallis, W. A.: Use of ranks in one-criterion variance analysis, J. Am. Stat. Assoc., 47, 583–621, doi:10.1080/01621459.1952.10483441, 1952.

5

10

25

- Kummu, M. and Sarkkula, J.: Impact of the Mekong River flow alteration on the Tonle Sap flood pulse, Ambio, 37, 185–192, 2008.
- Kummu, M., Lu, X. X., Wang, J. J., and Varis, O.: Basin-wide sediment trapping efficiency of emerging reservoirs along the Mekong, Geomorphology, 119, 181–197, doi:10.1016/j.geomorph.2010.03.018, 2010.
- Kummu, M., Tes, S., Yin, S., Adamson, P., Józsa, J., Koponen, J., Richey, J., and Sarkkula, J.: Water balance analysis for the Tonle Sap lake – floodplain system, Hydrol. Process., 28, 1722–1733, doi:10.1002/hyp.9718, 2014.

Lauri, H., de Moel, H., Ward, P. J., Räsänen, T. A., Keskinen, M., and Kummu, M.: Future

- changes in Mekong River hydrology: impact of climate change and reservoir operation on discharge, Hydrol. Earth Syst. Sci., 16, 4603–4619, doi:10.5194/hess-16-4603-2012, 2012.
 - Lehner, B., Liermann, C. R., Revenga, C., Vörösmarty, C., Fekete, B., Crouzet, P., Döll, P., Endejan, M., Frenken, K., Magome, J., Nilsson, C., Robertson, J. C., Rödel, R., Sindorf, N., and Wisser, D.: High-resolution mapping of the world's reservoirs and dams for sustainable river-flow management, Front. Ecol. Environ., 9, 494–502, doi:10.1890/100125, 2011.
- river-flow management, Front. Ecol. Environ., 9, 494–502, doi:10.1890/100125, 2011.
 MRC: Data and Information Services Master Catalogue, Mekong River Commission, Vientiane, Lao PDR, available at: http://portal.mrcmekong.org/master-catalogue (last access: 12 February 2014), 2009.

MRC: Impacts on the Tonle Sap Ecosystem, Basin Development Plan Programme, Phase 2, Mekong River Commission, Vientiane, Lao PDR, 2010.

- Nash, J. E. and Sutcliffe, J. V.: River flow forecasting through conceptual models Part 1: A discussion of principles, J. Hydrol., 10, 282–290, doi:10.1016/0022-1694(70)90255-6, 1970.
 Nilsson, C. and Berggren, K.: Alterations of riparian ecosystems caused by river regulation, Bio-Science, 50, 783–792, doi:10.1641/0006-3568(2000)050[0783:AORECB]2.0.CO;2, 2000.
- Nilsson, C., Reidy, C. A., Dynesius, M., and Revenga, C.: Fragmentation and flow regulation of the world's large river systems, Science, 308, 405–408, doi:10.1126/science.1107887, 2005.



- Petts, G. E.: Long-term consequences of upstream impoundment, Environ. Conserv., 7, 325–332, doi:10.1017/S0376892900008183, 1980.
- Piman, T., Cochrane, T. A., Arias, M. E., Green, A., and Dat, N. D.: Assessment of flow changes from hydropower development and operations in Sekong, Sesan and Srepok Rivers of the
- ⁵ Mekong Basin, J. Water Resour. PI.-ASCE, 139, 723–732, doi:10.1061/(ASCE)WR.1943-5452.0000286, 2013a.
 - Piman, T., Lennaerts, T., and Southalack, P.: Assessment of hydrological changes in the lower Mekong basin from basin-wide development scenarios, Hydrol. Process., 27, 2115–2125, doi:10.1002/hyp.9764, 2013b.
- Poff, N. L. and Zimmermann, J. K. H.: Ecological responses to altered flow regimes: a literature review to inform the science and management of environmental flows, Freshwater Biol., 55, 194–205, doi:10.1111/j.1365-2427.2009.02272.x, 2010.
 - Poff, N. L., Allan, J. D., Bain, M. B., Karr, J. R., Prestegaard, K. L., Richter, B. D., Sparks, R. E., and Stromberg, J. C.: The natural flow regime, BioScience, 47, 769–784, doi:10.2307/1313099, 1997.
 - Poff, N. L., Olden, J. D., Merritt, D. M., and Pepin, D. M.: Homogenization of regional river dynamics by dams and global biodiversity implications, P. Natl. Acad. Sci. USA, 104, 5732–5737, doi:10.1073/pnas.0609812104, 2007.

Räsänen, T. A. and Kummu, M.: Spatiotemporal influences of ENSO on precipitation and flood pulse in the Mekong River Basin, J. Hydrol., 476, 154–168,

doi:10.1016/j.jhydrol.2012.10.028, 2013.

15

30

- Räsänen, T. A., Koponen, J., Lauri, H., and Kummu, M.: Downstream hydrological impacts of hydropower development in the Upper Mekong Basin, Water Resour. Manage., 26, 3495– 3513, doi:10.1007/s11269-012-0087-0, 2012.
- Räsänen, T. A., Lehr, C., Mellin, I., Ward, P. J., and Kummu, M.: Palaeoclimatological perspective on river basin hydrometeorology: case of the Mekong Basin, Hydrol. Earth Syst. Sci., 17, 2069–2081, doi:10.5194/hess-17-2069-2013, 2013.
 - Richter, B. D., Baumgartner, J. V., Powell, J., and Braun, D. P.: A method for assessing hydrologic alteration within ecosystems, Conserv. Biol., 10, 1163–1174, doi:10.1046/j.1523-1739.1996.10041163.x. 1996.
 - Richter, B. D., Baumgartner, J., Wigington, R., and Braun, D.: How much water does a river need?, Freshwater Biol., 37, 231–249, doi:10.1046/j.1365-2427.1997.00153.x, 1997.



Stone, R.: Mayhem on the Mekong, Science, 333, 814–818, doi:10.1126/science.333.6044.814, 2011.

- The Nature Conservancy: Indicators of Hydrologic Alteration Version 7.1 User's Manual, available at: http://www.conservationgateway.org/ConservationPractices/
- 5 Freshwater/EnvironmentalFlows/MethodsandTools/IndicatorsofHydrologicAlteration/Pages/ indicators-hydrologic-alt.aspx (last access: 6 January 2014), 2009.
 - Thompson, J. R., Laizé, C. L. R., Green, A. J., Acreman, M. C., and Kingston, D. G.: Climate change uncertainty in environmental flows for the Mekong River, Hydrolog. Sci. J., doi:10.1080/02626667.2013.842074, in press, 2013.
- Ty, T. V., Sunada, K., and Ichikawa, Y.: A spatial impact assessment of human-induced intervention on hydrological regimes: a case study in the upper Srepok River basin, Central Highlands of Vietnam, Int. J. River Basin Manage., 9, 103–116, doi:10.1080/15715124.2011.595720, 2011.

Ty, T. V., Sunada, K., Ichikawa, Y., and Oishi, S.: Scenario-based impact assessment of land use/cover and climate changes on water resources and demand: a case study in

- Iand use/cover and climate changes on water resources and demand: a case study in the Srepok River Basin, Vietnam–Cambodia, Water Resour. Manage., 26, 1387–1407, doi:10.1007/s11269-011-9964-1, 2012.
 - Västilä, K., Kummu, M., Sangmanee, C., and Chinvanno, S.: Modelling climate change impacts on the flood pulse in the Lower Mekong floodplains, J. Water Clim. Change, 1, 67–86, doi:10.2166/wcc.2010.008, 2010.

20

25

- Walling, D. E.: The sediment load of the Mekong River, in: The Mekong, available at: http://www.sciencedirect.com/science/article/B9FBM-4Y59TWF-3/2/ca09cfb26971e88f95e25e39c9fe73ba, Academic Press, San Diego, 113–142, 2009.
- WB: Modelled Observations on Development Scenarios in the Lower Mekong Basin, World Bank, Vientiane, Lao PDR., 2004.
- Ziv, G., Baran, E., Nam, S., Rodriguez-Iturbe, I., and Levin, S. A.: Trading-off fish biodiversity, food security, and hydropower in the Mekong River Basin, P. Natl. Acad. Sci. USA, 109, 5609–5614, doi:10.1073/pnas.1201423109, 2012.





Table 1. Description of water infrastructure development scenarios.

Scenario name	Description	Active storage (km ³)
Baseline (BL)	Simulated baseline conditions 1986–2000 (Piman et al., 2013b)	9.1
Definite Future (DF)	Water infrastructure development plans up to 2015, including 3.4 million ha irrigation areas, water supply demands, and 6 dams in the Upper Mekong (Piman et al., 2013b)	32.3 (additional 23.2 from BL)
3S hydropower development (3S)	Construction and operation of 42 hydropower and regulation dams in the main tributaries and sub-tributaries of the Sesan, Sekong, and Srepok rivers (Piman et al., 2013a)	35.4 (additional 26.3 from BL)
DF + 3S	Cumulative impact of the DF and 3S scenar- ios described above	58.6 (additional 49.5 from BL)

Table 2. Kruskal–Wallis test results for comparison of annual parameters. Each column group represents a one-to-one comparison between baseline (BL), Definite future (DF) and 3S hydropower (3S) scenarios. χ^2 represents the test statistic and *p* represents the probability value of χ^2 . Significant *p* values (≤ 0.05) are highlighted.

	BL-DF	BL-DF BL-3S			DF	-3S
Parameters	χ²	р	χ ²	р	χ²	р
Monthly water levels						
Jan	0.00	0.98	0.00	0.95	0.01	0.92
Feb	0.72	0.40	0.53	0.47	0.01	0.92
Mar	2.55	0.11	2.42	0.12	0.02	0.90
Apr	7.84	0.01	6.72	0.01	0.08	0.77
Мау	8.07	0.00	6.94	0.01	0.41	0.52
Jun	1.93	0.16	0.95	0.33	0.59	0.44
Jul	0.19	0.66	0.02	0.90	0.19	0.66
Aug	0.27	0.60	0.17	0.68	0.01	0.92
Sep	0.80	0.37	0.47	0.49	0.07	0.79
Oct	1.21	0.27	1.03	0.31	0.01	0.92
Nov	0.72	0.40	0.47	0.49	0.03	0.85
Dec	0.41	0.52	0.23	0.63	0.08	0.77
Annual parameters						
1 day minimum	7.84	0.01	6.72	0.01	0.62	0.43
3 day minimum	7.84	0.01	6.72	0.01	0.62	0.43
7 day minimum	7.84	0.01	6.72	0.01	0.65	0.42
30 day minimum	7.50	0.01	6.09	0.01	0.59	0.44
90 day minimum	4.92	0.03	3.80	0.05	0.31	0.58
1 day maximum	1.03	0.31	0.95	0.33	0.00	1.00
3 day maximum	1.03	0.31	0.95	0.33	0.00	1.00
7 day maximum	1.03	0.31	0.87	0.35	0.00	0.98
30 day maximum	0.95	0.33	0.87	0.35	0.00	0.98
90 day maximum	0.95	0.33	0.95	0.33	0.08	0.77
Date of minimum	0.29	0.59	0.07	0.79	0.14	0.71
Date of maximum	0.04	0.85	0.00	0.98	0.04	0.85
Base flow index	18.79	0.00	17.72	0.00	1.60	0.21
Fall rate	8.94	0.00	8.96	0.00	0.20	0.66
Rise rate	2.69	0.10	0.65	0.42	0.80	0.37
Low pulse duration	0.00	0.98	0.00	0.98	0.02	0.90
High pulse duration	0.00	1.00	0.00	0.97	0.01	0.92
Number of reversals	0.00	0.96	0.11	0.73	0.08	0.78



Parameters	Baseline (BL)						Definite Future (DF)				Definite Future + 3S hydropower (DF + 3S)					
Monthly water levels	Median	CD ^a	Min	Max	Low RVA ^b Boundary	High RVA Boundary	Median	CD	Min	Max	HAF ^c	Median	CD	Min	Max	HAF
Jan	4.93	0.13	4.46	5.84	4.80	5.19	4.88	0.13	4.38	5.94	0.0	4.96	0.15	4.36	6.00	-0.33
Feb	3.87	0.13	3.51	4.65	3.82	4.09	3.95	0.13	3.56	4.76	0.0	4.06	0.14	3.64	4.85	0.00
Mar	2.94	0.15	2.65	3.60	2.89	3.11	3.14	0.14	2.83	3.77	0.0	3.28	0.15	3.01	3.92	-0.33
Apr	2.15	0.13	1.90	2.69	2.08	2.27	2.41	0.12	2.12	2.94	-0.6	2.62	0.12	2.36	3.15	-1.00
May	1.60	0.29	1.33	2.16	1.50	1.70	1.93	0.23	1.57	2.47	-0.8	2.21	0.19	1.83	2.70	-1.00
Jun	2.34	0.47	1.21	3.89	1.74	2.46	2.62	0.43	1.62	3.99	-0.2	2.71	0.34	1.88	4.06	0.20
Jul	3.97	0.57	2.48	7.13	3.43	4.10	4.03	0.55	2.71	6.94	0.0	4.04	0.46	2.84	6.77	0.00
Aug	6.27	0.33	4.39	8.86	5.54	7.04	6.12	0.34	4.37	8.59	0.2	6.05	0.32	4.31	8.50	0.40
Sep	8.01	0.21	6.77	9.67	7.42	8.60	7.82	0.23	6.53	9.60	0.2	7.66	0.25	6.34	9.60	0.00
Oct	8.56	0.18	7.42	9.26	7.82	8.82	8.42	0.21	7.08	9.22	0.2	8.31	0.23	6.78	9.22	-0.20
Nov	7.68	0.16	6.79	8.67	7.33	8.08	7.54	0.16	6.52	8.66	0.0	7.52	0.18	6.33	8.64	0.00
Dec	6.25	0.15	5.61	7.33	6.06	6.68	6.14	0.17	5.39	7.36	-0.4	6.17	0.20	5.29	7.39	-0.40
Min/Max periods																
1 day min	1.41	0.33	1.15	2.05	1.36	1.60	1.75	0.27	1.45	2.36	-0.4	2.05	0.21	1.73	2.60	-1.00
3 day min	1.42	0.33	1.15	2.05	1.36	1.60	1.75	0.27	1.45	2.37	-0.4	2.06	0.21	1.73	2.61	-1.00
7 day min	1.43	0.33	1.16	2.07	1.37	1.61	1.76	0.27	1.46	2.38	-0.4	2.06	0.21	1.73	2.62	-1.00
30 day min	1.52	0.31	1.22	2.18	1.45	1.69	1.84	0.25	1.51	2.48	-0.4	2.11	0.20	1.78	2.71	-1.00
90 day min	1.97	0.28	1.56	2.69	1.81	2.03	2.22	0.23	1.78	2.94	-0.6	2.46	0.16	2.04	3.14	-1.00
1 day max	8.71	0.18	7.51	9.80	7.93	9.01	8.55	0.22	7.40	9.74	0.2	8.43	0.23	7.12	9.74	-0.20
3 day max	8.71	0.18	7.51	9.80	7.93	9.00	8.55	0.21	7.40	9.74	0.2	8.43	0.23	7.12	9.74	-0.20
7 day max	8.69	0.18	7.50	9.78	7.92	8.99	8.54	0.22	7.39	9.73	0.2	8.42	0.23	7.11	9.73	-0.20
30 day max	8.58	0.19	7.42	9.67	7.84	8.92	8.43	0.21	7.29	9.60	0.2	8.32	0.24	7.08	9.59	-0.20
90 day max	8.12	0.20	7.04	9.27	7.48	8.52	7.96	0.22	6.84	9.17	0.2	7.86	0.24	6.64	9.15	-0.20

Table 3. Summary of monthly and minimum/maximum hydrological parameters. Largest alterations to occur during the dry season (April, May, 1, 3, 30, 90 day min).

^a CD = coefficient of dispersion ([75th percentile-25th percentile]/50th percentile);

^b RVA: Range of Variability Approach;

^c HAF: Hydrologic Alteration Factor, which is the percent difference between the expected baseline frequency and the simulated frequency for the impact scenarios.

HESSD 11, 2177–2209, 2014									
Dams on Mekong tributaries									
M. E. Arias et al.									
Title	Page								
Abstract	Introduction								
Conclusions	References								
Tables	Figures								
14	►I								
•	•								
Back	Close								
Full Scre	een / Esc								
Printer-frie	ndly Version								
Interactive	Interactive Discussion								
œ	BY BY								

Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper

HESSD 11, 2177-2209, 2014 **Dams on Mekong** tributaries M. E. Arias et al. Title Page Abstract Introduction Conclusions References **Tables Figures** Back Full Screen / Esc **Printer-friendly Version** Interactive Discussion

Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper

Table 4. Summary of annual hydrological parameters. Largest alterations factors (HAF) estimated for base flow index and water level fall rate.

Parameters	meters Baseline (BL)					Definite Future (DF)				Definitive Future + 3S hydropower (DF + 3S						
Monthly water levels	Median	CD ^a	Min	Max	Low RVA ^b Boundary	High RVA Boundary	Median	CD	Min	Max	HAF	Median	CD	Min	Max	HAF
Base flow index	0.31	0.17	0.27	0.37	0.29	0.32	0.37	0.09	0.33	0.43	-1.00	0.42	0.08	0.38	0.47	-1.00
Date of minimum	24/05	0.04	05/05	14/06	18/05	28/05	20/05	0.04	01/05	12/06	-0.20	20/05	0.04	06/05	13/06	-0.20
Date of maximum	08/10	0.02	16/09	24/10	04/10	09/10	08/10	0.02	17/09	29/10	0.33	06/10	0.03	17/09	30/10	0.20
Low pulse duration	91	0.3	48	120	86	101	81	0	34	113	-0.20	67	0.5	14	100	-0.5
High pulse duration	91	1	44	144	76	117	85	0.9	28	143	0.00	90	1.1	6	142	0.0
Rise rate (cmd ⁻¹)	5.3	21.9	3.7	6.8	5.1	5.9	4.8	21.1	3.0	6.4	-0.33	4.7	2.6	3.3	6.0	-0.83
Fall rate (cmd ⁻¹)	-3.2	-12.5	-3.6	-3.0	-3.4	-3.1	-2.8	-10.7	-3.4	-2.7	-0.20	-2.6	-1.5	-3.3	-2.4	-0.60

^a CD = coefficient of dispersion ([75th percentile-25th percentile]/50th percentile);

^b RVA: Range of Variability Approach; ^c HAF: percent difference between the expected baseline frequency and the simulated frequency for the impact scenarios.

	BL		DF		DF + 3S			
Percent of days inundated in 15 yr (%)	Area (km ²)	Area (km ²)	Area change from BL (%)	Area (km ²)	Area change from BL (%)			
0.5–10	1758	1935	10.1	2042	16.1			
10–20	1417	1468	3.6	1582	11.7			
20–30	1421	1361	-4.3	1275	-10.3			
30–40	1667	1554	-6.7	1480	-11.2			
40–50	1533	1420	-7.3	1349	-12.0			
50–60	1391	1229	-11.7	1018	-26.8			
60–70	931	866	-7.0	962	3.3			
70–80	949	941	-0.9	885	-6.7			
80–90	693	614	-11.4	623	-10.2			
90–100	4910	5188	5.7	5334	8.6			

Table 5. Changes in spatial patterns of flooding in the Tonle Sap.





Fig. 1. Map of the Mekong Basin highlighting the Tonle Sap floodplain and dams in the Definite future (black dots) and 3S development scenarios (violet triangles). The green triangle shows the Kampong Luong water level gauge location on the Tonle Sap.





Fig. 2. Models used and their general features. DF = Definite Future.





Fig. 3. Observed vs. projected daily water levels (in meters above sea level, ma.s.l.) during 1986–2000.











Fig. 5. Comparison of daily water levels and environmental flow components between the baseline scenario (BL) and the combine effect of the Definite Future and the 3S Hydropower scenario (DF + 3S).





Fig. 6. Exceedance probability plot of daily water levels. Greatest deviations expected for water levels near the 20% exceeding level (\sim 7ma.s.l.) and below the 70% exceeding level (less than 3ma.s.l.).





Fig. 7. Maps representing duration of flooding during the 15 yr simulations (a) baseline (BL) flood duration map as percentage of total simulation time; (b) map showing the difference in flood duration between DF + 3S and BL. Expected increase flood duration in the more frequently inundated areas (in blue) and a decrease in flood duration in the marginally inundated areas (in red, green and orange).



Discussion Paper