Hydrol. Earth Syst. Sci. Discuss., 11, 4477–4530, 2014 www.hydrol-earth-syst-sci-discuss.net/11/4477/2014/ doi:10.5194/hessd-11-4477-2014 © Author(s) 2014. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Assimilation of satellite data to optimize large scale hydrological model parameters: a case study for the SWOT mission

V. Pedinotti^{1,2}, A. Boone¹, S. Ricci³, S. Biancamaria⁴, and N. Mognard⁵

¹CNRM/GAME, Météo-France, CNRS, URA 1357, Toulouse, France
 ²Centre National d'études spatiales (CNES), Toulouse, France
 ³CERFACS/URA 1875, 42 Avenue Gaspard Coriolis, 31057 Toulouse cedex, France
 ⁴CNRS, LEGOS, UMR5566 CNRS-CNES-IRD-Université Toulouse III, France
 ⁵CNES, LEGOS, UMR5566 CNRS-CNES-IRD-Université Toulouse III, France

Received: 3 March 2014 - Accepted: 5 April 2014 - Published: 30 April 2014

Correspondence to: V. Pedinotti (vanessa.pedinotti@gmail.com)

Published by Copernicus Publications on behalf of the European Geosciences Union.



Abstract

During the last few decades, satellite measurements have been widely used to study the continental water cycle, especially in regions where in situ measurements are not readily available. The future Surface Water and Ocean Topography (SWOT) satellite ⁵ mission will deliver maps of water surface elevation (WSE) with an unprecedented resolution and provide observation of rivers wider than 100 m and water surface areas greater than approximately 250 m × 250 m over continental surfaces between 78° S and 78° N. This study aims to investigate the potential of SWOT data for parameter optimization for large scale river routing models which are typically employed in Land ¹⁰ Surface Models (LSM) for global scale applications. The method consists in applying a data assimilation approach, the Extended Kalman Filter (EKF) algorithm, to correct the Manning roughness coefficients of the ISBA-TRIP Continental Hydrologic System. Indeed, parameters such as the Manning coefficient, used within such models to de-

scribe water basin characteristics, are generally derived from geomorphological rela-

- tionships, which might have locally significant errors. The current study focuses on the Niger basin, a trans-boundary river, which is the main source of fresh water for all the riparian countries. In addition, geopolitical issues in this region can restrict the exchange of hydrological data, so that SWOT should help improve this situation by making hydrological data freely available. In a previous study, the model was first evaluated against
- in-situ and satellite derived data sets within the framework of the international African Monsoon Multi-disciplinary Analysis (AMMA) project. Since the SWOT observations are not available yet and also to assess the proposed assimilation method, the study is carried out under the framework of an Observing System Simulation Experiment (OSSE). It is assumed that modeling errors are only due to uncertainties in the Man-
- ning coefficient. The true Manning coefficients are then supposed to be known and are used to generate synthetic SWOT observations over the period 2002–2003. The impact of the assimilation system on the Niger basin hydrological cycle is then quantified. The optimization of the Manning coefficient using the EKF algorithm over an 18 month



period leads to a significant improvement of the river water levels. The relative bias of the water level is globally improved (a 30 % reduction). The relative bias of the Manning coefficient is also reduced (40 % reduction) and it converges towards an optimal value despite potential problems related to equifinality. Discharge is also improved by

the assimilation, but to a lesser extent than for the water levels (7%). Moreover, the method allows a better prediction of the occurrence and intensity of flood events in the inner delta and shows skill in simulating the maxima and minima of water storage anomalies in several continental reservoirs, especially the groundwater and the aquifer reservoirs. Results obtained in this preliminary study demonstrate SWOT potential for global hydrologic modeling, especially to improve model parameters.

1 Introduction

The impact of climate variability on land water storage is becoming an increasingly crucial issue for the development of future water resource management strategies. In order to do such impact studies, Continental Hydrologic Systems (CHSs) can be used to simulate water dynamics over and under the land surface as a response to environmental forcing. At regional or global scales, realistic representation of major surface hydrologic and hydrodynamic processes is very challenging using computationally efficient, easily parameterized, comparatively simple and physically based routing methodologies. However, land surface hydrologic processes are highly heterogeneous in space and time and are therefore difficult to parameterize given huge dimensions of Atmospheric

- time and are therefore difficult to parameterize given huge dimensions of Atmospheric General Circulation Model (AGCM) grid areas. Observational data describing the water dynamics and storage variations are required to evaluate CHS-simulated diagnostics, but also to calibrate these models. In-situ data have been extensively used, but they are limited by their temporal and spatial coverage. In addition to the information provided
- by in-situ measurements, satellite remote sensing instruments have been developed and continually improved. These instruments generally provide a large spatial coverage which is more appropriate for global applications, especially in areas where in-situ



data are scarce. Such areas are generally sparsely inhabited, with reduced infrastructures and possible geopolitical issues, such as large portions of the African continent or part of the Arctic (Alsdorf et al., 2007). Applications using satellite remote sensing techniques lead to many promising perspectives for improving the observation of land
 ⁵ surface and hydrological variables and processes.

Hydrologic modeling applications require information about continental water dynamics and storage variations over and under the surface. In situ discharge data, for example, give 1-dimensional information which quantifies water fluxes in a specific river channel, but such data do not give any information about runoff and lateral inflow. How-

- ever, in more hydrologically complex areas, such as wetlands and floodplains which are better represented as three-spatial-dimension processes, cannot be adequately resolved using one-spatial-dimension observations (Alsdorf et al., 2007). Spatially distributed observations, such as those provided by satellites, give 2-dimensional information about surface water dynamics. Recently, efforts have been made to build global
- ¹⁵ maps of floodplain variability and extent, providing an additional metric for CHSs evaluation (Papa et al., 2012). Nadir altimetry has also constituted a valuable progress for the monitoring of surface water dynamics and elevation (TOPEX-POSEIDON, EN-VISAT, JASON 1 and 2; Baup et al., 2007; Santos Da Silva et al., 2012).

Although useful, current remote sensing technology spatial resolution does not resolve small scale land water dynamics thereby limiting our understanding of large scale hydrologic and hydrodynamic processes. The future NASA-CNES-CSA Surface Water and Ocean Topography (SWOT) satellite mission will be launched in 2020 and will deliver maps of water surface elevation (WSE), slope and extent with an unprecedented resolution of 100 m.

²⁵ Concerning continental hydrology, the SWOT mission has the potential to help dealing with critical issues, such as monitoring trans-boundary basins and the development of management strategies in a changing world. It is thus necessary to determine how the SWOT data can be used to improve hydrological simulations and to better predict continental water storage. Several studies are thus currently being performed over



geographically diverse basins to propose efficient approaches to use SWOT observations for a variety of climates and geomorphology.

Data assimilation (DA) has been shown to be a promising technique for improving river modelling (Andreadis et al., 2007; Durand et al., 2008; Biancamaria et al.,

- ⁵ 2011; Yoon et al., 2012). Commonly used in operational meteorology and oceanography, DA combines data coming from various sources, such as numerical models or observations, while taking into account measurement errors and model uncertainties for a better description and prediction of the system. However, these methods are not yet extensively used in hydrology and related works are rare, especially for large scale
- applications. Drusch et al. (2009) used observations of 2 m air temperature and soil moisture to evaluate a Kalman filter based soil moisture analysis system and its impact on the operational ECMWF integrated forecast system. They showed that the impact of EKF on the forecast skill of the operational weather forecast model was neutral in terms of forecast score but gave the promising possibility to better constrain
- the soil water content with more accurate soil moisture estimates. Pereira-Cardenal et al. (2011), investigated the potential of using ENVISAT water levels observations in a real time or near real time by applying an Ensemble Kalman Filter in order to update semi-distributed hydrological model state variables. The method was applied to the Syr Darya River Basin, a complex mountainous region covering approximately
- ²⁰ 7000 km². They showed that data assimilation allowed a better real time estimation of reservoir levels over the region. However, because of the state updating procedure used in this study, which consisted in adding or abstracting water from reservoirs, the method is limited to medium-range forecasting. It is not suitable for long-term water resources scenario calculations, where mass balance has to be maintained. More re-
- ²⁵ cently, Michailovsky et al. (2013) used radar altimetry data from the ENVISAT mission for updating the storage of a routing model of the main reach of the Brahmaputra river driven by the outputs of a calibrated rainfall runoff model showing the potential for the use of altimetric data in combination with hydrological models for flow modeling in large rivers. However in situ flow data was required for the calibration of the rainfall



runoff model which may still be a limitation in some areas with poor data availability such as the Niger river. Salamon and Feyen (2009) used the residual re-sampling particle filter to assess parameter, precipitation and predictive uncertainty in the distributed rainfall-runoff hydrological model LISFLOOD for the Meuse catchment using

- discharge measurements. They showed that the equifinality hypothesis (several different parameter sets can lead to a good estimation of the discharge) was a limitation to the correction of a distributed hydrological parameter even in a physically based hydrologic model. Moreover, he emphasized the strong effect of rainfall uncertainties on the analysis. Finally, the results showed that accounting for parameter uncertainty only
- ¹⁰ during a calibration phase was not sufficient to properly predict uncertainty, limiting the application of the method for hydrologic forecasting over longer time periods. The aforementioned applications of DA in hydrological qmodeling have shown the potential of using remote sensing data in order to improve the model states or the parameters. However, they also showed the limitations due to the generally low spatial and temporal resolutions of these data sets.

Hydrological model uncertainties can come from several sources, such as model structure or input parameters, leading to the development of different DA methodologies. Indeed, depending on the study, DA either aims at optimizing the model input parameters or at directly correcting the model state (generally done in operational fore-

- ²⁰ cast applications for example). The current study investigates benefits of assimilating SWOT virtual water levels in order to improve input parameters of a large scale hydrological model within the context of a pre-launch study. The domain study area is the trans-boundary Niger basin (Fig. 1) which crosses a large part of the Sahel and is a critical source of water in this semi arid region which is characterized by an in-
- creasing population which is putting larger pressure on the already limited freshwater resources. The hydrology of this basin is modulated by the West African Monsoon (WAM) seasonal and inter annual variability which is characterized by extreme events such as droughts and floods which can have dramatic impacts on society and the regional economy. However, the lack of field measurements limits the understanding of



the salient hydrological processes in the Niger basin. For these reasons, it is an ideal test-bed for studying global hydrological issues. In a previous study, a Niger basin hydrological model application was set up and evaluated using the ISBA-TRIP distributed hydrological model. Along with river routing, this model includes a flooding scheme

- and a linear unconfined aquifer reservoir (Pedinotti et al., 2012). The modelling evaluation showed that the model was able to reasonably reproduce the major hydrologic and hydrodynamic processes. The importance of floodplains was also demonstrated, since they have a considerable impact on discharge downstream of the inland Niger delta. The confined aquifer improves the recession law and the simulation of low flows.
- However, some model deficiencies remain which can be due to forcing or model uncertainties. Among these sources of errors are the uncertainties of TRIP hydrological parameters. Indeed, these distributed parameters are defined by empirical relationships using available observations which are adapted towards obtaining the best results over the entire globe. However, such relationships might not give the best results locally (for
- a particular basin). These relationships thus lead to non-negligible errors which could be reduced using satellite data. Indeed, such data can potentially be used to spatially distribute parameters for each particular basin and then contribute to the development of a global database describing major river characteristics. Pedinotti et al. (2012) performed sensitivity tests to determine the main sources of uncertainty among the TRIP parameters.

The aim of the current study is to investigate how SWOT water level products can be used to optimize the Manning coefficient. Since SWOT observations are not yet available and to assess the usefulness of data assimilation, this study is carried out within the framework of an Observing System Simulation Experiment (OSSE) using

the TRIP model for the simulation of the Niger hydrodynamics. SWOT virtual measurements are produced using a reference ISBA-TRIP simulation. Here, it is assumed that modeling errors are only due to one key parameter which can not be directly estimated via observational data: the Manning roughness coefficient (the other sources of modeling errors are not considered here, and the reasons will be explained). The impact



of the assimilation system on the Niger river modeling is then quantified. First, a brief presentation of the study domain and the model is made in Sect. 2. In this section, the Manning coefficient is also defined and its spatial distribution used for the true simulation is shown. Then, the production of SWOT virtual water level is described in Sect. 3.

⁵ The methodology used to build the assimilation scheme is explained, and the main variables of the assimilation problem are described in Sect. 4. Finally, the impact of the assimilation on the main hydrological variables of the Niger basin are discussed in Sect. 5.

2 Study domain and model description

10 2.1 The Niger river basin

Originating in the Guinean highlands within the *Haute Guinée* and *Guinée Forestière* regions located in the *Fouta Djallon Massif* mountain range, the Niger river is the third longest river in Africa (4200 kilometers), after the Nile and the Congo. Its outlet is located in Nigeria, discharging through a massive delta into the Gulf of Guinea. On its way through Mali, it crosses a vast floodplain region called the Inland Delta. The Inland Delta has an average surface area of 73 000 km², and it dissipates a significant proportion of the flow of the river through absorption and evaporation (it is estimated that about 40% of water is lost through the inland delta by evaporation and/or infiltration, Andersen et al., 2005). From the headwaters to the Niger delta (taking into account the hydrologically active area), the Basin has an average area of about 1.5 million km².

The Niger river is shared by 9 countries and is the main source of water for about 100 million people living principally from agriculture and farming. During the 1970s and 1980s, West Africa faced extreme climate variations with extended drought conditions followed by floods, thus there is a need to better understand the functioning of this basin for water management purposes. The complexity of modelling the Niger basin is mainly due to the fact that it crosses very different climatic zones, from the tropical



humid Guinean coast where it generally rains every month of the year, to the desertic Saharan region. The main source of water over the basin is due to the West African Monsoon (WAM) which is characterized by a marked annual cycle and significant inter annual variability, leading to the succession of extreme events such as droughts and floods. The modelling of the Niger basin by CHSs thus requires a good description of

floods. The modelling of the Niger basin by CHSs thus requires a good description of climate conditions, especially of rainfall, and the knowledge of some key hydrological parameters which must be spatially distributed to account for their heterogeneity over the domain.

2.2 Review of the ISBA-TRIP model

- ISBA is a state-of-the-art land surface model which calculates the time evolution of the surface energy and water budgets (Noilhan and Planton, 1989). It represents the natural land surface component of the SURface-EXternalized (SURFEX) coupling platform at Météo-France (Masson et al., 2013). In the current study, we use the 3-layer forcerestore soil hydrology option (Boone et al., 1999). The options are also activated for
- a comprehensive representation of sub-grid hydrology in order to account for the heterogeneity of precipitation, topography and vegetation in each grid cell. A TOPMODEL approach (Beven and Kirkby, 1979) has been used to simulate a saturated fraction, *f*_{sat}, over which precipitation is entirely converted into surface runoff (Decharme et al., 2006). Infiltration is computed via two sub-grid exponential distributions of rainfall inten-
- sity and soil maximum infiltration capacity (Decharme and Douville, 2006). The TRIP original River Routing Model (RRM) was developed by Oki and Sud (1998) at University of Tokyo. It was first used at Météo-France to convert the model simulated runoff into river discharge using a global river channel network at a 1°. A more recent a 0.5° resolution global river network has been developed which is used for this study. The resolution global river network has been developed which is used for this study. The resolution global river network has been developed which is used for this study.
- ²⁵ ISBA-TRIP CHS was recently improved to take into account a simple groundwater reservoir, *G* (kg), which can be seen as a simple soil-water storage, and a variable stream flow velocity computed via the Mannings equation (Decharme et al., 2010). In addition, ISBA-TRIP includes a two-way flood scheme in which a flooded fraction of



the grid cell can be determined (Decharme et al., 2008, 2011). The flood dynamics are described through the daily coupling between ISBA land surface model and TRIP RIM, including a prognostic flood reservoir, F (kg). This reservoir fills when the river height exceeds the critical river bank full height (Fig. 3a), h_c (m). The flood interacts with the soil hydrology through infiltration, with the overlying atmosphere through precipita-

tion interception and through free water surface evaporation. For the Niger application, Pedinotti et al. (2012) added a simple linear confined aquifer reservoir, Aq (kg), to account for the long term water storage in deep and more or less confined aquifers. This reservoir was built on the example of the groundwater reservoir, *G*, but with a significantly longer time delay factor, τ_{aq} (s). The confined aquifer is supplied by a fraction

 $(1 - \alpha)$ of the drainage from ISBA, the remaining fraction (α) going to the groundwater reservoir. The TRIP schematic concept is presented on Fig. 2 and more details can be found in Pedinotti et al. (2012).

2.3 TRIP specific parameters

¹⁵ The Manning coefficient characterizes the roughness so that it modulates the surface water velocity and thus water levels and discharge, via the Manning formula. However, it is difficult to estimate via in-situ measurements or remote sensing techniques. In ISBA-TRIP, the Manning friction coefficient, n_{riv} , varies linearly and proportionally to the river width, W (m), from 0.04 near the river mouth to 0.1 (Decharme et al., 2011) in the upstream grid cells (Fig. 3b):

$$n_{\rm riv} = n_{\rm min} + (n_{\rm max} - n_{\rm min}) \left(\frac{W_{\rm mouth} - W}{W_{\rm mouth} - W_{\rm min}}\right)$$
(1

where n_{riv} represents the grid cell average Manning coefficient, n_{max} and n_{min} the maximum and minimum values of the Manning friction coefficient (equal to 0.1 and 0.04, respectively), W_{min} (m) the minimum river width value and W_{mouth} (m) is the width of the mouth in each basin of the TRIP network (W_{mouth} = 2000 for the Niger basin). The river width, W, is an important parameter because it controls both the river flow speed and



the floodplain dynamics. It is computed over the entire TRIP network via an empirical mathematical formulation that describes a simple geomorphological relationship between W and the mean annual discharge at each river cross section (Knighton, 1998; Arora and Boer, 1999; Decharme et al., 2011):

5
$$W = \max\left(30, \beta \times Q_{yr}^{1/2}\right)$$

where $Q_{\rm vr}$ (m³s⁻¹) is the annual mean discharge in each grid cell estimated using the global runoff database from Cogley (1979). As discussed in Decharme et al. (2011), this coefficient can vary drastically from one basin to another. β is equal to 20 for the branch of the river going from the river mouth (5° N) to 12° N and is fixed to 10 for the remaining river branch. The spatial distribution of the river width is shown in Fig. 3c. Another critical parameter is the river bankfull critical height, h_c , which is computed according to the river width via a simple power function (Decharme et al., 2011):

15

20

 $h_{\rm c} = W^{1/3}$.

10

The spatial distribution of h_c is shown in Fig. 3a. These relationships are found to work well at the global scale but can lead to significant errors for a specific basin at the regional scale (see the sensitivity tests in Pedinotti et al., 2012). Indeed, the asumption that the river width is proportional to the annual mean discharge can lead to significant errors in flooded areas where the river bed enlarges but the discharge is reduced through the flooding process. Moreover, it is assumed that the Manning coefficient is only dependant on the river width while other factors could be considered, such as the presence of vegetation, debris, soil type etc... Finally, these parameters are defined as constant in time which is a significant asumption, especially in a region with a marked seasonal climate variability such as the Niger basin. Remote sensing opens the pos-25 sibility of estimating the river width by direct measurements and the critical bankfull

height by indirect algorithms. However, the Manning coefficient will still be difficult to estimate even using remote sensing. This study focuses on finding a methodology to estimate this critical parameter via DA.



(2)

(3)

3 Satellite observations

The aim of this work is to estimate the potential benefits of using SWOT satellite measurements to provide spatially distributed estimates of the Manning coefficient over the Niger river basin. This section describes this future satellite mission and how virtual SWOT observations have been generated in this study.

3.1 The SWOT mission

5

10

SWOT will provide high-resolution images of water surface elevations over the oceans and continental surface water bodies. It will therefore observe continental surface waters at an unprecedented resolution, providing information for a better understanding of surface water dynamics and storage variations. The mission is currently planned to be launched around 2020.

The satellite main payload will be the Ka-band Radar Interferometer (KaRIN), a wide swath SAR (Synthetic Aperture Radar) interferometer. KaRIN will have two antennas separated by a 10 m boom, which will observe two ground swaths of 60 km on each ¹⁵ side of the satellite nadir, separated by a 20 km gap. The intrinsic pixel resolution will vary from 60 m (near range) to 10 m (far range) across-track and will be at best around 5 m along-track (however, this value is also dependent upon decorrelation time). Yet, for these intrinsic pixels, water elevation measurements have metric errors, which increase along the swath (depending on the look angle). To increase vertical accuracy, ²⁰ pixels have to be aggregated: over a 1 km² area inside the river mask, water elevation has a 10 cm or lower error (Rodríguez, 2012). River slopes will be measured with a 1 cm km⁻¹ resolution, after processing elevations over 10 km river reaches (Rodríguez, 2012). SWOT will be able to observe rivers wider than 100 m (requirement) and should be able to observe rivers wider than 50 m (goal). The chosen orbit will be

²⁵ a Low Earth Orbit with a 78° inclination, in order to observe almost all of the continental surfaces (Rodríguez, 2012).



3.2 Observing System Simulation Experiment (OSSE) and virtual SWOT data

The OSSE framework consists in simulating data that would be observed by the future measurement platform using a numerical model, in order to use them as virtual observations for DA experiments. The main objective of an OSSE is to validate the DA ⁵ method by using ideal conditions. Indeed, here it is assumed that the real state of the system is known. Also, the error statistics of the model state or parameters and in the observations are assumed to be known and correctly described which is not the case in real conditions. Also, this method is useful within the framework of the SWOT satellite mission preparation, since it allows, before launch, a quantification of the satellite data contribution to improve large scale river modeling (such as for the Niger basin). First, a realistic modeling of the studied basin in needed for the OSSE. Indeed, the model must be able to simulate the major hydrodynamic processes of the basin so that the simulated observations will reasonably represent the reality. The ISBA-TRIP

set-up evaluated in Pedinotti et al. (2012), with the inclusion of the flooding scheme and aquifer reservoir, is used to represent the true state of the hydrological system, also refered to as the *reference simulation*. For this so-called "truth", the model and its parameters are assumed to be perfect. An error is then added to this true state to build virtual observations. The background simulation results from the integration of

the same model in a different configuration, for instance with a different set of param eters (also called pertubed or background parameters). It gives an a priori description of the system that is an approximation of the truth. In the present study focussed on parameter estimation, the purpose of the DA algorithm is to retrieve an optimal set of model parameters starting with the background parameters, assimilating the virtual observations. It is important to note that in the present study, the error between the true
 Manning coefficients and the background Manning coefficients does not vary in time.

Within the framework of this SWOT-dedicated study, the true simulation is used to generate the SWOT observations, with the help of a relatively simple simulator developped by Biancamaria et al. (2011). Based on the prescribed orbit and swath, the



simulator provides an ensemble of SWOT tracks and related dates. The SWOT tracks are provided for the orbital period and then repeated over the years 2002–2003 (assuming the satellite starts its first orbit on 1 January 2002). The virtual data are the sum of the ISBA-TRIP water levels at the corresponding grid points, in addition to an

- instrumental error which is added to partialy account for the SWOT observation errors (see Sect. 4.2.1 for details). A river mask for the Niger comprising grid cells with a river width above 200 m is defined as illustrated in Fig. 4 which displays the Manning coefficient for the unmasked 110 pixels. It should be noted that the SWOT satellite will not measure absolute water level but free surface water elevation. Thus, in real-time
- ¹⁰ DA applications, the direct comparison between SWOT and ISBA-TRIP water levels will not be straightforward and will need further investigation. However, this issue is beyond the scope of an OSSE framework.

The 22 day repeat orbit and the 140 km swath used in this simulator allowed a global coverage of the study domain within 22 days. Among available orbits, two orbits have been pre-selected by the NASA-CNES project team, for various scientific and techni-

- ¹⁵ been pre-selected by the NASA-CNES project team, for various scientific and technical reasons (mainly to seek a compromise between both the hydrological and oceanographic scientific communities). These two orbits have the same repeat period, but different altitudes, meaning different subcycles. The repeat period corresponds to the minimum time taken by the satellite to fly over exactly the same ground location. Given
- the orbit parameters and the earth rotational speed, it requires a fixed number of satellite revolutions. For all of these revolutions, the part of the orbit that goes from North to South corresponds to the descending track and the one that goes from South to North corresponds to the ascending track. These ascending and descending tracks cross the equator at different times during one repeat period. The difference between these
- ²⁵ crossing times for two adjacent ascending (or descending) tracks during a repeat period is the orbit subcycle. The 970 km altitude orbit has a 3 day subcycle, whereas the 873 km altitude orbit has a 1 day subcycle. These two orbits both have global coverage but with a different time and spatial spread of the satellite tracks during one repeat period. The 1 day subcycle orbit has two adjacent swaths every day, meaning that each



river basin will be well sampled in few days, but then there will be no observations for several days (Fig. 5) with the risk of missing short term events. The 3 day subcycle orbit has two adjacent swaths every 3 days on average, meaning ground tracks will be more regularly distributed in space and time. Yet, there will be no tracks close in time

at any point during the cycle (Fig. 6). Thus, due to their spatial and temporal coverage over the domain, these two orbits present specific advantages and disadvantages that will be investigated in the framework of the DA framework. The OSSE is run over 2 years starting from the beginning of the monsoon season, on 1 June 2002. During each SWOT 22 day repeat, there are about 53 satellite overpasses on the Niger bassin
 for the 3 day subcycle orbit and 50 for the 1 day subcycle orbit.

4 Data assimilation schemes

4.1 Choice of the control variable.

The goal of using assimilation in this study is to correct the TRIP routing input parameters which are associated with uncertainties. The contribution of such corrections are estimated by comparing model outputs (water level, discharge, water storage...) with and without DA. Sensitivity tests in Pedinotti et al. (2012) determined the most sensitive TRIP parameters which impact the major hydrological processes of the Niger basin. It was shown that a modification of the Manning roughness coefficient, n_{riv} , has a significant impact on the hydrological variables over the Niger basin. Indeed, the Manning co-

- efficient, is used for flow calculations in the river stream, via the Manning formula. Due to its close relationship with water levels and discharge, it is one of the most important empirical parameters in the field of hydrology and hydraulics. Thus, a good estimation of this coefficient in the river bed leads to a better reproduction of surface water dynamics. There is a tendancy to regard the selection of Manning coefficient as an arbitrary
- or intuitive process. Indeed, hydrodynamic models usually determine the value of the Manning coefficient manually, often using estimations based on visual interpretation of



the land cover. The roughness can also be described by geomorphologic relationships, which are related to another parameter for which more information is known (river width for example). In ISBA-TRIP, the Manning coefficient, $n_{\rm riv}$, is assumed to vary linearly with the river width, *W*, from 0.04 near the river mouth to 0.10 in the upstream grid

- ⁵ cells (Eq. 1). These geomorphologic relationships are used to obtain the spatially distributed Manning coefficient which provides a "global" fit or best estimate, but might not be realistic at finer scales due to the potentially significant heterogeneity of the river and land properties. Thus, both approaches can lead to significant errors over a large computational domain which is characterized by multiple land use/cover classes. Al-
- though progress in remote sensing will probably improve our estimates of the Manning coefficient (using the two aforementioned approaches), this parameter will not be estimated directly via remote sensing and therefore will remain dependant on the physical relevance of the geomorphologic relationships. Thus, DA appears to be an appealing option for estimating the Manning coefficient using remote sensing data.
- In reality, the temporal variability of the error on the Manning coefficient is related to the flow dynamics as the river bed morphology can be significantly modified by flood events. Even though this temporal variability is not accounted for in our OSSE framework, the DA analysis is performed sequentially over a 2 day time window which allows a high variability of the correction on the Manning coefficient. It should be noted that
- in a real case study where sources of uncertainty are multiple (contrary to our OSSE framework where errors are only due to Manning coefficient perturbations), correcting the Manning could be interpreted as a way to account for other uncertainties (which are possibly characterized by errors with a higher temporal variability than that of the Manning coefficient). The choice of the time window length could be revisited in further
- ²⁵ studies. However, a longer assimilation window also requires a bigger storage capacity and this must be considered when selecting the length of the assimilation window. In the following section, along track virtual SWOT data over 2 days are assimilated to correct the Manning coefficient for the unmasked $n_t = 110$ ISBA-TRIP grid points. For



HESSD 11, 4477-4530, 2014 Pape Assimilation of SWOT data V. Pedinotti et al. Discussion Paper Title Page Abstract Introduction References Conclusions **Figures** Discussion Paper Back Full Screen / Esc Discussion **Printer-friendly Version** Interactive Discussion Pape

each analysis at time t (also called cycle), the control vector is thus a vector of 110 elements noted x_t .

4.2 The Extended Kalman Filter (EKF).

The assimilation algorithm used for the calculation of the analysis is the Extended Kalman Filter (EKF) which is presented in this section within the framework of parameter optimization. The true Manning coefficients (known in the framework on an OSSE but unknown in reality) are gathered in the vector $\mathbf{x}_t^{\text{true}}$ of size n_t . The vector of the a priori parameters \mathbf{x}_t^{b} for the hydrological models are presecribed by geomorphologic relationships which induce an error $\mathbf{e}_t^{\text{b}} = \mathbf{x}_t^{\text{true}} - \mathbf{x}_t^{\text{b}}$ of which statistics are described in the background error covariance matrix **B**. Here, these statistics are assumed to be constant over the assimilation cycles and to follow a Gaussian distribution, centered in 0 with a standard deviation, σ_t^{b} of 20% of the average value of the Manning coefficient over the river.

The observation vector y_t^0 of dimension p_t contains all the SWOT observations collected during the 2 day assimilation window. The observation operator H projects the 15 control vector onto the observation space. This operator is non-linear as it is the composition of the hydrological model M and of a selection operator S that simply extracts or interpolates the simulated water levels (over the whole gridded domain) at the observation points. Here, H = SoM where S represents the SWOT simulator and M is the integration of the hydrological model over the assimilation window. The relation 20 $y_t = H(x_t)$ allows to describe the true water level vector y_t^{true} at the observation points when x_t^{true} is used and the background hydrological water level vector y_t^{bck} at the observation points when x_t^{b} is used. In OSSE, an observation error e_t^{0} , is added to y_t^{true} to account for instrumental and representativeness errors. The observation errors are assumed to be decorrelated in space and time, and the observation error standard de-25 viation $(\sigma_t^o)^2$ is set equal to $(\sigma_t^b)^2$. The observation error covariance matrix **R**_t is thus assumed to be diagonal. Further work should focus on a complete estimation of the

observation error statistics in order to allow for along track correlation of the instrumental errors (Lion, 2012).

The EKF analysis vector \mathbf{x}_t^a is defined as a correction to the background vector, where the innovation vector $\mathbf{d}_t = \mathbf{y}_t^0 - H_t(\mathbf{x}_t^b)$ is muliplied by the gain matrix \mathbf{K}_t :

$$x_t^{a} = x_t^{b} + \mathbf{K}_t \boldsymbol{d}_t.$$

where \mathbf{K}_t reads:

$$\mathbf{K}_{t} = \mathbf{B}_{t}\mathbf{H}_{t}^{T}\left(\mathbf{H}_{t}\mathbf{B}_{t}\mathbf{H}_{t}^{T} + \mathbf{R}_{t}\right)^{-1}$$
(5)

¹⁰ where \mathbf{H}_t is the tangent linear of H with respect to \mathbf{x}_t . The statistics of the analysis error \boldsymbol{e}_t^a are determined by the analysis covariance matrix $\mathbf{A}_t = (\mathbf{I} - \mathbf{K}_t \mathbf{H}_t) \mathbf{B}_t$ (Bouttier and Courtier, 1999). The analysis vectors provide the corrected Manning coefficient values, which can then can be used to integrate the hydrological model and simulate the analyzed water levels over the whole domain. A schematic diagram of the assimilation process is shown in Fig. 7, and the key variables are represented in Eqs. (4) and (5) and listed in Table 1.

4.3 Jacobian matrix calculation

The EKF algorithm relies on the computation of a local approximation of the tangent linear of the observation operator that describes the relationship between the control vector and the observation space, with respect to the control vector. As the size of the control space is limited in this study, a finite difference scheme can be used to perform this approximation, in the vicinity of the background vector. Since the observation operator *H* includes the model propagation, the calculation of the Jacobian matrix \mathbf{H}_t requires the computation of n_t independent integrations of the hydrological model with



a perturbed element for each component of x_t .

$$\mathbf{H}_{t,ij} = \frac{\partial H}{\partial x}_{|_{t,ij}} = \frac{(H(x_t + \Delta x) - H(x_t - \Delta x))_i}{\Delta x_{t,j}} = \frac{\Delta y_{t,i}^+ - \Delta y_{t,i}^-}{\Delta x_{t,j}^+ + \Delta x_{t,j}^-}.$$

In Eq. (6), **H** translates the variations of water levels at the observation points induced by the variation of Manning coefficients. $\Delta y_{t,i}^+$ and $\Delta y_{t,i}^-$ represent the water level variations at the gridded pixel *i* related to variations $\Delta x_{t,j}^+$ and $\Delta x_{t,j}^-$ of the Manning coefficient at the gridded pixel *j*. A centered finite difference scheme was favoured over a one-sided scheme as it reduces noise on the evaluation of the local derivative. The computation of **H**_t thus requires $2 \times n_t$ integrations of ISBA-TRIP over the assimilation window using elementary perturbed Manning coefficients at the unmasked observation point. The computational cost of **H** could be optimized as only perturbations on Manning coefficients at the grid points located upstream of each observation point have an impact on water level at the observation point. In the present work, the $2 \times n_t$ integrations of ISBA-TRIP are achieved sequentially.

15 5 Results

The impact of DA on the hydrological processes is analysed using the relative error. For any variable v, the relative error is expressed as:

 $\operatorname{err}_{v} = \frac{v - v_{\operatorname{truth}}}{v_{\operatorname{truth}}}$

where v_{truth} refers to the variable v as described in the true simulation.

5.1 Impact of assimilation on Manning coefficient

The truth simulation is made using Manning coefficients which are constant in time, meaning that there is no temporal variation of the error on the model parameters,



(6)

(7)

thus it is expected that the DA analysis leads to a constant value of the corrected Manning close to the "true" values. However, since the Manning coefficient is spatially distributed, several spatial combinations of these parameters might resolve the assimilation problem which is generally referred to as the equifinality hypothesis. Figure 8

- ⁵ shows the Manning coefficient relative error (averaged over the river) time series for the two orbits. The average relative error of the Manning coefficient is significantly improved during the assimilation period and tends to converge to a stable value (about 0.19 for the 1 day subcycle orbit and 0.17 for the 3 day subcycle orbit), since the error is not significantly changed from January 2003 until the end of the assimilation experiment. The convergence towards the minimum value of the spatially averaged relative
- ¹⁰ iment. The convergence towards the minimum value of the spatially averaged relative error to the true averaged Manning coefficient is slightly faster for the 3 day subcycle orbit than for the 1 day subcycle.

The Manning coefficient temporal evolution at the 8 gage locations is shown in Fig. 9. It should be noted that in some places and for both subcycles, the "real" Manning coefficient value is only approached and not found through the assimilation cycles, which can be related to the equifinality problem. The 1 day subcycle and 3 day subcycle

- orbit assimilations converge to the same value in 5 locations out of 8. In Banankoro, Kandadji and Malanville, however, the coefficnet values for the two orbits converge to different values. Banankoro is located upstream of the river, so this difference can be
- explained by the lack of data uptream of this location for obtaining a robust estimate of the Manning coefficient at this site. Also, the impact of the Manning coefficient on the simulation depends on the rain amount over the observed locations. According to the considered subcycle, the satellite will see different zones and a different number of observations corresponding to different rain events which can lead to the different
- values obtained for the optimal Manning coefficient in some locations. Also, a noise with a frequency of about 20 days is observed in every location and for the two subcycles and might be related to the orbit repetitivity.



5.2 Impact of assimilation on water levels

Table 2 gives water level mean relative error computed with respect to the true water levels, first averaged over the entire river for the 2 year period and then at each of the 8 observing stations shown in Fig. 1. Figures 10 and 11 display the water level relative error averaged over the river and at the 8 observing stations as a function of time when (i) there is no assimilation (black curve), (ii) after a 1 day subcycle orbit SWOT-observation assimilation (green curve) and (iii) the 3 day subcycle orbit SWOTobservation assimilation (blue curve).

These results show that the DA analysis leads to a significant reduction of the water level relative error over the whole river (the averaged relative error is reduced by more than a factor of three with DA) and at the 8 gages. Indeed, in most of the 8 locations, there is an improvement of several meters reaching up to 9 m at Lokoja (for an 8 m averaged river depth). As for the Manning coefficient, a noise with a repeat period of 20 days is observed and can be directly related to the noise observed on the Manning

¹⁵ coefficient. Also, even in the locations where the analysed Manning coefficient defers for both subcycles, the same water levels are retrieved for both subcycles which confirms the equifinality hypothesis.

A great improvement in the water level is achieved with the first assimilation cycles since the background Manning parameters and thus the background water levels initially differ significantly from the true parameter values and water levels. For the following cycles, as the background parameters are set equal to the analysis parameters, the sequential correction results in a convergence towards the optimal Manning coefficients leading to water levels that are coherent with the true water levels. The improvement is larger for stations that are located downstream of the river, possibly because the Man-

ning coefficient has a greater impact when the river width is larger. These results are similar for both orbits as illustrated in Fig. 12 that shows the spatially distributed relative error of water levels averaged over the period from June 2002 to December 2003 for the run with (a) no assimilation, (b) for a 3 day subcycle assimilation and (c) for a 1 day

subcycle assimilation. Without assimilation, the relative error over the river ranges between 0 and 1.2. With assimilation, more than 90% of the river pixels have a relative error smaller than 0.2 for both subcycles, and no pixel has a relative error higher than 0.5.

5 5.3 Impact of assimilation on river discharge

Table 3 presents discharge mean relative error computed with respect to the true discharge, first averaged over the entire river for the 2 year period and then at each of the 8 observing stations shown in Fig. 1. Figures 13 and 14 display the discharge relative error averaged over the river and at the 8 observing stations as a function
of time when (i) there is no assimilation (black curve), (ii) after a 1 day subcycle orbit SWOT-observation assimilation (green curve) and (iii) the 3 day subcycle orbit SWOT-observation assimilation (blue curve). First, these results show that the assimilation also contributes to an improvement of the river discharge over the whole basin and at the 8 locations, although this improvement is smaller than for water levels. Moreover, the impact of assimilation on discharge has a seasonal variability which was not present for water levels.

Discharge improvement, even if less significant than for water levels, can represent several hundreds of $m^3 s^{-1}$ globally and up to $3000 m^3 s^{-1}$ in Lokoja. Discharge obtained after assimilation is somewhat "noisy", for both orbits during the wet season.

This is likely due to a higher discharge sensitivity to Manning coefficient change during this period. Discharge is improved, in particular, at Lokoja, i.e. the location situated the most downstream of the river which is a promising result for coupled land-ocean applications since it shows that the RRM can provide a reasonable estimation of discharge at the river mouth. Similar to what was found for water levels, there is almost no discharge sensitivity to the considered orbit.

Figure 15 shows spatially distributed relative error of discharge averaged over the period June 2002–December 2003 for the run without assimilation (a), for a 1 day subcycle assimilation (b) and for a 3 day subcycle assimilation (c). The discharge relative

error is globally improved with better results over the inner delta for the 1 day subcycle orbit. Otherwise, there is no significant difference in results between the two orbits. Without assimilation, the relative error range over the river goes from 0 to 0.4. With assimilation, all pixels have a relative error smaller than 0.2, with 80% of them having ⁵ errors less than 0.1.

To better understand the relationship between the water levels and the discharge, the flooded fraction time series at 2 locations (KeMacina and Lokoja) is shown on Fig. 16. In KeMacina, there was no flooded fraction before the assimilation while there was about 15% to 20% for the "truth". At this location, DA leads to a water level increase that generates flooding for both orbits, in agreement with the true run. The amplitude of the flooded fraction simulated with the assimilation for a 3 day subcycle is close to that of the true run while the flooded fraction simulated with assimilation for a 1 day cycle is overestimated. This results because the water level and discharge results slightly overestimate the results from the true run for the 1 day orbit.

10

¹⁵ Another interesting case is observed in Lokoja, where the model simulates floodplains (25%) with no assimilation, which is not observed for the "truth". Here again, by reducing water levels, the assimilation considerably reduces flooded fraction for the 1 day subcycle orbit and even prevents it from occuring for the 3 day subcycle orbit. No floods are modeled at the other sites for the truth, the run with no assimilation

- or the runs with assimilation, so these sites are not shown in Fig. 16. These results are valuable since they show that the use of DA corrects the flood prediction for two major sites of the Niger basin. Indeed, Ke Macina is located just upstream to the entrance of the inner delta region, while Lokoja is the last in-situ station upstream of the river outlet. It should be noted that the discharge response to water level modification
- depends on whether or not there are floods. For example, at Ke Macina during the monsoon period, water level is increased via assimilation, which results in a better fit with the truth simulation and to a discharge decrease. This is coherent with the results of Pedinotti et al. (2012), in which the introduction of floodplains leads to a reduction of

the discharge. However, in regions without floodplains, a water level increase leads to a discharge increase (see Kandadji for example).

The frequency of events as a function of the flooded fraction value (ratio of flooded area over pixel area) are shown in Fig. 17 for the truth (a), without assimilation (b), ⁵ with assimilation for a 1 day subcycle (c) and with a 3 day subcycle (d). Only the pixels with a flooded fraction greater than 10% (0.1 on horizontal axis) are considered. It is shown that without assimilation, the model does not simulate flooded fractions above 0.5, which represents about 8% of the flood events for the truth simulation. Moreover, without assimilation, the model tends to overestimate the occurence of smaller events.

¹⁰ This is corrected by the assimilation, with a slight tendancy to over-estimate flood intensity for the assimilation with the 3 day subcycle orbit, while the 1 day subcycle orbits leads to an excessive occurence of flooded fractions contained in the [0.2–0.3] range. According to these results, DA allows a better simulation of the water storage variations and it leads to better estimate flood events occurence and intensity in the inner delta area.

5.4 Water storage variations

Ideally, for water resource management applications and for making reliable future water resource projections, global hydrologic models should be able to reasonably simulate water storage variations in regional to large scale continental reservoirs. It is then

- of interest to see if DA can improve the simulation of these water variations. Figure 18 shows the relative water storage variations in 4 continental reservoirs (river, floodplains, aquifer and soil) for the truth (red), without assimilation (black), with a 1 day subcycle (blue) and with a 3 day subcycle (green). For each reservoir, the 20 day running average water storage variations are divided by the averaged water storage over the period
- of assimilation. The maximum relative water storage variations ranges from 6% in the river reservoir to about 30% in the floodplain reservoir which is not negligible. In the 4 reservoirs, the simulations with assimilation better represent the amplitude and the phase of the water storage variations. From these results, the assimilation seems to be

useful for better representing anomalies in continental reservoirs, which are subject to many uncertainties due to the lack of data.

6 Discussion

Optimization of the Manning coefficient using a DA methodology leads to a significant
⁵ improvement of the water levels over the Niger river, and also at the 8 locations with gages. Indeed, the relative error of the water level is globally improved (a 30% reduction) and the amplitude of the water level is closer to the truth with assimilation than without assimilation. The relative error of the Manning coefficient is also reduced (40% reduction) and it globally converges towards an optimal value despite potential
¹⁰ problems related to equifinality. Discharge is also improved by the assimilation, but to a lesser extent than for the water levels (7%). Moreover, the proposed methodology results in a better prediction of flood event occurence and intensity in the inner delta and better simulates water storage anomaly maxima and minima in several reservoirs, especially the groundwater and the aquifer reservoirs, for which the temporal evolution of the aquifer reservoirs.

- tion is difficult to observe. This study is promising since, to our knowledge, no large scale assimilation applications exist for the optimization of spatially distributed hydrological parameters. It shows SWOT observations would be useful for the improvement of CHSs. This method could lead to a better representation of the water cycle in climate prediction applications, but could also be used for large scale water resource manage-
- ²⁰ ment applications. Finally, there is no clear out advantage difference between the two subcycle orbits used for this study, each one having better skill for certain situations.

It should be noted that, this study has some limitations and several asumptions should be noted. The assumption of white noise error for SWOT observations is probably too optimistic. Furthermore, no correlation of the measurement errors along the ²⁵ swath has been assumed. Estimating satellite observation error sources has been the subject of several studies at the French space agency (CNES) in recent years. Initially, a white noise was introduced within the SWOT water level along track altimetric

estimate in order to represent the error due to satellite observations (Biancamaria et al., 2011). Lion (2012) presents methods to simulate, in a more realistic manner, different sources of SWOT satellite observation errors. These errors are generally due to several factors such as satellite attitude, baseline error, phase unwrapping errors, etc....

- ⁵ These errors are not always Gaussian and do not always have a mean value of 0. A perspective for improvement of the assimilation methodology proposed in this study is to introduce these errors into the assimilation system in order to get a more realistic estimation of SWOT observation errors and of the error covariance matrix **R**. However, their introduction in the system is not obvious and could lead to a degradation of the
- ¹⁰ error estimates due to the aforementionned Gaussian issue. Indeed, the Gaussian error distribution along SWOT tracks does not ensure that the error of the observation vector, y^0 , is Gaussian. Yet, the Gaussian nature of the observation error is a strong asumption of the EKF and possible solutions to get around this limitation exist, such as the use of an ensemble Kalman filter or a particle filter.
- The hypothesis that the Manning coefficient uncertainties are the only source of model errors is obviously a rather simple assumption since other errors, such as those related to precipitation forcing uncertainties, river bankfull depth error or the relatively simple ISBA-TRIP physics, can also be the sources of significant modeling errors. Within the framework of a real-data experiment, accounting for various sources of
- errors via Manning control will lead to improved Manning values that should not be interpreted as physical values. Modeling asumptions also put a limitation on the DA performance in the context of real-data experiments. For example, it is assumed in the TRIP model that geomorphological parameters such as the Manning coefficient are constant in time which is a significant asumption, especially in a region with a strong
- seasonal climate variability, such as the Niger basin. Hopefully, SWOT observations will help to correct this problem, for example, using this method to build seasonal climatologies of key parameters. To exploit this possibility, a further OSSE study could be done, in which the "true" Manning coefficient varies seasonnally.

Additionally, this study was done within the context of OSSE, in which the truth was issued from a reference ISBA-TRIP simulation. This allowed an evaluation of the methodology, but its performance will need to be re-evaluated with real observations. Indeed, in the study presented here, the truth and the perturbation are based on the

- same physical parameterizations: this is not true when real data are used. Therefore, the assimilation should be applied using either real observations of water level, or water level issued from a different model, such as hydrodynamic model. In further studies, longer assimilation windows could be exploited but also require a bigger storage capacity which must be considered for the choice of the assimilation window size.
- Finally, this method must be applied to other ISBA-TRIP parameters and for other large-scale basins to evaluate its global application capability. Indeed, it is not guaranteed that a methodolgy, which works for a specific basin could be used for all other major basins (with different climates, geoology, etc.). Ongoing work is focused on applying the methodology herein to other basins. These proposed improvements aim at ensuring the assimilation methodology will be applicable when real SWOT data will be available.

Finally, it could be potentially interesting to perform the assimilation on an ensemble of perturbed runs in order to take into account several uncertainty scenarii. Thus, the estimation of the background modeling matrix could be done using an ensemble method (Evensen et al., 2004).

7 Conclusions

20

25

This study presents a simple method for assimilating SWOT virtual water level into a large-scale coupled land-surface hydrology model (TRIP-ISBA) in order to improve estimates of the required global hydrological model input parameters. Based on the sensitivity tests performed in a previous study from Pedinotti et al. (2012), it was decided to apply the assimilation method in order to correct the Manning coefficient. Indeed, this coefficient is a key parameter which impacts surface water dynamics and

thus water level and discharge. However, its estimation is difficult and it is generally derived from geomorphologic relationships in global scale models. It is still possible to "tune" model parameters in order to fit observations for some basins. Yet, at the global scale, this type of approach is limited by the lack of observed data. This study showed

- that SWOT satellite data offer an alternative to better calibrate large scale hydrologic models through assimilation. To accomplish this, an Observing System Simulation Experiment (OSSE) was performed, using virtual SWOT observations of water levels. SWOT virtual observations have been generated using a reference ISBA-TRIP run. Two orbits, with different subcycles but with the same 22 days repeat period, have been
- ¹⁰ considered to generate the observations (1 day and 3 day subcycles), each one providing a specific spatial and temporal coverage of the domain. Then, a perturbed run was created considering only modeling uncertainties due to errors on Manning coefficient. The Extended Kalman Filter (EKF) algorithm has then been applied every 2 days (the length of the assimilation window) to compute a corrected Manning coefficient (analy-
- sis). The analysis has then been considered as the new control vector for the following assimilation cycle. Using this method, the estimation of an optimal spatially distributed Manning coefficient was possible. This Manning coefficient globally converged for two orbital subcycles to the same average value, the convergence being faster for the 3 day subcycle orbit. The optimal distribution of the Manning coefficient was closer to the true
- distribution than the perturbed one, showing that, in this experiment, equifinality was not a limitation. This method gives a promising perspective for global scale applications, and it could be extended to other large basins. However, several relatively simple hypotheses have been made, and these should be addressed and refined in future studies. For example, in this study, only uncertainties related to the Manning coefficient
- were considered. Other sources of uncertainties should be assumed for the assimilation, such as rainfall errors and/or river bankfull depth. Moreover, other modeling errors such as those from the ISBA land surface parameterisation could be considered, such as that pertaining to runoff. It was also considered that observation and modeling errors

were not correlated in space and time which might not be realistic. The use of more realistic errors simulated by Lion (2012) will be considered in future studies.

These preliminary results show that the method leads to a global reduction of 40% of the Manning coefficient error over the river. This correction significantly improved the ⁵ water levels (the error has been reduced by 30% for the river) and, to a lesser extent, discharge (7% of reduction of the error which can be significant for the Niger river in

- terms of water resources considering that its mean annual discharge is $6000 \text{ m}^3 \text{ s}^{-1}$). Moreover, the biggest improvements were observed downstream of the river (Lokoja), which is a valuable result for climate applications which require estimation of the discharge at large rivers meant the applications which require estimation of the discharge at large rivers.
- ¹⁰ charge at large rivers mouths. Another perspective consists in the application of this method to other TRIP parameters, or several parameters at a time. Correction of ISBA parameters, such as those controlling sub-grid runoff for example, is also planned but must be considered carefully as the impact on the river is less direct. Before the satellite launch, the AirSWOT airborne campaign will provide SWOT-like datasets of water
- ¹⁵ level, which will enable studies using a more realistic SWOT DA application, instead of the Observing Simulation System experiment presented here. Even if this airborne campaign will not cover the Niger basin, it will potentially provide a better observation error model. Yet, using more complex observations and model errors might require a modification of the assimilation scheme to overcome extremely strigent EKF filter
- ²⁰ asumptions of Gaussian unbiased errors. Possible assimilation techniques to test are the/run Ensemble Kalman Filter or the particle filter.

References

- Alsdorf, D. E., Rodriguez, E., and Lettenmaier, D. P.: Measuring surface water from space, Rev. Geophys., 45, RG2002, doi:10.1029/2006RG000197, 2007.
- ²⁵ Andersen, I., Dione, O., Jarosewich-Holder, M., and Olivry, J.-C.: The Niger river basin: A vision for sustainable management, World Bank, Washington, DC, 2005.

- Andreadis, K. M., Clark, E. A., Lettenmaier, D. P., and Alsdorf, D. E.: Prospects for river discharge and depth estimation through assimilation of swath-altimetry into a raster-based hydrodynamics model, Geophys. Res. Lett., 34, L10403, doi:10.1029/2007GL029721, 2007.
 Arora, V. K. and Boer, G. J.: A variable velocity flow routing algorithm for GCMs, J. Geophys.
- ⁵ Res., 104, 30965–30979, doi:10.1029/1999JD900905, 1999.

10

20

- Baup, F., Mougin, E., de Rosnay, P., Timouk, F., and Chenerie, I.: Surface soil moisture estimation over the AMMA Sahelian site in Mali using ENVISAT/ASAR data, Remote Sens. Environ., 109, 473–481, doi:10.1016/j.rse.2007.01.015, WOS:000248293300008, 2007.
- Beven, K. and Kirkby, M.: A physically-based variable contributing area model of basin hydrology, Hydrol. Sci. Bull., 24, 43–69, 1979.
- Biancamaria, S., Durand, M., Andreadis, K., Bates, P., Boone, A., Mognard, N., Rodriguez, E., Alsdorf, D., Lettenmaier, D., and Clark, E.: Assimilation of virtual wide swath altimetry to improve Arctic river modeling, Remote Sens. Environ., 115, 373–381, doi:10.1016/j.rse.2010.09.008, 2011.
- Bircher, S., Skou, N., and Kerr, Y. H.: Validation of SMOS L1C and L2 products and important parameters of the retrieval algorithm in the Skjern river catchment, Western Denmark, IEEE T. Geosci. Remote, 51, 2969–2985, doi:10.1109/TGRS.2012.2215041, 2013.
 - Boone, A., Calvet, J.-C., and Noilhan, J.: Inclusion of a third soil layer in a land surface scheme using the force–restore method, J. Appl. Meteorol., 38, 1611–1630, doi:10.1175/1520-0450(1999)038<1611:IOATSL>2.0.CO;2, 1999.
 - Bouttier, F. and Courtier, P.: Data Assimilation Concepts and Methods, ECMWF training course notes, 59 pp., 1999.
 - Cogley, J. G.: The Albedo of water as a function of latitude, Mon. Weather Rev., 107, 775–781, doi:10.1175/1520-0493(1979)107<0775:TAOWAA>2.0.CO;2, 1979.
- Dai, T. and Labadie, J. W.: River basin network model for integrated water quantity/quality management, J. Water Res. PI.-ASCE, 127, 295–305, doi:10.1061/(ASCE)0733-9496(2001)127:5(295), 2001.
 - Decharme, B. and Douville, H.: Introduction of a sub-grid hydrology in the ISBA land surface model, Clim. Dynam., 26, 65–78, doi:10.1007/s00382-005-0059-7, 2006.
- ³⁰ Decharme, B., Douville, H., Boone, A., Habets, F., and Noilhan, J.: Impact of an exponential profile of saturated hydraulic conductivity within the ISBA LSM: simulations over the Rhône basin, J. Hydrometeorol., 7, 61–80, doi:10.1175/JHM469.1, 2006.

Decharme, B., Douville, H., Prigent, C., Papa, F., and Aires, F.: A new river flooding scheme for global climate applications: off-line evaluation over South America, J. Geophys. Res., 113, D11110, doi:10.1029/2007JD009376, 2008.

Decharme, B., Alkama, R., Douville, H., Becker, M., and Cazenave, A.: Global evaluation of

- the ISBA-TRIP continental hydrological system, Part II: Uncertainties in River routing simulation related to flow velocity and groundwater storage, J. Hydrometeorol., 11, 601–617, doi:10.1175/2010JHM1212.1, 2010.
 - Decharme, B., Alkama, R., Papa, F., Faroux, S., Douville, H., and Prigent, C.: Global off-line evaluation of the ISBA-TRIP flood model, Clim. Dynam., 38, 1389–1412, doi:10.1007/s00382-011-1054-9, 2011.
- Drusch, M., Scipal, K., de Rosnay, P., Balsamo, G., Andersson, E., Bougeault, and Viterbo, P.: Towards a Kalman Filter based soil moisture analysis system for the operational ECMWF Integrated Forecast System, Geophys. Res. Lett., 36, L10401, doi:10.1029/2009GL037716, 2009.

10

- ¹⁵ Durand, M., Andreadis, K., Alsdorf, D., Lettenmaier, D., Moller, D., and Wilson, M.: Estimation of bathymetric depth and slope from data assimilation of swath altimetry into a hydrodynamic model, Geophys. Res. Lett., 35, L20401, doi:10.1029/2008GL034150, 2003.
 - Evensen, G.: Sampling strategies and square root analysis schemes for the EnKF, Ocean Dynam., 54, 539–560, doi:10.1007/s10236-004-0099-2, 2004.
- Habets, F., Boone, A., Champeaux, J. L., Etchevers, P., Franchistéguy, L., Leblois, E., Ledoux, E., Le Moigne, P., Martin, E., Morel, S., Noilhan, J., Quintana Seguí, P., Rousset-Regimbeau, F., and Viennot, P.: The SAFRAN-ISBA-MODCOU hydrometeorological model applied over France, J. Geophys. Res., 113, D06113, doi:10.1029/2007JD008548, 2008.

Kerr, Y., Wigneron, J., Ferrazzoli, P., and Waldteufel, P.: Soil moisture and vegetation biomass

- retrievals using L band, dual polarised and multi angular radiometric data in preparation of the SMOS mission, in: IGARSS 2000, IEEE 2000 International, vol. 3, 1244–1246, IEEE, Honolulu, doi:10.1109/IGARSS.2000.858081, 2000.
 - Kerr, Y., Waldteufel, P., Wigneron, J.-P., Delwart, S., Cabot, F., Boutin, J., Escorihuela, M.-J., Font, J., Reul, N., Gruhier, C., Juglea, S., Drinkwater, M., Hahne, A., Martin-Neira, M., and
- ³⁰ Mecklenburg, S.: The SMOS mission: new tool for monitoring key elements of the global water cycle, Proc. IEEE, 98, 666–687, doi:10.1109/JPROC.2010.2043032, 2010.
 - Lion, C.: Simulation des données SWOT haute résolution et applications à l'étude de l'estuaire de l'Amazone, Ph.D. thesis, Univ. Paul Sabatier Toulouse III, 2012.

- Masson, V., Le Moigne, P., Martin, E., Faroux, S., Alias, A., Alkama, R., Belamari, S., Barbu, A., Boone, A., Bouyssel, F., Brousseau, P., Brun, E., Calvet, J.-C., Carrer, D., Decharme, B., Delire, C., Donier, S., Essaouini, K., Gibelin, A.-L., Giordani, H., Habets, F., Jidane, M., Kerdraon, G., Kourzeneva, E., Lafaysse, M., Lafont, S., Lebeaupin Brossier, C., Lemonsu, A.,
- Mahfouf, J.-F., Marguinaud, P., Mokhtari, M., Morin, S., Pigeon, G., Salgado, R., Seity, Y., Taillefer, F., Tanguy, G., Tulet, P., Vincendon, B., Vionnet, V., and Voldoire, A.: The SUR-FEXv7.2 land and ocean surface platform for coupled or offline simulation of earth surface variables and fluxes, Geosci. Model Dev., 6, 929–960, doi:10.5194/gmd-6-929-2013, 2013.

Michailovsky, C., Milzow, C., and Bauer-Gottwein, P.: Assimilation of radar altimetry to

- a routing model of the Brahmaputra River, Water Resour. Res., 49, 4807–4816, doi:10.1002/wrcr.20345, 2013.
 - Noilhan, J. and Planton, S.: A Simple Parameterization of Land Surface Processes for Meteorological Models, Mon. Weather Rev., 117, 536–549, doi:10.1175/1520-0493(1989)1172.0.CO;2, 1989.
- ¹⁵ Oki, T. and Sud, Y. C.: Design of Total Runoff Integrating Pathways (TRIP) a global river channel network, Earth Interact., 2, 1–37, doi:10.1175/1087-3562(1998)002<0001:DOTRIP>2.3.CO;2, 1998.
 - Papa, F., Prigent, C., Aires, F., Jimenez, C., Rossow, W. B., and Matthews, E.: Interannual variability of surface water extent at the global scale, 1993–2004, J. Geophys. Res., 115, D12111, doi:10.1029/2009JD012674, 2010.
 - Pedinotti, V.: The SWOT satellite mission: Contribution of large swath altimetry to the improvement of hydrological and hydrodynamical processes in large scale models., Ph.D. thesis, INP, Toulouse, 2013.

20

Pedinotti, V., Boone, A., Decharme, B., Crétaux, J. F., Mognard, N., Panthou, G., Papa, F., and

- Tanimoun, B. A.: Evaluation of the ISBA-TRIP continental hydrologic system over the Niger basin using in situ and satellite derived datasets, Hydrol. Earth Syst. Sci., 16, 1745–1773, doi:10.5194/hess-16-1745-2012, 2012.
 - Pereira-Cardenal, S. J., Riegels, N. D., Berry, P. A. M., Smith, R. G., Yakovlev, A., Siegfried, T. U., and Bauer-Gottwein, P.: Real-time remote sensing driven river basin mod-
- ³⁰ eling using radar altimetry, Hydrol. Earth Syst. Sci., 15, 241–254, doi:10.5194/hess-15-241-2011, 2011.

Rodriguez, E.: SWOT Science Requirements Document, NASA/JPL Document, 11, 2012.

Salamon, P. and Feyen, L.: Assessing parameter, precipitation, and predictive uncertainty in a distributed hydrological model using sequential data assimilation with the particle filter, J. Hydrol., 376, 428–442, doi:10.1016/j.jhydrol.2009.07.051, 2009.

Santos Da Silva, J. and Calmant, S.: Mapping of the extreme stage variations using ENVISAT altimetry in the Amazon Basin Rivers, Int. Water Technol. J., 2, 14–25, 2012.

Stisen, S.: Geostationary Remote Sensing in Modelling of Land Surface Hydrology, Ph.D. thesis, Department of Geography and Geology, Faculty of Science, University of Copenhagen, 2007.

5

Tapley, B. D., Bettadpur, S., Ries, J. C., Thompson, P. F., and Watkins, M. M.:

- GRACE measurements of mass variability in the Earth system, Science, 305, 503–505, doi:10.1126/science.1099192, 2004.
 - Yoon, Y., Durand, M., Merry, C., Clark, E., Andreadis, K., and Alsdorf, D.: Estimating river bathymetry from data assimilation of synthetic SWOT measurements, J. Hydrol., 464, 363– 375, doi:10.1016/j.jhydrol.2012.07.028, 2012.
- ¹⁵ Zagona, E. A., Fulp, T. J., Shane, R., Magee, T., and Goranflo, H. M.: Riverware: a generalized tool for complex reservoir system modeling, J. Am. Water Resour. As., 37, 913–929, doi:10.1111/j.1752-1688.2001.tb05522.x, 2001.

	HESSD 11, 4477–4530, 2014									
	Assimilation of SWOT data V. Pedinotti et al.									
	Title	Page								
	Abstract Conclusions	Introduction References								
	Tables	Figures								
]	 Back 	► Close								
]	Full Scree	en / Esc								
,	Interactive	Discussion ev								

Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper

Table 1. Principal variables, vectors and matrices used in the data assimilation of SWOT water levels. The assimilation window length is N days. The number p of observed water levels during the assimilation window changes for each cycle.

Symbol	Variable	Dimensions
y ⁰ _t	Observation vector, containing the SWOT WL observations during the <i>N</i> day assimilation window	<i>p</i> (different for each assimilation cycle)
$\boldsymbol{x}_t^{\mathrm{b}}$	Background vector, containing the corrupted Manning coefficient over the river mask	<i>n</i> = 110
\boldsymbol{x}_{t}^{a}	Analysis vector, containing the corrected values of the Manning coefficient over the river mask	<i>n</i> = 110
M _t	ISBA-TRIP (non linear)	
$H_t(x_t^{b})$	ISBA-TRIP simulated water levels, using x_t^{b} as an input parameter	p
R _t	Observation error covariance matrix (related to water levels)	р×р
B _t	Background error covariance matrix (related to the Manning coefficient)	n × n
A _t	Analysis error covariance matrix	n × n
H _t	Jacobian matrix of <i>H</i> (sensitivity of ISBA-TRIP water levels to the Manning coefficient)	п×р
K _t	Gain matrix	

Discussion Paper **HESSD** 11, 4477-4530, 2014 Assimilation of SWOT data V. Pedinotti et al. **Discussion** Paper Title Page Abstract Introduction Conclusions References **Tables Figures Discussion Paper** Back Close Full Screen / Esc **Discussion** Paper **Printer-friendly Version** Interactive Discussion

Discussion Pap	HES 11, 4477–4	HESSD 11, 4477–4530, 2014							
er	Assimil SWO	Assimilation of SWOT data							
Discuse	V. Pedin	V. Pedinotti et al.							
sion F	Title	Page							
aper	Abstract	Introduction							
	Conclusions	References							
Discu	Tables	Figures							
ssion	14	►I.							
Pap	•	•							
)er	Back	Close							
_	Full Scre	een / Esc							
Discussior	Printer-frier Interactive	ndly Version Discussion							
Paper	8	() BY							

Table 2. Water level relative error averaged over the river and at the location of the 8 gages along the river (each gage is defined by its number specified inside the orange rectangles in Fig. 1). The relative error is calculated as the ratio $((h_{\text{with/without assi}} - h_{\text{truth}})/h_{\text{truth}}$ where *h* is the water level (m).

Location n°	Riv Mean	1	2	3	4	5	6	7	8
No assi	0.45	0.35	0.17	0.36	0.55	0.16	0.69	0.68	1.1
3dsbc	0.12	0.09	0.25	0.11	0.17	0.12	0.12	0.1	0.09
1dsbc	0.12	0.19	0.1	0.11	0.12	0.13	0.07	0.12	0.18

Discussion Pape	HESSD 11, 4477–4530, 2014
er	Assimilation of SWOT data
Discussi	V. Pedinotti et al.
ion Pap	Title Page Abstract Introduction
er	Conclusions References
Discuss	Tables Figures
ion Pape	A F
-	Full Screen / Esc
Discussion I	Printer-friendly Version
Daper	BY BY

Table 3. Discharge relative error averaged over the river and at location of the 8 gages along the river (each gage is defined by its number specified inside the orange rectangles on Fig. 1). The relative error is calculated as the ratio $((q_{\text{with/without assi}} - q_{\text{truth}})/q_{\text{truth}}$ where q is the discharge $(\text{m}^3 \text{s}^{-1})$.

Location n°	Riv Mean	1	2	3	4	5	6	7	8
No assi	0.14	0.06	0.1	0.18	0.22	0.2	0.2	0.15	0.14
3dsbc	0.08	0.04	0.04	0.11	0.14	0.14	0.14	0.09	0.06
1dsbc	0.07	0.03	0.03	0.09	0.13	0.13	0.11	0.08	0.06

Fig. 2. The TRIP model.

Fig. 4. Distribution of the "true" Manning coefficient over the river. This distribution of Manning coefficients was used as an imput parameter to run the reference ISBA-TRIP modelling.

Fig. 6. As in Fig. 5, except for a 22 day repeat, 970 km altitude, 3 day subcycle orbit average.

Fig. 7. Schematic of the assimilation scheme used in this study.

Fig. 9. Manning coefficient vs. assimilation cycle at 8 locations (Fig. 1) for the 3 day subcycle (blue) and 1 day subcycle (green) orbits. The value of the true coefficient is in red.

Fig. 10. Water level relative error averaged over the river vs. time with no assimilation (black), with a 1 day subcycle (green) and a 3 day subcycle (blue) orbits SWOT assimilation. The relative error is calculated as the ratio: $(h_{\text{with/without assi}} - h_{\text{truth}})/h_{\text{truth}}$, where *h* is the water level (m).

Fig. 11. Time evolution of water levels at the 8 locations shown on Fig. 1 for the "truth" (red curves), with no assimilation (black curves) and with assimilation of SWOT 1 day subcycle (green) and 3 day subcycle (blue) orbit observations.

Fig. 12. Relative error of water levels averaged over the period of assimilation.

Fig. 13. Discharge relative error averaged over the river vs. time with no assimilation (black), with a 1 day subcycle (orange) and a 3 day subcycle (blue) orbits SWOT assimilation. The relative error is calculated as the ratio: $((q_{\text{with/without assi}} - q_{\text{truth}})/q_{\text{truth}})$, where *q* is the discharge (m³ s⁻¹)).

Fig. 15. Relative error of dicharge averaged over the period of assimilation.

Fig. 16. Flooded fraction vs. time at Ke Macina and Lokoja, for the truth (red), with no assimilation (black), with assimilation for 3dsbc (blue) and 1dsbc (green).

Fig. 17. Frequency of flood events over the delta classified by intensity (flooded fraction). Only the pixels with a flooded fraction higher than 10% are considered for the calculation.

Fig. 18. Relative water storage variations in the river, the flood, the aquifer and the soil reservoirs for the truth (red), with no assimilation (black), with assimilation for the 1 day orbit subcycle (green) and for the 3 day subcycle (blue). For each reservoir, the 20 day running average water variations are divided by the averaged water storage over the period of assimilation (from June 2002 to December 2003).

