

Climate change and non-stationary flood risk for the Upper Truckee River Basin

L. E. Condon^{1,2}, S. Gangopadhyay¹ and T. Pruitt¹

[1]{Bureau of Reclamation Technical Service Center, Denver, Colorado}

[2]{Hydrologic Science and Engineering Program and Department of Geology and
Geological Engineering, Colorado School of Mines, Golden, Colorado}

Correspondence to: L. E. Condon (lcondon@mymail.mines.edu)

Abstract

Future flood frequency for the Upper Truckee River Basin (UTRB) is assessed using non-stationary extreme value models and design life risk methodology. Historical floods are simulated at two UTRB gauge locations, Farad and Reno using the Variable Infiltration Capacity (VIC) model and non-stationary Generalized Extreme Value (GEV) models. The non-stationary GEV models are fit to the cool season (November-April) monthly maximum flows using historical monthly precipitation totals and average temperature. Future cool season flood distributions are subsequently calculated using downscaled projections of precipitation and temperature from the Coupled Model Intercomparison Project Phase-5 (CMIP-5) archive. The resulting exceedance probabilities are combined to calculate the probability of a flood of a given magnitude occurring over a specific time period (referred to as flood risk) using recent developments in design life risk methodologies. This paper provides the first end-to-end analysis using non-stationary GEV methods coupled with contemporary downscaled climate projections to demonstrate the evolution of flood risk profile over typical design life periods of existing infrastructure that is vulnerable to flooding (e.g. dams, levees, bridges, and sewers). Results show that flood risk increases significantly over the analysis period (from 1950 through 2099). This highlights the potential to underestimate flood risk using traditional methodologies that don't account for time varying risk. Although model parameters, for the non-stationary method are sensitive to small changes in input parameters, analysis shows that the changes in risk over time are robust. Overall, flood risk at both locations (Farad and Reno) is projected to increase 10-20% between the historical period 1950-1999 and the future period 2000-2050 and 30-50% between the same historical period and 2050-2099.

1 Introduction

“Stationarity is Dead” [Milly et al., 2008], yet the standard practice for flood frequency analysis is predicated on this very assumption. This discrepancy has not gone unnoticed within the scientific community and there is a growing body of research investigating, (1) trends in observed floods [e.g. Franks, 2002; Vogel et al., 2011], (2) ways to incorporate non-stationarity into frequency distributions [e.g. Katz and Neveau, 2002; Raff et al., 2005] and (3) methodologies to interpret risk and approach design within a non-stationary framework [e.g. Mailhot and Duchesne, 2010; Rootzen and Katz, 2013; Salas and Obeysekara, 2014]. Both the frequency and intensity of extreme events are particularly susceptible to change because small shifts in the center of a distribution can potentially have much larger impacts on the tails [Meehl et al., 2000]. Regardless of climate change, naturally occurring long-term climate oscillations, such as ENSO, have been linked to low frequency variability in flood frequency [e.g. Cayan et al., 1999; Jain and Lall, 2001]. Anthropogenic climate change has the potential to amplify natural climatic variability throughout the interconnected climate and hydrologic systems.

Already trends in many hydrologic variables have been observed across the Western United states (as well as around the world). For example, clear increases in temperature have been measured across the west [e.g. Cayan et al., 2001; Dettinger and Cayan, 1995]. Precipitation trends are more variable. Regonda et al. [2005] found increased total winter precipitation (rain and snow) from 1950 to 1999 in many sites across the western United States, although springtime snow water equivalent (SWE) was shown to decline over the same period. Similarly, Mote et al. [2005] analyzed snowpack trends in western North America, and reported widespread declines in springtime SWE over the period 1925–2000, especially since the middle of the 20th century. They attribute this decline predominantly to climatic factors such as El Niño–Southern Oscillation (ENSO), Pacific Decadal Oscillation (PDO), and positive trends in regional temperature. Easterling et al. [2000] summarized previous studies on precipitation trends. They note that trends vary from region to region, but in general, increases in precipitation have occurred disproportionately in the extremes. Several subsequent studies have observed increasing trends in extreme precipitation events, although the changes are relatively small [Gutowski et al., 2008; Kunkel, 2003; Madsen and Figdor, 2007].

1 Research has also demonstrated increasing trends in flood frequency in some regions. Walter
2 and Vogel [2010] and Vogel et al. [2011] observed increasing flood magnitudes across the
3 United States using stream gauge records, and Franks [2002] showed statistically significant
4 increases in flood frequency since the 1940s. Still, non-stationary flood behaviour has been
5 historically difficult to quantify and there has been some debate on the significance of flood
6 frequency trends. For example, Hirsch [2011] noted both increasing and decreasing trends in
7 annual flood magnitudes in different regions of the US. Also, Douglas et al. [2000] found that
8 if one takes into account spatial correlation, many previous findings of flood trends are not
9 statistically significant. Difficulty in diagnosing flood trends is not unique to the Western US;
10 a literature review of historical flood studies across Europe also found spatial variability in
11 flood trends [Hall et al., 2014].

12 Even when significant trends are found, the complexity of flooding mechanisms that depend
13 on many variables and can vary regionally and seasonally makes it difficult to attribute trends
14 to specific causes. Illustrating the importance of seasonality, Small et al. [2006] showed that if
15 a high precipitation event occurs in the fall, as opposed to the spring, it will contribute to
16 baseflow rather than inducing flooding. Also, urbanization can drastically increase the
17 impervious area of a basin, thus amplifying floods by decreasing infiltration and speeding
18 runoff. The largest flood magnitude increases observed by both Walter and Vogel [2010] and
19 Vogel et al. [2011] were in basins with urban development. The influence of development
20 trends on flood behavior can be difficult to separate from other variables. For example,
21 Villarini et al. [2009] could not conclusively tie reduced stationarity (i.e. changes in mean
22 and/or variance) in peak discharge records to climate change because of variability in the
23 other factors that influence runoff.

24 Merz et al. [2012] note that attributing changes in flood hazard is complicated by the complex
25 array of drivers that can include; land cover change and infrastructure development as well as
26 natural climate variability and change. Here we set aside the impacts of development and
27 management practices and focus on the role of climate change. However, even with this
28 simplification, future extremes can still be influenced by a number of interrelated variables
29 such as changes in temperature, precipitation efficiency, and vertical wind velocity [Mullet et
30 al., 2011; O'Gorman and Schneider, 2009]. Analyzing global circulation model (GCM)
31 outputs Pierce et al. [2012] found total changes in precipitation to be small relative to the
32 existing variability but noted larger seasonal changes in storm intensity and frequency.

1 Despite uncertainty, many studies agree that warming will increase the potential for intense
2 rainfall [Allan, 2011; Gutowski et al., 2008; Pall et al., 2011; Sun et al., 2007]. Furthermore,
3 Min et al. [2011] found that some GCM simulations may underestimate extreme precipitation
4 events in the northern hemisphere. Indicating that projections of extreme precipitation based
5 on GCM outputs may be conservative.

6 Studies have also predicted increases in flood frequency and magnitude with a warmer
7 climate especially in snowmelt dominated basins [e.g. Das et al., 2011]. As with historical
8 flooding trends, translating forecasted climate variables to flood frequency is a complex
9 process and several methodologies have been used. Downscaled GCM climate forcings can
10 be used to drive hydrologic models and simulate future floods directly [e.g. Das et al., 2011;
11 Vogel et al., 2011; Raff et al., 2009]. With this approach traditional stationary flood
12 frequency distributions can be fit to the simulated floods to calculate return periods of
13 interest [e.g. Raff et al., 2009; Vogel et al., 2011]. This allows for return periods and flood
14 magnitudes that change over time, as with the flood magnification and recurrence reduction
15 factors calculated by Walter and Vogel [2010] and Vogel et al. [2011]. However, these
16 approaches still assume flood mechanisms are stationary over the time period that the
17 distribution is fit to.

18 This limitation can be overcome using non-stationary generalized extreme value (GEV)
19 distributions where the model parameters like mean (i.e. location) and spread (i.e. scale) are
20 allowed to vary as a function of time [e.g. Gilroy and McCuen, 2012] or with relevant
21 covariates [e.g. Griffis and Stedinger, 2007; Richard W Katz et al., 2002; Towler et al., 2010].
22 This approach has been gaining popularity for flood frequency estimation. Using this
23 technique it is not necessary to simulate future floods directly by forcing a hydrologic model
24 with projected hydroclimate fields (e.g. precipitation and temperature). The parameters of the
25 GEV model, like mean and spread change with time (i.e. non-stationary) based on a linear
26 combination of covariates like precipitation and temperature. Historical relationships between
27 extreme events and hydroclimate fields are used to identify the weighting of covariates. These
28 weights are then used to estimate parameters for future time periods using precipitation and
29 temperature outputs from hydroclimate projections. For example, Gilroy and McCuen [2012]
30 used non-stationary GEV models of flood frequency that incorporated a linear trend in the
31 location parameter. Similarly, Griffis and Stedinger [2007] and Towler et al. [2010] used
32 climate variables as covariates for the distribution parameters.

1 While, non-stationary flood forecasting methods provide flexibility to analyze flood
2 variability, they are also incongruent with many of the traditional metrics used in water
3 resources planning. Historically, most infrastructure that is vulnerable to flooding (e.g. dams,
4 levees, sewers and bridges) has been designed to withstand flooding of specified return period
5 (e.g. the 100 year flood). However, these calculations rely on a flood distribution which is
6 assumed to remain stationary with time, and hence the return period design metric is also
7 assumed to be stationary. When non-stationary methods are used, the underlying flood
8 distributions, and associated return periods, vary with time. Thus, under a non-stationary
9 climate, the notion of static return period flood event (e.g., 100-year flood, 200-year flood,
10 etc.) is no longer a valid concept.

11 To address this issue, Rootzén and Katz [2013] introduced the concept of design life level to
12 calculate the risk of a given flood magnitude occurring over a specified time period. Salas and
13 Obeysekera [2014] further demonstrated the relevance of this technique to hydrologic
14 community using flood frequency examples. However, this methodology has yet to receive
15 widespread attention within the hydrologic community. Here, we present a non-stationary
16 flood frequency assessment for the Upper Truckee River Basin (UTRB) using contemporary
17 downscaled climate projections and the non-stationary design life level technique introduced
18 by Rootzén and Katz [2013] to quantify flood risk (Note that following the convention of
19 Rootzén and Katz [2013] we use the term flood risk to refer to the probability of an extreme
20 event occurring and not as a quantification of expected losses). While the methodology used
21 for this analysis is previously established, this paper provides the first end-to-end
22 demonstration of non-stationary GEV analysis coupled with contemporary downscaled
23 climate projections (specifically, downscaled climate projections from the Coupled Model
24 Intercomparison Project Phase-5 (CMIP-5)), to quantify how the flood risk profiles may
25 evolve in the Truckee river basin over the next century. The intent of this work is 1) to
26 investigate potential flood risk changes over time in the Truckee basin and 2) to demonstrate
27 the applicability of non-stationary techniques in a regional flood analysis to make these tools
28 more accessible to the hydrologic community.

29 The paper is organized as follows. Section 2 provides background on the study area along
30 with data sets and models used. The methodologies of using non-stationary spatial GEV
31 analysis in conjunction with climate projections and time evolving risk assessment are

described in section 3. Results and discussions of findings are given in section 4. Summary and conclusions from the analysis are presented in section 5.

2 Background

This section provides background on the study area (2.1), streamflow data and simulations (2.2) and climate data and models (2.3).

2.1 Upper Truckee River Basin

The Truckee River originates in northern Sierra Nevada Mountains in California (above Lake Tahoe) and flows northeast to Nevada where it ends in the Pyramid Lake (Figure 1). The total basin area is roughly 7,900 square kilometres, however the area upstream of Reno (2,763 square kilometres) provides the majority of the basin's precipitation through snowpack. The focus of this analysis is on the Farad and Reno gauge locations shown in Figure 1, henceforth referred to as Farad and Reno. The Farad gauge is located roughly 1.5 kilometers downstream of the Farad hydropower plant and provides a cumulative measure of all of the upper basin tributaries [Stokes, 2002]. Most of the available water supply is generated upstream of the Farad Gauge [USACE, 2013a]. The Reno gauge is located downstream of Farad in the heart of Reno and is a good reference point for analyzing urban flooding. The intervening area between the Farad and Reno gauges is small, roughly 350 square kilometers and there are only two small tributaries that enter the main stem between Farad (Reno Dog Creek and Hunter Creek).

Flooding in the upper Truckee generally takes one of three forms. Some of the most severe floods have resulted from heavy rain events covering most of the basin and lasting one to six days. These storms generally occur from November to April and may be linked to Atmospheric Rivers [Ralph and Dettinger, 2012]. Snowmelt floods are also common from April to July. Although, snowmelt floods transmit large volumes of water for longer durations, they generally don't cause damage because they are well predicted and can be regulated with upstream reservoirs. Finally, in late summer (July – August) local cloudbursts can generate high intensity precipitation over small areas. These storms can cause local damage to tributaries but generally don't have a large impact on the main stem of the Truckee.

1 In the twentieth century, nine major floods have been recorded on the Truckee River,
2 all of which occurred from November to April [USACE, 2013b]. The flood of record
3 occurred in January of 1997 and was caused by warm rain falling on a large snowpack
4 (~180% of normal) and melting nearly all of the snowpack below 7,000 feet [USACE,
5 2013b]. The floods of 1950, 1955 and 1963 were some of the most damaging due to the
6 development of Reno along the river during this time period [USACE, 2013b]. Subsequent
7 flood damages have been, at least partially, mitigated by the implementation of flood
8 infrastructure starting in the 1960s.

9 **2.2. Streamflow data and simulations**

10 Streamflow has been measured at both the Farad and Reno USGS gauges. However,
11 gauge flows are not readily applicable to flood frequency analysis due to the presence and
12 development of water supply and flood control structures upstream. For example, upstream
13 of Reno there are four dams with flood control capabilities (i.e. Martis Creek Dam, Prosser
14 Creek Dam, Stampede Dam and Boca Dam) in addition to Tahoe, Donner and Independence
15 Lakes which provide incidental flood regulation. Unregulated flow estimates were developed
16 by the US Army Corps of Engineers (USACE) but are only available for historical flood
17 periods [USACE, 2013b]. Therefore, we simulate unregulated flows from 1950 to 1999 using
18 the Variable Infiltration Capacity (VIC) model and validate results using the available
19 unregulated flow estimates.

20 A brief summary of the VIC model is provided here, and for additional technical
21 specifications the reader is referred to Liang et al. [1994], Liang et al. [1996] and Nijssen et
22 al. [1997]. VIC is a gridded hydrologic model designed to simulate macro scale (spatial
23 resolution in greater than 1mile) water balances using parameterized sub-grid infiltration and
24 vegetation processes. In the VIC model, surface water infiltrates to the subsurface based on
25 conductivity, and soil moisture is distributed vertically through three model layers extending
26 up to about 2 meters below the land surface. At the surface, potential evapotranspiration
27 (PET) is simulated using the Penman Monteith PET model [Maidment et al., 1993]. Surface
28 flows are determined in a two-step process. First, the water balance for each grid cell is
29 calculated independently to determine surface runoff and baseflow, and subsequently runoff
30 from each cell is routed to river channels and outlets using a predefined routing network. Here
31 we drive VIC with daily weather forcings including precipitation, maximum and minimum
32 temperature and wind speed. Additional climate variables such as short and long wave

radiation, relative humidity and vapor pressure are calculated within the model. The VIC model is well documented and has already been used in a number of hydrologic and climate change studies [e.g. Christensen and Lettenmaier, 2007; Christensen et al., 2004; Gangopadhyay et al., 2011; Maurer et al., 2007; Payne et al., 2004; Reclamation, 2011; Van Rheeën et al., 2004]. Recently VIC has also been applied for real time flood estimation [Wu et al., in press].

The VIC model used for this analysis was developed and calibrated as part of the Bureau of Reclamation's (Reclamation) West Wide Climate Risk Assessment (WWCRA). The WWCRA VIC model encompasses the western US. Streamflows were evaluated at 152 locations primarily from the USGS Hydroclimatic Data Network [Slack et al., 1993] and 43 additional locations of importance to Reclamations water management activities. Among the evaluated locations are several in the Truckee basin including the Truckee River at Farad. For details on model calibration and development we refer the reader to Reclamation [2011] and Gangopadhyay et al. [2011]. While we do not discuss model calibration further here, in the subsequent sections we provide additional model verification for flood simulation in the UTRB.

2.3 Climate data and models

As noted in the previous section, the VIC model requires daily climate inputs to drive water balance simulations. We use the national $1/8^\circ$ (roughly 7 miles) gridded dataset from Maurer et al. [2002] for historical (i.e. 1950-1999) climate observations. Additionally, monthly total precipitation and average temperature were aggregated for the upstream area of each gauge for every month of the flood season (i.e. November through April). These values are used as covariates for fitting non-stationary GEV models as discussed in Section 3.

Future gridded precipitation and temperature values from 2000 to 2099 were generated from Global Circulation Model (GCM) outputs. We analyzed 234 projections generated by 37 different climate models from the CMIP-5 (Coupled Model Intercomparison Project Phase 5) archive [Taylor et al., 2012]. Projections span four Representative Concentration Pathways (RCPs) for greenhouse gas emissions. Each GCM projection includes monthly gridded precipitation and temperature from 1950 to 2099 at a coarse grid resolution ranging between ~65-250 kilometers.

1 Reclamation in collaboration with other federal and non-federal partners has developed a
2 monthly archive of downscaled CMIP-5 projections at the finer 1/8th degree resolution using
3 the two-step BCSD (Bias Correction and Spatial Disaggregation) algorithm described in
4 Wood et al. [2004]. For this analysis we extended the existing hydrology archive to cover the
5 UTRB domain for all 234 BCSD CMIP-5 climate projections following the steps detailed
6 below. A subset of the CMIP-5 hydrology projections is publically accessible through the
7 "Downscaled CMIP3 and CMIP5 Climate and Hydrology Projections" archive at [http://gdo-](http://gdo-dcp.ucllnl.org/downscaled_cmip_projections/)
8 [dcp.ucllnl.org/downscaled_cmip_projections/](http://gdo-dcp.ucllnl.org/downscaled_cmip_projections/). Additional documentation on the archive and
9 the methodology is provided in Reclamation [2014].

10 The downscaled climate variables include monthly total precipitation, monthly maximum and
11 minimum temperatures and monthly average temperature. Before applying the BCSD
12 algorithm all the 234 climate projections were first gridded from their respective native GCM
13 scale to a common grid of 1° latitude by 1° longitude. Similarly, the observed 1/8° degree
14 gridded dataset [Maurer et al., 2002] was aggregated to the coarser 1° latitude by 1° longitude
15 grid. Next, for a given climate variable, GCM, and location (1° latitude by 1° longitude grid
16 cell), the bias correction (BC) step uses quantile mapping between monthly CDFs
17 (Cumulative Distribution Functions) of historical simulated and historical observed values to
18 identify biases over a common climatological period – in this case, 1950-1999. The projected
19 future climate variables from the same GCM at the same location are then bias corrected
20 using the identified bias. The result of bias-correction is an adjusted GCM dataset (20th
21 century and 21st century, linked together) that is statistically consistent with the observed data
22 during the bias-correction overlap period (i.e., 1950-1999 in this application). Note that the
23 BC step happens at the coarse 1° latitude by 1° longitude grid. Next, adjustment factors that
24 are multiplicative (ratio of bias-corrected GCM to observed) for precipitation and an offset
25 (bias-corrected GCM minus observed) for temperature are calculated for each of the 1°
26 latitude by 1° longitude grid cell [Reclamation, 2013]. These adjustments are then spatially
27 disaggregated (SD) to a 1/8° latitude by 1/8° longitude grid. Finally, the adjustments are
28 applied (multiplicative for precipitation; additive for temperature) to the finer resolution, 1/8°
29 degree gridded observed precipitation and temperature fields [Maurer et al., 2002] to derive
30 the 1/8° degree gridded BCSD climate projections.

3 Methodology

This section describes the methodology used for flood frequency analysis in the UTRB. Discussion is divided into two sections. First, we describe the process of extreme value modeling using non-stationary GEV distributions (Section 3.1). Second, the methodology for design life level risk assessment is detailed (Section 3.2)

3.1 Extreme value modeling

Extreme values analysis (EVA) deals with the examination of the tail (i.e. extreme) values of a distribution (as opposed to standard approaches which are generally more concerned with the average system behaviour). EVA methods are standard practice for flood frequency analysis because they are designed to capture the behaviour of low frequency high impact events. Furthermore, in climate change studies Katz [2010] points out that traditional approaches are not sufficient and extreme value statistics are needed. For this analysis, we use the Generalized Extreme Value (GEV), which is commonly applied to flood frequency analysis to model block maxima from streamflow time series [e.g. Katz et al., 2002; Towler et al., 2010]. The cumulative distribution function (CDF) for the GEV is as follows:

$$F(z; \theta) = \exp \left\{ - \left[1 + \xi \left(\frac{z - \mu}{\sigma} \right)^{-\frac{1}{\xi}} \right] \right\} \quad (1)$$

Where z is the streamflow maxima value of interest and θ is the parameter set (μ, σ, ξ) used to specify the distribution such that the center is given by the location (μ) , the spread by the scale (σ) and the behavior of the upper tail by the shape (ξ) . Based on the shape parameter, the GEV can take one of three forms: Gumbel, or light tailed, when ξ is zero; Fréchet, or heavy tailed, if ξ is positive; and Weibull, or bounded, when ξ is negative. Following the methodology of Towler et al. [2010], GEV parameters (μ, σ, ξ) are fitted using the Maximum Likelihood Estimation (MLE) technique.

In traditional stationary flood frequency analysis, it is assumed that observations are independent and identically distributed (IID), and therefore model parameters (μ, σ, ξ) are derived from the observed flood record and are assumed to remain constant across the period of record and into the future. Here, we introduce non-stationarity into the distribution by allowing location and scale parameters to change with relevant covariates. Such that:

$$\mu(t) = \beta_{0,\mu} + \beta_{1,\mu}x_1 + \dots + \beta_{n,\mu}x_n \quad (2)$$

$$\sigma(t) = \beta_{0,\sigma} + \beta_{1,\sigma}x_1 + \dots + \beta_{n,\sigma}x_n \quad (3)$$

Where the β variables represent the coefficients, and the x variables are the covariates. In keeping with previous studies the shape parameter, which is the most difficult to estimate, is assumed constant [e.g. Obeysekera and Salas, 2014; Salas and Obeysekera, 2013; Towler et al., 2010].

Some previous studies [e.g. Salas and Obeysekera, 2013; Stedinger and Griffis, 2011] developed non-stationary location and scale parameters that are explicitly dependent on time. This approach requires first, the derivation of temporal flooding trends and second, the projection of this trend into the future. Here we derive location and scale parameters based on time varying meteorological variables (i.e. temperature and precipitation). With the approach used here, temporal trends in flooding are introduced as a function of temporal variability in precipitation and temperature but no explicit trend is specified apriori.

To determine the optimal set of covariates for a non-stationary model, additional statistical methods must be employed. The Akaike Information Criterion [AIC; Akaike, 1974], given in Equation 4, weighs the goodness of fit for a model with the level of complexity.

$$AIC = -2(\ln l) + 2K \quad (4)$$

Here $\ln l$ is the negative log likelihood estimated for a model fitted with K parameters. In this formulation, higher ranked models have lower AIC scores. For this analysis the best model is selected using pairwise comparisons of NLLH scores following the methods of Salas and Obeysekera [2014] and others. Models are compared using the deviance statistic (D) which is equal to twice the difference in NLLH scores. Deviance statistics are then tested for significance based on a chi-squared distribution with the degrees of freedom set equal to the difference in the number of parameters (K) between models. P-values less than 0.05 indicate a statistically significant (alpha of 0.05) improvement in model performance.

Following the methodology described above, GEV distributions are fit to time series of maximum monthly historical (1950-1999) one day simulated stream flows (detailed in Section 2) for the cool season. Although, there are some unregulated historical flow

estimates, the available dataset only covers six storms. Therefore, to be consistent we fit our model only to the simulated flows. The dataset includes maximum daily streamflows for each month in the cool season defined by the block of months November through April, as opposed to the more traditional single value per year. This technique was also used by Towler et al. [2010] who noted that expanding the dataset helps avoid the problems associated with using maximum likelihood estimate on small datasets. However, as noted by Towler et al. [2010], when multiple values are used per year the calculated probabilities must be adjusted appropriately to derive annual values. Floods during the cool season generally last between one and four days. Here we focus on the one day flood peak, as opposed to multi-day flood volumes, because this is a representative metric for flood damage. Additionally, using the one day flood maximum focuses the analysis on flood magnitude rather than duration.

Two covariates were considered, monthly total precipitation (P) and mean temperature (T) averaged over the upstream area for each gauge. As discussed in Section 2, precipitation is a relevant covariate because many of the floods in this season are rain on snow events or extreme rainfall events. Similarly, temperature drives snowmelt and is an important contributor to UTRB flood events (e.g., January 1997 event). Both stationary and non-stationary GEV models were evaluated using the extRemes package [Gilleland and Katz, 2011] in the ‘R’ statistical computing environment.

3.2 Time varying risk assessment

Traditional flood planning relies on the concept of return periods, which are usually calculated as the inverse of annual exceedance probability for a given flood magnitude, assuming a stationary distribution. For example, the log-Pearson Type III (LP3) distribution described by the Interagency Advisory Committee on Water Data Bulletin 17B [IACWD, 1982]. However, when non-stationary models are used, the distribution parameters, and hence the exceedance probabilities vary with time. Table 1 compares various flood probability calculations between stationary and non-stationary approaches [Salas and Obeysekera, 2014]. As shown here, when the flood distribution is stationary, the return period for a given flood magnitude is constant and relies only on the exceedance probability (4a). However, if distribution parameters are non-stationary then the return period will vary based on the period of interest (4b). This concept is easily extended to flood risk (here defined as the probability of a flood of a given magnitude occurring, not expected losses). In traditional analyses, the risk of a flood occurring in a given period depends only on the length

of the period (5a), while in a non-stationary analysis risk depends on both the length of time considered and the time period itself (5b). This is the concept of design life level proposed by Rootzén and Katz [2013]. Here, we adopt the design life level risk framework given in (5b) and calculate the risk of flood for a range of future periods and design life lengths.

4 Results and Discussion

Results are grouped into three sections. First we present the development of the non-stationary GEV models (4.1). Next the models are verified by comparing simulated results to observations (4.2). Finally we present future projections of flood frequency analysis (4.3).

4.1 Extreme value model development

A suite of models were fit to the logarithms of block (cool season, November-April) maxima flows (simulated by the calibrated VIC model) with different non-stationary parameter combinations. The model structures tested include stationary, non-stationary location, non-stationary scale and non-stationary location and scale. For all model structures model fit was tested using one or both covariates (i.e. precipitation (in) and temperature (F)). Models were also tested using the block maxima flows directly; however, performance was improved considerably with the logarithmic transformation. Validation of the VIC simulated flows as well as the GEV models are presented in the following section.

Table 2 summarizes negative log-likelihood (NLLH) and Akaike Information Criterion (AIC) scores for each model configuration. The deviance statistic (D) for pairwise comparisons of NLLH scores and the p-values calculated for each D based on a chi – squared distribution are also provided (Note that the bottom rows provide the number of parameters in each model and the model number that was used for the pairwise comparisons). As shown here the models with non-stationary location and scale relying on both precipitation and temperature as covariates have the best (i.e. lowest) NLLH scores for both stations, and are a statistically significant improvement over the other models listed in Table 2. Figure 2 plots, stationary and non-stationary location and scale models with histograms of observed flow for both gauges. Qualitatively, the stationary model fits well with the center of the distribution but overestimates the tails. The non-stationary models overestimate the median values but are a closer fit to the extreme values.

The coefficients for equations 2 and 3 for the selected models are provided in Table 3. Using the coefficients determined above, the location and scale parameters are calculated for every climate projection (i.e. 234) and flood season month (i.e. November to April 1950 to 2099) based on the downscaled precipitation and temperature values detailed in Section 2 (Note that the scale parameter remains fixed). Thus, for every future month there is a separate GEV curve for each of the 234 climate projections.

4.2 Hydrologic and GEV model validation

Because we utilize modeled VIC flows for flood analysis there are two considerations for model validation. First, we compare VIC simulated one day flood events to the observed unregulated flow estimates (i.e. validating that our calibrated VIC model is accurately simulating flood flows). Second, we compare the GEV modeled floods to the VIC simulated flows and the observed flow estimates (i.e. validating that the GEV models we fit to the simulated data match both the observed flows and the VIC simulated flows).

Although, unregulated flows are not available for the entire period of record, one-day maximum unregulated flow estimates are available at Reno for six historical floods [USACE, 2013b]. Figure 3 plots the observed flow (blue triangle) with the one-day VIC flow that was simulated using historical observed forcings from Maurer et al. [2002] (red triangle), and a boxplot of the non-stationary GEV distribution for the same month generated using the same monthly historical precipitation and temperature [i.e. Maurer et al., 2002]. Comparing first the one day maximum VIC simulated flow with the observed flow the maximum percent difference between the natural logarithm of simulated and observed flows is 12%. There does appear to be a slight positive bias in the VIC simulations (i.e. VIC simulated flows are greater than observed flood flows). Still, the simulated flood values (red circles) generally fall within the interquartile range of the GEV distribution, except in the case of the February 2, 1963 flood and the January 2, 1997 flood.

In these instances the VIC simulation matches very closely (percent difference in the natural logarithm of flows are 0.5% and 1.2% respectively) with the observed flow, however, the GEV model underestimates the events. This discrepancy is caused by the flood timing. In both cases the flood occurs at the very beginning of the month. In the GEV framework the precipitation and temperature are used as covariates for the flow of the same month. However, for these storms flooding is linked to precipitation and temperature in the month of flooding

1 and the preceding month. Therefore, the GEV model simulates the flood in the preceding
2 month and/or underestimates the flood magnitude if the precipitation is split between two
3 months. While this is a limitation for matching individual historical events, primarily timing,
4 it is not a major concern in future projections. This is because, for the purposes of risk
5 calculations, it really doesn't matter in which month the GEV model simulates the flood event
6 as long as it realistically captures flood magnitude behavior.

7 Comparing the GEV model distribution to the other observed floods (blue triangles), the
8 distribution encompasses the observed flood magnitude (within the 5th and 95th percentile)
9 for all except for two of the floods (1955 and 1963). For 1963, the VIC simulated and
10 observed floods are in close agreement (the difference between the natural logarithm of
11 simulated and observed flows is the smallest of any event at 0.5%) and the discrepancy with
12 the GEV model is consistent with the flood timing described above. The 1955 flood resulted
13 from 38 cm of melted snow combined with 33 cm of rainfall over a three day period [O'Hara et
14 al., 2007]. In the historical forcings used to drive the VIC model December 1955 has 75 cm of
15 precipitation which is the highest December precipitation value in the historical period. In this
16 instance the VIC simulated flow falls within the interquartile range of the GEV model, but the
17 high monthly precipitation results in an overestimate of the flood magnitude. Again, this is a
18 limitation of using monthly forcings because the total December precipitation is used as a
19 covariate and not a storm specific value though in many cases the storm specific values
20 constitute the bulk of the monthly precipitation totals.

21 Figure 4 is a time series plot of VIC historical simulated flow along with the median and 5th
22 to 95th percentile flow of the GEV model. As would be expected from the model fit
23 demonstrated in Figures 2 and 3, Figure 4 shows that the VIC simulated flows are generally
24 close to the median GEV modeled flow and nearly always fall within the 5th to 95th
25 percentile range. Although there are differences in the simulation of individual events
26 discussed above, the median simulated flood magnitudes are only greater than the maximum
27 observed flood in two instances.

28 In general, Figures 3 and 4 show that the VIC simulated flows match closely with the
29 observed floods (based on percent difference in the natural logarithm of flows) and that the
30 interquartile range of the GEV distributions encompass the observed and simulated flows in
31 most instances. Figure 3 does illustrate some of the complications in matching individual
32 events, however based on analysis of the driving forces behind each individual event we are

able to document the sources of these discrepancies. Based on this analysis we conclude that the model behaviour is a reasonable match with the natural system.

4.3 Future flood risk

Future flood risk is calculated using equation (5b) from Table 1. For the first part of this analysis we define ‘flood’ as one-day flow exceeding 1,065 cms (37,600 cfs). This is the maximum historical unregulated flow at Reno from the January 2, 1997 event and is considered to be the design flood for flood protection infrastructure design. For each simulation month (1950-2099 November –April) exceedance probabilities are calculated for every climate projection (234 in total) using the selected non-stationary GEV models from Table 3 and the projected monthly precipitation and temperature. As detailed in the section 3.2, when exceedance probabilities are time dependent, the flood risk (refer to equation 5b, Table 1) is a function of both the length of the design life and the period of operation. Figure 5 plots the risk of flood versus project life for three time periods, 1950 to 1999, 2000 to 2049 and 2050 to 2099. In other words this is the risk of a flood exceeding 1,065 cms in the next n years if you are standing in 1950, 2000 or 2050. The median and interquartile ranges show the distribution of the 234 climate projections simulated. Here we use the interquartile range, as opposed to the 5th and 95th percentile, to focus on the central tendencies of each time period and not the variability between projections. Note that the ranges presented here express the variability between climate models. Uncertainty in the historical data sources used for calibration and in the parameters of the VIC model are not investigated directly here. For more detailed analysis on uncertainty in VIC simulations the reader is referred to Elsner et al. [2014].

For both Farad and Reno there is a clear positive shift in flood risk between the three time periods. In all cases the median risk for each subsequent time period falls outside the interquartile range of the preceding time period although the prediction spread for Reno is greater than Farad. It is important to note that the flood risk is actually higher at Farad than Reno in both the historical and future periods despite the fact that the observed flow distributions at the two stations are very similar (refer to Figure2). This shift between Farad and Reno is caused by the differences in the shape parameters (refer to Table 3). Farad has a heavier tailed distribution and therefore flood risks are increased. The sensitivity of the model

parameters (and the associated flood risk) to small differences in the flow and covariate distributions is further demonstrated by Figure 6.

Figure 6 presents the project life risk from Figure 5 for three project life periods (10, 20 and 30 years). Boxplots show the non-stationary model results for the 234 climate projections with the different time periods compared side by side. Also, the risk calculated using a stationary GEV model and a stationary LP3 model (i.e. the distribution prescribed by Bulletin 17B fit using the L-moments [IACWD, 1982]) fit to the historical flow data are plotted for reference (blue and red dashed lines respectively). Comparing between these three approaches (non-stationary GEV, stationary GEV and stationary LP3) provides information on the sensitivity of results to model approach and non-stationary parameters. For instance, both stationary models are fit to the same historical simulated flows (one using MLE and the other using L-moments) so differences between the stationary lines reflect the impact of model choice and fitting approach on estimated risk. Conversely the stationary GEV model (blue line) and the historical non-stationary models (grey boxplot) have the same model form and cover the same time period; the only difference is the addition of covariates to estimate model parameters. Thus differences between these two show the effect of model parameter changes from the non-stationary approach. Finally, variability between the boxplots for a given design period demonstrates the evolution of risk over time (i.e. the impact of climate trends on risk). The latter (i.e. changing risk over time), is the purpose of this analysis, however before assessing trends over time we must first discuss the impact of model choice and parameters on risk estimates.

For both of the stationary methods, the risk increases with project life following equation (5a) from Table 1. The distinction between these lines and the non-stationary approaches is that, with the stationary approach, a single exceedance probability is calculated for the given flood magnitude and this probability is assumed to remain constant throughout the design life. Also, for both stationary approaches the model is fit directly to the historical one day maximum flow distribution and no covariates are required (note that stationary models are not fit to the future time periods because this would require future simulated flows). Comparing between the GEV (blue line) and the LP3 (red line) stationary models there is a 10-20% increase in risk between the two models. This difference is purely a function of model form and highlights the sensitivity of the risk calculations to model choice.

Contrasting the difference between the stationary (blue line) and the non-stationary GEV for the historical time period (grey boxplot) illustrates the effect of adding non-stationary parameters to a given model form. Recall that in both cases the GEV model is fit to the historical simulated flows. However, for the stationary approach, model fitting results in a single set of parameters (location, scale and shape) whereas with the non-stationary approach we derive the shape parameter and a set of coefficients for linear models to determine the location and scale parameters based on precipitation and temperature values. Thus, for the non-stationary approach, different location and scale parameters are calculated for every historical cool season month and GCM model (234).

Overall, there is close agreement between the stationary (S) and average non-stationary (NS) location parameters (6.55 S vs. 6.64 NS at Farad and 6.63 S vs. 6.78 NS at Reno). However, for both gauges the scale parameter is lower with the non-stationary approach (1.30 S vs. 0.94 NS at Farad and 1.28 S vs. 0.96 NS at Reno). At Reno the shape parameter is similar (-0.24 S vs. -0.27 NS), but at Farad the difference is somewhat larger (-0.24 S vs. -0.18 NS). Differences in model parameters are reflected in the distance between the stationary GEV model (blue line) and the median historical non-stationary GEV boxplots (center of the grey boxplots) in Figure 6. For Reno the stationary line is closer to the historical boxplots. However, at Farad, the non-stationary boxplots are consistently higher than the stationary line. The larger differences between the stationary and non-stationary models for Farad result from changes in the shape parameter between the stationary and non-stationary model fits. This change demonstrates the sensitivity of model results to changes in model parameters.

As with Figure 5, Figure 6 shows significant increases in risk moving into the future and subsequently larger differences between the stationary and non-stationary approach. By the second future period the differences between the stationary and non-stationary models can be as much as 50% or more. For both gauges difference in risk between the non-stationary and stationary approaches grows over time, indicating greater potential to underestimate risk looking further into the future if non-stationary parameters are not adopted.

Although the figures are not shown here, results were also grouped by RCPs to analyze connections between greenhouse gas emission rates and changes in flood risk. We observed no clear trend in flood risk based on the different RCPs. This indicates that the variability between GCM model form and initial conditions likely overwhelms the influence of greenhouse gas emissions when comparing between scenarios. In other words, the variability

1 between projections within any RCP scenario is larger than the difference between RCP
2 scenarios.

3 Given the sensitivity of projected risk to model parameters, an obvious question is whether
4 increases in risk over time are similarly sensitive. For the 1,065 cms flood plotted in Figure 6,
5 the increased risk with added project life (i.e. 20 years vs. 10 years) is greater with the non-
6 stationary models than the stationary one at both stations. This is intuitive, given the increased
7 flood risk with time demonstrated in Figure 5 for the non-stationary models. Although, Farad
8 has higher risk overall, the relative increase in risk between time periods is similar between
9 the two stations. For example, the median ten year flood risk increases by 21% for Farad
10 comparing between the first (1950-1999) and second (2000-2049) time periods compared to
11 29% for Reno.

12 Next, analysis is expanded to a range of flood magnitudes. Figure 7 plots the flood risk over a
13 ten year project life starting in 1950, 2000, and 2050 for flood values ranging from 283 to
14 1,416 cms (10,000 to 50,000 cfs). As would be expected the ten year flood risk decreases
15 with increasing flood rate. The shapes of the curves are slightly different between Farad and
16 Reno; flood risk decreases more sharply with increased flow at Reno than Farad. Again this
17 behavior is a function of the shape of the distribution. Despite these differences, both gauges
18 display clear shifts between time periods similar to Figure 5. Here again, the median risk for
19 each subsequent period consistently falls outside the interquartile range of the preceding
20 period.

21 Changes in the median flood risk (i.e. differences between the solid lines on Figure 7)
22 between each future period and the historical period are plotted in Figure 8 for both gauges.
23 As would be expected based on the qualitative differences in Figure 7, the shape of the Farad
24 and Reno difference curves are slightly different. However, the salient point for this analysis
25 is that the increased risk between periods is generally within 10% between the two stations.
26 Overall the increased risk between the first future period (2000-2050) and the historical
27 period (1950-1999) is between 10 and 20% for flows from 600 to 1,200 cms . Similarly, the
28 increased risk from the historical period to the second future period (2050-2099) is between
29 30 and 50%. Differences for the highest and lowest flows are difficult to assess because the
30 median is skewed by the upper and lower limits of risk (i.e. 0 and 100%).

31

20

5 Summary and Conclusions

The analysis presented is unique in its incorporation of non-stationary GEV analysis using CMIP 5 projections and the design life level risk assessment. We present our findings as a relevant case study and an example application of recent developments in non-stationary flood assessment. Lacking sufficient unregulated flow data we simulate historical floods using the VIC model. Subsequently we use the simulated floods to fit non-stationary GEV models with downscaled monthly precipitation and temperature as covariates. Although there are some discrepancies between individual simulated and observed floods, we demonstrate that the VIC model adequately captures the range of flood magnitudes. Furthermore, we show that the GEV modeled historical floods are in good agreement with both the VIC simulated floods and the published flood events [USACE, 2013b].

Discrepancies between historical and simulated events often result from the monthly time step used for covariates. This can affect the ability to model floods that are generated by precipitation that occurs in two months. Also, because the climate variables are monthly aggregates, and not event based, large floods can be generated in months with high precipitation even if that precipitation does not occur in one concentrated event. Despite these differences, comparison with historical floods demonstrated that the GEV model does a good job of encompassing historical flood magnitudes, even if some individual historical events are not matched exactly.

Using the derived non-stationary GEV models, we generate flood distributions for 234 CMIP5 climate projections from 1950 to 2099. For the historical one-day design flood magnitude of 1,065 cms, results show significant increases in the frequency of high flow events in the future. From a water management standpoint this finding translates directly to increased flood risk. For example, we calculate a 21% (29%) increase risk of a 1,065 cms flood over a 10 year design life for Farad (Reno) from the historical time period to the first future period, and similar increases from the first future period to the second. Increased risk between time periods is also relatively consistent for longer design life periods and similar shifts in flood risk are noted across a range of flood magnitudes. For both stations the increased risk from the historical to the first future period is between 10 and 20% and from the historical to the second future period is between 30 and 50% for floods ranging from 600 to 1,200 cms.

1 The significant increases in flood risk through time indicate the importance of non-stationary
2 flood frequency analysis for future infrastructure planning and the potential to underestimate
3 risk when stationarity is assumed. For both stations the difference between the stationary and
4 no-stationary approach increases over time. By the second future period differences in risk
5 calculations between the stationary and non-stationary models can be 50% or larger. This
6 finding is in keeping with a number of recent studies [e.g. *Griffis and Stedinger*, 2007; *Katz et*
7 *al.*, 2002; *Towler et al.*, 2010] that have highlighted potential applications for non-stationary
8 analysis of flood frequency.

9 An important consideration for this approach is the sensitivity of results to model parameters.
10 In all cases the flood risk is higher at Farad than Reno due to the heavier tailed distribution
11 that was fit. Estimated model parameters differed by station despite the fact that the flow,
12 precipitation and temperature distributions for both locations are very similar. While these
13 changes effected the overall risk projections the relative increase in risk over time remained
14 consistent between stations. This indicates that the more robust metric from this analysis is
15 the relative increase in flood risk and not the absolute values. This finding is further
16 supported by the fact that absolute flood risk estimates could be impacted by model bias. By
17 focusing on differences in risk we specifically highlight the impact of non-stationarity on risk
18 assessment, as opposed to parameter sensitivity. Similarly, it is important to note that this
19 analysis is based on natural flow estimates and does not include infrastructure development or
20 operation. As such results indicate the potential increase in the underlying natural flood risk
21 and not the potential increase in flood damages.

References

- Akaike, H. (1974), New look at statistical-model identification, *IEEE Trans. Autom. Control*, 19, 716-723.
- Allan, R. P. (2011), Climate change: Human influence on rainfall, *Nature*, 470, 344-345.
- Cayan, D. R., K. T. Redmond, and L. G. Riddle (1999), ENSO and Hydrologic Extremes in the Western United States, *Journal of Climate*, 12(2881-2893).
- Cayan, D. R., S. A. Kammerdiener, M. D. Dettinger, J. M. Caprio, and D. H. Peterson (2001), Changes in the Onset of Spring in the Western U.S., *Bulletin of the American Meteorological Society*, 82(3), 399-415.
- Christensen, N. S., and D. P. Lettenmaier (2007), A multimodel ensemble approach to assessment of climate change impacts on the hydrology and water resources of the Colorado River Basin, *Hydrology and Earth System Science*, 11, 1417-1434.
- Christensen, N. S., A. W. Wood, D. P. Lettenmaier, and R. N. Palmer (2004), Effects of climate change on the hydrology and water resources of the Colorado river basin, *Climate Change*, 62(103), 337-363.
- Das, T., D. W. Pierce, D. R. Cayan, J. A. Vano, and D. P. Lettenmaier (2011), The importance of warm season warming to western U.S. streamflow changes, *Geophysical Research Letters*, 38(L23403).
- Dettinger, M. D., and D. R. Cayan (1995), Large-scale Atmospheric Forcing of Recent Trends toward Early Snowmelt Runoff in California, *Journal of Climate*, 8(3), 606-623.
- Douglas, E. M., R. M. Vogel, and C. N. Kroll (2000), Trends in floods and low flows in the United States: impact of spatial correlation, *Journal of Hydrology*, 240(1-2), 90-105.
- Easterling, D. R., G. A. Meehl, C. Parmesan, S. A. Changnon, T. R. Karl, and L. O. Mearns (2000), Climate Extremes: Observations, Modeling and Impacts, *Science*, 289(5487), 2068-2074.
- Elsner, M. M., S. G. Gangopadhyay, T. Pruitt, L. D. Brekke, N. Mizukami and M. P. Clark (2014), How does the choice of distributed meteorological data affect hydrologic model calibration and streamflow simulations?, *Journal of Hydrometeorology*, 15, 1384-1403.

1 Franks, S. W. (2002), Identification of a change in climate state using regional flood data,
2 *Hydrol. Earth Syst. Sci.*, 6, 11-16.

3 Gangopadhyay, S., T. Pruitt, L. D. Brekke, and D. A. Raff (2011), Hydrologic Projections for
4 the Western United States, *EOS*, 92(48), 441-452.

5 Gilleland, E., and R. W. Katz (2011), New software to analyze how extremes change over
6 time. , *Eos* 92(2), 13-14.

7 Gilroy, K. L., and R. H. McCuen (2012), A nonstationary flood frequency analysis method to
8 adjust for future climate change and urbanization, *Journal of Hydrology*, 414-415, 40-48.

9 Griffis, V., and J. R. Stedinger (2007), Incorporating climate change and variability into
10 Bulletin 17B LP3 model, paper presented at ASCE World Env. & Water Resour. Congress.

11 Gutowski, W. J., G. C. Hegerl, G. J. Holland, T. R. Knutson, L. O. Mearns, R. J. Stouffer, P.
12 J. Webster, M. F. Wehner, and F. W. Zwiers (2008), Causes of Observed Changes in
13 Extremes and Projections of Future Changes in Weather and Climate Extremes in a Changing
14 Climate. Regions of Focus: North America, Hawaii, Caribbean, and U.S. Pacific IslandsRep.,
15 Washington, DC.

16 Hirsch, R. M. (2011), A perspective on nonstationarity and water management, *Journal of the*
17 *American Water Resources Association*, 47(3), 436-446.

18 Jain, S., and U. Lall (2001), Floods in a changing climate: Does the past represent the future?,
19 *Water Resources Research*, 37(12), 3193-3205.

20 Katz, R. W. (2010), Statistics of extremes in climate change, *Climate Change*, 100, 71-76.

21 Katz, R. W., M. B. Parlange, and P. Naveau (2002), Statistics of extremes in hydrology,
22 *Advances in Water Resources*, 25, 1287-1304.

23 Kunkel, K. E. (2003), North American Trends in Extreme Precipitation, *Natural Hazards*, 29,
24 291-305.

25 Liang, X., E. F. Wood, and D. P. Lettenmaier (1996), Surface soil moisture parameterization
26 of the VIC-2L model: Evaluation and modification, *Global and Planetary Change*, 13(1-4),
27 195-206.

1 Liang, X., D. P. Lettenmaier, E. F. Wood, and S. J. Burges (1994), A simple hydrologically
2 based model of land surface water and energy fluxes for general circulation models, *Journal*
3 *of Geophysical Research*, 99(D7), 14415-14428.

4 Madsen, T., and E. Figdor (2007), When it Rains it Pours - Global Warming and the Rising
5 Frequency of Extreme Precipitation in the U.S., edited, Environmental America Research and
6 Policy Center.

7 Maidment, D. R. (1993), Handbook of Hydrology, McGraw-Hill, ISBN 0070397325.

8 Mailhot, A. and S. Duchesne (2010), Design criteria of urban drainage infrastructures under
9 climate change, *Journal of Water Resources Planning and Management*, 136(2), 201-208.

10 Maurer, E. P., L. D. Brekke, T. Pruitt, and P. B. Duffy (2007), Fine-resolution climate
11 projections enhance regional climate change impact studies, *Eos Tran. AGU*, 88(47), 504.

12 Maurer, E. P., A. W. Wood, J. C. Adam, D. P. Lettenmaier, and B. Nijssen (2002), A Long-
13 Term Hydrologically-Based Dataset of Land Surface Fluxes and States for the Conterminous
14 United States, *Journal of Climate*, 15(22), 3237-3252.

15 Meehl, G. A., et al. (2000), An Introduction to Trends in Extreme Weather and Climate
16 Events: Observations, Socioeconomic Impact, Terrestrial Ecological Impacts, and Model
17 Projections, *Bulletin of the American Meteorological Society*, 81, 413-416.

18 Merz, B., S. Vorogushyn, S. Uhlemann, J. Delgado and Y. Hundecha (2012), More efforts
19 and scientific rigour are needed to attribute trends in flood time series, *Hydrol. Earth Syst.*
20 *Sci. Opinions*, 16, 1379-1387.

21 Milly, P. C. D., J. Betancourt, M. Falkenmark, R. M. Hirsch, Z. W. Kundzewicz, D. P.
22 Lettenmaier, and R. J. Stouffer (2008), Stationarity Is Dead: Whither Water Management,
23 *Science*, 319(5863), 573-574.

24 Min, S.-K., X. Zhang, F. W. Zwiers, and G. C. Hegerl (2011), Human contribution to more-
25 intense precipitation extremes, *Nature* 470, 378-381.

26 Mote, P.W., A.F. Hamlet, M.P. Clark, And D.P. Lettenmaier (2005), Declining Mountain
27 Snowpack In Western North America, *Bulletin of the American Meteorological Society*, 39-
28 49, doi: 10.1175/BAMS-86-1-39.

29 Mullet, C. J., P. A. O'Gorman, and L. E. Back (2011), Intensification of precipitation
30 extremes with warming in a cloud resolving model, *Journal of Climate*, 24(2784-2800).

1 Nijssen, B., D. P. Lettenmaier, X. Liang, S. W. Wetzel, and E. F. Wood (1997), Streamflow
2 simulation for continental-scale river basins, *Water Resources Research*, 33(4), 711-724.

3 Hall, J. et al. (2014), Understanding flood regime change in Europe: a state-of-the-art
4 assessment, *Hydrol. Earth Syst. Sci.*, 18, 2735-2772.

5 Interagency Advisory Committee on Water Data (IACWD) (1982), Guidelines for
6 determining flood flow frequency: Bulletin 17B of the Hydrology Subcommittee, Office of
7 Water Data Coordination, U.S. Geological Survey, Reston, VA., 183 p.

8 Obeysekera, J. and J. D. Salas (2014), Quantifying the uncertainty of design floods under
9 nonstationary conditions, *Journal fo Hydrologic Engineering*, 19, 1438-1446.

10 O'Gorman, P. A., and T. Schneider (2009), The physical basis for increases in precipitaiton
11 extremes in simulations of 21st century climate change, *Proceedings of hte National Academy
12 of Sciences*, 106, 14773-14777.

13 O'Hara, B.F., G.E. Barbato, J.W. James, H.A. Angeloff and T. Cylke (2007), 'Weather and
14 climate of the Redno-Carson City- Lake Tahoe Region, Nevada Bureau of Mines and
15 Geology, Special Publication 34.

16 Pall, P., T. Aina, D. A. Stone, P. A. Stott, T. Nozawa, A. G. J. Hilberts, D. Lohmann, and M.
17 R. Allen (2011), Anthropogenic greenhouse gas contribution to flood risk in England and
18 Wales in autumn 2000, *Nature*, 470, 382-385.

19 Payne, J. T., A. W. Wood, A. F. Hamlet, R. N. Palmer, and D. P. Lettenmaier (2004),
20 Mitigating the effects of climate change on the water resources of the Columbia River basin,
21 *Climate Change*, 62(1-3), 233-256.

22 Pierce, D. W., T. Das, D. R. Cayan, E. P. Maurer, N. L. Miller, Y. Bao, M. Kanamitsu, K.
23 Yoshimura, M. A. Snyder, L. C. Sloan, G. Franco, M. Tyree (2012), Probabilistic estimates of
24 future changes in California temperature and precipitation using statistical and dynamical
25 downscaling, *Climate Dynamics*, 40, 839-856.

26 Raff, D. A., T. Pruitt, and L. D. Brekke (2009), A framework for assessing flood frequency
27 based on climate projection information, *Hydrol. Earth Syst. Sci.*, 13, 2119-2136.

28 Ralph, F. M., and M. D. Dettinger (2012), Historical and National Perspectives on Extreme
29 West Coast Precipitation Associated with Atmospheric Rivers during December 2010,
30 *Bulletin of the American Meterorological Society*(June), 783-790.

Reclamation (2011), West-wide climate risk assessments: Bias-corrected and spatially downscaled surface water projections, Tech. Memo., 86-68210-2011-01, 138 pp., Tech. Serv. Cent., U.S. Dep. of the Inter., Denver Colo., March.

Reclamation (2013). Downscaled CMIP3 and CMIP5 Climate Projections: Release of Downscaled CMIP5 Climate Projections, Comparison with Preceding Information, and Summary of User Needs. Downscaled CMIP3 and CMIP5 Climate and Hydrology Projections. U.S. Department of the Interior, Bureau of Reclamation, Technical Service Center, Denver, Colorado, 116 p.

Reclamation (2014), 'Downscaled CMIP3 and CMIP5 Climate and Hydrology Projections: Release of Hydrology Projections, Comparison with preceding Information, and Summary of User Needs', prepared by the U.S. Department of the Interior, Bureau of Reclamation, Technical Services Center, Denver, Colorado. 110 pp.

Regonda, S. K., B. Rajagopalan, M. Clark, and J. Pitlick (2005), Seasonal Cycle Shifts in Hydroclimatology Over the Western U.S., *Journal of Climate*, 18(2), 372-384.

Rootzén, H., and R. W. Katz (2013), Design Life Level: Quantifying risk in a changing climate, *Water Resources Research*, 49, 5964-5972.

Salas, J., and J. Obeysekera (2014), Revisiting the Concepts of Return Period and Risk for Nonstationary Hydrologic Extreme Events, *Journal of Hyrol. Eng.*, 19(3), 554-568.

Slack, J.R., A.M. Lumb, and J.M. Landwehr (1993). 'Hydroclimatic data network (HCDN): A U.S. Geological Survey streamflow data set for the United Sates for the study of climate variation, 1874-1988,' *USGS Water Resour. Invest. Rep.*, 93-4076.

Small, D., S. Islam, and R. M. Vogel (2006), Trends in precipitation and streamflow in the eastern U.S.: Paradox or perception? *Geophysical Research Letters*, 2006(3).

Stedinger, J. R. and V. W. Griffis (2011), Getting from here to where? Flood frequency analysis and climate, *Journal of the American Water Resources Association*, 47(3), 506-513.

Stokes, J. (2002), Draft Farad Diversion Dam Replacement Project Environmental Impact Report^{Rep.}, State Water Resources Control Board, Sacramento, CA.

Sun, Y., S. Solomon, A. Dai, and R. W. Portmann (2007), How Often Will it Rain?, *Journal of Climate*, 20, 4801-4818.

1 Taylor, K. E., Stouffer, R. J. & Meehl, G. A. (2012), A Summary of the CMIP5 Experiment
2 Design. *Bull. Am. Meteorol. Soc.* 93, 485-498.

3 Towler, E., B. Rajagopalan, E. Gilleland, R. S. Summers, D. Yates, and R. W. Katz (2010),
4 Modeling hydrologic and water quality extremes in a changing climate: A statistical approach
5 based on extreme value theory, *Water Resources Research*, 46(W11504).

6 USACE (2013a), Final environmental impact statement for the Truckee Meadows Flood
7 Control Project: General Reevaluation Report Volume 1. US Army Corps of Engineers,
8 Sacramento.

9 USACE (2013b), Truckee Meadows Flood Control Project, Nevada: Draft General
10 Reevaluation Report *Rep.*, US Army Corps of Engineers, Sacramento.

11 Van Rheeën, N. T., A. W. Wood, R. N. Palmer, and D. P. Lettenmaier (2004), Potential
12 implications of PCM climate change scenarios for Sacramento-San Joaquin River Basin
13 hydrology and water resources, *Climate Change*, 62(1-3), 257-281.

14 Villarini, G., F. Serinaldi, J. A. Smith, and W. F. Krajewski (2009), On the stationarity of
15 annual flood peaks in the continental United States during the 20th century, *Water Resources*
16 *Research*, 45(8).

17 Vogel, R. M., C. Yaïndl, and M. Walter (2011), Nonstationarity: Flood magnification and
18 recurrence reduction factors in the United States, *JAWRA*, 47(3), 464-474.

19 Walter, M., and R. M. Vogel (2010), Increasing trends in peak flows in the northeastern
20 United States and their impacts on design, paper presented at 2nd Joint Federal Interagency
21 Conference, Las Vegas, NV.

22 Wood, A. W., Leung, L. S. R., Sridhar, V., and Lettenmaier, D. P. (2004), Hydrologic
23 implications of dynamical and statistical approaches to downscaling climate model outputs,
24 *Climatic Change*, 62, 189–216.

25 Wu, H., R. F. Adler, Y. Tian, G. J. Juffman, H. Li and J. J. Wang (In press), Real-time global
26 flood estimation using satellite-based precipitation and a coupled land surface routing model,
27 *Water Resources Research*.

28

1 **Table 1: Flood calculations using stationary and non-stationary distributions (adapted**
2 **from *Salas and Obeysekera [2014]*)**

Eqn. #	Description	a. Stationary	b. Non Stationary
1	Exceedance probability (Probability of flood occurring in year x) ¹	p	p_x
2	Probability of the first flood occurring in year x ²	$f(x) = (1 - p)^{x-1}p$	$f(x) = p_x \prod_{t=1}^{x-1} (1 - p_t)$
3	Probability of a flood occurring before year x ³	$F(x) = \sum_{i=1}^x f(i)$	
		$F(x) = 1 - (1 - p)^x$	$F(x) = 1 - \prod_{t=1}^x (1 - p_t)$
4	Return Period (Expected waiting time between flood occurrences ^{4,5})	$E(X) = \sum_{x=1}^{\infty} x \cdot P(X = x)$	
		$E(X) = 1/p$	$E(X) = 1 + \sum_{x=1}^{x_{max}} \prod_{t=1}^x (1 - p_t)$
5	Probability of a flood occurring before the design life n	$R = P(X \leq n) = F(n)$	
		$R = 1 - (1 - p)^n$	$R = 1 - \prod_{t=1}^n (1 - p_t)$

3 ¹ Flood is defined as a flow exceeding a predefined threshold

4 ² $f(x)$ = Probability density function of X

5 ³ $F(x)$ = Cumulative distribution function of X

6 ⁴ X = Random variable denoting the waiting time for the first flood occurrence

7 ⁵ x_{max} = Time when p_x equals 1

8
9

Table 2: Negative log likelihood(NLLH) and Akaike information Criterion (AIC) scores for each model, as well as the deviance statistics (D) of pairwise comparisons of different model configurations (P = precipitation only, T= temperature only P&T= both) and the p-values of each D score based on a chi-squared distribution. The number of parameters in each model and the models used for comparison are listed at the bottom of the table. The selected model for each station is shaded in grey.

Station	Metric	Stationary	Non stationary Location			Non stationary Scale			Non stationary Location and		
			P & T	P	T	P & T	P	T	P & T	P	T
		1	2	3	4	5	6	7	8	9	10
Farad	NLLH	508.9	422.9	467.1	499.7	487.3	500.9	506.5	416.4	462.2	496.9
	AIC	1023.7	855.9	942.3	1007.4	984.6	1009.8	1021.1	846.8	934.4	1003.8
	D		171.8	83.4	18.3	43.1	15.9	4.7	13.0	9.9	5.7
	p-value of D		< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
Reno	NLLH	505.4	418.4	462.5	496.0	484.4	497.6	503.1	408.8	457.4	493.2
	AIC	1016.8	846.8	932.9	1000.0	978.8	1003.2	1016.1	831.7	924.8	996.5
	D		174.0	85.9	18.8	42.0	15.6	4.7	19.1	10.1	5.5
	p-value of D		< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05	< 0.05
# of model parameters		3	5	4	4	5	4	4	7	5	5
Model # compared to for pval			1	1	1	1	1	1	2	3	4

1

2 Table 3: Summary of derived model covariates for equations 2 and 3.

	Farad	Reno
$\beta_{0\mu}$	2.155	2.582
$\beta_{1\mu}$	0.175	0.18
$\beta_{2\mu}$	0.115	0.105
$\beta_{0\sigma}$	0.211	0.530
$\beta_{1\sigma}$	-0.013	-0.018
$\beta_{2\sigma}$	0.027	0.017
Shape (ξ)	-0.178	-0.275

3

4





Figure 1: Map of model domain including the Farad and Reno gauges and their drainage areas.

1




2

3 Figure 2: PDFs of fitted stationary (solid black) and non-stationary (dashed) GEV models
 4 compared to historical VIC simulated flow histogram.

5

6



7

8 Figure 3: 'Observed' unregulated flow estimated from gauge records (blue triangle)
 9 compared with VIC simulated flow (red circles) and the simulated GEV distribution.
 10 Boxes span the 25th to 75th percentile of the GEV distribution for a given month and the
 11 whiskers extend to the 5th and 95th percentiles.




Figure 4: VIC simulated one- day flood maximums for November through April 1950 to 1999 (red lines) compared with the historical GEV distributions (blue line is median and grey shading is the 5th to 95th percentile range) and the six observed flow rates.




Figure 5: Probability of one day flood exceeding historical maximum of 37,600 cfs at Farad and Reno. Solid lines represent the median risk of the 234 climate projections and shading covers the interquartile range (i.e. 25th to 75th percentile).





Figure 6: Boxplots of the probability of a one-day flood exceeding 37,600 cfs for three project life lengths (10, 20 and 30 years). Results are grouped by time period (1950-1999, 2000-2049 and 2050-2099). Blue dashed lines show the flood risk calculated from the stationary GEV model fit to the historical data.


1



2

3 Figure 7: Probability of flood in a ten year project life vs. median one day flood rate (a)
4 Farad and (b) Reno for three time periods 1950-1999 (blue), 2000-2049 (red) and
5 2050-2099 (green). Solid lines represent the median of the 234 climate projections and
6 shading covers the interquartile range (i.e. 25th to 75th percentile).

7



8

1 Figure 8: Increased probability of flood occurrence for a 10 year project life from the
2 historical period (1950-1999) to each of the two future periods 2000-2050 (black) and
3 2050-2099 (grey). Farad is plotted with a solid line and Reno is a dashed line.
4