

Response #1

Thanks for reviewing the manuscript and giving valuable comments and suggestions. Those comments are all valuable and very helpful for revising and improving our paper. We have studied comments carefully and have made correction which we hope meet with approval. The main corrections in the paper and the responds to the reviewer's comments are as following:

- (1) It is assumed that all the model (TOPMODEL and VIC) parameters will not change under climate change only. This assumption should be stated clearly and discussed, and the calibration method, calibrated results and relevant parameter values should be provided and analyzed.

Response: The aim of this assumption is to keep the effect of human activities unchanged on streamflow variation in the impacted period compared with the baseline period. Hence, the simulated streamflow in the impacted period only reflects the influence of climate change. Then, the impact of human activities can be separated based on the equation (2) in the manuscript. Some studies (Bao, Z. et al., 2012; Ma H et al., 2010) also used this assumption to conduct similar investigation about this topic.

Bao, Z., Zhang, J., Wang, G., Fu, G., He, R., Yan, X., Jin, J., Liu, Y., and Zhang, A.: Attribution for decreasing streamflow of the Haihe River basin, northern China: Climate variability or human activities, *J. Hydrol.*, 460–461, 117–129, 2012.

Ma H, Yang D, Tan SK, Gao B, and Fu Q.: Impact of climate variability and human activity on streamflow decrease in the Miyun Reservoir catchment, *J. Hydro.*, 389: 317-324, 2010.

The parameters of TOPMODEL and VIC model were regulated by artificial means, and the results in calibration period (1960-1966) and validation period (1967-1969) of two hydrological models were shown in Fig.6 and Fig.7. We divided the JRB into 25 sub-basins and 17 sub-grids in TOPMODEL and VIC model, respectively. The parameters of each sub-basin for TOPMODEL are different, also the parameters of each sub-grid for VIC model are different too. The following is parameter values of 17 sub-grids of VIC model.

Table The parameters of VIC model

Sub-grid	<i>B</i>	<i>Ds</i>	<i>Dm</i>	<i>Ws</i>	<i>d2</i>	<i>d3</i>
1	0.58	0.66	2	0.55	1.80	0.73
2	0.63	0.75	2	0.52	1.75	0.75
3	0.61	0.68	2	0.64	1.62	0.70
4	0.68	0.72	2	0.59	1.82	0.68
5	0.64	0.73	2	0.62	1.66	0.65
6	0.59	0.66	2	0.68	1.75	0.71
7	0.57	0.64	2	0.59	1.73	0.75
8	0.63	0.78	2	0.65	1.69	0.78
9	0.68	0.69	2	0.58	1.52	0.69
10	0.70	0.67	2	0.63	1.54	0.63
11	0.72	0.77	2	0.55	1.48	0.75
12	0.73	0.78	2	0.55	1.65	0.76
13	0.69	0.68	2	0.62	1.78	0.82
14	0.59	0.64	2	0.69	1.65	0.74
15	0.56	0.59	2	0.76	1.50	0.65
16	0.64	0.58	2	0.78	1.54	0.79
17	0.71	0.63	2	0.74	1.65	0.78

(2) Line 8 on page 12750: change “soil and a water conservation project” to “soil and water conservation projects”.

Response: Corrected.

(3) Lines 27-28 on page 12570: check the sentence.

Response: We have changed into “Sect.3 is devoted to introduce the research methods; Sect. 4 provides the results about the methods of elasticity model and two hydrological models;”

(4) Line 9 on page 12571: delete “areal”.

Response: Corrected.

(5) Line 10 on page 12571: “variability” to “variabilities”.

Response: Corrected.

(6) Lines 12-13 on page 12571: check the sentence.

Response : According to the comment, we have changed the sentence into “Zhangjiashan station is the downstream hydrometric station on the main stream of the Jinghe River.”

(7) Lines 1-2 on page 12572: check the sentence.

Response: We have changed the sentence into “The monthly and annual precipitation was then established from the collected data, and the annual maximum, annual minimum, and multi-annual mean air temperature values were then calculated according to the daily data.”

(8) Lines 13 on page 12572: check the sentence.

Response: Corrected. We have changed it into “The historic streamflow series can be split into two subseries according to the streamflow break year, and before the year human activities were negligible.”

(9) Line 9 on page 12574: delete “the equilibrium”.

Response: Corrected.

(10) Lines 8-17 on page 12755: check the sentence, and different scenarios are presented in tables better.

Response: We didn't set scenarios in the paper, and there's no page of 12755.

Response #2

This paper quantitatively isolated the relative contributions that human activities and climate variability made to decadal streamflow changes in Jinghe Basin of China using an elasticity-based method and two hydrological models (TOPMODLE and VIC models). There are three major concerns with this manuscript.

1. I think the results could be made more concise and understandable, and the discussion should be deeper, especially for the uncertainties of the three methods.
2. The logic and statement should be consistent throughout the whole paper.
3. The paper is understandable but the English would need considerable improvement from a native speaker before it should be published.

Response: Sincere gratitude is extended to the reviewer for the careful review of the manuscript. Those comments are all valuable and very helpful for revising and improving our paper, as well as the important guiding significance to our researches. Here are our responses to the reviewers' comments.

We have made the results more concise and easily understood. The logic and statement were checked and modified throughout the paper. Meanwhile, the manuscript language has been edited.

Specific Comments

Abstract

1. P12748 L10 Relative to what, the decreased speed of streamflow was higher?

Response: In the part of Sect. 4.1 (P12757 L16-24), we have described as following:

“The multi-year average streamflow (from 1960 to 2010) was 37.03 mm, and the average annual streamflow was 43.47 mm from 1960 to 1990, which meant that the streamflow from 1960 to 1990 increased by 17.39% compared with the multi-year average streamflow. The average annual streamflow was 27.05 mm during 1991-2010 and was reduced by 26.96% compared with the multi-year average value; therefore, the speed of the streamflow decrease was higher since 1990.”

In order to be better understood, we have changed the statement into “The results showed that the maximum value of the moisture index (E0/P) was 1.91 and appeared in 1991-2000, and the decreased speed of streamflow was higher since 1990 compared with 1960-1990”.

2. P12748 L13 Please specify “the multi-year average value” represents the average value from which year to which year.

Response: “the multi-year average value” represents the average value from 1960 to 2010.

3. P12748 L18 Please point out what does the 99 and 40.4% mean, respectively?

Response: In the part of Sect. 5.1 (P12763 L7-13), we have described as following:

The most significant climate variability impacts were $2.7 \times 10^8 \text{ m}^3$ (47.4%), $2.5 \times 10^8 \text{ m}^3$ (43.9%) and $1.7 \times 10^8 \text{ m}^3$ (29.9%) for TOMODEL, VIC model and the elasticity based model, respectively, appearing in the 1990s. The most significant human

activities impacts were $3.8 \times 10^8 \text{ m}^3$ (95%), $4.5 \times 10^8 \text{ m}^3$ (112.5%) and $3.7 \times 10^8 \text{ m}^3$ (92.4%) for TOMODEL, VIC model and the elasticity based model, respectively, appearing in the 1980s.

Therefore, the average contribution ratios of human activities and climate variability of the three methods were 99% and 40.4%, respectively. In order to be better understood, we have changed the sentence into “The maximum contribution value of human activities was 99% when averaged over the three methods, and was appeared in 1981–1990 due to the effects of soil and water conservation measures and irrigation water withdrawal. Climate variability made the greatest contribution to runoff reduction in 1991–2000, the values of which was 40.4%.”

4. P12748 L19 What is the significance to emphasize the errors and uncertainties that may occur in the methods used in the study.

Response: Since some factors tend to disturb the results of the paper, it is necessary to point out the uncertainty of the methods. So, we qualitatively discussed the errors and uncertainties in the section of 5.2, however there is no quantitatively discussions. We will make an attempt for further research.

Introduction

5. P12750 L10 The “Yellow River basin” only appear once in the paper, I think that’s no necessary to use the abbreviation of YRB. Similarly, the MWR for the Ministry of Water Resources and the CMR for the China Meteorological Administration.

Response: Corrected.

6. P12750 L10-12 The references should be noted for the numbers of 1.28 °C/50 years and 8.8%.

Response: According to the comment, we have supplemented the reference: Yang D, Li C, Hu H, et al. Analysis of water resources variability in the Yellow River of China during the last half century using historical data[J]. Water Resources Research, 2004, 40(6).

7. P12750 L12-13 “A combination of these effects reduced the streamflow.” Does the streamflow reduced significantly?

Response: The changes of the annual streamflow shown in Fig.3 in the paper indicated that the streamflow reduced significantly compared with the baseline period

(1960-1970). Meanwhile, the decrease tendency of the streamflow is reported in some papers (Chang et al, 2015; Gao et al. 2013).

8. P12750 L13-16 The streamflow variation of the Jinghe River was mainly caused by the combination effect of climate change and human activities. As one important drinking water source for a population of over 6 million people, I think the streamflow variation of the Jinghe River should have been investigated by several previous researchers. The study about the relative contribution of climate change and human activities on the streamflow variation of the Jinghe River is probably few. Please elaborate clearly.

Response: There are some researches about the impact of human activities on streamflow variation in the JR. For example, Peng (2015) evaluated the impacts of soil and water conservation in JRB by means of the distributed eco-hydrological model, and the results showed that the streamflow might decrease as the vegetation evapotranspiration increased. Chen (2008) analyzed the vegetation dynamic changes and the relationship between precipitation and NDVI in JRB, and the results showed that vegetation dynamics in different areas tended to be induced by climate changes and human activities. Few studies assessed the impact of climate change and human activities on the streamflow in the JR.

Peng H, Jia Y, Niu C, et al. Eco-hydrological simulation of soil and water conservation in the Jinghe River Basin in the Loess Plateau, China[J]. Journal of Hydro-environment Research, 2015, 9(3): 452-464.

Chen C, Xie G, Zhen L, et al. Analysis on Jinghe watershed vegetation dynamics and evaluation on its relation with precipitation [J]. Acta Ecologica Sinica, 2008, 28(3):925-938.

9. P12750 L17 The objective of the study should be stated more clearly, especially, the innovation of the study.

Response: The aims of this study were to: 1) present a generic framework that investigate the impact of climate variability and human activities on streamflow using the concept of streamflow elasticity and hydrological models, the TOPMODEL and VIC models, which are fundamentally different in regard to their representation of streamflow generation; and 2) compare these methods.

Study area and data

Methodology

10. P12752 L13-14 What's does the meaning of the sentence that "the historic streamflow series can be split into subseries from a year before when human activities were negligible"?

Response: We split the historic streamflow series into two subseries according to the streamflow break year, and human activities in the recorded years prior to the break year can be negligible.

11. P12755 L8-9 "Hydrological models can also be used to assess the impact of climate change on streamflow." Does the impact of human activities on streamflow also can be assessed by the hydrological models?

Response: Yes, the impact of human activities on streamflow (ΔQ_H) also can be assessed by the hydrological models. In this paper, ΔQ_H was estimated as the difference between the mean annual average of the simulated streamflow and the mean annual average of the observed streamflow during the changed period.

12. P12757 L3 Why the break points appeared in the 1970s? Was it caused by human activities? Or climate change?

Response: We used sequential cluster method to estimate the break points of precipitation and streamflow series as shown in Fig.2, and the break points appeared in 1968 and 1970 respectively. The impact factors for decreased streamflow include human activities and climate change. The main objective of this paper is to investigate the impact of climate change and human activities on streamflow

13. P12757 L8 The mathematic expression of the NSE and WBE percentage should be given in the paper. Meanwhile, what's the evaluation standard for the calibration and validation results?

Response: We have added the mathematic expression of the NSE and WBE in the manuscript.

$$NSE = 1 - \frac{\sum_{i=1}^N (Q_{o,i} - Q_{s,i})^2}{\sum_{i=1}^N (Q_{o,i} - \bar{Q}_o)^2} \quad (9)$$

$$WBE = \left| \frac{100 * (\sum_{i=1}^N Q_{s,i} - \sum_{i=1}^N Q_{o,i})}{\sum_{i=1}^N Q_{o,i}} \right| \quad (10)$$

Where $Q_{o,i}$ is the observed streamflow of period i , $Q_{s,i}$ is the simulated streamflow of period i , and $\overline{Q_o}$ is the mean of observed streamflow.

We used the NSE and WBE as the evaluation standard for calibration and validation. The NSE value between 0.6 and 0.8 indicates that the model performs reasonably. Value between 0.8 and 0.9 indicates that the model performs very well and value between 0.9 and 1.0 indicates that the model performs extremely well. WBE performs best when a value of 0 is generated since no difference between simulated and observed streamflow occurs. The WBE between -5% and +5% indicates that a model performs well, while the WBE between +5% and +10% or -10% and -5% indicates a model with reasonable performance (Gumindoga W, 2014).

Gumindoga W, Rientjes T H M, Haile A T, et al. Predicting streamflow for land cover changes in the Upper Gilgel Abay River Basin, Ethiopia: A TOPMODEL based approach [J]. *Physics and Chemistry of the Earth, Parts A/B/C*, 2014, 76: 3-15.”

Results and discussion

14. P12757 L10 The sub-title of “Results and discussion” repeats with the sub-title of the “Discussion”.

Response: We have changed “Results and discussion” to “Results”.

15. P12758 L1-4 “...however, the minimum occurred in different years, which resulted from water withdrawal and other reasons, such as changes in groundwater.” This sentence is ambiguous. What does it mean the minimum occurred in different years?

Response: We mean that the minimum of precipitation and streamflow occurred in different years, which were 1997 and 2009 respectively.

16. P12758 L8 As we know, the runoff ratio decreased during dry years, while increased during wet years. Please elaborate why the increased runoff ratio during the wet years was emphasized, and the value of runoff ratio during the wet season should also be provided.

Response: The runoff coefficient reflects the influence of physiographic elements to the relationship of precipitation and runoff in the basin, and it is large in wet years. In Table1, we showed the characteristics of the inter-annual streamflow and

precipitation in the JRB. The mean annual runoff ratio is 0.05, and runoff ratios during the wet year and wet season were 0.08 and 0.06, respectively.

17. P12760 L15-16 “The correlation of the simulated streamflow and measured streamflow was higher during the calibration period and the R value exceeded 0.8.” What does the “higher” mean? Does the correlation coefficient of the simulated and measured streamflow was higher during the calibration period than that during the validation period? Maybe it’s better to note the correlation coefficient in each subfigure of the Fig. 7.

Response : Yes, the correlation of the simulated streamflow and measured streamflow was higher during the calibration period compared with the validation period. The R values of TOPMODEL are 0.987 and 0.944 during the calibration and validation periods, respectively. And in VIC model, they are 0.944 and 0.940. We have noted the R value in the Fig.7.

18. P12760 L18-21 “The NSE and WBE values during the validation period suggested that both the rainfall-runoff models and the calibration method used in the study were robust for the calibrated model to be used over an independent simulation period adequately.” 1) How to quantitatively evaluate the models used in the study is robust? 2) The different NSE and WBE values during the calibration period and the validation period was caused by the time-varied parameters inputted into the models. I think it is not sufficient to use the NSE and WBE values to indicate the models and calibration method used in the study were robust.

Response: 1) In general, the performance of the hydrological model is evaluated by some indexes, such as Nash-Sutcliffe efficiency (NSE), water balance error (WBE), co-efficient of determination (R) and total water error (TWE) (Liu Y, 2012; Nepal S, 2016). These indexes evaluate the results of the hydrological model from different aspects. NSE and R reflect the degree of agreement between the simulated and measured values, while WBE and TWE are used to evaluate the degree of deviation between the average observation value and average simulated value. In this paper, NSE, WBE and R were used to quantitatively evaluate the models.

2) It is sure that the difference of NSE and WBE values during the calibration period

and the validation period was caused by the time-varied parameters inputted into the models. As mentioned above, the hydrological model is usually evaluated according to some statistical parameters. In the paper, the NSE, WBE and R of TOPMODEL are 0.79, 2.1% and 0.987 in the calibration period, and are respectively 0.78, 9.2% and 0.944 in the validation period. The NSE, WBE and R of VIC model are 0.77, 3.5% and 0.944 in the calibration period, and are respectively 0.83, 4.7% and 0.940 in the validation period. We concluded that the models and calibration method used in the study were robust based on the evaluation standard of parameter NSE, WBE and R explained in 13.

Liu Y, Zhang J, Wang G, et al. Quantifying uncertainty in catchment-scale runoff modeling under climate change (case of the Huaihe River, China) [J]. *Quaternary International*, 2012, 282: 130-136.

Nepal S. Impacts of climate change on the hydrological regime of the Koshi river basin in the Himalayan region [J]. *Journal of Hydro-environment Research*, 2016, 10: 76-89.

19. P12761 L7-8 “The time series plots in Fig. 9 show that the simulated annual streamflow values were always higher than the observed streamflow.” What I got from the Fig. 9 is that the simulated annual streamflow was always higher than the observed streamflow before 1990, while the simulated streamflow was lower or similar to the observed values after 1990.

Response: The number of the years that the simulated streamflow was higher than the observed streamflow was 26 from 1970 to 2010 for TOPMODEL, and the number was 25 for VIC model. Additionally, most of the years appeared before 1990 or after 2005 for both of the models, and in the rest of the years the simulated streamflow was similar or lower to the observed value. We have revised the corresponding representation in the paper.

Discussion

20. P12763 L5-14 Please elaborate why the significant climate variability impacts appeared in the 1990s, while the most significant human activities impacts appeared in the 1980s. Does the impact decrease/increase the streamflow? What does the percentage mean in the bracket? Why the most significant human activities impact was 112.5% for the VIC model in the 1980s?

Response: The results of the three methods showed that the significant climate variability impacts appeared in the 1990s, and the significant human activities impacts appeared in the 1980s (Table 4, 5, 6). The precipitation and temperature are the dominant factors of climate changes, and we can see from the following table 1 that the maximum decrease of precipitation appeared in the 1990s compared with baseline period (1960s), and the minimum decrease was in the 1980s. The temperature showed a significant increase in the 1990s, but an insignificant increase in the 1980s. The changes of precipitation and temperature for different decades verified that the significant climate variability impacts appeared in the 1990s.

The percentages in the bracket mean the contribution ratios for streamflow decrease. The results of the three methods showed that human activities decreased the streamflow, and climate changes also decreased the streamflow except in the 1980s with VIC model. As shown table 6, the streamflow increased by $0.5 \times 10^8 \text{ m}^3$ impacted by climate changes in the 1980s, while the streamflow decreased by $4.5 \times 10^8 \text{ m}^3$ due to human activities, so the streamflow decreased by $4.0 \times 10^8 \text{ m}^3$ compared with baseline period (1960s). Therefore, the contribution ratio of human activities was 112.5% ($\frac{4.5}{4.0} * 100\%$) for the VIC model in the 1980s.

Table 1. Changes of the inter-annual precipitation and temperature of the JRB.

Time	Precipitation (mm)	Temperature (°C)	ΔP (mm)	ΔT (°C)
1960s	561.2	8.6	—	—
1970s	500.1	8.8	-61.1	0.2
1980s	535.5	8.8	-25.6	0.2
1990s	462.4	9.4	-98.8	0.8
2000s	506.5	9.8	-54.6	1.2

where ΔP and ΔT are the changes in precipitation and temperature, respectively

21. P12763 L19 What does the “two methods” represent?

Response: The “two methods” represents the climate elasticity method and the

Soil and Water Assessment Tool (SWAT) model.

22. P12763 L21-26 What's the relationship of Zhan et al. (2014) with this study?

Response: In the paper, the study area is Jinghe River, the largest tributary of the Weihe River. The purpose of quoting this paper (Zhan et al. 2014) is to compare with our study. Zhan et al. (2014) utilized the climate elasticity model to evaluate the impacts of human activities and climate changes on streamflow in Weihe River, and the results showed that the human activities played a more important role than the climate changes.

23. P12764 L19-22 "For the hydrological model the predictions of physically based distributed models commonly contained a certain degree of uncertainty." I think the information from this paragraph is common. That's no sense to emphasize the paragraph. However, a further discussion on the uncertainties of the TOPMODEL and VIC models is necessary.

Response: Since some factors tend to disturb the results of the paper, it is necessary to point out the uncertainty of the methods. The resources of hydrological model uncertainty include model structure, input data, and model parameters. There are many methods for analyzing uncertainty, such as GLUE, BaRE and MCMC, etc. We have applied modified GLUE method to discuss the TOPMODEL uncertainty. However, since this work contains lots of computation and analysis, we will write a paper focused on this topic.

24. P12765 L2-3 As mentioned above, the study area is a highly urbanized region and water withdrawal were extensive during the last several decades (P12749). Please elaborate how to get the result that "the human-induced reduction in streamflow in the JRB was primarily caused by soil and water conservation measures". If it is possible, please provide a multi-temporal land use map and briefly introduce it.

Response: I'm sorry that we had an inaccurate expression here. As we have described in the paper that the main human activities in the Jinghe River include water conservancy projects and water withdrawal, and we have not quantitatively analyzed the contribution ratios of the water conservation measure and water withdrawal. Hence, the statement of "the human-induced reduction in streamflow

in the JRB was primarily caused by soil and water conservation measures” wasn’t preciseness. We have revised it.

Some previous studies also illustrate that the human activities mainly come from the soil and water conservation measures and water withdrawal. For example, Shi (2013) analyzed the 11 factors that impacted streamflow, and the climate change, water consumption and soil conservation measures were all the major causes of runoff reducing in the second half of the last century in the middle Yellow River; Zhao (2013) quantitatively analyzed the effects of climatic factors and human activities on runoff in Weihe River, and the results showed that the influence of human activities can be mainly attributed to urbanization, irrigated agriculture, and water and soil conversion projects.

Shi C, Zhou Y, Fan X, et al. A study on the annual runoff change and its relationship with water and soil conservation practices and climate change in the middle Yellow River basin [J]. *Catena*, 2013, 100: 31-41.

Zhao, G., Mu, X., Tian, P., Wang, F., Gao, P., 2013. Climate changes and their impacts on water resources in semiarid regions: a case study of the Wei River basin, China. *Hydrol. Process.* 27, 3852–3863.

25. P12765 L14-17 If only the total comprehensive effect of the soil and water conservation measure and irrigation water withdrawal was assessed in the study, how to get the result mentioned in P12765L2-3 that the soil and water conservation measures is the primarily reason for the human-induced streamflow reduction?

Response: I think this issue is similar to NO.24. According to the comment, we have revised the paper.

Conclusions

26. P12766 L3-7 I think this paragraph is a method introduction but not a conclusion.

Response: Thanks for the comment. We have removed this paragraph from “Sect.6 Conclusion”

27. P12766 L17-19 As mentioned in P12751 L15-16, water withdrawal has increased rapidly due to the increase of the population, industry and agricultural water demand. However, the conclusion is the maximum contribution value of human activities appeared in 1981-1990 due to the effects of soil and water conservation

measures and irrigation water withdrawal. Does the irrigation is the primary cause for the water withdrawal? If so, please elaborate it in the result and discussion section but not only in the conclusion section.

Response: In China, agricultural is the main water user. Hence, the irrigation is the primary cause for water withdrawal. However, we didn't quantitatively evaluate of the individual effect of industry and agricultural water withdrawal on the decreased streamflow, therefore, we revised the conclusion.

28. P12766 L20 What does the “which” represent?

Response: The “which” represents the average contribution ratios of human activities and climate variability.

Tables and Figures

29. Table 2 It should be noted that the potential evaporation is an estimated value. The observation period for the temperature should also be noted.

Response: Corrected.

30. Table 3 What do the parameters of C_v , C_s , E_0 and T mean? The presentation of parameters should be consistent in Table 2 and Table 3. The time scale of the mean value of the potential evaporation and temperature should also be noted.

Response: Corrected. C_v is the deviation coefficient; C_s is the skewness coefficient. E_0 and T respectively mean the potential evaporation and temperature.

31. Table 5, Table 6 What does the parameter of η_c represent? Please also elaborate the parameter of η_c in the text.

Response: The parameter of η_c and η_H respectively represent the contribution ratios of climate changes and human activities to streamflow.

32. Fig. 1. The legend for the Jinghe River and the Weihe River is same. As mentioned in the text, Jinghe River is the secondary tributary of the Yellow River, the largest tributary of the Weihe River in China. I suggest to label the Yellow River and Weihe River in the Fig. 1.

Response: Corrected.

33. Fig. 2 No scale mark.

Response: Corrected

34. Fig. 4 It seems that the temperature values during the period from 2000 to 2010 are missed.

Response: Corrected.

35. Fig. 5 The such-titles are mismatch with the sub-figures of (b) and (c). Please check it.

Response: Corrected.

Assessing the impact of climate variability and human activities on streamflow variation

J. Chang, H. Zhang, Y. Wang, and Y. Zhu

State Key Laboratory Base of Eco-hydraulic Engineering in Arid Area, Xi'an University of
Technology, Xi'an 710048, China

ABSTRACT

Water resources in river systems have been changing under the impact of both climate variability and human activities. Assessing the respective impact on decadal streamflow variation is important for water resource management. By using an elasticity-based method and calibrated TOPMODEL and VIC hydrological models, we quantitatively isolated the relative contributions that human activities and climate variability made to decadal streamflow changes in Jinghe basin, located in the northwest of China. This is an important watershed of Shaanxi Province that supplies drinking water for a population of over 6 million people. The results showed that the maximum value of the moisture index (E_0/P) was 1.91 and appeared in 1991–2000, and the decreased speed of streamflow was higher since 1990 compared with 1960–1990. The average annual streamflow from 1990 to 2010 was reduced by 26.96% compared with the multi-year average value (from 1960 to 2010). The estimates of the impacts of climate variability and human activities on streamflow decreases from the hydrological models were similar to those from the elasticity-based method. The maximum contribution value of human activities was 99% when averaged over the three methods, and was appeared in 1981–1990 due to the effects of soil and water conservation measures and irrigation water withdrawal. Climate variability made the greatest contribution to streamflow reduction in 1991–2000, the values of which was 40.4%. We emphasized various source of errors and

24 uncertainties that may occur in the hydrological model (parameter and structural uncertainty) and
25 elasticity-based method (model parameter) in climate change impact studies.

26 Keywords: Streamflow variation, Human activities, Climate variability, VIC model,
27 TOPMODEL, Climate elasticity model

28

29 **1. Introduction**

30 Catchment hydrology and water resources are driven by climate and strongly
31 modulated by human activities. Climate variability affects catchment streamflow,
32 chiefly through precipitation and the variability of potential evaporation ([Scanlon et al.,](#)
33 [2007](#); [Chien et al., 2013](#); [Ward et al., 2009](#); [Chang et al., 2010](#)). Human activities
34 include land use/cover change, reservoir operations, and direct water extraction from
35 surface-water and groundwater, all of which can alter river streamflow. It is important
36 to separate and quantify the effects of climate variability and human activities so that
37 they can be used for land use planning, water extraction and water resource
38 management. With the increasing scarcity of water resources, hydrologists, decision
39 makers and policy makers have paid considerable attention to how much of the
40 observed change in annual streamflow can be attributed to climate variability and
41 human activities ([Zhang et al., 2008](#); [Tomer and Schilling, 2009](#); [Roderick and](#)
42 [Farquhar, 2011](#); [Destouni et al., 2013](#)).

43 Catchment experiments are very useful to determine the influence of vegetation
44 change on the water balance; however, they are often limited to small scales. A number
45 of catchment afforestation and deforestation studies have been conducted. Most of the
46 results indicated that catchment streamflow significantly decreased after afforestation

47 and increased after deforestation (Van Lill et al., 1980; Zhang et al., 2001; Tuteja et al.,
48 2007). Two other main approaches, process-based and statistic based, were generally
49 used. The process-based method uses hydrological models to quantify the contribution
50 of climate variability to streamflow change by varying the meteorological inputs for
51 fixed land use/cover conditions (Xu et al., 2013; Petchprayoon et al., 2010; Lin et al.,
52 2010; Tesfa et al., 2014; Zhang et al., 2012). Statistical methods for identifying the
53 contributions of climate and human impacts on runoff were also used, especially in
54 regions where long-term climate and hydrological data were available (Hamed, 2008;
55 Notebaert et al.2011; Renner et al. 2012; Roudier et al. 2014). Among the statistical
56 methods, streamflow elasticity was commonly used to quantify the influence of changes
57 in precipitation and potential evapotranspiration on streamflow (Sankarasubramanian
58 et al., 2001; Chiew, 2006; Fu et al., 2007; Roderick and Farquhar, 2011). Streamflow
59 elasticity can be obtained non-parametrically from observations or by employing a
60 parametric model, such as the Budyko hypothesis or other models. The Budyko
61 hypothesis was widely used, as it was an easy method with a limited requirement for
62 climate data (Donohue et al. 2007; Liu et al., 2009; Wang et al., 2011, 2013).

63 Climate change and human activities have had tremendous impact on the water
64 resources of China's highly urbanized regions. One such river basin is the Jinghe River,
65 which is the secondary tributary of the Yellow River, the largest tributary of the Weihe
66 River in China, with an area of 45,400 km² and an average annual natural streamflow
67 of 12.3×10⁸ m³. This is an important watershed of Shaanxi Province that supplies
68 drinking water for a population of over 6 million people. The area is an important

69 economic center of Shaanxi province in China, and the water shortage became a
70 bottleneck for economic progress. Human activities, such as water withdrawal, soil and
71 water conservation projects, have become extensive in the Jinghe River during the last
72 several decades. Climate change studies in the Yellow River basin reported warming
73 trends at a rate of 1.28 °C/50 years, while the average precipitation dropped by
74 approximately 8.8% over the second half of the 20th century (Yang et al, 2004). A
75 combination of these effects reduced the streamflow (Gao et al. 2013; Chang et al,
76 2015). Few studies were devoted to use the methods of elasticity model together with
77 hydrological model to quantitatively analyze the contributions of climate variability and
78 human activities to streamflow variation in the Jinghe River basin.

79 The aims of this study were to: 1) present a generic framework that investigate the
80 impact of climate variability and human activities on streamflow using the concept of
81 streamflow elasticity and hydrological models, the TOPMODEL and VIC models,
82 which are fundamentally different in regard to their representation of streamflow
83 generation; and 2) compare these methods. The elasticity based method only provides
84 results at a mean annual time scale, whereas the hydrological modeling results are at a monthly
85 and daily scale, and they are aggregated to the mean annual time scale for comparison with
86 those obtained from the statistical method.

87 The Jinghe River Basin (JRB) was chosen as the study area, which has presented a
88 significantly decreasing trend of annual streamflow since 1990 (Chang et al, 2014; Du
89 and Shi, 2012). This paper is organized as follows: Sect. 2 describes the study area and
90 data sources; Sect.3 is devoted to introduce the methods used; Sect. 4 provides

91 hydrological modeling and the elasticity method results; Sect. 5 compares the results from
92 the hydrological modeling with the elasticity-based method; and Sect. 6 discusses
93 several conclusions generated from the present study.

94 **2. Study area and data**

95 The JRB (E106°14' ~ 108°42' , N34°46' ~ 37°19') is located in semiarid area in
96 China and is approximately 455 km long, with a drainage area of 45400 km² (Fig. 1).
97 The climate is temperate, with cool, dry winters and hot summers, and the mean annual
98 temperature is in the 7.8-13.5 °C range across the basin. The mean annual precipitation
99 is approximately 514 mm, 80% of which falls between June and October, and the mean
100 annual potential evapotranspiration is 870 mm. The precipitation and streamflow both
101 have strong inter-annual and intra-annual variabilities. The seasonal variation of
102 streamflow is similar to that of precipitation. The streamflow between July and October
103 is approximately 65% of the mean annual streamflow. Zhangjiashan station is the
104 downstream hydrometric station on the main stream of the Jinghe River.

105 Human activities have become extensive in the JRB during the last several decades.
106 Water withdrawal has increased rapidly due to the increase of the population, industry
107 and agricultural water demand. Thick and highly erodible loess, unevenly distributed
108 rainfall, and the relatively high intensity of rainstorms have led to high soil loss rates
109 across the basin. To reduce soil loss, soil and water conservation measures have been
110 undertaken since the 1970s, which have resulted in an increase in vegetation cover.
111 Therefore, climate variability combined with human activities has contributed to the
112 decrease of the streamflow in the JRB (Chang et al, 2014; Du and Shi, 2012).

113 **Fig. 1.** Location of hydrological and meteorological stations along the Jinghe
114 River

115 In this study, the catchment information data set, including the catchment
116 boundary and runoff ratio, was from the Ministry of Water Resources of the People's
117 Republic of China. The daily, monthly, and annual climate variables and observed
118 streamflow were used. The daily meteorological data, including precipitation, air
119 temperature, sunshine hours, relative humidity, and wind speed, of ten stations during
120 1960–2010 were collected from the China Meteorological Administration. The monthly
121 and annual precipitation was then established from the collected data, and annual
122 maximum, annual minimum, and multi-annual mean air temperature values were then
123 calculated according to the daily data. The monthly potential evaporation was
124 calculated according to the monthly wind speed, sunshine hours, relative humidity and
125 air temperature using the Penman-Monteith method. The daily streamflow data of the
126 Zhangjiashan hydrological station for the same period were gathered from the Shaanxi
127 Hydrometric and Water Resource Bureau. The DEM data were obtained from the
128 SRTM 30 m Digital Elevation Data. The soil data were extracted from the FAO two-
129 layer 5-min 16-category global soil texture maps. Figure 1 also shows the location of
130 the meteorological stations and hydrological station in the basin.

131 **3. Methodology**

132 **3.1. Framework of Analysis**

133 The historic streamflow series can be split into two subseries according to the
134 streamflow break year, and human activities in the recorded years prior to the break
135 year can be negligible. The recorded years prior to this break year were defined as the

136 baseline period, while the recorded years after this break year were defined as the
137 changed period. The difference between the mean annual streamflow during the
138 changed period (Q_2) and the mean annual streamflow during the baseline period (Q_1)
139 represent the total change of the streamflow (ΔQ) after the break year. The ΔQ can be
140 regarded as a function of climatic variables and the integrated effects of topography,
141 soil, land use/land cover and human activities, such as water withdrawing. Under the
142 assumption that the topography and soil of the study area did not vary during the study
143 period, ΔQ was referred to as a combination of climate variability and human activities
144 and can be estimated as the formulation:

$$\Delta Q = Q_2 - Q_1 \quad (1)$$

145 where ΔQ is the total change in the mean annual streamflow and Q_1 and Q_2 are the
146 average annual streamflows before and after an abrupt change, respectively.
147

148 The total change in the mean annual streamflow can be estimated as:

$$\Delta Q = \Delta Q_C + \Delta Q_H \quad (2)$$

149 where ΔQ_C and ΔQ_H are the changes in the mean annual streamflow due to climate
150 and human activities, respectively.
151

152 3.2 Climate Elasticity Model for ΔQ_C

153 The concept of streamflow elasticity was first introduced by [Schaake \(1990\)](#) to
154 evaluate the sensitivity of streamflow to climate change. It represents the proportional
155 change in streamflow divided by the proportional change in a climatic variable (X),
156 such as precipitation or potential evapotranspiration, and is expressed as:

$$\varepsilon = \frac{\partial Q/Q}{\partial X/X} \quad (3)$$

157 Thus, precipitation elasticity and evapotranspiration elasticity of streamflow were
158

159 defined by [Schaake \(1990\)](#) as:

$$160 \quad \varepsilon_P(P, Q) = \frac{dQ/Q}{dP/P} = \frac{dQ}{dP} \frac{P}{Q} \quad (4)$$

$$161 \quad \varepsilon_{E_0}(E_0, Q) = \frac{dQ/Q}{dE_0/E_0} = \frac{dQ}{dE_0} \frac{E_0}{Q} \quad (5)$$

162 where P , E_0 and Q are precipitation, potential evapotranspiration and streamflow,
163 respectively. ε_P and ε_{E_0} are the elasticity of streamflow with respect to P and E_0 ,
164 respectively. Changes in these factors could lead to streamflow variation, and the
165 relationship can be estimated as ([Milly and Dunne, 2002](#)):

$$166 \quad \Delta Q_C = (\varepsilon_P \Delta P/P + \varepsilon_{E_0} \Delta E_0/E_0)Q \quad (6)$$

167 where ΔP and ΔE_0 are the changes in precipitation and potential evapotranspiration,
168 respectively, and $\varepsilon_P + \varepsilon_{E_0} = 1$. To estimate ΔQ_C using Eq. (6), the estimate of the
169 precipitation elasticity of streamflow ε_P is needed. In this paper, the Budyko
170 hypothesis was used to estimate ε_P .

171 The Budyko hypothesis ([Yang et al., 2008](#); [Teng et al., 2012](#); [Wang et al., 2015](#))
172 produces a simplified, but powerful, coupled water-energy balance method. It is a
173 holistic approach that assumes that water balance is controlled by water availability and
174 atmospheric demand. The water availability can be approximated by precipitation. The
175 atmospheric demand represents the maximum possible evapotranspiration and is often
176 equated with potential evapotranspiration. The role of the landscape properties on the
177 mean annual water balance is mainly implicit and is deemed to be subservient to the
178 dominant role of climate. In some formulations of the Budyko formulation, the role of
179 the landscape is represented by a separate, lumped parameter ([Yu et al., 2014](#); [Donohue
180 et al., 2007](#)), which is nevertheless estimated empirically. According to the long-term

181 water balance equation ($Q = P - E_a$) and the Budyko hypothesis, the actual
182 evapotranspiration (E_a) is a function of the aridity index ($\Phi = E_0/P$) and the precipitation
183 and potential evapotranspiration elasticity of streamflow can be expressed as (Arora,
184 2002; Dooge et al., 1999):

$$185 \quad \varepsilon_P = 1 + \Phi F'(\Phi)/(1 - F(\Phi)) \quad \text{and} \quad \varepsilon_P + \varepsilon_{E_0} = 1 \quad (7)$$

186 A couple of mathematical functions were proposed to represent the Budyko
187 hypothesis (e.g., Fu, 1996; Milly, 1993). We used the Budyko formulation of Fu (1981)
188 who combined a dimensional analysis with mathematical reasoning and developed
189 analytical solutions for the mean annual actual evapotranspiration:

$$190 \quad F(\Phi) = 1 + \Phi - (1 + \Phi^w)^{1/w} \quad (8)$$

191 where $F(\Phi)$ is a function proposed by the Budyko, which not only satisfies the
192 boundary conditions under the land surface evapotranspiration but also remains
193 independent from the balance equation of hydrothermal coupling (the water balance
194 and energy balance). w is a model parameter with range $(1, \infty)$, which is related to
195 vegetation type, soil hydraulic property, and topography (Fu, 1996). w was set to
196 2.0, according to Li et al. (2013).

197 3.3 Modeling-Based Approach for ΔQ_C or ΔQ_H

198 Hydrological models can also be used to assess the impact of climate change and
199 human activities on streamflow. A hydrological model was calibrated and validated to
200 estimate ΔQ_C and ΔQ_H by using the data from the baseline period. The model was run
201 using climate data (e.g., precipitation and temperature) during the changed period with
202 human activities (i.e., land use and management) and during the baseline period. ΔQ_C
203 was estimated as the difference between the mean annual average of simulated

204 streamflow during the changed period and the mean annual average of simulated
205 streamflow during the baseline period. ΔQ_H was estimated as the difference between
206 the mean annual average of the simulated streamflow during the changed period and
207 the mean annual average of the observed streamflow during the changed period.

208 In this study, two hydrological models, the TOPMODEL and VIC model, were used
209 to investigate the effects of climate variability and human activities on streamflow.
210 TOPMODEL (Beven and Kirkby, 1979) is a semi-distributed variable contributing area
211 hydrological model. It is based on simple physical reasoning and assumes that there is
212 a steady transfer of water in the saturated zone along hillslopes, with a water table nearly
213 parallel to the ground surface. It considers two stream flow sources: (shallow)
214 groundwater and saturation overland flow. The model assumes an exponential decay of
215 soil transmissivity with increasing water table depth, and it considers two main
216 parameters for the dynamics of the saturated store: the recession parameter m [L] and
217 the average soil transmissivity at saturation T [LT^{-1}]. The classical form for the
218 topographic index that follows from the exponential assumption, $\lambda_i = \ln(a/\tan b)$
219 was used, where a is the drained area per unit length of the contour curve and b is
220 the topographic gradient. All of the points in the catchment with the same topographic
221 index were predicted as having the same deficit, i.e., they were considered to be
222 hydrologically similar. The original TOPMODEL had four parameters: the maximum
223 allowable root storage deficit (SR_{max}), the transmissivity of the soil in the saturated state
224 (T), the maximum moisture max deficit (S_{zm}), and the recharge delay parameter (T_d).
225 Since the early 1990s, TOPMODEL has widely been applied to watersheds all over the

226 world because it can provide spatially distributed hydrological information with
227 available input requirements (e.g., Digital Elevation Model (DEM) data) (Seibert et al.,
228 1997, Chen and Wu, 2012; Furusho et al., 2013). Some studies also applied
229 TOPMODEL in semi-arid area basins, such as the Yellow River in China, and the
230 results showed that this model was applicable over a wide range of environments
231 (Xiong et al., 2004; Boston et al., 2004; Gumindoga et al., 2015).

232 The VIC model is a large-scale hydrological model that was originally developed
233 at the University of Washington (Liang et al., 1994; Grimson et al, 2013; Gao et al.,
234 2011). The hydrological processes of the model include the interaction of the
235 atmosphere with underlying vegetation and soils, where dynamic water and energy
236 fluxes are considered. One distinguishing characteristic of the VIC model is that it
237 represents the sub-grid spatial heterogeneity of precipitation with the sub-grid spatial
238 variability of soil infiltration capacity. A variable infiltration curve is used to represent
239 the sub-grid variability of the soil infiltration capability under different land cover and
240 soil types. Three types of potential evaporation are considered in the model: potential
241 evaporation from the canopy layer of each vegetation class, transpiration from each of
242 the vegetation classes, and bare soil potential evaporation. We used six parameters in
243 the calibration of the VIC model. These included three baseflow parameters: D_m , W_s ,
244 and D_s ; the variable soil moisture capacity curve parameter: b ; and two parameters, d_2
245 and d_3 , that controlled the thickness of the second and third soil layer, respectively. The
246 VIC model was successfully applied to assess the impact of climate change on
247 hydrology and water resources in China (Wang et al. 2010; Bao et al. 2012; Su and Xie,

248 2003; Liu et al. 2013).

249 We obtained the break points of precipitation and streamflow series in the JRB by
250 means of a sequential cluster analysis method, and the break points appeared in 1968
251 and 1970 respectively (Fig. 2), so we used 1960-1970 as the baseline period for this
252 study. The TOPMODEL and VIC model were calibrated using the historical data from
253 1960 to 1966 and validated against the observation during the period of 1967 to 1970.
254 During the calibration, adjustments were made to minimize the sum of squares of the
255 difference between the modeled and recorded monthly streamflow. Nash–Sutcliffe
256 efficiency coefficients (NSE) and relative Water Balance Error percentage (WBE) were
257 used for the model assessment using the observed data and model estimates.

$$258 \quad NSE = 1 - \frac{\sum_{i=1}^N (Q_{o,i} - Q_{s,i})^2}{\sum_{i=1}^N (Q_{o,i} - \bar{Q}_o)^2} \quad (9)$$

$$259 \quad WBE = \left| \frac{100 * (\sum_{i=1}^N Q_{s,i} - \sum_{i=1}^N Q_{o,i})}{\sum_{i=1}^N Q_{o,i}} \right| \quad (10)$$

260 Where $Q_{o,i}$ is the observed streamflow of period i , $Q_{s,i}$ is the simulated streamflow
261 of period i , and \bar{Q}_o is the mean of observed streamflow.

262 **Fig. 2.** The abrupt change points of precipitation and streamflow in the JRB with Sequential cluster.

263 **4. Results**

264 **4.1 The analysis of streamflow, precipitation, potential evaporation and** 265 **temperature**

266 The regional average precipitation, potential evaporation and temperature in the
267 JRB during 1960-2010 were calculated using the Thiessen polygon method of ArcGIS
268 9.3, according to the corresponding data of ten hydrometeorology stations.

269 The annual observed precipitation in the JRB and streamflow at Zhangjiashan
270 station both showed a statistically decreasing trend (Fig. 3), while the streamflow had

271 a larger decrease. The values of the regression slope were -1.44 and -0.58. The multi-
272 year average streamflow (from 1960 to 2010) was 37.03 mm, and the average annual
273 streamflow was 43.47 mm from 1960 to 1990, which meant that the streamflow from
274 1960 to 1990 increased by 17.39% compared with the multi-year average streamflow.
275 The average annual streamflow was 27.05 mm during 1991-2010 and was reduced by
276 26.96% compared with the multi-year average value; therefore, the speed of the
277 streamflow decrease was higher since 1990. The three-year moving curve showed that
278 precipitation and streamflow fluctuation was similar, which indicated that precipitation
279 was the main source of streamflow. The statistical results of precipitation, streamflow
280 and the runoff coefficient in JRB are listed in Table 1. The maximums of precipitation
281 and streamflow appeared at the same time in 1964; however, the minimum of
282 precipitation and streamflow occurred in different years (1997 and 2009), which
283 resulted from water withdrawal and other reasons, such as changes in groundwater. The
284 precipitation and streamflow during the flood season (from July to October) accounted
285 for 64.21% and 66.80%, respectively, and the proportion of the dry period (from
286 November to March of next year) was 7.46% and 18.22%, respectively. The proportion
287 of precipitation that became runoff was low, with a mean annual runoff ratio of 0.05,
288 but increased during the wet years. The runoff ratios during the wet year and wet season
289 were 0.08 and 0.06, respectively.

290 The result of Mann–Kendall’s test showed the same decreasing trend for the
291 annual precipitation and streamflow in JRB from 1960 to 2010. The Z value of
292 streamflow and precipitation was -4.26 (confidence level was 99%) and -1.39

293 (confidence level was 90%), respectively, which meant that the decreasing trend for
294 streamflow was significant, but was insignificant for precipitation at a = 0.05 level.

295 **Fig. 3.** Changes of the annual streamflow and precipitation of the JRB.

296
297 **Table1** Characteristics of the inter-annual streamflow and precipitation of the JRB.

298 Table 2 shows the monthly and seasonal potential evaporation and temperature in
299 the JRB, which indicated that the potential evaporation (122 mm) and temperature
300 (20.7 °C) in summer were much higher than the other three seasons, and the maximum
301 values for the potential evaporation and temperature appeared in June and July,
302 respectively. The inter-annual variation and characteristic values of the potential
303 evaporation and temperature are shown in Fig. 4 and Table 3. The mean annual potential
304 evaporation in the 1980s (822 mm) decreased compared with the values from the 1960s
305 (861 mm) and started to increase slowly in the 1990s (973 mm). The temperature
306 showed a slight upward trend in the 1970s and 1980s and had a sharp upward trend in
307 the 1990s era. The Z values of potential evaporation and temperature for Mann–
308 Kendall’s test were 0.4 and 4.12, respectively, which meant that the potential
309 evaporation presented an insignificant increasing trend, but the temperature had a
310 significant increasing trend.

311 **Table 2** The average monthly potential evaporation and temperature values of the JRB.

312
313 **Table 3** Statistical values of the potential evaporation and temperature of the JRB.

314
315 **Fig. 4.** Changes of the annual potential evaporation and temperature of the JRB.

316 317 **4.2 Climate Elasticity Model Results**

318 To assess the impact of climate variability on streamflow, the climate elasticity of
319 streamflow was calculated using Eqs. (3) – (8) based on the annual precipitation and

320 annual potential evapotranspiration of the period from 1971 to 2010. Table 4
321 summarizes the annual precipitation (P), potential evapotranspiration (E_0),
322 precipitation elasticity (ε_P), evapotranspiration elasticity (ε_{E_0}) of streamflow for
323 different periods, and percentage change in streamflow results for different periods
324 when using the elasticity-based approaches. The variation of ε_P was between 1.45 and
325 1.52, while the variation of ε_{E_0} was between -0.45 and -0.52. As shown in Table 4,
326 for the period of 1971 to 2010, the values of ε_P and ε_{E_0} obtained were 1.48 and -0.48,
327 respectively. The results indicated that a 10% decrease in precipitation would result in
328 a 14.8% drop in streamflow, while a 10% decrease in potential evapotranspiration
329 would induce a 4.8% increase of streamflow. According to Eq. (3), with the calculated
330 ε_P and ε_{E_0} , it was estimated that the 60.1 mm decrease in precipitation in 1971–2010
331 might have decreased the streamflow by 40.9 mm; meanwhile, the 7.3 mm increase in
332 the potential evapotranspiration may have caused a 5.1 mm decrease in streamflow.

333 The reductions in streamflow from 1971 to 2010 due to climate variability ranged
334 between 7.5% and 29.9%, with a median of 19.3%, for the JRB when using the Budyko
335 framework method. The maximum and minimum values of the moisture index (E_0/P ,
336 Willmott, C.J. and Feddema, J.J., 1992) were 1.91 and 1.53, respectively, and appeared
337 in 1991–2000 and 1981–1990, respectively. Compared with the 1960–1970 baseline
338 period, the reductions in ΔQ for 1991–2000 and 1981–1990 were $5.7 \times 10^8 \text{ m}^3$ and 4.0
339 $\times 10^8 \text{ m}^3$, respectively, with climate variability making the greatest and smallest
340 contributions (i.e., 29.9% and 7.5%, see Table 4).

341

342 **Table 4** The impact of climate variability and human activities on the streamflow with the

climate elasticity model.

4.3 Hydrological model calibration and validation

During the hydrological model simulation, the digital elevation quadrangles at a 30-m resolution in study area were used (Fig. 5). In TOPMODEL, several sub-basins were delineated according to the flow accumulation by means of ArcGIS, and the flow direction, flow accumulation were extracted in ArcGIS to calculate the topographic index-area ratio of sub-basin. The monthly precipitation, potential evapotranspiration and observed streamflow acted as the input data. Figure 6 shows the simulated and recorded streamflow for the calibration and validation periods. A calibrated VIC model was also employed to separate the hydrological impacts of land use change and climate change. The VIC model was used for the streamflow simulation at a 0.5 spatial and daily temporal resolution in the JRB (Fig. 5). Figure 6 shows the simulated and observed streamflows for the calibration and validation periods, with outputs computed on a monthly basis.

Fig. 5. (a) Elevation maps of the study area at a 30-m resolution. (b) Grid of the VIC model. (c) Sub-basin of TOPMODEL.

Fig. 6. The simulated and observed streamflow for TOPMODEL and the VIC model.

(a) Calibration period. (b) Validation period.

In the scatter plots in Fig. 7, the observed monthly streamflow was plotted along the x axis, and the model simulated streamflows (calibration and validation) were plotted along the y axis. The scatter plots in Fig. 7 showed that both the hydrological models performed reasonably well in the model calibration with high NSE values and low WBE values. The correlation of the simulated streamflow and measured streamflow (R) was higher during the calibration period compared with the validation

369 period. The observed and simulated streamflow over the non-calibration period were
370 compared to determine the suitability of the model for this study. The NSE, WBE and
371 R of TOPMODEL are 0.79, 2.1% and 0.987 in the calibration period, and are
372 respectively 0.78, 9.2% and 0.944 in the validation period. The NSE, WBE and R of
373 VIC model are 0.77, 3.5% and 0.944 in the calibration period, and are respectively 0.83,
374 4.7% and 0.940 in the validation period. The NSE, WBE and R values during the
375 validation period (see Fig. 7) suggested that both the rainfall–runoff models and the
376 calibration method used in this study were robust for the calibrated model to be used
377 over an independent simulation period adequately. Additionally, the results justified the
378 suitability of the models applied for assessing the change in streamflow due to climate
379 variability and human activities.

380 **Fig. 7.** Comparison of the observed and modeled monthly streamflows for the calibration and
381 validation periods.

382 **4.4 Hydrological model simulation results**

383 The calibrated model parameters for both the models from the baseline periods of
384 1960 to 1970 were used with the meteorological time series to simulate the streamflow
385 for the changed period of 1971 to 2010 and to investigate the effects of climate
386 variability and human activities. The scatter plots in Fig. 8 and Fig. 9 show the
387 comparison of the simulated and observed monthly and annual streamflow time series
388 for the JRB for the entire modeling period (1971–2010) for TOPMODEL and the VIC
389 model, respectively.

390 The model simulation results showed that streamflow had a strong response to the
391 environmental change after 1970. In the scatter plots in Fig. 8, the simulated monthly

392 streamflow values are mostly above the 1:1 line, indicating that the simulated
393 streamflow was much higher than the observed streamflow for most of the months. The
394 number of the years that the simulated streamflow was higher than the observed
395 streamflow was 26 from 1970 to 2010 for TOPMODEL, and the number was 25 for
396 VIC model. Additionally, most of the years appeared before 1990 or after 2005 for both
397 of the models, and in the rest of the years the simulated streamflow was similar or lower
398 to the observed value. The effect of climate variability was eliminated from the
399 simulations for the changed periods by using the actual observed climate to drive the
400 calibrated models. The difference in the observed and simulated streamflows during the
401 changed period was due to the difference in land cover and other human activities. The
402 results indicated that human activities caused significant reductions in streamflow, and
403 these results were consistent with other studies (Chang et al., 2014; Tang et al., 2013;
404 Zhan et al., 2014).

405 **Fig. 8.** Comparison of the observed and modeled monthly streamflow in 1971-2010.

406 (a)TOPMODEL. (b) VIC model.

407
408 **Fig. 9.** Time series of the observed and modeled annual streamflow for the entire modeling period.

409 **4.5 Influence of human activities and climate variability.**

410 To separate and quantify the effects of human activities on streamflow after 1970,
411 the simulated streamflows for the two models were compared against the observed
412 values during the baseline and changed periods (methodology details in Sect. 3.1). The
413 differences in the observed streamflow values during the baseline and changed periods
414 were caused by the differences in climatic conditions and human activities. Tables 5
415 and 6 summarize the mean annual statistics of the observed and simulated streamflow

416 for the different periods of the 1970s, 1980s 1990s and 2000s. The third column
417 provides the values for ΔQ , which were the differences between the observed
418 streamflow (Q_B) during the changed periods and the baseline. The fourth column shows
419 the simulated streamflow (Q_S) for the changed periods when using climate and
420 calibrated parameter values from the baseline period. ΔQ_H was the difference between
421 Q_B and Q_S for the changed periods, and ΔQ_C was the difference between Q_S for the
422 changed period and Q_B of the baseline. η_C and η_H were the contribution ratios of
423 climate change and human activities to streamflow, respectively.

424

425 **Table 5** The impact of climate variability and human activities on the streamflow with TOPMODEL.

426 **Table 6** The impact of climate variability and human activities on the streamflow with the VIC
427 model.

428 The results showed that the average annual streamflow for 1971-2010 (12.3×10^8
429 m^3) was less than that of the baseline period ($18.3 \times 10^8 \text{ m}^3$), which meant that the
430 recorded streamflow in the JRB markedly decreased over the past few decades. The
431 total reduction ΔQ in streamflow for the changed period of 1971 to 2010 (compared
432 to the baseline period) due to human activities and climate variability for the JRB were
433 $4.6 \times 10^8 \text{ m}^3$ and $1.4 \times 10^8 \text{ m}^3$ for the TOPMODEL, which was approximately 76.7% and
434 23.3% of the total reduction, respectively. The corresponding reductions were 4.7×10^8
435 m^3 (78.3%) and $1.3 \times 10^8 \text{ m}^3$ (21.7%) for the VIC model.

436 For the different periods of 1970s, 1980s, 1990s and 2000s, the reductions in
437 streamflow due to human activities were $5.6 \times 10^8 \text{ m}^3$ (81.2% of the total change), 3.8
438 $\times 10^8 \text{ m}^3$ (95% of the total change), $3.0 \times 10^8 \text{ m}^3$ (52.6% of the total change) and 6.1×10^8
439 m^3 (82.4% of the total change) for TOPMODEL model, respectively. For the VIC

440 model, the reductions in streamflow due to human activities for the 1970s, 1980s, 1990s
441 and 2000s were and $5.7 \times 10^8 \text{ m}^3$ (82.6% of the total change), $4.5 \times 10^8 \text{ m}^3$ (112.5% of the
442 total change), $3.2 \times 10^8 \text{ m}^3$ (56.1% of the total change) and $5.8 \times 10^8 \text{ m}^3$ (78.4% of the
443 total change), respectively. Compared to the baseline period of 1960 to 1970,
444 streamflow greatly decreased during 2001–2010. The change impacts (i.e., ΔQ_H and
445 ΔQ_C) in 2001–2010 were approximately 77.4% (ΔQ_H) and 22.6% (ΔQ_C) of the total
446 reduction when averaged over the two methods.

447 **5. Discussion**

448 **5.1 Results of comparing the three methods**

449 We used elasticity-based analyses, TOPMODEL and the VIC model, to isolate the
450 hydrological impact of human activities from that of climate variability. The climate
451 elasticity method is relatively simple and can easily be transplanted to other areas, and
452 it provides a general streamflow change with less data and parameters (Ma et al. (2010)).
453 On the contrary, the hydrological modeling method more precisely distinguishes the
454 streamflow change, such as the monthly change or daily change. In this paper, the three
455 methods were implemented independently at different time scales (climate elasticity
456 method based on the yearly scale, TOPMODEL based on the monthly scale and VIC
457 model hydrological simulation based on the daily scale (Peng D. Z., and Xu, Z. X.
458 2010)). For the whole JRB, the contribution ratios of climate variability in 1971-2010
459 were 23.3%, 21.7% and 19.3% from TOPMODEL, the VIC hydrological modeling
460 method and the elasticity method, respectively, and the mean contribution ratio was
461 21.4%. The most significant climate variability impacts were $2.7 \times 10^8 \text{ m}^3$ (47.4%),
462 $2.5 \times 10^8 \text{ m}^3$ (43.9%) and $1.7 \times 10^8 \text{ m}^3$ (29.9%) for TOMODEL, the VIC model and the

463 elasticity based model, respectively, appearing in the 1990s. The most significant
464 human activities impacts were $3.8 \times 10^8 \text{ m}^3$ (95%), $4.5 \times 10^8 \text{ m}^3$ (112.5%) and 3.7×10^8
465 m^3 (92.4%) for TOMODEL, the VIC model and the elasticity based model, respectively,
466 appearing in the 1980s. The analysis showed that the results from the two hydrological
467 models were similar to those from the commonly used elasticity-based approach.
468 Additionally, the results of the three methods showed that the significant climate
469 variability impacts appeared in the 1990s, and the significant human activities impacts
470 appeared in the 1980s. The precipitation and temperature are the dominant factors of
471 climate changes, and it is shown that the maximum decrease of precipitation appeared
472 in the 1990s compared with baseline period (1960s), and the minimum decrease was in
473 the 1980s (table 7). The temperature showed a significant increase in the 1990s, but an
474 insignificant increase in the 1980s. The changes of precipitation and temperature for
475 different decades verified that the significant climate variability impacts appeared in
476 the 1990s. We concluded that the three methods were in good agreement in terms of
477 the dominant contributor, i.e., human activities played a more important role in the
478 streamflow decrease than the change in climate in the JRB. The main result of this
479 research agreed with the findings of other studies in Northwest China. [Tang et al. \(2013\)](#)
480 used the climate elasticity method and the Soil and Water Assessment Tool (SWAT)
481 model to evaluate the impact of climate variability on streamflow in the Yellow River
482 basin, This two methods gave consistent results. [Zhan et al. \(2014\)](#) developed an
483 improved climate elasticity method based on the original climate elasticity method and
484 conducted a quantitative assessment of the impact of climate change and human

485 activities on the streamflow decrease in the Wei River basin. The results from the
486 improved climate elasticity method yielded a climatic contribution to the streamflow
487 decrease of 22-29% and a human contribution of 71-78%.

488 **Table 7** Changes of the inter-annual precipitation and temperature of the JRB.

489 There are still differences in terms of the magnitude of each attributor. Compared to
490 the results of the hydrological model, TOPMODEL and VIC model, the streamflow
491 variation caused by climate variability estimated from the elasticity-based methods was
492 smaller and that caused by human activities was larger, which agreed with the results
493 of [Li et al. \(2012\)](#) and [Sun et al. \(2014\)](#). Except for the annual precipitation change,
494 which was the most important factor in the streamflow change, the inter-annual and
495 intra-annual precipitation variability, as second order climate effects, could lead to a
496 significant change in streamflow. However, these second order climate effects cannot
497 be taken into account in the elasticity-based methods, while they can be considered in
498 the dynamic hydrological modeling method, which may partially explain the difference
499 in the results ([Potter and Chiew, 2011](#)).

500 **5.2. Errors and uncertainties with each approach**

501 The elasticity-based assessment of environmental change on streamflow has more
502 advantages than the hydrological modeling approach because it does not require
503 detailed spatial input data. In this paper, the elasticity coefficient (i.e., the sensitivity
504 coefficient of streamflow to climatic variable changes) was estimated. While it was
505 commonly suggested that catchment properties were spatially and temporally varied
506 and were influential on the streamflow of the watershed ([Roderick and Farquhar, 2011](#);
507 [Donohue et al., 2011](#)), the errors from both the model structure (Budyko equations) and

508 the model parameter in Fu's model (w), which we assumed to be temporally consistent,
509 caused the elasticity-based analysis to not be error-free.

510 For the hydrological model of TOPMODEL and the VIC model, due to the errors of
511 the model structure, input time series, and initial and boundary conditions, the
512 predictions of physically based distributed models commonly contained a certain
513 degree of uncertainty. For example, the higher resolution of the DEM (digital elevation
514 model), the smaller input time series scale and the optimal model parameters would
515 obtain better simulated results.

516 **5.3 The cause for streamflow change**

517 The results indicated that human activities were the dominant factors (approximately
518 80%) for the streamflow decrease in 1971–2010 in the study area. There were several
519 types of human activities that influenced streamflow, including water conservancy
520 projects, large hydraulic projects, and water withdrawal for industry and agricultural
521 demand. The human-induced reduction in streamflow in the JRB was primarily caused
522 by soil and water conservation measures and water withdrawal (Shi, 2013; Zhao, 2013).

523 From Table 8, it can be observed that the large-scale soil conservation area expanded
524 with time to prevent soil and water loss since the 1970s. As shown in Table 8, the
525 amount of afforestation and level terrace land steadily increased since 1970 and that the
526 amount of grass-planting land markedly increased since 1990. As of the 2000s, newly
527 increased soil and water conservation areas in the basin were composed of 2907 km² of
528 terrace land, 4773 km² of afforestation land, 1146 km² of grassland and 52 km² of
529 dammed land. These soil conservation practices intercept precipitation, change local

530 characteristics, improve the infiltration rate of water flow, slow down or retain the
531 streamflow, and consequently delay or even reduce streamflow. Additionally, during
532 the past few decades, there were dramatic increases in the population and the irrigated
533 area in the study area, which could have resulted in increased water withdrawal from
534 the river. The evaluation of the individual effects on the hydrological regime still poses
535 a challenge for hydrologists.

536
537 **Table 8** Cumulative area of soil and water conservation in JRB at the end of different years
538 (Unit:km²).
539

540 6. Conclusion

541 This paper investigated the impact of human activities and climate variability on
542 streamflow using observed data and three methods (an elasticity-based method, a
543 calibrated TOPMODEL and VIC model) for the JRB in China.

544 (1) The variability of streamflow, precipitation, potential evaporation and
545 temperature in the JRB was analyzed. The annual precipitation and streamflow both
546 showed a statistically decreasing trend, while the streamflow had a larger decrease, and
547 the decrease in speed was higher since 1990. The potential evaporation presented an
548 insignificant increasing trend; however, the temperature had a significant increasing
549 trend.

550 (2) The precipitation elasticity (ε_P) and evapotranspiration elasticity (ε_{E0}) of
551 streamflow for different periods were calculated using the Budyko formulation of Fu.
552 The results indicated that a 10% decrease in precipitation would result in a 14.8%
553 drop in streamflow, while a 10% decrease in potential evapotranspiration would

554 induce a 4.8% increase of streamflow.

555 (3) Compared to the baseline period of 1960 to 1970, streamflow in the JRB
556 greatly decreased during 2001–2010. Climate variability and human activities impacts
557 from the hydrological models were similar to those from the elasticity-based method.

558 (4) The maximum contribution value of human activities appeared in 1981-1990
559 due to the effects of soil and water conservation measures and water withdrawal for
560 industry and agricultural water demand, whereas climate variability made the greatest
561 contributions to the streamflow reduction in 1991–2000. The contribution ratios of
562 human activities and climate variability were 99% and 40.4% when averaged over the
563 three methods.

564

565 **Acknowledgments**

566 This research was supported by the Natural Science Foundation of China (51190093)
567 and Key Innovation Group of Science and Technology of Shaanxi (2012KCT-10).
568 Sincere gratitude is extended to the editor and the anonymous reviewers for their
569 professional comments and corrections.

570

571

572

573 **References**

574 Arora, V.K.: The use of the aridity index to assess climate change effect on annual runoff, *J. Hydrol.*,
575 265, 164–177, 2002.

576 Bao, Z., Zhang, J., Wang, G., Fu, G., He, R., Yan, X., Jin, J., Liu, Y., and Zhang, A.: Attribution
577 for decreasing streamflow of the Haihe River basin, northern China: Climate variability or

578 human activities, *J. Hydrol.*, 460–461, 117–129, doi.org/10.1016/j.jhydrol.2012.06.054, 2012.

579 Beven, K.J., and Kirkby, M.J.: A physically based variable contributing area model of basin
580 hydrology, *Hydrological Sciences Bulletin*, 24, 43-69 1979.

581 Boston, T., Xia, J., and Zhu, Y.: Pre-processing rainfall data from multiple gauges to improve
582 TOPMODEL simulation results in a large semi-arid region, *Hydrol. Process.*, 18, 2313–2325,
583 [doi:10.1002/hyp.5530](https://doi.org/10.1002/hyp.5530), 2004.

584 Chang, F.-J., Chang, L.-C., Kao, H.-S., and Wu, G.-R.: Assessing the effort of meteorological
585 variables for evaporation estimation by self-organizing map neural network, *J. Hydrol.*, 384,
586 118-129, 2010.

587 Chang, J.-X., Wang, Y., Istanbuluoglu, E., Bai, T., Huang, Q., Yang, D., and Huang, S.: Impact
588 of climate change and human activities on runoff in the Weihe River Basin, China, *Quatern.
589 Int.*, **380-381**, 169-179, 2015.

590 Chen, J. and Wu, Y.: Advancing representation of hydrologic processes in the Soil and Water
591 Assessment Tool (SWAT) through integration of the TOPographic MODEL (TOPMODEL)
592 features, *J. Hydrol.*, 420–421, 319–328, [doi:10.1016/j.jhydrol.2011.12.022](https://doi.org/10.1016/j.jhydrol.2011.12.022), 2012.

593 Chien, H., Yeh, P. J.-F., and Knouft, J. H.: Modeling the potential impacts of climate change on
594 streamflow in agricultural watersheds of the Midwestern United States, *J. Hydrol.*, 491, 73–88,
595 [doi:10.1016/j.jhydrol.2013.03.026](https://doi.org/10.1016/j.jhydrol.2013.03.026), 2013.

596 Chiew, F.H.S.: Estimation of rainfall elasticity of streamflow in Australia, *Hydrologic Science
597 Journal* 51, 613–625, 2006.

598 Destouni G, Jaramillo F, and Prieto C.: Hydroclimatic shifts driven by human water use for food
599 and energy production, *Nat Clim Change* 3, 213-217, doi.org/10.1038/nclimate1719, 2013.

600 Donohue, R.J., Roderick, M.L., and McVicar, T.R.: On the importance of including vegetation
601 dynamics in Budyko's hydrological model, *Hydro. Earth Syst. Sci.*, 11, 983–995, [doi:](https://doi.org/10.5194/hess-11-983-2007)
602 [10.5194/hess-11-983-2007](https://doi.org/10.5194/hess-11-983-2007), 2007.

603 Donohue, R.J., Roderick, M.L., and McVicar, T.R.: Assessing the differences in sensitivities of
604 runoff to changes in climatic conditions across a large basin, *J. Hydrol.*, 406, 234–244,
605 doi.org/10.1016/j.jhydrol.2011.07.003, 2011.

606 Dooge, J.C., Bruen, M., and Parmentier, B.: A simple model for estimating the sensitivity of
607 runoff to long-term changes in precipitation without a change in vegetation, *Adv. Water*
608 *Resour.*, 23, 153–163, 1999.

609 Du J., and Shi C.: Effects of climate factors and human activities on runoff of the Weihe River in
610 recent decades. *Quaternary International*. 282, 58-65, 2012

611 Fu, B.P.: On the calculation of the evaporation from land surface, *Chinese Journal of Atmospheric*
612 *Sciences*, 5, 23–31, 1981.

613 Fu, B.P.: On the calculation of evaporation from land surface in mountainous areas, *Scientia*
614 *Meteorologica Sinica* 6, 328– 335, 1996.

615 Fu, G., Charles, S.P., and Chiew, F.S.H.: A two-parameter climate elasticity of streamflow index
616 to assess climate change effects on annual streamflow, *Water Resour. Res.* 43, W11419.
617 [doi:10.1029/2007WR005890](https://doi.org/10.1029/2007WR005890), 2007.

618 Furusho, C., Chancibault, K., and Andrieu, H.: Adapting the coupled hydrological model ISBA-
619 TOPMODEL to the long-term hydrological cycles of suburban rivers: evaluation and sensitivity
620 analysis, *J. Hydrol.*, 485, 139–147, 2013.

621 Gao, H., Bohn, T.J., Podest, E., McDonald, K.C., and Lettenmaier, D.P.: On the causes of the

622 shrinking of lake Chad, *Environ. Res. Lett.* 6, 034021, [doi:10.1088/1748-9326/6/3/034021](https://doi.org/10.1088/1748-9326/6/3/034021),

623 2011.

624 Gao, P., Geissen, V., Ritsema, C. J., Mu, X.-M., and Wang, F.: Impact of climate change and

625 anthropogenic activities on stream flow and sediment discharge in the Wei River basin, China,

626 *Hydrol. Earth Syst. Sci.*, 17, 961–972, [doi:10.5194/hess-17-961-2013](https://doi.org/10.5194/hess-17-961-2013), 2013.

627 Grimson, R., Montroull, N., Saurral, R., Vasquez, P., and Camilloni, I.: Hydrological modelling of

628 the Iber á Wetlands in southeastern South America, *J. Hydrol.*, 503, 47–54,

629 [doi:10.1016/j.jhydrol.2013.08.042](https://doi.org/10.1016/j.jhydrol.2013.08.042), 2013.

630 Gumindoga, W., Rientjes, T. H. M., Haile, A. T., and Dube, T.: Predicting streamflow for land

631 cover changes in the Upper Gilgel Abay River Basin, Ethiopia: a TOPMODEL based approach,

632 *Phys. Chem. Earth*, 76-78, 3-15, 2014.

633 Hamed, K.H.: Trend detection in hydrologic data: the Mann–Kendall trend test under the scaling

634 hypothesis, *J. Hydro.* 349, 350–363, 2008.

635 Li, D., Pan, M, Cong, Z., and Wood, E.: Vegetation control on water and energy balance within

636 the Budyko framework, *Water Resour. Res.* 49, 969-976, [doi: 10. 1002/wrcr.20107](https://doi.org/10.1002/wrcr.20107), 2013.

637 Li, H., Zhang, Y., Vaze, J., and Wang, B.: Separating effects of vegetation change and climate

638 variability using hydrological modelling and sensitivity-based approaches, *J. Hydro.*, 420–421,

639 403–418, 2012.

640 Liang, X., Lettenmaier, D.P., Wood, E.F., and Burges, S.J.: A simple hydrologically based model

641 of land surface water and energy fluxes for GSMs, *J. Geophys. Res.* 99, 415–428, 1994.

642 Lin, S.-H., Liu, C.-M., Huang, W.-C., Lin, S.-S., Yen, T.-H., Wang, H.-R., Kuo, J.-T., and Lee, Y.

643 C.: Developing a yearly warning index to assess the climatic impact on the water resources of

644 Taiwan, a complex-terrain island, *J. Hydrol.*, 390, 13–22, 2010.

645 Liu, H., Tian, F. *, Hu, H. C., Hu, H. P., and Sivapalan, M.: Soil moisture controls on patterns of
646 grass green-up in Inner Mongolia: an index based approach, *Hydrol. Earth Syst. Sci.*, 2013,
647 17:805-815, doi:10.5194/hess-17-805-2013.

648 Liu, Q., Yang, Z., Cui, B., and Sun, T.: Temporal trends of hydro-climatic variables and runoff
649 response to climatic variability and vegetation changes in the Yiluo River basin, China, *Hydro.*
650 *Process.*, 23, 3030–3039, 2009.

651 Ma H, Yang D, Tan SK, Gao B, and Fu Q.: Impact of climate variability and human activity on
652 streamflow decrease in the Miyun Reservoir catchment, *J. Hydro.*, 389: 317-324, 2010.

653 Milly, P.C.D.: An analytic solution of the stochastic storage problem applicable to soil water,
654 *Water Resource Res.*, 29, 3755– 3758, 1993.

655 Milly, P.C.D., and Dunne, K.A.: Macroscale water fluxes 2. Water and energy supply control of
656 their inter-annual variability, *Water Resour. Res.*, 38, 241–249, 2002.

657 Notebaert, B., Verstraeten, G., Ward, P., Renssen, H., and Van Rompaey, A.: Modeling the
658 sensitivity of sediment and water runoff dynamics to Holocene climate and land use changes at
659 the catchment scale, *Geomorphology* 126, 18–31, 2011.

660 Petchprayoon, P., Blanken, P.D., Ekkawatpanit, C., and Hussein, K.: Hydrological impacts of
661 land use/land cover change in a large river basin in central–northern Thailand, *Int. J. Climatol.*,
662 30, 1917–1930, 2010.

663 Peng D. Z., and Xu, Z. X.: Simulating the impact of climate change on streamflow in the Tarim
664 River basin by using a modified semi-distributed monthly water balance model. *Hydrol.*
665 *Process.* 24, 209–216 (DOI: 10.1002/hyp.7485). 2010.

666 Potter, N.J., and Chiew, F.H.S.: An investigation into changes in climate characteristics causing
667 the recent very low runoff in the southern Murray– Darling Basin using rainfall–runoff models,
668 Water Resour. Res., 47, doi.org/10.1029/2010WR010333, 2011.

669 Renner M, Seppelt R, and Bernhofer C: Evaluation of water-energy balance frameworks to predict
670 the sensitivity of streamflow to climate change. Hydrol. Earth Syst. Sci., 16, 1419-1433, [doi:](https://doi.org/10.5194/hess-16-1419-2012)
671 [10.5194/hess-16-1419-2012](https://doi.org/10.5194/hess-16-1419-2012), 2012.

672 Roderick, M.L., and Farquhar, G.D.: A simple framework for relating variations in runoff to
673 variations in climatic conditions and catchment properties, Water Resour. Res., 47, W00G07,
674 [doi: 10.1029/2010WR009826](https://doi.org/10.1029/2010WR009826), 2011.

675 Roudier, P., Ducharne, A., and Feyen, L.: Climate change impacts on runoff in West Africa: a
676 review. Hydrol. Earth Syst. Sci., 18, 2789-2801, [doi: 10.5194/hess-18-2789-2014](https://doi.org/10.5194/hess-18-2789-2014), 2014.

677 Sankarasubramanian, A., Vogel, R.M., Limbrunner, J.F.: Climate elasticity of streamflow in the
678 United States, Water Resour. Res., 37, 1771–1781, 2001.

679 Scanlon, B.R., Jolly, I., Sophocleous, M., and Zhang, L.: Global impacts of conversion from
680 natural to agricultural ecosystem on water resources: quantity versus quality, Water Resour.
681 Res., 43, W03437. dx.doi.org/10.1029/2006WR005486, 2007.

682 Schaake, J.C.: From climate to flow. In: Waggoner, P.E. (Ed.), Climate Change and U.S. Water
683 Resources, John Wiley, New York, pp. 177–206, 1990.

684 Seibert, J., Bishop, K.H., and Nyberg, L.: A test of TOPMODEL’s ability to predict spatially
685 distributed groundwater levels, Hydrol. Process. 11, 1131–1144, 1997.

686 Shi C, Zhou Y, Fan X, et al. A study on the annual runoff change and its relationship with water
687 and soil conservation practices and climate change in the middle Yellow River basin. Catena,

688

100: 31-41, 2013.

689 Su, F., and Xie, Z.: A model for assessing effects of climate change on runoff of China, *Prog. Nat.*

690 *Sci.*, 13, 701–707, 2003.

691 Sun, Y., Tian, F., Yang, L., and Hu, H.: Exploring the spatial variability of contributions from

692 climate variation and change in catchment properties to streamflow decrease in a mesoscale

693 basin by three different methods, *J. Hydrol.*, 508, 170–180, 2014.

694 Tang, Y., Tang, Q., Tian, F., Zhang, Z., and Liu, G.: Responses of natural runoff to recent climatic

695 variations in the Yellow River basin, China, *Hydrol. Earth Syst. Sci.*, 17, 4471–4480, doi:

696 [10.5194/hess-17-4471-2013](https://doi.org/10.5194/hess-17-4471-2013), 2013.

697 Teng, J., Vaze, J., Chiew, F.H.S., Wang, B., and Perraud, J.M.: 2012. Estimating the relative

698 uncertainties sourced from GCMs and hydrological models in modelling climate change impact

699 on runoff, *J. Hydrometeorol.*, 13, 122–139, 2012.

700 Tesfa T.K., Li H.-Y., Leung, L. R. Huang, M., Ke, Y., Sun, Y., and Liu, Y.: A Subbasin-based

701 framework to represent land surface processes in an Earth System Model, *Geosci. Model*

702 *Dev.*, 7, 947-963, doi: [10.5194/gmd-7-947-2014](https://doi.org/10.5194/gmd-7-947-2014), 2014.

703 Tomer MD, and Schilling K.E.: A simple approach to distinguish land-use and climate-change

704 effects on watershed hydrology, *J. Hydrol.*, 376: 24-33, 2009.

705 Tuteja, N.K., Vaze, J., Teng, J., and Mutendeudzi, M.: Partitioning the effects of pine plantations

706 and climate variability on runoff from a large catchment in southeastern Australia, *Water*

707 *Resour. Res.*, doi: [10.1029/2006WR005016](https://doi.org/10.1029/2006WR005016), 2007.

708 Van Lill, W.S., Kruger, F.J., and Van Wyk, D.B.: The effect of afforestation with Eucalyptus

709 Grandis Hill ex Maiden and Pinus Patula Schlecht. et Cham. On streamflow from experimental

710 catchments at Mokobulaan, Transvaal, *J. Hydrol.*, 48, 107–118, 1980.

711 Wang, D., and Hejazi, M.: Quantifying the relative contribution of the climate and direct human
712 impacts on mean annual streamflow in the contiguous United States, *Water Resour. Res.*, 47,
713 W00J12, doi.org/10.1029/2001wr000760, 2011.

714 Wang, D., Hagen, S. C., and Alizad, K.: Climate change impact and uncertainty analysis of
715 extreme rainfall events in the Apalachicola River basin, Florida, *J. Hydrol.*, 480, 125–135,
716 2013.

717 Wang, D.B., Zhao, J.S., Tang, Y., and Sivapalan, M.: A thermodynamic interpretation of Budyko
718 and L’vovich formulations of annual water balance: Proportionality Hypothesis and maximum
719 entropy production, *Water Resour. Res.*, 51, 3007-3016, [doi: 10.1002/2014WR016857](https://doi.org/10.1002/2014WR016857), 2015

720 Wang, J.H., Hong, Y., Gourley, J., Adhikari, P., Li, L., and Su, F.G.: Quantitative assessment of
721 climate change and human impacts on long-term hydrologic response: a case study in a sub-
722 basin of the Yellow River. China, *Int. J. Climatol.*, 30, 2130–2137, doi.org/10.1002/joc.2023,
723 2010.

724 Ward, P.J., van Balen, R.T., Verstraeten, G., Renssen, H., and Vandenberghe, J.: The impact of
725 land use and climate change on late Holocene and future suspended sediment yield of the
726 Meuse catchment, *Geomorphology*, 103, 389–400, 2009.

727 Willmott, C.J., Robeson, S.M., and Feddema, J.J.: Influence of spatially variable instrument
728 networks on climatic averages. *Geophysical Research Letters*, 18, 2249-2251, 1991.

729 Willmott, C.J. and Feddema, J.J.: A more rational climatic moisture index. *Professional*
730 *Geographer*, 44, 84-88. [doi:10.1111/j.0033-0124.1992.00084](https://doi.org/10.1111/j.0033-0124.1992.00084). 1992.

731 Xiong, L. and Guo, S.: Effects of the catchment runoff coefficient on the performance of

732 TOPMODEL in rainfall–runoff modelling, *Hydrol. Process.*, 8, 1823–1836,
733 [doi:10.1002/hyp.1449](https://doi.org/10.1002/hyp.1449), 2004.

734 Xu, X., Yang, H., Yang, D., and Ma, H.: Assessing the impacts of climate variability and human
735 activities on annual runoff in the Luan River Basin, China, *Hydrol. Res.*, 44, 940–952,
736 doi.org/10.2166/nh.2013.144, 2013.

737 Yang D., Li C., Hu H., et al. Analysis of water resources variability in the Yellow River of China
738 during the last half century using historical data[J]. *Water Resources Research*, 2004, 40(6).

739 Yang, H., Yang, D., Lei, Z., and Sun, F., New analytical derivation of the mean annual water-
740 energy balance equation, *Water Resour. Res.*, 44, W034103, [doi: 10.1029/2007WR006135](https://doi.org/10.1029/2007WR006135),
741 2008.

742 Yu Sun, Fuqiang Tian, Long Yang, Heping Hu. Exploring the spatial variability of contributions
743 from climate variation and change in catchment properties to streamflow decrease in a mesoscale
744 basin by three different methods. *J. Hydrol.*, 508,170–180, 2014.

745 Zhao, G., Mu, X., Tian, P., Wang, F., Gao, P., Climate changes and their impacts on water
746 resources in semiarid regions: a case study of the Wei River basin, China. *Hydrol. Process.* 27,
747 3852-3863, 2013.

748 Zhan, C. S., Jiang, S. S., Sun, F. B., Jia, Y. W., Niu, C. W., and Yue, W. F.: Quantitative contribution
749 of climate change and human activities to runoff changes in the Wei River basin, China, *Hydrol.*
750 *Earth System Sci.*, 18, 3069-3077, [doi: 10.5194/hess-18-3069-2014](https://doi.org/10.5194/hess-18-3069-2014), 2014.

751 Zhang, C., Peng, Y., Chu, J., Shoemaker, C. A., and Zhang, A.: Integrated hydrological modelling
752 of small- and medium-sized water storages with application to the upper Fengman Reservoir
753 Basin of China, *Hydrol. Earth Syst. Sci.*, 16, 4033–4047, [doi:10.5194/hess-16-4033-2012](https://doi.org/10.5194/hess-16-4033-2012), 2012.

754 Zhang, L., Dawes, W.R., and Walker, G.R.: Response of mean annual evapotranspiration to

755 vegetation changes at catchment scale, *Water Resour. Res.*, 37, 701–708, 2001.

756 Zhang, X., Zhang, L., Zhao, J., Rustomji, P., and Hairsine, P.: Responses of streamflow to

757 changes in climate and land use/cover in the Loess Plateau, China, *Water Resour. Res.*, 44,

758 W00A07, doi: [10.1029/2007WR006711](https://doi.org/10.1029/2007WR006711), 2008.

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

Table 1 Characteristics of the inter-annual streamflow and precipitation of the JRB.

Feature	Mean (mm)	Maximum		Minimum		Extremes ratio	Variation coefficient C_v	Wet year (mm)	Flood period (%)	Dry period (%)
		time	(mm)	time	(mm)					
Precipitation	514	1964	794	1997	343	2.31	0.20	613.11	64.21	7.46
Streamflow	29.51	1964	85.46	2009	7.09	12.05	0.48	66.80	66.8	18.22
Runoff coefficient	0.05	1964	0.12	2009	0.04	3.34	0.28	0.08	—	—
Flood runoff coefficient	0.06	1964	0.12	2007	0.03	3.86	0.33	—	—	—

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806
807
808
809
810
811
812
813
814
815
816
817
818
819
820

Table 2 The average monthly estimated potential evaporation and temperature value of the JRB from 1960 to 2010.

Month	3	4	5	6	7	8	9	10	11	12	1	2
E_0 (mm)	61	90	118	131	126	108	70	49	32	24	26	34
Mean (mm)	90 (Spring)			122 (Summer)			50 (Autumn)			28 (Winter)		
T (°C)	4.1	10.7	15.8	20	21.8	20.3	15.2	9.2	2.4	-3.3	-4.7	-1.7
Mean (°C)	10.2			20.7			8.9			-3.3		

821 Note: E_0 was the potential evaporation; T was the temperature.

822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843

844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883

Table 3 Statistical values of the potential evaporation and temperature of the JRB from 1960 to 2010.

Feature	Mean	C_v	C_s	Maximum		Minimum	
				time	Max	time	Min
E_0 (mm)	870	0.08	0.53	2004	1092	1964	713
T (°C)	9.1	0.07	0.09	1998	10.2	1967	7.6

Note: the Mean was the multi-year average value; C_v was the deviation coefficient; C_s was the skewness coefficient;

884
885
886
887
888
889
890
891
892

Table 4 The impact of climate variability and human activities on streamflow with the climate elasticity model.

Period	E ₀ (mm)	P (mm)	Q (10 ⁸ m ³)	aridity index	ΔE ₀ (mm)	ΔP (mm)	ΔQ (10 ⁸ m ³)	ε _P	ε _{E0}	ΔQ _P (mm)	ΔQ _{E0} (mm)	ΔQ _C (mm)	Human activities		Climate variation		
													ΔQ _H (10 ⁸ m ³)	η _H (%)	ΔQ _C (10 ⁸ m ³)	η _C (%)	
1960-1970	846.5	561.2	18.3	1.54	—	—	—	—	—	—	—	—	—	—	—	—	—
1971-1980	894	500.1	11.4	1.79	29.5	-61.1	-6.9	1.46	-0.46	-40.6	-3.2	-43.9	-5.8	83.6	-1.1	16	
1981-1990	817.2	535.5	14.3	1.53	-47.3	-25.6	-4	1.49	-0.49	-18	6.3	-11.8	-3.7	92.4	-0.3	7.5	
1991-2000	881.9	462.4	12.6	1.91	17.5	-98.8	-5.7	1.45	-0.45	-64.2	-1.8	-66	-4	70.1	-1.7	29.9	
2001-2010	893.9	506.5	10.9	1.76	29.4	-54.6	-7.4	1.52	-0.52	-36.5	-3.3	-39.8	-6.4	86.1	-1	13.5	
1971-2010	871.8	501.1	12.3	1.74	7.3	-60.1	-6	1.48	-0.48	-40.9	5.1	-35.8	-4.8	80.7	-1.2	19.3	

893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917

918
 919
 920
 921
 922
 923
 924
 925

Table 5 The impact of climate variability and human activities on streamflow with TOPMODEL.

Period	Annual mean streamflow			Human activities		Climate variation	
	Q_B (10^8 m^3)	ΔQ (10^8 m^3)	Q_S (10^8 m^3)	ΔQ_H (10^8 m^3)	η_H (%)	ΔQ_C (10^8 m^3)	η_C (%)
1960-1970	18.3						
1971-1980	11.4	-6.9	17.0	-5.6	81.2	-1.3	18.8
1981-1990	14.3	-4.0	18.1	-3.8	95	-0.2	5
1991-2000	12.6	-5.7	15.6	-3.0	52.6	-2.7	47.4
2001-2010	10.9	-7.4	17.0	-6.1	82.4	-1.3	17.6
1971-2010	12.3	-6.0	16.9	-4.6	76.7	-1.4	23.3

926
 927
 928
 929
 930
 931
 932
 933
 934
 935
 936
 937
 938
 939
 940
 941
 942
 943
 944

945
 946
 947
 948
 949
 950
 951
 952
 953
 954
 955
 956
 957
 958
 959
 960
 961
 962
 963
 964
 965
 966
 967
 968
 969
 970
 971
 972
 973
 974
 975

Table 6 The impact of climate variability and human activities on streamflow with the VIC model.

Period	Annual mean streamflow			Human activities		Climate variation	
	Q_B (10^8 m^3)	ΔQ (10^8 m^3)	Q_S (10^8 m^3)	ΔQ_H (10^8 m^3)	η_H (%)	ΔQ_C (10^8 m^3)	η_C (%)
1960-1970	18.3	—	—	—	—	—	—
1971-1980	11.4	-6.9	17.1	-5.7	82.6	-1.2	17.4
1981-1990	14.3	-4.0	18.8	-4.5	112.5	0.5	-12.5
1991-2000	12.6	-5.7	15.8	-3.2	56.1	-2.5	43.9
2001-2010	10.9	-7.4	16.7	-5.8	78.4	-1.6	21.6
1971-2010	12.3	-6.0	17.0	-4.7	78.3	-1.3	21.7

976
977
978
979
980
981
982
983
984
985
986

Table 7 Changes of the inter-annual precipitation and temperature of the JRB.

Time	Precipitation (mm)	Temperature (°C)	ΔP (mm)	ΔT (°C)
1960s	561.2	8.6	—	—
1970s	500.1	8.8	-61.1	0.2
1980s	535.5	8.8	-25.6	0.2
1990s	462.4	9.4	-98.8	0.8
2000s	506.5	9.8	-54.6	1.2

987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008

Note: ΔP and ΔT are the changes in precipitation and temperature, respectively

1009
1010
1011
1012
1013
1014
1015
1016

Table 8 Cumulative area of soil and water conservation in the JRB at the end of different years
(Unit:km²)


Time	Level terrace	Afforestation	Grass-planting	Check dam	Total
1960s	50	184	11	4	249
1970s	330	666	90	10	1096
1980s	729	1520	169	18	2436
1990s	2356	4135	1023	49	7563
2000s	2907	4773	1146	52	8878

1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031

1032

1033

1034



1035

Figure 1. Location of hydrological and meteorological stations along the Jinghe River.

1036

1037

1038

1039

1040

1041

1042

1043

1044

1045

1046


1047

1048

1049

1050

1051



1052

Figure 2. The abrupt change points of precipitation and streamflow in the JRB with Sequential

1053

cluster.

1054

1055

1056

1057

1058

1059

1060

1061

1062

1063

1064

1065

1066


1067

1068

1069

1070


1071
1072
1073
1074



1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094


Figure 3. Changes of the annual streamflow and precipitation of the JRB.

1095
1096
1097
1098
1099




1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117


Figure 4. Changes of the annual potential evaporation and temperature of the JRB.



(a)



(b)




(c)

Figure 5. (a) Elevation maps of the study area at a 30-m resolution. (b) Sub-basin of TOPMODEL. (c) Grid of the VIC model.

1118
1119

1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137

1138
1139
1140



1141

1142

Figure 6. The simulated and observed streamflow for TOPMODEL and the VIC model.

1143

(a) Calibration period. (b) Validation period.

1144

1145

1146

1147

1148

1149

1150

1151

1152

1153

1154

1155

1156

1157

1158

1159

1160

1161

1162

1163

1164

1165


1166

1167

1168

1169


1170
1171
1172
1173



1174
1175
1176

(a) Calibration streamflow for TOPMODEL

(b) Validation streamflow for TOPMODEL



1177
1178


(c) Calibration streamflow for VIC model

(d) Validation streamflow for VIC model

1179 **Figure 7.** Comparison of the observed and modeled monthly streamflows for the calibration
1180 and validation periods.

1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194


1195
1196
1197
1198
1199
1200



1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227

Figure 8. Comparison of the observed and modeled monthly streamflow in 1971-2010.
(a)TOPMODEL. (b) VIC model.

1228
1229
1230
1231
1232
1233



1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258

Figure 9. Time series of the observed and modeled annual streamflow for the entire modeling period.