AUTHOR'S RESPONSE

Dear Editor:

We have attended successfully the comments from reviewers and revised the manuscript accordingly. All reviewer's comment (bold, red-colored), our answers (black), some modified parts (italic, blue colored) are included in the response to the reviewers:

Review 1, part 1 (Custodio)

General comments:

 The paper presents an interesting point of view on groundwater hydrogeochemisty from the volcanic caldera toward the west to Guadalajara. Complementary hydrogeological details are scarce. They are needed to support what is presented and concluded.

Answer:

We agree completely with the reviewer. We extended the Hydrogeological Settings (section 2.1), modified the Groundwater flow system (section 4.4) and replaced Figure 1 with two new figures (Fig. 2 Hydrogeological settings, Fig. 3 Cross sections) for a better visualization. The rest of the figures were renumbered.

2. Also water chemical data are treated with statistical tools of quite common nature. This is a good approach but the detail relative to groundwater flow are lost or poorly developed. So, the transfer of hydrochemical characteristics along the flow paths is not presented and exploited.

Answer:

The reason that we did not include geochemical evolution along flow paths is that we are currently developing a paper that is dealing with geochemical transfers/reactions along selected flow paths using PHREEQC code. However, we agree with you that there should be a description in the current paper connecting the hydrochemical characterization with groundwater flow. Thus, we modified the section 4.1 and changed the title to "Groundwater Chemical Characterization".

3. Specific comments: geothermal conditions are no clearly shown as a 180 shift to heavier values, which are expectable when there is a mixing of recent recharge with thermally affected water containing evolved chemical characteristics.

Answer:

We understand that there is a shift to heavier values, however it is relatively small. Recharge water from La Primavera (group 4) has a signature of (-68.5/-9.5 permil), while thermally affected water has a signature of (-66.7/-9.0 permil). The small difference may be explained by the effect that most waters have at least a small component of thermal affected waters, as also confirmed by the mixing model M3 (Table 4). On the other hand, Gutierrez et al. (1994) reports values of -8.7 to -9.2 permil for thermal waters in the study area with temperatures between 64 and 85 °C (Sanchez-Diaz, 2007).

4. The values of SiO2 are not those expectable from a hot chemically active acid volcanic rock environment.

Table 1 should correctly say "Si" instead of "SiO2". The laboratory reported elemental concentrations. Otherwise the Si values must be converted to SiO2 by dividing the Si values through 0.4674. We arrange the corresponding changes in Table 1.

5. 3H content is what is expectable from an unconfined system recharged from the surface taking into account the mixing produced by a spring or a long screened pumped well. This is not addressed. It seems that the groundwater equivalent water depth is relatively small. This is also not addressed.

Answer

We agree that this issue is not addressed and propose to add the following paragraph which describes 3H results in the section "4.2 Isotope hydrology" (line 302 – 312):

Tritium results indicate that groundwater within the study area includes both pre-modern (pre-1950s) and modern recharge. The values range from 0.3 to 3.0 TU which suggests a contribution from modern water in every sampled site (Table 1). The majority of waters with ³H lower than 1.0 TU are in the southern portion of the aquifer system. Elevated ³H values (>1.5 TU) located mostly in the La Primavera volcanic system represent young waters or recent recharge with little mixing of path lines. Waters with ³H values <1.5 TU illustrates that these wells may represent mixing of flow paths with modern and pre-modern groundwater residence times. These waters are found mostly in Toluquilla, corresponding to elevated EC, Cl and DIC values. The mixing of water from different ages is expectable because the aquifer is under unconfined conditions, while wells penetrate the saturated zone to a considerable depth, at times up to 500 m, and are almost always completely screened.

6. Technical comments: in tables say that pH has no units. Make clear if what is given is SiO2 or Si; both are used with close figures. TDS is as STD in the tables. The two cross sections of figure 8 are shown in figure 2 and not in figure 1; they seem too simplistic; some added hydrogeological information will be welcome. The two cross sections of figure 8 are shown in figure 2 and not in figure 1; they seem too simplistic; some added hydrogeological information will be welcome.

Answer:

- We attend these technical comments correspondingly in the manuscript as well as all other modification as result of the required changes.
- The two cross sections have been re-elaborated considerably addressing hydrogeological information and can be seen in new Figures 2 and 3.
- Original Figure 8 was cancelled.

Review 1, part 2 (Custodio)

7. 3H analyses are not inexpensive when electrolytic concentration is needed.

Answer:

3H analysis (including enrichment) cost typically 200 USD per sample at a commercial basis and with a turnaround time of more or less 2 months. We think that radioactive tracers like 14C and 3H are now relatively accessible in comparison to earlier times because the methods are now standard and there is an availability of a large number of competitive labs worldwide. We propose to use in the text "accessible" instead of "inexpensive" (line 53).

8. The accuracy of data is not given and this is important.

Answer:

The average accuracy of tritium analyses was ~0.3 TU (consider that groundwater values varied between 0.4 and 2.1 TU). We added this information in section 3.1 (Field and Laboratory, line 169).

9. Since 18O and 2H are highly correlated, one of them can be excluded from the statistical analysis o better 2H can be substitutes by excess deuterium to enhance the small differences in Fig 6 caption how and altitude has been given to the samples should be given to be able to understand properly the plot; it seems that some altitude effect is present but looks too high.

Answer:

- This information is complemented in section 4.2 (line 271-301).
- The graphical 18O and deuterium excess was added in new Figure 7.
- 10. The calcedonia geothermometer does not point to the type of rock (basalt, andesite) as said in pp13 If possible fig 8 will improve introducing some more geological data instead of only rock classification

Answer:

This observation was also addressed in the comment 1 referring to the hydrogeological section. Fig. 8 was replaced with a new Fig. 3 as mentioned in the previous comments. In addition, pp.13 in Section 4.4 was changed.

Review 2 (anonymous)

1. GENERAL COMMENTS The manuscript appears not well finalized to the scope of the research due to the scarce integration of geochemical analyses with a consistent conceptual hydrogeological model of the area. This scarce connection limits the significance of the research just to the geochemical aspect. Following, some specific comments are reported that would finalize the manuscript more clearly to the scope of the research (title).

Answer:

We agree that the hydrochemical work has to be connected with the hydrogeological framework. Thus we have revised the section 2.1 that describes the Hydrogeological Settings and included the evolution of hydrochemical facies in the Results section (see below).

2. SPECIFIC COMMENTS.

Section 2:

- a) a classification of the climate type, by means of known system (e.g. Köppen-Geiger), would improve the description of the area;
- b) the estimate of the mean annual actual evapotranspiration (e.g. by the Turc or Coutagne formulas) could give, together the mean annual rainfall, a general assessment of the groundwater recharge of the area.

Answer:

The classification of climate has been considered in section 2 (line 79-84), as follows:

2. Study area:

The study area is situated in the central portion of the state of Jalisco (Fig. 1). It belongs to the Lerma-Santiago river system, which drains into the Pacific Ocean. The climate in the study area according Köppen is a warm temperate with dry winter "Cwa" (Peel et al., 2007; Kottek, 2006). The National Water Commission reports an average annual temperature of 20.9°C and an average annual precipitation of 904 mm, occurring mostly between May and October. The mean annual evapotranspiration is 712 mm according to Turc formula (CONAGUA, 2010).

- 3. Section 2.1:
- c) This chapter reveals some discrepancies respect the declared scope of the research (title):
- a. regional geological setting and local hydrogeological setting should be described separately; in detail, the first aspect should be reduced respect to the present form, while the second one should be expanded.
- b. hydrogeological description of the area is very scarce and limited to surficial aquifers only; moreover it does not correspond to what is shown in Figs 2 and 8;
- c. hydrostratigraphic units should be described and characterized in terms of hydrogeological properties (e.g. type and degree of porosity and permeability, transmissivity, etc.);
- d. data regarding groundwater levels and altitude of springs should be illustrated and interpreted in order to support a conceptual model of groundwater flow of the area.

Answer:

We agree completely with your suggestion. We revised the local hydrogeological settings (2.1) in the manuscript: In the Description of the Study area we propose to extend the description of the hydrogeology of the study area as follows, and replaced Figures 2 and 8 with two new figures (Fig. 2 Hydrogeological settings, Fig. 3 Cross sections) for a better visualization.

4. Section 3.2:

d) "Techniques of analysis" seems describe better the contents of this paragraph instead of "Interpretation".

Answer:

Usually we use "Interpretation" in our papers but we have no problem with the suggestion and attend it correspondingly in the manuscript (line 170).

5. Section 4.4:

A. Spatial distribution of groundwater types should be discussed consistently with the conceptual hydrogeological model and vice versa.

Answer

We agree with you and modified Section 4.4.

6. Figures 2 and 8:

- B. Fig. 2 seems to be not an ordinary hydrogeological map because it does not represent hydrostratigraphic units with a description of the related hydrogeological characteristics:
- C. Fig. 2 should be associated to a hydrostratigraphic column provided with information about their hydrogeological characteristics, etc.;
- D. groundwater flow paths are too approximate, not supported by explanations of a related conceptual groundwater flow model and not indicating to which aquifer they are related (e.g. surficial or deep);
- E. topographic contour lines are not well visible.

Answer:

We agree with the comments. Fig 2 was modified, hydrostratigaphic characteristics were described in the text (section 2.1, see above), groundwater flow paths are added to new Fig. 3, the text indicates that they relate to the upper aquifer; topographic contour lines were eliminated and water table contour lines added.

7. Figures 3 and 5:

F. results reported in these geochemical graphical analyses should be reported in Fig. 2 or in other figures showing geographical distribution of groundwater types.

Answer:

New Fig 3. shows water types of selected, representative wells along cross section.

Review 3 (anonymous)

1. The manuscript describes a very interesting study on a hydrothermal volcanic system with the aim to assess the hydrological processes occurring within the Atemajac-Toluguilla aguifer unit by means of a combination of different techniques. In particular, the combination of geochemical and statistical methodologies based on a huge dataset is a valuable approach to understand the complex dynamics taking place in the volcanic aguifer. The overall manuscript is well written, structured and referenced. Nevertheless, the paper has two main weak points: 1) the definition of the reference values for the different groundwater typologies; 2) the missing estimate of the overall uncertainty associated to the mixing proportions. From the reported data, the authors estimations of mixing proportions cannot be considered accurate, since, as they write in the text, they do not use "real" end-members. Nevertheless, if they wanted to use the most representative groundwaters (as supposed end-members), the estimations of the mixing proportions should be reported with amplified uncertainties, which are not even mentioned in the text. Moreover, since they are using data from one single campaign, the temporal variability of their reference values, which is another term contributing to the overall uncertainty, cannot be estimated.

Answer:

- We agree that the endmembers are not "real", especially the geothermal endmember. However, we found data from former studies (Mahood et al., 1991; Maciel-Flores and Rosas-Elguera, 1992; y Prol-Ledezma et al., 1995) about the La Primavera geothermal field which are considered as hydrothermal reference waters in the revised version. Concretely, data from 3 deep wells were used to estimate the mixing proportions with M3. These wells showed by far higher temperatures and Cl, B, Li and Na concentrations in relation to the sampled wells from our study. The results from these estimations were quite different from the first version. They were validated with the mixing proportions based on a Cl mass balance calculation. The methods and new results were included in section 3.2 (Techniques of analysis, line 186-202) and section 4.3 (Mixing patterns with M3). The abstract and conclusions were also revised accordingly.
- We are aware that the temporal variation of reference values undoubtedly plays an important role in estimation of groundwater mixing. However for various reasons it is not always possible to carry out a periodically sampling as in our case. There are also other studies applying M3 as a tool for evaluating mixing proportions using data from only one field campaign (e.g. Chae et al., 2006; Forrest et al., 2013). In our case, the resulting mixing proportions are only a first approximation (consider that this is the first paper at all describing groundwater flow and chemistry in Guadalajara area). This proportions may vary with time. However, our objective in this paper was to comprehend the groundwater flow and factors that control groundwater chemistry, among these the mixture of different fluids. An accurate quantification of mixing proportions is beyond the scope of this paper (see section 1 Introduction). In this paper we demonstrated the applicability of M3 program using groundwater that is affected by polluted and thermal waters, and its validation with an independent method, the CI mass balance. It is however advisable to continue with this effort to perform more field campaigns addressing the seasonal variations (line 381-386).

2. The output numbers of the model M3 in the Table 4 should be reported with the overall associated uncertainties. In summary, the overall associated uncertainty should include, besides the sampling and analytical uncertainty, the variability associated to the supposed "end-members" considering also their seasonal variability. Only in the case of the uncertainty assessment, it would be possible to give accurate estimation of the mixing proportions. I would suggest to include in the Abstract at least the isotopic techniques used and the relative purpose. Regarding the study area, I couldn't find a reference in text about its extension.

Answer:

It would be difficult to calculate the overall associated uncertainty because some of the components are not available as mentioned above. Instead, we propose the following:

- The average and standard deviation of the estimation of mixing proportion with both methods (M3 and CI mass balance) are included in Table 4.
- Table 1 includes the ion balance error of the analytical results.
- M3 results are validated using a chloride mass balance (line 314-333).
- The explanation was modified and expanded in Section 4.3: Mixing patterns with M3
- In the abstract we included techniques used and respective purpose: Stable water isotopes (δ2H, δ18O) were used to trace hydrological processes and tritium (3H) to evaluate the relative contribution of modern water in samples (line 13-14).
- The study area is 1368 km2. We feel sorry for this omission It is added in the revised section 2: Study area (line 79).
- 3. Due to the number of wells monitored (about 40) it would be desirable to have a water table reconstruction at the time of the sampling, since from the text it is not pointed out this kind of survey has been realized in the study area. Moreover, I would suggest to write a sentence about the goodness of chemical analyses (e.g. reporting the range of the ion balance values for the acceptation of chemical analyses). Summarizing, the manuscript can be accepted only if major revisions will be done by the authors, regarding the main points previously illustrated and remarked.
 - The water table configuration was included in new Figure 2. We extended the Hydrogeological Settings (2.1), modified the description of the Groundwater flow system (4.4) and replaced Figure 2 with two new figures (Fig. 2 Hydrogeological settings, Fig. 3 Cross sections) for a better visualization.
 - The ion balance error was included in Table 1.

Groundwater flow processes and mixing in active volcanic systems: The case of Guadalajara (Mexico)

A. Hernández-Antonio¹, J. Mahlknecht^{1,*}, C. Tamez-Meléndez¹, J. Ramos-Leal², A. Ramírez-Orozco¹, R.

4 Parra¹, N. Ornelas-Soto¹, C.J. Eastoe³

¹Centro del Agua para América Latina y el Caribe, Tecnológico de Monterrey

²División de Geociencias Aplicadas, Instituto Potosino de Investigación Científica y Tecnológica

³ Department of Geosciences, University of Arizona

Abstract:

Groundwater chemistry and isotopic data from 40 production wells in the Atemajac and Toluquilla Valleys, located in and around the Guadalajara metropolitan area, were determined to develop a conceptual model of groundwater flow processes and mixing. Stable water isotopes (δ^2 H, δ^{18} O) were used to trace hydrological processes and tritium (3 H) to evaluate the relative contribution of modern water in samples. Multivariate analysis including cluster analysis and principal component analysis were used to elucidate distribution patterns of constituents and factors controlling groundwater chemistry. Based on this analysis, groundwater was classified into four groups: cold groundwater, hydrothermal water, polluted groundwater and mixed groundwater. Cold groundwater is characterized by low temperature, salinity, and Cl and Na concentrations and is predominantly of Na-HCO3 type. It originates as recharge at Primavera caldera and is found predominantly in wells in the upper Atemajac Valley. Hydrothermal water is characterized by high salinity, temperature, Cl, Na, HCO3, and the presence of minor elements such as Li, Mn and F. It is a mixed HCO3 type found in wells from Toluquilla Valley and represents regional flow circulation through basaltic and andesitic rocks. Polluted groundwater is characterized by elevated nitrate and sulfate concentrations and is usually derived from urban water cycling and subordinately from agricultural return flow. Mixed groundwaters between cold and hydrothermal components are predominantly found in the lower Atemajac Valley. Most groundwater contains at least a small fraction of modern water. The application of a multivariate mixing model allowed to evaluate the mixing proportions of hydrothermal fluids, polluted waters and cold groundwater in sampled water. This study may help local water authorities to identify and dimension

Commented [JM1]: Changed according to authors

Commented [JM2]: Modified

- 27 * Corresponding author: Jürgen Mahlknecht, Centro del Agua para América Latina y el Caribe,
- 28 Tecnológico de Monterrey, Ave. Eugenio Garza Sada No. 2501, C.P. 64849 Monterrey, Nuevo León,
- 29 México. E-mail: jurgen@itesm.mx

groundwater contamination, and act accordingly.

Introduction

30 31 Active volcanic systems are frequently accompanied by an intense hydrothermal circulation, which is 32 controlled by the exchange of mass and energy between groundwater systems, magmatic fluids and hot 33 rock (Goff and Janik, 2000; Di Napoli et al., 2009). The characterization of such hydrothermal systems Commented [JM3]: Citations in chronological order helps on the one hand to quantify its geothermal energy potential and, on the other hand, to assess 34 volcanic-related risks (Di Napoli et al., 2011). Hot springs, mud deposits, fumaroles, vaporization and 35 36 degassing soils give initial clues about subsurface hydrothermal conditions (Hockstein and Browne, 2000; Navarro et al., 2011). The chemical characterization of fluids and groundwater has been used as an 37 38 indicator of the subsurface structure and the origin of released fluids when hydrogeological information 39 is scarce (Henley and Ellis, 1983; Appelo and Postma, 2005). Hydrochemical data, such as high electrical Commented [JM4]: Idem 40 conductivity (EC), high temperatures and elevated concentrations of As, B, Br, Cl, Cs, F, Fe, Ge, I, Li, Mn, Mo, Na, Rb, Sb, Ta, U and W denote the presence of hydrothermal fluids in groundwater (Reimann et al. 41 2003; Dogdu and Bayari, 2005; Aksoy et al. 2009). However, hydrothermal volcanic systems are 42 Commented [JM5]: idem 43 sometimes difficult to analyse due to the fact that groundwater is a mixture of fluids from various sources, sometimes consisting of shallow meteoric waters from recent infiltration, seawater and hot water rising 44 45 from deep hydrothermal reservoirs (Chiodini et al., 2001; Evans et al, 2002; Di Napoli et al., 2009). Commented [JM6]: idem 46 The combination of different environmental tracer techniques helps elucidate the groundwater's origin, 47 recharge, flow velocity and direction, residence or travel times, connections between aquifers, and 48 surface and groundwater interrelations (Edmunds and Smedley 2000; De Vries and Simmers 2002; Appello and Postma, 2005; Ako et al., 2013; Stumpp et al., 2014). These techniques have been applied in large 49 Commented [JM7]: idem 50 semiarid to arid rift systems (Bretzler et al., 2011; Furi et al. 2011; Ghiglieri et al, 2012; Siebert et al., 2012; 51 Panno et al., 2013; Forrest et al., 2013; Williams et al., 2013). Stable isotopes (2H, 18O) provide information Commented [JM8]: idem 52 regarding origins, recharge processes, flow paths and residence times, especially in fractured rock

aquifers. Radioactive tracers like tritium (3H) are relatively accessible methods to estimate groundwater ages and characterize groundwater flow systems. Relatively few studies attempt to quantify mixing between different hydrothermal and cold fluids (Forrest et al., 2013). This study was carried out in the Atemajac-Toluguilla aguifer system (ATAS) which underlies the metropolitan area of Guadalajara, second-most populated city in Mexico (~4.6 million inhabitants), and is located in a complex neotectonic active volcanic system in the Tepic-Zacoalco Rift. Adjacent to this aquifer system is the "La Primavera" caldera. Several survey wells have been drilled up to 3 km deep at La Primavera to explore the potential for geothermal energy (CFE, 2000). Temperatures between 80 and 300 °C have been registered in these wells (Verma et al., 2012), and temperatures higher than 40°C have been measured in adjacent springs (Sánchez-Díaz, 2007). The hydrothermal fluids and springs are characterized by high concentrations of Na, Cl, SiO₂, HCO₃, B, F, and TDS. A mixture of hydrothermal fluids and meteoricderived water has been identified in the springs of "La Primavera" (Sánchez-Díaz, 2007). While it is assumed that this caldera influences the aquifer system underneath the metropolitan area, the proportion of hydrothermal fluids and cold water is not clear. Moreover, nitrate contamination has been related to exogenic processes induced by anthropogenic activity (GEOEX-SIAPA, 2003). The diversity of the chemical results from previous studies has contributed to the difficulty in clearly evaluating the relationship between the fluids (see Results and Discussion section). This study aims to understand the flow dynamics of groundwater by using the combination of statistical and geochemical methods. Water groups and factors that control the groundwater chemical processes were identified using a cluster and principal component analysis. Environmental tracers were used to assess chemical evolution. Mixing proportions of selected fluids in public wells were estimated by means of a multivariate mixing calculation and validated by a chloride mass balance. This study is the first of its kind to report a comprehensive understanding of groundwater flow processes below the Guadalajara

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

Commented [JM9]: added

Commented [JM10]: changed

Commented [JM11]: added to indicate the antropogenic impact elucidated by previous study

Commented [JM12]: modified according to authors' response

- 76 metropolitan area. This information is strategic to decision makers from local water authorities regarding
- 77 water resources management.

2 Study area

78

85

90

- 79 The study area (1368 km²) is situated in the central portion of the state of Jalisco (Fig. 1). It belongs to the
- 80 Lerma-Santiago river system, which drains into the Pacific Ocean. The climate according to Köppen is a
- 81 warm temperate with dry winter "Cwa" (Peel et al., 2007). The National Water Commission reports an
- 82 average annual temperature of 20.9°C and an average annual precipitation of 904 mm, occurring mostly
- 83 between May and October. The mean annual evapotranspiration is 712 mm according to Turc formula
- 84 (CONAGUA, 2010).

2.1 Hydrogeological Settings

- Ref. The study area is located in the western portion of the Mexican Volcanic Belt (MVB), a 1000 km-long
- 87 volcanic arc that crosses central Mexico in E–W direction from the Pacific to the Atlantic Ocean. The MVB
- 88 originated in the Late Miocene in response to the subduction of the Cocos and Rivera plates below the
- 89 North American plate along the Middle America Trench. The belt has a composition of intermediate to
 - silicic rocks (Alva-Valdivia et al., 2000). The western end of the MVB defines the fault bounded crustal
- 91 Jalisco Block (Ferrari et al., 2007; Valencia et al., 2013). The northern and eastern boundaries of this block
- 92 consist of asymmetric continental rifts formed by tilted blocks with escarpments between 800 and 1000m
- 93 (Zárate-del Valle and Simoneit, 2005); the Tepic-Zacoalco Rift to the north runs in an NW-SE direction,
- 94 and the Colima Rift to the east runs in an N–S direction; these rifts join the E–W oriented Citala or Chapala
- 95 Rift in what is known as the Jalisco Triple Junction located 60 km SSW of the city of Guadalajara (Fig. 1).
- 96 This area is a complex and active neotectonic structure that controls and regulates the development of
- 97 the rift-floor, limited by normal faults (Michaud et al., 2000; Zárate-del Valle and Simoneit, 2005). The
- 98 Atemajac and Toluquilla Valleys are located in the lower Tepic-Zacoalco Rift and are bordered by hills,

volcanic cones (El Cuatro, San Martín), plateaus (Tonalá) and volcanic calderas (La Primavera), among other features (Sánchez-Diaz, 2007).

101

102

103

104

105

106

107

108

109

110

111

112113

114

115

116

117118

119

120

121

100

99

Atemajac and Toluquilla valleys consist of a relatively thin cover of Quaternary lacustrine deposits overlying a thick section of Neogene volcanic rocks including silicic domes, lava and cinder cones, lithic tuffs, basalts, ignimbrites and other pyroclastic rocks, andesites and volcanic breccia, and a basement consisting of Oligocene granite (Campos-Enríquez et al., 2005; Gutiérrez-Negrín, 1988; Urrutia et al., 2000) (Fig. 2). Hydrogeologically, these valleys are underlain by two aquifers (Fig. 3). The upper aquifer consists of alluvial and lacustrine sediments, Pleistocene pre-caldera pyroclastic materials (Tala tuff) such as volcanic ash flows and lapilli, and rhyolitic domes. These sediments represent an unconfined aquifer of up to 450 m thickness with hydraulic conductivities ranging from 1.6×10^{-7} to 2.0×10^{-4} m/s and porosities from 20 to 40% (Sánchez-Díaz, 2007; CONAGUA, 2010). Groundwater recharge sources of this aquifer are rainwater and ascending vertical fluids from the lower aquifer (Gutierrez-Negrin, 1991). Groundwater flows via faults and Toba tuffs in direction to the central and northern portion of the study area. The lower aquifer consists of fractured andesites and basalts from Pliocene, with hydraulic conductivities and porosities ranging from 10-8 to 10-4 m/s and from 5 to 50%, respectively. This semi-confined to confined aquifer has been related to geothermal fluids (Venegas et al., 1991; GEOEX-SIAPA, 2003). Groundwater of this aquifer flows preferentially in southeastern direction (Ramírez et al., 1982). Pumping wells are drilled in the upper aquifer. Its water table distribution is shown in Fig. 2. In the Atemajac valley, groundwater flow direction is oriented mainly from southwest to northeast, from the topographically higher areas, towards the Santiago river, with possible recharge from normal faults west from Guadalajara city (Fig. 3, section I and II); while in Toluquilla the flow of groundwater circulates from

northwest to southeast (Fig. 3, section III) (GEOEX-SIAPA, 2003; CONAGUA, 2009). However,

anthropogenic activity has been changing the flow paths, resulting in the formation of different cones of depression. The major discharge is given by well pumping activities and springs in the escarpment of the Santiago river (GEOEX-SIAPA, 2003; CONAGUA, 2009 and 2010). Due to the heavy extractions from the aquifer system, water table levels are falling up to 2.2 m/year and 0.3 m/yr on average in Atemajac and Toluquilla aquifers, respectively (GEOEX-SIAPA, 2003). The constructed well depth is up to 500 m and up to 380 m in the valley of Atemajac and Toluquilla, respectively. Depth to water table reaches up to 150 m below ground level in the Atemajac valley and 50 m in Toluquilla valley (GEOEX-SIAPA, 2003).

2.2 Hydrothermal System

122

123

124

125

126 127

128

129

130131

132

133134

135

136

137

138

139

140

141

142

143

144

145

The La Primavera caldera, with a diameter of ~10 km, borders the study area to the west. It is a very young (Late Pleistocene) volcanic complex underlain by a magma chamber whose top reaches a depth of 4 km (Verma et al., 2012). Drilling has revealed that the oldest units consist of granitic and granodioritic rocks found mainly at a depth of approximately 3000 m. These rocks are mainly overlain by andesitic rocks approximately 1150 m thick. The third lithologic unit, which is approximately 100 m thick, consists of rhyolites. The uppermost unit is a sequence of lithic tuffs and minor andesite with an average thickness of approximately 750 and 1000 m, respectively (Campos-Enríquez et al, 2005; Urrutia et al., 2000; Verma et al., 2012). The system is characterized by an asymmetric structure with NW-SE regional basalt lineaments that belong to the Tepic Zacoalco Rift and local NE-SW fractures in the upper units extending beneath Guadalajara (Alatorre-Zamora and Campos-Enríquez, 1991; Campos-Enríquez and Alatorre-Zamora, 1998). The temperatures, which were measured at the bottom of exploratory wells that were drilled up to 3 km deep, vary from 80 to 300°C (Verma et al., 2012). It appears that heated meteoric water ascends along fault or fracture zones to near surface depths and supplies springs with temperatures of >40°C (Venegas et al., 1985). The hydrothermal fluids are characterized by very high concentrations of Na $(679-810 \text{ mg } \text{I}^{-1})$, CI $(865-1100 \text{ mg } \text{I}^{-1})$, SiO₂ $(943-1320 \text{ mg } \text{I}^{-1})$, B $(75-150 \text{ mg } \text{I}^{-1})$ and TDS $(2810-4065 \text{ mg } \text{I}^{-1})$ (Maciel-Flores and Rosas-Elguera, 1992), while the springs are of Na-Cl-HCO₃ type with relatively high **Commented [JM13]:** Rewritten according to authors response

concentrations of Na (260-331 mg l^{-1}), Cl (85-185 mg l^{-1}), SiO₂ (209-253 mg l^{-1}), HCO₃ (395-508 mg l^{-1}), B (10.8-12.3 mg l^{-1}), F (8.5 mg l^{-1}) and TDS (1071-1240 mg l^{-1}), indicating a mixture between hydrothermal fluids and local rainwater origin with ratios of 1:2 to 1:10 (Gutiérrez-Negrín, 1988; Sánchez-Diaz, 2007).

3 Methods

3.1 Field and laboratory

Water samples were collected from 40 production wells in March 2011 using standard protocols. The samples were analyzed for major and minor ions, trace elements and isotopes (δ^2 H, δ^{18} O, 3 H). Field parameters such as temperature, pH, electrical conductivity (EC), and dissolved oxygen (DO), were measured using portable meters (Thermo, Orion). Alkalinity was determined in the field by volumetric titration (0.02N H₂SO₄) of filtered water samples to pH 4.3. At each sampling site, new and pre-rinsed low density polyethylene bottles were filled with filtered (0.45 μ m) sample water. Cation and silica samples were acidified with ultrapure HCl to pH<2, and all of the samples were stored in the laboratory at a constant temperature of 4°C. Dissolved cations and anions were determined by inductive-coupled plasma mass spectrometry (ICP-MS) and ion chromatography, respectively. Duplicates of selected samples were analyzed using inductive-coupled plasma optical emission spectrometry (ICP-OES) and ion chromatography, following standard methods (APHA, 2012).

Stable water isotopes were analyzed at Environmental Isotope Laboratory, University of Waterloo, Canada. To conduct deuterium (²H) analyses, sample water was reduced on hot manganese (512°C) and the released hydrogen was analyzed by GC-MS. To conduct oxygen-18 (¹⁸O) analyses, water was equilibrated with CO₂. Preparation and extraction took place on a fully automated system vessel attached to a VG MM 903 mass spectrometer. The ²H and ¹⁸O results are reported as δ-values with respect to the VSMOW (Vienna Standard Mean Ocean Water) standard. Tritium (³H) was analyzed at Environmental

Commented [JM14]: Modified

Isotope Laboratory, University of Arizona, using a liquid scintillation counter after electrolytic enrichment.

The average accuracy of tritium analyses was ~0.3 TU.

Commented [JM15]: Modified according to authors response

Commented [JM16]: Changed according to authors response

3.2 Techniques of analysis

A preliminary description of water chemistry and identification of possible processes was performed using a correlation analysis. A hierarchical cluster analysis (HCA) organized samples into classified groups which were evaluated according to their geographic correspondence. A principal component analysis (PCA) elucidated the main controls on groundwater chemistry. All of the statistical calculations were performed using Minitab version 17.1 (Minitab, 2013).

The multivariate mixing and mass balance model, or M3 (Laaksoharju et al., 2008), was used to help to understand groundwater composition. The main aim of M3 is to differentiate between what is due to mixing and what is due to water-rock reactions. The M3 method compares the measured groundwater composition of each sample to the selected reference water and reports the changes in terms of mixing and reactions. A PCA is used to summarize the groundwater data by using the majority of the dissolved groundwater constituents Ca, Na, Mg, K, Cl, SO₄ and HCO₃ in combination with the isotopes δ^2 H, δ^{18} O and 3 H. The outcome of the analyses can be visualized as a scatter plot (PCA plot) for the first two principal components. The observations inside the polygon of the PCA plot are compared to the previously chosen reference water compositions. The mixing calculations create ideal mixing models that use linear distances of the samples from the selected reference waters in the PCA plot.

In this study, the following compositions of samples were used as reference waters: i) three deep wells located in the La Primavera geothermic field and representing hydrothermal water; with data taken from Mahood (1983), Maciel-Flores (1992) and Prol-Ledezma (1995): well PP1 (T=255 °C, Cl=851 mg l⁻¹, B=120 mg l⁻¹, Li=9.9 mg l⁻¹ and Na= mg l⁻¹), well PP2 (T=265 °C, Cl=1,120 mg l⁻¹, B=131 mg l⁻¹, Li=8.5 mg l⁻¹ and Na=2000 mg l⁻¹), and well PP3 (T=265 °C, Cl=1,500 mg l⁻¹, B=54 mg l⁻¹, Li=3.9 mg l⁻¹ and Na=3310 mg l⁻¹); ii)

well AT37 representing local groundwater with low temperature and salinity (Table 1); iii) well AT12 with low temperature and high salinity was taken as polluted reference water (Table 1). Although it is uncertain whether the selected reference waters are end members or close to, they were selected from the available dataset. Well AT37 is an adequate candidate for local groundwater because it is located in the recharge area showing little interaction with rocks. The three deep wells in La Primavera caldera are most probably also an appropriate selection of hydrothermal reference water because their temperatures are in the range of geothermic temperatures according to Verma et al. (2012).

Commented [JM17]: Modified according to authors response

Chloride mass balance was applied with the purpose of validation of the M3 modeling estimates. This method has been discussed and applied in similar environments (e.g. Han et al., 2010) and assumes that extracted groundwater is a mix of two end members (thermal and non-thermal) and that the Cl ion behaves conservative which means that it does not participate in any chemical reactions even at high temperatures.

4 Results and discussion

Sánchez-Diaz (2007) used groundwater temperature and total dissolved solids as criteria to classify wells in hydrothermal water from Toluquilla (HT), hydrothermal water from springs NE of Guadalajara (HG), non-hydrothermal, local groundwater (LG), and mixed groundwater (MG) with both HT and LG (Fig. 4). Considering different sets of historical and new data, this classification is too subjective, especially in the lower TDS range. Furthermore, some inconsistencies between correlation results from different sampling campaigns show that the interpretation is not straightforward. The Mg concentration, for example, decreases with increasing temperature as expected from hydrothermal fluids (Panichi and Gonfiantini, 1981); on the other hand, an increasing Mg trend at low temperatures is observed indicating saline groundwater. Finally, it was not clear if there are different sources of hydrothermal or saline waters that affect the local groundwater. These complications motivated us to use multivariate techniques instead of

commonly used scatterplots and criteria to divide samples into groups and interpret for potential factors/sources. Because the measured parameters varied considerably from study to study, only data from this study were considered for chemical characterization and multivariate analyses.

Commented [JM18]: changed

Commented [JM19]: Changed

4.1 Groundwater Chemical Characterization

214

215

216

217

218

219

220

221

222

223

224

225226

227

228

229

230

231

232

233234

235

236

Table 1 shows the concentrations of measured groundwater chemical elements, field parameters and isotopic data, along with the hydrochemical classification. The classification of waters was performed with HCA using 20 variables (pH, temperature, EC, DO, Na, K, Ca, Mg, Cl, HCO3, SO4, NO3-N, Sr, Si, Fe, F, Zn, 3H, ²H, ¹⁸O). With the help of Ward's linkage rule iteratively neighboring points (samples) were linked through a similarity matrix (Ward, 1963). The squared Euclidian distance was selected as the similarity measurement. The second method was a PCA. For both cluster algorithms, lognormal distributed data were previously log-transformed, and all of the variables standardized (z-scores). The HCA samples were classified into 4 major groups as represented by the dendrogram (Fig. 5) and median values (Table 2). The values for Li, Mn and Ba were not considered in the cluster analysis, because most samples had concentrations below the detection limit. The four groups are plotted on a Piper diagram to demonstrate chemical differences (Fig. 6). Salinity increases as groundwater moves east- and southeastwards from La Primavera field to discharge areas along topographic flow path. EC values reach typically 600 μS cm⁻¹ in the discharge areas of urbanized Guadalajara, except for Toluquilla wells where values ascend to 2300 μS cm⁻¹. Group 4 (n=19) is a Na-HCO₃ water type located in recharge zones in the western portion and reflects a short (local) groundwater flow path with poor circulation. It shows low temperatures (average 25.3 °C) and salinity (254 µS cm⁻¹), however elevated NO₃-N (9.1 mg l⁻¹) values, possibly derived from agricultural practices. Groundwater that moves in northern and eastern direction attains a Na-HCO₃ to mixed HCO₃ water type (group 2, n=12), with increased temperatures (30.2 °C) but similar low salinities (300 μS cm⁻¹), indicating water-rock interactions. Groundwater in the discharge area in central Guadalajara city evolves to a Na-SO4 to mixed HCO₃ water type (group 3, n=3), with higher concentrations of several elements indicating an important impact from anthropogenic pollution, i.e. SO₄ (70.6 mg l⁻¹), NO₃-N (12.4 mg l⁻¹), Na (52.2 mg l⁻¹) and Cl (38.9 mg l⁻¹). Finally, water that moves from recharge zone at Primavera caldera southeast towards the central part of Toluquilla valley, attains a Mg-HCO3 and mixed HCO3 type (group 1, n=6). These wells show highest temperatures (33.8 °C) and salinity (EC=1,575 μ S cm⁻¹), and lowest NO3-N (0.17 mg l⁻¹) (Fig. 3). This preliminary evaluation of evolution of groundwater chemistry along principal flow paths indicates that groundwater flow is affected by different sources. In the central and northern part of the study area local groundwater from La Primavera caldera undergoes water-rock interactions and mixes with mountain-front recharge as well as return flow from agricultural plots and urban water cycling (Fig. 3, Section I and II), while in the southern portion local water mixes with water from deeper formations that interacts with volcanic rocks of the La Primavera caldera and causes increased mineralization and temperatures (Fig. 3, Section I and II). A factor analysis transformed the 20 variables into a reduced number of factors. The PCA, which loads most of the total variance onto one factor, was used in this study. The factors were extracted through the principal components method. Varimax rotation, where one factor explains mostly one variable, was selected. For fixing the maximum number of factors to be extracted, only factors with eigenvalues higher than one were taken into consideration (Kaiser normalization). Table 3 shows that 4 factors may explain 77% of the variance. Factor 1 (42% of the variance) largely represents high salinity. The correlations of temperature, Na and Cl indicate hydrothermal influence, while HCO₃, Na and Sr could be connected to mineralization and rock dissolution processes, and cationic exchange. In factor 2 (17%) the temperature is inversely related with DO, 3H, and to a lesser degree, NO₃ and SO₄, suggesting that this factor represents water affected by human activities, either urban or

237

238

239

240

241242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

agricultural. In addition, Table 1 and Figure 7 shows that waters affected by human activities are most evaporated. Sulfate could be related to contamination due to the infiltration of commonly applied sulfate-based fertilizers during the rainy season. This occurs because all the wells are undersaturated with regard to gypsum, indicating that the water does not move through deposits of this mineral. In factor 3 (11%) the relationship between ²H and ¹⁸O reveals the existence of recharge water. This factor is generated almost entirely by the linear relationship between O and H isotopes. The relation with temperature indicates the recharge conditions at different recharge sites. Factor 4 (7%) may be indicative of dissolution of minerals that contain F. The study of Sánchez-Díaz (2007) indicates that rhyolitic rocks and ashes of the study area are responsible for releasing F. Comparable trends have been observed in various similar volcanic environments in central and northern Mexico (Mahlknecht et al., 2004, Mahlknecht et al., 2008).

4.2 Isotope hydrology

Data from this study and complementary data reported by other investigations (González et al., 1992; GEOEX-SIAPA, 2003) are used to study the origin and evolution of water in the study area (Fig. 7a). The δ^2 H vs. δ^{18} O graph shows that groundwater is of meteoric origin with variable evaporation and mixed with hydrothermal fluid. Although all studies show a similar trend, the data reported by González et al. (1992) registered heavier δ^{18} O values that may be attributable to evaporation or hydrothermal influence. Similar δ^{18} O values in thermal systems have been reported in other studies, e.g. El-Fiky (2009) and Stumpp et al. (2014) with δ^{18} O values ranging from -6.7 to -5.6 % and -4.8 to +0.8 %, respectively. Water from group 1 (hydrothermal influenced) collected in Toluquilla, has a narrow range of δ^{18} O (-9.4 to -8.8%) and δ^2 H (-67 to -68%) values. They tend to fall slightly below and parallel to the RMWL, possibly indicating different climate conditions during recharge. These samples show isotopic depletion, indicating that recharge by meteoric water is low, as demonstrated by a deuterium excess that ranges from 4 to 8 % with an average of 5.5 % (Fig. 7b). On the other hand, it is possible that only a displacement of δ^{18} O is occurring, which

could correspond to a geothermal effect and mixing with meteoric waters (Giggenbach and Lyon, 1977; Herrera and Custodio, 2003). The increased CI concentrations compared to other groups evidences mixture with hydrothermal fluids and longer residence times (Fig. 7c). Group 2 waters, collected in the eastern and southern part of the ATAS, have δ^{18} O and δ^{2} H values ranging from -9.6 to -8.6% and from -63 to -71‰, respectively. These waters fall along the RMWL. Deuterium excess values vary between 5.3 and 8.1 ‰ with an average of 6.7 ‰. These values are similar to other groups (Fig. 7b), therefore, in accordance with the low concentration of CI, groundwater recharge is of meteoric origin (Fig. 7c). Group 3 waters (influenced by anthropogenic pollution) are quite different from the rest; they have heavier δ^{18} O values ranging from -7.9 to -5.7‰, and δ^2 H values varying from -59.6 to -47.5‰, and are strongly affected by evaporation. Also a lower deuterium excess in the order of +4‰ is observed (Fig. 6b y 6c). The enriched outlier AT12 represents groundwater from a recreational park with lagoons. In this well there is a negative deuterium excess indicating that rainwater presented evaporative diffusion processes in the soil during recharge process (Custodio, 1997; Manzano et al., 2001). Group 4 waters, mostly from La Primavera recharge area, are covering a relative wide range of values compared to group 1 and 2. Their δ^{18} O signatures vary from -10.3 to -8.4%, and their δ^2 H signatures from -72.2% to -63.9%. Deuterium excess in these wells is the highest and indicate preferential recharge during certain times of the year (Jiménez-Martínez and Custodio, 2008). The overlapping of group 1, 2 and 4 indicates that aquifer formations are mostly hydraulically interconnected. Although altitude variations are in the order of only 400 m around La Primavera caldera, this seems to be enough to generate an altitude effect (Fig 7d). Tritium results indicate that groundwater within the study area includes both pre-modern (pre-1950s) and modern recharge. The values range from 0.3 to 3.0 TU which suggests a contribution from modern water in most sampled sites (Table 1). Lowest values are in the order of laboratory analysis accuracy, thus these waters may not contain modern water. The majority of waters with ³H lower than 1.0 TU are in the southern portion of the aquifer system. Elevated ³H values (>1.5 TU) located mostly in the La Primavera

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297298

299

300

301

302

303

304

305

volcanic system represent young waters or recent recharge with little mixing of path lines. Waters with ³H values <1.5 TU illustrate that these wells may represent mixing of flow paths with modern and premodern groundwater residence times. These waters are found mostly in Toluquilla, corresponding to elevated EC, Cl and DIC values. The mixing of water from different ages is expectable because the aquifer is under unconfined conditions, while wells penetrate the saturated zone to a considerable depth, at times up to 500 m, and are almost always completely screened.

4.3 Mixing patterns

Using a recommended permissible factor of 0.05 (Laaksoharju et al, 2009), all samples are located inside the cover area of the polygon of PCA plot (Fig. 8). The estimated mixing proportions are present in Table 4. Results indicate that the proportions of hydrothermal fluids are largest in group 1 varying from 1.9 to 12.5%. The hydrothermal mixing proportions according to CI mass balance method were consistently higher, ranging from 6.2 to 20.6%. Especiall AT5 shows important differences between both methods. The other groups show hydrothermal fractions below 1.4% according to M3 modeling and 4.4% obtained from CI mass balance method. The differences between the two methods is not only due to the distinct underlying algorithm of both methods, but also due the fact that M3 modeling uses 3 reference waters and CI mass balance only 2 reference waters (thermal/non-termal). Group 3 represents an insignificant share of hydrothermal water (~0%) due to fact that these wells are located in recharge areas. On the other hand, this group shows an important proportion of anthropogenic impacted water (>50%), while all other groups are less affected (<37%).

These results validate the initial selection of groups based on cluster analysis. Geographically, groundwater with elevated hydrothermal proportions is located in the south to southeastern area (Toluquilla), and elevated proportions of polluted groundwater are located mostly in the urbanized area

of Guadalajara. Hydrothermal fractions computed with Cl mass balance method are general higher than

those with M3 program, while for group 3 (fresh groundwater) there is no correspondence between methods. Differences may be due to the underlying conceptual differences in both approaches. However there is a generally high correlation between both methods ($r^2 = 0.87$) which validates the results.

4.4 Groundwater Flow System of Guadalajara

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

The hydrogeological Atemajac-Toluquilla system is located in the northeastern area of the Tepic-Zacoalco Rift, a complex and active neotectonic structure. Local groundwater recharge for Atemajac-Toluquilla Valley originates from rainfall mainly over the La Primavera caldera in the central western portion of the study unit. It flows from the upper alluvial sediments towards the valley floor and Santiago River. Recharge water is of Na-HCO3 water type with low temperatures, salinities, Cl and Na values, elevated NO3 concentrations, as well as relatively high tritium activities in the range of 0.5 -2.9 TU indicating little mixing of flow paths and recent recharge from pristine soils and return flow from agricultural plots, especially in Toluquilla valley. This result confirms also a relatively fast transport through the unsaturated zone (Herrera and Custodio, 2014). As groundwater circulates in northeastern (Atemajac valley) and eastern direction (Guadalajara city) following the hydraulic gradient, its temperature and salinity increases moderately. The wells are typically drilled in Tala tuff underlain by andesites to basaltic andesite rocks. Locally groundwater evolves to a Na-SO₄ to mixed HCO₃ water type, with relatively high contents of SO₄, NO₃, Na, CI and tritium (~2TU) indicating an important impact from anthropogenic pollution in urban Guadalajara. Underground heat flow suggests the existence of a magma chamber below the La Primavera caldera, which provides hydrothermal fluids observed on surface expressions such as the La Soledad solfatara and the Cerritos Colorados geothermal field. Regional groundwater that is in contact with these fluids circulates through the lower Atemajac-Toluguilla aguifer specifically below Santa Anita and Toluguilla

locations. These Mg-HCO3 to mixed HCO3 waters are characterized by elevated temperatures, salinity, Cl,

Na and HCO₃ values, low tritium values (<1.7 TU) and contain considerable concentrations of Li, Mn, B and F, indicating thermal influence, circulation through an active volcanic center and fault zones, and waterrock interactions. The corresponding wells are typically drilled in basalt-andesitic rock formations. The well depth of these wells range from 200 to 300 m and depth-to-water table is about 50 m. The low tritium concentration indicates pre-modern infiltration. Low tritium concentrations in deep wells, according to Herrera and Custodio (2014), are due to a mix of water from the upper aquifer and the vertical ascending flow from the lower aquifer. On the other hand, the tritium values show that geochemically speaking, the water predominates as an old fraction (Custodio, 1989). The isotopic composition of groundwater confirms the interconnectivity between water from deeper and shallow rock materials.

Commented [JM20]: Rewritten according to authors

5 Conclusions

This work represents the first time that groundwater flow dynamics of Guadalajara region have been analyzed and characterized by using a suite of statistical and geochemical methods. Geochemical methods have been combined with multivariate statistical analysis and the multivariate mixing and mass-balance model (M3) to determine the mixing patterns of different fluids when considering fresh groundwater, hydrothermal fluids and human impacted waters. The mixing proportions have been compared to estimates from chloride mass balance method.

The initial classification of groundwater groups by cluster analysis has been confirmed by water isotopic technologies, and identifying the controlling factors by principle component analysis is consistent with M3 modeling. The origin of groundwater recharge and the mixture of fresh groundwater with hydrothermal fluids and polluted water components was identified. A conceptual flow model was constructed for the Atemajac-Toluquilla aquifer system. The local flow is associated with the infiltration of rainwater that occurs at higher altitudes. Hydrothermal waters are probably related to recharge outside the study area and upward vertical flow in the La Primavera caldera and the valley of Toluquilla. TDS, CI, Na, Mn and Li,

are most indicative of hydrothermal fluids. Modern water polluted with SO₄ and NO₃ can be associated with infiltration of urban sewage and agricultural return flow. According to M3 modeling, the proportion of hydrothermal fluids within older waters was between 1.9% and 12.5%, whereas it was lower than 1.4% within other waters. The proportion of polluted water in groundwater reached up to 52% in urbanized areas. M3 is a powerful tool to evaluate the mixing proportions of selected reference waters present in aquifers. We recommend the use of the suite of traditional methods, environmental tracers, statistical analysis and M3 modeling in other aquifers with potentially multiple groundwater origins, especially in active volcanic systems where mixing is an important process. One limitation with this approach, however, is the representativeness of selected reference waters and samples. Part of this uncertainty may be overcome by repeating the field campaign considering seasonal/time variations. These outcomes may help water authorities to identify wells with hydrothermal mixture or polluted water and act accordingly. The information regarding the proportions of fresh groundwater, hydrothermal fluids and polluted waters in each well indicates that the contaminants can be attributed to source waters. For example, Li, Mn, Ba, F and As can be associated with hydrothermal fluids, and SO₄ and NO₃ are related to the production or use of fertilizers, dyes, glass, paper, soaps, textiles, fungicides or insecticides. These results helps authorities to decide whether certain wells have to be isolated or closed in order to provide

Commented [JM21]: Modified according to authors respsonse

Acknowledgments

Guadalajara with the required drinking water quality.

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

This work was financially supported by Fundación FEMSA and the Chair for Sustainable Water Use (Tecnológico de Monterrey). Fundación FEMSA had no role in study design, data collection and analysis,

decision to publish, or preparation of the manuscript. We would like to thank R. Ledesma and A. Mazón for their assistance in the field work and graphical edition.


References

397

398

- Ako, A. A., Eyong, G. E. T., Shimada, J., Koike, K., Hosono, T., Ichiyanagi, K., Akoachere, R., Tandia, B. K.,

 Nkeng, G. E., and Ntankouo, N. R.: Nitrate contamination of groundwater in two areas of the Cameroon
- 402 Volcanic Line (Banana Plain and Mount Cameroon area), Appl. Water Sci., 4, 99-113, 2013.
- 403 Aksoy, N., Simsek, C., and Gunduz, O.: Groundwater contamination mechanism in a geothermal field: a
- 404 case study of Balcova, Turkey, J. Contam. Hydrol., 103, 13-28, 2009.
- 405 Alatorre-Zamora, M. A. and Campos-Enríquez J. O.: La Primavera Caldera (Mexico): Structure inferred
- from gravity and hydrogeological considerations, Geofis. Int., 31, 371-382, 1991.
- 407 Alva-Valdivia, R., Goguitchaichvili, A., Ferrari, L., Rosas-Helguera, J., Urrutia-Fucugauchi, J., and Zambrano-
- 408 Orozco, J. J.: Paleomagnetic data from the Trans-Mexican Volcanic Belt: Implications for tectonics and
- volcanic stratigraphy, Earth Planets Space, 52, 467-478, 2000.
- 410 APHA.: Standard Methods for examination of water and wastewater, 22nd ed., Washington: American
- 411 Public Health Association, 2012.
- 412 Appelo, C. A. J. and Postma, D.: Geochemistry, groundwater and pollution (2nd ed.): Leiden, The
- 413 Netherlands, A.A. Balkema, 649 p., 2005.
- 414 Bretzler, A., Osenbrück, K., Gloaguen, R., Ruprecht, J. S., Kebede, S. and Stadler, S.: Groundwater origin
- 415 and flow dynamics in active rift systems e a multi-isotope approach in the Main Ethiopian Rift, J.
- 416 Hydrol., 402, 274-289, 2011.



439 J. 10, 5-17, 2002. 440 Di Napoli, R., Aiuppa, A., Bellomo, S., Brusca, L., D'Alessandro, W., Gagliano Candela, E., Longo, M., 441 Pecoriano, G., and Valenza, M.: A model for Ischia hydrothermal system: evidences from the chemistry 442 of thermal groundwaters, J. Volcanol. Geotherm. Res., 186, 133-159, 2009. 443 Di Napoli, R., Martorana, R., Orsi, G., Aiuppa, A., Camarda, M., De Gregorio, S., Gagliano Candela, E., Luzio, 444 D., Messina, N., Pecoraino, G., Bitetto, M., de Vita, S., and Valenza, M.: The structure of a hydrothermal 445 system from an integrated geochemical, geophysical and geology approach: The Ischia Island case 446 study, Geochem. Geophys. Geosyst., 12, 1-25, 2011. Dogdu, M. S. and Bayari, C. S.: Environmental impact of geothermal fluids on surface water, groundwater 447 448 and streambed sediments in the Akarcay Basin, Turkey, Environ. Geol., 47, 325-340, 2005. 449 Edmunds, W. and Smedley, P.: Residence time indicators in groundwater: the East Midlands Triassic 450 sandstone aquifer, Appl. Geochem., 15, 737-752, 2000. 451 El-Fiky, A.: Hydrogeochemistry and Geothermometry of Thermal Groundwater from the Gulf of Suez 452 Region, Egypt, J. King Abdulaziz Univ. Sci., 20, 71-96, 2009. Evans, W. C., Sorey, M. L., Cook, A. C., Kennedy, B. M., Shuster, D. L., Colvard, E. M., White, L. D., and 453 454 Huebner, M. A.: Tracing and quantifying magmatic carbon discharge in cold groundwaters: lessons learned from Mammoth Mountain, USA, J. Volcanol. Geotherm. Res., 114, 291-312, 2002. 455

Ferrari, L., Valencia-Moreno, M., and Bryan, S.: Magmatism and tectonics of the Sierra Madre Occidental

and its relation with the evolution of the western margin of North America, in: Geology of México:

Celebrating the Centenary of the Geological Society of México, edited by: Alaniz-Álvarez, S.A. and

Nieto-Samaniego, A.F., Geol. Soc. Am., Special Paper, 422, 1-39, 2007.

De Vries, J. J. and Simmers, I.: Groundwater recharge: an overview of processes and challenges, Hydrogeol.

438

456

457

458

460 Forrest, M. J., Kulongoski, J. T., Edwards, M. S., Farrar, C. D., Belitz, K., and Norris, R. D.: Hydrothermal 461 contamination of public supply wells in Napa and Sonoma Valleys, California. Appl. Geochem., 33, 25-462 40, 2013. 463 Furi, W., Razack, M., Abiye, T. A., Kebede, S., and Legesse, D.: Hydrochemical characterization of complex 464 volcanic aquifers in a continental rifted zone: the Middle Awash basin, Ethiopia, Hydrogeol. J., 20, 385-400, 2011. 465 466 GEOEX-SIAPA.: Estudio geohidrológico Atemajac-Toluquilla, Sistema Intermunicipal de Agua Potable y 467 Alcantarillado (SIAPA), Guadalajara, Jalisco, México, 2003 Ghiglieri, G., Pittalis, D., Cerri, G., and Oggiano, G.: Hydrogeology and hydrogeochemistry of an alkaline 468 volcanic area: the NE Mt. Meru slope (East African Rift-Northern Tanzania), Hydrol. Earth. Syst. Sci., 16, 469 470 529-541, 2012. 471 Giggenbach, W. F. and Lyon, G. L.: The chemical and isotopic composition of water and gas discharges 472 from the Ngawha geothermal field, Northland, DSIR, Chem. Div. Report No: CD:30/555/7, 1977. 473 Goff, F. and Janik, C. J.: Geothermal systems, in: Encyclopedia of Volcanoes, edited by: Sigurdsson, H., 474 Houghton, B., McNutt, S., Rymer, H., and Stix, J., Academic Press, San Diego, CA, 817-834, 2000. 475 González, H. L., Mata, A. I., Sánchez, D. L. F.: Estudio isotópico e hidroquímico de los acuíferos de 476 Toluquilla-Ocotlán-La Barca, en el estado de Jalisco, Informe técnico, Instituto Mexicano de Tecnología 477 del Agua, 1992. 478 Gutiérrez-Negrín, L. C. A.: Recursos Geotérmicos en La Primavera, Jalisco, Ciencia y Desarrollo, 16, 57-69, 1991. 479

Gutiérrez-Negrin, L.: La Primavera, Jalisco, Mexico: geothermal field, Transactions of the Geothermal

480

481

Research Council, 12, 161-165, 1988.


482 Han, D. M., Liang, X., Jin, M. G., Currell, M. J., Song, X. F., and Liu, C.M.: Evaluation of groundwater 483 hydrochemical characteristics and mixing behavior in the Daying and Qicun geothermal systems, 484 Xinzhou Basin, J. Volcanol. Geotherm. Res., 189, 92-104, 2010. 485 Henley, R. W. and Ellis, A. J.: Geothermal systems, ancient and modern: a geochemical review, Earth. Sci. 486 Rev., 19, 1-50, 1983. 487 Herrera C. and Custodio, E.: Hipótesis sobre el origen de la salinidad de las aguas subterráneas en la isla de Fuerteventura, Archipiélago de Canarias, España, Bol. Geol. Min., 114, 433-52, 2003. 488 489 Herrera, C. and Custodio, E.: Groundwater flow in a relatively old oceanic volcanic island: The Betancuria 490 area, Fuerteventura Island, Canary Islands, Spain. Sci. Total. Environ., 496, 531-550, 2014. 491 Hockstein, M. P. and Browne, P. R. L.: Surface manifestations of geothermal systems with volcanic heat sources, in: Encyclopedia of Volcanoes, edited by: Sigurdsson, H., Houghton, B., McNutt, S., Rymer, H., 492 493 and Stix, J., Academic Press, San Diego, CA, 835-856, 2000. 494 Jiménez-Martínez, J. and Custodio E.: El exceso de deuterio en la lluvia y en la recarga a los acuíferos en 495 el área circum-mediterránea y en la costa mediterránea española, Boletín Geológico y Minero, 119, 496 21-32, 2008. Laaksoharju, M., Skårman, E., Gómez, J.B., and Gurban, I.: M3 version 3: user's manual. SKB TR-09-09. 497 498 Stockholm, Sweden: Svensk Kärnbränslehantering AB; 2009. 499 Laaksoharju, M., Smellie, J., Tullborg, E-L., Gimeno, M., Molinero, J., Gurban, I., and Hallbeck, L.: 500 Hydrogeochemical evaluation and modelling performed within the site investigation programme, 501 Appl. Geochem, 23, 1761-1795, 2008.

Maciel-Flores, R. and Rosas-Elguera, J.: Modelo geológico y evaluación del campo geotérmico La

Primavera, Jal., México, Geofís. Int., 31, 359-370, 1992.

502

504	Mahlknecht, J., Horst, A., Hernández-Limón, G., and Aravena, R.: Groundwater geochemistry of the
505	Chihuahua City region in the Rio Conchos Basin (Northern Mexico) and implications for water resources
506	Management, Hydrol. Process., 22, 4736-4751, 2008.
507	Mahlknecht, J., Steinich, B., and Navarro de León I.: Groundwater chemistry and mass transfers in the
508	Independence aquifer, central Mexico, by using multivariate statistics and mass-balance models,
509	Environ. Geol, 45, 781-95, 2004.
510	Mahood, G. A., Truesdell, A. H. and Templos M. L. A.: A reconnaissance geochemical study of La Primavera
511	geothermal area, Jalisco, Mexico, J. Volcanol. Geotherm. Res., 16, 247-261, 1983.
512	Manzano, M., Custodio, E., Loosli, H., Cabrera, M. C., Riera, X., and Custodio, J.: Palaeowater in coastal
513	aquifers of Spain, in: Palaeowaters in Coastal Europe: Evolution of Groundwater since the Late
514	Pleistocene, edited by: Edmunds, W.M. and Milne, C.J., Geological Society of London: Special
515	Publication, 189: 107-138, 2001.
516	Michaud, F., Gasse, F., Bourgois, J., and Quintero, O.: Tectonic controls on lake distribution in the Jalisco
517	Block area (western Mexico) from Pliocene to Present, in: Cenozoic Tectonics and Volcanism of Mexico,
518	edited by: Delgado-Granados, H., Aguirre-Díaz, G.J., and Stock, J.M., Geol. Soc. Am., Special paper, 334,
519	99-110, 2000.
520	Minitab (2013). Statistical Software (versión 17.1). MINITAB® and all other trademarks and logos for the
521	Company's products and services are the exclusive property of Minitab Inc. All other marks referenced
522	remain the property of their respective owners.
523	Navarro, A., Font, X., and Viladevall, M. Geochemistry and groundwater contamination in the La Selva
524	geothermal system (Girona, Northeast Spain), Geothermics, 40, 275-285, 2011.



547 Siebert, C., Rosenthal, E., Möller, P., Rödiger, T., and Meiler, M.: The hydrochemical identification of 548 groundwater flowing to the Bet She'an-Harod multiaquifer system (Lower Jordan Valley) by rare earth 549 elements, yttrium, stable isotopes (H, O) and Tritium, Appl. Geochem, 27, 703-714, 2012. 550 Stumpp, C., Ekdal, A., Gönenc, I. E., and Maloszewski, P.: Hydrological dynamics of water sources in a 551 Mediterranean lagoon, Hydrol. Earth. Syst. Sci., 18, 4825-4837, 2014. 552 Urrutia F. J., Alva-Valdivia, L. M., Rosas-Elguera, J., Campos-Enriquez, O. Goguitchaichvili, A., Soler-553 Arechalde, A. M., Caballero-Miranda, C., Venegas Salgado, S., and Sanchez-Reyes, S.: 554 Magnetostratigraphy of the volcanic sequence of Río Grande de Santiago-Sierra de la Primavera 555 region, Jalisco, western Mexico, Geofis. Int., 39, 247-265, 2000. Valencia, V. A., Righter, K., Rosas-Elguera, J., Lopez-Martinez, M., and Grove, M.: The age and composition 556 557 of the pre-Cenozoic basement of the Jalisco Block: implications for and relation to the Guerrero 558 composite terrane, Contrib. Mineral. Petrol., 166, 801-824, 2013. 559 Venegas, S. S., Ramírez, S. G., Romero, G. C., Reyes, V. P., Razo, M. A., Gutiérrez, N. L. C. A., Arellano, G. F. and Rerezyera, Z. J.: La Primavera geothermal field, Jalisco, in: The Geology of North America, edited 560 561 by: Salas, G.P., Economic Geology, Mexico. The Geological Society of America, 1991. 562 Venegas, S., Herrera, J. J., and Maciel, F. R.: Algunas características de la Faja Volcánica Mexicana y de sus 563 recursos geotérmicos, Geofis. Int., 24, 47-83, 1985. 564 Verma, S. P., Arredondo-Parra, U. C., Andaverde, J., Gómez-Arias, E., and Guerrero-Martínez, F. J.: Threedimensional temperature field simulation of a cooling of a magma chamber, La Primavera caldera, 565 566 Jalisco, Mexico, Int. Geol. Rev., 54, 833-843, 2012.

Ward, J. H.: Hierarchical grouping to optimize an objective function, J. Am. Stat. Assoc., 58, 236-244, 1963.

568 Wassenaar, L. I., Van Wilgenburg, S. L., Larson, K., and Hobson, K. A.: A groundwater isoscape (δD, δ¹⁸O) 569 for Mexico, J. Geochem. Explor., 102, 123-36, 2009. 570 Williams, A. J., Crossey, L. J., Karlstrom, K. E., Newell, D., Person, M., and Woolsey, E.: Hydrogeochemistry 571 of the Middle Rio Grande aquifer system - Fluid mixing and salinization of the Rio Grande due to fault 572 inputs, Chem. Geol., 351, 281-298, 2013. 573 Zarate-del Valle, P. F. and Simoneit, B. R. T.: La generación de petróleo hidrotermal en sedimentos del 574 Lago Chapala y su relación con la actividad geotérmica del rift Citala en el estado de Jalisco, Rev. Mex. 575 Cienc. Geol., 22, 358-370, 2005. 576 **Table Captions** 577 578 Table 1: Concentrations of measured field parameters, groundwater elements, isotopic data, and 579 hydrochemical classification. Data are given in mg I⁻¹, except otherwise indicated. Note: T = temperature, 580 DO = dissolved oxygen, EC = electrical conductivity, Bal. = ion balance error, S.U. = standard units 581 Table 2: Median values of water chemistry of the groundwater subgroups determined from HCA. Data are given in mg l⁻¹, except where otherwise indicated. 582 583 Table 3: Rotated component matrix of the factor analysis for groundwater samples from the Atemajac Toluquilla aquifer system. Coefficients between -0.1 and 0.1 are suppressed. Note: DO = dissolved oxygen, 584 T = temperature, EC = electrical conductivity. 585 586 Table 4: Mixing proportions from the multivariate mixing and mass-balance model, M3, using the 587 following reference waters: deep wells PP1, PP2 and PP3 as a reference for hydrothermal fluids; no. 12 as 588 a reference for polluted water; and no. 37 as reference for fresh groundwater, and hydrothermal mixing




Figure Captions 595 Figure 1: Location of study area (black area) in Mexico and tectonic structures of western Central Mexico. 596 597 Figure 2: Surface geology, water table distribution and location of wells sampled in the study area. Note: 598 GMA = Guadalajara metropolitan area 599 Figure 3: Cross-sections indicated in Fig. 2 and considering hydrogeological settings and water types of 600 selected wells. Figure 4: Plot of water temperature vs. total dissolved solids for different groundwater collecting 601 602 campaigns in the study area. The delimitation of classified wells according to Sánchez-Díaz (2007) is also 603 shown. Note: HT=hydrothermal water from Toluquilla, HG=hydrothermal water from springs NE of Guadalajara, LG=local groundwater, MG = mixed groundwater (HT and LG). 604 605 Figure 5: Dendrogram showing HCA classification with groups and subgroups of samples of the Atemajac-606 Toluquilla aquifer system. The dashed line indicates the "phenon line", an arbitrary line that defines 607 subgroups. Figure 6: Piper diagram of groundwater samples from the Atemajac-Toluquilla aquifer system with well 608 609 groups. 610 Figure 7: (a) Deuterium and oxygen-18 in groundwater from the ATAS using this and previous studies. Note: GMWL = Global Meteoric Water Line (Rozanski et al., 1993), RMWL = Regional Meteoric Water Line 611 (Wassenaar et al., 2009); (b) oxygen-18 vs. deuterium excess with labelled altitudes; (c) oxygen-18 vs. 612 613 chloride concentration; and (d) oxygen-18 vs. altitude. Figure 8: PCA plots of the M3 model from mixing of hydrothermal fluids with cold groundwater and 614 615 polluted waters.

ID	Well name	Well depth	pH	Т	EC	DO	Na	к	Ca	Mg	CI	HCO ₃	SO ₄	NO ₃ -N	Sr	SiO ₂	Fe	F	Zn	Li	Mn	Ва	3H	²H	10	Bal	Water type
		(m)	(S.U.)	(°C)	(uS cm ⁻¹)																		(TU)	(‰)	(%)	(%)	
AT1	Toluquilla 1	300	7.3	25	345	5.34	44.2	6.8	13.3	4.9	9.4	146.4	21.5	3.8	0.07	44	0.05	0.95	0.040	0.06	<0.01	0.05	1.70	-64.3	-8.6	-4	Na-Ca-HCO3
AT2	Toluquilla 6	300	7.0	25	1619	5.76	152.0	58	28.9	103	70.1	1068.8	6.5	<0.04	0.38	38.5	0.14	0.33	0.066	0.33	0.26	0.5	0.70	-68.4	-9.3	-8	Mg-Na-HCO3
AT3	Toluquilla 17	200	7.0	25	2310	5.25	114.0	36	58.7	92.9	82.4	1031.3	5.0	0.07	0.45	35.1	0.18	0.65	0.018	0.33	0.51	0.32	0.70	-66.5	-8.8	-10	Mg-Na-HCO3
AT4	Toluquilla 22	300	7.0	31.8	1792	5.1	147.0	40.9	89.7	113	85.4	1415.2	6.6	<0.04	0.61	53.6	0.05	0.99	0.076	0.37	0.22	0.26	1.20	-67.4	-9.1	7	Mg-Na-HCO3
AT5	Toluquilla 7	230	7.0	36.4	1900	5.48	174.0	48.4	80.7	104	229.0	697.6	22.4	< 0.04	0.52	61.6	0.37	3.50	0.088	0.47	0.83	0.39	0.40	-66.5	-8.9	3	Mg-Na-HCO3-CI
AT6	Las Pintas	250	7.2	33.6	718	6.21	102.0	33.9	31.2	16	14.5	435.2	5.9	0.03	0.32	40	0.04	0.26	0.023	<0.05	0.04	0.08	0.90	-64.7	-8.8	6	Na-HCO3
AT7	Garabatos	200	6.8	25	188.9	6.73	16.1	1.2	2	0.4	2.2	24.4	9.7	4.53	0.01	22.8	0.03	1.01	0.020	<0.05	<0.01	<0.02	2.20	-70.5	-9.6	2	Na-HCO3-SO4
AT8	Santa Ana Tepetitlan	250	6.9	25.8	240.4	6.02	38.5	2.3	5.8	1	30.6	18.3	34.6	71.6	0.01	45.3	0.02	3.79	0.005	0.08	<0.01	<0.02	0.60	-71.5	-9.9	9	Na-NO3-CI-SO4
AT9	Tapatios 1	258	6.2	25	310	6.61	57.3	7.2	6.7	2.3	3.7	122.0	12.3	4.68	0.02	52.6	0.03	0.97	0.224	0.09	<0.01	<0.02	1.20	-71.1	-9.8	9	Na-HCO3
AT10	Topacio	235	6.7	21.8	569	6.34	63.8	21	14.3	6.3	5.2	242.2	8.9	0.42	0.1	38.4	0.03	0.84	0.092	<0.05	<0.01	0.05	0.90	-65.2	-8.9	13	Na-Ca-Mg-HC03-S04-CI
AT11	Jardines del Bosque	250	7.1	27.8	309	5.75	26.5	3.5	7.8	2.6	14.0	30.5	29.4	5.76	0.03	29.8	0.02	0.46	0.046	<0.05	<0.01	0.04	2.10	-63.9	-8.4	12	Na-Mg-Ca-HCO3
AT12	Agua Azul	40	7.1	29.1	354	3.3	44.1	8.9	23	7.4	50.3	24.4	95.2	11.8	0.12	41.4	0.02	0.20	0.005	<0.05	<0.01	<0.02	2.40	-47.5	-5.7	0	Na-Mg-Ca-HCO3
AT13	Educadores Jalisc.	300	6.5	32.8	1111	3.93	14.6	6.3	16.8	4.8	1.3	102.5	1.1	0.43	0.12	35	0.02	0.21	0.161	<0.05	<0.01	<0.02	0.50	-67.0	-9.1	7	Na-Mg-HCO3
AT14	Tanque Tesistán	292	7.1	32.5	325	4.22	23.3	6	5.1	2.6	4.8	58.6	7.1	1.12	0.04	22.9	0.02	0.72	0.092	<0.05	<0.01	<0.02	1.00	-64.4	-8.8	7	Na-Ca-HCO3
AT15	Górgoros	80	7.4	30.6	231.7	6.5	38.4	4.5	4.2	1.3	11.0	78.1	25.2	5.40	0.02	48.6	0.03	0.81	0.198	<0.05	<0.01	<0.02	1.50	-65.6	-9.0	-5	Na-Ca-Mg-HCO3
AT16	Fray Pedro	70	7.3	30	334	4.28	21.0	6.5	4.6	2.2	5.6	68.3	8.5	1.43	0.03	20.1	0.02	0.34	0.095	<0.05	<0.01	<0.02	0.30	-62.4	-8.7	9	Na-Mg-HCO3
AT17	Bajo La Arena B	80	8.7	24.6	218.5	4.32	20.8	2.8	1.8	0.5	0.7	53.7	2.2	2.40	0.01	48.3	0.04	1.40	0.584	<0.05	<0.01	<0.02	0.90	-72.2	-9.9	4	Na-Mg-Ca-HCO3
AT18	S. Juan de Ocotán 1	120	7.9	22.5	345	4.95	27.1	8.5	4.5	4.2	2.0	87.8	1.5	0.05	0.02	25.6	0.04	2.49	0.132	<0.05	<0.01	<0.02	0.70	-67.1	-9.4	8	Na-Ca-HCO3-SO4
AT19	Manantial Toluquilla		8.3	24.6	143.9	5.8	57.5	13.4	25	12.6	35.6	87.8	65.7	13.8	0.18	38.2	0.07	0.57	0.308	<0.05	<0.01	0.13	2.00	-59.2	-7.9	-1	Na-HCO3-F
AT20	La Estancia 4	150	7.7	23.6	382	2.42	39.1	9.4	13.3	8.6	3.3	162.7	2.5	0.41	0.16	37.7	0.19	0.32	0.294	<0.05	<0.01	0.03	0.40	-67.0	-9.4	12	Na-Ca-HCO3
AT21	La Loma de S. Juan	60	7.5	25.3	569	4.4	38.3	8.6	16.7	12.9	7.2	172.2	6.1	0.95	0.18	44.3	0.03	0.46	0.963	<0.05	<0.01	<0.02	0.80	-67.8	-9.5	5	Na-Mg-Ca-HCO3
AT22	Rancho Alegre	150	7.7	27.5	213.9	4.5	92.6	28.5	37.3	47.8	41.5	467.9	19.6	0.80	0.47	46.6	0.06	0.94	0.397	0.16	0.13	0.12	0.50	-66.3	-9.3	1	Na-HCO3
AT23	Mimbela	50	6.9	28.2	445	5.02	55.0	10.3	18.5	6.1	30.7	97.6	50.8	11.7	0.09	43.4	0.03	0.22	0.008	<0.05	<0.01	0.03	1.90	-59.6	-7.9	-3	Na-HCO3
AT24	Tesistan 14	120	7.0	25.1	305	6.34	33.9	3.5	3.8	1.3	3.1	126.9	13.5	4.20	0.02	45.4	0.05	0.37	0.020	0.06	<0.01	<0.02	1.90	-68.8	-9.6	7	Na-Ca-SO4-HCO3-CI
AT25	Fovisste	200	6.8	24.4	649	6.68	18.4	7.8	3.1	1.7	1.8	43.9	6.7	2.08	0.02	44.2	0.03	0.35	0.035	<0.05	<0.01	<0.02	0.80	-69.2	-9.5	5	Na-Ca-SO4-CI
AT26	Power Center	90	7.5	32.6	190.7	5.65	35.3	6.1	7.5	2.7	2.1	113.7	8.6	1.58	0.04	41.9	0.05	0.24	0.033	<0.05	<0.01	<0.02	1.60	-68.3	-9.5	4	Ca-Na-Mg-HCO3
AT27	Virreyes	300	6.8	29.4	363	4.81	43.9	7.2	5	3.2	1.1	146.4	1.5	0.73	0.02	51.6	0.12	1.16	0.113	0.06	<0.01	<0.02	0.80	-70.9	-10.0	5	Na-HCO3
AT28	Tesistan 61	275	6.7	24.6	222.4	5.94	27.0	4.4	4	1.6	1.4	83.0	3.5	2.07	0.02	47.8	0.35	0.39	0.431	<0.05	<0.01	<0.02	1.60	-69.4	-9.7	1	Na-HCO3-SO4
AT29	Tesistan 56	270	6.9	33.7	298	7.66	16.7	1.7	7.1	2.1	7.6	30.5	21.0	6.75	0.01	19.1	0.02	0.22	0.019	<0.05	<0.01	<0.02	1.70	-66.5	-9.3	6	Na-HCO3
AT30	Tesistan 70	250	7.1	26	107.8	4.83	20.0	8.8	7	1.9	2.9	60.8	12.3	5.72	0.07	47.5	0.03	0.390	0.048	<0.05	<0.01	<0.02	1.70	-67.8	-9.4	-1	Na-HCO3
AT31	Unid. Dep. Tonala	118	6.7	29.8	351	3.5	40.3	12.7	13.3	7.6	3.4	181.8	1.7	1.06	0.14	35.2	0.06	0.26	0.112	<0.05	<0.01	<0.02	0.70	-65.6	-9.0	13	Na-HCO3
AT32	San Ismael	285	6.7	23.9	451	4.37	20.2	7.5	15.8	7.8	0.3	132.2	0.2	0.05	0.17	33.6	0.03	0.06	0.100	<0.05	<0.01	0.03	0.70	-64.8	-8.8	15	Na-Ca-HCO3-SO4-CI
AT33	Tateposco 2	250	6.8	25.5	192.1	5.46	44.5	13.4	12.6	8	6.3	166.4	2.4	0.7	0.14	35.9	0.03	0.34	0.130	<0.05	<0.01	<0.02	0.70	-64.5	-8.9	-15	Na-HCO3
AT34	El Lindero	55	6.7	26.6	138.9	6.57	22.2	7.4	8.5	5.5	1.2	97.6	6.1	2.02	0.11	40.8	0.03	0.18	0.182	<0.05	<0.01	0.03	2.00	-68.9	-9.6	4	Na-HCO3
AT35	Vivero Los Amigos	24	6.6	27.3	234.7	7.72	19.9	16.6	10.1	4.1	2.7	53.7	40.1	25.4	0.08	30.9	0.02	0.03	0.070	<0.05	<0.01	<0.02	2.90	-64.5	-9.4	5	Na-HCO3
AT36	El Taray	200	6.4	24.7	242	4.37	11.5	7.8	9.3	4.7	0.5	102.5	0.3	0.12	0.04	36	0.03	0.26	0.341	<0.05	<0.01	<0.02	0.70	-67.1	-9.3	3	Na-HCO3
AT37	Viveros del Sur	54	6.3	27.7	160.3	5.63	14.1	0.6	1.9	0.3	2.1	29.3	2.1	1.19	0.01	20.3	0.14	4.90	0.084	<0.05	0.02	<0.02	0.50	-71.6	-10.3	2	Na-HCO3
AT38	Las Pomas	115	6.2	26.4	310	5.74	33.9	1.8	13.5	2.4	9.5	78.1	21.2	5.94	0.02	27.3	0.02	1.67	1.040	0.08	<0.01	<0.02	1.80	-68.5	-9.5	4	Na-Ca-HCO3-SO4
AT39	Potrero La Ordeña	64	6.7	25	165.9	5.93	31.9	8.8	13.2	8.2	10.1	97.6	23.4	17.7	0.15	25.5	0.03	1.25	0.065	<0.05	<0.01	<0.02	1.00	-68.3	-9.4	-22	Na-Ca-HCO3
AT40	Los Gigantes	62	8.0	31.6	182.8	5.65	30.9	2.7	4.7	1.3	2.8	58.6	6.9	4.87	0.02	38.3	0.02	1.71	0.252	0.06	<0.01	<0.02	0.50	-70.4	-9.6	-6	Na-Ca-Mg-HCO3
		·		1	·									<u> </u>				<u> </u>	<u> </u>								

Table 2:

Group	N	Parameter	pH (S.U.)	T	EC cm-1)	TDS	DO	³ H (TU)	б²Н С	δ ¹⁸ O	HCO ₃	к	Mg	Si	Ca	Fe	Na	Sr	Zn	F	CI	NO ₃ -N	SO ₄	Li	Ва	Mn
1	6	Average	6.9	33.8	1575	733	5.4	0.73	-66.65	-9.02	852.7	41.0	79.5	45.9	54.4	0.14	130.3	0.46	0.11	1.11	87.2	0.17	11.0	0.29	0.28	0.33
		Median	7.0	33.6	1706	710	5.4	0.70	-66.52	-8.98	864.5	38.5	98.0	43.3	48.0	0.10	130.5	0.46	0.07	0.80	76.3	0.05	6.5	0.33	0.29	0.24
2	12	Average	7.2	30.2	300	95	4.5	0.66	-66.09	-9.10	128.0	9.2	5.9	33.6	10.9	0.04	31.2	0.10	0.23	0.67	3.5	0.97	0.0		0.04	
		Median	7.1	29.9	317	89	4.4	0.70	-66.27	-9.07	117.4	8.2	5.6	35.6	13.0	0.03	29.0	0.11	0.13	0.34	3.3	0.57	2.4	0.00	0.03	0.01
3	3	Average	6.8	23.4	556	229	4.7	2.1	-55.5	-7.2	69.9	10.9	8.7	41.0	22.2	0.04	52.2	0.13	0.11	0.3	38.9	12.4	70.6	0.00	0.08	0.01
		Median	6.7	23.9	569	241	5.0	2.0	-59.2	-7.9	87.8	10.3	7.4	41.4	23.0	0.03	55.0	0.12	0.01	0.2	35.6	11.8	65.7	0.00	0.08	0.01
4	19	Average	7.0	25.3	254	84	6.0	1.5	-68.5	-9.5	75.5	5.4	2.5	38.6	6.6	0.06	29.4	0.04	0.17	1.1	6.2	9.1	15.5	0.02	0.04	0.01
		Median	6.8	25.0	235	77	5.9	1.6	-68.8	-9.5	78.1	4.5	2.1	44.0	6.7	0.03	27.0	0.02	0.07	8.0	2.9	4.5	12.3	0.00	0.04	0.01

Table 3:

Variable	PC1	PC2	PC3	PC4
рН				0.47
Т	0.24	0.23	0.29	
EC	0.32			
DO		-0.25		
³ H		-0.37		0.15
² H			0.45	-0.20
¹⁸ O			0.45	
HCO₃	0.32			
К	0.32			
Mg	0.33			
SiO ₂				-0.23
Ca	0.32			
Fe				-0.37
Na	0.33			
Sr	0.32			0.13
Zn				
F				-0.371
Cl	0.3			
NO ₃		-0.40		
SO ₄		-0.50		
Eigenvalue	8.43	3.38	2.21	1.34
% of variance	42	17	11	7
Cum. % variance	42	59	70	77

Table 4:

			Cl m-b calculations						
Well ID	Well group	% fresh grou	ndwater	% pollut	ed water	% hydrothei	rmal water	% hydrothe	ermal water
		Avg	SD	Avg	SD	Avg	SD	Avg	SD
2	1	78.1	0.6	17.0	0.1	4.9	0.7	6.2	1.4
3	1	68.1	0.7	26.4	0.1	5.5	0.7	7.3	1.7
4	1	73.6	0.7	21.3	0.1	5.1	0.8	7.6	1.7
5	1	63.1	2.0	24.4	0.2	12.5	2.2	20.6	4.8
6	1	67.7	0.0	30.4	0.0	1.9	0.0	1.1	0.3
22	1	75.6	0.3	21.4	0.0	3.0	0.3	3.6	0.8
10	2	71.1	0.1	28.5	0.0	0.4	0.1	0.3	0.1
33	2	69.5	0.1	29.8	0.0	0.7	0.1	0.4	0.1
18	2	80.3	0.1	19.0	0.0	0.7	0.1	0.0	0.0
40	2	89.0	0.0	10.2	0.0	0.8	0.0	0.1	0.0
14	2	68.3	0.1	31.2	0.0	0.6	0.1	0.2	0.1
16	2	62.6	0.1	36.1	0.0	1.2	0.1	0.3	0.1
13	2	76.1	0.1	22.5	0.0	1.4	0.1	0.0	0.0
32	2	69.0	0.1	30.4	0.0	0.7	0.1	0.0	0.0
36	2	78.9	0.1	20.1	0.0	1.1	0.1	0.0	0.0
21	2	82.7	0.0	16.5	0.0	0.9	0.0	0.5	0.1
31	2	72.3	0.1	26.4	0.0	1.3	0.1	0.1	0.0
20	2	80.4	0.1	19.3	0.0	0.3	0.1	0.1	0.0
12	3	0.0	0.0	100.0	0.0	0.0	0.0	4.4	1.0
19	3	48.2	0.0	51.8	0.0	0.0	0.0	3.1	0.7
23	3	48.8	0.0	51.0	0.0	0.1	0.0	2.6	0.6
1	4	66.3	0.0	33.7	0.0	0.0	0.0	0.7	0.2
15	4	73.4	0.0	26.6	0.0	0.0	0.0	0.8	0.2
11	4	63.0	0.0	36.8	0.0	0.2	0.1	1.1	0.2
38	4	84.8	0.0	15.2	0.0	0.0	0.0	0.7	0.2
39	4	82.9	0.0	16.7	0.0	0.3	0.0	0.7	0.2
7	4	89.7	0.0	10.1	0.0	0.2	0.0	0.0	0.0
29	4	78.4	0.0	21.4	0.0	0.2	0.0	0.5	0.1
34	4	86.7	0.0	13.3	0.0	0.0	0.0	0.0	0.0
35	4	75.8	0.0	24.2	0.0	0.0	0.0	0.1	0.0
9	4	93.1	0.0	6.6	0.0	0.3	0.0	0.1	0.0
25	4	85.9	0.1	13.8	0.0	0.4	0.1	0.0	0.0
24	4	86.5	0.0	13.5	0.0	0.1	0.0	0.1	0.0
26	4	84.1	0.1	15.5	0.0	0.4	0.1	0.0	0.0
30	4	82.3	0.0	17.7	0.0	0.0	0.0	0.1	0.0
17	4	96.2	0.0	3.3	0.0	0.5	0.0	0.0	0.0
27	4	95.2	0.0	4.8	0.0	0.0	0.0	0.0	0.0
28	4	88.4	0.0	11.1	0.0	0.5	0.0	0.0	0.0
8	4	93.8	0.2	4.5	0.0	1.7	0.3	2.6	0.6
37	4	100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Figure 1:




Figure 3:




Figure 4:




Figure 5:




Figure 6:




Figure 7:




Figure 8:

