# **Anonymous Referee #1**

Suggestions for revision or reasons for rejection (will be published if the paper is accepted for final publication)

The authors have generally addressed my comments in an acceptable manner. I have a few suggestions for further corrections with regard to my earlier comments. Once those and the other reviewers' comments have been addressed, the manuscript can be published, but should be throughly proofread by a native/fluent English speaker.

**Answer:** Thank you for your comment. Originally, this manuscript was proofread by professional English edit company. However, we read and modified the manuscript very carefully according to Referee's suggestion..

1) The comments about snow detection and R>200 mm/h cases would be good to mention in appropriate places in the manuscript text in addition to your reply to reviewers.

**Answer:** Thank you for your comment. According to Referee's suggestion, we added the sentences as follows:

[Line 187-189]

'i) Non-liquid type data (e.g., snow, hail etc.) were excluded by routine observation and surface weather chart provided by Korea Meteorological Administration (KMA).'

[Line 192-194]

'data for R>200 mm h<sup>-1</sup> were not included in the analyses, even though the number of samples was only 64 for the entire period.'

2) The tendency of the Gamma DSD to overestimate at D0 < 0.5 mm is not an intrinsic property of the Gamma DSD. I'm afraid that the authors have misunderstood the statements in the studies they have cited. This statement should be removed from the text in order to avoid misrepresenting the cited studies.

**Answer:** Thank you for your comment and we understood Referee's meaning. Therefore we removed this sentence to avoid misunderstand.

3) Regarding the T-Matrix, allow me to rephrase my original question because the authors still have not answered it after two revisions. What I tried to ask was: did you write your T-Matrix program yourself, or did you use somebody else's code? If you used code from somebody else, which code was it?

**Answer:** Thank you for your comment and we apologize for misunderstand Referee's comment exactly. This T-matrix program code was given by Prof. Bringi at Colorado State University.

We added sentence about this in the Acknowledgments as follows;

[Line 565-567]

The authors acknowledge providing, weather chart, and AWS data for this work from the Korea Meteorological Administration. The authors also acknowledge providing codes for scattering simulation from Professor V. N. Bringi at Colorado State University.

# **Anonymous Referee #4**

Suggestions for revision or reasons for rejection (will be published if the paper is accepted for final publication)

The paper has been improved and corrected with the proposed comments and suggestions.

There's just a new error that must be corrected at line 239: the exponent must be preceded by a minus sign.

**Answer:** Thank you for your comment. I corrected the equation as follows

[Line 244]

 $N_0 > 4 \times 10^9 R^{-4.3} \text{ in } m^{-3} mm^{-1}$ 

# Climatological Characteristics of Raindrop Size

1

2

# Distributions in Busan, Korea

3	Sung-Ho SUH <sup>1</sup>
4	
5	Cheol-Hwan YOU <sup>2*</sup>
6	Email: youch@pknu.ac.kr
7	
8	Dong-In LEE <sup>1,2</sup>
9	
10	
11	Institutional addresses:
12	<sup>1</sup> Department of Environmental Atmospheric Sciences, Pukyong National University, Daeyeon
13	campus 45, Yongso-ro, Namgu, Busan 608-737 Republic of Korea
14	
15	<sup>2</sup> Atmospheric Environmental Research Institute, Daeyeon campus 45, Yongso-ro, Namgu
16	Busan 608-737 Republic of Korea
17	
18	* Corresponding author
19	

#### **Abstract**

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

Raindrop size distribution (DSD) characteristics within the complex area of Busan, Korea (35.12°N, 129.10°E) were studied using a Precipitation Occurrence Sensor System (POSS) disdrometer over a four-year period from February 24th 2001 to December 24th 2004. Also, to find the dominant characteristics of polarized radar parameters which is differential radar reflectivity  $(Z_{dr})$ , specific differential phase  $(K_{dp})$  and specific attenuation  $(A_h)$ , T-matrix scattering simulation was applied in present study. To analyze the climatological DSD characteristics in more detail, the entire period of recorded rainfall was divided into 10 categories not only covering different temporal and spatial scales, but also different rainfall types. When only convective rainfall was considered, mean values of mass weighted mean diameter (D<sub>m</sub>) and normalized number concentration (N<sub>w</sub>) values for all these categories converged around a maritime cluster, except for rainfall associated with Typhoons. The convective rainfall of a Typhoon showed much smaller  $\,D_m\,$  and larger  $\,N_w\,$  compared with the other rainfall categories. In terms of diurnal DSD variability, we observe analyzed maritime (continental) precipitation during the daytime (DT) (nighttime, NT), which likely results from sea (land) wind identified through wind direction analysis. These features also appeared in the seasonal diurnal distribution. The DT and NT Probability Density Function (PDF) during the Summer was similar to the PDF of the entire study period. However, the DT and NT PDF during the Winter season displayed an inverse distribution due to seasonal differences in wind direction.

40

41

**Keyword:** DSD, POSS disdrometer, Climatological characteristics, Land and sea wind.

#### 1. Introduction

42

**Drop** Raindrop Size Distribution (DSD) is controlled by the microphysical processes of rainfall 43 44 and therefore it plays an important role in the development of the quantitative Quantitative rainfall Precipitation estimation Estimation (QPE) algorithms based on forward scattering 45 simulations of radar measurements (Seliga and Bringi, 1976). DSD data accurately reflects 46 47 local rainfall characteristics within an observation area (You et al., 2014). Many DSD models have been developed to characterize spatial-temporal differences in DSDs under various 48 49 atmospheric conditions (Ulbrich, 1983). Marshall and Palmer (1948) developed an exponential DSD model using DSD data collected by a filter paper technique ( $N(D) = 8 \times$ 50  $10^3 \exp(-410 R^{-0.21} D)$  in m<sup>-3</sup>mm<sup>-1</sup>, D in mm and R in mm h<sup>-1</sup>). In subsequent studies, a 51 lognormal distribution was assumed to overcome the problem of exponential DSD 52 53 mismatching with real data (Mueller, 1966; Levin, 1971; Markowitz, 1976; Feingold and Levin, 1986). 54 To further investigate natural DSD variations, Ulbrich (1983) developed a gamma DSD that 55 permitted changing the dimension of the intercept parameter ( $N_0$  in  $m^{-3}$  mm<sup>-1- $\mu$ </sup>) with 56  $(N(D) = N_0 D^{\mu} \exp(-\Lambda D))$ . In addition, to enable the quantitative analysis of different rainfall 57 events, the development of a normalized gamma DSD model that accounted for the 58 59 independent distribution of DSD from the disdrometer channel interval enabled a better representation of the actual DSD (Willis, 1984; Dou et al., 1999; Testud et al., 2001). 60 DSDs depend on the rainfall type, geographical and atmospheric conditions and, and 61 62 observation time., and Also these are closely linked to microphysical characteristics that 63 control rainfall development mechanisms. In the case of stratiform rainfall, raindrops grow by the accretion mechanism because of the relatively long residence time in weak updraft 64

conditions, in which almost all water droplets are changed to ice particles. With time, the ice particles grow sufficiently and fall to the ground. The raindrop size of stratiform rainfall observed at the ground level is larger than that of convective rainfall for a same rainfall intensity<del>rate</del> due to the resistance of the ice particles to break-up mechanisms. In contrast to stratiform rainfall, in convective rainfall raindrops grow by the collision-coalescence mechanism associated with relatively strong vertical wind speeds and short residence time in the cloud. Fully-grown raindrops of maritime precipitation are smaller in diameter than those in stratiform rainfall due to the break-up mechanism in case of same rainfall rate (Mapes and Houze Jr, 1993; Tokay and Short, 1996). Convective rainfall can be classified into two types based on the origin and direction of movement. Rainfall systems occurring over ocean and land are referred to as maritime and continental rainfall, respectively (Göke et al., 2007). Continental rainfall is related to a cold-rain mechanism whereby raindrops grow in the form of ice particles. In contrast, maritime rainfall is related to a warm-rain mechanism whereby raindrops grow by the collision-coalescence mechanism. Therefore, the mass-weighted drop diameter (D<sub>m</sub>) of continental rainfall observed on the ground is larger than that of maritime rainfall, and a smaller normalized intercept parameter (N<sub>w</sub>) is observed in continental rainfall (Bringi et al., 2003). Specific heat is a major climatological feature that creates differences between DSDs in maritime and continental regions. These two regions have different thermal capacities and thus display different temperature variations are occurred with time. The surface temperature of the ocean changes slowly because of the water's higher thermal capacity compared with land, w. While the continental regions, which have comparatively lower thermal capacity, display show greater diurnal temperature variability. Sea winds generally is are occurred in from afternoon to early evening when the temperature gradient between the sea and land becomes negative, which is the opposite of the gradient in the daytime (DT). In coastal regions, the land and sea

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

wind effect causes a pronounced difference between the DT and nighttime (NT) DSD characteristics. Also, when mountains are located near the coast, the difference is intensified by the effect of mountain and valley winds (Qian, 2008).

In the present study, we analyzed a four-year dataset spanning from 2001 to 2004, collected from Busan, Korea (35.12°N, 129.10°E) using a Precipitation Occurrence Sensor System (POSS) disdrometer, to investigate the characteristics of DSDs in Busan, Korea which consist complex mid-latitude region comprising both land and ocean. To quantify the effect of land and sea wind on these characteristics, we also analyzed diurnal variations in DSDs. The remainder of the manuscript is organized as follows. In Section 2 we review the normalized gamma model and explain the DSD quality control method and the classification of rainfall. In Section 3 we report the results of DSD analysis with respect to stratiform/convective and continental/maritime rainfall, and discuss diurnal variations. Finally, a summary of the results and the main conclusions are presented in Section 4.

#### 2. Data and Methods

#### 2.1. Normalized Gamma DSD

The DSDs is are defined by  $N(D) = N_0 \exp(-\Lambda D)$  (m<sup>-3</sup>mm<sup>-1</sup>) and the one of the methods to are reflect the microphysical characteristics of rainfall using the number concentration of rainfall drops (N(D)). Also, DSDs is are able to calculate the many kind of parameters which show the dominant feature of raindrops. Normalization is used to define the DSD and to solve the non-independence of each DSD parameter (Willis, 1984; Dou et al., 1999; Testud et al., 2001). Furthermore, a normalized gamma DSD enables the quantitative

- 111 comparison for rainfall cases regardless of time scale and rain rate. Here, we use the DSD
- model designed by Testud et al. (2001):

114 
$$N(D) = N_w f(\mu) \left(\frac{D}{D_m}\right)^{\mu} exp\left[-(4+\mu)\frac{D}{D_m}\right].$$
 (1)

115

- where D is the volume equivalent spherical raindrop size diameter (mm), and  $f(\mu)$  is
- defined using the DSD model shape parameter ( $\mu$ ) and gamma function ( $\Gamma$ ) as follows:

118

119 
$$f(\mu) = \frac{6}{4^4} \frac{(\mu + 4)^{4 + \mu}}{\Gamma(4 + \mu)}$$
 (2)

120

From the value of N(D), the median volume diameter  $(D_0 \text{ in mm})$  can be obtained as follows:

122

123 
$$\int_0^{D_0} D^3 N(D) dD = \frac{1}{2} \int_0^{D_{\text{max}}} D^3 N(D) dD.$$
 (3)

124

- Mass-weighted mean diameter ( $D_m$  in mm) is calculated as the ratio of the fourth to the third
- moment of the DSD:

128 
$$D_{m} = \frac{\int_{0}^{D_{max}} D^{4} N(D) dD}{\int_{0}^{D_{max}} D^{3} N(D) dD}.$$
 (4)

130 The normalized intercept parameter ( $N_w$  in  $m^{-3}mm^{-1}$ ) is calculated as follows:

132 
$$N_{\rm w} = \frac{4^4}{\pi \rho_{\rm w}} \left(\frac{\rm LWC}{D_{\rm m}^4}\right)$$
. (5)

- The shape of the DSD is calculated as the ratio of  $D_{m-}$  to the standard deviation (SD) of  $D_{m-}$
- $(\sigma_{m} \text{ in mm})$  (Ulbrich and Atlas, 1998; Bringi et al., 2003; Leinonen et al., 2012):

137 
$$\sigma_{\rm m} = \left[\frac{\int_0^{\rm D_{max}} D^3 (D - D_{\rm m})^2 N(D) dD}{\int_0^{\rm D_{max}} D^3 N(D) dD}\right]^{\frac{1}{2}}.$$
 (6)

139 In addition,  $\sigma_m/D_m$  is related to  $\mu$  as follows:

141 
$$\frac{\sigma_{\rm m}}{D_{\rm m}} = \frac{1}{(4+\mu)^{1/2}}$$
 (7)

Liquid water content (LWC in g  $m^{-3}$ ) can be defined from the estimated DSD:

145 LWC = 
$$\frac{\pi}{6} \rho_w \int_0^{D_{\text{max}}} D^3 N(D) dD$$
. (8)

where  $\rho_w$  is the water density (g m<sup>-3</sup>) and it assumed as  $1 \times 10^6$  g m<sup>-3</sup> for a liquid water.

Similarly, the rainfall rate (R in mm  $h^{-1}$ ) can be defined as follows:

150 
$$R = \frac{3.6}{10^3} \frac{\pi}{6} \int_0^{D_{\text{max}}} v(D) D^3 N(D) dD.$$
 (9)

where the value of factor  $3.6 \times 10^3$  is the unit conversion which converts the mass flux unit  $(mg m^{-2} s^{-1})$  to the common unit  $(mm h^{-1})$  for the convenience. v(D)  $(m s^{-1})$  is the fall terminal velocity for each raindrop size. The relationship between v(D)—and equivalent spherical raindrop size (D in (mm)) is given by Atlas et al. (1973) who developed an empirical formula based on the data reported by Gunn and Kinzer (1949):

158 
$$v(D) = 9.65 - 10.3 \exp[-0.6D].$$
 (10)

### 2.2 Quality Control of POSS Data

POSS <u>was is</u> used to measure the number of raindrops within the diameter range of 0.34-5.34 mm, using bistatic, continuous wave X-band Doppler radar (10.525 GHz) across 34 channels (Fig. 1; Sheppard and Joe, 2008). To estimate DSDs, Doppler power density spectrum

164 is generated calculated as follows;

165

166

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

Where S(f) means Doppler spectrum power density,  $V(D_m, \rho, h, w)\overline{S}(f, D_m, \rho, h, w)$  means weighting function of S(f),  $\bar{S}$  is the mean of S(f),  $\rho$  is density of precipitation distribution, h is the shape of precipitation distribution, w (m s<sup>-1</sup>) is wind speed and V(x) is sample volume and the symbol 'x' means arbitrary parameters which affect the sampling volume. The Doppler power density spectrum has a resolution of 16Hz and terminal velocity (v<sub>t</sub>) has a resolution of 0.24 m s<sup>-1</sup>. Transmitter and receiver skewed about 20° toward each other, and cross point of signal is located over 34 cm from transmitter-receiver. Transmitter-receiver toward upper side detects N(D)-of raindrops in observation volume (V(Dx)) (Sheppard, 1990). Also, Sheppard (1990) and Sheppard and Joe (1994) noted some shortcomings as the overestimation of small drops at horizontal wind larger than 6 m s<sup>-1</sup>. However, in present study, the quality control of POSS for wind effect was not considered because it lies beyond this work. Detailed specifications and measurement ranges and raindrop sizes for each observation channel of the POSS disdrometer are summarized in Table 1. A POSS disdrometer was installed have been operating in Busan, Korea (35.12°N, 129.10°E), along with other atmospheric instruments, the locations of which are shown in Fig. 2. Estimating raindrop size diameter correctly is challenging and care should be taken to ensure

reliable data are collected. We performed the following quality controls to optimize the
accuracy of the disdrometer estimates. i) Non-liquid type event data (e.g., snow, hail etc.)
detected by POSS were excluded by routine observation and surface weather chart provided
by Korea Meteorological Administration (KMA)., to focus only on liquid state rainfallii)
DSD spectra in which drops were not found in at least five consecutive channels were removed
as non-atmospheric. iii) Only data recorded in more than 10 complete channels were considered.
iv) To compensate for the reduced capability to detect raindrops smaller than 1 mm when R
> 200 mm h <sup>-1</sup> (as recorded by the disdrometer), <u>data for R&gt;200 mm h<sup>-1</sup> were not included in</u>
the analyses, even though the number of samples was only 64 for the entire period.data
collected when $R > 200$ mm $h^{-1}$ were not included in the analysesv) To eliminate wind
and acoustic noise, data collected when $R < 0.1 \ \text{mm h}^{-1} \ \underline{\text{arewere}}$ removed (Tokay and Short,
1996).
-vi) The value of $-D_{\theta}$ -which is calculated by Eq. (3) tends to be overestimated when $-D_{\theta}$ < 0.5
mm (Leinonen et al., 2012). Because the correlation coefficient between D <sub>0</sub> and D <sub>m</sub> was
0.985 for the whole study period, we considered that -D <sub>m</sub> could be used for the analysis instead
of D <sub>u</sub> .
After performing all quality control procedures, 99,388 spectra were left from an original total
data (of 166,682) for 1-min temporal resolution. Accumulated rainfall amount from POSS
during the entire period was 4261.49 mm. To verify the reliability of the POSS data, they were
compared with data collected by a 0.5 mm tipping bucket rain gaugeat an automatic weather
existem (AWS) located 268 m from the DOSS (Fig. 2)

## 2.3 Radar Parameters

First, the radar reflectivity factor (z<u>in</u>,—mm<sup>6</sup>m<sup>-3</sup>) and non-polarized radar reflectivity (Z<u>in</u>

Z09 JdBZ) were computed using the DSD data collected by POSS, as follows:

211 
$$z = \int_0^{D_{\text{max}}} D^6 N(D) dD.$$
 \_\_\_\_\_(12)

213 
$$Z = 10\log_{10}(z)$$
. (13)

D (mm) < 4, as follows:

The T-matrix method used in this study is initially proposed by Waterman (1965, 1971) to calculate electromagnetic scattering by single non-spherical raindrops. The adaptable parameters for this calculation are frequency, temperature, hydrometeor types, raindrop's canting angle and drop-axis ratio\_(γ) and explained the following sentences. Axis ratios of raindrops differ with atmospheric conditions and rainfall type. To derive the drop shape relation from the drop diameter, we applied the results of numerical simulations and wind tunnel tests employing a forth-polynomial equation, as in many previous studies (Beard and Chuang, 1987; Pruppacher and Beard, 1970; Andsager et al., 1999; Brandes et al., 2002). The drop shapeaxis ratio relation used in the present study is a combination of those from Andsager et al. (1999) and Beard and Chuang (1987) for three raindrop size ranges (Bringi et al., 2003).

$$r = 1.0048 + 0.0057D - 2.628D^{2} + 3.682D^{3} - 1.677D^{4}.$$
 (14)

The raindrop axis ratio relation of Andsager et al. (1999) is applied in the range of 1 <

The drop-shape relation of Beard and Chuang (1987) is applied in the range of D < 1 mm and D > 4 mm, as follows:

233 
$$r = 1.012 + 0.01445D - 0.01028D^2$$
. (15)

We assumed SD and the mean canting angle of raindrops as  $7^{\circ}$  and  $0^{\circ}$ , respectively. The refractive indices of liquid water at  $20^{\circ}$ C were used (Ray, 1972). Also, the condition of frequency for electromagnetic wave of radar is 2.85 GHz (S-band). We calculated dual polarized radar parameters based on these conditions. The parameters of differential reflectivity; ( $Z_{dr}$  in  $Z_{dr}$  (dB), specific differential phase\_, ( $K_{dp}$  ( $K_{dp}$  in deg km<sup>-1</sup>), and attenuation\_; ( $A_{h}$  in (dB km<sup>-1</sup>), using DSD data were calculated and analyzed.

#### 2.4. Classification of Rainfall Types and Rainfall Events

Rainfall systems can be classified as stratiform or convective in nature, via analysis of the following microphysical characteristics: i) DSD, using relationships between  $N_0$  and R ( $N_0 > 4 \times 10^9 R^{-4.3}$  in  $m^{-3}mm^{-1}$  is considered as convective rainfall, Tokay and Short, 1996; Testud et al., 2001); ii) radar reflectivityZ, where, according to Gamache and Houze (1982), a rainfall system that displays radar reflectivity larger than 38 dBZ is considered to be convective; and iii) rainfall rateR, where average value larger than 0.5 mm per 5 min is considered as convective rainfall (Johnson and Hamilton, 1988). Alternatively, rainfall that has

1-min R > 5 (0.5) mm  $h^{-1}$  and a SD of R > (<) 1.5 mm  $h^{-1}$  is considered as convective 250 251 (stratiform) type (Bringi et al., 2003). The rainfall classification method proposed by Bringi et al. (2003) is applied in the present study. 252 It is necessary to categorize different rainfall systems because their microphysical 253 254 characteristics show great variation depending on the type of rainfall, as well as the type of rainfall event; e.g., Typhoon, Changma, heavy rainfall and seasonally discrete rainfall. To 255 investigate the temporal variation in DSDs, we analyzed daily and seasonal DSDs. Likewise, 256 to investigate diurnal variability in DSD, DT and NT data were considered by using the sunrise 257 and sunset time in Busan (provided by the Korea Astronomy and Space Science Institute 258 259 [KASI]). In the middle latitudes, and including Busan, the timings of sunrise and sunset vary due to solar culminating height. The earliest and latest sunrise (sunset) time of the entire period 260 261 is 0509 KST (1712 KST) and 0733 KST (1942 KST), respectively. DT (NT) is defined as the 262 period from the latest sunrise (sunset) time to the earliest sunset (sunrise) time for the unity of classification of each time group (Table 2). 263 To analyze the predominant characteristics of DSDs for Typhoon rainfall, nine Typhoon events 264

266

265

267

268

269

270

271

272

273

This study utilizes the Korea Meteorological Administration (KMA) rainfall warning regulations to identify heavy rainfall events. The KMA issues a warning if the accumulated rain amount is expected to be >70 mm within a 6-hour period, or >110 mm within a 12-hour period. Rainfall events classified as Changma and Typhoon were not included in the classification 'heavy rainfall'.

were selected from throughout the entire study period which is summarized in Table 2.

Changma is the localized rainfall system or rainy season that is usually present over the Korean Peninsula between mid-June and mid-July which is similar to the Meiyu (China) or Baiu

(Japan). The selected dates and periods of each rainfall category are summarized in Table 2.

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

274

## 3. Results

#### 3.1. DSD and Radar Parameters

Figure 4 shows the Probability Density Function (PDF) and Cumulative Distribution Function (CDF) of DSDs and radar parameters with respect to the entire, stratiform and convective rainfall. The PDFs of DSD and radar parameters were calculated using the nonparameterization kernel estimation to identify the dominant distribution of each parameter recorded in Busan. Non-parameterization kernel estimation was also used to identify continuous distributions of DSDs. The PDF of stratiform rainfall is more similar to that of the dataset for the entire analysis period due to the dominant contribution of stratiform rainfall (about 62.93%) to the overall rainfall than that of convective rainfall. However, the PDF for convective rainfall is significantly different from that of the entire analysis period, and as the convective rainfall contributes only 6.11% of the overall rainfall (Table 3). When  $\mu$  < 0 the distribution of  $\mu$  for convective rain has more value of PDF than that for stratiform rain (Fig. 4a). Alternatively, the frequency of  $\mu$  for stratiform rainfall is higher than that of convective rainfall when  $0 < \mu < 5$ . The value of  $\mu$  for convective rainfall is higher than that for stratiform rainfall because the break-up mechanism would be increase the number concentration of small raindrops. The number concentrations of mid-size raindrops increased due to the decrease in the number concentration of relatively large raindrops (Hu and Srivastava, 1995; Sauvageot and Lacaux, 1995). However, we observed a higher frequency of convective

rainfall than stratiform rainfall in the negative µ range.

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

The PDF of D<sub>m</sub> displays peak around 1.2 and 1.4 mm for stratiform rainfall and the entire rainfall dataset, respectively. We note that a gentle peak exists around 0.7 mm for both stratiform and convective rainfall datasets (Fig. 4b). These features are similar to the distribution of D<sub>m</sub> observed in a high-latitude region at Järvenpää, Finland (Fig. 4 of Leinonen et al., 2012). For  $D_m$  values > 1.7 mm, the PDF for convective rainfall is higher than stratiform rainfall. Accordingly, the value of DSD for stratiform rainfall is higher than that of convective rainfall when  $D_m < 1.7$  mm. Generally, stratiform rainfall that develops by the cold rain process displays weaker upward winds and less efficient break-up of raindrops. Therefore, in the same rainfall rate, stratiform rainfall tends to produce larger raindrops than convective rainfall that develops by the warm rain process. However, the average  $\,D_m\,$  values for convective and stratiform rain for the entire period are approximately 1.45 and 1.7 mm, respectively. In short,  $D_{m}$  is proportional to R regardless of rainfall type. This finding is consistent with the results of Atlas et al. (1999) who found that the  $D_m$  of convective rainfall is larger than that of stratiform rainfall on Kapingamarangi Island, Micronesia. The PDF of  $\log_{10}(N_w)$  for the entire rainfall dataset was evenly distributed between 1.5 and 5.5, with a peak at  $N_w = 3.3$  (Fig. 4c). The PDF of  $log_{10}(N_w)$  for stratiform rainfall is rarely > 5.5, while for convective rainfall it is higher at > 5.5 than that of stratiform. There is a similar frequency in the stratiform and convective rainfall at 4.4.\_-The PDF distributions for  $log_{10}(R)$  and  $log_{10}(LWC)$  are similar each other (Fig. 4d and e). It is inferred that the similar results come from the using of alike moment of DSD as 3.67 and 3 for R and LWC, respectively. The PDF of  $\log_{10}(R)$  for the entire rainfall dataset ranged

between -0.5 and 2. A peak exists at 0.3 and the PDF rapidly decreases from the peak value as

R increases. The PDF for stratiform rainfall has a higher frequency than that of the entire 318 rainfall when  $-0.3 < \log_{10}(R) < 0.7$ , while the PDF for convective rainfall is denser between 319 0.4 and 2. Furthermore, the frequency of the PDF for convective rainfall was higher than that 320 of stratiform rainfall in case of  $\log_{10}(R) > 0.65$  and the peak value shown was as 0.9. 321 The PDF and CDF for non-polarized reflectivity (Z), differential reflectivity (Z<sub>dr</sub>), specific 322 differential phase (K<sub>dp</sub>), and specific attenuation of horizontal reflectivity (A<sub>h</sub>) are shown in 323 Fig. 4f-i. The PDF of  $\frac{Z_BZ}{R}$  for stratiform rainfall (Fig. 4f) is widely distributed between 10 and 324 325 50 dBZ with the peak at approximately 27 dBZ. Conversely, for convective rainfall, the value 326 of PDF lie between 27 and 55 dBZ and the peak frequency value at approximately 41 dBZ. The frequency value of reflectivity is higher for convective rainfall than for stratiform rainfall 327 in the range of ~>35 dBZ. Furthermore, the shape of the PDF for convective rainfall is similar 328 to that reported for Darwin, Australia (Steiner et al., 1995); however, for stratiform rainfall 329 330 there are significant differences between Busan and Darwin in terms of the shape of the 331 frequency distribution. The PDF of Z<sub>dr</sub> for the entire rainfall primarily exists between 0 and 332 2.5 dB, and the peaks are at 0.3 and 1.8 dB (Fig. 4g). The distribution of Z<sub>dr</sub> for convective 333 and stratiform rainfall is concentrated between 0.6 and 1.6 dB, and between 0.3 and 2 dB, respectively. The frequency of  $\, Z_{dr} \,$  for convective (stratiform) rainfall exists in ranges higher 334 (lower) than stratiform (convective) at 0.9 dB. 335 The dominant distribution of  $K_{dp}$  for the entire dataset and for stratiform rainfall lies 336 between 0 and 0.14 deg km<sup>-1</sup>, with a peak value of 0.03 deg km<sup>-1</sup> and 0.08 deg km<sup>-1</sup>. 337 However, for convective rainfall the PDF of  $K_{dp}$  is evenly exist between 0.01 and 0.15 338  $deg \ km^{-1}$ . Furthermore, when  $\ K_{dp} > 0.056 \ deg \ km^{-1}$ , the frequency of the PDF for 339 convective rainfall is higher than that of stratiform rainfall (Fig. 4h). 340

The PDF of  $A_h$  is similar to that of  $K_{dp}$  and is exist between 0 and 0.01 dB km<sup>-1</sup>. For the case of the entire rainfall dataset and for stratiform rainfall, the PDF of  $A_h$  is concentrated between 0 and  $2.0 \times 10^{-3}$  dB km<sup>-1</sup> and that of convective rainfall is strongly concentrated between  $1.0 \times 10^{-3}$  and  $8.0 \times 10^{-3}$  dB km<sup>-1</sup> (Fig. 4i). Unlike the PDF of  $A_h$  for convective rainfall, the PDF for stratiform rainfall shows a strong peak at about  $7.0 \times 10^{-4}$  dB km<sup>-1</sup>.

### 3.2. Climatological Characteristics of DSD in Busan

The climatological characteristics of DSDs for 10 rainfall categories are analyzed in this study. Sample size and ratio rainfall for each category are summarized in Table 3. Figure 5a illustrates the distribution of all 1-min stratiform rainfall data, and Fig. 5b shows scatter plots of averaged  $D_m$  and  $\log_{10}(N_w)$  for all 10 rainfall categories for stratiform rainfall data. Figure 5a displays a remarkable clear boundary in the bottom sector and shows that most of the data lie below the reference line used by Bringi et al. (2003) to classify convective and stratiform rainfall. The average value of  $D_m$  and  $\log_{10}(N_w)$  for all rainfall categories, except for heavy rainfall, exist between 1.4 mm and 1.6 mm and between 3.15 and 3.5, respectively (Fig. 5b). These values are relatively small compared with the reference line presented by Bringi et al. (2003). The distribution of 1-min convective rainfall data is displayed in Fig. 6a and the distribution of average values of  $D_m$  and  $N_w$  for the 10 rainfall categories in the case of convective rainfall in Fig. 6b. The blue and red plus symbols represent maritime and continental rainfall, respectively, as defined by Bringi et al. (2003). The scatter plot of 1-min convective rainfall data shows more in the continental cluster than the maritime cluster; however, the average values for the 10 rainfall categories are all located around the maritime cluster, except for the

Typhoon category. By considering the entire average values including Typhoon event (Fig. 6b), we can induce the simple linear equation using  $D_{\rm m}$  and  $\log_{10}(N_{\rm w})$  as follows:

$$\log_{10}(N_{\rm w}) = -1.8D_{\rm m} + 6.9.$$
 (16)

Even the coefficients in Equation Eq. 16 might be changed slightly with the Typhoon values, this result does not represent in  $D_m < 1.2$  mm and  $D_m > 1.9$  mm. The  $D_m$  ( $N_w$ ) value for the Typhoon category was considerably smaller (larger) than that of the other categories as well as that of stratiform type of Typhoon. This result does not agree with that reported by Chang et al. (2009), who noted that the  $D_m$  of convective rainfall Typhoon showed a large value compared with that associated with stratiform rainfall.

#### 3.3 Diurnal Variation in Raindrop Size Distributions

#### 3.3.1. Diurnal Variations in DSDs

Figure 7a shows a histogram of normalized frequency of 16 wind directions recorded by the AWS, which is the same instrument as that used to collect the data shown in Fig. 3. To establish the existence of a land and sea wind, the difference in wind direction frequencies between DT and NT were analyzed. Figure 7b shows the difference between DT and NT, difference frequency means normalized frequency of wind direction for DT subtract to that of NT for each direction, in terms of the normalized frequency of 16 wind directions. In other word, positive (negative) values indicate that the frequency of wind is more often observed during DT (NT). Also, land (sea) wind defined in present study from 225° (45°) to 45° (225°) according to the

geographical condition in Busan. The predominant frequency of wind direction in the DT (NT), 386 between 205° (22.5°) and 22.5° (205.5°), is higher than that in the NT (DT) (Fig. 7b). The 387 observation site where the POSS was installed at western side from the closest coast line, 388 distance is about 611 m, suggesting that the effect of the land and sea wind would have been 389 390 recorded.-To understand the effects of the land and sea wind on DSD characteristics, we analyzed the 391 392 PDF and 2-hour averaged DSD parameters for DT and NT. Figure 8 illustrates the distributions of  $\mu$ ,  $D_m$ ,  $\log_{10}(N_w)$ ,  $\log_{10}(LWC)$ ,  $\log_{10}(R)$ , and Z. There were large variations of  $\mu$ 393 with time. The  $\mu$  values varied from 2.41 to 3.17 and the minimum and maximum  $\mu$  values 394 395 occurred at 0800 KST and 1200 KST, respectively (Fig. 8a). A D<sub>m</sub> larger than 1.3 mm dominated from 0000 KST to 1200 KST, before decreasing remarkably between 1200 and 1400 396 KST. The minimum and maximum D<sub>m</sub> appeared at 1400 KST and 0800 KST, respectively 397 398 (Fig. 8b). N<sub>w</sub> distribution showed generally varies inversely to D<sub>m</sub>; however, no inverse relationship 399 400 was identified between D<sub>m</sub> and N<sub>w</sub> in case of the time series (Fig. 8c). The maximum and minimum values of  $\,N_{\rm w}\,$  were found at 0600 KST and 2200 KST. 401 Variability through time was similar for R, LWC, and Z<sub>h</sub> as D<sub>m</sub>. There was an increasing 402 trend from 0000 KST to 0800 KST followed by a remarkably decreasing trend from 0800 KST 403 to 1400 KST (Figs 8d, 11e and 11f). Note that the time of the sharp decline for R between 404 405 1200 KST and 1400 KST is simultaneous with a D<sub>m</sub> decrease. Larger (smaller) drops would contribute to higher R in the morning (afternoon). These variations considerably matched 406 with the diurnal sea wind time series (Fig. 8g). Sea wind is the sum value of normalized wind 407 frequency between 45° and 225°. From 0200 (1400) KST to 1200 (2000) KST shows smaller 408

- 409 (larger) value of sea wind frequency which is opposite to the relatively larger (smaller) parts of
- 410 each parameter  $(D_m, R, LWC \text{ and } Z_h)$ .
- 411 The PDF distribution of  $\mu$  between -2 and 0 is more concentrated for NT than for DT.
- Furthermore, when  $\mu > 0$ , DT and NT frequency distributions are similar (Fig. 9a). A larger
- 413 N(D) of small or large raindrops would be expected in NT than in DT.
- The distribution of DT  $D_m < 0.7$  mm is wider than that of the NT. However, between 0.7
- and 1.5 mm the frequency for NT is higher than that for DT, whereas the distribution in the
- range\_ $D_m$ \_-> 1.5 mm is similar for both DT and NT (Fig. 9b). We note that the smaller peak
- of  $D_m$  around 0.6 mm for the entire rainfall dataset (Fig. 4b) was observed only in DT.
- The distribution of  $log_{10}(N_w)$  for DT has higher value of PDF at larger  $log_{10}(N_w)$  than that
- 419 of NT at  $log_{10}(N_w) > 4$  (Fig. 9c).
- Bringi et al. (2003) noted that the maritime climatology displayed larger  $N_w$  and smaller  $D_m$
- values than the continental climatology, based on observed DSDs in the low and middle latitude.
- Also, Göke et al. (2007) emphasized that rainfall type can be defined by the origin location and
- movement direction. In accordance with these previous results, we consider NT rainfall in the
- Busan region to be more likely caused by a continental convective system.
- In the present study, the shape of the PDF of LWC and R for DT and NT are similar which is
- 426 the same reason with the results of Fig. 4e-f. LWC and R distributions during the DT (NT)
- are higher (lower) than in the NT (DT) when  $log_{10}(LWC)$  and  $log_{10}(R)$  are larger (smaller)
- 428 than -1.2 and 0, respectively (Fig. 9d and e). The Z has similar pattern with LWC and R
- during the DT (NT) was higher (lower) than in the NT (DT) in the range below (above) about
- 430 27 *dBZ* (Fig. 9f).

#### 3.3.2. Diurnal Variations of DSDs with respect to Season

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

Busan experiences distinct atmospheric conditions that are caused by the different frequencies and magnitudes of land and sea winds in response to variable sunrise and sunset times. To identify seasonal variations of DSDs with respect to the effect of the land and sea wind, we analyzed the DT and NT PDF of  $\,D_m\,$  and  $\,N_w\,$  in the Summer and Winter. The start and end times of DT (NT) were sorted using the latest sunrise (sunset) and the earliest sunset (sunrise) time for each season (Table 4) which is same method that of entire period classification. Figure 10a shows a histogram of wind directions in Summer (light grey) and Winter (dark grey). The frequencies of Summer and Winter wind directions are similar to each other. However, in Fig. 10b, the DT and NT distributions of Winter wind direction display opposing frequencies. Note that Winter season shows remarkable frequency of land (sea) wind between 0° (157.5°) and 45° (202.5°) at DT (NT) compared with results of those for Summer season. The accumulated value of normalized wind frequencies at the sea and land wind show different feature between Summer and Winter season (Table 5). To identify the variability of DSDs caused by the land and sea wind in Summer and Winter, a 2-hour interval time series of  $D_m$ ,  $N_w$  and R was analyzed. In the Summer, the time series of  $D_m$  displays considerably large values between 0000 KST and 1200 KST, compared with the period between 1400 KST and 2200 KST (Fig. 11a). The mean value of  $D_m$  decreases dramatically between 1200 KST and 1400 KST.  $log_{10}(N_w)$  generally—has a negative relationship with  $D_m$  (Fig. 11b). However, the inverse relation between  $log_{10}(N_w)$  and  $D_m$ is not remarkable. The  $log_{10}(R)$  tends to increase gradually from 0000 KST to 0800 KST and decrease from 0800 KST to 1400 KST, which is similar to the pattern that of entire period (Fig. 11c). Kozu et al. (2006) analyzed the diurnal variation in R at Gadanki (South India),

Singapore, and Kototabang (West Sumatra) during the Summer monsoon season. All regions displayed maximum R at approximately 1600 LST, except for Gadanki. Also, Qian (2008), who analyzed the diurnal variability of wind direction and R on Java Island during the Summer season using 30 years (from 1971 to 2000) of NCEP/NCAR reanalyzed data. They found that a land wind occurred from 0100 LST to 1000 LST and a sea wind from 1300 LST to 2200 LST (Fig. 7 of Qian (2008)). Normalized wind frequency for each direction is similar pattern to the results of Qian (2008) but pattern of R is different with that of Kozu et al. (2006). The diurnal variation of rain rate in the present study from 0200 (1200) KST to 1000 (2000) KST shows relatively smaller (larger) frequencies of sea wind. It is different pattern with the result of Kozu et al. (2006). However, these patterns matched with the time series of  $D_m$  and  $log_{10}(N_w)$ . Larger frequency of sea wind direction shows counter-proportional (proportional) relationship to the smaller (larger) frequency of  $D_m$  ( $log_{10}(N_w)$ ). Variability of the  $D_m$  time series for Winter is the inverse of the Summer time series (Fig. 11a). The mean value of  $D_m$  steadily increases from 0000 KST to 1600 KST and then decreases from 1600 KST to 2200 KST. The Winter  $log_{10}(N_w)$  time series displays a clear inverse pattern compared with the  $D_m$  variation with time and increases from 1600 KST to 0400 KST and then steadily decreases from 0400 KST to 1600 KST (Fig. 11b). The peak of  $log_{10}(N_w)$ occurs at 0400 KST. However, the time series of  $log_{10}(R)$  for Winter season shows similar pattern with that of Summer unlike to another parameters (Fig. 11c). Based on the diurnal variation of R, the variations of  $D_m$  and  $N_w$  would be independent to R. Alike to the  $D_m$  and  $log_{10}(N_w)$ , normalized wind frequency of wind direction for Winter season shows inverse relationship to that of Summer season (Fig. 11d). The value of frequency generally decreases (increases) from 0400 (1400) KST to 1400 (0400) KST. Also, it shows

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

- symmetry pattern with that of Summer season.
- The PDF distribution of Summer  $D_m$  displays a relatively large DT frequency compared with
- NT when  $D_m < 1.65$  mm, except for the range between 0.6 and 0.9 mm. However, in the
- range of  $D_m > 1.65\,$  mm, the NT PDF displays a larger frequency (Fig. 12a). The PDF of
- 482  $log_{10}(N_w)$  for DT (NT) has a larger frequency than the NT (DT) when  $log_{10}(N_w) > (<) 3.3$
- but smaller frequency when  $log_{10}(N_w) < (>) 3.3$  (Fig. 12c).
- 484 The DT and NT PDFs of  $D_m$  and  $log_{10}(N_w)$  during Winter display an inverse distribution
- to that of Summer. For the PDF of  $D_m$ , there is a considerable frequency for NT (DT) when
- 486  $D_m < (>)$  1.6 mm (Fig. 12b). The PDF of  $log_{10}(N_w)$  of Summer season for NT (DT) is
- larger than that of the DT when  $log_{10}(N_w) < (>) 3.5$  (Fig. 12d). In the PDF analysis, relatively
- large (small)  $D_m$  and small (large)  $log_{10}(N_w)$  are displayed during the NT (DT) when a land
- wind (sea wind) occurs.
- Bringi et al. (2003) referred that the convective rainfall type is able to be classified as the
- continental and maritime-like precipitation using D<sub>m</sub> and N<sub>w</sub>. As the previous study result, we
- analyzed the PDF of DSDs for Summer and Winter with respect to convective rainfall type.
- These feature would be shown more clearly in convective type. The convective rainfall type of
- 494 PDFs of DT and NT for Summer show similar shape of distribution to that of all rainfall type
- 495 (Fig. 3a). For the PDF of  $D_m$ , there is a more frequency for DT (NT) than NT (DT) when  $D_m$
- 496 < (>) 2.0 mm except for between 0.7 mm and 1.2 mm (Fig. 13a). The PDF of convective
- rainfall type's  $log_{10}(N_w)$  for DT (NT) has a larger frequency than the NT (DT) when
- $log_{10}(N_w) > (<) 3.4$  except for between 4.3 and 5.5 (Fig. 12c). PDF distributions for Winter
- season show more clear pattern compared with those of the entire rainfall type. The value of
- PDF for  $D_m$  in DT (NT) have considerably larger than NT (DT) when  $D_m > (<)$  1.9 mm,

especially between 2.15 mm and 2.3 mm (Fig. 13b). Also, those for  $\log_{10}(N_w)$  in DT (NT) show dramatic values when  $\log_{10}(N_w) < (>)$  3.6. Furthermore, PDF values significantly concentrated on between  $3 < \log_{10}(N_w) < 3.2$  (Fig. 13d). In short, considering the DSD parameters with wind directions, the maritime (continental)-like precipitation would depend on the sea (land) wind.

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

501

502

503

504

505

## 4. Summary and Conclusion

Climatological characteristics of DSDs in Busan were analyzed using the DSD data observed by POSS over a four-year period from February 24<sup>th</sup> 2001 to December 24<sup>th</sup> 2004. Observed DSDs were filtered to remove errors by performing several quality control measures, and an AWS rain gauge installed nearby was used to verify the rainfall amount recorded by the POSS. We analyzed DSD characteristics of convective and stratiform rainfall types, as defined by Bringi et al. (2003). The rainfall dataset was thus divided into stratiform and convective rainfall and their contributions to the total rainfall were 62.93% and 6.11%, respectively. Also, to find the climatological characteristics of DSD for rainfall case, the entire rainfall data was classified as 10 rainfall categories including the entire period case. According to the study by Bringi et al. (2003), the rainfall in Busan shows maritime climatological DSD characteristics. The mean values of D<sub>m</sub> and N<sub>w</sub> for stratiform rainfall are relatively small compared with the average line of stratiform rainfall produced by Bringi et al. (2003), except for heavy rainfall events. In case of convective type, mean values of D<sub>m</sub> and N<sub>w</sub> are converged around the maritime cluster, except for the Typhoon category. The convective rainfall associated with a Typhoon has considerably smaller D<sub>m</sub> and larger N<sub>w</sub> values compared with the other rainfall categories. This is likely caused by increased raindrop breakup mechanism as a result of strong wind effects. Furthermore, the distributions of mean D<sub>m</sub> and N<sub>w</sub> values for all rainfall categories associated with convective rainfall displays a linear relationship including the Typhoon category. The analysis of diurnal variation in DSD yielded the following results: first, the frequency of μ is higher at NT than during the DT in the negative value. The PDF of R is higher at NT than during the DT when  $log_{10}(R) > 0.6$ . The value of PDF for  $D_m$  during DT is larger than NT smaller than 0.65 mm. For N<sub>w</sub>, which tends to be inversely related to D<sub>m</sub>, its frequency is higher at NT than DT when  $log_{10}(N_w) > 3.8$ . This feature is matched with the time series of normalized frequency of sea wind which shows inverse relationship to D<sub>m</sub>. Smaller D<sub>m</sub> corresponds to the larger sea wind frequency. In short, maritime (continental) –like precipitation are observed in the DT (NT) more often than in the NT (DT) according to the features of wind. The abovementioned DSD characteristics are likely due to the land and sea wind caused by differences in specific heat between the land and ocean. These features are also apparent in the seasonal diurnal distribution. The PDF of DT and NT for convective rainfall type during the Summer is similar to the PDF of the entire period; however, those of the Winter displays the significant inverse distribution compared to the Summer because of obvious seasonal differences in wind direction.

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546	
547	
548	
549	
550	
551	
552	
553	
554	
555	
556	
557	Author contributions
558	Cheol-Hwan You designed the study. Sung-Ho Suh modified the original study theme and
559	performed the study. Cheol-Hwan You and Sung-Ho Suh performed research, obtained the
560	results and prepared the manuscript along with contributions from all of the co-authors. Dong-
561	In Lee examined the results and checked the manuscript.
562	
563	Acknowledgement
564	This work was funded by the Korea Meteorological Industry Promotion Agency under Grant
565	KMIPA 2015-1050. The authors acknowledge providing, weather chart, and AWS data for this

566	work from the Korea Meteorological Administration. The authors also acknowledge providing
567	codes for scattering simulation from Professor V. N. Bringi at Colorado State University.
568	
569	
570	
571	
572	
573	
574	
575	
576	
577	
578	
579	References
515	References
580	Andsager, K., Beard, K. V., and Laird, N. F.: Laboratory measurements of axis ratios for large
581	raindrops, Journal of the Atmospheric Sciences, 56, 2673-2683, 1999.
582	Atlas, D., Srivastava, R., and Sekhon, R. S.: Doppler radar characteristics of precipitation at
583	vertical incidence, Reviews of Geophysics, 11, 1-35, 1973.
584	Atlas, D., Ulbrich, C. W., Marks, F. D., Amitai, E., and Williams, C. R.: Systematic variation
585	of drop size and radar-rainfall relations, Journal of Geophysical Research: Atmospheres (1984–

- 586 2012), 104, 6155-6169, 1999.
- Beard, K. V., and Chuang, C.: A new model for the equilibrium shape of raindrops, Journal of
- the Atmospheric sciences, 44, 1509-1524, 1987.
- Brandes, E. A., Zhang, G., and Vivekanandan, J.: Experiments in rainfall estimation with a
- polarimetric radar in a subtropical environment, Journal of Applied Meteorology, 41, 674-685,
- 591 2002.
- Bringi, V., Chandrasekar, V., Hubbert, J., Gorgucci, E., Randeu, W., and Schoenhuber, M.:
- Raindrop size distribution in different climatic regimes from disdrometer and dual-polarized
- radar analysis, Journal of the atmospheric sciences, 60, 354-365, 2003.
- 595 Chang, W.-Y., Wang, T.-C. C., and Lin, P.-L.: Characteristics of the raindrop size distribution
- and drop shape relation in Typhoon systems in the western Pacific from the 2D video
- 597 disdrometer and NCU C-band polarimetric radar, Journal of Atmospheric and Oceanic
- 598 Technology, 26, 1973-1993, 2009.
- Dou, X., Testud, J., Amayenc, P., and Black, R.: The parameterization of rain for a weather
- radar, Comptes Rendus de l'Académie des Sciences-Series IIA-Earth and Planetary Science,
- 601 328, 577-582, 1999.
- Feingold, G., and Levin, Z.: The lognormal fit to raindrop spectra from frontal convective
- clouds in Israel, Journal of Climate and Applied Meteorology, 25, 1346-1363, 1986.
- 604 Göke, S., Ochs III, H. T., and Rauber, R. M.: Radar analysis of precipitation initiation in
- 605 maritime versus continental clouds near the Florida coast: Inferences concerning the role of
- 606 CCN and giant nuclei, Journal of the Atmospheric Sciences, 64, 3695-3707, 2007.
- 607 Gamache, J. F., and Houze Jr, R. A.: Mesoscale air motions associated with a tropical squall
- line, Monthly Weather Review, 110, 118-135, 1982.
- 609 Gunn, R., and Kinzer, G. D.: The terminal velocity of fall for water droplets in stagnant air,

- 610 Journal of Meteorology, 6, 243-248, 1949.
- Hu, Z., and Srivastava, R.: Evolution of raindrop size distribution by coalescence, breakup, and
- evaporation: Theory and observations, Journal of the atmospheric sciences, 52, 1761-1783,
- 613 1995.
- Johnson, R. H., and Hamilton, P. J.: The relationship of surface pressure features to the
- precipitation and airflow structure of an intense midlatitude squall line, Monthly Weather
- 616 Review, 116, 1444-1473, 1988.
- Kozu, T., Reddy, K. K., Mori, S., Thurai, M., Ong, J. T., Rao, D. N., and Shimomai, T.: Seasonal
- and diurnal variations of raindrop size distribution in Asian monsoon region, JOURNAL-
- 619 METEOROLOGICAL SOCIETY OF JAPAN SERIES 2, 84, 195, 2006.
- Leinonen, J., Moisseev, D., Leskinen, M., and Petersen, W. A.: A climatology of disdrometer
- 621 measurements of rainfall in Finland over five years with implications for global radar
- observations, Journal of Applied Meteorology and Climatology, 51, 392-404, 2012.
- 623 Levin, Z.: Charge separation by splashing of naturally falling raindrops, Journal of the
- 624 Atmospheric Sciences, 28, 543-548, 1971.
- Mapes, B. E., and Houze Jr, R. A.: Cloud clusters and superclusters over the oceanic warm
- 626 pool, Monthly Weather Review, 121, 1398-1416, 1993.
- Markowitz, A. H.: Raindrop size distribution expressions, Journal of Applied Meteorology, 15,
- 628 1029-1031, 1976.
- Marshall, J. S., and Palmer, W. M. K.: The distribution of raindrops with size, Journal of
- 630 meteorology, 5, 165-166, 1948.
- 631 Mueller, E. A.: Radar cross sections from drop size spectra, University of Illinois at Urbana-
- 632 Champaign, 1966.
- Pruppacher, H., and Beard, K.: A wind tunnel investigation of the internal circulation and shape

- of water drops falling at terminal velocity in air, Quarterly Journal of the Royal Meteorological
- 635 Society, 96, 247-256, 1970.
- Qian, J.-H.: Why precipitation is mostly concentrated over islands in the Maritime Continent,
- Journal of the Atmospheric Sciences, 65, 1428-1441, 2008.
- Ray, P. S.: Broadband complex refractive indices of ice and water, Applied Optics, 11, 1836-
- 639 1844, 1972.
- Sauvageot, H., and Lacaux, J.-P.: The shape of averaged drop size distributions, Journal of the
- 641 Atmospheric Sciences, 52, 1070-1083, 1995.
- 642 Seliga, T., and Bringi, V.: Potential use of radar differential reflectivity measurements at
- orthogonal polarizations for measuring precipitation, Journal of Applied Meteorology, 15, 69-
- 644 76, 1976.
- Sheppard, B. E.: Measurement of raindrop size distributions using a small Doppler radar. J.
- 646 Atmos. Oceanic Technol., 7, 255–268, 1990.
- Sheppard, B. E. and P. I. Joe: Comparison of raindrop size distribution measurements by a
- Joss–Waldvogel disdrometer, a PMS 2DG spectrometer and a POSS Doppler radar. J. Atmos.
- 649 Oceanic Technol., 11, 874–887, 1994.
- Sheppard, B., and Joe, P.: Performance of the precipitation occurrence sensor system as a
- precipitation gauge, Journal of atmospheric and Oceanic technology, 25, 196-212, 2008.
- 652 Steiner, M., Houze Jr, R. A., and Yuter, S. E.: Climatological characterization of three-
- dimensional storm structure from operational radar and rain gauge data, Journal of Applied
- 654 Meteorology, 34, 1978-2007, 1995.
- 655 Testud, J., Oury, S., Black, R. A., Amayenc, P., and Dou, X.: The concept of "normalized"
- distribution to describe raindrop spectra: A tool for cloud physics and cloud remote sensing,
- 657 Journal of Applied Meteorology, 40, 1118-1140, 2001.

658	Tokay, A., and Short, D. A.: Evidence from tropical raindrop spectra of the origin of rain from
659	stratiform versus convective clouds, Journal of applied meteorology, 35, 355-371, 1996.
660	Ulbrich, C. W.: Natural variations in the analytical form of the raindrop size distribution,
661	Journal of Climate and Applied Meteorology, 22, 1764-1775, 1983.
662	Ulbrich, C. W., and Atlas, D.: Rainfall microphysics and radar properties: Analysis methods
663	for drop size spectra, Journal of Applied Meteorology, 37, 912-923, 1998.
664	Waterman, P.C.: Matrix formulation of electromagnetic scattering. Proc. IEEE, 53, 805-812,
665	1965.
666	Waterman, P.C.: Symmetry, unitarity, and geometry in electromagnetic scattering, Physical
667	review D, 3, 825, 1971.
668	Willis, P. T.: Functional fits to some observed drop size distributions and parameterization of
669	rain, Journal of the Atmospheric Sciences, 41, 1648-1661, 1984.
670	You, CH., Lee, DI., and Kang, MY.: Rainfall estimation using specific differential phase
671	for the first operational polarimetric radar in Korea, Advances in Meteorology, 2014, 2014.
672	

**Tables** 

**Tables 1.** Specification of POSS disdrometer.

Specifications	Detail
Manufacturer	ANDREW CANADA INC
Module	PROCESSOR
Model number	POSS-F01
Nominal power	100 mW
Bandwidth	Single frequency

# Emission Pointing direction Antenna Range of sample area Wavelength Physical dimension Net weights

43 mW
20 ° (to the vertical side)
Rectangular pyramidal horns
<2 m
10.525 GHz ± 15 GHz
277×200×200 cm<sup>3</sup>
Approximately 110 kg

**Table 2.** Designated date with respect to the source of rainfall.

Rainfall Category	l Period			
	2001	2002	2003	2004
Typhoon	-	7.5-7.6, 8.31	5.29, 6.19, 8.7, 9.11-12	6.20, 8.19, 9.6
Changma	6.18-6.19, 6.23-6.26, 6.29-6.30, 7.1, 7.5-7.6 7.11-7.14	6.23-6.25, 6.30, 7.1-7.2	6.12-6.14, 6.23, 6.27 6.30, 7.1, 7.3- 7.15	7.11-7.13, 7.14

Heavy rainfall	02.04.15. 20:13 to 02.04.16 06:29			
	Spring	Summer	Autumn	Winter
Seasonal	Mar. to May	Jun. to Aug.	Sep. to Nov.	Dec. to Feb.
Dimmol	DT (KST)		NT (KST)	
Diurnal	0733 - 1712		1942 - 0509	

695 —

**Table 3.** Rainfall rate for each rainfall category and the number of sample size for 1-min data.

Rainfall Category	Total precipitation	Stratiform precipitation (%)	Convective precipitation (%)
Typhoon	5095	3118 (61.19)	652 (12.79)
Changma	18526	11099 (59.91)	1611 (8.69)
Heavy rainfall	359	153 (42.61)	150 (41.78)
Spring	30703	20370 (66.34)	1478 (4.81)
Summer	37187	22566 (60.68)	3409 (9.16)
Autumn	19809	12033 (60.74)	850 (4.29)
Winter	11689	7582 (64.86)	339 (2.90)
Daytime	41328	26373 (63.81)	2539 (6.14)
Nighttime	37455	23063 (84.00)	2242 (5.89)
Entire	99388	62551 (62.93)	6076 (6.11)

Table 4. DT and NT (KST) in Summer and Winter season.

Rainfall Category	Period	Beginning time (KST)	Finishing time (KST)	
Summer	DT	0533	1927	
	NT	1942	0509	
Winter	DT	0733	1712	
	NT	1819	0654	

**Table 5.** Sum of the normalized wind direction frequencies between Summer and Winter.

Sum of the normalized wind direction frequencies							
Season	Summer		Winter				
Туре	Sea wind	Land wind	Sea wind	Land wind			
Frequency	0.4139	0.5861	0.3137	0.6863			
Differenc	e of the normalized	wind direction frequen	cy between DT and	NT (DT-NT)			
Season	Summer		Winter				
Туре	Sea wind	Land wind	Sea wind	Land wind			
Frequency	0.0731	-0.0731	-0.0697	0.0697			

## **Figures**



**Figure 1.** 

Photograph of the POSS instrument used in this research.




Figure 2.

Locations of the POSS and the AWS rain gauge installed in Busan, Korea.




Figure 3.

Comparison of the recorded rainfall amounts between the POSS and AWS instrument.




Figure 4.

PDF and CDF eurves for (a)  $\mu$ , (b)  $D_m$ , (c)  $\log_{10}(N_w)$ , (d)  $\log_{10}(R)$ , (e)  $\log_{10}(LWC)$ , (f) Z, (g)  $Z_{dr}$ , (h)  $K_{dp}$ , and (i)  $A_h$  for the entire rainfall dataset (solid black line), stratiform rainfall (solid green line), and convective rainfall (solid blue line). The solid red line represents the CDF for entire rainfall dataset. The solid vertical line represents the mean value of each type.




Figure 5.

(a) Scatter plot of 1-min  $D_m$  and  $N_w$  for the 10 rainfall categories with respect to stratiform rainfall data. The broken grey line represents the average line as defined by Bringi et al. (2003). (b) Scatter plot of mean  $D_m$  and  $log_{10}(N_w)$  values of the 10 rainfall categories with respect to stratiform rainfall and these mean values for each rainfall type are shown as circle symbols. The vertical line represents  $\pm 1\sigma$  of  $log_{10}(N_w)$  for each category.





Figure 6.

(a) As in Figure 5(a), but for convective rainfall. The blue and red plus symbols represent maritime and continental rainfall, respectively, as defined by Bringi et al. (2003). (b) As in Figure 5(b), but for convective rainfall. The broken red line represents the mathematical expression described in Eq. (16).



(a) Histogram of normalized frequency of 16 wind directions for the entire study period. (b) Difference values of wind direction frequencies between DT and NT (DT - NT).

Figure 7.




Figure 8.

Two hour interval time series of (a)  $\mu$ , (b)  $D_m$ , (c)  $\log_{10}(N_w)$ , (d)  $\log_{10}(R)$ , (e)  $\log_{10}(LWC)$ , (f)  $Z_h$  and (g) normalized frequency of wind direction for sea wind (45° to 225°) with quartiles for the total period. Solid lines are quartiles for each time.




Figure 9.

PDF and CDF curves for (a)  $\mu$ , (b)  $D_m$ , (c)  $log_{10}(N_w)$ , (d)  $log_{10}(R)$ , (e)  $log_{10}(LWC)$ , and (f) Z for DT and NT according to the entire period. The solid red and blue lines represent the PDF for DT and NT, respectively. The broken light red and blue lines represent the CDF for DT and NT, respectively.




Figure 10.

Histogram of normalized frequency for 16 wind directions in (a) the entire period and (b) differences of normalized frequency with respect toof wind directions between DT and NT (DT – NT) for Summer (light grey) and Winter (dark grey) season.




Figure 11.

Two hour interval time series and quartiles of (a)  $D_m$ , (b)  $log_{10}(N_w)$  (c)  $log_{10}(R)$  and (d) normalized frequency of wind direction for sea wind (45° to 225°) for the Summer (red) and Winter (blue) season. Solid (broken) lines are quartiles of Summer (Winter) for each time, respectively.




Figure 12.

PDF and CDF of (a)  $D_m$  ((b)  $D_m$ ) and (c)  $N_w$  ((d)  $N_w$ ) for the entire rainfall type in the Summer (Winter) season. Red and blue solid lines represent the PDF of DT and NT, respectively. The light red and blue broken lines represent the CDF for each season




Figure 13.

As in Figure 12, but for convective rainfall type.