1 Technical Note: Application of artificial neural networks in

2 groundwater table forecasting – a case study in Singapore 3 swamp forest

4

5 Yabin Sun^{a,*}, Dadiyorto Wendi^a, Dong Eon Kim^a, Shie-Yui Liong^{a,b}

- ^a: Tropical Marine Science Institute, National University of Singapore, 18 Kent Ridge Road,
 Singapore 119227, Singapore
- 8 ^b: Willis Research Network, Willis Re Inc., 51 Lime Street, London, United Kingdom
- 9 *: Corresponding author
- 10 E-mail: tmssy@nus.edu.sg; Phone: +65-96379168; Fax: +65-67761455
- 11

12 Abstract

Accurate prediction of groundwater table is important for the efficient management of 13 groundwater resources. Despite being the most widely used tools for depicting the 14 hydrological regime, numerical models suffer from formidable constraints, such as extensive 15 data demanding, high computational cost and inevitable parameter uncertainty. Artificial 16 neural networks (ANNs), in contrast, can make predictions on the basis of more easily 17 accessible variables, rather than requiring explicit characterization of the physical systems 18 19 and prior knowledge of the physical parameters. This study applies ANN to predict the 20 groundwater table in a freshwater swamp forest of Singapore. The inputs to the network are 21 solely the surrounding reservoir levels and rainfall. The results reveal that ANN is able to 22 produce accurate forecast with a leading time up to 7 days, whereas the performance slightly 23 decreases when leading time increases.

Keywords: Artificial neural networks; Groundwater table forecasting; Freshwater swamp
 forest

26 **1. Introduction**

27 Physical-based numerical models are commonly used in groundwater table simulation. Different numerical models have been developed for different regions with different 28 29 objectives, such as to describe regional groundwater flow patterns, and to understand local 30 hydrological processes. (e.g. Matej et al., 2007; Pool et al., 2011; Yao et al. 2014). Numerical 31 models solve the deterministic equations to simulate the groundwater systems based on the 32 knowledge of the system characteristics, initial conditions, system forcings, etc. To develop a 33 groundwater numerical model, essential data include: topography, geological coverage, soil 34 properties, land use map, vegetation distribution, evapotranspiration information, hydrologic and climatic data, etc. Extensive data demanding makes numerical models highly data 35 dependent and data sensitive. Fitting a physical model is not possible when data are not 36 37 sufficient, and the accuracy of the numerical model to a great extent depends on how accurate the model inputs are. Numerical models are also less competent in forecast as most of the system forcings (e.g. evapotranspiration, rainfall) are less predictable. As a result of aforementioned constraints, numerical models tend to produce imperfect results in spite of the perfect knowledge of the governing laws (Sun et al., 2010).

42 To combat the deficiencies of the numerical models, artificial neural networks (ANNs) have 43 emerged as an alternative modelling and forecasting approach with a variety of applications in 44 hydrology research (e.g. French et al., 1992; Maier and Dandy, 2000). Unlike the traditional 45 physical-based models, the ANN-based approach does not require explicit characterization of the physical properties, or accurate representation of the physical parameters, but rather 46 47 simply determines the system patterns based on the relationships between inputs and outputs 48 mapped in the training process. ANNs typically use input variables that are more accessible to 49 make predictions, and therefore circumvent the data reliance inherent to the numerical models. 50 As compared to classical regression techniques, e.g. linear regression model, ANNs are 51 capable of taking into account of the nonlinear dynamics of the hydrological processes and 52 hence result in superior modelling and forecasting performance.

53 ANNs in recent years have also been successfully applied in groundwater table modelling. Yang et al. (1997) utilized ANN to predict groundwater table variations in subsurface-drained 54 farmland. Coulibaly et al. (2001) calibrated three different ANN models using groundwater 55 56 recordings and other hydro-meteorological data to simulate groundwater table fluctuations. 57 Lallahem et al. (2005) showed the feasibility of using ANN to estimate groundwater level in an unconfined chalky aquifer. Daliakopoulous et al. (2005) examined the performance of 58 59 different ANN architectures and training algorithms in groundwater table forecasting. 60 Taormina et al. (2012) developed a two-step ANN model to simulate the groundwater fluctuations in a coastal aquifer using past observed groundwater levels and external inputs, 61 i.e., evapotranspiration and rainfall. Most of above studies, however, focus on applying ANN 62 63 in large-scale semiarid or arid watersheds, where groundwater table is less variable and longterm groundwater table variation (e.g. monthly, annually) is of more concerns. In addition, 64 65 these studies use historical groundwater tables as inputs to the network, requiring 66 continuously long groundwater table recordings which can be a luxury for many regions.

This study, for the first time, applies ANN to forecast the groundwater table in a tropical 67 68 wetland - the Nee Soon Swamp Forest (NSSF) in Singapore. Being nourished with water 69 supply from reservoirs and precipitation, the groundwater table in the NSSF is close to the 70 ground level and extremely sensitive to the changes in hydro-meteorological conditions. This 71 study selects surrounding reservoir levels and rainfall as inputs to the network, avoiding the 72 requirement on continuously long groundwater table recordings. The forecast is made with 3 73 leading times, i.e., 1 day, 3 days and 7 days, which provides sufficient reaction time for 74 human intervention to maintain favorable hydrological conditions for conserving local 75 ecosystem. The methodology, application, results and conclusions are elaborated in the 76 following sections.

77 2. Methodology

78 **2.1 Overview**

As defined by Haykin (1999), artificial neural networks (ANNs) are massively paralleldistributed processors made up of simple processing units, known as neurons, which have a

natural propensity for storing experiential knowledge and making it available for use. ANNs
are inspired by biological neural networks to emulate the way in which human brains function.
The fact that neurons can be interconnected in numerous ways results in numerous possible
topologies that can be divided into two basic classes, i.e., feedforward neural networks (FNNs)
and recurrent neural networks (RNNs). In FNNs information flows from inputs to outputs in
only one direction, whereas in RNNs some of the information can flow not only in one
direction from inputs to outputs but also in opposite direction.

88 There are many algorithms for training neural network models, most of which employ some 89 form of gradient descent using backpropagation to compute the actual gradients (Werbos, 90 1974). The backpropagation algorithm is implemented by taking the derivatives of the cost 91 function with respect to the synaptic weights and then changing the weights in a gradient-92 related direction (Sexton and Dorsey 2000; Mandischer, 2002).

This study opts for a standard FNN and a quasi-Newton training algorithm, more specifically
a multilayer perceptron (MLP) trained with the Levenberg-Marquardt (LM) algorithm,
attributing to its superior accuracy in groundwater table forecasting (Daliakopoulous et al.,
2005).

97 2.2 Multilayer perceptron

Multilayer perceptron (MLP) was developed for pattern classification by Rosenblatt (1958).
Figure 1 shows the architecture of a typical MLP consisting of an input layer, one hidden layer and an output layer. In mathematical terms, a computational neuron in the hidden or output layers can be described by following pair of equations:

$$102 u = \sum_{i=1}^{n} w_i x_i (1)$$

103 and

104
$$y = \varphi(u+b)$$
 (2)

105 where $x_1, x_2, ..., x_n$ are the input signals to the neuron, $w_1, w_2, ..., w_n$ are the synaptic 106 weights, u is the linear combiner of the input signals, b is the bias, y is the output signal of 107 the neuron, whereas $\varphi(\cdot)$ is the activation function to limit the amplitude of the output signal 108 and to create a mapping between the input and output signals.

109 The universal approximation theorem states that every continuous function defined on a 110 closed and bounded set can be approximated arbitrarily closely by a MLP provided that the 111 number of neurons in the hidden layers is sufficiently high and that their activation functions 112 belong to a restricted class of functions with particular properties (Hornik et al., 1989).

113 2.3 Levenberg-Marquardt algorithm

The Levenberg-Marquardt (LM) algorithm, independently developed by Levenberg (1944)
and Marquardt (1963), provides a numerical solution to the problem of minimizing a
nonlinear function. The update rule of the LM algorithm can be presented as follows:

117
$$W_{k} = W_{k} - \left(J_{k}^{T}J_{k} + \mu_{k}I\right)^{-1}J_{k}e_{k}$$
(5)

118 where k is the iteration index, J is the Jacobian matrix, μ is the combination coefficient, I 119 is the identity matrix and e is the error vector.

120 The LM algorithm essentially blends the steepest descent method and the Gauss-Newton 121 algorithm. The optimization process is guided by the combination coefficient μ . Around the 122 error surface with complex curvature, the LM algorithm switches to the steepest descent 123 algorithm with a bigger μ , whereas if the local curvature is proper to make a quadratic 124 approximation, μ can be decreased, giving the LM algorithm a step closer to the Gauss-125 Newton algorithm. The LM algorithm is faster, more stable and less easily trapped in local 126 minima than other algorithms (Toth et al., 2000).

127 **3. Application**

128 **3.1 Study case**

Figure 2 shows the geographical location of the study area – the Nee Soon Swamp Forecast (NSSF) in Singapore. The NSSF is located in the northern part of the Singapore central catchment nature reserve bounded by the Upper Seletar, Upper Peirce and Lower Peirce reservoirs. As the only substantial freshwater swamp forest remaining in Singapore Island, the NSSF houses a diversity of flora and fauna some of which are found nowhere else in Singapore or the world (Karunasingha et al., 2013).

With an estimated area of about 750 ha, the NSSF covers the lower area of shallow valleys with slow-flowing streams and a few higher grounds with dryland forests. The elevation of NSSF ranges between 1 m to 80 m above mean sea level (MSL). The aquifer depth in the NSSF is from 20 m to 40 m, and the major soil type features silty sand with a hydraulic conductivity of 4.05 x 10^{-5} m/s. Figure 2 also depicts the locations of the 4 piezometers installed for groundwater table monitoring. The piezometers are deployed near the streams, where the observed groundwater tables vary between 0 to 1 m below the ground level.

142 3.2 ANN setup

143 The surrounding reservoirs serve as important fresh water storage for Singapore, with 144 reservoir levels being kept at relatively high levels ranging from 10 to 40 m above MSL. 145 Singapore has a typical tropical rainforest climate with abundant rainfall; the annual rainfall at 146 the NSSF region can be as high as 3,000 mm. Despite being another important influential 147 factor for the groundwater, observed evapotranspiration is not available due to the constraints 148 imposed from setting up monitoring stations in the protected forest, and hence it is exclude in 149 the ANN setup. Reservoir levels and rainfall, as the major water source and driving force, are 150 fed to the networks as inputs, while the output is the observed groundwater tables with a leading time of 1 day, 3 days and 7 days (i.e., future observed groundwater tables after 1 day, 151 3 days and 7 days). 152

A multiple-input multiple-output (MIMO) network is selected over 4 multiple-input singleoutput (MISO) ANNs for 2 reasons: (1) it is easier to implement; and (2) cross-correlation exists in the observed groundwater tables, e.g. the synchronous response to dry and wet

156 conditions; targeting the groundwater table measurements at 4 locations simultaneously, the cross-correlation impact can be captured in the synaptic weights of the trained ANN and 157 hence a better performance is expected. The MIMO network is composed of an input layer 158 with 4 input neurons (including 3 reservoir levels and one rainfall), a hidden layer with 10 159 neurons (determined by trial and error), and an output layer with 4 output neurons (future 160 observed groundwater tables at the 4 piezometers). The logistic function and threshold 161 162 function are respectively adopted as the activation functions for the hidden layer and the 163 output layer.

Daily observed data, i.e., reservoir levels, rainfall and groundwater tables, are available in2012 and 2013. The data set is divided into 3 subsets as follows:

• Training data (January 2012 to December 2012)

167 Training data are used for adjusting the synaptic weights in the network. An entire year's data168 are selected as the training data, so as to expose the network to a complete annual cycle for a169 robust training.

• Cross validation data (January 2013 to June 2013)

171 Cross validation data are used for avoiding overfitting. When the errors between the predicted 172 values and desired values in the cross validation data begin to increase, the training stops and 173 this is considered to be the point of best generalization. Half a year's data are selected as the 174 cross validation data.

• Testing data (July 2013 to December 2013)

176 Testing data are used for evaluating the performance of the network. Once the network is 177 trained, the weights are frozen; the testing set is fed into the network and the network output 178 is then compared with the desired output. Remaining half a year's data are selected as the 179 testing data.

180 **4. Results and discussion**

Figure 3 illustrates examples of the observed groundwater tables and the ANN-forecasted 181 182 groundwater tables at P1 with a leading time of 1 day, 3 days and 7 days; the corresponding scatter plots are presented in Figure 4. The 1 day network forecast agrees well with the 183 observed groundwater tables, whereas the discrepancies become larger when leading time 184 185 increases to 7 days. The response of the groundwater tables to the system forcings - reservoir 186 levels and rainfall, for such a confined and wet catchment, is rapid and sensitive. When the 187 leading time progresses, the correlation fades out between the inputs and outputs, the 188 accuracy of the ANN forecast therefore decreases. The groundwater tables experience a 189 drastic drop in July and August 2013, caused by a continuous two-month drought. As such a 190 drought condition does not exist in the training data, the ANN tends to over-predict the groundwater tables for that period. In general, the network forecast successfully resolves the 191 rising and falling tendencies of the groundwater tables, resulting in rather reasonable 192 193 groundwater table forecast.

Figure 5 and Figure 6 respectively present the groundwater table time series and scatter plotsat P4. P4 is located near the Upper Seletar reservoir, and the groundwater table is affected by

the spillway discharge released from the reservoir. Failing to include the spillway information
makes the ANN less competent in capturing the groundwater table extreme values caused by

the spillway discharge, and hence results in the lower forecast accuracy at P4.

199 Table 1 summarizes the ANN forecast efficiency through evaluating based on the testing data 200 the root mean square error (RMSE) and the correlation coefficient (r). The forecast accuracy 201 decreases slightly when the leading time increases due to the rapid and sensitive response of 202 the groundwater tables to the system forcings. The RMSE is in general within 10 cm with the 203 exception at P4 caused by the absence of the spillway information. Averaged over the 3 leading times, at P1 to P3 the RMSE is less than 8.0 cm with correlation coefficient r higher 204 205 than 0.7, whereas at P4 the averaged RMSE and correlation coefficient r are respectively 13.8 cm and 0.67. 206

207 5. Conclusions

This study, for the first time, applies artificial neural networks (ANNs) to predict the 208 209 groundwater table variations in a tropical wetland - the Nee Soon Swamp Forest (NSSF) in Singapore. The groundwater table, in such a confined freshwater swamp forest, varies rapidly 210 in the superficial aquifer layer and is very sensitive to the changes in the hydro-metrological 211 212 condition. The complex geological condition and demand on ecology conservation also 213 hinder the installation of monitoring stations to acquire the necessary input information for the numerical models. The ANN model solely utilizes the easily accessible surrounding 214 215 reservoir levels and rainfall as inputs to forecast the groundwater tables, without requiring any other prior knowledge of the system's physical properties. 216

217 The forecast is made at 4 piezometer locations with 3 leading times, i.e., 1 day, 3 days and 7 218 days. The ANN forecast shows promising accuracy, while its performance slightly decreases when the leading time progresses due to the fading correlation between the network inputs 219 and outputs. The network forecast in general successful resolves the rising and falling 220 221 tendencies of the groundwater tables, resulting in rather reasonable groundwater table forecast. 222 Averaged over the 3 leading times, the RMSE is within 10 cm and the correlation coefficient r is higher than 0.7 at P1 to P3, whereas at P4 the averaged RMSE and correlation coefficient r 223 224 are respectively 13.8 cm and 0.67 caused by the absence of the spillway information.

225 In this study, surrounding reservoir levels and rainfall are selected as ANN inputs. The 226 limited number of inputs eliminates the data demanding restrictions inherent in the numerical 227 models. However, improvements are expected if trained with more inputs, such as spillway 228 discharge, evapotranspiration and water level measurements. Less data demanding, lower computational cost and higher site-specific forecast accuracy are the advantages of the ANN-229 230 based approach over the physical-based numerical models. Numerical models, however, can 231 be applied to describe the system processes over the entire model domain given sufficient 232 information on the model inputs. Therefore, the ANN and numerical model can act as natural 233 complements in such a way that ANN is more suitable for site-specific forecast while the 234 numerical model provides a better spatial coverage.

235 Acknowledgements

- 236 This study forms part of the research project "Nee Soon Swamp Forest Biodiversity and
- 237 Hydrology Baseline Studies—Phase 2" funded by National Parks Board, Singapore. The
- authors are grateful of the financial support for making this study possible.

239 **References**

- Coulibaly, P., Anctil, F., Aravena, R., Bobee, B., 2001. Artificial neural network modeling of
 water table depth fluctuations. Water Resources Research 37 (4), 885–896.
- Daliakopoulosa, I.N., Coulibaly, P., Tsanis, I.K., 2005. Groundwater level forecasting using
 artificial neural networks. Journal of Hydrology 309, 229–240.
- French, M.N., Krajewski, W.F., Cuykendall, R.R., 1992. Rainfall forecasting in space and
 time using a neural network. Journal of Hydrology 137, 1–31.
- 246 Haykin, S., 1999. Neural Networks: A Comprehensive Foundation. Prentice Hall, New Jersey.
- Hornik, K., Stinchcombe, M., White, M., 1989. Multilayer feedforward networks are
 universal approximators. Neural Networks 2, 359–366.
- Karunasingha, D.S.K., Chui, T.F.M., Liong, S.Y., 2013. An approach for modelling the
 effects of changes in hydrological environmental variables on tropical primary forest
 vegetation. Journal of Hydrology 505 (2013), 102–112.
- Lallahem, S., Mania, J., Hani, A., Najjar, Y., 2005. On the use of neural networks to evaluate
 groundwater levels in fractured media. Journal of Hydrology 307, 92–111.
- Levenberg, K., 1944. A method for the solution of certain problems in least squares.
 Quarterly of Applied Mathematics 5, 164–168.
- Maier, H.R., Dandy, G.C., 2000. Neural networks for the prediction and forecasting of water
 resources variables: a review of modeling issues and applications. Environmental Modelling
 & Software 15, 101–124.
- Mandischer, M., 2002. A comparison of evolution strategies and backpropagation for neural
 network training. Neurocomputing 42 (1-4), 87–117.
- Marquardt, D., 1963. An algorithm for least-squares estimation of nonlinear parameters.
 SIAM Journal on Applied Mathematics 11 (2), 431–441.
- Matej, G., Isabelle, W., Jan, M., 2007. Regional groundwater model of north-east Belgium.
 Journal of Hydrology 335, 133–139.
- Pool, D.R., Blasch, K.W., Callegary, J.B., Leake, S.A., Graser, L.F., 2011. Regional
 Groundwater-Flow Model of the Redwall-Muav, Coconino, and Alluvial Basin Aquifer
 Systems of Northern and Central Arizona: USGS Scientific Investigation Report 2010-5180,
 v. 1.1, 101.
- Rosenblatt, F., 1958. The perceptron: a probabilistic model for information storage and
 organization in the brain. Psychological Review 65 (6), 386–408.

- 271 Sexton, R.S., Dorsey, E.D., 2000. Reliable classification using neural networks: a Genetic
 272 Algorithm and backpropagation comparison. Decision Support Systems 30, 11–22.
- Sun, Y., Babovic, V., Chan, E.S., 2010. Multi-step-ahead model error prediction using timedelay neural networks combined with chaos theory. Journal of Hydrology 395 (2010), 109–
 116.
- Taormina, R., Chau, K-W., Sethi, R., 2012. Artificial neural network simulation of hourly
 groundwater levels in a coastal aquifer system of the Venice lagoon. Engineering
 Applications of Artificial Intelligence, 25 (2012), 1670–1676.
- Toth, E., Brath, A., Montanari, A., 2000. Comparison of short-term rainfall prediction models
 for real-time flood forecasting. Journal of Hydrology 239, 132–147.
- Werbos, P.J., 1974. Beyond Regression: New Tools for Prediction and Analysis in the
 Behavioral Sciences. Ph.D. Thesis, Harvard University, Cambridge, MA.
- Yang, C.C., Prasher, S.O., Lacroix, R., Sreekanth, S., Patni, N.K., Masse, L., 1997. Artificial
 neural network model for subsurface-drained farmlands. Journal of Irrigation and Drainage
 Engineering 123 (4), 285–292.
- Yao, Y., Zheng, C., Liu, J., Cao, G., Xiao, H., Li, H., Li, W., 2015. Conceptual and numerical
 models for groundwater flow in an arid inland river basin. Hydrological Processes 29 (6),
 1480–1492.
- 289



292 Figure 1 Architectural diagram of a typical multilayer perceptron







Figure 3 Observed vs. ANN-forecasted groundwater tables (P1)







305 Figure 5 Observed vs. ANN-forecasted groundwater tables (P4)





	P1		P2		P3		P4	
	RMSE		RMSE		RMSE		RMSE	
	(cm)	Г	(cm)	Г	(cm)	Г	(cm)	ſ
1day	5.4	0.88	6.4	0.78	5.2	0.77	12.2	0.69
3 day	8.2	0.76	7.1	0.76	6.6	0.71	13.3	0.68
7 day	9.9	0.64	9.2	0.72	8.6	0.67	15.8	0.65
Average	7.8	0.76	7.6	0.75	6.8	0.72	13.8	0.67

311 Table 1 Evaluation statistics of the ANN forecast