

1 **Improving multi-objective reservoir operation optimization with**
2 **sensitivity-informed dimension reduction**

3 Jinggang Chu¹, Chi Zhang¹, Guangtao Fu², Yu Li¹, Huicheng Zhou¹

4 ¹ School of Hydraulic Engineering, Dalian University of Technology, Dalian 116024,
5 China

6 ² Centre for Water Systems, College of Engineering, Mathematics and Physical
7 Sciences, University of Exeter, North Park Road, Harrison Building, Exeter EX4 4QF,
8 UK

9

10

11 *Corresponding author:

12 Dr. Chi Zhang

13 School of Hydraulic Engineering, Dalian University of Technology

14 Dalian 116024, China

15 Tel.: 86-411-8470-8517

16 Fax: 86-411-8470-8517

17 E-mail: czhang@dlut.edu.cn

18

19 **Abstract**

20 This study investigates the effectiveness of a sensitivity-informed method for
21 multi-objective operation of reservoir systems, which uses global sensitivity analysis
22 as a screening tool to reduce the computational demands. Sobol's method is used to
23 screen insensitive decision variables and guide the formulation of the optimization
24 problems with a significantly reduced number of decision variables. This
25 sensitivity-informed **method** dramatically reduces the computational demands
26 required for attaining high quality approximations of optimal tradeoff relationships
27 between conflicting design objectives. The search results obtained from the reduced
28 complexity multi-objective reservoir operation problems are then used to
29 pre-condition the full search of the original optimization problem. In two case studies,
30 the Dahuofang reservoir and the inter-basin multi-reservoir system in Liaoning
31 province, China, sensitivity analysis results show that reservoir performance is
32 strongly controlled by a small proportion of decision variables. Sensitivity-informed
33 **dimension reduction** and pre-conditioning are evaluated in their ability to improve the
34 efficiency and effectiveness of multi-objective evolutionary optimization. Overall,
35 this study illustrates the efficiency and effectiveness of the sensitivity-informed
36 method and the use of global sensitivity analysis to inform **dimension reduction of**
37 **optimization problems** when solving the complex multi-objective reservoir operation
38 problems.

39 **Keywords** water supply; complexity reduction; multi-objective optimization;
40 preconditioning; sensitivity analysis; reservoir operation

41 **1 Introduction**

42 Reservoirs are often operated considering a number of conflicting objectives (such
43 as different water uses) related to environmental, economic and public services. The
44 optimization of Reservoir Operation Systems (ROS) has attracted substantial attention
45 over the past several decades. In China and many other countries, reservoirs are
46 operated according to reservoir operation rule curves which are established at the
47 planning/design stage to provide long-term operation guidelines for reservoir
48 management to meet expected water demands. Reservoir operation rule curves
49 usually consist of a series of storage volumes or levels at different periods (Liu et al.,
50 2011a and 2011b).

51 In order to solve the ROS problem, there are different approaches, such as implicit
52 stochastic optimization (ISO), explicit stochastic optimization (ESO), and
53 parameter-simulation-optimization (PSO) (Celeste and Billib, 2009). ISO uses
54 deterministic optimization, e.g., dynamic programming, to determine a set of optimal
55 releases based on the current reservoir storage and equally likely inflow scenarios
56 (Young, 1967; Karamouz and Houck, 1982; Castelletti et al., 2012; François et al.,
57 2014). Instead the use of equally likely inflow scenarios, ESO incorporates inflow
58 probability directly into the optimization process, including stochastic dynamic
59 programming and Bayesian methods (Huang et al., 1991; Tejada-Guibert et al., 1995;
60 Powell, 2007; Goor et al., 2010; Xu et al., 2014). However, many challenges remain
61 in application of these two approaches due to their complexity and ability to
62 conflicting objectives (Yeh, 1985; Simonovic, 1992; Wurbs, 1993; Teegavarapu and

63 Simonovic, 2001; Labadie, 2004).

64 In a different way, PSO predefines a rule curve shape and then utilizes
65 optimization algorithms to obtain the combination of rule curve parameters that
66 provides the best reservoir operating performance under possible inflow scenarios or a
67 long inflow series (Nalbantis and Koutsoyiannis, 1997; Oliveira and Loucks, 1997).
68 In this way, most stochastic aspects of the problem, including spatial and temporal
69 correlations of unregulated inflows, are implicitly included, and reservoir rule curves
70 could be derived directly with genetic algorithms and other direct search methods
71 (Koutsoyiannis and Economou, 2003; Labadie, 2004). Because PSO reduces the curse
72 of dimensionality problem in ISO and ESO, it is widely used in reservoir operation
73 optimization (Chen, 2003; Chang et al., 2005; Momtahan and Dariane, 2007). In this
74 study, the PSO-based approach is used to solve the ROS problem.

75 In the PSO procedure to solve the ROS problem, the values of storage volumes or
76 levels in reservoir operation rule curves are optimized to achieve one or more
77 objectives directly. Quite often, there are multiple curves, related to different purposes
78 of reservoir operation. The dimension of a ROS problem depends on the number of
79 the curves and the number of time periods. For a cascaded reservoir system, the
80 dimension can be very large, which increases the complexity and problem difficulty
81 and poses a significant challenge for most search tools currently available (Labadie,
82 2004; Draper and Lund, 2004; Sadegh et al., 2010; Zhao et al., 2014).

83 In the context of multi-objective optimal operation of ROS, there is not one single
84 operating policy that improves simultaneously all the objectives and a set of

85 non-dominating Pareto optimal solutions are normally obtained. The traditional
86 approach to multi-objective optimal reservoir operation is to reformulate the
87 multi-objective problem as a single objective problem through the use of some
88 scalarization methods, such as the weighted sum method (Tu et al., 2003 and 2008;
89 Shiau, 2011). This method has been developed to repeatedly solve the single objective
90 problem using different sets of weights so that a set of Pareto-optimal solutions to the
91 original multi-objective problem could be obtained (Srinivasan and Philipose, 1998;
92 Shiau and Lee, 2005). Another well-known method is the ϵ -constraint method (Ko et
93 al., 1997; Mousavi and Ramamurthy, 2000; Shirangi et al., 2008): all the objectives
94 but one are converted into constraints and the level of satisfaction of the constraints is
95 optimized to obtain a set of Pareto-optimal solutions. However, with the increase in
96 problem complexity (i.e., the number of objectives or decision variables), both
97 approaches become inefficient and ineffective in deriving the Pareto-optimal
98 solutions.

99 In the last several decades, bio-inspired algorithms and tools have been developed
100 to directly solve multi-objective optimization problems by simultaneously handling
101 all the objectives (Nicklow et al., 2010). In particular, multi-objective evolutionary
102 algorithms (MOEA) have been increasingly applied to the optimal reservoir operation
103 problems, with intent of revealing tradeoff relationships between conflicting
104 objectives. Suen and Eheart (2006) used the non-dominated sorting genetic algorithm
105 (NSGAI) to find the Pareto set of operating rules that provides decision makers with
106 the optimal trade-off between human demands and ecological flow requirements.

107 Zhang et al. (2013b) used a multi-objective adaptive differential evolution combined
108 with chaotic **neural** networks to provide optimal trade-offs for multi-objective
109 long-term reservoir operation problems, balancing hydropower operation and the
110 requirement of reservoir ecological environment. Chang et al. (2013) used an
111 adjustable particle swarm optimization – genetic algorithm (PSO-GA) hybrid
112 algorithm to minimize water shortages and maximize hydro-power production in
113 management of Tao River water resources.

114 However, significant challenges remain for using MOEAs in large, real-world
115 ROS applications. The high dimensionality of ROS problems makes it very difficult
116 for MOEAs to identify ‘optimal or near optimal’ solutions with the computing
117 resources that are typically available in practice. Thus the primary aim of this study is
118 to investigate the effectiveness of a sensitivity-informed optimization methodology
119 for multi-objective reservoir operation, which uses sensitivity analysis results to
120 reduce the dimension of the optimization problems, and thus improves the search
121 efficiency in solving these problems. This framework is based on the previous study
122 by Fu et al. (2012), which developed a framework **for dimension reduction of**
123 **optimization problems** that can dramatically reduce the computational demands
124 required to obtain high quality solutions for optimal design of water distribution
125 systems. The ROS case studies used to demonstrate this framework consider the
126 optimal design of reservoir water supply operation policies. Storage volumes at
127 different time periods on the operation rule curves are used as decision variables. It
128 has been widely recognized that the determination of these decision variables requires

129 a balance among different ROS objectives. Sobol's sensitivity analysis results are
130 used to form simplified optimization problems considering a small number of
131 sensitive decision variables, which can be solved with a dramatically reduced number
132 of model evaluations to obtain Pareto approximate solutions. These Pareto
133 approximate solutions are then used to pre-condition a full search by serving as
134 starting points for the multi-objective evolutionary algorithm. The results from the
135 Dahuofang reservoir and inter-basin multi-reservoir system case studies in Liaoning
136 province, China, whose conflicting objectives are minimization of industry water
137 shortage and minimization of agriculture water shortage, illustrate that
138 sensitivity-informed **dimension reduction** and pre-conditioning provide clear
139 advantages to solve large-scale multi-objective ROS problems effectively.

140

141 **2 Problem formulation**

142 Most reservoirs in China are operated according to rule curves, i.e., reservoir
143 water supply operation rule curves. Because they are based on actual water storage
144 volumes, they are simple to use. **Fig. 1 shows an illustration of rule curves for**
145 **Dahuofang reservoir based on 36 10-day periods.**

146 **As we know that water demand could be fully satisfied only when there is**
147 **sufficient water in reservoir. Water supply operation rule curve, which is used to**
148 **operate most reservoirs in China, represents the limited storage volume for water**
149 **supply in each period of a year. In detail, water demand will be fully satisfied when**
150 **the reservoir storage volume is higher than water supply operation rule curve; whereas**

151 water demand needs to be rationed when the reservoir storage volume is lower than
152 water supply operation rule curve. In general, a reservoir has more than one water
153 supply target, and there is one to one correspondence between water supply rule curve
154 and water supply target. The water supply with lower priority will be limited prior to
155 the water supply with higher priority when the reservoir storage volume is not
156 sufficient. To reflect the phenomenon that different water demands can have different
157 reliability requirements and thus different levels of priority in practice, the operation
158 rule curve for the water supply with the lower priority is located above the operation
159 rule curve for the water supply with the higher priority.

160 Fig. 1 shows water supply operation rule curves for agriculture and industry where
161 the maximum storage is smaller in the middle due to the flood control requirements in
162 wet seasons. In Fig. 1, the red line with circle represent water supply rule curve for
163 agriculture, the green line with triangle represent water supply rule curve for industry.
164 The water supply rule curve for agriculture with lower priority is located above the
165 water supply rule curve for industry with higher priority. The water storage available
166 between the minimum and maximum storages is divided into three parts: zone 1, zone
167 2 and zone 3 by the water supply rule curves for agriculture and industry.

168 Specifically, both the agricultural demand D_1 and the industrial demand D_2
169 could be fully satisfied when the actual water storage is in zone 1, which is above the
170 water supply rule curve for agriculture. When the actual water storage is in zone 2, the
171 industrial demand could be fully satisfied, and the agricultural demand has to be
172 rationed. Both the agricultural demand and the industrial demand have to be rationed

173 when the actual water storage is in zone 3. The water supply rule for a specific water
174 user consists of one water supply rule curve and rationing factors that indicate the
175 reliability and priority of the water user. The rationing factors used to determine the
176 amount of water supply for different water demands can be either assigned according
177 to the experts' knowledge or determined by optimization (Shih and ReVelle, 1995). In
178 this paper, rationing factors are given at the reservoir's design stage according to the
179 tolerable elastic range of each water user in which the damage caused by rationing
180 water supply is limited. Assuming that the specified water rationing factor α_1 is
181 applied to the water supply rule curve for agriculture in Fig. 1, the agricultural
182 demand D_1 could be fully supplied without rationing when the actual water storage
183 is in zone 1, however, when the water storage is in zone 2 or zone 3, the agricultural
184 demand has to be rationed, i.e., $\alpha_1 * D_1$. Similarly, assuming that the specified water
185 rationing factor α_2 is applied to the water supply rule curve for industry in Fig. 1, the
186 industrial demand D_2 could be fully supplied without rationing when the actual
187 water storage is in zone 1 or zone 2, however, when the water storage is in zone 3, the
188 industrial demand has to be rationed, i.e., $\alpha_2 * D_2$.

189 To provide long-term operation guidelines for reservoir management to meet
190 expected water demands for future planning years, the projected water demands and
191 long-term historical inflow are used. The optimization objective for water supply
192 operation rule curves is to minimize water shortages during the long-term historical
193 period. The ROS design problem is formulated as a multi-objective optimization
194 problem, i.e., minimizing multiple objectives simultaneously. In this paper, the

195 objectives are to minimize industry and agriculture water shortages:

$$196 \quad \min f_i(\mathbf{x}) = SI_i = \frac{100}{N} \sum_{j=1}^N \left(\frac{D_{i,j} - W_{i,j}(\mathbf{x})}{D_{i,j}} \right)^2 \quad (1)$$

197 where \mathbf{x} is the vector of decision variables, i.e., the water storages at different
 198 periods on a water-supply rule curve; SI_i is the shortage index for water demand i
 199 (agricultural water demand when $i = 1$, industrial water demand when $i = 2$), which
 200 measures the average annual shortage occurred during N years, and is used as an
 201 indicator to reflect water supply efficiency; N is the total number of years simulated;
 202 $D_{i,j}$ is the demand for water demand i during the j th year; $W_{i,j}(\mathbf{x})$ is the actually
 203 delivered water for water demand i during the j th year. The term $W_{i,j}(\mathbf{x})$ is
 204 calculated below using agricultural water demand ($i = 1$) as an example. If the
 205 actual water storage is above the water supply rule curve for agricultural water
 206 demand ($i = 1$) at period t in a year, the delivered water at period t is its full
 207 demand without being rationed, $D_{1,t}$. If the actual water storage is below the water
 208 supply rule curve for agricultural water demand at period t , the delivered water for
 209 agricultural water demand at period t is its rationed demands, $\alpha_1 * D_{1,t}$.

210 For the ROS optimization problem, the mass balance equations are:

$$211 \quad S_{t+1} - S_t = I_t - R_t - SU_t - E_t \quad (2)$$

$$212 \quad R_t = g(\mathbf{x}), SU_t = k(\mathbf{x}), E_t = e(\mathbf{x}) \quad (3)$$

$$213 \quad ST_t^{\min} \leq S_t \leq ST_t^{\max}, ST_t^{\min} \leq \mathbf{x} \leq ST_t^{\max} \quad (4)$$

214 where S_t is the initial water storage at the beginning of period t ; S_{t+1} is the
 215 ending water storage at the end of period t ; I_t, R_t, SU_t and E_t are inflow, delivery
 216 for water use, spill and evapotranspiration loss, respectively; and ST_t^{\max} and ST_t^{\min}

217 are the maximum and minimum storage, respectively. Additionally, because $W_{i,j}(x)$
218 in Equation (1) is the actually delivered water for water demand i during the j th
219 year, the sum of R during the j th year equals to $W_{1,j}(x) + W_{2,j}(x)$.

220

221 **3 Methodology**

222 Pre-conditioning is a technique that uses a set of known good solutions as starting
223 points to improve the search process of optimization problems (Nicklow et al., 2010).
224 It is very challenging in determining good initial solutions, and different techniques
225 including the domain knowledge can be used. This study utilizes a
226 sensitivity-informed **dimension reduction** to develop simpler search problems that
227 consider only a small number of highly sensitive decisions. The results from these
228 simplified search problems can be used to successively pre-condition search for larger,
229 more complex formulations of ROS design problems. The ϵ -NSGAI, a popular
230 multi-objective evolutionary algorithm, is chosen as it has been shown effective for
231 many engineering optimization problems (Kollat and Reed, 2006; Tang et al., 2006;
232 Kollat and Reed, 2007). For the two-objectives (ϵ_{SL_1} and ϵ_{SL_2}) considered in this
233 paper, their epsilon values in ϵ -NSGAI were chosen based on reasonable and
234 practical requirements and were both set to 0.01. According to the study by Fu et al.
235 (2012), the sensitivity-informed methodology, as shown in Fig. 2, has the following
236 steps:

237 1. Perform a sensitivity analysis using Sobol's method to calculate the sensitivity
238 indices of all decision variables regarding the ROS performance measure;

239 2. Define a simplified problem that considers only the most sensitive decision
240 variables by imposing a user specified threshold (or classification) of sensitivity;

241 3. Solve the simplified problem using ε -NSGAI with a small number of model
242 simulations;

243 4. Solve the original problem using ε -NSGAI with the Pareto optimal solutions
244 from the simplified problem fed into the initial population.

245 3.1 Sobol's sensitivity analysis

246 Sobol's method was chosen for sensitivity analysis because it can provide a
247 detailed description of how individual variables and their interactions impact model
248 performance (Tang et al., 2007b; Zhang et al., 2013a). A model could be represented
249 in the following functional form:

$$250 \quad y = f(\mathbf{x}) = f(x_1, \dots, x_p) \quad (5)$$

251 where y is the goodness-of-fit metric of model output, and $\mathbf{x} = (x_1, \dots, x_p)$ is the
252 parameter set. Sobol's method is a variance based method, in which the total variance
253 of model output, $D(y)$, is decomposed into component variances from individual
254 variables and their interactions:

$$255 \quad D(y) = \sum_i D_i + \sum_{i<j} D_{ij} + \sum_{i<j<k} D_{ijk} + \dots + D_{12\dots m} \quad (6)$$

256 where D_i is the amount of variance due to the i th variable x_i , and D_{ij} is the
257 amount of variance from the interaction between x_i and x_j . The model sensitivity
258 resulting from each variable can be measured using the Sobol's sensitivity indices of
259 different orders:

$$260 \quad \text{First-order index: } S_i = \frac{D_i}{D} \quad (7)$$

261 Second-order index: $S_{ij} = \frac{D_{ij}}{D}$ (8)

262 Total-order index: $S_{Ti} = 1 - \frac{D_{\sim i}}{D}$ (9)

263 where $D_{\sim i}$ is the amount of variance from all the variables except for x_i , the
264 first-order index S_i measures the sensitivity from the main effect of x_i , the
265 second-order index S_{ij} measures the sensitivity resulting from the interactions
266 between x_i and x_j , and the total-order index S_{Ti} represents the main effect of x_i
267 and its interactions with all the other variables.

268 3.2 Performance metrics

269 Since MOEA uses random-based search, performance metrics are used in this
270 study to compare the quality of the approximation sets derived from replicate
271 multi-objective evolutionary algorithm runs. Three indicators were selected: the
272 generational distance (Veldhuizen and Lamont, 1998), the additive ϵ -indicator (Zitzler
273 et al., 2003), and the hypervolume indicator (Zitzler and Thiele, 1998).

274 The generational distance measures the average Euclidean distance from solutions
275 in an approximation set to the nearest solution in the reference set, and indicates
276 perfect performance with zero. The additive ϵ -indicator measures the smallest
277 distance that a solution set needs to be translated to completely dominate the reference
278 set. Again, smaller values of this indicator are desirable as this indicates a closer
279 approximation to the reference set.

280 The hypervolume indicator, also known as the S metric or the Lebesgue measure,
281 measures the size of the region of objective space dominated by a set of solutions. The
282 hypervolume not only indicates the closeness of the solutions to the optimal set, but

283 also captures the spread of the solutions over the objective space. The indicator is
284 normally calculated as the volume difference between a solution set derived from an
285 optimization algorithm and a reference solution set. In this study, the worst case
286 solution is chosen as reference. For example, the worst solution is (1, 1) for two
287 minimization objectives in the normalized objective space. Thus larger hypervolume
288 indicator values indicate improved solution quality and imply a larger distance from
289 the worst solution.

290

291 **4 Case study**

292 Two case studies of increasing complexity are used to demonstrate the advantages
293 of the sensitivity-informed methodology: (1) the Dahuofang reservoir, and (2) the
294 inter-basin multi-reservoir system in Liaoning province, China. The inter-basin
295 multi-reservoir system test case is a more complex ROS problem with Dahuofang,
296 Guanyinge and Shenwo reservoirs. In the two ROS problems, the reference sets were
297 obtained from all the Pareto optimal solutions across a total of 10 random seed trials,
298 each of which was run for a maximum number of function evaluations (NFE) of
299 500,000. Additionally, the industrial and agricultural water demands in the future
300 planning year, i.e., 2030, and the historical inflow from 1956 to 2006 were used to
301 optimize reservoir operation and meet future expected water demands in the two case
302 studies.

303 **4.1 Dahuofang reservoir**

304 The Dahuofang reservoir is located in the main stream of Hun River, in Liaoning

305 province, Northeast China. The Dahuofang reservoir basin drains an area of 5437 km²,
306 and within the basin the total length of Hun River is approximately 169 km. The main
307 purposes of the Dahuofang reservoir are industrial water supply and agricultural water
308 supply to central cities in Liaoning province. The reservoir characteristics and yearly
309 average inflow are illustrated in Table 1.

310 The Dahuofang ROS problem is formulated as follows: the objectives are
311 minimization of industrial shortage index and minimization of agricultural shortage
312 index as described in Equation (1); the decision variables include storage volumes on
313 the industrial and agricultural curves. For the industrial curve, a year is divided into
314 24 time periods (with ten days as the scheduling time step from April to September,
315 and one month as the scheduling time step in the remaining months). Thus there are
316 twenty-four decision variables for industrial water supply. The agricultural water
317 supply occurs only in the periods from the second ten-day of April to the first ten-day
318 of September, thus there are fifteen decision variables for agricultural water supply. In
319 total, there are thirty-nine decision variables.

320 **4.2 Inter-basin multi-reservoir system**

321 As shown in Fig. 3, Dahuofang, Guanyinge and Shenwo reservoirs compose the
322 inter-basin multi-reservoir system in Liaoning province, China.

323 Liaoning province in China covers an area of 146×10^3 km² with an extremely
324 uneven distribution of rainfall in space. The average amount of annual precipitation
325 decreases from 1100 mm in east to 600 mm in west (WMR-PRC, 2008). However, the
326 population, industries, and agricultural areas mainly concentrate in the western parts.

327 Therefore, it is critical to develop the best water supply rules for the inter-basin
328 multi-reservoir system to decrease the risk of water shortages caused by the mismatch
329 of water supplies and water demands in both water deficit regions and water surplus
330 regions. Developing inter-basin multi-reservoir water supply operation rules has been
331 promoted as a long-term strategy for Liaoning province to meet the increasing water
332 demands in water shortage areas. In the inter-basin multi-reservoir system of Liaoning
333 province, the abundant water in Dahuofang, Guanying and Shenwo reservoirs is
334 diverted downstream to meet the water demands in water shortage areas, especially
335 the region between Daliaohekou and Sanhekou hydrological stations.

336 The main purposes of the inter-basin multi-reservoir system are industrial water
337 supply and agricultural water supply to eight cities (Shenyang, Fushun, Anshan,
338 Liaoyang, Panjin, Yingkou, Benxi and Dalian) of Liaoning province, and
339 environmental water demands need to be satisfied fully. The characteristics of each
340 reservoir in the inter-basin multi-reservoir system are illustrated in Table 2.

341 The flood season runs from July to September, during which the inflow takes up a
342 large part of the annual inflow. The active storage capacities of Dahuofang and
343 Shenwo reservoirs reduce significantly during flood season for the flood control.

344 The inter-basin multi-reservoir operation system problem is formulated as follows:
345 the objectives are minimization of industrial shortage index and minimization of
346 agricultural shortage index as described in Equation (1). Regarding Shenwo reservoir,
347 which has the same water supply operation rule curve features as Dahuofang reservoir,
348 the decision variables include storage volumes on the industrial and agricultural

349 curves and there are thirty-nine decision variables. Regarding Guanying reservoir,
350 the decision variables include storage volumes on the industrial curve and water
351 transferring curve due to the requirement of exporting water from Guanying
352 reservoir to Shenwo reservoir in the inter-basin multi-reservoir system, which is
353 similar to the water supply operation rule curve for industrial water demand, and there
354 are forty-eight decision variables. Therefore, the inter-basin multi-reservoir system
355 has six rule curves and $39 \times 2 + 48 = 126$ decision variables in total.

356

357 **5 Results and discussions**

358 **5.1 Dahuofang reservoir**

359 In the Dahuofang reservoir case study, a set of 2000 Latin Hypercube samples
360 were used per decision variable yielding a total number of $2000 \times (39 + 2) =$
361 82000 model simulations used to compute Sobol's indices. Following the
362 recommendations of Tang et al. (2007a, b) boot-strapping the Sobol' indices showed
363 that 2000 samples per decision variable were sufficient to attain stable rankings of
364 global sensitivity.

365 The first-order indices representing the individual contributions of each variable to
366 the variance of the objectives are shown in blue in Fig. 4. The total-order indices
367 representing individual and interactive impacts on the variance of the objectives are
368 represented by the total height of bars. Agr4_2 represents decision variable
369 responding to water storage volume on the agricultural curve at the second ten days of
370 April and ind3_3 represents decision variable responding to water storage volume on

371 the industrial curve at the last ten days of March, and so on. Considering the shortage
372 index for the industrial water demand, the water storages at time periods ind1, ind2,
373 ind3, ind10, ind11, and ind12, i.e., the water storages at time periods 1, 2, 3, 10, 11,
374 and 12 of water supply operation rule curves for industrial water demand are the most
375 sensitive variables, accounting for almost 100% of the total variance. Considering the
376 agricultural shortage index, the water storages at time periods from agr4-2 to agr5-3,
377 i.e., the water storages at the first five time periods of water supply operation rule
378 curves for agricultural water demand are the most sensitive variables. **The explanation**
379 **for the most sensitive variables in water supply operation rule curves for industrial**
380 **and agricultural water demands will be provided in section 5.1.3.**

381 **5.1.1 Simplified problems**

382 Building on the sensitivity results shown in Fig. 4, one simplified version of the
383 Dahuofang ROS problem is formulated: only 11-periods are considered for
384 optimization, i.e., time periods ind1, ind2, ind3, ind10, ind11, and ind12 for industrial
385 curve and agr4-2, agr4-3, agr5-1, agr5-2, and agr5-3 for agricultural curve based on a
386 total-order Sobol's index threshold of greater than 10%. **The threshold is subjective**
387 **and its ease-of-satisfaction decreases with increasing number of parameters or**
388 **parameter interactions. In all of the results for the Sobol's method, parameters**
389 **classified as the most sensitive contribute, on average, at least 10 percent of the**
390 **overall model variance (Tang et al., 2007a, b).** The full search 39-period problem
391 serves as the performance baseline relative to the reduced complexity problem.

392 **5.1.2 Pre-conditioned optimization**

393 In this section, the pre-conditioning methodology is demonstrated using the
394 11-period simplification of the Dahuofang ROS test case from the prior section, **while**
395 **the insensitive decision variables are set randomly first with domain knowledge and**
396 **kept constant during the solution of the simplified problem.**

397 Using the sensitivity-informed methodology, the 11-period case was first solved
398 using ϵ -NSGAI with a maximum NFE of 2000, and the Pareto optimal solutions
399 **combined with the constant insensitive decision variables** were then used as starting
400 points to start a complete new search with a maximum NFE of 498,000. The standard
401 search using ϵ -NSGAI was set to a maximum NFE of 500,000 so that the two
402 methods have the same NFE used for search. In this case, 10 random seed trials were
403 used given the computing resources available. The search traces in Fig. 5 show for all
404 three metrics (generational distance, additive epsilon indicator, and hypervolume) that
405 the complexity-reduced case can reliably approximate their portions of the industrial
406 and agricultural water shortage tradeoff given their dramatically reduced search
407 periods. All three metrics show **diminishing values** at the end of the reduced search
408 periods. The pre-conditioning results are shown in Fig. 5 in red search traces
409 continuing from the blue reduced complexity search results.

410 Fig. 5 clearly highlight that the sensitivity-informed pre-condition problems
411 dramatically enhance search efficiency in terms of the generational distance, additive
412 epsilon indicator, and hypervolume metrics. Overall, sensitivity-informed **dimension**
413 **reduction** and pre-conditioning yield strong efficiency gains and more reliable search
414 (i.e., narrower band widths on search traces) for the Dahuofang ROS test case.

415 Fig. 6(a) shows Pareto fronts from a NFE of 3000, 5000 and 8000 in the evolution
416 process of one random seed trial. In the case of the pre-conditioned search, the
417 solutions from 3000, 5000 and 8000 evaluations are much better than the
418 corresponding solutions in the case of standard baseline search. The results show that
419 the Pareto approximate front of the pre-conditioned search is much wider than that of
420 the standard search, and clearly dominates that of the standard search in all the
421 regions across the entire objective space.

422 Fig. 6(b) shows the best and worst Pareto fronts from a NFE of 500,000 and 8000
423 in the evolution process of ten seed trials. In the case of the pre-conditioned search,
424 the best solutions from 500,000 evaluations are better than the corresponding
425 solutions in the case of standard baseline search. Although it is obvious that there are
426 not many differences between solutions obtained from pre-conditioned search and
427 solutions from standard baseline search due to the complexity of the problem, the best
428 Pareto fronts from a NFE of 8000 in the case of the pre-condition search are
429 approximate the same as the best Pareto fronts from a NFE of 500,000 in the case of
430 the standard baseline search.

431 Fig. 7 shows the computational savings for two thresholds of hypervolume values
432 0.80 and 0.85 in the evolution process of each seed trial. In both cases of the
433 thresholds of hypervolume values 0.80 and 0.85, NFE of the pre-conditioned search is
434 less than standard baseline search for each seed. In the case of the threshold of
435 hypervolume value 0.80, the average NFEs of full search and pre-conditioned full
436 search are approximately 94,564 and 25,083 for one seed run respectively, and the

437 computation is saved by 73.48%. Although the NFE of Sobol's analysis is 82,000, the
438 average NFEs of pre-conditioned full search is approximately $25,083 + 82,000/$
439 $10 = 33,283$ for each seed run, and the computational saving is 64.80%.

440 Similarly, in the case of the threshold of hypervolume value 0.85, which is
441 extremely difficult to achieve, the average NFEs of full search and pre-conditioned
442 full search are approximately 214,049 and 105,060 for each seed run respectively, and
443 the computation is saved by 50.92%. When the computation demand by Sobol's
444 analysis is considered, the computational saving is still 47.09%.

445 **5.1.3 Optimal operation rule curves**

446 The rule curves for Dahuofang reservoir from the final Pareto fronts based on the
447 projected water demands and long-term historical inflow are shown in Fig. 8 (S2).
448 The effectiveness and reasonability of the rule curves for Dahuofang reservoir are
449 analyzed as follows.

450 Firstly, the optimal operational rule curves in Fig. 8 (S2) have the same
451 characteristics as they are used in practice. During the pre-flood season (from April to
452 June), the curves gradually become lower so that they can reduce the probability of
453 limiting water supply and empty the reservoir storage for the flood season (from July
454 to early September). During the flood season, the curves also stay in low positions
455 owing to the massive reservoir inflow and the requirement of flood control, so that it
456 is beneficial to supply as much water as possible. However, during the season from
457 mid-September to March, the curves remain high, especially from mid-September to
458 October, in order to increase the probability of limiting water supply and retaining

459 enough water for later periods to avoid severe water-supply shortages as drought
460 occurs.

461 Secondly, Fig. 8 (S2) shows that different water demands occur at different
462 periods, e.g., industrial water demand occurs throughout the whole year, and
463 agricultural water demand occurs only at the periods from the second ten-day of April
464 to the first ten-day of September. Specially, during the flood season, there are still
465 agricultural water demands due to temporal and spatial variations of rainfall though
466 they are significantly reduced. Also note that the water supply curves are developed
467 based on a historical, long-term rainfall series and the projected demands are also
468 based on historical demands, covering stochastic uncertainties in demands and
469 rainfalls. Due to the higher priority of industrial water supply than agricultural water
470 supply, the industrial water supply curve is more close to minimum storage
471 throughout the year than the agricultural water supply curve. Due to the conflicting
472 relationship between industrial and agricultural water demands, the industrial water
473 supply curve is higher during the non-flood season. Thus, if the industrial water
474 supply curve is too low during the non-flood season from January to April, which
475 implies that the industrial water demand is satisfied sufficiently, there would not be
476 enough water supplied for the agricultural water demand in the same year. Similarly,
477 if the industrial water supply curve is too low during the non-flood season from
478 September to December, there would not be enough water supplied for the
479 agricultural water demand in the next one or more years.

480 Thirdly, the inflow and industrial water demands are relatively stable during the

481 non-flood seasons from January to March and from October to December, so one
482 month is taken as the scheduling time step, which is in accordance with the
483 requirement of Dahuofang reservoir operation in practice. Due to the larger amount of
484 industrial water demand in periods 1, 2, 3, 10, 11 and 12 (January-March and
485 October-December) than other periods, the water storages at these time periods are
486 very important to industrial water supply, making them the most sensitive variables.
487 Because the agricultural water demand is very high during the non-flood period from
488 April to May, the agricultural water supply curve at this time period is higher, and the
489 water storages at time periods from agr4-2 to agr5-3, i.e., the water storages at the
490 first five time periods of water supply operation rule curve for agricultural water
491 demand, are the most important variables. On the other hand, in practice, if the
492 agricultural water demand could not be satisfied at the first few periods of water
493 supply operation rule curve, the agricultural water supply at each period throughout
494 the year would be limited, i.e., the interactive effects from variables are noticeable at
495 time periods from agr4-2 to agr5-3.

496 Additionally, comparisons are made among the optimized solutions from the final
497 Pareto fronts, including industry-favoring solution (S0), agriculture-favoring solution
498 (S1) and compromised solution (S2). The comparisons of water shortage indices
499 among different solutions are shown in Table 3, and the optimal rule curves for
500 different solutions are shown in Fig. 8.

501 It could be seen from Table 3 and Fig. 8 that there are larger differences among
502 different solutions. With industry-favoring solution (S0), the agricultural water supply

503 curve at the period from April to May is the highest among the three solutions.
504 Because the agricultural water demand is very high during the non-flood period from
505 April to May, the highest position of agricultural water supply curve at these periods
506 could cause that the agricultural water demand would not be satisfied at the first few
507 periods of agricultural water supply operation rule curve, and the agricultural water
508 supply at each period throughout the year would be limited easily. Therefore, in S0,
509 the industrial water demand could be fully satisfied through limiting agricultural
510 water supply to a large extent, and lowering the industrial water supply curve;
511 industrial and agricultural water shortage indices are 0.000 and 3.550, respectively.
512 Opposite to S0, the agricultural water demand in S1 could be satisfied largely through
513 lowering the agricultural water supply curve on the period from April to May and
514 raising the industrial water supply curve; and industrial and agricultural water
515 shortage indices are 0.020 and 1.380, respectively. Compared with solutions S0 and
516 S1, two objectives are balanced in compromised solution (S2), where industrial and
517 agricultural water shortage indices are 0.007 and 1.932, respectively.

518

519 **5.2 Inter-basin multi-reservoir system**

520 **5.2.1 Sensitivity analysis**

521 Similar to the Dahuofang case study, a set of 2000 Latin Hypercube samples were
522 used per decision variable yielding a total number of $2000 \times (126 + 2) = 256,000$
523 model simulations to compute Sobol's indices in this case study.

524 The first-order and total-order indices for 126 decision variables are shown in Fig.

525 9. Similar to the results obtained from the Dahuofang ROS Problem in Fig. 4, the
526 variance in the two objectives, i.e., industrial and agricultural shortage indices, are
527 largely controlled by the water storages at time periods from agr4-2 to agr5-3 of
528 Shenwo reservoir water supply operation rule curves for agricultural water demand,
529 the water storages at time periods from agr4-2 to agr5-3 of Dahuofang reservoir water
530 supply operation rule curves for agricultural water demand, the water storages at time
531 periods ind1, ind2, ind3, ind7-1, ind10, ind11, and ind12 of Dahuofang reservoir
532 water supply operation rule curves for industrial water demand based on a total-order
533 Sobol's index threshold of greater than 3%, which is subjective and its
534 ease-of-satisfaction decreases with increasing numbers of parameters or parameter
535 interactions. These 17 time periods are obvious candidates for decomposing the
536 original optimization problem and formulating a pre-conditioning problem. Therefore,
537 the simplified problem is defined from the original design problem with the 109
538 intensive time periods removed, while the insensitive decision variables are set
539 randomly first with domain knowledge and kept constant during the solution of the
540 simplified problem. It should be noted that the increased interactions across sensitive
541 time periods in this test case. These interactions verify that this problem represents a
542 far more challenging search problem.

543 5.2.2 Pre-conditioned optimization

544 Using the sensitivity-informed methodology, the simplified problem was first
545 solved using ϵ -NSGAI with a maximum NFE of 5000, and the Pareto optimal
546 solutions combined with the constant insensitive decision variables were then used as

547 starting points to start a complete new search with a maximum NFE of 495,000. The
548 standard search using ϵ -NSGAI was set to a maximum NFE of 500,000 so that the
549 two methods have the same NFE used for search. In this case, 10 random seed trials
550 are used given the computing resources available. Similar to the results obtained from
551 the Dahuofang ROS problem in Fig. 5, the search traces in Fig. 10 show all three
552 metrics (generational distance, additive epsilon indicator, and hypervolume) that
553 represent performance metrics for the inter-basin multi-reservoir water supply
554 operation system problem. Similarly, the pre-conditioning results are shown in Fig. 10
555 in red search traces continuing from the blue reduced complexity search results. It is
556 clear that the sensitivity-informed pre-condition problems enhance search efficiency
557 in terms of the generational distance, additive epsilon indicator, and hypervolume
558 metrics. However, with the increase in problem complexity in comparison to the first
559 case study (i.e., the number of decision variables from 39 to 126), the search of ROS
560 optimization problem becomes more difficult, and so the metrics obtained from
561 pre-conditioned search are not improved greatly compared with the standard baseline
562 search and the pre-conditioning results shown in Fig. 10 are as good as the results
563 shown in Fig. 5.

564 Fig. 11(a) shows Pareto fronts from a NFE of 6000, 8000 and 10,000 in the
565 evolution process of one random seed trial. In the case of the pre-conditioned search,
566 the solutions from the three NFE snapshots are much better than those from standard
567 baseline search. Similar to Fig. 6(a), the results show that the Pareto approximate
568 front of the pre-conditioned search is much wider than that of the standard search, and

569 clearly dominates that of the standard search in all the regions across the entire
570 objective space. Additionally, in the case of the pre-conditioned search, the solutions
571 from 6000 evaluations are as good as those from 8000 evaluations and 10,000
572 evaluations. And they are much better than the solutions from the standard baseline
573 search. It should be noted that the slow progress in the Pareto approximate fronts from
574 6000 to 10,000 evaluations reveals the difficulty of the inter-basin multi-reservoir
575 operation system problem.

576 Fig. 11(b) shows the best and worst Pareto fronts from a NFE of 500,000 in the
577 evolution process of ten seeds trials. Although it is obvious that the best Pareto
578 approximate front of the pre-conditioned is as good as that of the standard search in
579 all the regions across the entire objective space approximately, the Pareto solutions
580 from 10 trials of the pre-conditioned search have significantly reduced variation,
581 indicating a more reliable performance of the pre-conditioned method. In other words,
582 the results show that the Pareto solution from one random seed trial of the
583 pre-conditioned search is as good as the best solution from ten random seed trials of
584 the standard search. That is to say, in the case of the pre-conditioned search, one
585 random seed trial with a NFE of 500,000 is sufficient to obtain the best set of Pareto
586 solutions, however, in the case of the standard search, ten seed trials with a total of
587 $500,000 * 10 = 5,000,000$ NFE are required to obtain the Pareto solutions. Note that
588 the NFE of Sobol's analysis is 256,000, which is about half of the NFE of one
589 random seed trial. Thus, an improvement in search reliability can significantly reduce
590 the computational demand for a complex search problem such as the multi-reservoir

591 case study, even when the computation required by sensitivity analysis is included.

592

593 **5.3 Discussions**

594 The methodology tested in this study aims to reduce the number of decision
595 variables through sensitivity-guided **dimension reduction** to form simplified problems.

596 The optimization results from the two ROS problems show the reduction in decision
597 space can make an impact on the reliability and efficiency of the search algorithm. For
598 the Dahuofang ROS problem, recall that the original optimization problem has 39
599 decision variables, and the simplified problem has 11 decision variables based on
600 Sobol's analysis. In the case of the inter-basin multi-reservoir operation system, the
601 original optimization problem has 126 decision variables, and the simplified problem
602 has a significantly reduced number of decision variables, i.e., 17. Searching in such
603 significantly reduced space formed by sensitive decision variables makes it much
604 easier to reach good solutions.

605 Although Sobol's global sensitivity analysis is computationally expensive, it
606 captures the important sensitive information between a large number of variables for
607 ROS models. This is critical for correctly screening insensitive decision variables and
608 guiding the formulation of ROS optimization problems of reduced complexity (i.e.,
609 fewer decision variables). For example, in the Dahuofang ROS problem, accounting
610 for the sensitive information, i.e., using total-order or first-order indices, result in a
611 simplified problem for threshold of 10% as shown in Fig. 4. Compared with the
612 standard search, this sensitivity-informed **method** dramatically reduces the

613 computational demands required for attaining high quality approximations of optimal
614 ROS tradeoffs relationships between conflicting objectives, i.e., the best Pareto fronts
615 from a NFE of 8000 in the case of the pre-condition search are approximately the
616 same as the best Pareto front from a NFE of 500,000 in the case of the standard
617 baseline search.

618 In reality for a very large and computationally intensive problem, the full search
619 with all the decision variables would likely be so difficult that it may not be optimized
620 sufficiently. However, as shown here, these simplified problems can be used to
621 generate high quality pre-conditioning solutions and thus dramatically improve the
622 computational tractability of complex problems. The framework could be used for
623 solving the complex optimization problems with a large number of decision variables.

624 For example, Fu et al. (2012) has used the framework for reducing the complexity
625 of the multi-objective optimization problems in water distribution system (WDS), and
626 applied it to two case studies with different levels of complexity - the New York
627 Tunnels rehabilitation problem and the Anytown rehabilitation/redesign problem. For
628 the New York Tunnels network, because the original optimization problem has 21
629 decision variables (pipes) and each variable has 16 options, the decision space is
630 $16^{21} = 1.934 \times 10^{25}$. The simplified problem with 8 decision variables based on
631 Sobol's analysis have a decision space of $16^8 = 4.295 \times 10^9$. To obtain the same
632 threshold of hypervolume value 0.78 for the New York Tunnels rehabilitation problem,
633 the most the pre-conditioned search need is 60 to 70% fewer NFE relative to the full
634 search through 50 random seed trials. In the case of the Anytown network, the original

635 problem has a space of 2.859×10^{73} , and the simplified problem has a significantly
636 reduced space of 8.364×10^{38} . Through 50 random seed trials for the Anytown
637 rehabilitation/redesign problem, the full search requires average of 800000
638 evaluations to reach hypervolume value 0.77, and the pre-conditioned search exceeds
639 hypervolume value 0.8 in all trials in fewer than 200000 evaluations. The results also
640 show that searching in such significantly reduced space formed by sensitive decision
641 variables makes it much easier to reach good solutions, and the sensitivity-informed
642 reduction of problem size and pre-conditioning improve the efficiency, reliability and
643 effectiveness of the multi-objective evolutionary optimization.

644 It should be noted that the framework for sensitivity-informed dimension
645 reduction of optimization problems is completely independent of multi-objective
646 optimization algorithms, that is, any multi-objective algorithms could be embedded in
647 the framework, including AMALGAM (Vrugt and Robinson, 2007). When dealing
648 with three or more objectives, the formulation of the optimization problems with a
649 significantly reduced number of decision variables will dramatically reduce the
650 computational demands required to attain Pareto approximate solutions in a similar
651 way to the two-objective optimization case studies considered in this paper.

652

653 **6 Conclusions**

654 This study investigates the effectiveness of a sensitivity-informed optimization
655 method for the ROS multi-objective optimization problems. The method uses a global
656 sensitivity analysis method to screen out insensitive decision variables and thus forms

657 simplified problems with a significantly reduced number of decision variables. The
658 simplified problems dramatically reduce the computational demands required to attain
659 Pareto approximate solutions, which themselves can then be used to pre-condition and
660 solve the original (i.e., full) optimization problem. This methodology has been tested
661 on two case studies with different levels of complexity- the Dahuofang reservoir and
662 the inter-basin multi-reservoir system in Liaoning province, China. The results
663 obtained demonstrate the following:

664 1. The sensitivity-informed **dimension reduction** dramatically increases both the
665 computational efficiency and effectiveness of the optimization process when
666 compared to the conventional, full search approach. This is demonstrated in both case
667 studies for both MOEA efficiency (i.e., the NFE required to attain high quality
668 tradeoffs) and effectiveness (i.e., the quality approximations of optimal ROS tradeoffs
669 relationships between conflicting design objectives).

670 2. The Sobol's method can be used to successfully identify important sensitive
671 information between different decision variables in the ROS optimization problem
672 and it is important to account for interactions between variables when formulating
673 simplified problems.

674 Overall, this study illustrates the efficiency and effectiveness of the
675 sensitivity-informed method and the use of global sensitivity analysis to inform
676 **dimension reduction**. This method can be used for solving the complex
677 multi-objective optimization problems with a large number of decision variables, such
678 as optimal design of water distribution and urban drainage systems, distributed

679 hydrological model calibration, multi-reservoir optimal operation and many other
680 engineering optimization problems.

681

682 **Acknowledgements**

683 This study was supported by the China Postdoctoral Science Foundation Grants
684 (2014M561231), and National Natural Science Foundation of China Grants
685 (51320105010, 51279021, and 51409043).

686

687

688 **References**

- 689 Castelletti, A., Pianosi, F., Quach, X., Soncini-Sessa, R. 2012. Assessing water
690 reservoirs management and development in Northern Vietnam. *Hydrology and*
691 *Earth System Sciences* 16, 189-199.
- 692 Celeste, A.B., Billib, M. 2009. Evaluation of stochastic reservoir operation
693 optimization models. *Advances in Water Resources* 32, 1429-1443.
- 694 Chang, F.J., Chen, L., Chang, L.C. 2005. Optimizing the reservoir operating rule
695 curves by genetic algorithms. *Hydrological Processes* 19 (11), 2277-2289.
- 696 Chen, L. 2003. Real coded genetic algorithm optimization of long term reservoir
697 operation. *Journal of the American Water Resources Association* 39 (5),
698 1157-1165.
- 699 Chang, J.X., Bai, T., Huang, Q., Yang, D.W. 2013. Optimization of water resources
700 utilization by PSO-GA. *Water Resources Management* 27 (10), 3525-3540.
- 701 Draper, A.J., Lund, J.R. 2004. Optimal hedging and carryover storage value. *Journal*
702 *of Water Resources Planning and Management* 130 (1), 83-87.
- 703 François, B., Hingray, B., Hendrickx, F., Creutin, J.D. 2014. Seasonal patterns of
704 water storage as signatures of the climatological equilibrium between resource
705 and demand. *Hydrology and Earth System Sciences* 18, 3787-3800.
- 706 Fu, G.T., Kapelan, Z., Reed, P. 2012. Reducing the complexity of multi-objective
707 water distribution system optimization through global sensitivity analysis.
708 *Journal of Water Resources Planning and Management* 138 (3), 196-207.
- 709 Goor, Q., Halleux, C., Mohamed, Y., Tilmant, A. 2010. Optimal operation of a

710 multipurpose multireservoir system in the Eastern Nile River Basin. *Hydrology*
711 and *Earth System Sciences* 14, 1895-1908.

712 Huang, W.C., Harboe, R., Bogardi, J.J. 1991. Testing stochastic dynamic
713 programming models conditioned on observed or forecasted inflows. *Journal of*
714 *Water Resources Planning and Management* 117, 28-36.

715 Karamouz, M., Houck, M.H. 1982. Annual and monthly reservoir operating rules
716 generated by deterministic optimization. *Water Resources Research* 18 (5),
717 1337-1344.

718 Ko, S.K., Oh, M.H., Fontane, D.G. 1997. Multiobjective analysis of
719 service-water-transmission systems. *Journal of Water Resources Planning and*
720 *Management* 132 (2), 78-83.

721 Kollat, J.B., Reed, P.M. 2006. Comparing state-of-the-art evolutionary multi-objective
722 algorithms for long-term groundwater monitoring design. *Advances in Water*
723 *Resources* 29, 792-807.

724 Kollat, J.B., Reed, P.M. 2007. A computational scaling analysis of multiobjective
725 evolutionary algorithms in long-term groundwater monitoring applications.
726 *Advances in Water Resources* 30 (3), 408-419.

727 Koutsoyiannis, D., Economou, A. 2003. Evaluation of the parameterization-
728 simulation-optimization approach for the control of reservoir systems. *Water*
729 *Resources Research* 39 (6), WES2.1-WES2.17.

730 Labadie, J.W. 2004. Optimal operation of multireservoir systems: state-of-the-art
731 review. *Journal of Water Resources Planning and Management* 130 (2), 93-111.

732 Liu, P., Guo, S.L., Xu, X.W., Chen, J.H. 2011a. Derivation of aggregation-based joint
733 operating rule curves for cascade hydropower reservoirs. *Water Resources*
734 *Management* 25, 3177-3200.

735 Liu, P., Cai, X.M., Guo, S.L. 2011b. Deriving multiple near-optimal solutions to
736 deterministic reservoir operation problems. *Water Resources Research* 47,
737 W08506, doi:10.1029/2011WR010998.

738 Momtahan, S., Dariane, A.B. 2007. Direct search approaches using genetic algorithms
739 for optimization of water reservoir operating policies. *Journal of Water*
740 *Resources Planning and Management* 133 (3), 202-209.

741 Mousavi, H., Ramamurthy, A.S. 2000. Optimal design of multi-reservoir systems for
742 water supply. *Advances in Water Resources* 23, 613-624.

743 MWR-PRC (Ministry of Water Resources of PRC), 2008. *China Water Resources*
744 *Bulletin*. Beijing: China Water Resources and Hydropower Press, (in Chinese).

745 Nalbantis, I., Koutsoyiannis, D. 1997. A parametric rule for planning and management
746 of multiple-reservoir systems. *Water Resources Research* 33 (9), 2165-2177.

747 Nicklow, J., Reed, P.M., Savic, D., Dessalegne, T., Harrell, L., Chan-Hilton, A.,
748 Karamouz, M., Minsker, B., Ostfeld, A., Singh, A., Zechman, E. 2010. State of
749 the art for genetic algorithms and beyond in water resources planning and
750 management. *Journal of Water Resources Planning and Management* 136 (4),
751 412-432.

752 Oliveira, R., Loucks, D.P. 1997. Operating rules for multireservoir systems. *Water*
753 *Resources Research* 33 (4), 839-852.

754 Powell, W.B. 2007. *Approximate Dynamic Programming: Solving the Curses of*
755 *Dimensionality*. John Wiley & Sons, Inc., ISBN-13: 9780470171554.

756 Sadegh, M., Mahjouri, H., Kerachian, R. 2010. Optimal inter-basin water allocation
757 using crisp and fuzzy shapely games. *Water Resources Management* 24,
758 2291-2310.

759 Shiau, J.-T. 2011. Analytical optimal hedging with explicit incorporation of reservoir
760 release and carryover storage targets. *Water Resources Research* 47, W01515,
761 doi:10.1029/2010WR009166.

762 Shiau, J.-T., Lee, H.-C. 2005. Derivation of optimal hedging rules for a water-supply
763 reservoir through compromise programming. *Water Resources Management* 19
764 (2), 111-132.

765 Shih, J.S., ReVelle, C. 1995. *Water supply operations during drought: a discrete*
766 *hedging rule*. *European Journal of Operational Research* 82 (1), 163-175.

767 Shirangi, E., Kerachian, R., Bajestan, M.S. 2008. A simplified model for reservoir
768 operation considering the water quality issues: Application of the Young conflict
769 resolution theory. *Environmental Monitoring and Assessment* 146, 77-89.

770 Simonovic, S.P. 1992. *Reservoir systems analysis: closing gap between theory and*
771 *practice*. *Journal of Water Resources Planning and Management* 118 (3),
772 262-280.

773 Srinivasan, K., Philipose, M.C. 1998. Effect of hedging on over-year reservoir
774 performance. *Water Resources Management* 12, 95-120.

775 Suen, J.P., Eheart, J.W. 2006. Reservoir management to balance ecosystem and human

776 needs: Incorporating the paradigm of the ecological flow regime. *Water*
777 *Resources Research* 42, W03417, doi:10.1029/2005WR004314.

778 Tang, Y., Reed, P.M., van Werkhoven, K., Wagener, T. 2007a. Advancing the
779 identification and evaluation of distributed rainfall-runoff models using global
780 sensitivity analysis. *Water Resources Research* 43, W06415,
781 doi:10.1029/2006WR005813.

782 Tang, Y., Reed, P.M., Wagener, T. 2006. How effective and efficient are multiobjective
783 evolutionary algorithms at hydrologic model calibration? *Hydrology and Earth*
784 *System Sciences* 10, 289-307.

785 Tang, Y., Reed, P.M., Wagener, T., van Werkhoven, K. 2007b. Comparing sensitivity
786 analysis methods to advance lumped watershed model identification and
787 evaluation. *Hydrology and Earth System Sciences* 11, 793-817.

788 Teegavarapu, R.S.V., Simonovic, S.P. 2001. Optimal operation of water resource
789 systems: trade-offs between modeling and practical solutions. In: Mariño, M.A.,
790 Simonovic, S.P., editors. *Integrated water resources management 272 (IAHS*
791 *Publ), 257-263.*

792 Tejada-Guibert, J.A., Johnson, S.A., Stedinger, J.R. 1995. The value of hydrologic
793 information in stochastic dynamic programming models of a multireservoir
794 system. *Water Resources Research* 31, 2571-2579.

795 Tu, M.-Y., Hsu, N.-S., Tsai, F.T.-C., Yeh, W.W.-G. 2008. Optimization of hedging
796 rules for reservoir operations. *Journal of Water Resources Planning and*
797 *Management* 134 (1), 3-13.

798 Tu, M.-Y., Hsu, N.-S., Yeh, W.W.-G. 2003. Optimization of reservoir management and
799 operation with hedging rules. *Journal of Water Resources Planning and*
800 *Management* 129 (2), 86-97.

801 Veldhuizen, D.A.V., Lamont, G.B. 1998. Evolutionary Computation and Convergence
802 to a Pareto Front. In: John, R., Koza, editors. *Late Breaking Papers at the Genetic*
803 *Programming Conference*, 221-228.

804 Vrugt, J.A., Robinson, B.A. 2007. Improved evolutionary optimization from
805 genetically adaptive multimethod search. *Proceedings of the National Academy*
806 *of Sciences of the United States of America* 104, 708-711.

807 Wurbs, R.A. 1993. Reservoir-system simulation and optimization models. *Journal of*
808 *Water Resources Planning and Management* 119 (4), 455-472.

809 Xu, W., Zhang, C., Peng, Y., Fu, G.T., Zhou, H.C. 2014. A two stage Bayesian
810 stochastic optimisation model for cascaded hydropower systems considering
811 varying uncertainty of flow forecasts. *Water Resources Research* 50,
812 doi:10.1002/2013WR015181.

813 Yeh, W.W.-G. 1985. Reservoir management and operations models: a state-of-the-art
814 review. *Water Resources Research* 21 (12), 1797-1818.

815 Young, G.K. 1967. Finding, reservoir operating rules. *Journal of Hydraulic Division*
816 93 (HY6), 297-321.

817 Zhang, C., Chu, J.G., Fu, G.T. 2013a. Sobol's sensitivity analysis for a distributed
818 hydrological model of Yichun River Basin, China. *Journal of Hydrology* 480,
819 58-68.

820 Zhang, H.F., Zhou, J.Z., Fang, N., Zhang, R., Zhang, Y.C. 2013b. An efficient
821 multi-objective adaptive differential evolution with chaotic neuron network and
822 its application on long-term hydropower operation with considering ecological
823 environment problem. *Electrical Power and Energy Systems* 45 (1), 60-70.

824 Zhao, T.T.G., Zhao, J.S., Yang, D.W. 2014. Improved dynamic programming for
825 hydropower reservoir operation. *Journal of Water Resources Planning and*
826 *Management* 140 (3), 365-374.

827 Zitzler, E., Thiele, L. 1998. Multiobjective optimization using evolutionary
828 algorithms-a comparative case study. In: Eiben, A., Back, T., Schoenauer, M.,
829 Schwefel, H.-P., editors. *Parallel problem solving from nature (PPSN V)*. Lecture
830 notes in computer science. Berlin, Amsterdam, the Netherlands: Springer-Verlag,
831 292-301.

832 Zitzler, E., Thiele, L., Laumanns, M., Fonseca, C.M., Fonseca, V.G. 2003.
833 Performance assessment of multiobjective optimizers: An analysis and review.
834 *IEEE Transactions on Evolutionary Computation* 7 (2), 117-132.

835

836

837

Table 1 Reservoir characteristics and yearly average inflow (10^8 m^3)

Reservoir name	Minimum capacity	Utilizable capacity	Flood control capacity	Yearly average inflow
Dahuofang	1.34	14.30	10.00	15.70

838

839

840

Table 2 Characteristics of each reservoir in the inter-basin multi-reservoir system

Reservoir	Active storage (10^8 m³)		Role in water supply project
	Flood season	Non-flood season	
Dahuofang	10.00	14.30	Supplying water
Guanyinge	14.20	14.20	Supplying water and exporting water to Shenwo
Shenwo	2.14	5.43	Supplying water and importing water from Guanyinge

841

842

843

Table 3 Comparisons of water shortage indices among different solutions

Solutions	Water Shortage Index (-)	
	Industrial water demand	Agricultural water demand
(S0) Industry-favoring solution	0.000	3.550
(S1) Agriculture-favoring solution	0.020	1.380
(S2) Compromised solution	0.007	1.932

844

845

846

847 **List of Figure Captions**

848 **Fig. 1** Reservoir operational rule curves

849 **Fig. 2** Flowchart of the sensitivity-informed methodology

850 **Fig. 3** Layout of the inter-basin multi-reservoir system

851 **Fig. 4** First-order and total-order indices for the Dahuofang ROS problem regarding

852 (a) industrial shortage index and (b) agricultural shortage index. The x-axis labels

853 represent decision variables (water storage volumes on the industrial and agricultural

854 curves)

855 **Fig. 5** Performance metrics for the Dahuofang ROS problem - (a) Generational

856 Distance; (b) Additive Epsilon Indicator; (c) Hypervolume

857 **Fig. 6** Pareto fronts derived from pre-conditioned and standard full searches for the

858 Dahuofang ROS problem. (a) Sample Pareto fronts with different numbers of function

859 evaluations for one random seed trial. (b) The best and worst Pareto fronts of ten seed

860 trials.

861 **Fig. 7** Computational savings for two hypervolume values - (a) *hypervolume* =

862 0.80; (b) *hypervolume* = 0.85

863 **Fig. 8** Optimal rule curves for different solutions, (S0) Industry-favoring solution; (S1)

864 Agriculture-favoring solution; (S2) Compromised solution

865 **Fig. 9** First-order and total-order indices for the inter-basin multi-reservoir operation

866 problem regarding industrial shortage index and agricultural shortage index. The

867 x-axis labels represent decision variables (water storage volumes on the industrial,

868 agricultural and water transferring curves)

869 **Fig. 10** Performance metrics for the inter-basin multi-reservoir water supply operation
870 problem - (a) Generation Distance; (b) Additive Epsilon Indicator; (c) Hypervolume

871 **Fig. 11** Pareto fronts derived from pre-conditioned and standard full searches for the
872 inter-basin multi-reservoir operation problem. (a) Sample Pareto fronts with different
873 numbers of function evaluations for one random seed trial. (b) The best and worst
874 Pareto fronts of ten seed trials.