Hydrol. Earth Syst. Sci. Discuss., 7, 6757–6792, 2010 www.hydrol-earth-syst-sci-discuss.net/7/6757/2010/ doi:10.5194/hessd-7-6757-2010 © Author(s) 2010. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Reliability and robustness of rainfall compound distribution model based on weather pattern sub-sampling

F. Garavaglia¹, M. Lang², E. Paquet¹, J. Gailhard¹, R. Garçon¹, and B. Renard²

¹EDF – DTG, 21 Avenue de l'Europe, BP 41, 38040 Grenoble Cedex 9, France ²CEMAGREF, UR HHLY, Hydrology-Hydraulics, 3bis quai Chauveau, CP220, 69366 Lyon Cedex 09, France

Received: 30 July 2010 - Accepted: 24 August 2010 - Published: 7 September 2010

Correspondence to: F. Garavaglia (federico-externe.garavaglia@edf.fr)

Published by Copernicus Publications on behalf of the European Geosciences Union.





Abstract

Design floods for EDF (Électricité de France, French electricity company) dam spillways are now computed using a probabilistic method named SCHADEX (Climatic-Hydrological Simulation of Extreme Floods) based on an extreme rainfall model named

- the MEWP (Multi Exponential Weather Pattern) distribution. This probabilistic model provides estimates of extreme rainfall quantiles using a mixture of exponential distributions. Each exponential distribution applies to a specific sub-sample of rainfall observations, corresponding to one of eight typical atmospheric circulation patterns that are relevant for France and the surrounding area.
- The aim of this paper is to validate the MEWP model by assessing its reliability and robustness with rainfall data from France, Spain and Switzerland. Data include 37 long series for the period 1904–2003, and a regional data set of 478 rain gauges for the period 1954–2005. Two complementary properties are investigated: (i) the reliability of estimates, i.e. the agreement between the estimated probabilities of exceedance
- ¹⁵ and the actual exceedances observed on the dataset; (ii) the robustness of extreme quantiles and associated confidence intervals, assessed using various sub-samples of the long data series. New specific criteria are proposed to quantify reliability and robustness. The MEWP model is compared to standard models (seasonalised Generalised Extreme Value and Generalised Pareto distributions). In order to evaluate the suitability of the exponential model used for each weather pattern (WP), a general case
- of the MEWP distribution, using Generalized Pareto distributions for each WP, is also considered.

Concerning the considered dataset, the exponential hypothesis of asymptotic behaviour of each seasonal and weather pattern rainfall records, appears to be reason-²⁵ able. The results highlight: (i) the interest of WP sub-sampling that lead to significant improvement in reliability models performances; (ii) the low level of robustness of the models based on at-site estimation of shape parameter; (iii) the MEWP distribution proved to be robust and reliable, demonstrating the interest of the proposed approach.





1 Introduction

The distributions of hydrologic variables such as rainfall and streamflow play a key role in the design of water-related infrastructures (i.e. dam spillways or river dikes). The objective of hydrologic design is to quantify and mitigate the flood risk arising from

high rainfall and streamflow values. The methods used for the computation of flood risk for extreme floods can be devised into two families: the deterministic methods and the probabilistic methods. The deterministic models approach this issue from a physic point of view and they are based on the concept of Probable Maximum Flood (PMF). The PMF can be defined as the flood that may be expected from the most severe
 combination of critical meteorological and hydrologic conditions that are reasonably possible in a particular drainage area. On the other hand the probabilistic methods based on statistic models treat the problems in terms of probability (or equivalently in terms of return level) introducing the concept of flood distribution.

Historically in French context the probabilistic method are preferred to the determinis-

- tic ones. More precisely EDF design floods for dam spillway have been computed using the Gradex method since 1970 (Guillot and Duband, 1967; CFGB, 1994). This method is based on the assumptions that: (i) extreme rainfalls are realizations from an exponential distribution, and (ii) when the catchment is close to saturation, each increase of rainfall dP induces an equivalent increase of discharge dQ. This implies an asymptotic
- ²⁰ parallelism between rainfall and discharge cumulative distribution functions (cdf) plotted in Gumbel axes. The Gradex method therefore extrapolates the flood distribution beyond a return period T_g , using the scale parameter (called the gradex parameter) of the rainfall distribution. Assumptions (i) and (ii) may appear too restrictive, as the former underestimates the rainfall distribution with an excessive number of exceedances
- of 10-year rainfall quantiles (Garçon, 1995), and the latter overestimates the rate of the discharge cdf near the return period T_g (asymptotic parallelism considered to be effective from Tg). So far, EDF has a positive feedback: there is no significant indication of under-estimation of design flood on a dataset of 450 hydrologic designs. But there was





a need to assess both the rainfall and discharge hazards in more depth. This is one of the reasons that have promoted the development of the Schadex method (Paquet et al., 2006). This method uses a continuous simulation process for flood frequency estimation (see Boughton and Droop, 2003 for a review). The Schadex method therefore aims at estimating extreme flood quantiles by combining a rainfall probabilistic model

- aims at estimating extreme flood quantiles by combining a rainfall probabilistic model and a continuous conceptual rainfall-runoff model. In particular, the rainfall probabilistic model, named the MEWP (Multi-Exponential Weather Pattern) distribution, is a mixture of exponential distributions fitted on rainfall sub-samples based on a weather pattern classification (Garavaglia et al., 2010).
- ¹⁰ The aims of this paper are to validate the MEWP distribution and to compare it with standard probabilistic models stemming from extreme value theory. To this aim, specific criteria quantifying the models performance in terms of reliability and robustness are proposed. This assessment is based on a large dataset of daily rainfall series located in France, Switzerland and Spain. The paper is organized as follows: Sect. 2 summarizes
- the standard sampling techniques used in hydrological applications and details the probabilistic models used in this paper. The rainfall data set is presented in Sect. 3, and Sect. 4 describes the criteria used to evaluate the reliability and robustness of the different probabilistic models. Results of the comparison are presented in Sect. 5, before drawing some conclusions and discussing potential improvements in Sect. 6.

20 2 Sampling techniques and probabilistic models for extreme values

25

This section describes the standard sampling techniques used in extreme value analysis and two additional sampling techniques (seasonal and weather pattern subsampling) commonly used in hydrological applications. It also describes the probabilistic models, the method used to estimate model parameters, and the computation of confidence intervals.





2.1 Standard sampling techniques

5

Two standard sampling techniques are used to build samples of extreme values:

- Block Maximum (BM). The maximum values within blocks of equal length are selected. The choice of block size is important as too small blocks can lead to bias and too large blocks generate too few block maxima, thus yielding a large estimation variance (Coles, 2001). Usually a one-year block is used for daily discharges or rainfall data, yielding annual maxima (AM) series. Asymptotic considerations suggest that the distribution of AM can be approximated by a generalized extreme value (GEV) distribution (Coles et al., 2003).
- Peaks over threshold (POT). All events exceeding a given threshold are selected (see Lang et al., 1999; Rosbjerg and Madsen, 2004, for a review). According to Coles (2001), such a sample may be considered as independent realizations of a random variable whose distribution can asymptotically (i.e., for high thresholds) be approximated by a generalized Pareto (GP) distribution.
- ¹⁵ According to Coles et al. (2003), if daily series are available, POT sampling may be more efficient than AM sampling, because additional information on several large events occurring during the same year is taken into account.

2.2 Seasonal and weather patterns sampling techniques

Seasonal sampling is widely used in hydrological applications (Leonard et al., 2008)
 and overall considered as essential in precipitation analysis. This kind of stratification is often performed to produce more homogeneous sub-samples than the whole population (Lang et al., 1994; Djerboua and Lang, 2007). Several studies have shown that in the Mediterranean area of Europe (French, Spanish and Italian regions) extreme rainfall events are mainly end of summer and autumn (Zveryaev, 2004; Müller et al., 2009;
 Karagiannidis et al., 2009). Consequently, a "Season-at-Risk" period is defined as the





three consecutive months with highest monthly rainfall maxima. A seasonal analysis of the considered rainfall dataset will be presented in the following section.

A number of authors have shown (e.g. Bardossy et al., 1995; Trigo and DaCamara, 2000; Linderson, 2001) that within the same season, the rainfall hazard in a specific
⁵ area strongly depends on the atmospheric situation. The relationship between large-scale atmospheric circulation and precipitation events has been extensively studied (see Yarnal, 2001; Boé and Terray, 2008; Martinez et al., 2008). It has been demonstrated that the analysis of the synoptic situation can provide significant information on heavy rainfall events (Littmann, 2000). Consequently, the rainfall probabilistic model
¹⁰ of the SCHADEX method (Paquet et al., 2006) is based on this type of clustering. A specific Weather Pattern (WP) classification was developed (Garavaglia et al., 2010). It classifies each day into one of eight contrasted synoptic situations for France and

2.3 Probabilistic models

surrounding areas, without seasonal distinction.

¹⁵ Table 1 describes the six probabilistic models considered in this study. The MEWP distribution is a particular case of the Multi Generalized Pareto Weather Patterns (MG-PWP) distribution. Both probabilistic models are introduced by Garavaglia et al. (2010). Those mixture distributions will be compared to four standard models: the Gumbel (GUM) and the GEV distributions for AM samples, and the Exponential (EXP) and the ²⁰ GP distributions for POT samples.

The parameters of the six probabilistic models are estimated using the maximum likelihood method. The compound models (MEWP and MGPWP distributions) have more parameters than the standard probabilistic models. The MEWP and the MGPWP distributions have respectively 8 (one scale parameter for each WP) and 16 parameters

²⁵ (one scale and one shape parameter for each WP). One of the goals of the comparison carried out in this paper is to assess the potential over-parameterisation of these models. Note that the weights p_i (see Table 1), equal to the frequency of each WP within





a given season, should not be considered as parameters because they are directly computed from the daily time series of WP.

Confidence intervals are computed using the non-parametric bootstrap technique (Efron, 1979). Random sampling with replacement from the initial sample produces new Bootstrap samples with the same length as the initial sample. For all *B* bootstrap samples, the p-quantile q_p is computed with each probabilistic model, yielding a sample of *B* quantile estimates $(q_p^{(i)})_{i=1...B}$. The confidence interval at $(1 - \alpha)$ level is then equal to $[q_{p,\alpha/2}, q_{p,1-\alpha/2}]$, where $q_{p,\alpha/2}, q_{p,1-\alpha/2}$ are the empirical quantiles with frequency $\alpha/2$ and $1 - \alpha/2$ computed from $(q_p^{(i)})_{i=1...B}$.

3 Precipitation and their preprocessing

The validation of the rainfall mixture distribution model is based on an extensive dataset composed of two daily rainfall archives:

- Dense dataset: data from 1502 rain gauges belonging to EDF, the French meteorological office Météo-France, the Swiss meteorological office Météo-Swiss and the Spanish meteorological office Instituto Nacional de Meteorología (INM) for the period 1953–2005. These stations are located in the Alps, Pyrenees and Massif Central at an average altitude of 622 m.
- Long dataset: 308 long series from Météo-France covering the period 1904– 2003. These stations are mainly located in the plain at an average altitude of 305 m.

Both original datasets were first subject to a quality-check analysis, thus reducing the number of stations available for the model comparison. Only series with less than 10% of missing values per year were considered. Moreover, these series were further





15

20

analysed to detect several anomalies: time shifts due to sensor replacement or station relocation, step changes or trends in rainfall intensity series.

The step change anomalies were studied by testing the stability over time of the residual of a multiple linear regression linking observations of the studied rain gauge
with observations at the neighbouring rain gauges (Peterson and Easterling, 1994; Gottardi, 2009). Two statistics were combined in this test, based on the Alexandersson homogeneity test (Alexandersson, 1986) and of the sum of residuals with associated confidence intervals (Bois, 1976). Various tests are available for trend detection. In this study, we chose distribution-free tests because they do not require hypotheses
on the data distribution (Hamed, 2009). According to Lang et al. (2006), two tests are commonly used to detect trends in non auto-correlated data series with unknown

- are commonly used to detect trends in non auto-correlated data series with unknown distribution: the Mann-Kendall test (Mann, 1945; Kendall, 1975) and Spearman's rho test (Lehmann, 1975; Sneyers, 1990). The Mann-Kendall test was selected since it is as powerful as Spearman's rho test (Yue et al., 2002). 478 rain gauges from the dense
- ¹⁵ dataset and 37 rain gauges from the long dataset were selected (Table 2) using this pre-processing. For the long dataset, the most severe test has been the criterion on the percentage of missing value, whereas for the dense dataset the test for the trends detection led to discard a lot of stations. Figure 1a shows the location of the selected stations from the two datasets.

²⁰ For these datasets, the highest rainfalls occur at the end of the summer and during the autumn (from August to November). The "Season at-risk" (Sect. 2.2) is computed for each rain gauge accordingly. The whole dataset (Long and Dense datasets) is divided into two datasets depending on the "Season at-risk": the regional dataset A ("Season at-risk" from August to October) and the regional dataset B ("Season at-

risk" from September to November). Such a regional subdivision reveals a coherent spatial pattern, as shown in Fig. 1b. Figure 2a and c show the box plots of monthly rainfall maxima of regional datasets A and B. As expected, the highest quantiles are reached between August and October (regional dataset A) or between September and November (regional dataset B). Figure 2b and d show that the two regional data sets





cover a large variability of rainfall intensities, from 40 to 170 mm (resp. 40 to 290 mm) for the empirical daily 10-year rainfall for dataset A (resp. B) and from 50 to 220 mm (resp. 70 to 520 mm) for the empirical daily 50-year rainfall for the dataset A (resp. B).

4 Comparison of probabilistic models

- ⁵ This section describes the strategy used to compare the probabilistic models, and defines several criteria to quantify the reliability and robustness of each model. Several statistical tests are reported in the literature to measure the goodness of fit: Pearson's chi-square test (Plackett, 1983), Kolmogorov-Smirnov test (Kolmogorov, 1941; Smirnov, 1944), Anderson-Darling Test (Anderson and Darling, 1952), Cramer-von ¹⁰ Mises criterion (Cramer, 1928; Darling, 1957), Shapiro-Wilk test (Shapiro and Wilk, 1965) and test of Lilliefors (Lilliefors, 1967). These standard tests are not perfectly suited for extreme value distributions, mainly because they are not enough sensitive to deviations in the tails of the distribution. In order to take into account these limitations, several transformations of standard tests have been proposed (e.g. Khamis, 1997;
 ¹⁵ Liao and Shimokawa, 1999; Laio, 2004). Applications of the Akaike information cri-
- terion (AIC) (Akaike, 1974) and on the Bayesian information criterion (BIC) (Schwarz, 1978) are also often found in the literature (e.g. Nacházel, 1993; Di Baldassarre et al., 2009; Laio et al., 2009). In contrast with the list of standard tests given above, the AIC and BIC criteria introduce a penalty term for the number of parameters. Laio
- et al. (2009) evaluated their capability to identify the correct parent distribution from the available data and showed that these criteria perform well if the parent distribution is a two-parameter distribution. In contrast, they are less efficient in the case of three-parameters distribution.

This paper does not solely focus on goodness of fit, and instead attempts to evalu-²⁵ ate the predictive performance of a model using independent validation data (i.e. not used to calibrate the model). Moreover, focus is on the tail of the distribution, i.e. the performance of the model in estimating the exceedance probability of large values. It





is argued that the evaluation of goodness-of-fit is not sufficient to assess the ability of a model to predict the exceedance probability of future (unobserved) values. Consequently, we propose an alternative approach based on specific criteria computed on an extensive dataset.

- ⁵ A probabilistic model of extreme rainfall should be both reliable and robust. A reliable model assigns the "correct" exceedance probability to high values. In practice, this property can only be evaluated with respect to observed data. Consequently, it is useful to consider both long series and dense data sets in order to increase the sample of observed extreme values. On the other hand, a robust probabilistic model yields 10 similar estimates when a slight perturbation of data is introduced. This property is
- very important, especially in the extrapolation of extreme quantiles, in order to avoid an estimate being overly sensitive to sampling variability. Robustness is easier to quantify than reliability but an analysis solely based on the former is not sufficient because robustness does not give any information about the ability of the model to describe
- or predict observations. In the absence of reliability diagnostics, a robust model is not necessarily preferable: a model can be robust but totally unreliable. In conclusion these properties are complementary: the reliability of the model should be evaluated first, and in a second step, the most robust model (amongst reliable ones) should be preferred. Specific criteria quantifying reliability and robustness are proposed in the following sections.

4.1 Reliability criteria

25

As mentioned above, measuring the reliability of probabilistic estimations of high quantiles is not an easy task. We take cues from methods developed in the context of skill assessment of probabilistic forecasts, in particular, the reliability diagram (also called attribute diagram) (Wilks, 1995). This tool is used to assess the consistency of a probabilistic forecast of binary events. It plots the observed frequency against the forecast probability in order to evaluate their agreement. This diagram is widely





used in forecasts analysis and comparisons (e.g. see Bartholmes et al., 2009, for an application).

Similarly, we propose a specific procedure to evaluate the agreement between the exceedance probabilities of extreme events provided by a probabilistic model and their observed frequencies. This tool, named *FF* criterion, is based on a split-sample procedure and was introduced by Garçon (1995). Let *D* be a regional data set of *L* stations of length *N*, D^i is the time series at site *i*. The computation of the *FF* criterion can be divided into the following steps:

1. Each D^i is split into two successive sub-samples of equal length N/2: $\begin{pmatrix} x_1^i, \dots, x_{N/2}^i \end{pmatrix}$ and $\begin{pmatrix} x_{N/2+1}^i, \dots, x_N^i \end{pmatrix}$.

10

15

- 2. Two cdf $F_1^i(x)$ and $F_2^i(x)$ of the same probabilistic model are fitted using each sub-sample.
- 3. Let $m_1^i = \max\{x_1^i, ..., x_{N/2}^i\}$ and $m_2^i = \max\{x_{N/2+1}^i, ..., x_N^i\}$. Under the hypothesis of i.i.d. random variables the probability of non-exceedance of m_1^i (resp. m_2^i) is computed with the cdf fitted to the second part $F_2^i(x)$ (resp. the first part $F_1^i(x)$) as follows:

$$FF_{1}^{i} = Pr\left(M_{i} \le m_{1}^{i}\right) = \left[F_{2}^{i}\left(m_{1}^{i}\right)\right]^{N/2}$$
(1a)

$$FF_{2}^{i} = Pr\left(M_{i} \le m_{2}^{i}\right) = \left[F_{1}^{i}\left(m_{2}^{i}\right)\right]^{N/2}$$
(1b)

2L values of probabilities *FF* are therefore computed. With a perfect probabilistic model, the distribution of *FF* values should be a Kumaraswamy's double bounded distribution of parameters *N* and 1; i.e. *K*[*N*,1] (Kumaraswamy, 1980); see appendix A. A pp-plot is used to check this feature: the closer the *FF* distribution to the 1:1 diagonal, the more reliable the probabilistic model.



In practice, the theoretical distributions $F'_1(x)$ and $F'_2(x)$ are replaced by their estimates based on samples of limited size, thus leading to departures from the 1:1 line. To quantify this, *FF* is calculated on 1000 random datasets of three different sample sizes, generated from an exponential population. The size of the first sample is similar

to that of the actual rainfall dataset (L = 552, N = 50), the second is smaller (L = 552, N = 10) and the third is bigger (L = 552, N = 1000). Figure 3 shows the median of the simulated *FF* distributions for each dataset size. It appears that logically, the *FF* distribution plot moves closer to the 1:1 diagonal (theoretical result) when the sample size increases. Because of the bias introduced by the limited sample size, the analysis of the reliability test is mainly qualitative and provides a way to compare concurrent probabilistic models.

The *FF* procedure is used to assess the ability of a probabilistic model to assign the "correct" probability to the highest observed values that were not used for model fitting. With analogy with the split sample test, this kind of procedure can be named *FF* validation procedure. Note that the *FF* procedure solely focuses on the maximum observed value during the validation period: it is therefore primarily geared toward the assessment of reliability in the tail of the distribution.

A modification of the *FF* validation procedure can be introduced in order to assess reliability based on the calibration sub-sample. Instead of computing the non-exceedance probability of the maximum of the first sub-sample with the cdf estimated on the second sub-sample, the cdf fitted on the same sub-sample can be used:

20

$$\left(FF_{1}^{i}\right)^{*} = Pr\left(M_{i} \le m_{1}^{i}\right) = \left[F_{1}^{i}\left(m_{1}^{i}\right)\right]^{N/2}$$

$$\left(FF_{2}^{i}\right)^{*} = Pr\left(M_{i} \le m_{2}^{i}\right) = \left[F_{2}^{i}\left(m_{2}^{i}\right)\right]^{N/2}$$
(2a)
(2b)

This approach can be interesting in cases where the observed distribution of FF^* values is less variable than the theoretical K[N, 1] distribution. Indeed, the latter distribution corresponds to what should be observed using the true distribution of data:





it corresponds to a lower bound for the variability of FF^* values, solely resulting from sampling variability. Consequently, a probabilistic model yielding FF^* values less variable than the theoretical K[N,1] distribution tends to "over-fit" extreme values, which is typical of over-parameterized models. With analogy to the *FF* validation procedure, this second approach can be named the *FF* calibration procedure.

In order to improve the comparison a robustness assessment is presented into the following paragraph.

4.2 Robustness criteria

20

25

The robustness is the ability of a method to yield close estimations when two different calibration periods are utilised. Robustness is quantified using several sub-samples of the whole long data series, in order to increase the reliability of the assessment. To analyse the results and compare the models, two scores are computed: the $SPAN_T$ criterion and the $COVER_T$ criterion.

The $SPAN_T$ criterion aims to evaluate the variability of extreme quantile estimation. This criterion can be defined as follows:

$$SPAN_{T} = \frac{\max\{\hat{q}_{T,n=1,...,m}\} - \min\{\hat{q}_{T,n=1,...,m}\}}{\frac{1}{m}\sum_{n=1}^{m}\hat{q}_{T,n}}$$
(3)

where $\hat{q}_{T,n}$ is the model estimate for the return period *T* and the sub-period *n* amongst *m* non-overlapping sub-periods. The value of this score is greater or equal to 0, zero being the ideal score, occurring for a probabilistic model that is completely unaffected by the sub-period used for calibration.

Moreover, it is reasonable to assert that a probabilistic model is more robust if the confidence intervals calculated for different sub-periods overlap well. Note that we are interested here in confidence interval overlap and not in their width. Indeed, for a given model and return period, two confidence intervals (computed from two different sub-samples) could be narrow but totally disconnected. Such behavior is not in line with the





robustness requirement. To quantify this property, a second criterion, named $COVER_T$ is derived. The analytical expression of this score is as follows:

$$COVER_{T} = \frac{\prod_{n=1}^{m} Pr\left(\max\left\{\hat{q}_{T,\alpha/2,n=1,...,m}\right\} \le \hat{q}_{T,n} \le \min\left\{\hat{q}_{T,1-\alpha/2,n=1,...,m}\right\}\right)}{(1-\alpha)^{m}}$$
$$= \frac{\prod_{n=1}^{m} Pr\left(a \le \hat{q}_{T,n} \le b\right)}{(1-\alpha)^{m}}$$

⁵ where $\hat{q}_{T,\alpha,n}$ is the model estimate for the return level *T* with a confidence level α and computed on the sub-period *n* (amongst *m* non overlapping sub-periods).

This score therefore provides a quantitative value of the confidence interval overlap for each sub-period. The graphical explanation of the $COVER_{T}$ criterion is shown in Fig. 4 for two sub-periods. This figure highlights that the optimum of the criterion is 1 (confidence intervals are identical), and the minimum value is 0 (confidence intervals are disconnected).

4.3 Comparaison methodology

10

In this paragraph the comparison methodology (in terms of reliability and robustness) is detailed. The datasets are divided into 25-years sub-periods: two sub-periods of 25 years for the dense dataset and four sub-periods of 25 years for the long dataset. The division diagram is shown in Fig. 5. According to the same division scheme (Fig. 5) the *FF* validation and calibration procedures are computed using the different probabilistic models. In regards to the long dataset we have considered the couples 1st–2nd period (1904–1928 and 1929–1953) and 3th–4th period (1954–1978 and 1979–2003). Fur-

thermore in order to quantify the robustness, the probabilistic models were calibrated on all sub-periods (N = 25 years; L = 478 + 2.37 = 552 stations). SPAN_T and COVER_T criteria are computed for each station and for different return levels.



(4)



Alternative division schemes, yielding sub-periods with different length and/or random sub-periods (i.e. containing non-consecutive years) were also tested in order to check that the results were not influenced by climatic effects or by the relative length of calibration/validation periods. The division scheme presented in Fig. 5 and these alternative division schemes led to similar results, so a for practical reason the latter results are not presented.

5 Results

10

This section presents the results of the model comparison. The GUM (resp. GEV) distribution performs identically to the EXP distribution (resp. GP) so the scores of GUM and GEV distributions appear only in the tables and not in the figures of this section.

5.1 Reliability

Starting with the reliability criteria, the *FF* calibration and validation criteria are calculated for the six models using the whole dataset. The results of these tests are
presented through the pp-plot between the empirical and theoretical frequencies of the *FF* values (Fig. 6). According to these results the MGPWP performs as well as MEWP distribution in validation but is the worst model in calibration. In particular, the shape of the MGPWP pp-plot in calibration suggests that the observed *FF* values are less variable than theoretically expected. As indicated in Sect. 4.1, this is typical of
over-parameterised models. Fitting the shape parameter on each WP sub-sample, the MGPWP distribution tends to over-fit extreme values. However, and perhaps surprisingly, this does not result in a loss of predictive performance in validation. Overall, and based on both criteria (*FF* calibration and validation criteria) the MEWP distribution is the most reliable model given that its distribution is the closest to the 1:1 diagonal.

²⁵ Compared to MEWP and MGPWP distributions, the EXP and GP distributions have a





distinctly lower predictive performance in validation (Fig. 6, right panel): this highlights the value of weather-pattern sub-sampling in estimating extreme quantiles. Moreover, the EXP distribution performs better than the GP distribution, which may appear surprising. Nevertheless this result is due to high variability of estimated shape parameter

- ⁵ ξ for the GP distribution. This parameter is sometimes negative, corresponding to an upper-bounded distribution. In such case, the *FF* validation criterion is equal to 1 if the maximum observed value in the validation period is greater than the upper bound (corresponding to an "impossible" observation according to the model). In the whole dataset and in all sub-periods (1104 stations \cdot periods) 632 negative shape parameter
- ¹⁰ were estimated (~ 57%), yielding ~ 9% of *FF* values equal to 1. These results highlight the limits of fitting the shape parameter using a few years of at-site data. On the contrary in the case of MGPWP distribution only 43 (~ 4%) negative shape parameter were estimated for the WP at-risk (i.e. the WP associated to the highest scale parameter), yielding less then ~ 1% of *FF* values equal to one. These results show the interest of fitting the shape parameter on WP sample and not on the global population. This will be further discussed in Sect. 6.

Particular attention has to be paid to the highest frequency in the presented pp-plot. In this regard, the *FF* validation procedure may be expressed for high quantiles as follows. For example, with the EXP distribution the empirical frequency of the 0.95 quantile of FF_{EXP} is 0.86 (Fig. 7). This means that a value supposed to occur one time out of 20, according to the EXP distribution ($FF_{\text{EXP}} = 0.95$), has been observed about one time out of 7 (empirical frequency of 0.86). This kind of analysis has been done for each model (including the simulation using an exponential distribution presented in Sect. 4.1) and for different frequencies (0.9, 0.95 and 0.99). Table 3 illustrates the results of this analysis. It shows that the MEWP and MGPWP distributions are less biased than the other distributions, with observed values (resp. 7, 11 and 34 for the MEWP distribution and 8, 15, 32 for the MGPWP distribution) closer to both the theoretical values (resp. 10, 20 and 100) and the simulated values (resp. 7, 11 and 38) including the sampling effect (Fig. 3).





5.2 Robustness

Figure 8 shows the empirical distributions of the two robustness criteria (*SPAN*₇ and *COVER*₇) computed at the 20-years, 100-years and 1000-years return levels. The GP and the MGPWP distributions are the most sensitive to sampling variability, as the

SPAN₁₀₀ and SPAN₁₀₀₀ scores are markedly larger than with the other distributions. The SPAN₂₀ remains almost similar for all the considered models (being MEWP the best one and MGPWP the worst one). Also in this case such a low level of robustness in these two models is due to high variations of the shape parameter *ξ* in different subperiods. Furthermore the MGPWP distribution drifts further away from the ideal SPAN₇ than GP distributions, especially for 1000-years return level. The other probabilistic

models (EXP and MEWP distributions) yield similar and better $SPAN_{100}$ and $SPAN_{1000}$ scores.

In order to complete the robustness comparison, it is important to pay attention to the confidence interval overlap. The MEWP and the MGPWP distribution have the empirical distribution of the *COVER*₂₀ score closest to the ideal score. Instead in the case of the empirical distribution of the *COVER*₁₀₀ and *COVER*₁₀₀₀ scores, the MGPWP distribution performs better than the other ones. The good performance of

MGPWP distribution in terms of $COVER_T$ criterion is a consequence of the width of its confidence intervals. Indeed, as the confidence intervals are wide, the probability to observe a good confidence interval overlap is higher. On the whole dataset, the MG-

- ²⁰ observe a good confidence interval overlap is higher. On the whole dataset, the MG-PWP distribution at 100-years return level has in average an interval confidence width equal to ± 0.76 of the central estimation. The EXP, GP and MEWP distributions have respectively interval confidence width equal to ± 0.17 , ± 0.52 and ± 0.22 of the central estimation. The MEWP distribution yields satisfactory scores however its confidence
- ²⁵ interval size is appreciably moderate. The EXP and GP distributions are slightly less robust than the two distributions based on WP sub-sampling. In term of non-overlapping confidence intervals ($COVER_T$ score equal to 0), these two models have for about 10% of the rain gauges the confidence intervals, computed on two different periods, totally disconnected.





A global robustness assessment may be summarized for the proposed criteria. Table 4 shows the mean $SPAN_T$ and $COVER_T$ criteria at the 10-years, 20-years, 50-years, 100-years and 1000-years return levels for the six probabilistic models considered. According to the results shown in Fig. 8 and in Table 4, the MEWP distribution provides a good level of robustness, from moderate to high return levels, either for the variability of extreme quantile estimation ($SPAN_T$ criterion) or for confidence interval overlap ($COVER_T$ criteria).

6 Discussion and conclusions

5

The aim of this paper was to assess a probabilistic model based on atmospheric circulation pattern by comparing it with standard probabilistic models derived from extreme value theory using an extensive data set. A specific method for the comparison of probabilistic models was introduced. Firstly, the reliability of the model to estimate extreme rainfall quantiles was investigated. Secondly, the comparison examined the robustness of the extreme quantiles and their associated Bootstrap confidence intervals, based on

various sub-samples of long data series (about 100 years). The use of long data series made it possible to compare the probabilistic models on extreme values. Seasonal variability of precipitation in France and in the surrounding area was taken into account.

Some interesting conclusions can be drawn. The results of the comparison clearly highlight the interest of a WP sub-sampling. In particularly the probabilistic models

based on WP approach provide good predictive performance in validation (*FF* validation criterion). This conclusion means to suggest that the number of parameter, *a priori* a negative feature, does not affect the statistical qualities of the proposed probabilistic models based on WP.

For the GP and MGPWP distributions, the presented results shows that the shape parameter estimation leads to a drop in robustness, overall for high (100-years and 1000-years) return levels. Therefore in operational application a regional analysis is recommended for robust estimation of shape parameter (Madsen et al., 1995; Ribatet et al., 2007; Pujol et al., 2008).





The purpose of this paper was to assess the MEWP probabilistic model and not to decry the GEV and GPD approach, as already said their observed low level of robustness is linked to the local estimation of the model parameters (especially the shape parameter ξ). Results for the MGPWP distribution are very contrasted. On the one

⁵ hand a good level of *FF* validation and $COVER_{T}$ criteria are observed, but on other hand this model presents a very low level of *FF* calibration and $SPAN_{T}$ criteria. This aspect strongly reduces its applicability in operational application for reasons of coherence and repeatability. However we plan to carry out a future investigation on the use of a GP distribution for the most severe WP, with a regional assessment of the shape parameter.

In conclusion the MEWP distribution presents a good level of reliability and robustness with respect to the proposed criteria.

In the proposed comparison technique the spatial dependence between samples maxima was not taken into account. The spatial dependence could influence the re-¹⁵ sults of the *FF* procedure, with a similar effect than the sampling effect presented in Fig. 3. However, the spatial dependence should not change the global results for a comparison purpose since all models are applied to the same data, affected by the same spatial dependence. Also we plan to carry out a future investigation on spatial distribution of computed scores and on correlation analyses between model perfor-

- ²⁰ mance and climatological features. The question of assessing the reliability (in addition to the robustness) of estimated uncertainties is also of interest. In our study the maximum likelihood method was used to fit models parameters. The uncertainties were not taken into account in the estimation of models parameters and so it could be potentially interesting to check if taking into account uncertainties (i.e. use a predictive
- ²⁵ distribution as models estimation, see Gelman et al., 1995) could improve reliability and robustness of models. Such developments are currently investigated within the French National research project named ExtraFlo 2009–2012 (EXTreme RAinfall and FLOod estimation: design values for extreme rainfall and floods. https://extraflo.cemagref.fr).





Appendix A

Reliability criterion FF

Let:

5

- D a regional dataset of M stations;
 - D^i the time series at site *i*;
 - N^i the length of the D^i time series;
 - m^i the observed maximum of D^i ;
 - \hat{F}^i the probabilistic model fitted on D^i .
- The *FF* score at site *i* can be defined as follow: $FF^{i} = \hat{F}^{i}(m^{i})$ If the estimation is perfectly reliable ($\hat{F}^{i} = F^{i}$), then $FF^{i} \sim K[N^{i}, 1]$ (Kumaraswamy's dou-10 ble bounded distribution, Kumaraswamy, 1980), i.e. its cdf is $Pr(FF^{i} \leq t) = t^{N'}$ where 0 < *t* < 1. Proof:

$$Pr(FF^{i} \le t) = Pr(\hat{F}^{i}(m^{i}) \le t).$$
If $\hat{F}^{i} = F^{i}$:
$$Pr(FF^{i} \le t) = Pr(m^{i} \le \{F^{i}\}^{-1}(t))$$

$$= Pr(D_{k}^{i} \le \{F^{i}\}^{-1}(t)\forall k = 1, ..., N^{i})$$

$$= \left[F(\{F^{i}\}^{-1}(t))\right]^{N^{i}}$$

$$= t^{N^{i}}$$

20

1

Acknowledgements. The authors gratefully acknowledge Météo-France, Météo-Swiss and In stituto Nacional de Meteorologa for the daily data sets.

	Discussion Pap	_	HESSD 7, 6757–6792, 2010				
	er Discussion	I	Reliability and robustness of rainfall compound distribution model F. Garavaglia et al.				
1-	Paper	-	Title Page				
е	—		Abstract	Introduction			
	Discussion		Conclusions Tables	References Figures			
	ר Pape		14	►I			
	<u>e</u> r		•	•			
	D		Back	Close			
	iscus		Full Screen / Esc				
	sion Pa		Printer-frier	ndly Version			
۱-	aper		Interactive	Discussion			



References

Akaike, H.: A new look at the statistical model identification, IEEE T. Automat. Contr., 19, 6, 716-723, 1974. 6765

Alexandersson, H.: A homogeneity test applied to precipitation data, J. Climatol., 6, 661–675, 1986. 6764

- Anderson, T. W. and Darling, D. A.: Asymptotic theory of certain goodness-of-fit criteria based on stochastic processes, Ann. Math. Stat., 23, 193-212, 1952. 6765
- Bardossy, A., Duckstein, L., and Bogardi, I.: Fuzzy rule-based classification of atmospheric circulation patterns, Int. J. Climatol., 15, 1087–1097, 1995. 6762
- Bartholmes, J. C., Thielen, J., Ramos, M. H., and Gentilini, S.: The european flood alert system EFAS Part 2: Statistical skill assessment of probabilistic and deterministic operational forecasts, Hydrol. Earth Syst. Sci., 13, 141-153, doi:10.5194/hess-13-141-2009, 2009. 6767 Boé, J. and Terray, L.: A weather type approach to analysing winter precipitation in France: twentieth century trends and influence of anthropogenic forcing, J. Clim., 21, 3118-3133, 2008. 6762

15

25

5

Bois, P.: Contrôle de séries chronologiques corrélées par étude du cumul des résidus de la corrélation. Il Journées Hydrologiques de l'ORSTOM, 89-100, 1976. 6764

Boughton, W. and Droop, O.: Continuous simulation for design flood estimation-a review, Environ. Modell. Softw., 18, 309-318, 2003. 6760

CFGB: Design flood determination by the gradex method. 18th congress CIGB-ICOLD n2, nov., Bulletin du Comité Francais des Grands Barrages-FRCOLD News, 96 pp., 1994. 6759 Coles, S.: An introduction to statistical modeling of extreme values. Springer, 45-90, London, 2001.6761

Coles, S., Perricchi, L., and Sisson, S.: A fully probabilistic approach to extreme rainfall modelling, J. Hydrol., 273, 35-50, 2003. 6761

Cramer, H.: On the composition of elementary errors, Skand. Aktuarietids, 11, 13-74 and 141-180, 1928, 6765

Darling, D. A.: The Kolmogorov-Smirnov, Cramer-von Mises Tests, Ann. Math. Stat., 28, 823-838, 1957, 6765

- Di Baldassarre, G., Laio, F., and Montanari, A.: Design flood estimation using model selection 30 criteria, Phys. Chem. Earth, 34, 606-611, 2009. 6765
 - Dierboua, A. and Lang, M.: Scale parameter of maximal rainfall distribution: comparison of three sampling techniques, Revue des Sciences de l'Eau, 20, 111-125, 2007. 6761





- Efron, B.: Bootstrap methods: Another look at the jackknife, Ann. Stat., 7, 1–26, 1979. 6763 Garavaglia, F., Gailhard, J., Paquet, E., Lang, M., Garçon, R., and Bernardara, P.: Introducing a rainfall compound distribution model based on weather patterns sub-sampling, Hydrol. Earth Syst. Sci., 14, 951–964, doi:10.5194/hess-14-951-2010, 2010. 6760, 6762
- Garçon, R.: Oral communication. Statistical and Bayesian Methods in Hydrological Sciences. A joint UNESCO International Conference in honor of Jacques Bernier, September 11–13, Paris, 1995. 6759, 6767
 - Gelman, A., Carlin, J. B., Stern, H. S., and Rubin, D. B.: Bayesian data analysis, Chapmann & Hall, London, 526 pp., 1995. 6775
- ¹⁰ Gottardi, F.: Estimation statistique et réanalyse des précipitations en montagne, PhD thesis, Polytechnic Institute of Grenoble, 252, Grenoble, 2009. 6764
 - Guillot P. and Duband D.: La méthode du gradex pour le calcul de la probabilité des crues à partir des pluie, AISH Red Book, 84, 560, 1967. 6759

Hamed, K.: Exact distribution of the Mann-Kendall trend test statistic for persistent data, J.

¹⁵ Hydrol., 365, 86–94, 2009. 6764

25

Karagiannidis, A., Karacostas, T., Maheras, P., and Makrogiannis, T.: Trends and seasonality of extreme precipitation characteristics related to mid-latitude cyclones in Europe, Adv. Geosci., 20, 39–43, doi:10.5194/adgeo-20-39-2009, 2009. 6761

Kendall, M. G.: Rank correction methods, Griffin, London, 202 pp., 1975. 6764

- ²⁰ Khamis, H. J.: The delta-corrected Kolmogorov-Smirnov test for the two-parameter Weibull distribution, J. Appl. Stat., 24, 301–301, 1997. 6765
 - Kolmogorov, A. N.: Confidence limits for an unknown distribution function, Ann. Math. Stat., 12, 461–463, 1941. 6765
 - Kumaraswamy, P.: A generalized probability density function for double-bounded random processes, J. Hydrol., 46, 79–88, 1980. 6767, 6776
 - Laio, F.: Cramer-von Mises and Anderson-Darling goodness of fit tests for extreme value distribution with unknown parameters, Water Resour. Res., 40, W09308, doi:10.1029/2004WR003204, 2004. 6765

Laio F., Di Baldassarre, G., and Montanari, A.: Model selection techniques for the frequency

- ³⁰ analysis of hydrological extremes. Water Resour. Res., 45, W07416, ISSN:0043-1397, doi:10.1029/2007WR00666, 2009. 6765
 - Lang, M. and Desurosne, I.: Esquisse des risques de crues a l'échelle euro-méditerranéenne: les premiers résultats du programme FRIEND-AHMY exploitant les modèles AGREGEE et





TPG, 23emes Journées de l'hydrauliques, Congrès SHF Crues et Inondations, Nimes, 14–15–16 September, 1994. 6761

- Lang, M., Ouarda, T. B. M. J., and Bobée, B.: Towards operational guidelines for over-threshold modeling, J. Hydrol., 225, 103–117, 1999. 6761
- ⁵ Lang M., Renard, B., Sauquet, E., Bois, P., Dupeyrat, A., Laurent, C., Mestre, O., Niel, H., Neppel, L., and Gailhard, J.: A national study on trends and variations of French floods and droughts, IAHS Publication, 308, 514–519, 2006. 6764
 - Lehmann, E. L.: Nonparametrics, Statistical Methods Based on Racks. Holden-Day, Inc, California, 480 pp., 1975. 6764
- Leonard, M., Metcalfe, A., and Lambert, M.: Frequency analysis of rainfall and streamflow extremes accounting for seasonal and climatic partitions, J. Hydrol., 348, 135–147, 2008. 6761

Liao, M. and Shimokawa, T.: A new goodness-of-fit test for type-I extreme-value and 2parameter Weibull distributions with estimated parameters, J. Stat. Comput. Sim., 64, 23–48, 1999. 6765

15

- Lilliefors, H.: On the Kolmogorov-Smirnov test for normality with mean and variance unknown, J. Am. Stat. Assoc., 62, 399–402, 1967. 6765
- Linderson, M.: Objective classification of atmospheric circulation over southern Scandinavia, Int. J. Climatol., 21, 155–169, 2001. 6762
- Littmann, T.: An empirical classification of weather types in the Mediterranean Bassin and their interrelation with rainfall, Theor. Appl. Climatol., 66, 161–171, 2000. 6762
 - Madsen, H., Rosbjerg, D., and Harremoës, P.: Application of the Bayesian approach in regional analysis of extreme rainfalls, Stoch. Env. Res. Risk A., 9, 77–88, 1995. 6774

Mann, H. B.: Nonparametric tests against trend, Econometrica, 13, 245–259, 1945. 6764

- ²⁵ Martinez, C., Campins, J., Jansà, A., and Genovés, A.: Heavy rain events in the Western Mediterranean: an atmospheric pattern classification, Adv. Sci. Res., 2, 61–64, 2008. 6762
 - Müller, M., Kašpar, M., and Matschullat, J.: Heavy rains and extreme rainfall-runoff events in Central Europe from 1951 to 2002, Nat. Hazards Earth Syst. Sci., 9, 441–450, doi:10.5194/nhess-9-441-2009, 2009. 6761
- ³⁰ Nacházel, K.: Estimation Theory in Hydrology and Water Systems (Developments in Water Science), Elsevier Science, 270 pp., 1993. 6765
 - Paquet, E., Gailhard, J., and Garçon, R.: Evolution de la méthode du GRADEX: approche par type de temps et modélisation hydrologique, La Houille Blanche, 5, 80–90, 2006. 6760, 6762





Title Page Introduction Abstract Conclusions References **Tables Figures** 14 Back Close Full Screen / Esc **Printer-friendly Version** Interactive Discussion

HESSD

7,6757-6792,2010

Reliability and

robustness of rainfall

compound

distribution model

F. Garavaglia et al.

Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper

- Peterson, T. and Easterling, D. R.: Creation of homogeneous composite climatological reference series, Int. J. Climatol., 14, 671–679, 1994. 6764
- ⁵ Pujol, N., Neppel, L., and Sabatier, R.: Regional tests for trend detection in maximum precipitation series in the French Mediterranean region, Hydrol. Sci. J., 52, 956–973, 2008. 6774 Ribatet, M., Sauquet, E., Gresillon, J., and Ouarda, T. B. M. J.: Usefulness of the Reversible Jump Markov Chain Monte Carlo Model in Regional Flood Frequency Analysis. Water Resour. Res., 43, W08403, doi:10.1029/2006WR005525, 2007. 6774
- Rosbjerg, D. and Madsen, H.: Advanced approaches in PDS/POT modelling of extreme hydrological events in Hydrology: Science & Practice for the 21th Century, British Hydrological Society, London, 217–221, 2004. 6761
 - Schwarz, G.: Estimating the dimension of a model, Ann. Stat., 6, 461–464, doi:10.1214/aos/1176344136, 1978. 6765
- ¹⁵ Shapiro, S. and Wilk, M. B.: An analysis of variance test for normality (complete samples), Biometrika, 52, 3 and 4, 591–611, 1965. 6765
 - Smirnov, N. V.: Approximate laws of distribution of random variables from empirical data, Uspehi Matem. Nauk., 10, 179–206, 1944. 6765

Sneyers, R.: On the statistical analysis of series of observations. World Meteorological Organ-

- ²⁰ isation. Technical note 143, WMO 415, 1990. 6764
 - Trigo, R. M. and DaCamara, C. C.: Circulation weather types and their influence on the precipitation regime in Portugal, Int. J. Climatol., 20, 1559–1581, 2000. 6762
 - Wilks, D. S.: Statistical Methods in the Atmospheric Sciences: An Introduction, Academic Press, 467 pp., 1995. 6766
- ²⁵ Yarnal, B., Comrie, A. C., Frakes, B., and Brown, D. P.: Developments and prospects in synoptic climatology, Int. J. Climatol., 21, 1923–1950, 2001. 6762
- Yue, S., Pilon, P., and Cavadias, G.: Power of the Mann-Kendall and Spearman's rho tests for detecting monotonic trends in hydrological series, J. Hydrol., 259, 254–271, 2002. 6764
 Zveryaev, I.: Seasonality in precipitation variability over Europe. J. Geophys. Res., 109, 16, D05102. doi:10.1020/2002.ID002668.2004.6761
- ³⁰ D05103, doi:10.1029/2003JD003668, 2004. 6761

lier lieeinn Da	HESSD 7, 6757–6792, 2010							
ner Diecheeinn	Reliability and robustness of rainfall compound distribution model F. Garavaglia et al.							
Dupor	Title Page							
	Abstract Introduction							
	Conclusions References							
	Tables Figures							
D	I4 DI							
D	4 Þ							
_	Back Close							
	Full Screen / Esc							
D	Printer-friendly Version							
anor	Interactive Discussion							

 Table 1. Cumulative distribution functions and related sampling method.

	Distribution function	Sampling
GUM	$F(x \mu,\lambda) = \exp\left[-\exp\left\{-\left(\frac{x-\mu}{\lambda}\right)\right\}\right]$	Seasonal Maxima
GEV	$F\left(x \mu,\lambda,\xi\right) = 1 - \exp\left(-\left[1 + \xi\left(\frac{x-\mu}{\lambda}\right)\right]^{-1/\xi}\right)$	
EXP	$F(x \lambda) = 1 - \exp\left(\frac{x}{\lambda}\right)$	Seasonal POT
GPD	$F(x \lambda,\xi) = 1 - \left(1 + \xi \frac{x}{\lambda}\right)^{-1/\xi}$	
MEWP	$F(x \lambda_{1,\dots,8}) = \sum_{i=1}^{8} \left(1 - \exp\left[-\frac{x}{\lambda_{i}}\right]\right) \cdot \rho_{i}$	Seasonal and WP POT
MGPWP	$F(x \lambda_{1,,8},\xi_{1,,8}) = \sum_{i=1}^{8} \left(1 - \left[1 + \xi_i \frac{x}{\lambda_i}\right]^{-1/\xi_i}\right) \cdot p_i$	

 Table 2. Characteristics of the rainfall data sets.

	Selected Period	Years of record	Numbe	r of rain gauges	Network	
			Total	Selected		
Dense dataset		53	603	209	EDF-DTG	
	1052 2005		555	193	Météo France	
	1955-2005		213	65	Météo Swiss	
			131	11	INM	
Long dataset	1904–2003	100	308	37	Météo France SQR	





Table 3. Results of the reliability procedure for the six probabilistic models.

			$\frac{1}{1-f(FF)}$	f(FF)
A value	Simulation EXP (M=552, N=50)		7	0.850
exceeded	GÚM	is shear ad	5	0.784
one time	GEV	ono timo	4	0.744
over 10	EXP		5	0.780
according	GPD	Over	4	0.734
to:	MEWP		7	0.866
	MGPWP		8	0.869
A value	Simulation EXP (M=552, N=50)		11	0.909
exceeded	GÚM		7	0.860
one time	GEV	is observed one time over	5	0.793
over 20	EXP GPD MEWP		7	0.864
according			5	0.783
to:			11	0.913
	MGPWP		15	0.931
A value	Simulation EXP (M=552, N=50)		38	0.974
exceeded	GUM	ic obcorved	16	0.938
one time	GEV EXP	one time	7	0.847
over 100			17	0.941
according	GPD	0001	7	0.848
to:	MEWP		34	0.970
	MGPWP		32	0.969





)iscussion Pa	HES 7, 6757–6	HESSD 7, 6757–6792, 2010					
per Discussion	Reliabil robustness comp distributio F. Garava	lity and s of rainfall ound on model aglia et al.					
Paper	Title	Title Page					
—	Abstract	Introduction					
Disc	Conclusions	References					
ussion	Tables	Figures					
Pap	14						
er -	•	•					
	Back	Close					
iscussion F	Full Scree Printer-frier	Full Screen / Esc Printer-friendly Version					
aper	Interactive	Interactive Discussion					

Table 4. Mean $SPAN_{T}$ and $COVER_{T}$ criteria (the numbers in bold highlight the best performance for each return period).

Score	Return period (year)	Ideal score	GUM	GEV	EXP	GPD	MEWP	MGPWP
	10	0	0.09	0.10	0.09	0.10	0.08	0.10
	20	0	0.10	0.12	0.10	0.12	0.09	0.15
CDAN	50	0	0.11	0.16	0.12	0.16	0.10	0.22
SPAN _T	100	0	0.11	0.19	0.12	0.19	0.11	0.31
	1000	0	0.12	0.31	0.13	0.32	0.13	0.62
	10	1	0.58	0.50	0.51	0.48	0.58	0.10
$COVER_T$	20	1	0.59	0.53	0.53	0.48	0.67	0.66
	50	1	0.60	0.58	0.53	0.51	0.68	0.71
	100	1	0.60	0.60	0.54	0.53	0.69	0.76
	1000	1	0.61	0.64	0.55	0.54	0.70	0.81



Fig. 1. (a) Rain gauges location. **(b)** Regional classification as a function of the "Season at-Risk", i.e. the three consecutive months that maximize the sum of the monthly rainfall maxima.







Fig. 2. Box plot of the three consecutive monthly rainfall maxima of regional dataset A (a) and regional dataset B (c). Empirical distribution of rainfall quantile estimates associated with 10-and 50-year return periods for regional dataset A (b) and regional dataset B (d).







Fig. 3. *FF* distribution provided by simulation with random samples extracted from an exponential distribution. Different curves represent three kinds of simulations with samples of different sizes.







Fig. 4. Schematic confidence intervals overlap criteria: $COVER_{T}$. Three cases are shown: $COVER_{T}$ equal to 0 (null overlap), 0.5 (half overlap) and 1 (total overlap).









Fig. 6. pp-plot of FF scores in calibration and validation







Fig. 7. Close-up of the upper tail of the *FF* validation procedure. The gray circles highlight the values shown in Table 3.











Fig. 8. Empirical distribution of $SPAN_{T}$ and $COVER_{T}$ criteria at 20-years, 100-years and 1000-years return levels.