Hydrol. Earth Syst. Sci. Discuss., 8, 4099–4120, 2011 www.hydrol-earth-syst-sci-discuss.net/8/4099/2011/ doi:10.5194/hessd-8-4099-2011 © Author(s) 2011. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Generalized analytical solution for advection-dispersion equation in finite spatial domain with arbitrary time-dependent inlet boundary condition

J.-S. Chen¹ and C.-W. Liu²

 ¹Graduate Institute of Applied Geology, National Central University, Jhongli City, Taoyuan County, 32001, Taiwan
 ²Departmnent of Bioenvironmental Systems Engineering, National Taiwan University, Taipei, 10617, Taiwan

Received: 23 March 2011 - Accepted: 12 April 2011 - Published: 26 April 2011

Correspondence to: J.-S. Chen (jschen@geo.ncu.edu.tw)

Published by Copernicus Publications on behalf of the European Geosciences Union.





Abstract

This study presents a generalized analytical solution for one-dimensional solute transport in finite spatial domain subject to arbitrary time-dependent inlet boundary condition. The governing equation includes terms accounting for advection, hydrodynamic

- dispersion, linear equilibrium sorption and first order decay processes. The generalized analytical solution is derived by using the Laplace transform with respect to time and the generalized integral transform technique with respect to the spatial coordinate. Several special cases are presented and compared to illustrate the robustness of the derived generalized analytical solution. Result shows an excellent agreement. The an-
- ¹⁰ alytical solutions of the special cases derived in this study have practical applications. Moreover, the derived generalized solution which consists an integral representation is evaluated by the numerical integration to extend its usage. The developed generalized solution offers a convenient tool for further development of analytical solution of specified time-dependent inlet boundary conditions or numerical evaluation of the ¹⁵ concentration field for arbitrary time-dependent inlet boundary problem.
 - 1 Introduction

Solute transport in subsurface is generally described with the advection-dispersion equation (ADE). Analytical solutions for one-, two- and three-dimensional ADEs have been reported in literature for predicting the transport of various contaminants in the semi-finite or infinite spatial domain (e.g., van Genuchten and Alves, 1982; Batu, 1989, 1993, 1996; Leij et al., 1991, 1993; Park and Zhan, 2001; Zhan et al., 2009). The number of analytical solutions for finite spatial domain is limited compared with semi-finite or infinite spatial domain solutions. The reason for the lack of progress in developing analytical solutions for finite spatial domain is that the solution procedures tend to be relatively cumbersome, requiring complicated or difficult mathematical derivation and manipulations (Pérez Guerrero et al., 2009a,b). In groundwater hydrology, the





Laplace transform technique has been widely applied to develop the analytical solutions to advection-dispersion equation. The process of applying Laplace transform to obtain analytical solutions for finite spatial domain in the Laplace space is not complicated, whereas analytically inverting the analytical solution from the Laplace space

- ⁵ back to the original time domain is much more difficult. The inverse Laplace transform is mostly performed based on the complex functions and residual theory, thus limiting the numbers and types of the analytical solutions for finite spatial domain. Accordingly, some researchers used the classic or generalized integral transform technique to develop the analytical solution for solute transport in finite spatial domain. For instance,
- the analytical solutions for one-dimensional advection-dispersion transport in finite spatial domain subject to first- and third-type inlet boundary conditions were presented by Clearly and Adrian (1973), Selim and Mansell (1976), respectively. van Genuchten and Alves (1982) presented the analytical solution for finite spatial domain associated with exponentially decaying time-dependent inlet boundary condition. Recently, Pérez
- ¹⁵ Guerrero et al. (2009a) presented a general integral transform technique which provides a systematic, efficient, and straightforward approach for deriving the analytical solution of the solute transport within a finite spatial domain. Prior to applying general integral transform technique Pérez Guerrero et al. (2009a) suggested that a change-of-variable is carried out to homogenize the inhomogeneous boundary condition using
- a filter function due to that solutions of inhomogeneous problems based on eigenfunction expansions may converge slowly or even exhibit anomalous behavior, especially in the vicinity of the boundaries as noted by Ozisik (1980) and Cotta and Mikhailov (1997). For the case of the transport in a finite spatial domain associated with time-invariant boundary conditions, the filter function for homogenizing the inhomogeneous
- ²⁵ boundary condition can be easily derived. However, the procedure for obtaining the filter function for finite spatial domain with time-dependent boundary condition is much more complicated because of the need to define the filter function over both the time and spatial domain. Accordingly, the application of generalized integral technique to obtain the analytical solution for ADE in finite spatial domain is limited to time-invariant





constant and time-dependent exponentially decaying inlet boundary condition (Pérez Guerrero et al., 2009a,b, 2010; Pérez Guerrero and Skaggs, 2010).

As the authors aware, analytical solution for finite spatial domain associated with arbitrary time-dependent inlet boundary condition has not been reported in literature

- ⁵ yet. In many instances the solute transport problems may involve the various types of time-dependent inlet boundary conditions. For example, naturally occurring isotopes into a system from a flow through-lake can be dependent upon natural, cyclic, water-quality variations or liquid waste disposal operates on a periodic cycle. Additionally, the tracer test may be performed by adopting an instantaneous slug input. The
- solution for arbitrary time-dependent input function should be useful for describing solute transport in a natural or human-made system in which the input at a boundary is a function of time (Logan and Zlotnik, 1995, 1996). In the present study we attempt to derive the generalized analytical solution for ADE in finite spatial domain subject to arbitrary time-dependent inlet boundary condition. The Laplace transform in combi-
- nation with generalized integral transform is used to obtain the generalized analytical solution. Laplace transform is applied to convert the time-dependent inhomogeneous boundary condition into non-time-dependent boundary condition and the constraint in obtaining the filter function for transport in finite special domain with transient boundary condition can be overcome. The generalized analytical solution is applied to derive
- some specific analytical solutions to demonstrate its practical applications. Moreover, the generalized analytical solution which consists of a definite integral expression is evaluated by means of numerical integration technique to extend its applicability for describing solute transport associated with arbitrary time-dependent inlet boundary condition.

25 2 Governing equations

Herein we consider a problem of one-dimensional advective-dispersive solute transport in finite spatial domain subject to arbitrary time-dependent inlet boundary condition.





The solute transport equation incorporates terms accounting for advection, dispersion, linear equilibrium sorption, and first-order decay processes. The governing equation for the solute transport problem is expressed as

$$D_{\rm L}\frac{\partial^2 C}{\partial x^2} - V\frac{\partial C}{\partial x} - kC = R\frac{\partial C}{\partial t}$$

⁵ where C(x,t) is the solute concentration; x is the spatial coordinate; t is time; V stands for the averaged steady-state pore water velocity; D_L represents the longitudinal dispersion coefficient; R is the retardation coefficient of the solute and k is first-order decay rate constant.

The initial and boundary conditions considered herein are

10
$$C(x, t = 0) = 0$$
 $0 \le x \le L$

$$VC(x=0,t) - D_{L} \frac{\partial C(x=0,t)}{\partial x} = Vf(t) \quad t > 0$$

$$\frac{\partial C(x=L,t)}{\partial x} = 0 \quad t > 0 \tag{4}$$

where *L* is the length of the finite spatial domain, f(t) represents the arbitrary expression input function applied at x = 0 which will be specified later.

Inserting the following dimensionless variables, $x_D = \frac{x}{L}$ and $t_D = \frac{Vt}{L}$ into Eqs. (1)–(4) yields the following governing equation and its auxiliary and boundary conditions in dimensionless form as

$$\frac{1}{Pe_{\rm L}}\frac{\partial^2 C}{\partial x_{\rm D}^2} - \frac{\partial C}{\partial x_{\rm D}} - k_{\rm D}C = R\frac{\partial C}{\partial t_{\rm D}}$$
(5)

$$C(x_{\rm D}, t_{\rm D} = 0) = 0$$
 $0 \le x_{\rm D} \le 1$

15

²⁰
$$C(x = 0, t_{\rm D}) - \frac{1}{Pe_{\rm L}} \frac{\partial C(x_{\rm D} = 0, t_{\rm D})}{\partial x_{\rm D}} = f(\frac{L}{V}t_{\rm D}) \quad t_{\rm D} > 0$$

4103

Discussion Paper **HESSD** 8, 4099-4120, 2011 Generalized analytical solution for advection-dispersion **Discussion** Paper equation J.-S. Chen and C.-W. Liu **Title Page** Introduction Abstract **Discussion** Paper Conclusions References **Figures Tables** 14 Back Close **Discussion** Paper Full Screen / Esc **Printer-friendly Version** Interactive Discussion

(1)

(2)

(3)

(6)

(7)

$$\frac{\partial C(x_{\rm D}=1,t_{\rm D})}{\partial x_{\rm D}} = 0 \quad t_{\rm D} > 0$$

where $Pe_{L} = \frac{VL}{D_{L}}$ and $k_{D} = \frac{kL}{V}$.

3 Derivation of the generalized analytical solution

The analytical solution to Eq. (5) subject to Eqs. (6)–(8) is derived using the Laplace transform with respect to t_D and the general integral transform technique with respect

to $x_{\rm D}$.

0

5

10

First, the Laplace transform is carried out on Eq. (5) with the help of Eq. (6) and its auxiliary boundary conditions Eqs. (7) and (8) with respect to t_D . After the Laplace transform procedure the governing equation (Eq. 5) and boundary conditions (Eqs. 7–8) become

$$\frac{1}{Pe_{\rm L}}\frac{d^2C_{\rm L}}{dx_{\rm D}^2} - \frac{dC_{\rm L}}{dx_{\rm D}} - (k_{\rm D} + s)C_{\rm L} = 0$$

$$C_{\mathsf{L}}(x_{\mathsf{D}}=0,s) - \frac{1}{Pe_{\mathsf{L}}} \frac{dC_{\mathsf{L}}(x_{\mathsf{D}}=0,s)}{dx_{\mathsf{D}}} = \overline{f}(s)$$

$$\frac{dC_{\rm L}(x_{\rm D}=1,s)}{dx_{\rm D}} = 0 \tag{11}$$

where *s* denotes the Laplace transform parameter and $C_L(x_D, s)$ and $\overline{f}(s)$ represent the Laplace transforms of $C(x_D, t_D)$ and $f(\frac{L}{V}t_D)$, respectively, which is defined by the following equations

$$C_{L}(x_{D},s) = L[C(x_{D},t_{D})] = \int_{0}^{\infty} C(x_{D},t_{D})e^{-st_{D}}dt_{D}$$
(12)
4104



(8)

(9)

(10)

$$\overline{f}(s) = L\left[f\left(\frac{L}{V}t_{\rm D}\right)\right] = \int_{0}^{\infty} f\left(\frac{L}{V}t_{\rm D}\right)e^{-st_{\rm D}}dt_{\rm D}$$

The general integral transform technique is then adopted to analytically solve the Eq. (9) and its auxiliary initial and boundary conditions Eqs. (10) and (11). Further information regarding the use of the generalized integral transform can be found in ⁵ Pérez Guerreo et al. (2009a,b; 2010). Prior to applying general integral transform technique a change-of-variable is carried out to homogenize the boundary condition Eq. (12) and to covert Eq. (9) into a purely diffusive type differential equation. This approach was demonstrated previously by Pérez Guerreo et al. (2009a). Inserting the variable change $C_V(x_D, s) = \left[C_L(x_D, s) - \overline{f}(s)\right] \exp\left(-\frac{Pe_L}{2}x_D\right)$, Eqs. (9)–(11) can be written in terms of the $C_V(x_D, s)$ as

$$\frac{1}{Pe_{\rm L}}\frac{d^2C_{\rm V}}{dx_{\rm D}^2} - \left(\frac{Pe_{\rm L}}{4} + k_{\rm D} + s\right)C_{\rm V} = \exp\left(-\frac{Pe_{\rm L}}{2}x_{\rm D}\right)(k_{\rm D} + s)\overline{f}(s) \tag{14}$$

$$\frac{dC_{\rm V}(x_{\rm D}=0,s)}{dx_{\rm D}} - \frac{Pe_{\rm L}}{2}C_{\rm V}(x_{\rm D}=0,s) = 0$$
(15)

$$\frac{dC_{\rm V}(x_{\rm D}=1,s)}{dx_{\rm D}} + \frac{Pe_{\rm L}}{2}C_{\rm V}(x_{\rm D}=1,s) = 0$$
(16)

Following the procedures of the generalized integral transform, the eigenfunction is determined from the following Sturm-Liouville problem with the same kinds of boundary conditions as specified for $C_V(x_D, s)$:

~

$$\frac{d^2 K(x_{\rm D})}{dx_{\rm D}^2} + \psi^2 K(x_{\rm D}) = 0$$
(17)



(13)

$$\frac{dK(x_{\rm D} = 0)}{dx_{\rm D}} - \frac{Pe_{\rm L}}{2}K(x_{\rm D} = 0) = 0$$
$$\frac{dK(x_{\rm D} = 1)}{dx_{\rm D}} + \frac{Pe_{\rm L}}{2}K(x_{\rm D} = 1) = 0$$

Solving for Eqs. (17)-(19), we have the following normalized eigenfunction

$$\mathcal{K}(\psi_m, z_{\mathsf{D}}) = \frac{\sqrt{2} \left[\psi_m \cos(\psi_m z_{\mathsf{D}}) + \frac{P_{\theta_{\mathsf{L}}}}{2} \sin(\psi_m z_{\mathsf{D}}) \right]}{\left(\frac{P e_{\mathsf{L}}^2}{4} + \frac{P_{\theta_{\mathsf{L}}}}{2} + \psi_m^2 \right)^{\frac{1}{2}}}$$
(20)

s where ψ_m is the eigenvalue determined from the following equation:

$$\psi_m \cot \psi - \frac{\psi_m^2}{Pe_L} + \frac{Pe_L}{4} = 0 \tag{21}$$

The generalized integral transform pairs are readily defined as

$$\overline{C_{\mathsf{V}}}(\psi_m, s) = \int_0^1 \mathcal{K}(\psi_m, x_{\mathsf{D}}) C_{\mathsf{V}}(x_{\mathsf{D}}, s) dx_{\mathsf{D}}$$
(22a)

$$\overline{C_{\mathsf{V}}}(x_{\mathsf{D}},s) = \sum_{m=1}^{\infty} \mathcal{K}(\psi_m, x_{\mathsf{D}}) C_G(\psi_m, s)$$
(22b)

¹⁰ Making use of the above generalized integral transform on Eq. (14) and solving for $\overline{C_V}(x_D, s)$, one obtains

$$\overline{C_{\rm V}}(x_{\rm D},s) = \frac{-\sqrt{2}\psi_m P e_{\rm L}}{\left(\frac{P e_{\rm L}^2}{4} + \frac{P e_{\rm L}}{2} + \psi_m^2\right)^{\frac{1}{2}} \left(\frac{P e_{\rm L}^2}{4} + \psi_m^2\right)} \cdot \frac{s + k_{\rm D}}{s + \frac{\psi_m^2}{P e_{\rm L}} + \frac{P e_{\rm L}}{4} + k_{\rm D} + s} \overline{f}(s)$$
(23)
4106



(18)

(19)



The analytical solution in original domain can readily be obtained by successively applications of the general integral transform inversion (Eq. 22b), change of variable, as well as the Laplace transform inversion. The inverse Laplace transform is achieved using convolution theorem. Following the aforementioned procedures, the final analytical ⁵ solution can be expressed in dimensionless form as

$$C(x_{\rm D}, t_{\rm D}) = f\left(\frac{L}{V}t_{\rm D}\right) - \sum_{m=1}^{\infty} \exp\left(\frac{Pe_{\rm L}}{2}x_{\rm D}\right) E(\psi_m, x_{\rm D})F(t_{\rm D})$$
(24)

where
$$E(\psi_m, x_D) = \frac{2Pe_L\psi_m \left[\psi_m \cos(\psi_m x_D) + \frac{Pe_L}{2}\sin(\psi_m x_D)\right]}{\left(\frac{Pe_L^2}{4} + \frac{Pe_L}{2} + \psi_m^2\right) \left(\frac{Pe_L^2}{4} + \psi_m^2\right)},$$

 $F(t_D) = f\left(\frac{L}{V}t_D\right) - \left(\frac{\psi_m^2}{Pe_L} + \frac{Pe_L}{4}\right)e^{-\left(\frac{\psi_m^2}{Pe_L} + \frac{Pe_L}{4} + k_D\right)t_D}\int_0^t f\left(\frac{L}{V}\tau\right)e^{\left(\frac{\psi_m^2}{Pe_L} + \frac{Pe_L}{4} + k_D\right)\tau}d\tau$

Results and discussion 4

Development of specific solutions using the generalized analytical solution 4.1 10

The generalized analytical solution (Eq. 24) provides useful foundation for deriving specific analytical solutions having practical applications. Solution for specified timedependent input function can be readily derived by substituting $f(\frac{L}{V}t_{\rm D})$ into the integral expression of Eq. (24). In this study three specific analytical solutions for constant, exponentially decaying and sinusoidally periodic time-dependent input functions are 15 derived using integral expression of Eq. (24). Table 1 summarizes three specified time-dependent input functions and their corresponding analytical solutions. The solutions for constant and exponentially decaying input functions have been previously

HESSD

8, 4099-4120, 2011

Generalized analytical solution for advection-dispersion

equation

J.-S. Chen and C.-W. Liu

Title Page

Abstract

Conclusions

Tables

14

Back

Introduction

References

Figures

Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper

presented in literature (van Genuchten and Alves, 1982). The solutions for constant and exponential decaying time-dependent input functions in Table 1 are the same as those reported in literature.

- The solution for a finite spatial domain associated with sinusoidally periodic bound-5 ary condition has not been presented in literature. The specific analytical solution for sinusoidally periodic input function is in the form of the sum of the infinite series expansion and can be straightforwardly evaluated. Generally, the number of the terms in the infinite series expansion plays a key role in determining the accurate result. Accordingly, we are interesting to examine how many terms are required to numerically determine the accurate solution. The parameter values for the numerical results for sinusoidal periodic input function are summarized in Table 2. Table 3 illustrates the convergence of the numerical evaluation of analytical solution for the sinusoidally pe-
- riodic input. The required number of terms drastically increases with increasing Pe_1 . Numbers of terms 10, 60 and 1800 can achieve convergence to 4 decimal places for
- *Pe*₁ equal to 1, 10 and 50. After determining the number of terms for solution convergence we compare the developed periodic analytical solution with the corresponding numerical solution to examine the correctness of the mathematical derivations and manipulations in the solution development for sinusoidal periodic input function. The numerical solution is generated using the Laplace transform finite difference (LTFD)
- technique proposed by Moridis and Reddel (1991). The LTFD technique has several advantages over the conventional time-marching finite difference method. The input parameter values are the same as those in Table 2. Figure 2 depicts the breakthrough curves observed at x = 1 m obtained from the specific analytical solution and the corresponding numerical solution. As expected, the developed analytical solutions agree 25
- well with the corresponding numerical solutions.

4.2 Effect of D and k on periodic solute transport

After validating the analytical solution for sinusoidal periodic input function, we use this analytical solution to carry out the parametric investigation in which the effect of D and k



on periodic solute transport are illustrated and discussed. Each of the two parameters, namely D and k is parametrically varied, respectively, while the other parameters are kept constant. It is observed in Fig. 2 that increasing D will decrease the amplitude of the periodic concentration wave due to larger spreading of the solute mass. In Fig. 3,

s a lower concentration is observed at the crest and trough of concentration wave for large k.

4.3 Evaluation of the generalized analytical solution using numerical integration

In Sect. 4.1 we derive some specific analytical solution using the developed generalized analytical solution (Eq. 24) by substituting the specified time-dependent input function into the integral expression. However, in many instances the development of the specific analytical solution is difficult or prohibited, therefore, the numerical integration method need to be used to evaluate the result of Eq. (24). The reason for using numerical integration method may be due to that the anti-derivative for the specified in-

- ¹⁵ put function is impossible or difficult to find or the input function is known only at certain points, such as obtained by sampling. The integral in Eq. (24) is numerically evaluated by means of the Gaussian integration procedure using 30–61 quadrature points. A FORTRAN subroutine DQDAG/QDAG (Visual Numerics, Inc., 1997) based on the Gaussian rule, is readily employed to perform the numerical integration. The accuracy
- of the evaluated results of Eq. (24) using numerical integration is compared with two specific analytical solutions for exponential decaying and sinusoidal periodic input functions. Figsures 4 and 5 show the results from the numerical integration of Eq. (24) and the two specific analytical solutions for exponentially decaying and sinusoidally periodic input functions. The applicability of the Eq. (24) is illustrated with excellent agreements between the results from numerical integration of Eq. (24) and the specific analytical
 - solutions for both cases. From above results we can conclude that the developed generalized analytical solution serves as a useful tool for development of the analytical solution for some specified





4110

. . . .

time-dependent input functions or numerical evaluation of concentration distribution for arbitrary time-dependent input function.

5 Conclusions

- This study derives a generalized analytical solution for one-dimensional advectivedispersive transport in finite spatial domain subject to arbitrary dependent inlet boundary condition. The solution procedures consist of taking Laplace transform with respect to time and generalized integral transform with respect to spatial coordinate. Three simple time-dependent inlet conditions including constant, exponentially decaying and sinusoidally periodic input functions are considered to demonstrate the applicability of the generalized analytical solution for development of the specific analytical solution for some specified input function. Specifically, parametric analysis is performed to illustrate the salient behavior of solute transport resulting from a periodic input function. Moreover, the generalized solution which consists of an integral representation is also evaluated by means of the numerical integration to extend its usage. The
- generalized analytical solution provides the foundation for deriving analytical solution for some specified types of the time-dependent inlet condition or numerically evaluating the concentration distribution for arbitrary time-dependent inlet boundary condition. Furthermore, the solution derived for sinusoidal periodic function will be added to the compendium of the analytical solution to the advection-dispersion equation reported
- ²⁰ by other researchers in literature. The analytical solution for finite spatial domain associated with time-dependent inlet boundary condition should be particularly useful for verification of the more comprehensive numerical models because several field numerical simulations generally involve finite domain and time-dependent source boundary conditions.





References

- Batu, V.: A generalized two-dimensional analytical solution for hydrodynamic dispersion in bounded media with the first-type boundary condition at the source, Water Resour. Res., 25(6), 1125–1132, 1989.
- ⁵ Batu, V.: A generalized two-dimensional analytical solute transport model in bounded media for flux-type finite multiple sources, Water Resour. Res., 29(8), 2881–2892, 1993.
 - Batu, V.: A generalized three-dimensional analytical solute transport model for multiple rectangular first-type sources, J. Hydrol., 174(1–2), 57–82, 1996.
 - Clearly, R. W. and Adrian, D. D.: Analytical solution of the convective-dispersive equation for cation adsorption in soils, Soil Sci. Soc. Am. Pro., 37, 197–199, 1973.
 - Cotta, R. M. and Milkhailov, M. D.: Heat Conduction: Lumped Analysis, Integral Transforms, Symbolic Computations, Wiley-Interscience, New York, 1997.
 - Leij, F. J., Skaggs, T. H., and van Genuchten, M. Th.: Analytical solution for solute transport in three-dimensional semi-infinite porous media, Water Resour. Res., 27(10), 2719–2733, 1991.
- 15

10

- Leij, F. J., Toride, N., and van Genuchten, M. Th.: Analytical solutions for non-equilibrium solute transport in three-dimensional porous media, J. Hydrol., 151(2–4), 193–228, 1993.
- Logan, J. D. and Zlotnik, V.: The convection-diffusion equation with periodic boundary condtion, Appl. Math. Lett., 8(3), 55–61, 1995.
- Logan, J. D. and Zlotnik, V.: Time-periodic transport in heterogeneous porous media, Appl. Math. Comput., 75, 119–138, 1996.
 - Moridis, G. J. and Reddell, D. L.: The Laplace transform finite difference method for simulation of flow through porous media, Water Resour. Res., 27(8), 1873–1884, 1991.
 - Ozisik, M. N.: Heat Conduction, Wiley, New York, 1980.
- Park, E. and Zhan, H.: Analytical solutions of contaminant transport from finite one-, two, threedimensional sources in a finite-thickness aquifer, J. Contam. Hydrol., 53(1–2), 41–61, 2001.
 Peréz Guerrero, J. S. and Skaggs, T. H.: Analytical solution for one-dimensional advection– dispersion transport equation with distance-dependent coefficients, J. Hydrol., 390(1–2), 57– 65, 2010.
- Pérez Guerrero, J. S., Pimentel, L. C. G., Skaggs, T. H., and van Genuchten, M. Th.: Analytical solution of the advection-diffusion transport equation using a change-of-variable and integral transform technique, Int. J. Heat Mass Tran., 52, 3297–3304, 2009a.





CCC D

Pérez Guerrero, J. S., Skaggs, T. H., and van Genuchten, M. Th.: Analytical solution for multispecies contaminant transport subject to sequential first-order decay reactions in finite media, Transport Porous Med., 80, 373–357, 2009b.

Pérez Guerrero, J. S., Skaggs, T. H., and van Genuchten, M. Th.: Analytical solution for multispecies contaminant transport in finite media with time-varying boundary conditions, Trans-

port Porous Med., 85, 171–178, 2010.

15

Selim, H. M. and Mansell, R. S.: Analytical solution for transport of reactive solutes through soils, Water Resour. Res., 12(3), 528–532, 1976.

van Genuchten, M. Th. and Alves, W. J.: Analytical Solutions of the One-Dimensional

¹⁰ Convective-Dispersive Solute Transport Equation, US Department of Agriculture, Technical Bulletin No. 1661, Washington, DC, USA, 151 pp., 1982.

Visual Numerics, Inc.: IMSL User's Manual, Houston, TX, USA, Vol. 1, 591–594, 1997.

Zhan, H., Wen, Z., and Gao, G.: An analytical solution of two-dimensional reactive solute transport in an aquifer-aquitard system, Water Resour. Res., 45, W10501, doi:10.1029/2008WR007479, 2009.



Specified input	Solution expression for specified input function $f(t)$					
$f(t) = C_0$	$C(x,t) = C_0[B_1(x) - B_2(x,t)]$					
	$B_1(x) = 1 - \sum_{m=1}^{\infty} \frac{E(\beta_m, x) \frac{kL^2}{D} \exp\left(\frac{Vx}{2D}\right)}{\beta_m^2 + \left(\frac{VL}{2D}\right)^2 + \frac{kL^2}{D}}$					
	$B_2(x,t) = \sum_{m=1}^{\infty} \frac{E(\psi_m, x) \left[\beta_m^2 + \left(\frac{VL}{2D}\right)^2\right] \exp\left(\frac{Vx}{2D} - \frac{kt}{R} - \frac{V^2t}{4DR} - \frac{\beta_m^2 Dt}{L^2 R}\right)}{\beta_m^2 + \left(\frac{VL}{2D}\right)^2 + \frac{kL^2}{D}}$					
	$E(\beta_m, x) = \frac{\frac{2VL}{D}\beta_m \left[\beta_m \left(\frac{\beta_m x}{L}\right) + \frac{VL}{2D}\sin\left(\frac{\beta_m x}{L}\right)\right]}{\left[\left(\frac{VL}{2D}\right)^2 + \frac{VL}{2D} + \beta_m^2\right]\left[\left(\frac{VL}{2D}\right)^2 + \beta_m^2\right]}$					
$f(t) = C_a e^{-\lambda t}$	$C(x,t) = C_a \ e^{-\lambda t} [F_1(x) - F_2(x,t)]$					
	$F_1(x) = 1 - \sum_{m=1}^{\infty} \frac{E(\beta_m, x) \frac{(k-\lambda R)L^2}{D} \exp\left(\frac{Vx}{2D}\right)}{\beta_m^2 + \left(\frac{VL}{2D}\right)^2 + \frac{(k-\lambda R)L^2}{D}}$					
	$F_2(x,t) = \sum_{m=1}^{\infty} \frac{E(\beta_m, x) \left[\beta_m^2 + \left(\frac{VL}{2D}\right)^2\right] \exp\left(\frac{Vx}{2D} - \frac{kt}{R} + \lambda t - \frac{V^2t}{4DR} - \frac{\beta_m^2 Dt}{L^2 R}\right)}{\beta_m^2 + \left(\frac{VL}{2D}\right)^2 + \frac{(k-\lambda R)L^2}{D}}$					
$f(t) = C_a \sin(\omega t)$	$C(x_{\rm D}, t_{\rm D}) = C_b \left[G_1(x, t) + G_2(x, t) - G_3(x, t) \right]$					
	$G_{1}(x,t) = \left[1 - \sum_{m=1}^{\infty} \frac{E(\beta_{m}, x) \left\{ \left[\beta_{m}^{2} + \left(\frac{VL}{2D}\right)^{2} + \frac{kL^{2}}{D}\right] \frac{kL^{2}}{D} + \frac{\omega RL^{2}}{D} \right\} \exp\left(\frac{Vx}{2D}\right)}{\left[\beta_{m}^{2} + \left(\frac{VL}{2D}\right)^{2} + \frac{kL^{2}}{D}\right]^{2} + \left(\frac{\omega RL^{2}}{D}\right)^{2}} \right] \sin(\omega t)$					
	$G_{2}(x,t) = \sum_{m=1}^{\infty} \frac{E\left(\beta_{m}, x\right) \left\{ \left[\beta_{m}^{2} + \left(\frac{VL}{2D}\right)^{2}\right] \frac{\omega RL^{2}}{D} \right\} \exp\left(\frac{Vx}{2D}\right)}{\left[\beta_{m}^{2} + \left(\frac{VL}{2D}\right)^{2} + \frac{KL^{2}}{D}\right]^{2} + \left(\frac{\omega RL^{2}}{D}\right)^{2}} \cos(\omega t)$					
	$G_{3}(x,t) = \sum_{m=}^{\infty} \frac{E\left(\beta_{m}, x\right) \left\{ \left[\beta_{m}^{2} + \left(\frac{VL}{2D}\right)^{2}\right] \frac{\omega RL^{2}}{D} \right\} \exp\left(\frac{Vx}{2D} - \frac{kt}{R} + \lambda t - \frac{V^{2}t}{4DR} - \frac{\beta_{m}^{2}Dt}{L^{2}R}\right)}{\left[\beta_{m}^{2} + \left(\frac{VL}{2D}\right)^{2} + \frac{kL^{2}}{2}\right]^{2} + \left(\frac{\omega RL^{2}}{2}\right)^{2}}$					

Table 1. Three time-dependent input functions and their corresponding analytical solutions.



4113

Table 2. Descriptive simulation conditions and transport parameters.

Parameter	Value
Domain length L (m)	1
Average velocity V (m d ⁻¹)	1
Longitudinal dispersion coefficient $D (m^2 d^{-1})$	1
First decay rate constant $k (1 d^{-1})$	0.01
Frequency of sinusoidal periodic input function ω (1 d ⁻¹)	1
Decay rate constant of exponential decaying input function λ (1 d^{-1})	1





Table 3. Solution convergence for sinusoidal periodic function $(1 + \sin t)$.

0. 1								
t	N = 2	N = 4	N = 6	N = 8	<i>N</i> = 10			
0.4	0.2926	0.2913	0.2912	0.2912	0.2912			
0.8	0.7214	0.7204	0.7203	0.7203	0.7203			
1.2	1.1045	1.1039	1,1039	1.1039	1.1039			
1.6	1.4135	1.4135	1,4135	1.4135	1.4135			
2.0	1.6208	1.6213	1.6213	1.6213	1.6213			
2.4	1.7066	1.7077	1.7077	1.7077	1.7077			
2.8	1.6658	1.6672	1.6672	1.6673	1.6673			
3.2	1.5099	1.5113	1.5114	1.5114	1.5114			
3.6	1.2666	1.2679	1.2680	1.2680	1.2680			
4.0	0.9764	0.9774	0.9774	0.9774	0.9774			
4.4	0.6863	0.6868	0.6868	0.6868	0.6868			
4.8	0.4429	0.4428	0.4428	0.4428	0.4428			
5.2	0.2851	0.2844	0.2844	0.2844	0.2844			
5.6	0.2381	0.2370	0.2369	0.2369	0.2369			
6.0	0.3095	0.3081	0.3080	0.3080	0.3080			
6.4	0.4882	0.4867	0.4866	0.4866	0.4866			
6.8	0.7460	0.7447	0.7446	0.7446	0.7446			
7.2	1.0422	1.0413	1.0413	1.0413	1.0412			
7.6	1.3302	1.3298	1.3298	1.3298	1.3298			
		Pe	= 10					
t	N = 20	N = 30	N = 40	N = 50	N = 60			
0.40	0.0214	0.0206	0.0205	0.0205	0.0205			
0.80	0.4332	0.4326	0.4325	0.4325	0.4325			
1.20	1.0132	1.0129	1.0128	1.0128	1.0128			
1.60	1.4550	1.4550	1.4550	1.4550	1.4550			
2.00	1.7427	1.7430	1.7431	1.7431	1.7431			
2.40	1.8809	1.8815	1.8816	1.8816	1.8816			
2.80	1.8682	1.8690	1.8691	1.8691	1.8692			
3.20	1.7137	1.7145	1.7147	1.7147	1.7147			
3.60	1.4440	1.4448	1.4449	1.4449	1.4449			
4.00	1.1024	1.1029	1.1030	1.1030	1.1030			
4.40	0.7429	0.7431	0.7432	0.7432	0.7432			
4.80	0.4224	0.4223	0.4223	0.4223	0.4223			
5.20	0.1915	0.1911	0.1911	0.1911	0.1911			
5.60	0.0867	0.0861	0.0860	0.0860	0.0859			
6.00	0.1245	0.1238	0.1236	0.1236	0.1236			
6.40	0.2990	0.2982	0.2981	0.2980	0.2980			
6.80	0.5826	0.5819	0.5817	0.5817	0.5817			
7.20	0.9305	0.9300	0.9299	0.9299	0.9299			
7.60	1.2878	1.2876	1.2875	1.2875	1.2875			
		Pe	= 50					
t	N = 400	N = 800	N = 1200	N = 1600	N = 1800			
0.40	0.0069	0.0006	0.0003	0.0002	0.0002			
0.80	0.1651	0.1603	0.1600	0.1600	0.1600			
1.20	1.0559	1.0534	1.0532	1.0532	1.0532			
1.60	1.5337	1.5338	1.5338	1.5338	1.5338			
2.00	1.8046	1.8073	1.8074	1.8075	1.8075			
2.40	1.9417	1.9466	1.9468	1.9469	1.9469			
2.80	1.9284	1.9347	1.9351	1.9351	1.9351			
3.20	1.7670	1.7737	1.7741	1.7742	1.7742			
3.60	1.4830	1.4890	1.4894	1.4894	1.4894			
4.00	1.1211	1.1255	1.1258	1.1258	1.1258			
4.40	0.7386	0.7407	0.7408	0.7408	0.7408			
4.80	0.3958	0.3952	0.3951	0.3951	0.3951			
5.20	0.1468	0.1436	0.1434	0.1434	0.1434			
5.60	0.0309	0.0256	0.0254	0.0253	0.0253			
6.00	0.0665	0.0600	0.0596	0.0595	0.0595			
6.40	0.2479	0.2411	0.2408	0.2407	0.2407			
6.80	0.5465	0.5405	0.5402	0.5401	0.5401			
7.20	0.9151	0.9109	0.9107	0.9106	0.9106			
7.60	1.2956	1.2938	1.2937	1.2937	1.2937			















Fig. 2. Comparison of the breakthrough curves at x = 1 m for different D. The sinusoidal periodic input function is $f(t) = 1 + \sin t$. Parameter D is varied and other parameters are kept constant.



Fig. 3. Comparison of the breakthrough curves at x = 1 m for different k. The sinusoidal periodic input function is $f(t) = 1 + \sin t$. Parameter k is varied and other parameters are kept constant.









Fig. 5. Comparison of the breakthrough curves at x = 1 m from the numerical integration of Eq. (24) and the specific analytical solution for sinusoidal periodic input function ($f(t) = 1 + \sin t$).



Printer-friendly Version