

1

2 **The referential grain size and effective porosity in the Kozeny-**
3 **Carman model**

4

5 K. Urumović¹ and K Urumović Sr²

6 ¹ Croatian Geological Survey, Sachsova 2, P.O. box 268, HR-10001 Zagreb, Croatia

7 ² Ulica Lea Müllera 3. odvojak 2, 10090 Zagreb, Croatia

8

9

10 Correspondence to: Kosta Urumović, kosta.urumovic@hgi-cgs.hr

11

1 **Abstract**

2 In this paper, the results of permeability and specific surface area analyses as functions of
3 granulometric composition of various sediments (from silty clays to very well-graded gravels) are
4 presented. The effective porosity and the referential grain size are presented as fundamental
5 granulometric parameters expressing an effect of the forces operating on fluid movement through the
6 saturated porous media. This paper suggests procedures for calculating referential grain size and
7 determining effective (flow) porosity, which result in parameters that reliably determine the specific
8 surface area and permeability. These procedures ensure the successful application of the Kozeny-
9 Carman model up to the limits of validity of Darcy's law. The value of effective porosity in the
10 referential mean grain size function was calibrated within the range of 1.5 μm to 6.0 mm. The
11 reliability of the parameters applied in the KC model was confirmed by a very high correlation
12 between the predicted and tested hydraulic conductivity values ($R^2=0.99$ for sandy and gravelly
13 materials; $R^2=0.70$ for clayey-silty materials). The group representation of hydraulic conductivity
14 (ranging from 10^{-12} m/s up to 10^{-2} m/s) presents a coefficient of correlation of $R^2=0.97$ for a total of
15 175 samples of various deposits. These results present new developments in the research of the
16 effective porosity, the permeability and the specific surface area distributions of porous materials. This
17 is important because these three parameters are critical conditions for successful groundwater flow
18 modeling and contaminant transport. Additionally, from a practical viewpoint, it is very important to
19 identify these parameters swiftly and very accurately.

20

1 Introduction

2 The effect of the granulometric composition of granular porous media on its transmissivity,
3 accumulation and suction parameters is both a permanent scientific challenge and a practical issue. In
4 hydrogeology, particular attention is given to hydraulic conductivity. Hazen (1892) and Slichter
5 (1902) have published widely accepted and reputable models for calculating the hydraulic
6 conductivity of uniform sands using effective grain size. The term “effective grain”, used for grain
7 diameters in both formulae could lead to confusion (Mavis and Wilsey, (1936). However, Hazen’s
8 formula uses D_{10} (soil particle diameter where 10% of all soil particles are finer (smaller) by weight),
9 and Slichter proposes using the mean diameter. This confusion persisted, and in recent decades, grain
10 size D_{10} has been misused frequently (Kovács, 1981), (Vukovic & Soro, 1992), (Cheng & Chen,
11 2007), (Odong, 2008) in formulae that actually use another effective grain size.

12 The usage of certain forms of mean grain size became inevitable with the development of
13 hydraulic conductivity models that describe relations between the hydraulic conductivity and the
14 specific surface area (Krüger, 1918), (Zunker, 1920), (Blake, 1922), (Kozeny, 1927) (Fair & Hatch,
15 1933). (Kozeny, 1927) introduced the equation of permeability for the flow model containing a bundle
16 of capillary tubes of even length. Kozeny’s permeability formula was later modified by (Carman,
17 1937) and (Carman, 1939). Carman redefined specific surface area and presented it as a conversion of
18 mean grain size and the index of porosity and incorporated an effect of tortuosity for the flow around
19 individual grains. The resultant form of the equation is known as the Kozeny-Carman’s (KC) equation.
20 The verity of the KC formula application results is strongly dependent on the verity of effective
21 porosity and representative grain size. (Kozeny, 1927) used the harmonic mean grain size of samples.
22 (Bear, 1972) recommended the same grain size. (Koltermann & Gorelick, 1995) and (Kamann, Ritzi,
23 David, & Conrad, 2007) stated that the harmonic mean performed best in samples with high fine grain
24 contents. Chapuis and Aubertin (2003) proposed laboratory tests for determining the specific surface
25 area of fine grained materials for application in the KC formula. Several authors (Al-Tabbaa & Wood,
26 1987, Dolinar & Otoničar, 2007) have studied applicability of KC formulae for calculation of
27 hydraulic conductivity of fine grained materials. All of them have concluded that KC model in its
28 original form does not apply on clays. Dolinar and Otoničar (2007) have also proposed modified form
29 of KC equation.

30 The objective of this article is to research the relationship between average mean grain size
31 and effective porosity in relation to permeability and specific surface area for a wide range of grain
32 sizes and particle uniformities in various soil samples. In the hydraulic conductivity calculations, the
33 Kozeny-Carman equation was used to discover the algorithm for calculating the referential mean grain
34 size. This grain size, along with effective porosity, generates a harmonious parametric concept of the
35 impact of porous media geometrics on its transmission capacity.

36 2 Study area and analyzed deposits

37 For the purpose of this work, data on sandy and gravely aquifers and clayey-silty deposits
38 were collected. All of the study sites are located in the plains of the Republic of Croatia (Fig. (1)). The
39 northern parts of the Republic of Croatia are covered by thick quaternary deposits with sandy and
40 gravely aquifers (Brkić et al. 2010). Covering aquitards are composed of silty-clayey deposits.
41

1 Figure 1. The map of Northern Croatia with test sites locations

2

3 The analyses of non-cohesive deposits were conducted on 36 gravel test samples from six
4 investigation boreholes on the Đurđevac well field (marked as GW on Fig. (1); 19 uniform sand test
5 samples from the investigation boreholes on two well fields – Beli Manastir (marked as SU1) and
6 Donji Miholjac (marked as SU2); and 28 samples of sand with laminas made of silty material from
7 two investigation boreholes on two well fields – Ravnik (marked as FS/SU1) and Osijek (marked as
8 FS/SU2). Appropriate pumping tests were conducted on the test fields to determine the average
9 hydraulic value of aquifers.

10 Cohesive deposits were investigated on three sites. Soil samples from exploration boreholes
11 (depth 1.0 – 30.0 m) were laboratory tested. Analyses on granulometric composition (grain size
12 distribution), hydraulic conductivity and Atterberg limits were conducted. On the first test field (route
13 of Danube, Sava channel; marked as CI/MI1), all the aforementioned analyses were conducted for
14 each soil sample. Sixty-five samples of various soil types were analyzed. On the second and third test
15 sites (Ilok, marked as CI/MI2, and Našice, marked as CI/MI3), loess and aquatic loess-like sediments
16 were investigated. Laboratory analyses were conducted on 21 samples from eight investigation
17 boreholes. Specific analyses at various depths were conducted on the samples from this test site, and
18 on account of this, the mean values for the individual boreholes were correlated (Urumović K. , 2013).

19 3 Methodology

20 3.1 Hydraulic model

21 The effects of porosity n and specific surface area a on fluid movements in porous media can
22 be illustrated by analyzing the force field in the representative elementary volume (REV) $\delta V = \delta A \delta s$
23 (Fig. (2)) in the direction of elementary length δs that is perpendicular to the elementary plane δA .

24

25 Figure 2. Definition sketch of liquid driving and opposed viscous forces for elemental volume

26

27 The forces of pressure and gravity cause the motion of the fluid in the pores. A pressure force
28 is transferred to δs between the entry plane δA and its parallel exit plane. The total amount is
29 proportional to the gradient $\delta p / \delta s$. A component of the gravity force ρg in the fluid volume $n \delta A \delta s$
30 is proportional to the sine of the angle made by δs with its projection on the horizontal plane. This equals
31 $\rho g n \delta A \delta s \sin \theta = \rho g n \delta A \delta s \frac{\partial z}{\partial s}$. These two driving forces are, in fluid motion, against the force of viscosity τ . The
32 force of viscosity is proportional to the viscosity coefficient of water μ , the average velocity q_s of
33 water flow in direction δs , and the effect of the geometry of void space, which is given by the drag
34 resistance constant r_s in direction δs and is proportional to the specific surface area. When the water
35 flows, these forces are in balance, and hence (Hantush, 1964), (Urumović S. K., 2003):

$$-n\delta V \frac{\partial p}{\partial s} - n\delta V \rho g \frac{\partial z}{\partial s} - \delta V \mu r_s q_s = 0 \quad (1)$$

36 or:

$$q_s = -\frac{n\rho g}{r_s\mu} \frac{\partial(p/\rho g + z)}{\partial s} = -\frac{n\rho g}{r_s\mu} \frac{\partial h}{\partial s} = -K_s \frac{\partial h}{\partial s} = -k_s \frac{\rho g}{\mu} \frac{\partial h}{\partial s} \quad (2)$$

1 These relations express Darcy's law, as theoretically described by Hubbert (1956). Here, the focus is
 2 on permeability as a property of porous media that is (in Eq. (2)) given by the relation $k_s=n/r_s$, k_s [L²].
 3 Porosity n is measured as the volume of moving fluid and is connected with the specific effect of the
 4 driving forces of pressure and gravity. The constant r_s expresses an effect of void geometry on the
 5 amount of viscosity forces and represents the extent of the effect of void geometry on water retention.
 6 The size of this effect is equivalent to a specific surface area a_p , [L⁻¹] inside the porous media, that is,
 7 to a relation between 1) the surface of the solid grains that confronts the water flow and 2) the
 8 saturated void volume that transfers the flow driving force. Following the Hagen Poiseuille law, the
 9 specific surface area a_p [L⁻¹] is inversely proportional to the hydraulic radius R_H [L]. Thus, in an
 10 isotropic environment, $r_s \propto a_p^{-2}$, the permeability is given as follows:

$$k = \frac{n}{r_s} = C \frac{n}{a_p^2} = CnR_H^2 \quad (3)$$

11 where C represents the dimensionless coefficient of proportionality that is dependent on the particle
 12 shape. $R_H=1/a_p$ represents the hypothetical hydraulic radius of the porous media and the impact of the
 13 specific surface area of effective flow voids (Irmay, 1954).

14 3.2 Geometric parameters of permeability

15 There are four ways to express the specific surface area A_s [L²] based on solid volume, V_s [L³].
 16 They are as follows:

- 17 a_p [L⁻¹] – specific surface area based on the volume of contented pores V_p ;
- 18 a_T [L⁻¹] – specific surface area based on the total volume (solids + pores) V_T ;
- 19 a_m [L²M⁻¹] – specific surface area based on the mass of solids M_s ;
- 20 a_s [L⁻¹] – specific surface area based on the volume of solids V_s of density ρ_s

21 All of the above-mentioned forms of specific surface area are related to the hydraulic radius of porous
 22 media R_H . The relationship between these forms is given by the following expression:

$$a_p = \frac{A_s}{V_p} = \frac{a_T}{n} = \frac{\rho_s(1-n)}{n} a_m = \frac{(1-n)}{n} a_s = \frac{1}{R_H}. \quad (4)$$

23 Kozeny (1927) used Eq. (4) with a_T . He developed a theory for a bundle of capillary tubes of equal
 24 length. Carman (1937) verified the Kozeny equation and expressed the specific surface per unit mass
 25 of solid as $a_m=A_s/M_s$, such that it does not vary with porosity. Furthermore, Carman (1939) tried to
 26 consider the tortuosity of the porous media by introducing an angular deviation of 45° from the mean
 27 straight trajectory. He obtained the best fit from the experimental results with a factor $C=0,2$ in Eq.
 28 (3).

29 In hydrogeology, the specific surface area is often presented with a conversion of mean grain
 30 diameter D_m . Permeability is given by the following expression (Bear, 1972):

$$k = \frac{n^3}{180(1-n)^2} D_m^2 \quad (5)$$

31 This relation has been achieved by inserting the solid specific surface area ($a_s=6/D_m$) from Eq. (4) into
 32 Eq. (3) with $C=0,2$. This solution of the Kozeny-Carman equation (Bear, 1972) is given for uniform

1 sphere particles. Thus, the critical factors of porous media transmissivity are effective porosity n_e (in
 2 the form of porosity function) and referential mean grain diameter D_m . Grouping these terms
 3 functionally gives the following expression:

$$K = C \frac{n_e}{a_p^2} = \frac{n_e}{180} \left(\frac{n_e}{(1 - n_e)} D_m \right)^2 \quad (6)$$

4

5 Figure 3. Effects of driving (n) and drag resistance ($n^2/(1-n)^2$) factors in porosity function ($n^3/(1-n)^2$)

6

7 Evidently, the effective porosity n_e , has a direct impact on the magnitude of driving forces and
 8 an indirect impact as $n_e^2/(1-n_e)^2$ (Fig. 3) on the conversion of the specific surface value into a value of
 9 the referential mean grain diameter, which is the carrier of drag resistance. Both of the aforementioned
 10 forces affect the moving fluid. Therefore, effective porosity is an active factor only in relation to the
 11 pores through which the water flows.

12 3.3 Referential grain size

13 Many authors present the Kozeny-Carman equation with D_m^2 instead of a_s^2 in Eq. (5) without
 14 completely indicating the calculation of this equivalent mean diameter. In engineering practice, there
 15 are three ways to calculate the mean of the rated size of adjacent sieves:

16 Arithmetic: $d_{i,a} = (d_{i<} + d_{i>}) / 2$ (7)

17 Geometric: $d_{i,g} = \sqrt{d_{i<} \times d_{i>}}$ (8)

18 Harmonic: $d_{i,h} = 2 / [(1/d_{i<}) + (1/d_{i>})]$ (9)

19 where $d_{i<}$ [L] is the smallest grain and $d_{i>}$ [L] is the largest grain in the segment. It can be shown that
 20 $d_{i,h} < d_{i,g} < d_{i,a}$, across all cases. However, the difference is not significant. Todd (1959) recommends the
 21 use of the geometric mean. Bear (1972) prefers the harmonic mean. Recent authors often follow these
 22 recommendations.

23 The integration of all of the mentioned grain sizes (Eq(s) (7), (8), (9)) in the sieve residue
 24 across the entire sample has a crucial effect on the mean grain size value. An overview of both the
 25 related expert and scientific literature indicates the use of either the arithmetic mean:

$$D_a = \frac{\sum P_i d_{i,a}}{100} \quad (10)$$

26 or the harmonic mean:

$$D_h = \frac{100}{\sum (P_i / D_{i,h})} \quad (11)$$

27 which is the sum of mean grain sizes in sieve residue d_i . Here, P_i is a percentile of the sieve residue
 28 mass in the total mass of the sample. Accurate results of permeability and specific surface were only
 29 achieved for the uniform deposits of sand and silt (Chapuis & Aubertin, 2003), (Kasenow, 1997).
 30 Major errors resulted from applying Eqs. (10, 11) for samples with a wide range of particle sizes.
 31 Similar observations were noted in sedimentology and soil science research. Arkin and Colton (1956)
 32 noted that the arithmetic mean may be significantly distorted by extreme values and therefore may not
 33 be appropriate. For soil samples, Irani and Callis (1963) advocated the use of geometric rather than
 34 arithmetic statistical properties. The reason, in part, is that in a natural soil sample there is wide range
 35 of particle sizes making the geometrical scale much more suitable than the arithmetic scale. The

1 general mathematical expressions for calculating the geometric particle size diameter D_g of the sample
2 are as follows:

$$D_g = \text{EXP} \left[\frac{1}{M_s} \sum m_i \ln(d_{i,g}) \right] \quad (12)$$

3 or

$$D_g = \text{EXP} \left[0,01 \sum P_i \ln(d_{i,g}) \right] \quad (13)$$

4
5 where M [M] represents the mass of the sample and m_i [M] represents the mass of particular sieve
6 residues, $P_i = 100m_i/M$. It can be shown that $D_h < D_g < D_a$. This difference is very small when calculated
7 for uniform deposits but rapidly grows when calculated for the mean grain sizes of poorly sorted
8 deposits. In the case of gravelly sediments, the difference may reach up to 2 orders of magnitude.

1 3.4 Porosity factor

2 In a permeability model, the porosity function expressed by porous media transmissivity factors
3 (Eq. (6)) applies only to flow pores (Eq. (2)). Accordingly, it was named effective porosity. The
4 effective porosity could sometimes differ from the specific yield, which is a drainable porosity,
5 determined in a laboratory. The numerical difference between the effective porosity and the specific
6 yield may not be discernible when analyzing uniform sand, but it can increase significantly when
7 analyzing samples containing a greater percentage of small size (clay, silt) particles. Expressions of
8 specific yield functions of granulometric aggregates (Eckis, 1934) or median grain size (Davis & De
9 Wiest, 1966) are unsuitable in permeability equations (Eq. (6)) for two reasons. First, in these figures,
10 specific yield was not shown in relation to referential grain size (D_g). Second, the specific yield
11 represents the drainage in negative pressure conditions. Effective porosity represents the active pores
12 at the time of fluid flow for a sample of certain D_g , as shown in this paper. These relations were based
13 on the analysis of data from several samples of various deposits (from clay to gravel). The initial
14 values of porosity used in this procedure were ranges of an average specific yield value (Fig. (4)),
15 according to the data from the U.S. Geol. Survey Water Supply Paper (Morris & Johnson, 1967). The
16 laboratory reputation and a large number of analyses (33 samples of gravel, 287 of sand and 266 of silt
17 and clay) provided a high quality base for the identification of the mean value of a specific yield
18 range.

19
20 Figure 4. Range and arithmetic mean of the specific yield values for 586 analyses in Hydrol. Lab. of
21 the U.S. Geol. Survey (from Morris & Johnson, 1967)

22
23 The value of effective porosity is slightly lower than the value of the specific yield. This value
24 is related to the referential mean grain size (D_g), forming the function of drag resistance effect in the
25 water flow through a porous media (Eq. (6), Fig. (3)). The reliable reconstruction of the effective
26 porosity range (Fig. (5)) was ensured through the strong impact of the discussed form of the porosity
27 function ($n^3/(n-1)^2$) (Fig. (3)) and the accurate calculation of referential mean grain size (Eq. (12), Eq.
28 (13)). These relations simultaneously verified the applicability of the Kozeny-Carman equation for a
29 wide range of granulometric composition, in terms of both grain size (samples with D_g from 1.5 μm up
30 to 6 mm) and grade (Fig 5).

31
32 Figure 5. Relation between referential mean grain D_g and effective porosity n_e . Note: Dot line divides
33 uniform grain deposits $U=D_{60}/D_{10}<2$, and medium uniform grain deposit $2<U<20$. Verified samples
34 of non-uniform grain deposits of sand and gravel ($U>20$) lie below the full line

35 4 Results and verification

36 Reliable verification of the analyzed parameter relations for a wide range of granulometric
37 compositions was conducted using the Kozeny-Carman equation and the analyses of the hydraulic
38 conductivity researched deposits in situ as well as in the laboratory. Hydraulic conductivity K [LT^{-1}]
39 given by the KC equation (according to Eq. (6)) is:

$$K = \frac{\rho g}{\mu} \frac{n_e^3}{180(1-n_e)^2} D_m^2 = 0,0625 D_g^2 \frac{n_e^3}{(1-n_e)^2} \quad (14)$$

1 where ρ [ML⁻³] represents the density and μ [ML⁻¹T⁻¹] represents the viscosity of water, with gravity g
 2 [LT⁻²]. The coefficient 0.0625 is correct for a diameter of the referential mean grain D_g expressed in
 3 mm and a water temperature of 10°C. Hazen's (1892) non-dimensional temperature correction factor
 4 $\tau = 0.70 + 0.03T$ (T - temperature in °C) was used to present an effect of temperature difference,
 5 ensuring an error less than 2% for $T < 30^\circ\text{C}$.

6 The Kozeny-Carman equation is actually a special form of Darcy's law (in the case of the unit
 7 value of hydraulic gradient). Hence, it should be applicable across all possible natural samples of
 8 porous media. The hydraulic testing of natural deposits poses a problem in correlation investigations.
 9 Non-cohesive deposits make it almost impossible to ensure the laboratory testing of the content and
 10 distribution of particles or to consolidate material in its natural and undisturbed state. The average
 11 hydraulic conductivity calculated by analyzing the pumping test data was used for correlation in the
 12 non-cohesive deposits. Test sites were chosen to fulfill the following criteria: the borehole core must
 13 be of a 100% natural lithological compound, and the analysis of particle size distribution must be
 14 conducted on the core samples. If the exploration borehole was located in the vicinity of the tested
 15 well, the hydraulic conductivity of the local scale was used. If there were more boreholes at a greater
 16 distance from the pumped well, the hydraulic conductivity of a sub-regional scale was determined and
 17 used for correlation. Values of the predicted K appropriate to the test data scale, obtained from the
 18 grain size distribution analysis, were averaged. Silty and clayey samples were processed in a specific
 19 way. If a specific sample was analyzed in the laboratory (grain size analysis and hydraulic
 20 conductivity), the results were (both literally and functionally) on a laboratory scale.

21 The criteria for evaluating the acceptable accuracy of the predicted hydraulic conductivity,
 22 expressed by its correlation with a tested K value, should not be equal for different types of materials.
 23 Chapuis and Aubertin (2003) of the *École Polytechnique de Montréal* conducted a very interesting
 24 study. They concluded that the acceptable accuracy of a predicted value of K for clayey materials is
 25 between 1/3 and 3 times the measured K -value, which is within the expected margin of variation for
 26 the laboratory permeability test. That relation is referred to a calculation of K by the Kozeny-Carman
 27 equation using a specific surface area determined in the laboratory. Such criteria can definitely be an
 28 acceptable accuracy limit for calculating the K using referential grain size. In the case of silty, non-
 29 plastic soils, three specimens of the same sample may give K -values ranging between ½ and 2 times
 30 the mean value. An excellent precision (K -value within $\pm 20\%$) can be reached with sand and gravel
 31 when the special procedure is applied (Chapuis & Aubertin, 2003). These criteria were accepted for
 32 hydraulic conductivity calculations using the KC equation and applying the effective porosity and
 33 referential mean grain size. The accepted criteria require a high level of accuracy for determining the
 34 referential mean grain size and effective porosity in their roles in Eq. (14).

35 In the verification process, the results acquired using the KC equation were matched with the
 36 results of the hydraulic tests. The average local K -values of sandy aquifers were identified (pumping
 37 test data) and compared to the average sample K value. Verification of K -values for the gravelly
 38 aquifer is of a sub-regional scale because the boreholes that provided the high-quality core were
 39 located at a distance of 150 – 500 m from the pumped well. The tested value of hydraulic conductivity
 40 was determined by analyzing a series of successive steady states. The third case was of a laboratory
 41 scale where K -values of cohesive materials were analyzed. The hydraulic conductivity values of silty-
 42 clayey samples and the granulometric parameters were the results of the laboratory testing of each

1 sample. The criteria for correlating predicted and tested K-values were customized to these
2 procedures.

3 **4.1 Incohesive deposit**

4 The results of the calculation of hydraulic conductivity using the KC formula (Eq 14) for
5 individual samples of sand and gravel were presented graphically, according to borehole depths. The
6 average values of hydraulic conductivity for individual pilot fields are presented in the tables. In this
7 process, the arithmetic (D_a), geometric (D_g) and harmonic (D_h) forms of calculating the mean value of
8 grain size were used.

9 **4.1.1 Sandy aquifer**

10 The hydraulic conductivities of samples from various depths are presented for four distinctive
11 aquifers.

12 First, two aquifers are built of uniform, poorly graded mean to coarse grained sand (fig. 6)
13 lying on different depths. Second, two aquifers are built of well graded fine to mean grained sand (fig.
14 7), also lying on different depths.

15
16 Table 1. Average difference (%) between predicted and tested hydraulic conductivity for sandy
17 aquifers

18 Figure 6. Predicted hydraulic conductivity calculated using KC equation for samples from uniform
19 sandy aquifer ($K(D_{40}) - K$ calculated using effective grain size D_{40} , $K(D_a)$ - K calculated using
20 arithmetic mean grain size, $K(D_h)$ - K calculated using harmonic mean grain size, $K(D_g)$ - K calculated
21 using geometric mean grain size, K_t – tested hydraulic conductivity)

22 Figure 7. Predicted hydraulic conductivity calculated using KC equation for samples from sandy
23 aquifers with thin silty intercalations

24
25 Table 1 gives the average difference between the predicted and tested (pumping test) hydraulic
26 conductivities. In all cases, the overestimated value of hydraulic conductivity is a result of using the
27 arithmetic mean grain size in calculations. The underestimated values of hydraulic conductivity are a
28 result of using the harmonic mean grain size. The results are very close to tested value of hydraulic
29 conductivity because the geometric mean grain size was used in the KC formula. The applicability of
30 grain sizes according to the specific sieve size was also analyzed for median grain size value D_{50} and
31 smaller grain sizes. Using the median grain size value (D_{50}) resulted in the regular overestimation of
32 hydraulic conductivity, and using grain size D_{30} regularly underestimated hydraulic conductivity
33 (Table 1). An especially interesting fact is that the use of grain size D_{40} (Table 1, Fig. (6)) provided
34 remarkable results with practically negligible errors.

35 The analyses of samples from fine sandy aquifers with silty laminas (Fig. (7), Fig. (8)) resulted
36 in regularly underestimated K-values. The laminas of silt were so thin that it was not possible to
37 isolate the sand content in the samples (Fig. (8)).

38
39 Figure 8. Fine sand sample with thin silty intercalations - test field FS/SU1(Ravnik)

40

1 In such specific cases, grain size D_{40} or even D_{50} present hydraulic properties of sandy
2 deposits much better than the calculated mean grain size of the whole sample. Thin laminas of silt,
3 through which the horizontal flow is negligible, have a strong impact on the grain size distribution
4 curve. Yet, these distortions are considerably weaker if the referential geometric mean grain size, D_g
5 and not D_a or D_h is used in the calculations.

6 **4.1.2 Gravelly aquifer**

7 The predicted K-values of the gravelly aquifer were analyzed through the same procedures as
8 those of the sandy aquifer. Due to clarity, only K-values based on D_g , D_a , D_h and D_{40} (Table 2, Fig.
9 (9)) are presented. The extreme graduation of deposits is specific to this pilot field. These deposits
10 contain pebbles (of diameters up to 10 cm), sand and small amount of silt (uniformity $U = D_{60}/D_{10} =$
11 $17 - 262$).

12
13 Figure 9. Gravel core from 23 to 30 m depth from borehole SPB-3 – test field GW (Đurđevac) (see
14 fig. 10a)

15
16 A high-quality drilling core (Fig. 9) from six exploration boreholes and a particle size
17 distribution data analysis of relevant core samples was used. All of the boreholes were scattered
18 around the pumped well at test field GW. Borehole SPB-2 is situated on the border of the well field
19 where a part of an aquifer of sandy development is located, and hence, the data do not correspond to a
20 correlated average K-value. The predicted K-values of particular samples and two boreholes (SPB-3,
21 SPB-5) mean values are presented graphically in Fig. (10). The mean predicted $K(D_g)$ of borehole
22 SPB-3 (Fig. 10a) is only 10% smaller than the tested value. The core quality of this borehole is
23 presented by a core segment of depth from 23.0 m to 30.0 m (Fig. (9)).

24
25 Figure 10. Predicted hydraulic conductivity calculated using KC equation for samples from gravelly
26 aquifer (test field GW) – a) borehole SPB-3; b) borehole SP B-5

27
28 The highest deviation of the predicted $K(D_g)$ in relation to the tested K_t value was noted in the
29 borehole SPB-5 core. The average $K(D_g)$ value is 71% higher than K_t value. However, the most
30 important fact is that the geometric mean $K(D_g)$ of all boreholes (Table 2) in the tested area is only 5%
31 higher than K_t . Both values are of the same regional significance. Namely, $K(D_g)$ presents 1) the result
32 of total geometric mean size of all of the grains in the sample, 2) the hydraulic conductivity of all of
33 the samples in the borehole and 3) all of the boreholes on the test field. The tested hydraulic
34 conductivity K_t is identified by analyzing the series of successive cones of depression achieved in that
35 area during the long term pumping test. Conversely, $K(D_a)$ shows higher values by two orders of
36 magnitude and $K(D_h)$ shows lower values by three orders of magnitude. This shows the degeneration
37 of arithmetic algorithm for calculating mean grain size for a wide range of particle sizes.

38
39 Table 2. Average predicted hydraulic conductivities K (m/s) for boreholes in gravelly aquifer (test field
40 GW)

41 Table 3. Numerical results of correlations between tested K_t and predicted K for samples from test
42 fields in Croatia. and U.S. Geol. Survey laboratory

43

1 The correlation of hydraulic conductivity mean value results for referential grain sizes D_g , D_a ,
2 D_h and D_{40} and the tested mean hydraulic conductivity K_t on all pilot fields is presented graphically in
3 Fig. (11a). It is clear that the values of predicted hydraulic conductivity using the referent grain size D_g
4 closely correlate with the tested (K_t) value for all incohesive deposits, regardless of their uniformity.
5 Using D_a and D_h results in the overestimation and the underestimation of hydraulic conductivities,
6 respectively. This distortion significantly depends on the graduation of samples. When the sample is
7 poorly graded, distortion was negligible. In the cases of well graded samples, distortion reaches up to a
8 few orders of magnitude. A very high Pearson's coefficient of correlation (Fig 11 b, Table 3) confirms
9 the closeness of tested K_t values and the predicted hydraulic conductivity $K(D_g)$.

10
11 Figure 11. Graphical correlation between predicted K and tested K_t for sandy and gravely aquifers. (a)
12 Difference between arithmetic, geometric and harmonic mean grain size, (b) Results of correlation
13 between predicted $K(D_g)$ and tested K_t

14
15 From a practical point of view, an interesting fact is that very good results are achieved using
16 grain size D_{40} (Fig. 11a).

18 4.2 Cohesive deposit

19 The validities of the aquitard's predicted K-values was analyzed for 86 samples using the
20 geometric (D_g), arithmetic (D_a) and harmonic (D_h) mean grain sizes. The results of the correlation
21 between the predicted and laboratory tested hydraulic conductivities for the samples of cohesive
22 deposits are presented in Fig. (12a). The permeability test and grain size analysis were performed for
23 each individual sample. The samples were of various compounds of silty and clayey materials, and
24 their tested hydraulic conductivities have a wide range, exceeding three orders of magnitude (between
25 10^{-11} and 10^{-7} m/s). This wide range ensures reliable graphical and numerical correlations. These
26 results are similar to the results of previously explained analyses of non-cohesive deposits. The
27 arithmetic mean grain sizes result in overestimating $K(D_a)$, and the harmonic mean grain sizes result in
28 underestimating $K(D_h)$ (that is, average $K(D_a)/K_t$ equaled 14.5 and $K(D_h)/K_t$ equaled 0.17). Good
29 results were achieved using the referential geometrical mean grain size, and the predicted values of
30 hydraulic conductivity $K(D_g)$ were very close to the tested value K_t (within the set limits of the
31 accuracy criteria).

32
33 Figure 12. Graphical correlation between predicted K and tested K_t for silt and clay deposit. (a)
34 Difference between arithmetic, geometric and harmonic mean grain size, (b) Result of correlation
35 between predicted $K(D_g)$ and tested K_t

36
37 The graphical correlation (Fig. (12b)) illustrates concentrated $K(D_g)$ values in the neighborhood
38 of the tested value K_t , and most of the results are within the range $1/3K_t < K(D_g) < 3K_t$. The numerical
39 correlation confirms their high correlativity, $R^2=0.696$. This is a very high value, especially
40 considering the fact that some of deviations may be the result of an error in conducting the laboratory
41 permeability test. The achieved results confirm earlier conclusions that the total geometric mean grain
42 diameter D_g truly represents the referent mean grain size of the silty-clayey deposits. Additionally, it

1 was used as a reliable reference point for the verification of the porosity curve $n_e=f(D_g)$, presented in
2 Fig. (5).

3 **5 Discussion**

4 The Kozeny–Carman equation was limited to only calculating the hydraulic conductivity of
5 incohesive materials (Kasenow, 1997), (Kasenow, 2010). Additionally, the use of the KC equation for
6 calculating the hydraulic conductivities of cohesive materials using particle size has been frequently
7 disputed in numerous papers and reports. The reasons include varied particle size, high proportions of
8 fine fractions in deposits (Young & Mulligan, 2004), electrochemical reaction between the soil
9 particles and water and large content of particles such as mica (Carrier, 2003). All of these factors also
10 affect the effective porosity, and some of them also affect the mean grain size. Is the effect of the fore-
11 mentioned factors incorporated (and/or how much) in the size and distribution of effective porosities
12 and referential mean grain sizes?
13

14 Figure 13. Relation between of effects of mean grain size D_a , D_g and D_h on predicted hydraulic
15 conductivity for all analyzed samples
16

17 The conducted analyses, as graphically summarized in Fig. 13, confirmed that the use of 1)
18 geometric mean as a referent mean grain size (Eq. 12 or 13) and 2) effective porosity according to Fig.
19 (5) in the Kozeny–Carman equation forms a model of flow through the porous media. This model is
20 valid for various soil materials and mixtures with a wide range of hydraulic conductivity values (from
21 10^{-12} m/s up to 10^{-2} m/s). The use of the arithmetic mean D_a and the harmonic mean D_h result in the
22 overestimation and the underestimation, respectively, of the value of hydraulic conductivity. The
23 overestimated porosity is followed by the overestimated value of hydraulic conductivity. This can
24 have a huge impact on predicting the hydraulic conductivity of clayey-silty deposits, which are of very
25 high total porosity but very low effective porosity. Therefore, the use of total instead of effective
26 porosity in Eq (14) can lead to a misunderstanding regarding the validity of the harmonic mean grain
27 size for calculating the hydraulic conductivities of cohesive materials.

28 Pearson’s correlation analysis was conducted for the numerical and logarithmic values of
29 predicted hydraulic conductivities $K(D_g)$ of all of the samples, grouped in three basic data groups
30 (Table 3). These include non-cohesive materials (gravel and sand), cohesive materials (silt and clay),
31 and the group of all of the analyzed samples. The verification of the results for the non-cohesive
32 materials group was conducted for eight more samples from the USGS laboratory (Morris & Johnson,
33 1967). The verification of the results for cohesive materials was conducted by the analyses of two
34 more samples from the USGS laboratory. The correlation results of all of the $K(D_g)$ are presented in
35 Fig. (14).
36

37 Figure 14. Verification of graphical and numerical correlation between the tested K_t and the predicted
38 hydraulic conductivity $K(D_g)$ using referential geometric mean size for all samples
39

40 A separate sub-group was formed by the non-cohesive material data from all five CRO test
41 fields by using the referent grain size D_{40} . This correlation results in very high correlation coefficients.
42 The lowest values of the correlation coefficients were observed for the silty-clayey materials group,

1 but their values (in Table 3) certainly confirm the validity of the observed relations. It is very
2 important to note that the test data used in this research refer to standard, serial tests and that specific
3 tests may potentially result in even stronger correlations.

4 The graphical correlation between the tested and the predicted hydraulic conductivities (Fig.
5 (14)) illustrates the universality of the KC model (when applying referential mean grain size D_g and an
6 effective porosity n_e) in a wide range of flow conditions. The very high values of correlation
7 coefficients R^2 (Table. 3) confirm the relations in continuous porous media conditions on a laboratory
8 scale.

9 6 Conclusions

10 The following conclusions can be drawn from this study:

11 1. The geometric mean size of all particles contained in the sample D_g unambiguously
12 affects the permeability and specific surface area of cohesive and non-cohesive deposits,
13 regardless of the grain size and distribution of specific particles. Hence, D_g represents the
14 referential grain size of the sample.

15 2. The distribution of effective porosities in functions of the referential grain size $n_e =$
16 $f(D_g)$ is presented graphically for all types of clastic deposits. The graph was constructed
17 following previously reported data and was calibrated according to the congruence between
18 the tested hydraulic conductivity and its predicted value calculated by applying the Kozeny-
19 Carman equation. Thus, this effective porosity presents the flow porosity and is slightly lower
20 than the specific yield commonly referred to the literature.

21 3. The successful application of the KC flow model confirms its validity in a range of
22 hydraulic conductivities between 10^{-12} and 10^{-2} m/s. Simultaneously, the value of effective
23 porosity and its relative referential grain size D_g in a range of 1.5 μm to 6 mm has been
24 verified. It can be concluded that, through the presented parameters, the range of applying the
25 Kozeny-Carman model for calculating permeability and specific surface area is extended up to
26 the limits of Darcy's law validity.

27 4. The value of the referent mean grain size in cases of analyzed non-cohesive samples is
28 very close to the value of the grain size D_{40} (read from grain size distribution curve).

29
30 Acknowledgments:

31 The authors would like to thank Ms. Željka Brkić, Ph.D, Mr. Željko Miklin and Ms. Ivana
32 Žunić Vrbanek for their perseverance and help in collecting large amounts of laboratory data used in
33 this study. This study was supported by the Ministry of Science, Education and Sports of the Republic
34 of Croatia (Basic Hydrogeological Map of the Republic of Croatia 1:100.000 - basic scientific project
35 of Croatian Geological Survey)

1 References

- 2 Al-Tabbaa, A., & Wood, D. (1987). Some measurements of the permeability of kaolin. *Geotechnique*,
3 37, 499-503.
- 4 Arkin, H., & Colton, R. (1956). *Statistical methods*. 4th ed. New York: Barnes & Noble Inc.
- 5 Bear, J. (1972). *Dynamics of Fluid in Porous Media*. New York: Elsevier.
- 6 Bear, J., Zaslavsky, D., & Irmay, S. (1968). *Physical Principles of Water Percolation and Seepage* (
7 Publ. No. XXXIX ed.). Paris: UNESCO, Arid Zone Research,.
- 8 Blake, F. C. (1922). The resistance of packing to fluid flow. *Transactions of the American Institute of*
9 *Chemical Engineers*, 14, str. 415-421.
- 10 Boadu, F. K. (2000). Hydraulic conductivity of soils from grain-size distribution: New Models.
11 *Journal of Geotechnical and Geoenvironmental Engineering*, Vol. 126 No 8, 739-746, Vol. 126
12 No 8, str. 739-746.
- 13 Brkić, Ž., Larva, O., & Urumović, K. (2010). The quantitative status of groundwater in alluvial
14 aquifers in norther Croatia. (M. Horvat, Ed.) *Geologia Croatica, Journal of the Croatian*
15 *Geological Survey nad the Croatian Geological Society*, 63, pp. 283-298.
- 16 Carman, P. C. (1937). Fluid flow through granular beds. *Transactions*, str. 150-166.
- 17 Carman, P. C. (1939). Permeability of saturated sand, soil and clay. *Journal of Agricultural Science*,
18 29, str. 263-273.
- 19 Carrier, W. D. (2003, November). Goodbye, Hazen; Hello, Kozeny-Carman. *Journal of Geotechnical*
20 *and Geoenvironmental Engineering*, 129, No 11, pp. 1054-1056.
- 21 Chapuis, R. P., & Aubertin, M. (2003). *Predicting the coefficient of permeability of soils using the*
22 *Kozeny-Carman equation*. Montreal: Département des génies civil, géologique et des mines.
23 École Polytechnique de Montréal.
- 24 Chapuis, R., & Légaré, P.-P. (1992). A Simple Method for Determining the Surface Area of Fine
25 Aggregates and Fillers in Bituminous Mixtures. *In Effects of aggregates and mineral filters*
26 *on asphalt mixture performance ASTM STP 1147* (pp. 177-186). ASTM.
- 27 Cheng, C., & Chen, X. (2007). Evaluation of methods for determination of hydraulic properties on an
28 aquifer-aquitard system hydrologically connected to river. *Hydrogeol. J.*, pp. 669-678.
- 29 Davis, S. N., & De Wiest, R. J. (1966). *Hydrogeology*. New York: John Wiley & Sons.
- 30 Dolinar, B., & Otoničar, M. (2007). Evaluation of permeability of saturated clays based on their
31 physical properties. *Geologija*, 50(2), 487-49.
- 32 Eckis, R. (1934). *South Coastal Basin investigation, geology, and ground water storage capacity of*
33 *valley fill*. Sacramento: California Division of Water Resources Bulletin 45.
- 34 Fair, G., & Hatch, L. (1933). Fundamental factors governing the stream-line flow of water through
35 sand. *Journal of American Water Works Association*, 18, str. 1551-1565.
- 36 Freeze, R., & Cherry, J. (1979). *Groundwater*. Engelwood Cliffs, New Jersey: Prentice-Hall, Inc.,.
- 37 Hantush, M. S. (1964). *Hydraulics of wells*. New York: Academic Press.
- 38 Hazen, A. (1892). *Some Physical Properties of Sands and Gravels, With Special Rreference to Their*
39 *Use in Filtration*. Massachusetts State Board of Health.
- 40 Hubbert, M. K. (1956). Darcy's law and the field equations of the flow of underground fluids.
41 *Petroleum Transactions, AIME(207)*, pp. 222-239.
- 42 Irani, R., & Callis, C. (1963). *Particle Size: Measurement, Interpretation and Application*. New York:
43 John Wiley & Sons.

- 1 Irmay, S. (1954). On the hydraulic conductivity of unsaturated soils. *Transactions, American*
2 *Geophysical Union*.
- 3 Kamann, P. J., Ritzi, R. W., David, D. F., & Conrad, C. M. (2007, July - August). Porosity and
4 Permeability in Sediment Mixtures. *Groundwater*, 45, pp. 429-438.
- 5 Kasenow, M. (1997). *Applied ground-water hydrology and well hydraulics*. Highlands Ranch,
6 Colorado: Water Resources Publications, LLC.
- 7 Kasenow, M. (2010). *Determination of hydraulic conductivity from grain size analysis*. Highlands
8 Ranch, Colorado: Water Resources Publications, LLC.
- 9 Koch, K., Kemna, A., Irving, J., & Hollinger, K. (2011). Impact of changes in grain size and pore
10 space on the hydraulic conductivity and spectral induced polarization response of sand.
11 *Hydrol. Earth Syst. Sci.*, 15, pp. 1785-1794.
- 12 Koltermann, C. E., & Gorelick, S. M. (December 1995). Fractional packing model for hydraulic
13 conductivity derived from sediment mixtures. *Water Resources Research*, str. 3283-3297.
- 14 Kovács, G. (1981). *Seepage hydraulics*. Amsterdam: Elsevier Science Publishers.
- 15 Kozeny, J. (1927). Über Kapillare Leitung des Wassers im Boden. pp. 271-306.
- 16 Krüger. (1918). Die Grundwasserbewegung. U *Internationale Mitteilungen für Bodenkunde* (Svez. 8,
17 str. 105).
- 18 Mavis, F. T. (1936). *A study of the permeability of sand*. Iowa City: State University of Iowa.
- 19 Morris, D., & Johnson, A. (1967). *Summary of Hydrologic and Physical Properties of Rock and Soil*
20 *Materials, as Analyzed by the Hydrologic Laboratory of U.S. Geological Survey 1948-60*.
21 Washington: U.S. Geological Survey.
- 22 Odong, J. (2008). Evaluation of Empirical Formulae for Determination of Hydraulic Conductivity
23 based on Grain-Size Analysis. *The Journal of American Science*, str. 1-6.
- 24 Slichter, C. S. (1902). *The Motions of Underground Waters* (Water Supply and Irrigation Paper izd.).
25 U.S. Geological Survey.
- 26 Terzaghi, K. (1925). Principles of Soil Mechanics. *Engineering News - Record*(Vol. 95), str. 19-
27 23, 25-27, pp. 742-746, 796-800, 832-836, 874-878, 912-915, 987-990, 1026-1029, 1064-
28 1068.
- 29 Todd, D. K. (1959). *Ground Water Hydrology*. New York: John Wiley & Sons.
- 30 Urumović, K. (2013, July). Parameter quantification of clastic sediments hydrogeologic properties
31 based on test fields in northern Croatia. *Dissertation, unpubl.*, 164. Zagreb, Croatia: University
32 of Zagreb, RGNf.
- 33 Urumović, S. K. (2003). *Physical Principles of Groundwater Dynamics (in croatian)*. Zagreb: Faculty
34 of Mining, Geology and Oil Engineering.
- 35 Vukovic, M., & Soro, A. (1992). *Determination of hydraulic conductivity of porous media from grain*
36 *size composition*. Littleton, Colorado: Water Resources Publications.
- 37 Young, R. N., & Mulligan, C. N. (2004). *Natural Attenuation of Contaminants in Soils*. Boca Raton:
38 Lewis Publishers.
- 39 Zunker, F. (1920). Das allgemeine Grundwasserfließgesetz. *J. Gasbel. u. Wasserversorg.*, 63, str. 332.

40

41

1 Table 1. Average difference (%) between predicted and tested hydraulic conductivity for sandy
 2 aquifers

	Variety of equivalent grain size	Diameter form grain-size distribution curves			Mean grain size			Tested K_t (m/s)	Kind of sand
		$K(D_{30})$	$K(D_{40})$	$K(D_{50})$	$K(D_a)$	$K(D_h)$	$K(D_g)$		
Well fields	SU-1	-16,5	-0,1	+14,3	+48,5	-9,1	+15,8	$2,55 \cdot 10^{-4}$	Medium uniform
	SU-2	-37,1	-1,4	+32,9	+48,7	-13,6	+9,9	$2,78 \cdot 10^{-4}$	
	FS/SU-1	-23,5	+1,5	+26,3	+48,3	-76,0	-21,1	$1,16 \cdot 10^{-4}$	Fine to medium
	FS/SU-2	-48,8	-27,3	-4,9	+38,3	-48,9	-12,8	$1,40 \cdot 10^{-4}$	
	Average	-31,5	-6,8	+17,2	+46,0	-36,9	-2,1		

3

4

1 Table 2. Average predicted hydraulic conductivity K (m/s) for boreholes in gravely aquifer (test field
 2 GW)

Bore- hole	$K(D_g)$		$K(D_a)$		$K(D_h)$		$K(D_{40})$		Tested K_f (m/s)
	Geom.	Aritm.	Geom.	Aritm.	Geom.	Aritm.	Geom.	Aritm.	
SPB-1	2,5E-03	3,5E-03	5,5E-02	5,8E-02	6,6E-06	8,7E-06	1,1E-03	2,4E-03	1,8E-03
SPB-3	1,6E-03	2,5E-03	5,9E-02	6,4E-02	2,2E-06	3,3E-06	6,4E-04	1,6E-03	
SPB-4	1,3E-03	2,2E-03	4,3E-02	4,9E-02	1,4E-06	1,8E-06	5,1E-04	1,1E-03	
SPB-5	3,0E-03	4,2E-03	5,5E+02	5,6E-02	5,7E-06	8,3E-06	1,6E-03	4,6E-03	
SPB-6	1,2E-03	1,4E-03	2,6E-02	2,8E-02	2,2E-06	2,4E-06	7,1E-04	8,8E-04	
Aver.	1,8E-03	2,6E-03	2,9E-01	4,9E-02	3,1E-06	4,0E-06	8,4E-04	1,8E-03	
K/K_t	1,02	1,47	163	28	0,0017	0,0023	0,48	1,01	

3


4

1 Table 3. Numerical results of correlations between tested K_r and predicted K for samples from test
 2 fields in Croatia. and U.S. Geol. Survey laboratory

Samples from	Materials	Referential mean grain size	Mark	Pearson's correlation coefficients			
				Nominal values		Log values	
				R	R ²	R	R ²
CRO test fields	Gravel, sand	D_g	R ₁	0,999	0,998	0,988	0,976
	Gravel, sand	D_{40}	R ₂	1,000	1,000	0,995	0,991
Togeather CRO + USGS lab.	Gravel, sand	D_g	R ₃	0,997	0,994	0,993	0,985
CRO test fields	Silt, clay	D_g	R ₄	0,740	0,547	0,834	0,696
	Gravel, sand, silt,clay	D_g	R ₅	1,000	0,999	0,971	0,942
All togeather CRO+USGS lab.	Gravel, sand, silt,clay	D_g	R ₆	0,997	0,995	0,985	0,971

3


4



1

2 Figure 1. The map of Northern Croatia with test sites locations


3



1

2 Figure 2. Definition sketch of liquid driving and opposed viscous forces for elemental volume


3



1

2 Figure 3. Effects of driving (n) and drag resistance ($n^2/(1-n)^2$) factors in porosity function ($n^3/(1-n)^2$)


3



1

2 Figure 4. Range and arithmetic mean of specific yield values for 586 analyses in Hydrol. Lab. of the
 3 U.S. Geol. Survey (from Morris & Johnson, 1967)


4



1

2 Figure 5. Relation between referential mean grain D_g and effective porosity n_e . Note: Dot line divides
 3 uniform grain deposits $U=D_{60}/D_{10}<2$, and medium uniform grain deposit $2<U<20$. Verified samples
 4 of non-uniform grain deposits of sand and gravel ($U>20$) lie below the full line


5



1

2 Figure 6. Predicted hydraulic conductivity calculated using KC equation for samples from uniform
 3 sandy aquifer ($K(D_{40})$ – K calculated using effective grain size D_{40} , $K(D_a)$ - K calculated using
 4 arithmetic mean grain size, $K(D_h)$ - K calculated using harmonic mean grain size, $K(D_g)$ - K calculated
 5 using geometric mean grain size, K_t – tested hydraulic conductivity)

6



1

2 Figure 7. Predicted hydraulic conductivity calculated using KC equation for samples from sandy
 3 aquifers with thin silty intercalations

4



1

2 Figure 8. Fine sand sample with thin silty intercalations - test field FS/SU1 (Ravnik)


3



1

2 Figure 9. Gravel core from 23 to 30 m depth from borehole SPB-3 – test field GW (Đurđevac) (see
3 fig. 10a)


4



1

2 Figure 10. Predicted hydraulic conductivity calculated using KC equation for samples from gravely
 3 aquifer (test field GW) – a) borehole SPB-3; b) borehole SP B-5



4



1

2 Figure 11. Graphical correlation between predicted K and tested K_t for sandy and gravelly aquifers. (a)
 3 Difference between arithmetic, geometric and harmonic mean grain size, (b) Results of correlation
 4 between predicted $K(D_g)$ and tested K_t

5




1

2 Figure 12. Graphical correlation between predicted K and tested K_t for silt and clay deposits. (a)

3 Difference between arithmetic, geometric and harmonic mean grain size, (b) Result of correlation

4 between predicted $K(D_g)$ and tested K_t


5



1

2 Figure 13. Relation between of effects of mean grain size D_a , D_g and D_h on predicted hydraulic
 3 conductivity for all analyzed samples

4



1

2 Figure 14. Verification of graphical and numerical correlation between the tested K_t and the predicted
 3 hydraulic conductivity $K(D_g)$ using referential geometric mean size for all samples

4