- **1** Processing and performance of topobathymetric LiDAR
- 2 data for geomorphometric and morphological

3 classification in a high-energy tidal environment

4

M.S. Andersen¹, Á. Gergely¹, Z. Al-Hamdani², F. Steinbacher³, L.R. Larsen⁴,
 V. B. Ernstsen¹

7 [1] Department of Geosciences and Natural Resource Management, University of8 Copenhagen, Denmark

9 [2] Geological Survey of Denmark and Greenland, Denmark

- 10 [3] Airborne Hydro Mapping GmbH, Austria
- 11 [4] NIRAS, Denmark
- 12 Correspondence to: V. B. Ernstsen (vbe@ign.ku.dk)
- 13

14 Abstract

15 The transition zone between land and water is difficult to map with conventional 16 geophysical systems due to shallow water depth and often challenging environmental 17 conditions. The emerging technology of airborne topobathymetric Light Detection And 18 Ranging (LiDAR) is capable of providing both topographic and bathymetric elevation 19 information, using only a single green laser, resulting in a seamless coverage of the 20 land-water transition zone. However, there is no transparent and reproducible method 21 for processing green topobathymetric LiDAR data into a Digital Elevation Model 22 (DEM). The general processing steps involve data filtering, water surface detection and 23 refraction correction. Specifically, the procedure of water surface detection and 24 modelling, solely using green laser LiDAR data, has not previously been described in 25 detail for tidal environments. The aim of this study was to fill this gap of knowledge by 26 developing a step-by-step procedure for making a Digital Water Surface Model 27 (DWSM) using the green laser LiDAR data. The detailed description of the processing 28 procedure augments its reliability, makes it user friendly and repeatable. A DEM was

obtained from the processed topobathymetric LiDAR data collected in spring 2014 from 1 2 the Knudedyb tidal inlet system in the Danish Wadden Sea. The vertical accuracy of the LiDAR data is determined to ± 8 cm at a 95% confidence level, and the horizontal 3 4 accuracy is determined as the mean error to ±10 cm. The LiDAR technique is found capable of detecting features with a size of less than 1 m^2 . The derived high resolution 5 DEM was applied for detection and classification of geomorphometric and 6 7 morphological features within the natural environment of the study area. Initially, the 8 Bathymetric Positioning Index (BPI) and the slope of the DEM were used to make a 9 continuous classification of the geomorphometry. Subsequently, stage (or elevation in 10 relation to tidal range) and a combination of statistical neighbourhood analyses (moving 11 average and standard deviation) with varying window sizes, combined with the DEM 12 slope were used to classify the study area into six specific types of morphological 13 features (i.e. subtidal channel, intertidal flat, intertidal creek, linear bar, swash bar and 14 beach dune). The developed classification method is adapted and applied to a specific 15 case, but it can also be implemented in other cases and environments.

16

17 **1** Introduction

18 The coastal zone is under pressure from human exploitation in many and various ways. 19 Many large cities are located near the coast, and they grow gradually with the increase 20 in worldwide population and urbanization. Many industrial activities take place in close 21 vicinity to the coast, e.g. fishery, construction, maintenance dredging for safety of navigation, and mining for raw materials. The coastal zone also provides the setting for 22 23 many recreational and touristic activities, such as sailing, swimming, hiking, diving and 24 surfing. In addition to human exploitation, climate change also poses a future threat 25 with a predicted rising sea level and increasing storm intensity and frequency, expected 26 to cause erosion and flooding in the coastal zone (Mousavi et al., 2011). All these 27 pressures and different interests underpin the societal need for high resolution mapping, 28 monitoring, and sustainable management in the coastal zone.

Historically, the transition zones between land and water have been difficult or even impossible to map and investigate in high spatial resolution due to the difficulties in collecting data in these challenging, high-energy environments. The airborne near-

infrared (NIR) Light Detection And Ranging (LiDAR) is a technique often used for
measuring high-resolution topography, however, NIR laser is incapable of measuring
bathymetry due to the absorption and reflection of the laser light at the water surface.
Traditionally, high-resolution bathymetry is measured with a multibeam echosounder
(MBES) system mounted on a vessel, but it does not cover the bathymetry in the
shallow water due to the vessel draft limitation.

7 NIR LiDAR and MBES are applied in different environments; however, the data are 8 very similar and the processed high-resolution topography/bathymetry is often captured, 9 visualised and analysed in a Digital Elevation Model (DEM). The processed DEM may 10 be applied for various purposes, e.g. for geomorphological mapping. Previous studies 11 classifying morphology in either terrestrial or marine environments have been performed numerous times (Al-Hamdani et al., 2008; Cavalli and Marchi, 2008; Hogg 12 13 et al., 2016; Höfle and Rutzinger, 2011; Ismail et al., 2015; Kaskela et al., 2012; 14 Lecours et al., 2016; Sacchetti et al., 2011). These classification studies generally focus 15 on either the marine or the terrestrial environment and do not cover the fine-scale 16 morphology in the shallow water, due to the challenging environmental conditions. To 17 overcome this impediment a new generation of airborne green topobathymetric LiDAR 18 that enables high resolution measurements of both topography and shallow bathymetry 19 has been introduced (Guenther, 1985; Jensen, 2009; Pe'eri and Long, 2011). The 20 potential of merging morphological classifications of marine and terrestrial 21 environments enables a holistic approach for managing the coastal zone.

22 The raw topobathymetric LiDAR measurements are spatially visualized as points in a 23 point cloud, with each point containing information of its location and elevation. The 24 point cloud must be piped through a series of steps before it can be visualised as a 25 DEM. Most of the processing steps required to process raw topobathymetric LiDAR data into a DEM are similar to the processing steps of topographic LiDAR data (Huising 26 27 and Gomes Pereira, 1998). However, additional processing steps are required for topobathymetric LiDAR data due to the refraction of the laser beam at the water 28 29 surface. All submerged LiDAR points have to be corrected for refraction; therefore, the water depth must be known for each point. This sets a requirement for making a Digital 30 31 Water Surface Model (DWSM), before the refraction correction can be performed.

Often the water surface is detected and modelled from simultaneous collection of green 1 2 and NIR LiDAR measurements, where the green laser reflects from the seabed and the NIR laser reflects from the air-water interface, and the NIR laser data are then used to 3 4 detect and model the water surface (Allouis et al., 2010; Collin et al., 2008; Guenther, 2007; Parker and Sinclair, 2012). The use of NIR LiDAR data for water surface 5 detection has been applied in several studies. For instance, Hofle et al. (2009) proposed 6 7 a method for mapping water surfaces based on the geometrical and intensity information 8 from NIR LiDAR data. Su and Gibeaut (2009) classified water points from NIR LiDAR 9 based on point density, intensity and elevation. They identified the shoreline based on 10 the large sudden decrease in NIR LiDAR intensity values when going from land to 11 water. Brzank et al. (2008) used the same three variables (point density, intensity and 12 elevation) in a supervised fuzzy classification to detect the water surface in a section of 13 the Wadden Sea. Another study in the Wadden Sea by Schmidt et al. (2012) used a 14 range of geometric characteristics as well as intensity values to classify water points 15 from NIR LiDAR data.

16 The capability of NIR LiDAR data for detecting the water surface is thus well 17 documented. However, deriving all the information from a single green LiDAR dataset 18 would be a more effective solution for water surface and seabed detection, with respect 19 to the financial expenses and for the difficulties of storing and handling often very large 20 amounts of data. However, there is no definitive method for making a DWSM from 21 green topobathymetric LiDAR data. For this purpose, the Austrian LiDAR company 22 RIEGL have developed a software, *RiHYDRO* (RIEGL, 2015), in which it is possible to 23 model the water surface in a two-step approach: 1) Classification of water surface points based on areas with two layers (water surface and seabed) and extending the 24 25 classification to the entire water body, and 2) Generation of a geometric gridded DWSM 26 for each flight swath based on the classified water surface points. However, RiHYDRO 27 is commercial software, and thus the algorithms, which form the basis of the 28 classification and water surface modelling, are not publicly available. Other software 29 packages, such as HydroFusion (Optech, 2013) and LiDAR Survey Studio (Leica, 2015), 30 also proclaim to have incorporated methods for the entire data processing workflow, but 31 the algorithms in these software packages are also closed and cannot be accessed by 32 public users.

Only few research studies have investigated the potential of water surface detection and 1 2 modelling from green LiDAR data. In a relatively recent publication Guenther et al. (2000) even regarded water surface detection from green LiDAR data as unacceptable 3 4 and they justified it with two fundamental issues: 1) No water surface returns are 5 detected in the dead zone, and 2) Uncertainty of the water surface elevation, because the green water surface returns are actually a mix of returns from the air/water interface and 6 7 from volume backscatter returns, and they are generally found as a cloud of points 8 below the water surface. Mandlburger et al. (2013) addressed the second issue by 9 comparing the water surface points of NIR and green LiDAR data, and they concluded 10 that it is possible to derive the water surface elevation from the green LiDAR data with 11 sub-decimetre vertical precision relative to a reference water surface derived by the NIR 12 LiDAR data. However, their work addressed only the determination of the water surface 13 elevation, without going into detail on the actual procedure of generating a DWSM. An 14 approach for modelling the water surface from green LiDAR data was presented by 15 Mandlburger et al. (2015), who did their study in a riverine environment with only few 16 return signals from the water surface. Their method was based on manual estimates of 17 the water level in a series of river cross sections, after which interpolation between the 18 cross sections filled out the gaps with no water surface points to derive a continuous 19 water surface model.

The aim of this study was to investigate the potential of improving the procedure of processing green LiDAR data and generating DEMs in tidal environments, and of improving the classification of morphological units in such environments. More specifically, the objectives were:

- To develop a robust, repeatable and user friendly processing procedure of raw
 green LiDAR data for generating high resolution DEMs in land-water transition
 zones.
- 27 2. To quantify the accuracy and precision of the green LiDAR data based on object28 detection.
- 3. To automatically classify morphological units based on geomorphometricanalyses of the generated DEM.

The investigations were based on studies undertaken in a section of the Knudedyb tidalinlet system in the Danish Wadden Sea.

2 2 Study area

1

The Knudedyb tidal inlet system is located between the barrier islands of Fanø and Mandø in the Danish Wadden Sea (Fig. 1A). The tidal inlet system is a natural environment without larger influence from human activity. The tides in the area are semi-diurnal, with a mean tidal range of 1.6 m, and the tidal prism is in the order of $175 \cdot 10^6 \text{ m}^3$ (Pedersen and Bartholdy, 2006). The main channel is approximately 1 km wide and with an average water depth of approx. 15 m (Lefebvre et al., 2013).

9 The study site is an elongated 3.2 km^2 (0.85 × 4 km) section of the Knudedyb tidal inlet 10 system (Fig. 1B). The section is located perpendicular to the main channel and stretches 11 across both topography and bathymetry. The study site extends towards north into an 12 area on Fanø with dispersed cottages (Fig. 1C). The most prominent morphological 13 features within the study site include beach dunes (Fig. 1D), small mounds (Fig. 1E), 14 swash bars (Fig. 1F-G) and linear bars (Fig. 1H).

15

16 3 Methods

17 3.1 Topobathymetric LiDAR

18 The topobathymetric LiDAR technique is based on continuous measurements of the 19 distance between an airplane and the ground/seabed. The distance (or range) is 20 calculated by half the travel time of a laser beam, going from the airplane to the surface 21 of the earth and back to the airplane. The wavelength of the laser beam is in the green spectrum, usually 532 nm, since this wavelength is found to attenuate the least in the 22 23 water column, resulting in the largest penetration depth of the laser (Jensen, 2009). In 24 literature, topobathymetric LiDAR data is sometimes referred to as either bathymetric 25 LiDAR or Airborne LiDAR bathymetry. These are different terms with the same 26 meaning, and in this paper, topobathymetric LiDAR is preferred, since it describes the 27 system's ability to simultaneously measure bathymetry as well as topography.

A single laser beam may encounter many targets of varying nature on its way from the airplane and back again, and different processes are influencing the laser beam propagation through air and water. First, the laser beam may be reflected by targets in 1 the air, such as birds or dust particles, and these can show up as LiDAR points in the 2 space between the airplane and the surface. When encountering water, the speed of the 3 laser decreases from 3×10^8 ms⁻¹ to e.g. 2.25×10^8 ms⁻¹ in 10°C freshwater or e.g. 2.24 4 $\times 10^8$ ms⁻¹ in 10°C saltwater of 30 PSU (Millard and Seaver, 1990).

5 The changing speed of the laser beam also affects the direction of the laser beam when
6 penetrating the water surface with an angle different from nadir (Fig. 2) (Guenther,
7 2007; Jensen, 2009). The laser beam will be refracted according to Snell's Law:

$$8 \quad \frac{\sin a_{\text{air}}}{\sin a_{\text{water}}} = \frac{c_{\text{air}}}{c_{water}} = \frac{n_{\text{water}}}{n_{\text{air}}} \tag{1}$$

9 where α_{air} is the incidence angle of the laser beam relative to the normal vector of the 10 water surface and α_{water} is the refraction angle in water. n_{water} and n_{air} are the 11 refractive indices of water and air, respectively (Mandlburger et al., 2013).

The penetration depth in water is limited by the attenuation of the laser beam. Water molecules, suspended sediment and dissolved material all act on the laser beam by absorption and scattering, resulting in substantial reduction in power as the signal propagates into the water (Guenther, 2007; Mandlburger et al., 2013; Steinbacher et al., 2012). The laser beam also diverges in the water column, resulting in a wider laser beam footprint (Guenther et al., 2000), and this effect reduces the resolving capability of fine-scale morphology the deeper the laser beam penetrates.

19 The returned signal is represented as a distribution of energy over time, also called the 20 'full-waveform' (Alexander, 2010; Chauve et al., 2007; Mallet and Bretar, 2009). The 21 peaks in the full-waveform are detected as individual targets encountered by the 22 propagating laser beam. If the laser hits two targets with a small vertical difference, 23 such as a water surface and seabed in very shallow water, then the two peaks in the full-24 waveform may merge together, resulting in the detection of only one target (Fig. 2). 25 This results in a detection minimum of successive returns from a single laser pulse, 26 referred to as the 'dead zone' (Mandlburger et al., 2011; Nayegandhi et al., 2009). The 27 dead zone is a clear limitation to the LiDAR measurements, which is an important 28 parameter to consider in very shallow water, such as intertidal environments.

1 **3.2** Surveys and instruments

LiDAR data and ortophotos were collected by Airborne Hydro Mapping GmbH (AHM)
during two surveys on 19 April 2014 and 30 May 2014.

4 On 19 April 2014, the quality of the LiDAR data was validated at two sites along Ribe
5 Vesterå River (Fig. 1I-J):

Validation site 1 with a 2.50 × 1.25 × 0.80 m cement block located on land next
 to the mouth of Ribe Vesterå River (Fig. 1I). The block was covered by 7 swaths
 retaining 227 LiDAR points from the block surface, which were used for
 assessing the accuracy and precision of the LiDAR data.

10 Validation site 2 with a $0.92 \times 0.92 \times 0.30$ m steel frame located in the Ribe 11 Vesterå River, its top situated just below the water surface (Fig. 1J). The frame 12 was covered by 4 swaths retaining 46 LiDAR points from the surface of the 13 frame, which were used for precision assessment, and for testing the feature 14 detection capability of the LiDAR system. According to the International Hydrographic Organization survey standards, cubic features of at least 1 m^2 15 16 should be detectable in Special Order areas, which are areas with very shallow 17 water as in the study site (IHO, 2008).

18 Ground control points (GCPs) were measured for the four corners of the block with 19 accuracy better than 2 cm using a Trimble R8 RTK GPS. Measurements were repeated 20 three times and averaged to minimize errors caused by measurement uncertainties. 21 GCPs were also collected for the frame; however, during the LiDAR survey the frame 22 experienced an unforeseen intervention by local fishermen using the frame as fishing platform. Therefore, the frame was only used to assess the deviation between the 23 24 LiDAR points (the precision), and not to assess the deviation between the LiDAR points 25 and the GCP's (the accuracy).

On 30 May 2014, the study site was covered by 11 swaths, which were used for generating the DWSM and DEM. The overflight was carried out during low tide, and the water level was measured to -1 m DVR90 at Grådyb Barre, approx. 20 km NW of the study site. 1 The weather conditions were similar during the two surveys, with sunny conditions, 2 average wind velocities of 7-8 m/s (DMI, 2014) and significant wave heights, measured west of Fanø at 15 m water, of approx. 0.5 m coming from NW (DCA, 2014). However, 3 the waves in the less exposed Knudedyb tidal inlet were observed in the 30 May LiDAR 4 5 point cloud to be 0.2-0.3 m, which can be explained by the location of the study site in lee of the western most intertidal flats and the ebb-tidal delta. The wave heights in the 6 7 rest of the study site (flood channel and intertidal ponds) were in the scale of sub 8 decimetres. There were no waves at validation site 2 during the 19 April LiDAR survey.

9 LiDAR data were collected with a RIEGL VQ-820-G topobathymetric airborne laser 10 scanner in both surveys (RIEGL, 2014). The scanner was characterized by emitting 11 green laser pulses with 532 nm wavelength and 1 ns pulse width. It had a very high laser pulse repetition rate of up to 520,000 Hz. The flying altitude was 400 m, which 12 13 combined with a beam divergence of 1 mrad created a laser beam footprint of 40 cm 14 diameter at the ground. The high repetition rate and narrow footprint made it well suited 15 to capture fine-scale landforms (Doneus et al., 2013; Mandlburger et al., 2011). An arc shaped scan pattern results in a swath width of approx. 400 m, while maintaining an 16 17 almost constant 20° ($\pm 1^{\circ}$) incidence angle of the laser beam when penetrating the water 18 surface (Niemeyer and Soergel, 2013). The typical water depth penetration of the laser 19 scanner is claimed by the manufacturer to be 1 Secchi disc depth (RIEGL, 2014).

For each returned signal, the collected LiDAR data contained information of x, y and z, as well as a GPS time stamp and values of the amplitude, reflectance, return number, attribute and laser beam deviation (RIEGL, 2012).

23 **3.3** Processing raw topobathymetric LiDAR data into a gridded DEM

The essential processing steps, which are standard procedure when processing
topobathymetric LiDAR data, were followed to produce a DEM in the study area. These
steps included:

- 27 1. Determination of flight trajectory.
- 28 2. Boresight calibration: Calculating internal scanner calibration.
- 29 3. Collecting topobathymetric LiDAR data.

- 4. Swath alignment based on boresight calibration: The bias between individual
 swaths was minimized.
- 5. Filtering: The raw data contained noise located both above and below ground,
 which needed to be filtered from the point cloud.
- 6. Water surface detection: A DWSM had to be established in order to correct for
 refraction in the following step.
- 7 7. Refraction correction: All the points below the water surface in the DWSM were8 corrected for the refraction of the laser beam.
- 9 8. Point cloud to DEM: The points were transformed into a gridded elevation
 10 model representing the real world terrain in the study area, including cottages
 11 and vegetation on Fanø in the northern part.

12 Step 1 and 2 were performed prior to the LiDAR survey. The different instruments 13 (LiDAR, IMU and GPS) were integrated spatially by measuring their position relative 14 to each other, when mounted on the airplane, and temporally by calibrating their time 15 stamps.

16 Step 3 was the actual LiDAR survey and step 4 was the initial processing step after the 17 LiDAR survey. The bias between the swaths was minimized in the software 18 RiPROCESS (RIEGL LMS) by automatically searching for planes in each swath and 19 then matching the planes between the swaths.

20 Steps 5-8 represent the processing of the point cloud into a DEM. The methods involved 21 in these steps are the main focus in this study and they are described in detail in the 22 following sub-sections. Each swath was pulled individually through the processing 23 workflow to account for the continually changing water level in the study area due to tides. The broad term "DEM" is used, rather than the more specific terms "Digital 24 25 Terrain Model (DTM)" or "Digital Surface Model (DSM)", because the generated 26 model includes both natural terrain in the tidal environment, which is the main focus 27 area in this study, as well as vegetation and cottages on Fanø.

28 **3.3.1 Filtering**

29 The raw LiDAR data contained noise in the air column originating from the laser being 30 scattered by birds, clouds, dust and other particles, and noise was also appearing below 1 the ground/seabed (Fig. 3A-B). This noise had to be filtered before further processing.

2 The filtering process involved both automatic and manual filtering.

3 The automatic filtering was carried out in HydroVish (AHM) with the tool Remove flaw 4 echoes (Fig. 3C). The filtering tool was controlled by three variable parameters: search 5 radius, distance and density. The search radius parameter specified the radius of a 6 sphere in which the distance and density filters were utilized. The distance parameter 7 rejected a point, if it was too far from any other point within the sphere. The density 8 parameter specified the lower limit of points within the sphere. The automatic filter 9 iterated through all the points in the point cloud. The settings for the automatic filtering 10 were based on a sensitivity analysis of three fragments of the LiDAR data, and the 11 settings were selected so that a minimum of valid points were removed by the automatic 12 filter. The settings were: Search radius = 1 m, distance = 0.75 m and density = 4.

The automatic filter could not to remove two layers of noise points closely above and below ground, but on the other hand, more widely dispersed points in the deeper bathymetry were removed. To account for this, the point cloud went through manual filtering in Fledermaus (QPS) software, where the remaining noise points were rejected and the valid bathymetric points were accepted (Fig. 3D).

18 The filtered point cloud (with water points) was used in the following step to detect the 19 water surface. Meanwhile, a copy of the data was undergoing additional manual 20 filtering, removing all the water points (Fig. 3E). After this final filtering step, there 21 were only points representing topography, bathymetry, vegetation and man-made 22 structures left in the dataset.

23 **3.3.2 Water surface detection**

The water surface detection was based on determining the water surface *elevation* and the water surface *extent*, thereby producing a DWSM. The water surface elevation was determined based on the water surface points, and the extent was determined by extrapolating the water surface until it intersected the surface of the topography. Two assumptions were made in the production of the DWSM:

The water surface was horizontal. This was a simplification of the real world.
 Tidal processes and wind- and wave-setup may cause the water surface to be

1 sloping, and the water is often topped by more or less significant waves. A linear 2 fit through the water surface LiDAR points along the main channel, showed a 3 changing water level of 0.13 m over a distance of 400 m, corresponding to a 0.325×10^{-3} (0.019 deg.) sloping water surface. A similar fit through the LiDAR 4 points along the flood channel showed a slope of 0.156×10^{-3} (0.009 deg.). The 5 maximum wave heights observed in the main channel were 20-30 cm. Based on 6 7 the moderate slope of the water surface and relatively low wave height, the 8 water surface was assumed flat. This assumption is deemed error prone, but at 9 the time of this study, it was our best estimate.

10 2. The study area contained water bodies with two different water levels: One 11 represented the water level in the main channel and the other represented the 12 water level in the flood channel. This was also a simplification, as the tidal flat 13 contained small ponds with potentially different water levels. However, almost 14 all of these ponds contained no LiDAR points of the water surface, which means 15 that the water depth in the ponds must have been within the limitation of the 16 dead zone. Therefore, it was impossible to detect individual water surfaces in the 17 ponds.

18 A series of processing steps were performed to produce the DWSM. The first step was 19 to extract a shallow surface and a deep surface from the filtered point cloud (with water points) in Fledermaus (Fig. 3F). Both surfaces consisted of 0.5×0.5 m cells, and the 20 21 elevation of each cell was equal to the highest point within the cell (shallow surface) 22 and the lowest point within the cell (deep surface), respectively. The shallow surface 23 should then display the topography along with the water surface, whereas the deep 24 surface should display the topography and the seabed (as long as the seabed was 25 detected by the laser). It is worth noting, that the extraction of the shallow surface and 26 the deep surface had nothing to do with the final DEM, as they were merely 27 intermediate steps performed for the water surface detection.

The following steps were focused on the shallow surface to determine the elevation of the water surface (Fig. 3G). First, the shallow surface was down-sampled to a surface with a cell size of 2×2 m, and the new cells were populated with the maximum elevation of the input cells. The down-sampling was done for smoothing the water surface, and thereby eliminating most of the outliers. The exact cell size of 2×2 m, as

1 well as populating them with the maximum value, was chosen based on the work by 2 Mandlburger et al. (2013). They compared water surface detection capability between green LiDAR data, collected with the same RIEGL-VQ-820-G laser scanner, and NIR 3 4 LiDAR data, which was assumed to capture the true water surface. They found that the 5 green LiDAR generally underestimated the water surface elevation, but that reliable results were achieved by increasing the cell size and only taking the top 1-5% of water 6 7 points into account. According to their work, it was assumed that placing the water 8 surface on the highest points in 2 m cells provided a good estimate of the true water 9 level. However, based on their results it could be expected that the water surface 10 elevation in this case would be underestimated in the order of 2-4 cm.

11 The water-covered areas in the main channel and the flood channel were manually 12 extracted from the newly down-sampled shallow surface. The average elevation of the 13 2 m cells within each area was calculated, and these values constituted the elevation of 14 the water surfaces in the main channel and in the flood channel, respectively. Two 15 horizontal water surfaces were created in the flood channel and the main channel with a 16 cell size of 0.5×0.5 m and cell values equal to the calculated water surface elevations. 17 The high spatial resolution of 0.5 m cells was chosen to produce a detailed DWSM 18 along the edges of the land-water transition.

Finally, the extent of the water surfaces was determined by subtracting the deep surface
cell elevations from the water surface elevation and discarding all cells with resulting
negative values (Fig. 3H), together forming the DWSM.

22 **3.3.3 Refraction correction**

The refraction correction of all the points below the DWSM was calculated in HydroVish (AHM). The input parameters were the filtered point cloud (without water points), the derived DWSM and the trajectory data of the airplane. The refraction correction was calculated automatically for each point based on the water depth, the incident angle of the laser beam, and the refracted angle according to Snell's Law (Eq. 1 and Fig. 3I).

1 3.3.4 Point cloud to DEM

2 After iterating through the processes of filtering, water surface detection and refraction 3 correction for all the individual swaths, the LiDAR points of all swaths were combined. 4 The transformation from point cloud into a DEM was performed with ArcGIS (ESRI) 5 software. The DEM was created as a raster surface with a cell size of 0.5×0.5 m, and 6 each cell was attributed the average elevation of the points within the cell-boundaries. It 7 was chosen to make the resolution of the DEM lower than the laser beam footprint size 8 (i.e. 40 cm), due to the inaccuracies arising from attributing smaller cells with measured 9 elevation values spanning across a larger area. Furthermore, the 0.5 m cell size was 10 chosen to get as high resolution as possible without making any significant interpolation 11 between the measurements. In this way, each cell represented actually measured 12 elevations instead of interpolated values. However, there were still very few gaps of 13 individual cells with no data in the resulting raster surface in areas with relatively low 14 point density. Despite of the general intention of avoiding interpolation it was chosen to 15 populate these cells with interpolated values to obtain a full coverage DEM (except for 16 the bathymetric parts beyond the maximum laser penetration depth). The arguments for 17 interpolation were that: 1) the interpolated cells were scattered and represented only 1.7 18 % of all the cells, 2) they were found primarily on the tidal flat where the slope is 19 generally less than 1°, meaning that the elevation difference from one cell to a 20 neighbouring cell is usually less than 1 cm, and 3) the general point density in most of 21 the study area was so high that the loss of information by lowering the DEM resolution 22 would represent a larger sacrifice than interpolating a few scattered cells. The 23 interpolation was performed by assigning the average value of all neighbouring cells to 24 the empty cells. The final DEM was thereby fully covering the topography, and the 25 bathymetry was covered down to a depth equal to the maximum laser penetration depth.

26

3.4 Accuracy and precision of the topobathymetric LiDAR data

The term a*ccuracy* refers to the difference between a point coordinate (in this case a LiDAR point) compared to its "true" coordinate measured with higher accuracy, e.g. by a total station or a differential GPS; while the term *precision* refers to the difference between successive point coordinates compared to their mean value, i.e. the repeatability of the measurements (Graham, 2012; Jensen, 2009; RIEGL, 2014). Two "best-fit planes" based on the LiDAR points on the block and the frame surfaces were established with the *Curve Fitting tool* in MATLAB (MathWorks). We propose the use of these two planes to give an indication of the relative precision of the LiDAR measurements.

5 Another best-fit plane was established based on the block GPS measurements, and this 6 plane was regarded as the "true" block surface for assessment of the accuracy of the 7 LiDAR measurements. The established planes were described by the polynomial 8 equation:

9
$$z(x, y) = a + bx + cy$$
 (2)

10 where x, v and z are coordinates and a, b and c are constants. Inserting x and y 11 coordinates for the LiDAR surface points in Eq. (3) led to a result of the corresponding 12 elevation (z) as projected on the fitted plane. The difference between the elevation of 13 the LiDAR point and the corresponding elevation on the fitted plane was used as a 14 measure of the vertical accuracy (for the GCP fitted plane of the block) and the vertical 15 precision (for the LiDAR point fitted plane of the block and the frame). Statistical 16 measures of the standard deviation (σ), mean absolute error (E_{MA}), and root mean 17 square error (E_{RMS}) were calculated by:

18
$$\sigma = \sqrt{\frac{\sum (z_i - z_{\text{plane}})^2}{n-1}}$$
(3)

19
$$E_{\rm MA} = \frac{\Sigma |z_{\rm l} - z_{\rm plane}|}{n} \tag{4}$$

$$20 E_{\rm RMS} = \sqrt{\frac{\sum (z_{\rm j} - z_{\rm plane})^2}{n}} (5)$$

where z_i is the elevation of the measured LiDAR points, z_{plane} is the corresponding elevation on the best-fit plane, and *n* is the number of LiDAR points. The vertical accuracy and precision were determined at a 95% confidence level based on the accuracy standard presented in *Geospatial Position Accuracy Standards Part 3: National Standard for Spatial Data Accuracy* (NSSDA) (FGDC, 1998):

26
$$C_{95\%} = E_{\rm RMS} \cdot 1.96$$
 (6)

1 The horizontal accuracy was determined as the horizontal mean absolute error $(E_{MA,xy})$ 2 based on the horizontal distances between the block corners, measured with RTK GPS, 3 and the best approximation of the block corners derived from the LiDAR points of the 4 block surface. The minimum distance between a block corner and the perimeter of the 5 LiDAR points was regarded as the best approximation. Hereafter $E_{MA,xy}$ was calculated 6 as the average of the four corners.

7 **3.5** Geomorphometric and morphological classifications

8 The processed DEM was applied in two classification analyses; first a *geomorphometric* 9 classification and then a morphological classification. Both were based on the DEM and 10 derivatives of the DEM, but they differentiated by the resulting classification classes, 11 which showed 1) Surface geometry and 2) Surface morphology. The analysis mode, as 12 defined by Pike et al. (2009), was "general" in the geomorphometric classification where the surface geometry was continuously classified within the study site, while 13 14 being "specific" in the morphological classification where discrete morphological units 15 were classified. The northern part of the study site with cottages on Fanø was excluded 16 in the classification analyses, as the objective of this work was to classify the natural 17 terrain (geomorphometry and morphology) in the high-energy and dynamic tidal 18 environment.

19 **3.5.1** Geomorphometric classification analysis

20 The tool Benthic Terrain Modeler (BTM) (Wright et al., 2005) was used for the 21 geomorphometric classification. The tool is an extension to ArcGIS Spatial Analyst, 22 originally used for analysing MBES data (Diesing et al., 2009; Lundblad et al., 2006; 23 Rinehart et al., 2004). The BTM classification tool uses fine- and broad-scale 24 Bathymetric Positioning Indexes (BPIs) (Verfaillie et al., 2007) in a multiple-scale 25 terrain analysis to classify fine- and broad-scale geometrical features. The BPIs are 26 measures of the elevation of a cell compared to the elevation of the surrounding cells 27 within the determined scale (radius) size. Positive BPI values indicate a higher elevation 28 than the neighbouring cells and negative BPI values indicate a lower elevation than the 29 neighbouring cells. For instance, a BPI value of 100 corresponds to 1 standard deviation 30 and a value of -100 corresponds to -1 standard deviation of the cell elevation compared

to the elevation of the surrounding cells within the determined scale size. BPI values
 close to zero are derived from flat areas or from constant slopes.

3 The elevation values of each cell in the DEM were exaggerated by a factor of 10 before 4 the classification, to enable the BTM to detect the shapes of the terrain. The fine- and 5 broad-scales were determined based on the BPI results for different radius sizes. The 6 best results were obtained from a broad-scale BPI of 100 m radius and a fine-scale BPI 7 of 10 m radius, based on visual inspection. The fine- and broad-scale BPIs were used, 8 together with the slope of the actual DEM (not the exaggerated) to classify the 9 investigated area into the geomorphometric classes: Fine-scale crests, broad-scale 10 crests, depressions, slopes and flats (Fig. 4). The classification classes were decided 11 based on previous studies using the BTM classification tool with success (Diesing et al., 12 2009; Lundblad et al., 2006). The thresholds for the fine- and broad-scale BPIs were in 13 previous studies often defined as 1 standard deviation (Lundblad et al., 2006; Verfaillie 14 et al., 2007), however, thresholds of 0.5 standard deviations have also previously been 15 applied (Kaskela et al., 2012). We used a low threshold of 0.5 standard deviations due 16 to the generally very gentle variations in the terrain geometry of the tidal inlet system. 17 We defined the threshold between slopes and flats as 2°. This definition was a 18 compromise between detecting as many slopes as possible but avoiding too many "false 19 slopes" being detected along the swath edges, which seemed to be a consequence of 20 lower precision at the outer beams of the swath, as well as differences between 21 overlapping swaths.

22 **3.5.2** Morphological classification analysis

23 A morphological classification was developed for delineating actual morphological 24 features in the study area. The classification was built partly on different neighbourhood 25 analyses and slopes derived from the DEM, and partly on the local tidal range. Broadscale crests from the geomorphometric classification were also incorporated in the 26 27 analysis. Figure 5 describes the steps performed in ArcGIS, which led to the classification of 6 morphological classes: Swash bars, linear bars, beach dunes, 28 29 intertidal flats, intertidal creeks and subtidal channels. All the criteria for defining a 30 particular morphological class had to be fulfilled for a cell to be classified into that class. Cells that did not meet the criteria to be classified into any of the morphological
 classes were assigned the class "unclassified".

33 years of continuous measurements of the water level at Havneby on Rømø, 25 km
south of the study area, showed a mean low water level of -0.94 m (DVR90) and a mean
high water of 0.94 m (DVR90) (Klagenberg et al., 2008). Although the tidal range in
Knudedyb was probably slightly different, it was the best estimate for the study site.
Therefore, these water levels were used to separate between the supratidal, intertidal and
subtidal zones.

9 Subtidal channels were defined as everything below the mean low water, which was -10 0.94 m. A "smooth DEM" was created, in which each cell of the original DEM was assigned the average elevation value of its surrounding cells in a window size of 11 12 100×100 m (actually 199×199 cells, i.e. 99.5×99.5 m). The result was subtracted from the original DEM, creating an Elevation Change Model (ECM), which made it 13 14 possible to extract information about the deviation of the cells in the DEM compared to 15 its surrounding cells. The principle is similar to the BPI, and again the purpose was to 16 locate cells, with a higher/lower elevation than its surrounding cells. Positive values 17 were higher cells and negative values were lower cells. Certain thresholds were found 18 suitable for classifying beach dunes (> 0.8 m) and intertidal creeks (< -0.3 m). These 19 two classes were furthermore classified into their respective tidal zones (supratidal and 20 intertidal) based on the elevation. Intertidal flats were classified by low slope values (< 21 1°) of a down-sampled 2 m DEM (each down-sampled cell was assigned the mean 22 value of its 4×4 original cells). Moreover, to be classified as a flat, the ECM had to be 23 within ± 10 cm to avoid any incorrect intertidal flat classification of flat crests on top of 24 bars or flat bottoms inside creeks or channels. The BTM classification class "broad-25 scale crests" was used as an input, since it was found to capture bar features. However, the thresholds used in the BTM classification resulted in capturing features larger than 26 27 bars in the broad-scale crests class. To distinguish between bars and larger features, the standard deviation of each DEM cell in a moving window size of 250×250 m (actually 28 249×249 cells, i.e. 124.5×124.5 m) was calculated. A suitable threshold to distinguish 29 30 between bars and larger features was 0.6 standard deviations. Finally, swash bars and 31 linear bars were identified by an area/perimeter-ratio, based on the assumption that linear bars have smaller ratio than swash bars, due to the different shapes. Based on
 visual interpretation, a ratio of 4 was found to be a suitable threshold.

3

4 4 Results

5 4.1 Refraction correction and dead zone extent

6 The vertical adjustment of the LiDAR points (z_{diff}) due to refraction correction is 7 linearly correlated with the water depth (*d*) (Fig. 6). An empirical formula is derived for 8 this relationship:

9
$$z_{\text{diff}} = 0.227 \cdot d$$
, $R^2 = 0.997$ (7)

A LiDAR point at 1 m water depth is vertically adjusted by approximately 0.23 m (Fig.
6). The variations around the linear trend in Fig. 6 are due to changing incidence angles
of the laser beam that varies with the airplane attitude (roll, pitch and yaw).

The vertical extent of the dead zone is approx. 28 cm, determined by plotting the vertical difference between the shallowest and the deepest LiDAR point within 0.5 m cells – i.e. between the shallow surface and the deep surface (Fig. 7). The difference is manifested by an abrupt change at the dead zone, and the highest rate of change is shown to be at a water depth of approx. 28 cm.

18 **4.2** Sub-decimetre accuracy and precision

The vertical root mean square error of the LiDAR data is ± 4.1 cm, and the accuracy is ± 8.1 cm with a 95% confidence level (Table 1 and Fig. 8A). The vertical precision of the LiDAR data with a 95% confidence level is ± 3.8 cm for the points on the frame, and ± 7.6 cm for the points on the block (Table 1).

The horizontal accuracy calculated as the horizontal mean absolute error ($E_{MA,xy}$) is determined to ±10.4 cm (Fig. 8B).

25 **4.3** Point density and resolution

The average point density is 20 points per m^2 , which equals an average point spacing of 20 cm (Table 2). The point density of the individual swaths varies between 7-13 points

1 per m^2 , and the point density of the combined swaths in the study area, varies between 2 0-216 points per m^2 , although above 50 points per m^2 are rare.

3 4.4 DEM and landforms

4 The elevations in the studied section of the Knudedyb tidal inlet system range from -4 5 m DVR90 in the deepest parts of the flood channel and main channel to 21 m DVR90 on top of the beach dunes on Fanø (Fig. 9). Beach dunes and cottages of the village 6 Sønderho are clearly visible in the northern part of the study site (Fig. 9A-B). The 7 8 intertidal zones are generally flat, while the most varying morphology is found in the 9 area of the flood channel (Fig. 9C-D), and in the area close to the main channel (Fig. 10 9E-F). The flood channel is approximately 200 m wide in the western part and it divides 11 into two channels towards east. The bathymetry of the channel bed is clearly captured 12 by the LiDAR data in the eastern part, and also in the western part down to -4 m DVR90, which approximately equals a water depth of 3 m at the time of survey. An 13 14 intertidal creek joins the flood channel from the north (Fig. 9D). From the flood channel 15 towards south, the tidal flat is vaguely upward sloping, until reaching two distinct swash 16 bars, which are rising 0.9 m above the surrounding tidal flat, reaching a maximum 17 elevation of 1.5 m DVR90 (Fig. 9E-F). Further south, the linear bars along the margin 18 of the main channel are clearly captured in the DEM (Fig. 9E).

19 **4.5** Geomorphometric and morphological classifications

20 The geomorphometric and morphological classifications show that most of the study 21 area is located in the intertidal zone, and is mostly flat. This is manifested by the 22 dominating two classes; flats and intertidal flats (Fig. 10A-B). The geomorphometric 23 classification identifies slopes as stripes with NNW-SSE directionality across the flats. 24 These are following the direction of the survey lines, and thus, they are not real 25 morphological features but more an indication of lower precision of the LiDAR data, 26 especially at the outer beams of the swath. These swath artefacts are smoothed out in the 27 morphological classification by down-sampling the DEM to 2 m resolution, and 28 therefore, the intertidal flats appear uniform and seamless. The bar features close to the 29 main channel are well defined in the geomorphometric classification where they are 30 classified as broad-scale crests and fine-scale crests surrounded by slopes. In the

morphological classification, these are identified based on neighbourhood analyses and 1 2 separated by the area/perimeter-ratio into two classes, swash bars and linear bars (Fig. 10C). Broad-scale crests are also found on Fanø in the northern part of the area, and 3 4 most of these are classified as beach dunes in the morphological classification. The 5 geomorphometric classification identifies more broad-scale crests along the banks of the flood channel, however, these are not real bar features but they are identified as crests 6 7 due to the nearby flood channel and creeks resulting in a positive broad-scale BPI. In 8 the morphological classification it is possible to distinguish between these and the actual bar features, by looking at elevation deviations at an even broader scale than the broad-9 10 scale BPI. The intertidal creek in the NWern part of the area is a mix of depressions, 11 slopes and fine-scale crests in the geomorphometric classification, whereas it is 12 relatively well defined and properly delineated in the morphological classification (Fig. 13 10D).

14 The geomorphometric classification identifies slopes along the banks of the main 15 channel, flood channel and the intertidal creek, as well as in front of the beach dunes and along the edges of the swash bars and linear bars. The slopes seem particularly 16 reliable at delineating the features in the intertidal zone, i.e. swash bars, linear bars and 17 18 creeks. Depressions are primarily identified in the deepest detected parts of the main 19 channel and in the flood channel, in the intertidal creek and in the beach dunes. Fine-20 scale crests are found in the geomorphometric classification in locations which are high 21 compared to its near surroundings. They are primarily seen as parts of the linear bars 22 close to the main channel, in the beach dunes on Fanø and along the banks of the 23 intertidal creeks.

A few small circular mounds of approx. 5 m diameter with patches of *Spartina Townsendii* (Common Cord Grass) located on the intertidal flat are classified as finescale crests in the geomorphometric classification (Fig. 11). It clearly shows the capability of capturing fine-scale features in the DEM and in the derived classification.

1 5 Discussion

2 **5.1** Performance of the water surface detection method

The water surface in topobathymetric LiDAR surveys is most often detected from NIR LiDAR data, which is simultaneously collected along with the green LiDAR data (Collin et al., 2012; Guenther et al., 2000; Parker and Sinclair, 2012; Wang and Philpot, 2007). However, detecting the water surface and generating a DWSM based on the green LiDAR data alone provides a potential to perform topobathymetric surveys with just one sensor, thus optimizing the survey costs as well as data handling and storage.

9 The two critical issues risen by Guenther et al. (2000), as mentioned in the introduction, 10 concerning the water surface detection with green LiDAR were thoroughly investigated 11 in this study. The first issue, regarding the gap of detected water surface signals in the 12 dead zone, is addressed by detecting the water surface based on areas which are known 13 to be covered by water, and thereafter extending the water surface until it intersects the 14 topography, so that also the dead zone is covered by the modelled water surface. The 15 second issue, regarding uncertainty in the water surface elevation determination, is 16 addressed using the results presented by Mandlburger et al. (2013) who found a 17 statistical relationship between the cloud of water surface points in the green LiDAR 18 data and the water surface elevation derived from NIR LiDAR data. Mandlburger et al. 19 (2013), however, did not describe the actual method of modelling a DWSM, which is 20 done in this study. Mandlburger et al. (2015), on the other hand, did propose a method 21 for modelling the water surface, however, it was done in a fluvial environment and the 22 water level was based on manual determinations of cross sectional water levels. The 23 water surface detection method in this study is thus new in combining the properties: 1) 24 It is only using green LiDAR data, 2) it is based on automatic water level determination, 25 3) it is applied in a tidal environment (can be applied in any coastal environment) and 4) 26 it is transparent and repeatable due to the detailed description of data processing steps 27 given in the text.

The developed water surface detection method is new but it must be pointed out that the assumption of a flat DWSM leaves room for improvements for the future, especially if it is applied in a fluvial environment. Assuming a flat water surface is indeed a simplification of the real world, since the water surface in reality can be inclined, and itcan be topped by waves.

3 **5.2** Implications of the dead zone

4 The vertical extent of the dead zone is in this study determined to approx. 28 cm (Fig. 7), which means that no return signal is detected from the water surface when the water 5 depth is less than 28 cm. The implication of the dead zone along the channel edges is 6 minimised by extending the DWSM until it intersects the topography, but the setting is 7 8 different for the small ponds on the intertidal flats. They may have different water levels 9 than in the large channels, but no detected water surface points, since the water depth in 10 the ponds are generally less than the vertical extent of the dead zone, i.e. approx. 28 cm. 11 The presented method is not capable of detecting a water surface in these ponds, which 12 means that the bottom points of the ponds are not corrected for refraction. Omitting 13 refraction correction of a 28 cm deep pond will result in -6 cm elevation error according 14 to the calculated refraction (Fig. 6).

15 **5.3** Evaluation of the topobathymetric LiDAR data quality

The vertical accuracy of conventional topographic LiDAR data has previously been 16 17 determined to ±10-15 cm (Hladik and Alber, 2012; Jensen, 2009; Klemas, 2013; Mallet and Bretar, 2009). Only few previous studies have focused on the accuracy of shallow 18 19 water topobathymetric LiDAR data (Mandlburger et al., 2015; Nayegandhi et al., 2009; Steinbacher et al., 2012). Nayegandhi et al. (2009) determined the vertical E_{RMS} of 20 LiDAR data in 0-2.5 m water depth to $\pm 10-14$ cm, which is above the ± 4.1 cm $E_{\rm RMS}$ 21 22 found in this study (Table 1). Steinbacher et al. (2012) compared topobathymetric 23 LiDAR data from a RIEGL VQ-820-G laser scanner with 70 ground-surveyed river cross sections, serving as reference, and found that the system's error range was $\pm 5-10$ 24 cm, which is comparable to the ± 8.1 cm accuracy found in this study. Mandlburger et 25 26 al. (2015) compared ground-surveyed points from a river bed with the median of the 27 four nearest 3D-neighbors in the LiDAR point cloud, and they found a standard 28 deviation of 4.0 cm, which is almost equal to the ± 4.1 cm standard deviation found in 29 this study (Table 1). In comparison with these previous findings of LiDAR accuracy,

1 the assessment of the vertical accuracy in this study indicates a good quality of the

2 LiDAR data.

3 Mapping the full coverage of tidal environments, such as the Wadden Sea, requires a 4 combination of topobathymetric LiDAR to capture topography and shallow bathymetry 5 and MBES to capture the deeper bathymetry. The two technologies make it possible to 6 produce seamless coverage of entire tidal basins; however, merging the two products 7 raises the question whether the quality of the data from the two different sources is 8 comparable. Comparing the LiDAR accuracy with previous findings of accuracy 9 derived from MBES systems indicates similar or slightly better accuracy from the 10 MBES systems (Dix et al., 2012; Ernstsen et al., 2006). Dix et al. (2012) determined the 11 vertical accuracy of MBES data by testing the system on different objects and in 12 different environments, and found the vertical $E_{\rm RMS}$ to be ±4 cm. Furthermore, they 13 tested a LiDAR system on the same objects and found a similar vertical E_{RMS} of ±4 cm. 14 The vertical E_{RMS} of ±4.1 cm found in this study is very close to both the MBES 15 accuracy and LiDAR accuracy determined by Dix et al. (2012). Another study by 16 Ernstsen et al. (2006) determined the vertical precision of a high-resolution shallow-17 water MBES system based on 7 measurements of a ship wreck from a single survey 18 carried out in similar settings as the present study, namely in the main tidal channel in 19 the tidal inlet just north of the inlet investigated in this study. They found the vertical 20 precision to be ± 2 cm, which is slightly better than the vertical precision of ± 3.8 cm 21 (frame) and ±7.6 cm (block) found in this study. Overall, accuracy and precision are 22 within the scale of sub decimetres for both topobathymetric LiDAR and MBES systems, 23 which enables the mapping of tidal basins with full coverage and with comparable 24 quality.

Due to technical and logistical reasons, the data validation and the actual survey were carried out on different days and in different locations. Based on this, it is a fair question to ask, whether the determined quality actually represents the quality of the data within the study site. Differences between the determined data quality at the validation sites and the data quality at the study site may arise from 1) different environmental conditions on the two surveying days and/or 2) different environments at the validation sites compared to the study site. 1 The environmental conditions were similar on the two surveying days (as mentioned in 2 the section "Surveys and instruments"), meaning that the different days are not affecting 3 the representation of the data quality within the study site.

The environmental differences between validation site 2 and the study site include the presence of up to 0.2-0.3 m waves in the main channel next to the study site. The waves introduce a source of error, because the proposed water surface detection method is not modelling the waves. The precision of the seabed points within the study site are therefore expected to be worse than the ± 3.8 cm precision determined at validation site 2.

10 The water clarity/turbidity impacts the accuracy of the LiDAR data negatively, due to scattering on particles in the water column, which causes the laser beam to spread 11 12 (Kunz et al., 1992; Niemeyer and Soergel, 2013). Moreover, part of the light is reflected 13 in the direction of the receiver, and such return signals can be difficult to distinguish 14 from the seabed return (Kunz et al., 1992). The turbidity was measured at validation site 2 and in the flood channel close to the study site during the 19 April survey by 15 16 collecting water samples and subsequently analysing the samples for suspended sediment concentration (SSC) and organic matter content (OMC). The analyses showed 17 18 that the average SSC was higher in the flood channel (17.2 mg/kg) than in the river 19 (10.2 mg/kg). In contrast, the average OMC was lower in the flood channel (25.5 %) 20 than in the river (40.0 %). These observations indicate that 1) the underwater precision 21 is assessed in a location with higher turbidity than the environment within the study site; 22 therefore, the turbidity cannot be a cause of lower precision in the study site, and 2) the 23 penetration depth seems to be controlled by the OMC rather than by the SSC. This is 24 new knowledge, since no previous studies (from what we know) have investigated the 25 relative effect of organic matter as opposed to inorganic matter on the laser beam penetration depth. However, in order to determine the relationship with statistical 26 27 confidence, a more comprehensive study is needed, involving measurements of penetration depth at different SSCs and OMCs, and without disturbance from other 28 29 environmental parameters.

5.4 Spatial variations of topobathymetric LiDAR data quality

2 The quality of spatial datasets is often provided as single values, such as ± 8.1 cm for the 3 vertical accuracy in this case, and then the determined value represents the 4 accuracy/precision of the whole dataset. However, in reality the value is only a measure 5 of the local quality at the location where the assessment is conducted. The quality of the 6 dataset varies spatially, and one way to illustrate this is to extract the maximum vertical 7 difference between the LiDAR points of the processed point cloud within every 0.5×0.5 8 m cell throughout the study site (Fig. 12). In flat areas, without multiple return signals, 9 this shows the spatially varying precision of the dataset. There are large differences on 10 Fanø, which is expected due to vegetation causing multiple LiDAR returns from both 11 the vegetation canopy and from the bare ground. In contrast, the differences on the very 12 gently sloping, non-vegetated tidal flat are up to 10 cm, and there is no simple and natural reason for this variation. A range of factors contribute to the observed variations: 13

14 Laser beam incidence angle: The incidence angle, at which the laser beam hits the 15 ground/seabed, is determined by a combination of the scan angle, the water surface 16 angle and the terrain slope. The shape of the footprint is stretched with larger incidence 17 angles, and this effect can cause pulse timing errors in the detected signal, which leads 18 to a decreasing vertical accuracy (Baltsavias, 1999). The error associated with larger 19 scan angles is generally causing the outer beams, toward the swath edges, to attain a 20 lower accuracy (Guenther, 2007). This is a reason for the observed variations along the 21 swath edges (Fig. 12). Terrain slopes have the same effect of decreasing the vertical 22 accuracy due to the footprint stretching. The measured elevation tends to be biased 23 toward the shallowest point of the slope within the laser beam (Guenther, 2007). 24 However, the influence of slope is not crucial in the Knudedyb tidal inlet system, since 25 it is generally a very flat area.

26 <u>Vertical bias between overlapping swaths</u>: Areas covered by more than a single swath 27 tend to show more vertical variation in the LiDAR point measurements. This can be 28 caused by variance/error in the GPS measurements and/or IMU errors (Huising and 29 Gomes Pereira, 1998). The vertical bias between swaths has been observed in the point 30 cloud to be up to 5 cm, but it is varying throughout the study site. In most environments, a bias of 5 cm would be unnoticeable, but because of the large and very flat parts of the
Knudedyb tidal inlet system, even a small bias becomes readily evident.

3 Water depth: The accuracy and precision are expected to be lower as the laser beam 4 penetrates deeper into the water column (Kunz et al., 1992). The laser beam footprint is diverging as it moves through the water column, resulting in a larger footprint on the 5 6 seabed. The elevation of the detected point is thus derived from the measurement on a 7 larger area on the seabed, which will decrease the vertical accuracy, as well as decrease 8 the capability of detecting small objects. With this in mind, the higher precision at the 9 frame compared to the block is opposite of what would be expected, since the frame is 10 below water and the block is on land. In this case, other factors, such as overlapping 11 swaths and/or scan angle deviations, have more influence on the precision than the 12 water depth. Also, it should be remembered that the frame surface was close to the 13 water surface, and the effect of the water depth on the precision would most likely be 14 more evident if it was located in deeper water.

Additional factors, beside the ones mentioned above, may influence the quality of LiDAR datasets. For instance, a dense vegetation cover of the seabed or breaking waves that makes the laser detection of the seabed almost impossible. However, these factors do not have a great influence in the studied part of the Knudedyb tidal inlet system, and thus they are not further elaborated.

20 **5.5** Evaluation of the morphological classification

21 The morphological classification presented in this study is based on the studied section 22 of the Knudedyb tidal inlet system. The overall concept of using tidal range, slope and 23 variations of the elevation at different spatial scales proves to be a reliable method for 24 delineating the morphological features in this tidal environment. The concept, however, 25 can be applied in other environments. The specific thresholds in the classification 26 determined in this study may deviate in other areas. Morphological features of different 27 sizes require steps of other spatial scales in the neighbourhood analyses to produce a 28 successful classification. In the future the classification method will be improved by implementing an objective method for determining the scales, which can make it 29 applicable in areas with different morphological characteristics. Such an objective scale 30 31 determination method is presented by Ismail et al. (2015), who determined the scales 1 based on the variance of the DEM at progressively larger window sizes. In this way, the

2 sizes of the morphological features are determining the scales for the classification.

5.6 Using topobathymetric LiDAR data to map morphology in a highly 4 dynamic tidal environment

5 The study demonstrates the capability of green topobathymetric LiDAR to resolve finescale features, while covering a broad-scale tidal inlet system. Collecting 6 topobathymetric LiDAR data with a high point density of 20 points/m² on average 7 8 enables detailed seamless mapping of large tidal environments, and the LiDAR data has 9 further proved to maintain a high accuracy. The combined characteristics of mapping 10 with high resolution and high accuracy in a traditionally challenging environment 11 provide many potential applications, such as mapping for purposes of spatial planning 12 and management, safety of navigation, nature conservation, or morphological 13 classification, as demonstrated in this study. The developed LiDAR data processing 14 method is tailored to a morphological analysis application. The best representation of 15 the morphology is mapped by gridding the average value of the LiDAR points into a DEM with a 0.5×0.5 resolution. Other applications would require different gridding 16 17 techniques. For instance hydrographers, who are generally interested in mapping for 18 navigational safety, would use the shallowest point for gridding. However, the overall 19 method for processing the point cloud can be used regardless of the application. Only 20 the last and least challenging/time consuming step of gridding the point cloud into a 21 DEM, may vary depending on the application.

Applying topobathymetric LiDAR data for morphological analyses in tidal environments enables a holistic approach of seamlessly merging marine and terrestrial morphologies in a single dataset. However, a combination of topobathymetric LiDAR and MBES data is required, in order to map the morphology of tidal environments in full coverage. The comparable quality and resolution of LiDAR and MBES data gives a potential to map broad-scale tidal environments, such as the Wadden Sea, in full coverage and with high resolution and high accuracy.

1 6 Conclusions

2 A method was developed for processing raw topobathymetric Light Detection And 3 Ranging (LiDAR) data into a Digital Elevation Model (DEM) with seamless coverage 4 across the land-water transition zone. The method relies on basic principles, and the 5 entire processing method is described with a high level of detail, which makes it 6 transparent and easy to implement for future studies. Specifically a new procedure was 7 developed for water surface detection in a tidal environment utilizing automatic water 8 level determination solely based on green LiDAR data. The water surface detection 9 method presented in this work did not take into account the variation in wave heights 10 and surface slopes, which therefore constitutes a challenge to be addressed in future 11 studies.

12 The vertical accuracy of the LiDAR data was determined by object detection of a 13 cement block on land to ± 8.1 cm with a 95% confidence level. The vertical precision 14 was determined at the cement block to ± 7.6 cm, and ± 3.8 cm at a steel frame, placed 15 just below the water surface. The horizontal mean error was determined at the block to 16 ± 10.4 cm. Overall, vertical and horizontal precision are within sub decimetre scale.

17 A seamless topobathymetric DEM was created in a 4×0.85 km section in the Knudedyb tidal inlet system. An average point density of 20 points per m² made it 18 19 possible to create an elevation model of 0.5×0.5 m resolution without significant 20 interpolation. The DEM extended down to water depths of 3 m, which was determined 21 as the maximum penetration depth of the laser scanning system at the given 22 environmental conditions. Measurements of suspended sediment concentration and 23 organic matter content indicated that the penetration depth was limited by the amount of 24 organic matter rather than the amount of suspended sediment.

The vertical "dead zone" of the LiDAR data was determined to approx. 0-28 cm in thevery shallow water.

The DEM was used as input in the Benthic Terrain Modeler tool to classify the study area into 5 classes of geomorphometry: broad-scale crests, fine-scale crests, depressions, slopes and flats. A morphological classification method was developed for classifying the area into 6 morphological classes: swash bars, linear bars, beach dunes, intertidal flats, intertidal creeks and subtidal channels. The morphological classification 1 method was based on parameters of tidal range, terrain slope, a combination of various 2 statistical neighbourhood analyses with varying window sizes and the area/perimeterratio of morphological features. The concept can be applied in any coastal environment 3 4 with knowledge of the tidal range and the input of a DEM; however, the thresholds may need adaptation, since they have been determined for the given study area. In the future 5 the classification method should be improved by implementing an objective method for 6 7 determining thresholds, which makes it immediately applicable across different 8 environments.

9 Overall this study has demonstrated that airborne topobathymetric LiDAR is capable of 10 seamless mapping across land-water transition zones even in environmentally 11 challenging coastal environments with high water column turbidity and continuously 12 varying water levels due to tides. Furthermore, we have demonstrated the potential of 13 topobathymetric LiDAR in combination with morphometric analyses for classification 14 of morphological features present in coastal land-water transition zones.

15

16 Acknowledgements

17 This work was funded by the Danish Council for Independent Research | Natural 18 Sciences through the project "Process-based understanding and prediction of 19 morphodynamics in a natural coastal system in response to climate change" (Steno 20 Grant no. 10-081102) and by the Geocenter Denmark through the project "Closing the 21 gap! – Coherent land-water environmental mapping (LAWA)" (Grant no. 4-2015). 22

1 References

- 2 Al-Hamdani, Z., Alanen, U., Andersen, J. H., Bekkby, T., Bendtsen, J., Bergström, U., Bučas, M.,
- 3 Carlén, I., Dahl, K., and Daunys, D.: Baltic Sea marine landscapes and habitats-mapping and
- 4 modeling, BALANCE Technical Summary Report, part 2/4, 2008.
- 5 Alexander, C.: Classification of Full-waveform Airborne Laser Scanning Data and
- Extraction of Attributes of Vegetation for Topographic Mapping, PhD Thesis, University of
 Leicester, 2010.
- 8 Allouis, T., Bailly, J. S., Pastol, Y., and Le Roux, C.: Comparison of LiDAR waveform 9 processing methods for very shallow water bathymetry using Raman, near-infrared and 10 green signals, Earth Surface Processes and Landforms, 35, 640-650, 2010.
- 11 Baltsavias, E. P.: Airborne laser scanning: basic relations and formulas, ISPRS Journal of 12 Photogrammetry and Remote Sensing, 54, 199-214, 1999.
- Brzank, A., Heipke, C., Goepfert, J., and Soergel, U.: Aspects of generating precise digital
 terrain models in the Wadden Sea from lidar-water classification and structure line
 extraction, ISPRS Journal of Photogrammetry and Remote Sensing, 63, 510-528, 2008.
- Cavalli, M., and Marchi, L.: Characterisation of the surface morphology of an alpine alluvial
 fan using airborne LiDAR, Natural Hazards and Earth System Science, 8, 323-333, 2008.
- 18 Chauve, A., Mallet, C., Bretar, F., Durrieu, S., Deseilligny, M. P., and Puech, W.: Processing
- Full-Waveform LiDAR data: Modelling raw signals, Internatinal archives ofPhotogrammetry, Remote Sensing and Spatial Information Sciences, 2007.
- Collin, A., Archambault, P., and Long, B.: Mapping the shallow water seabed habitat with
 the SHOALS, Geoscience and Remote Sensing, IEEE Transactions on, 46, 2947-2955, 2008.
- Collin, A., Long, B., and Archambault, P.: Merging land-marine realms: Spatial patterns of
 seamless coastal habitats using a multispectral LiDAR, Remote Sensing of Environment,
 123, 390-399, 2012.
- 26 DCA (Danish Coastal Authority): Wave data Fanø Bugt, 27 <u>http://kysterne.kyst.dk/pages/10852/waves/showData.asp?targetDay=30-05-</u>
- 28 2014&ident=3071&subGroupGuid=16406, last access: 9 March 2016, 2014.
- Diesing, M., Coggan, R., and Vanstaen, K.: Widespread rocky reef occurrence in the central
 English Channel and the implications for predictive habitat mapping, Estuarine, Coastal
 and Shelf Science, 83, 647-658, 2009.
- 32 Dix, M., Abd-Elrahman, A., Dewitt, B., and Nash, L.: Accuracy Evaluation of Terrestrial 33 LIDAR and Multibeam Sonar Systems Mounted on a Survey Vessel, Journal of Surveying
- 34 Engineering, 138, 203-213, 10.1061/(ASCE)SU.1943-5428.0000075, 2012.
- DMI (Danish Meteorological Institute): Vejr- og klimadata, Danmark Ugeoversigt 2014 22, 26 Maj 2014 1 Juni 2014,
 <u>http://www.dmi.dk/uploads/tx_dmidatastore/webservice/t/g/i/s/r/20140601ugeoversi</u>
 gt.pdf, last access: 9 March 2016, 2014.
- 39 Doneus, M., Doneus, N., Briese, C., Pregesbauer, M., Mandlburger, G., and Verhoeven, G.:
- 40 Airborne laser bathymetry-detecting and recording submerged archaeological sites from 41 the air, J Archeol Sci, 40, 2136-2151, 2013.
- 42 Ernstsen, V. B., Noormets, R., Hebbeln, D., Bartholomä, A., and Flemming, B. W.: Precision 43 of high-resolution multibeam echo sounding coupled with high-accuracy positioning in a
- 44 shallow water coastal environment, Geo-mar lett, 26, 141-149, 2006.

- 1 Graham, L.: Accuracy. Precision and all That Jazz, LiDAR Magazine, 2, 2012.
- Guenther, G. C.: Airborne laser hydrography: System design and performance factors, DTIC
 Document, 1985.
- 4 Guenther, G. C., Cunningham, A. G., LaRocque, P. E., and Reid, D. J.: Meeting the accuracy
- 5 challenge in airborne lidar bathymetry, EARSel, Dresden, 2000.
- Guenther, G. C.: Airborne lidar bathymetry, Digital elevation model technologies and
 applications: The DEM users manual, 2, 253-320, 2007.
- 8 Hladik, C., and Alber, M.: Accuracy assessment and correction of a LIDAR-derived salt
 9 marsh digital elevation model, Remote Sens Environ, 121, 224-235, 2012.
- Hofle, B., Vetter, M., Pfeifer, N., Mandlburger, G., and Stotter, J.: Water surface mapping
 from airborne laser scanning using signal intensity and elevation data, Earth Surface
 Processes and Landforms, 34, 1635, 2009.
- Hogg, O. T., Huvenne, V. A., Griffiths, H. J., Dorschel, B., and Linse, K.: Landscape mapping at
 sub-Antarctic South Georgia provides a protocol for underpinning large-scale marine
 protected areas, Scientific Reports, 6, 33163, 2016.
- Huising, E. J., and Gomes Pereira, L. M.: Errors and accuracy estimates of laser data
 acquired by various laser scanning systems for topographic applications, ISPRS Journal of
 Photogrammetry and Remote Sensing, 53, 245-261, <u>http://dx.doi.org/10.1016/S0924-</u>
 <u>2716(98)00013-6</u>, 1998.
- Höfle, B., and Rutzinger, M.: Topographic airborne LiDAR in geomorphology: A
 technological perspective, Zeitschrift für Geomorphologie, Supplementary Issues, 55, 1-29,
 2011.
- IHO: IHO Standards for Hydrographic Surveys (S-44), 5th edition, International
 Hydrographic Bureau Monaco, 2008.
- Ismail, K., Huvenne, V. A., and Masson, D. G.: Objective automated classification technique
 for marine landscape mapping in submarine canyons, Marine Geology, 362, 17-32, 2015.
- Jensen, J. R.: Remote sensing of the environment: An earth resource perspective 2/e,Pearson Education India, 2009.
- Kaskela, A. M., Kotilainen, A. T., Al-Hamdani, Z., Leth, J. O., and Reker, J.: Seabed geomorphic
 features in a glaciated shelf of the Baltic Sea, Estuarine, Coastal and Shelf Science, 100,
 150-161, <u>http://dx.doi.org/10.1016/j.ecss.2012.01.008</u>, 2012.
- Klagenberg, P. A., Knudsen, S. B., Sørensen, C., and Sørensen, P.: Morfologisk udvikling i
 Vadehavet: Knudedybs tidevandsområde, Kystdirektoratet, 2008.
- Klemas, V.: Airborne remote sensing of coastal features and processes: An overview, J
 Coastal Res, 29, 239-255, 2013.
- Kunz, G., Lamberts, C., van Mierlo, G., de Vries, F., Visser, H., Smorenburg, C., Spitzer, D., and
 Hofstraat, H.: Laser bathymetry in the Netherlands, EAR-SeL Advances in Remote Sensing,
 36-41, 1992.
- Lecours, V., Dolan, M. F. J., Micallef, A., and Lucieer, V. L.: A review of marine
 geomorphometry, the quantitative study of the seafloor, Hydrol. Earth Syst. Sci., 20, 32073244, 10.5194/hess-20-3207-2016, 2016.
- 42 Lefebvre, A., Ernstsen, V. B., and Winter, C.: Estimation of roughness lengths and flow
- 43 separation over compound bedforms in a natural-tidal inlet, Cont Shelf Res, 61-62, 98-111,
 44 10.1016/j.csr.2013.04.030, 2013.

- 1 Leica: Leica LiDAR Survey Studio flyer, available at: http://leica-
- 2 <u>geosystems.com/products/airborne-systems/software/leica-lidar-survey-studio</u>, last
- 3 access: 24 March 2016, Heerbrugg, Switzerland, 2015.
- 4 Lundblad, E. R., Wright, D. J., Miller, J., Larkin, E. M., Rinehart, R., Naar, D. F., Donahue, B. T.,
- 5 Anderson, S. M., and Battista, T.: A benthic terrain classification scheme for American
- 6 Samoa, Marine Geodesy, 29, 89-111, 2006.
- Mallet, C., and Bretar, F.: Full-waveform topographic lidar: State-of-the-art, ISPRS J
 Photogramm, 64, 1-16, 2009.
- Mandlburger, G., Pfennigbauer, M., Steinbacher, F., and Pfeifer, N.: Airborne Hydrographic
 LiDAR Mapping-Potential of a new technique for capturing shallow water bodies,
 Proceedings of ModSim'11, 2011.
- Mandlburger, G., Pfennigbauer, M., and Pfeifer, N.: Analyzing near water surface
 penetration in laser bathymetry-A case study at the River Pielach, ISPRS Annals of
 Photogrammetry, Remote Sensing and Spatial Information Sciences, 1, 175-180, 2013.
- Mandlburger, G., Hauer, C., Wieser, M., and Pfeifer, N.: Topo-bathymetric LiDAR for
 monitoring river morphodynamics and instream habitats—A case study at the Pielach
 River, Remote Sensing, 7, 6160-6195, 2015.
- Millard, R. C., and Seaver, G.: An index of refraction algorithm for seawater over temperature, pressure, salinity, density, and wavelength, Deep Sea Research Part A.
 Oceanographic Research Papers, 37, 1909-1926, <u>http://dx.doi.org/10.1016/0198-</u>0149(90)90086-B, 1990.
- Mousavi, M., Irish, J., Frey, A., Olivera, F., and Edge, B.: Global warming and hurricanes: the
 potential impact of hurricane intensification and sea level rise on coastal flooding, Climatic
 Change, 104, 575-597, 10.1007/s10584-009-9790-0, 2011.
- Nayegandhi, A., Brock, J., and Wright, C.: Small-footprint, waveform-resolving lidar
 estimation of submerged and sub-canopy topography in coastal environments, Int J
 Remote Sens, 30, 861-878, 2009.
- Niemeyer, J., and Soergel, U.: Opportunities of Airborne Laser Bathymetry for the
 Monitoring of the Sea Bed on the Baltic Sea Coast, ISPRS J Photogramm, Remote Sensing
 and Spatial Information Sciences, 1, 179-184, 2013.
- Optech: Optech HydroFusion Information Sheet, available at:
 <u>http://www.teledyneoptech.com/wp-content/uploads/specification hydrofusion.pdf</u>, last
 access: 24 March 2016, Canada, 2013.
- Parker, H., and Sinclair, M.: The successful application of Airborne LiDAR Bathymetry
 surveys using latest technology, OCEANS, 2012 Yeosu, 2012, 1-4,
- Pe'eri, S., and Long, B.: LIDAR technology applied in coastal studies and management, J
 Coastal Res, 1-5, 2011.
- Pedersen, J. B. T., and Bartholdy, J.: Budgets for fine-grained sediment in the Danish
 Wadden Sea, Mar Geol, 235, 101-117, 2006.
- 40 Pike, R., Evans, I., and Hengl, T.: Geomorphometry: a brief guide, Developments in Soil41 Science, 33, 3-30, 2009.
- 42 RIEGL: LAS extrabytes implementation in RIEGL software Whitepaper, RIEGL Laser
- 43MeasurementSystemsGmbH,availableat:44www.riegl.com/uploads/txpxpriegldownloads/Whitepaper -

- <u>LAS extrabytes implementation in Riegl software 01.pdf</u>, last access: 24 March 2016,
 2012.
- 3 RIEGL: Datasheet RIEGL VQ-820-G, RIEGL Laser Measurement Systems GmbH, available
- 4 at: http://www.riegl.com/uploads/tx_pxpriegldownloads/DataSheet_VQ-820-G_2015-03-
- 5 <u>24.pdf</u>, last access: 24 March 2016, 2014.
- 6 RIEGL: Data Sheet RiHYDRO, RIEGL Laser Measurement Systems GmbH, available at:
- 7 <u>http://www.riegl.com/uploads/tx_pxpriegldownloads/11_DataSheet_RiHYDRO_2015-08-</u>
- 8 <u>24_01.pdf</u>, last access: 24 March 2016, 2015.
- 9 Rinehart, R., Wright, D. J., Lundblad, E. R., Larkin, E. M., Murphy, J., and Cary-Kothera, L.:
- 10 ArcGIS 8. x benthic terrain modeler: Analysis in American Samoa, Proceedings of the 24th
- 11 Annual ESRI User Conference, San Diego, CA, Paper, 2004, 2004,
- Sacchetti, F., Benetti, S., Georgiopoulou, A., Dunlop, P., and Quinn, R.: Geomorphology of the
 Irish Rockall Trough, North Atlantic Ocean, mapped from multibeam bathymetric and
- backscatter data, Journal of Maps, 7, 60-81, 2011.
- Schmidt, A., Rottensteiner, F., and Soergel, U.: Classification of airborne laser scanning data
 in Wadden sea areas using conditional random fields, International Archives of the
 Photogrammetry, Remote Sensing and Spatial Information Sciences XXIX-B3, 161-166,
- 18 2012.
- Steinbacher, F., Pfennigbauer, M., Aufleger, M., and Ullrich, A.: High resolution airborne
 shallow water mapping, International Archives of the Photogrammetry, Remote Sensing
 and Spatial Information Sciences, Proceedings of the XXII ISPRS Congress, 2012,
- Su, L., and Gibeaut, J.: EXTRACTING SURFACE FEATURES OF THE NUECES RIVER DELTA
 USING LIDAR POINTS, ASPRS/MAPPS 2009 Fall Conference, San Antonio, Texas,
 November 16-19, 2009.
- Verfaillie, E., Doornenbal, P., Mitchell, A. J., White, J., and Van Lancker, V.: The bathymetric
 position index (BPI) as a supprt tool for habitat mapping. Worked example for the MESH
- Final Guidance, 14 pp., 2007.
- Wang, C.-K., and Philpot, W. D.: Using airborne bathymetric lidar to detect bottom type
 variation in shallow waters, Remote Sensing of Environment, 106, 123-135, 2007.
- Wright, D., Lundblad, E., Larkin, E., Rinehart, R., Murphy, J., Cary-Kothera, L., and Draganov,
 K.: ArcGIS Benthic Terrain Modeler, Corvallis, Oregon, Oregon State University, Davey
 Jones Locker Seafloor Mapping/Marine GIS Laboratory and NOAA Coastal Services Center,
- 33 Accessible online at: <u>http://www</u>. csc. noaa. gov/products/btm, 2005.
- 34
- 35

- 1 Table 1: Vertical accuracy and precision of the LiDAR point measurements, in terms of
- 2 minimum error (E_{\min}) , maximum error (E_{\max}) , standard deviation (σ) , mean absolute

Accuracy/ Precision	Object	Best-fit plane	# points	$E_{\rm min}$ (cm)	E _{max} (cm)	σ (cm)	E _{MA} (cm)	E _{RMS} (cm)	<i>Cl</i> _{95%} (cm)
			n						
Accuracy	Cement block	GCPs	227	0.01	12.1	4.1	3.5	±4.1	±8.1
Precision	Cement block	Point cloud	227	0.04	12.9	3.9	2.8	±3.9	±7.6
Precision	Steel frame	Point cloud	46	0.02	5.5	2.0	1.6	±1.9	±3.8

3 error (E_{MA}), root mean square error (E_{RMS}) and the 95% confidence level ($Cl_{95\%}$).

Swath number	1	2	3	4	5	6	7	8	9	10	11	All
Point spacing (m)	0.30	0.30	0.36	0.31	0.36	0.32	0.37	0.29	0.35	0.36	0.28	0.20
Point density (pt./m ²)	10.8	10.8	7.8	10.2	7.5	9.6	7.2	11.7	8.0	7.8	12.7	19.6

Table 2: LiDAR point spacing and density for all the 11 individual swaths, which

covered the study area, and for the combined swaths.



1 Figure 1: A) Overview of the study area location in the Danish Wadden Sea and the 2 specific locations of the study site (B) and the two validation sites (I and J) (22 April 3 2015 satellite image, Landsat 8). B) The study site in the Knudedyb tidal inlet system 4 (30 May 2015 Orthophoto, AHM). C) Cottages in the dunes on Fanø. D) Beach dunes 5 on Fanø. E) Patch of Spartina Townsendii (Common Cord Grass). F-G) Swash bars. H) Linear bar. I) Validation site 1 with a cement block on land, used for accuracy and 6 7 precision assessment (19 April 2015 orthophoto, AHM). J) Validation site 2 with a steel 8 frame in Ribe Vesterå River, used for precision assessment (19 April 2015 orthophoto, 9 AHM).



1 2

Figure 2: Conceptual sketch of the laser beam propagation and return signals. The beam 3 refracts upon entering the water body, and it diverges as it propagates through the water 4 column. Return signals are produced both in the air, at the water surface, in the water 5 column and at the seabed. The LiDAR instrument has limited capability in very shallow 6 water (the "dead zone" in the figure) because the successive peaks from the water 7 surface and the seabed are not individually separated in time and amplitude. Only the 8 largest peak, which is from the seabed, is detected.

surface (orange). I) Correction for the effect of refraction on all the submerged points. J) Processed point cloud

- 3 Figure 4: Classification decision tree, showing how the geomorphometric classification
- 4 was conducted in the Benthic Terrain Model tool.
- 5

3 Figure 5: Classification decision tree of the morphological classification. All steps were

4 performed in ArcGIS.

transect (see location in Fig. 1B).

Figure 7: Vertical difference between the shallowest and the deepest LiDAR point
within 0.5 m grid cells in the land-water transition zone. The abrupt change is caused by
the dead zone. The vertical extent of the dead zone is determined to approx. 28 cm,
derived by the maximum rate of change of a polynomial fit through the points.

Figure 8: Vertical and horizontal distribution of the LiDAR points describing the block
surface and the actual block surface derived from GCPs. A) LiDAR points (grey dots)
compared to the GCP block surface (black line) for determining the vertical accuracy.
The grey line shows the LiDAR block surface as a best-linear-fit through the points. B)
Block surface derived from the four GCP corner points and the block surface derived by
the perimeter of the LiDAR points.

2

Figure 9: Topobathymetric DEM across the northern part of the Knudedyb tidal inlet system with close-up views of different detail level in specific areas. The northern supratidal part of the study area (A and B) includes beach dunes, vegetation and cottages, thus the DEM can be regarded as a DSM in this specific section. In the suband intertidal parts of the study area (C, D, E and F), the DEM reflects the natural terrain, thus it can be regarded as a DTM. A) Beach dunes, vegetation and cottages. B)

- 1 Cottages. C) Flood channel. D) Intertidal creek. E) Swash bars, linear bars and
- 2 bathymetry of the main channel. F) Swash bar. A hillshade is draped upon the close-up
- 3 views for improved visualization of morphological features.

Figure 10: Two classifications derived from topobathymetric LiDAR data: A)
Geomorphometric classification, and B) Morphological classification. C) Zoom-in on
the swash bars and linear bars close to the main channel in the morphological
classification. D) Zoom-in on the intertidal creek in the morphological classification. A
hillshade of the DEM is draped over C and D.

Figure 11: Vegetated mounds on the intertidal flat are clearly visible in the DEM and
classified as fine-scale crests in the geomorphometric classification. To the right is an
image of one of the mounds.

 0.5×0.5 m grid cells.