Interactive comments on "Numerical simulations of potential contribution of the proposed Huangpu Gate to flood control in Taihu Lake basin of China"

Zhang Hanghui, Liu Shuguang,

 5 Department of Hydraulic Engineering, Tongji University, 200092, Shanghai August 20, 2017 zhang_hanghui@hotmail.com RE: <u>hess-2016-310</u>

10

Dear Editor:

We appreciate much the comments from both reviewers. We all agree that these comments indeed help us improve the quality of our manuscript, and hence all comments from Reviewers have been considered

- 15 and incorporated into our newly revised manuscript. In this round of revisions, our manuscript has been through very serious, word-by-word revisions from head to toe. We believe our current manuscript is in a much better shape close to the publication level than all our previous versions. We invite the Editor and both Reviewers have a read on our newly revised version of manuscript. Meanwhile, we have provided point-to-point detailed responses to the Reviewers' comments below. We also made efforts to
- 20 correct the mistakes and improve the English of the manuscript. Finally, we have made some minor changes on the title of this manuscript.

Yours sincerely,

25 Zhang Hanghui and Liu Shuguang On behalf of all co-Authors

Part I Responses to Referee #1

Main Comments:

Authors refer to two types of floods in the Taihu Lake basin (i.e. monsoon-induced and typhoon-induced floods), and the basin is impaced by both marine (e.g. tides, storm surges) and river flooding &

- 5 waterloddging. The methodology section leaves the reader with an expectation of applications of the HOHY model to investigate the potential impacts of different operating modes of the gate to the flood control of the basin for typical flood events mentioned above, such as the 1999 flood, the 1991 flood. However, this expection goes unfulfilled in the result analysis and discussion sections, and the reader is left wondering why scenario analysis was made only for the 1999 flood event.
- 10

A: Thanks for your comments. The Huangpu River is the main shipping and drainage route to the port city Shanghai in China. The main role of the proposed gate is to block tide intrusion. Considering the shipping function, it is impossible for this gate to operate like other gates along the Yangtze River, which are operated more frequently for other purposes. Moreover, the dike also can protect Shanghai

- 15 when normal floods occur. In this study, the proposed gate will be operated only if the flooding conditions in the Taihu Lake basin are very severe. The 1999 flood is the largest flood in history for the study basin, and the total rainfall during the 43-days monsoon period reached 670 mm, three times more than the long-term (1954-2010) average during the same period. The return period of the 1999 flood event was estimated to be 200 years. From the viewpoint of engineering design as is the
- 20 main purpose of this study, only the most extreme situation such as the 1999 flooding condition is of our main concern. That is the main reason we choose only the 1999 flood event for our model simulation.

Responses to Specific Comments:

25

30

Q(1) The introduction should point out the issues you want to study, review the research advances in international hydrology society, and present the main research content of the paper. In this regards, it is suggested for authors to review the techniques and approaches adopted for impact study on flood control by operating estuary barries in Japan, England, Netherland and other countries, and evaluate the innovation or new findings in this applied research. In other words, it should indicate why the reader

should be interested in reading the paper?

A: Thanks for your comments. Yes, we have reorganized the chapter, which can be found on Page 2-3 in the newly revised manuscript.

35 **Q(2)** Detailed about the study area of the Taihu Lake should moved from Introduction to Study Area section.

A: Thanks for your comments. Yes, we have modified this chapter, which can be found on Page 3-5 in the newly revised manuscript.

Q(3) More information about the typical floods in the Taihu Lake basin (e.g. the 1999 flood, the 1991 flood) should be given in Study Area section, including the causes of the flooding (e.g. Rainstorm, astronomical tide, storm surge).

A: Thanks for your comments. Yes, we have added more information about the causes of the 5 flooding, which can be found in the sections of Introduction and the Study Area in the newly revised manuscript.

Q(4) General information about sedimentation in Huangpu river and estuaries is needed to supplement in Study area section.

10

A: Thanks for your comments. Yes, we have added more information about sediment, which can be found on the Page 5 Line 14-17 in the newly revised manuscript.

Q(5) In 3.1 Scenarios description (Page 4 Line 20-35), authors describes five scenarios used in the study.
 The reader wonder about the criteria or principles of proposing the five scenarios. What are the main
 factors to be considered in the gate operation scenarios design?

A: Thanks for your comments. The scenario "base A" means the estuary gate would not be constructed at the outlet of the Huangpu River, which is used as a basis for comparison. Scenario "A1" and "A2" are designed to quantitatively analyze its benefits of draining the floodwater from the Taihu lake and the upstream areas. Scenario "A3" is to analyze quantitatively its role to block tide intrusion.

20 The last scenario is just a case to calculate the potential maximum benefits to flood control of the basin.

Q(6) In 3.2 Model description (Page 5 Line 12-35), authors should also say if this is the first presentation on the HOHY model in an international Journal. A brief introduction on the HOHY model's structure and methodology, and further development of the model by authors in this study are also recommended

to be added in the paper.

25

30

A: Thanks for your comments. As for the HOHY model, "Cheng et al. (2006)" is the main reference which provides a lot of information listed in the reference of new manuscript (Page 12 Line 5). We have added some necessary and important information of this model, which can be found on Page 7 Line 17-23.

Q(7) Page 1 Line 19: Change "access" to "assess"

A: We have changed "access" to "assess" on Page 1 Line 22.

35 Q(8) Page 5 Line 6: "the ehorage". What does it mean?

A: Thanks for pointing out, and we have corrected it. The "Anchorage Ground" is the name of a place; in Chinese it is called "长航锚地". We have modified into "It is called anchorage ground in the unpublished master's thesis with English abstract (Hu, 2006)" which can be found on Page 6 Line 24-25.

Q(9) Page 1 Line 5: change "Ministry of Water Resources" to "Ministry of Water Resources of P.R. China"

A: Thanks for your comments. We have changed "Ministry of Water Resources" to "Ministry of Water Resources of P.R. China", which can be found on Page 1 Line 7.

5

Q(10) Figure 1(a) and (b): Please show rivers of Wangyu and Huangpu, location of Huangpu Park station in the map. Boundaries of six hydrology units and rivers are not clearly distinguished in the fig. 1. Can they be refined with amendation?

A: Thanks for your comments. Yes, it has been done, please see the new Figure 1.

10

Q(11) Problems with References: the following references were not mentioned in the main text of the manuscript.

(1)Duinker Peter and Greig Lorne: Scenario Analysis in Environmental Impact Assessment: Improving Explorations of the Future, Environmental Impact Assessment Review, 214, 2007

15 A: Thanks for your comments. We have deleted this reference.

(2)EA (Environment Agency): Summary of Thames Barrier Flood Defence Closures, Retrieved June 21, 2012, from http:// www.environment-agency.gov.uk, 2012

A: Thanks for your comments. This reference is mentioned in Page 3 Line 3 of our revised manuscript.

(3)JinKe, Wang Chuanhai, Yu Xiaoliang and Lin Hejuan: Application of Joint Regulation Model of 20
 Quantity & Quality in Emergency Water Diversion from Yangtze to Taihu, China Water Resource No.1, 18-20, 2008

A: Thanks for your comments. This reference is mentioned in Figure 2 of our revised manuscript. (4)JinKe: A Methodological Study to Improve Flood Management of the Taihu Lake Basin (Unpublished

25 master's thesis), The International Centre for Water Hazard and Risk Management (ICHARM), Japan, ICHARM Master Paper No.13, 14, 2009

A: Thanks for your comments. This reference is mentioned in Page 7 Line 3 of our revised manuscript.

Part II Responses to Referee #2

General Comments:

Writing improves a lot in this version and most of my comments are addressed in an appropriate way.However, the response to my general comments on parameter sensitivity and uncertainty is still notconvincing.

Responses to General Comments:

A: Thanks for your comments. The simulation results are indeed dependent on the model parameters, and the most sensitive parameters in this study is the roughness coefficient for channels. The smaller

- 10 the roughness coefficient is, the stronger the carrying capacity of the channel is. Meanwhile, uncertainty exists for determining this parameter due to river deposition, channel curvature and so on. In the HOHY model there is a fixed roughness coefficient for each channel segment, which is based on a previous comprehensive river drainage test. Since the year of 1999, the capacity and shape of the TaiPu Canal and Huangpu River have changed little. As a result, the parameters determined
- 15 previously should not have the need to adjust. On the other hand, in this study we focus on the potential impacts of constructing an estuary gate on the flood control in terms of evacuating flood discharge and reducing peak water levels under five different scenarios, all of which are based on the identical HOHY model simulations with the same parameters set. Therefore, we did not put substantial effort in analyzing the sensitivity of parameters in this study.

Part III Marked-up manuscript version

Numerical <u>Simulations</u> Analysis of Potential Contribution of the Proposed Huangpu Gate to Flood Control in <u>the</u> Taihu Lake Basin<u>of</u> China

Zhang Hanghui^{1,2}, Liu Shuguang¹*, Ye Jianchun^{4,2}, Pat J.-F. Yeh³

¹ Department of Hydraulic Engineering, Tongji University, 200092, Shanghai

² Taihu Basin Authority of Ministry of Water Resources <u>of P.R.China</u>, 200434, Shanghai

³ Department of Civil and Environmental Engineering, National University of Singapore, 117576, Singapore

*Correspondence to: Liu Shuguang (liusgliu@tongji.edu.com)

15

5

Abstract

The Taihu Lake basin (36895 km²), one of the most developed regions in China located in the hinterland of the Yangtze River Delta, has experienced increasing flood risk. The largest flood in history occurred in 1999 with a return period estimate of 200 years, much higher than the current capacity of flood defense

- 20 with the design return period of 50 years. Due to its flat saucer-like terrain, the capacity of flood control system in this basin depends on flood control infrastructures and peripheral tidal conditions. The Huangpu River, an important river of the basin connecting Taihu Lake upstream and Yangtze River Estuaries downstream, drains two-fifth of the entire basin. Since the water level in Huangpu River is significantly affected by the high tide conditions in estuaries, constructing an estuary gate is considered
- 25 as the most effective solution for flood mitigation. The main objective of this paper is to assess the potential contribution of the proposed Huangpu gate to the flood control capacity of the basin. To achieve this goal, five different scenarios of flooding and the associated gate operations are considered by using numerical model simulations. Results of quantitative analyses show that the Huangpu gate is effective to evacuate floodwaters. It can help to reduce both the peak values and the duration of high water levels in
- 30 the Taihu Lake to benefit the surrounding areas along the Taipu Canal and Huangpu River for more than 100 km2. The contribution of the gate to the flood control capacity is closely associated with its operation modes and duration. For the maximum potential contribution of the gate, the net outflow at the proposed site is increased by 52%. The daily peak level is decreased by a maximum of 0.12m in the Taihu Lake, by a maximum of 0.26-0.37 m and 0.46-0.60m in the Taipu Canal and Huangpu River, respectively, and
- 35 by 0.05-0.39m in surrounding areas along the two rivers depending on local topography. It is concluded that the proposed Huangpu gate can reduce flood risks in the Taihu Lake basin and the surrounding areas along the Taipu Canal and Huangpu River significantly, which is of great benefits to the flood management in the basin and the Yangtze River Delta.

Keywords: Flood control; Huangpu Gate; Taihu Lake Taihu Lake Basin; Numerical analysis

1 Introduction

- 5 The Huangpu River, located in the downstream part of the Taihu Lake basin, The Taihu Lake Basin, located in the hinterland of the Yangtze River Delta, Eastern China, is a region which is impacted by both marine, such as tides, waves and the influx of saline water, and river, such as flows of fresh water and siltation. Extensive urban development has contributed to increasing flood magnitude and flood frequency in this region. Major flood disasters, flooding more than 3000 km², have occurred more than
- 10 ten times during the twentieth century (Yu et al. 2000). The largest flood disaster occurred in 1999 and it resulted in damages with direct economic loss of 16 billion USD (Wang et al., 2011). There are 239 typhoons affecting the basin from 1949 to 2013, averaging about 3 to 4 per year on average (Ye & Zhang, 2015). According to the report from The Intergovernmental Panel on Climate Change (IPCC), the flood control of coastal systems and low lying areas is addressed, including the Yangtze River delta, which is
- 15 identified as one of the highly vulnerable coastal deltas (2007). The Huangpu River_is the main shipping and drainage route to the port city Shanghai in China. The state of the Taihu Lake Taihu Lake basin, is the last significant tributary of the Vangtze River. The Huangpu River is not only the major river that drains the local floodwater of the Shanghai city but also one of the major rivers that drains the floodwater of the Taihu Lake Basin. With
- 20 a length of 113 km, it flows through the urban core of Shanghai city, which is evaluated as one of the most vulnerable metropolises to extreme flooding in the world (Balica et al., 2012). Wang et al. (2012) <u>Another research predicted that half of Shanghai will be flooded and 46% of seawalls and levees will be overtopped in 2100 (Wang et al. 2012)</u>, causing serious urban flooding. Typhoon is one of main naturrual factors to trigger flood disaster in this area. When typhoon is comingcomes, the storm surges caused will
- be driven into the Yangtze River estuary to further <u>-causingincrease</u> storm tide levels<u>to-increase</u> additionally because of due to the shallow waters and confined dimensions within the estuary (Nai et al., 2004). When this <u>conjuncts</u>coincides with the astronomical high tides, the storm tide traveling into the Huangpu River can <u>easirapidly</u> raise water levels in river and possibley cause inundation of the urban areas of Shanghai. It has been reported that along with global climate change, the frequency and intensity of typhoons have increased substantially (Qin et al., 2005).
 - Taihu Lake Taihu Lake is located about 80 kilometers away west of the Shanghai city center (Figure 1). The Huangpu River is not only the major river draining local-floodwaters of both the Shanghai city but alsoand Taihu Lake basin the major routine that drains the floodwater from the lake. After the completion of eleven key projects for the integrated water resources management in Taihu lakeTaihu
- 35 <u>Lakethe basin, the discharge from the upper reach of Huangpu River increased correspondingly, which resultsing in a considerable rise of water level rise in the Huangpu River (Zhou et al., 2016). The river embankments, which is an traditional flood defense infrastructure, has been was built along the Huangpu River since in the 1950s. Its flood control capacity, however, is has been decreased by</u>

increasing storm surges and extreme tides, man-made changes in the estuary, land subsidence, and aging infrastructures. Currently, the river embankments need to be periodically raised to withstand the increasing water levels.

- The designed return period of the Huangpu River embankment approved in 1985 is 1000 years, which was approved in 1985. The historical highest water levels recorded are-was recorded during the 11th typhoon in 1997. At the Huangpu Park observational station near the Shanghai city core, the water level reached the historical height of 5.72 m₇ (-0.5 m higher than the second largest record in 1981) and only 0.14 m lower than the design water level at this location (Nai et al., 2004). Based on the revised hydrological analyses which extended the water level series from 1912-1983 to 1912-2002, the
- 10 embankment height in its original design corresponds to less than 200-year return period due to the newly recorded high tide in 1997 (Shao, 1999; Yao, 2001; Lu, 2008). In 2004, the standard of 1000-year recurrence level was foundinvestigated to been degraded to the 100-year level mainly due to because of sea-level rise and land subsidence (Tang et al. 2014), indicating that the flood protection capacity was reduced. To enhance the currflood protection capacity of thein Shanghai city, the height of embankments
- 15 needs has toto be raised to meet the standard of 1000-year return period. However, the continuous increase of the height will not only require huge economic cost but also affect urban landscape and water environment, <u>-with Another another potential risk of high river embankment isbeing</u> that the extreme dam-break flooding will be more devastating. <u>MoreoverIn addition</u>, the reliability of the reinforced embankment structure is in question because of the <u>its</u> aging foundation and core of the embankment,
- 20 which was built in the around 1950s (Zhou et al., 2016).

40

A combination of the flood defense walls and estuary barriers has been <u>used-proposed</u> as an alternative <u>measure to against the reduced capability of flood control flood control infrastructure</u> in the low-lying regions in Japan, England, Netherland, <u>Germany</u>, <u>among-and</u> other countries (Xiao, 2017; Jin, 2016). The Thames barrier in UK, for instance, has been operated for more than 30 years

- 25 with a significant flood control capacity for protecting the large cities upstream. It can effectively mitigate flood risks caused by discharge from upstream areas and high tides caused by storm surges (EA, 2012). Xiao (2017) reported that an area of 125 km² in London can be protected against the high water level of 1000-year return period when the Thames barrier is completed. After the completion of the Delta Storm Surge Barriers project in the Dutch delta, the protection standard was
- 30 increased from once in the return period of 1250 years to once in that of 4000 years, protecting one third of the areas of Netherlands as well as 4.5-million people. The Aames tidal gate in Germany has raised the level of protection against storm surge from the North Sea up to 3.7 meter above the mean sea level. Inspired by the above international experiences of flood protection, Inspired by thatsince 1998 the Shanghai–Municipal Government of Shanghai city has been investigating the
- 35 <u>feasibility to protect this area with a storm surge barrier at the mouth</u> of the Huangpu Riverproposed to build a storm surge barrier in the mouth of the Huangpu River so as to increase the city's design flood with a return period of 1000 years (Nai et al., 2004).

<u>As the Huangpu River runs through</u> one of the most <u>important metropoli</u>tan areas <u>in ChinaSince the</u> 1990s, numerous studies <u>since 1990s</u> have demonstrated the significance of constructing an estuary gate to enhance the safety of <u>the Shanghai city</u>, which is a metropolis in the upstream areas of the Huangpu

River (Chen, 2001; Shao, 1999; Shao and Yao, 1999). Chen (2002) presented an economic and efficiency analysis of the proposed tidal gate at the estuary of the Huangpu River. Chen (2001) and Shao (1999) carried out comparative studies based on the experiences of the well-known Thames Barrier in UK and the Delta Storm Surge Barriers in Netherlands. Jin (2016) conducted an in-depth analysis of typical large

5 tidal gates built globally on the aspects of planning and design, investment and construction, and operation and maintenance-outside China. Chen (2002(a)) analysed a rough estimated of the economic benefits in terms of based on the protected areas by the proposed tidal gate at the estuary of the Huangpu River.

Most afore-mentioned studies research on the importance and necessity of constructing the estuary

10 gate are based on comparative and qualitative analyses only. Although some previous research provided quantitative estimation for the potential benefits of the proposed gate (Chen, 2002(b); Cui, 2012), the majority of them only considered the role of the gate in blocking the tide intrusion for the local estuary areas of the Huangpu River. Few research have provided a holistic evaluation on the potential contribution of the proposed gate to flood control for the entire Taihu Lake basin, in particular the

15 synergistic effects for the upstream areas of the basin due to gate construction. As the Huangpu River connects the Taihu Lake with the Yangtze River estuary to drain floodwater from both local and lake upstream areas, the investigation of potential contributions of the proposed gate to flood control for the entire basin is of great engineering significance, and this is the main thrust of this study. To achieve this goal, various scenarios of the monsoon-induced floods are analyzed in this study and their impacts are

20 <u>quantified through numerical modelling simulations.</u>

benefits of the proposed Huangpu gate is based on qualitative approaches, while little research focuses on the quantitative analyses of the potential benefits of the proposed Huangpu gate when fluvial flooding occurs. The main objective of this paper is to access the potential contributions of the proposed Huangpu gate to flood control capacity of the basin. To achieve this goal, through numerical simulations,

25 various monsoon induced floods scenarios are quantitatively analysed.

2 Study Area

The Taihu Lake Basin, located in the hinterland of the Yangtze River delta, is one of the most developed areas in China. The Taihu Lake is located in the center of the basin, surrounded by the Yangtze River on the north, the Hangzhou Bay on the south, and the East China Sea on the east, as shown in Fig. 1(a). This
basin is not a sizable basin with the total area of 36,895 km², which is only 0.4% of the national total (Hu &-and Wang, 2009). However, the Gross Domestic Product (GDP) is up to RMB 6.69 trillion by the end of 2015, accounting for about 10% of the national total, and the regional per capita GDP being more than 2.5 times of the national average. This region is of great significance for the social and economic development of China. However, the extensive urban development has contributed to the risk

35 of increasing flood magnitude and flood frequency overin this region.

The Taihu Lake Basin is characteristic of a dense water web and a flat saucer like landform, forming a complex hydro-system that includes interlaced rivers, dense water nets, and dotted depression lakes of different sizes (Qin, 2008). The water <u>networksystem</u> and drainage system in the basin possesses the <u>following unique individual properties</u>: (1) it has a saucer-like landform, and the elevation of more than half of the floodplains is lower than the water level of flood control; (2) it is a typical river plain region with <u>a high river net density of 3.2 km/km² and the total river length of sabout 120,000 km; (3) the surface gradient is about 1/100,000 - 1/200,000, and the river flow velocity is only 0.3 - 0.5m/s in flood</u>

5 seasons; (4) the daily drainage time of <u>the</u> peripheral outlets in the basin is about 13 - 14 hours due to <u>the</u> semi-diurnal tides. Overall, the capacity of flood control system in the basin is dependent <u>to a large extent</u> on the flood defense infrastructure and the peripheral tidal conditions-to a certain extent. Based on the characteristics of the topography and the water networks, the basin is divided into eight sub-areas, namely theand they are Huxi, Wuchengxiyu, Zhexi, Taihu lake Taihu Lake, Yangchengdianmao, Hangjiahu, Puxi,

10 and Pudong (as shown in Figure.-1a). TAmong these, he irrigation systems were built which control the water exchange amongof these sub-areas (Fig. 1(a)). The special-unique saucer-like topography of the Taihu Lake Taihu Lake dictates thatmakes the water storage is easy to accumulate but difficult to drain, hence rendersso the surroundings flood-prones occur readily in this areas (Gao et al., 2005).

15

20

Theis Taihu Lake basin lies in a subtropical climate zone and is thus characterized by mild annual temperatures, high humidity and abundant rainfall (long-term average with an precipitation of 1177mm/year). The basin is prone to to suffering both monsoon-induced and typhoon-induced floods. Major flood disasters, with the inundation areas greater flooding more than 3000 km², have occurred more than ten times during the twentieth century (Yu et al. 2000). The largest flood disaster occurred in 1999 and it-resulted in damages with direct economic loss of 16 billion USD (Wang et al., 2011). There are 239 typhoons hittaffecting the basin during thefrom 1949-to-2013 period, averaging on average about 3 to 4 per year on average (Ye & and Zhang, 2015). According to the recent assessment report (AR5)

compiled byfrom tThe Intergovernmental Panel on Climate Change (IPCC, 2013) where the flood control of coastal systems and low-lying areas is addressed, the flood control of coastal systems and low lying areas is addressed, including the Yangtze River deltadelta, which is identified as one of the highly vulnerable coastal deltas in the world-(2007).

Generally, the basin is characterized by <u>thea</u> monsoonal climate with the period concentrated in summer (,-from June to July), lasting several weeks or even months. Consequently, <u>the</u>broad_-scale 30 rainfall events <u>occur frequently are prone to occurring with andue to</u> excessive <u>magnitude arainfnd a all</u> with long duration, <u>which</u> contributinges to <u>the</u> basin-wide floods. <u>Meanwhile, the monsoon flood risks</u> are exacerbated by the very low lying topography and high tide conditions of peripheral outlets in the basin. The_largest flood in history occurred in 1999, and the total rainfall in <u>a the 43</u>-days monsoon period reached 670 mm, <u>which was</u> three times more than the long-term (<u>1954-2010</u>) average

- 35 precipitation_during the same period of time of the year in the 1954-2010 periods. The return period of 1999 flood event is estimated as 200-years (Evans and& Cheng, 2010), much highlarger than both the current-capacity of 50-year design return period of the flood control capacity of in the basin with 50 years return period and the pprojected_lanned capacity with 100 year_designs return period in 2025 (MWR, 2008). MTotal_ean totalsaverage rainfall of the 7-day, 15-day, 30-day, 45-day, 60-day and 90-day
- 40 <u>accumulated rainfall</u> in 1999 all exceeded the historical <u>records</u> values recorded (Wu, 2000). During this

flood, the high water level in <u>Taihu Lake</u> Taihu Lake set a new record of 5.08 m, <u>which exceedinged</u> the previous record set in the 1991 flooddesign water level of 50-year return period by 0.29-43 m.

In the basin, there are numerous tidal channels-that linking-the lakes and the coast (bay, estuary), and most outlets are controlled by the floodgates subject to tidal locking tide locking. The Huangpu River

- 5 meandering s-through the downtown area of Shanghai City -and-connects the westward-located Taihu Lake with the Yangtze River estuary in the North East, as shown in Fig. 1(a). The Huangpu River is 113 kilometerskilometers long, with a depth of 5-15 meters, and a width of 300-500 meters (800 m at the estuary), formed by - It is born from the convergence of Xietang riverRiver originated from the Taihu Lake and Area Area Yangchengdianmao, Yuanxiejing Creek and DamMaogang Creek from Area
- 10 originated from Area Hangjiahu. The river then-flows proceeds through the downtown Shanghai before i and finally injectflowings into the YangzteYangtze River at the estuary mouth of Wusong, -mouth as the only one without an estuary gate in the basin. The tidal effect complicates the flow patterns of the Huangpu River, and helps to keep the floodwater in the river. Generally, the river can naturally drain floodwaters only for 13-14 hours per day. The Huangpu River, as the only one without an estuary gate,
- 15 flows into the Yangtze River estuary and experiences two high tides and two low tides each day (semi-diurnal tides), and receivinges about 40.9 billion m³ of tidal water from the Yangtze River (Zhang, 1997)., as shown in Fig. 1(a). For this reason, t<u>The tidal effect complicates the flow patterns</u> of the Huangpu River. As the 'barrier effect', the high tide helps to keep the floodwater in the river. Generally, <u>Tthe river can, therefore, naturally drain floodwaters in the Taihu Lake and the middle of the floodplain only</u>
- 20 for 13-14 hours per day. The Huangpu River receives about 40.9 billion m³ of tidal water from the Yangtze River (Zhang, 1997). The total tidal influx of the Huangpu River is about 47.47 million m³-/per year, and the total inflow from its upstream area is about 10.02 billion m³/-per year. Its sediment concentration upstream is of 0.049 kg/m³, and that is of 0.213 kg/m³ downstream (Yan, 1992). The problem caused by sediment and siltation is not serious in this river because the inflow from the upstream

25 area is far more than the tidal water from the estuary.

3 Methodology

3.1 Description of five scenarios

It is instructive to investigate the potential contribution of the proposed Huangpu gate to the flood control of the Taihu Lake basin, which is still in the preliminary demonstration-of-benefit stage currently.

30 The main research strategy use<u>d</u> in this study is <u>the</u> scenario analysis_based on <u>numerical model</u> <u>simulations</u>, which is a process of analysing possible future events by considering alternative possible outcomes.

It is instructive to investigate the potential contributions of the proposed Huangpu gate to the flood control of the basin, which is still in the preliminary demonstration-of-benefit stage.

35 In total five different scenarios are are-considered used in this study as summarized in Table 1. Among them, the firstone scenario considers the case is the case-without gate construction, and all the remaining f. Four scenarios considerare the cases with with proposed gate construction, but each with different operational rules for the comparison to others. TSpecific ally speaking, s'Scenario "base A" is used as the

basis for comparison with other scenarios (Table 1). It- represents the case-means that the estuary gate is would-not be-constructed at the Huangpu River mouth, which is used as a basis for comparison. The s-Scenarios "A1" - and "-Scenario-A2" - are designed for the quantitative analysis_of tanalyze-heits potential benefits due to gate operation in draining the-floodwaters from the Taihu L-lake and its-the

5 upstream areas. The s'Scenario "A3" is designed to quantitatively-analyze theits contribution (function) of gate construction to block tide intrusion. The last sscenario, "A4", is the-just a case for to-analyzinge the potential maximum benefits to flood control of the basin. TAll he numerical simulations for the five different the scenarios are all based on the conditions during the 1999 flood event, which is, the largest flood in history for the study area.

10

40

For <u>the s</u>'Scenario <u>"base A"</u>, $\stackrel{,}{\rightarrow}$ the estuary gate <u>iswould</u> not <u>be</u> constructed at the outlet of the Huangpu River. Thus, the water in the Huangpu River and <u>the</u> Yangtze River estuary can exchange naturally.

For the s^cScenario "A1"² the proposed gate will be operated in the rising stage of the lake levels according which is to create a new record with a high possibility to create new record of the lake in level based onseveral days due to weather forecast. In the model simulation of the 1999 flood event, it began to operate seven days in advance before the lake level reached its peak value.

For <u>the s</u>⁴Scenario <u>"A2"</u>, ² the proposed gate will be operated when <u>the</u> large basin-wide floods
 occur with the lake level higher than 4.50 m, <u>which</u> meanings a severe and urgent flooding -situation inof
 the <u>Taihu LakeTaihu Lake which</u> requires is very severe anthe acceleration of floodwater drainage -of
 the major downstream rivers, including the Huangpu River.

- For the s^cScenario "A3", a²: portionart of the tidal water intrusion would ill be blocked, by the gate, and the gate will remain opennot be closed to prevent tide intrusion until the tide rises to a threshold (defined in this study as 4.0m). That is, the gate will not be closed for blocking tide intrusion every day; instead, it will only be closed underfor the situationcase when the high water exceeds the tide threshold and is forecasted to continue rise.
- 30 For <u>the last <u>s</u>-Scenario <u>"A4"</u>, -: the gate would prevent all <u>the intrusion of tidal water intrusion</u> during the flooding period, representing a hypothetical extreme case since it is not practical in implementation owing to the difficulty <u>inof</u> frequent operation (<u>e.g., i.e.</u> to close twice every day) of such a huge gate with a width of about 400—500 m. This scenario is <u>merelyjust</u> a case for analyzing the potential maximum benefits to flood control of the basin. <u>Indeed, Furthermore</u>, it is not necessary to <u>blockprevent</u> all tidal</u>
- 35 water intrusionintrusion, which would, entirely resulting in a stop any of water exchange between the Huangpu River and the Yangtze River networks. Under <u>suchthis</u> condition, it is also likely to produce a negative impacts on both waterway transportation and water environment system.

Considering the time needed for making policy decision and gate construction, it is highly likely that the Huangpu gate will <u>not be completed and start to operate work</u> after <u>in 2025</u>. For this reason, the proposed flood control projects <u>in the plan designed by in the Plan (MWR (, 2008) will also be</u>

<u>incorporated as the are also simulated in the scenarios of aflood defense infrastructure in this studys</u>. <u>TAlso, he model parameters inof</u> the <u>numerical simulations model in this study</u> are <u>specified as</u> the same as those used <u>in the design plan by in the Plan (MWR (, 2008)</u>. Hu (2006) proposed the <u>Aanchorage Geround</u> located at the mouth of Huangpu River (as shown in Fig<u>ure 1</u>) as the best

- 5 site for the gate construction <u>since</u>, <u>since it is in the first regular bank and hence theits</u> negative impacts to the shipping and navigation are the least <u>due to its location</u>. Cui (2012) and Lu (2008) proposed the <u>sameimilar</u> location for gate construction. <u>Similarly for In</u> the numerical <u>model</u> simulations <u>in of</u> this study, the estuary gate will also be <u>constructed simulated</u> at the <u>Aanchorageehorage Gg</u>round, the place <u>name in the unpublished master's thesis with English abstract (Hu, 2006), which is, place which is</u> about
- 10 5-6 km from the Huangpu <u>R</u>river <u>outletmouth</u>.

3.2 Model description

The HOHY model, developed by the Hohai University_in_, China; is used in this study. This model has been was tested for numerous regional applications since 1970s, and was applied to study the whole Taihu Lake basin in 1997[YJ1]. It is one of the main productions of a three-year water study atim the Taihu
Lake basin_supported by the World Bank and, which were-jointly undertaken by the Hohai University and the Delft Hydraulics in, the Netherlands. The HOHY model can simulate the cycle of flood-waters well. Meanwhile, the model can provide sa broad-scale, at a broad scale, a reasonable simulation of the flooding control system in the Taihu Lake Taihu Lake basin-flooding system. It can simulate not only simulate complex hydro-systems with numerous interlaced rivers and lakes, complicated relationships
between river nets, hilly topography and tidal boundaries, and also the simulate complex operational rules of control structures, such as sluices, pumps and siphons. This model htt as been has been utilized inused in a variety of past studiesfields, such as the preliminary demonstration-of-benefit stage of water works in the Taihu Lake basin. In particular, the model has been successfully applied in the flood control planning of the Taihu Lake basin as, which was approved by the Minister of Water Resources

25 of P.R.C in 2008 WMR (MWR, 2008).

The model is composed of two parts: a hydrological part for simulating runoff generation and routing and a hydraulic part for simulating channel flows. Each of them can run independently. The schematization of the model is shown in Fig. 2. More details of the model can be found in Cheng et al. (2006) and Jin (2009)

30 (2006) <u>and Jin (2009</u>).

Runoff is generated when precipitation exceeds the infiltration, interception and depression storage. The basin land use is classified into four types: water surface, paddy field, non-irrigated farmland and constructed land. Each of them employs different parameterizations to calculate runoff generation. Runoff is then routed according to basin topography. In hilly areas, the instantaneous unit hydrograph

35 method is used, considering the store and drainage processes of reservoirs and large ponds. In plain areas, the method of runoff curve number is used for each computed area.

After the runoff from the hilly and plain areas flows into river networks, the hydraulic method is applied for simulation of river flow. Only those lakes with larger water surface are considered as possessing the function of storing floodwater, while the others are considered as intersections like the links among rivers. The operation of water-engineering works such as the simulations of gates, pumping stations and siphons will be simulated in the model. The Saint Venant Equations are used as the governing equations for the 1-D unsteady open channel flow, including the continuity_equation (1) and momentum equations (2) as follows

5

10

$$\frac{\partial Q}{\partial x} + \frac{\partial A}{\partial t} = q_L \tag{1}$$

$$\frac{\partial Q}{\partial t} + \frac{\partial}{\partial x} \left(\alpha \frac{Q^2}{A}\right) + gA \frac{\partial Z}{\partial x} + gA \frac{n^2 |Q| Q}{R^{1.333}} = q_L v_x$$
(2)

where [YJ2] <u>x</u> is the distance along each channel; t is the time; <u>A</u> is the cross section; <u>Q</u> is the flow rate; <u>Z</u> is the water level; α is the the the temperature correction coefficient; <u>R</u> is the hydraulic radius; q_{1} [YJ3] is the lateral inflow per unit length of channel; <u>Vx</u> is the velocity of the lateral inflow in the x-direction; and g is the gravity acceleration.

The model [YJ4] calibration data are from two consecutive years 1984 to 1985, and the validation data are from 1995 and 1996 (Liang et.al, 1993). The model is tested for three-the 1999basin wide flood

- 15 events <u>by</u> -in 1999. The 1999 flood event was simulated by Ou and Wu (2001) which also contains detailed comparisons between model simulation and observational data <u>simulated by Ou and Wu (2001)</u>. Fig.3 compares water level differences between model simulations and observations in 1999 flood at eight representative stations in the basin (see Fig.1 for the locations of eight stations)-(a). Fig.4 shows the difference in river discharges between observations and simulations at the Taipu Gate and Wangting
 20 Siphon (as shown in Fig.1), respectively(a). The comparison of simulated water levels and discharges
- with observations demonstrates that the HOHY model simulations are of sufficiently high accuracy for the following analyses.

Among the five scenarios considered, the operational rules in the scenario A3 are the most complex to simulate since the following different operational rules of the gate will be applied for the flood tide and ebb tide respectively. If the high water in the flood tide is higher than the tide threshold, the gate will be closed. Once the gate is closed, it will not be re-opened until it has the natural water-expelling ability to drain floodwater in the ebb tide (until the tide level falls to be lower than the water level in the upstream of the gate). Hence, the HOHY model needs to modify in order to enhance its capability for this purpose.

- The model modification focuses on the part of flood routing related to the algorithms of unsteady 30 open channel flow, and the control rules of gates related to the tidal conditions. The main program was improved by adding a function to judge the stage of tide before running the gates (i.e. in the flood or ebb tide), which makes the specification of the control rules of gates more flexible. The original program is modified based on the flowchart given in Fig. 2.
- The modified model is tested by using a simple case of which the tide threshold is assumed to be 4.0 m. The simulation results are presented in Fig.5 and Fig.6. The first figure describes the case when the gate remains open since the high water in this tidal period is always lower than 4.0 m. The second figure, as a comparison, is the case that the gate should be closed when the rising tide is higher than 4.0

m. The gate will re-open to drain floodwater when the gate has the natural water-expelling ability to evacuate floodwater in the ebb tide.

The model results including the gate discharge, the tide water level at the estuary, and the difference of water levels between the upstream and downstream of the gate, show the reasonable relationships of

- 5 the operational rules of the gate. The results in Fig.5 demonstrate that the discharge at the gate resembles a sinusoidal curve as affected by the tidal boundary. It is likely that the gate needs not to be closed since the high water in this tidal period is less than the tide threshold of 4.0 m. Fig.6 is another case of the gate operational rules of which the high water is about 4.70 m. At 2:30 am, 15/August/1999, the tide level at the river outlet in the flood tide slightly exceeded the tide threshold of 4.0 m, and the gate has to be
- 10 closed. It was not re-opened in the ebb tide until 8:15 am, 15/August/1999 when water level in the upstream is higher than that in the downstream near the proposed gate, meaning that the gate has the natural water-expelling ability to drain floodwater at this moment (see the red bars in Fig.6). Overall, the modified model has demonstrated the ability to simulate the complex operational rules of the proposed gate.

15 4 Result analysis and discussion

20

Based on the topography and water systems of the study region, the Huangpu River receives floodwaters from the Taihu LakeTaihu Lake and the surrounding areas draining into the Taipu Canal and Huangpu River, in particular those low-lying areas in the southern part of the Yangchengdianmao catchment, the northern part of the Hangjiahu catchment, and the western part of the Puxi catchment (Fig. 7). Therefore, the potential contributions of the proposed Huangpu gate to the flood control capacity will be analyzed in the following section with respect to three target regions: (1) the Taihu LakeTaihu Lake, (2) the surrounding areas, and (3) the Taipu Canal and the Huangpu River.

4.1 Potential contribution to flood control of the Taihu Lake Taihu Lake

Table 2 summarizes the peak lake water levels and the duration (the number of days) during the June-August period in 1999 when various control water levels were exceeded under five different scenarios considered in this study. Fig. 8 plots the simulated water levels at the <u>Taihu LakeTaihu Lake</u> corresponding to five different scenarios during the 1999 flood event from June to August. As seen, the lake levels in the scenarios A1, A2, A3 and A4 are all lower than that in the base A scenario. Similarly, the durations when the water level is higher than certain control levels were also reduced. Compared with the maximum daily water level of 5.03m (occurred in early July) in the base A scenario, the maximum water levels in other scenarios were decreased by 0.04 m, 0.01 m, 0.03 m and 0.12 m, respectively, for the scenarios A1, A2, A3 and A4. Thus, these four scenarios contribute to the flood control capacity of

the Taihu Lake Taihu Lake and its adjoining low-lying areas to the west.
It should be noted that the differences in the design water levels corresponding to different return
periods are not significant for such typical of shallow lakes located in the low-lying plains. For instance, the design water level of 100-year return period is 4.80 m, 0.15 m higher than that of 50-year return period. For this reason, the decrease in the peak lake level by 0.04 m in Scenario A1 as well as by 0.12

m in Scenario A4 is significant for the flood control of the lake. Additionally, the western adjoining floodplains also benefit from the proposed gate construction. Due to the relatively lower flood control capacity of the western adjoining areas, those regions are likely to be inundated when the sluices cannot yet control the water intrusion from the lake to the adjoining areas once if the lake level is too high. The flooding in the western adjoining areas will be even worse once if the lake breaches the dike.

5

From the viewpoint of flood control of the lake, it can be concluded that the Huangpu River with an estuary gate is more effective than the natural river without a gate. The extent of gate contribution to flood control depends largely on the total operation time of the gate. The longer the gate is operated, the more tidal water will intrude into the Huangpu River estuary. The gate operation will prevent and reduce

- 10 the amount of tidal water from entering the upper estuaries that are already with high water levels caused by high river flows. Clearly, the floodwaters in the lake will be drained slowly by the Taihu <u>C</u>eanal and the Huangpu <u>River River, which haveing</u> high water levels due to tide intrusion. Overall, the scenario A1 is a good example to examine the potential contribution of the proposed gate. In the simulation of the 1999 flood event, the Huangpu gate is more effective to reduce flood risk in the lake by operating the
- 15 estuary gate in advance. Even with the case of operating the gate by a relatively short period of time, such as one week as in this study, the contribution to reduce the peaks and slow down the rising rate of lake levels are rather significant.

4.2 Potential contribution to flood control of the surrounding areas

Floodwaters from the following surrounding areas are also drained into the Huangpu River: (1) Yangchengdianmao, (2) Hangjiahu, (3) Puxi, and (4) Pudong catchment, as shown in Fig. 7. Therefore, the safety of these four catchment areas against flooding is also closely linked to the capacity of the Huangpu River. Table 3 lists the peak water levels at the four representative stations (S1 to S4, shown as the star-orange circles in Fig. 1. each for one of the above four surrounding areas respectively)(b). Fig. 9 plots the simulated daily water levels during the 1999 flood event at these four stations, from which the

25 similar trend as the water level in the Taihu Lake Taihu Lake (Fig. 8) can be observed. The scenario A4 represents the maximum potential contribution of the proposed gate, i.e., the maximum decrease in the daily peak level at the four stations in the surrounding areas is 0.32 m, 0.19 m, 0.39 m and 0.05 m, respectively. In contrast, the improvement in the flood control capacity at station 4 at the Pudong catchment is the smallest among four stations due to its unique terrain. The local floodwater in the 30 Pudong catchment draining to the East China Sea has the priority over that draining to the Huangpu River due to its natural water-expelling ability. Generally, the flood capacity of station 4 does not depend much

on the drainage capacity of Huangpu River as the other three stations.

In contrast, for the scenario A1 in which the gate is operated in advance, the gate can play a notable role in reducing the peak water levels by the amount between 0.15m and 0.35m except for the station 4,

35 while for the scenario A2, the gate only decreases the peak water levels by 0.07-0.15 m. However, the scenario A2 has more advantages in speeding up the drainage rate of floodwaters at the recession stage and shortening the waterlogging time.

4.3 Potential contribution to flood control of the Taipu Canal and Huangpu River

Fig.10 plots the simulated daily water levels in the Taipu Canal and Huangpu River at the seven crosssections (as marked by the purple rectangular in Fig. 1)(c). The daily water levels at the Taipu Canal and Huangpu River decrease to various extents when the gate is in operation. The scenario A4 represents the

5 potential maximum contribution of the gate due to the complete prevention of tidal water intrusion. In this scenario, the maximum reduction of peak water level is 0.26-0.37m for the Taipu Canal is 0.26 - 0.37m, and 0.46-0.60m for the Huangpu River.

The Huangpu River benefits more from the proposed gate construction than the Taipu Canal because the latter is located relatively farther away from the gate. The potential contribution of the gate can be

- 10 attributed to the reduction of tidal water intrusion during the flooding period. Generally, the tidal intrusion is mainly concentrated on the lower reach of the Huangpu River, although the intrusion can propagate upward as far as more than 100 km from the estuary. The water level will rise in the upstream reach of Huangpu River when the gate is closed, and then the discharge rate will increase when the gate re-opens again due to the relatively large difference in water levels between the upstream and
- 15 downstream side near the gate. Therefore, the gate can decrease the water levels of Huangpu River more markedly than that of Taipu Canal.

In the scenario A1, the gate is operated in advance during the rising stage of the lake level, and the peak flood level in the Taipu Canal and Huangpu River can be decreased considerably due to the enlargement of drainage capacity of the Huangpu River. In the scenario A2, the gate is operated when

20 the lake level is higher than 4.5 m, and its contribution to the peak water levels is less than the scenario A1, while the draining rate in the recession stage is faster. If the gate is operated by blocking the high tide during the flood period (Scenario A3), the peak water levels at the Taipu Canal and Huangpu River are decreased during the spring tides. This conclusion is completely consistent with those discussed in the previous sections on the contribution of the proposed gate to the flood control of the lake and the surrounding areas.

4.4 Analyses of the inflow and outflows in the Huangpu River

Table 4 describes the inflow volumes from the upstream tributaries to the Huangpu River during the flood period. In addition to the Taipu Canal, there are many upstream tributaries originating from the northwest and southwest upstream areas of the Huangpu River (Fig. 7). In the scenario A4, the inflow

- 30 volume from the southwest tributaries into the Huangpu River is up to 3.25 billion m³, more than twice of that in the scenario base A (1.50 billion m³). The inflow from the northwest upstream areas in the scenario A4 is about 1.05 billion m³, increases by 78% in comparison to that in the scenario base A (0.59 billion m³). The inflow volume from the Taipu Canal is about 5.0 billion m³, only increased by 27.2% compared to that in the scenario base A (3.93 billion m³). In terms of the major inflows into the Huangpu
- 35 River, the inflow volumes from the southwest and northwest upstream areas increase significantly in comparison to that from the Taipu Canal, suggesting that the Huangpu River plays a dominant role for these two upstream subareas.

Table 5 describes the tide intrusion and outflow volume at the site of the proposed gate during the flooding period. The proposed gate helps to improve the drainage efficiency of Huangpu River by

preventing the river from tidal water intrusion. Compared to the scenario base A, the net outflow volumes at the gate site during the entire flooding period under other four scenarios are increased by 4% (scenario A1), 8% (scenario A2), 22% (scenario A3) and 52% (scenario A4), respectively. Fig.11 shows the comparison of simulated river discharges at the site of the proposed gate between the scenarios base A

- 5 and A1 from June 27 to July 3 in 1999. The difference in river discharge between these two scenarios clearly reflects the difference in the drainage efficiency of the Huangpu River. Although the river discharge in the scenario A1 is only increased by 4% for the entire flooding period (increased from 7.20 to 7.46 billion m³). It should be noted that the influence on the flood control during the gate operation period is more significant because the net outflow volume is nearly doubled by changing the billion is not a floor to floor the floor of the floor of the scenario floor to floor the floor of the fl
- 10 directional flow to the unidirectional flow.

5 Conclusions

Compared to a natural river channel, an estuary gate can prevent tidal water from intrusion into the upstream estuaries. This study shows that the construction of an estuary gate at the Huangpu River is an effective measure for evacuating floodwaters and reducing peak levels in the upstream reaches of the

- 15 river. The potential contributions of the proposed gate are closely associated with its operation duration. Regarding the maximum potential contribution, the net outflow at the site of the proposed gate is increased by 52% for the entire flooding period in 1999, and hence the efficiency of the drainage capacity from the Taihu Lake Taihu Lake to the Yangtze River estuary is significantly improved.
- Constructing the proposed gate will benefit the <u>Taihu LakeTaihu Lake</u>, the surrounding areas, and 20 the two major river channels, namely the Taipu Canal and the Huangpu River. The inflow volume from the upstream tributaries into the Huangpu River is increased by 27% (in the Taipu Canal), 78% (in the north part of Hangjiahu catchment) and 117% (in the south part of the Yangchengdianmao catchment), respectively. Meanwhile, the daily peak level is decreased by a maximum of 0.12 m in the Taihu Lake, by 0.05-0.39m in the surrounding upstream areas depending on local topography, and by 0.26-0.37m and

25 0.46-0.60m, respectively, in the Taipu Canal and Huangpu River.

The potential contribution of the gate depends on the operating time of the gate. For the scenario A1, it is beneficial to decrease the peak flood level and slow down the water level rise during the rising stage. For the scenario A2, it is helpful to speed up the drainage rate during the recession stage, to reduce the duration of high water level, and to decrease the flood risk of the lake and its adjoining upstream areas. For the scenario A3, it appears that the flood control is more effective during the spring tides.

30 areas. For the scenario A3, it appears that the flood control is more effective during Generally, the contribution of the gate is more notable in August than in other months.

Overall, it is significant and effective to build an estuary gate at the outlet of the Huangpu River to improve the capacity of flood control against the basin-wide large floods. The implementation of the gate needs further investigation, including the feasibility assessment on the economics, environment and

35 navigation. When the operation rules of the proposed gate are formulated, much attention should be paid to the navigation in the river so as to mitigate the adverse influences on the shipping.

Acknowledgements

This study was sponsored by the Chinese National Science & Technology Pillar Program (No. 2014BAL05B02) and the program of the National Natural Science Foundation of China (No. 41672230).

5

25

30

35

References

- Balica, S. F., Wright, N. G., and F. van der Meulen: A Flood Vulnerability Index for Coastal Cities and its use in Assessing Climate Change Impacts, Nature Hazards, doi: 10.1007/s11069-012-0234-1, 2012_
- 10 Chen, <u>MeifaM. F.</u>: A Compelling Call for Constructing a Tidal Gate at the Estuary of the Huangpu River, Shanghai Water, 1-3, 2001(in Chinese).
 - Chen, <u>WeiminW. M.:</u>, The Analyses and Evaluation on Economic and Efficiency of the Proposed Tidal Gate at the Estuary of the Huangpu River, Shanghai Water, 1-5, 12, 2002(<u>a</u>)-(<u>in Chinese</u>).

Chen, W. M.: Economic benefit analysis of the estuary gate at the Huangpu river mouth, J. Econ-. Water

15 Resources, 53-58, 2002(b).

- Cheng, W.H., Wang, C.H., and Zhu, Y.: The Taihu Lake Taihu Lake Modeling, Hohai University Press, 2006 (in Chinese).
- Cui, <u>DongD.</u>, Zhao, <u>GengrunG. R.</u>, and Lu, <u>YongjinY. J.</u>: Preliminary Analysis of Efficiency of
 Construction of a Tidal Sluice in Estuary of Huangpu River, Advances in Science and Technology
 of Water Resources, doi:10.3880/j.issn.1006-7647.2012.01.012, 2012-(in Chinese).
 - Duinker Peter and Greig Lorne: Scenario Analysis in Environmental Impact Assessment: Improving Explorations of the Future, Environmental Impact Assessment Review, 214, 2007
 - EA (Environment Agency): Summary of Thames Barrier Flood Defence Closures, Retrieved June 21,

2012, from http:// www.environment-agency.gov.uk, 2012.

- Evans, E.P. and Cheng, X.T.: China/UK Scientific Cooperation Project, Scenario Analysis Technology for River Basin Flood Risk Management in the Taihu Basin, Summary Report. Government Office for Science, London. Retrieved May 8, 2012, from http://
- www.nottingham.ac.uk/shared/shared_cpi/documents/discussion_papers/Discussion_44_Harvey_River_ _Basin.pdf, 2012.
- Gao J., Chen Y., K Takara, I. D. Cluckie and H. F. Smedt.: Impact of land use changes on runoff of the Taihu basin, China, International Conference of GISis and& Remote Sensing in Hydrology, 219-226, 2005.
- Hu, <u>Qingfang Q.F.</u>, and Wang, <u>Yintang Y.T.</u>: Impact assessment of climate change and human activities on annual highest water level of <u>Taihu Lake Taihu Lake</u>. Water Science and Engineering, <u>doiDOI</u>:
 - 10.3882/j.issn.1674-2370, 2009.
- Hu, XinX.: Study on the site selection of the estuary tidal sluice in Huangpu River (Unpublished master's thesis), Hohai University, China, 2006.

- IPCC (2013), Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change, edited by: Stocker, T. F., Qin, D., Plattner, G.-K., Tignor, M., Allen, S. K., Boschung, J., Nauels, A., Xia, Y., Bex, V., and Midgley, P. M., Cambridge University Press, Cambridge.
- 5 Jin, H., Wang, J. P., Jiang, F. R., Liao, S. H., Liu, D. W., Li, F. P.: Drawing on experiences from foreign countries for large tidal sluice, China Water Resource, 56-60, 2016.
 - Jin, <u>KeK.</u>, Wang, <u>ChuanhaiC. H.</u>, Yu, <u>Xiaoliang X. L.</u>, and Lin, <u>HejuanH. J.</u>: Application of Joint Regulation Model of Quantity & Quality in Emergency Water Diversion from Yangtze to Taihu, China Water Resource, No.1, 18-20, 2008.
- 10 Jin, K.e: A Methodological Study to Improve Flood Management of the Taihu Lake Taihu Lake Basin (Unpublished <u>M</u>master's thesis), The International Centre for Water Hazard and Risk Management (ICHARM), Japan, ICHARM Master Paper-<u>No.13, 14</u>, 2009.
 - Liang, RuijuR. J., Cheng, W.<u>H.enhui</u>, Cai, <u>WenxiangW. X.</u>, and Ma, <u>Xieyao X. Y.(1993)</u>: Hydrological System Model for Taihu Lake Taihu Lake Drainage Basin-<u>Journal J.of</u> Lake Sciences, Vol.5, No.2,
- 15 Jun., 99-107, 1993 (in Chinese with English abstract).
 - Lu<u>YongjinY. J.</u>: The Defense Situation and Countermeasures against Storm Surge in Shanghai.-<u>.</u> Shanghai Water, Vol.23, No.4, Mar. 2008, 6-10, 2008-(in Chinese).
 - MWR (Ministry of Water Resources of China): The Approval of the Flood Control Planning in the Taihu Lake Taihu Lake Basin, Retrieved March 1, 2012, from
- 20 http://www.gov.cn/gongbao/content/2008/content_928455.htm, 2008-(in Chinese).
 - NaiAI J.-Y., P.-H.-A.-J.-M. VanAN GelderELDER, P.-J.-M. KerssensERSSENS, Z.-B. WangANG, and E.-VanAN BeekEEK: Copula Approach for Flood Probability Analysis of the Huangpu River during Barrier Closure (Coastal Engineering 2004 (4-Volume Set), Proceedings of the 29th International Conference), Volume II, 2004, 1591-1603, 2004.
- 25 Ou<u>YanlunY.L.</u> and Wu<u>HaoyunH.Y.</u>: 1999 Catastrophic Flood in the <u>Taihu Lake</u> Basin-, China Water Power Press, 2001-(in <u>Chinese</u>).
 - Qin B. Q. (eds): Lake Taihu China Dynamics and Environmental Change, Springer Science + Business Media B.V., 2008.
 - Qin, D. H., Chen, Y. Y., and Li, X. Y.: Chinese climate and environment evolution. Science Press,
- 30 <u>Beijing-, 2005-(in Chinese)</u>.
 - Shao<u>, ChangkanC. K.</u>: Revisit of the Necessity to Construct an Estuary Gate at the Mouth of the Huangpu River, Shanghai Water, 18-21, 1999-(in Chinese).
 - Shao, <u>Changkan-C. K.</u>, and Yao, <u>WeichengW. C.</u>: Discussion of the Possibility of Constructing a Tidal Gate at the Estuary of the Huangpu River, Shanghai Water, 13-16, 46., 1999 (in Chinese).
- 35 Tang, Y. Z., Xu, G. Q., and Gao, C. C.: Assessment of present_capacity of flood control system in Pudong New Zone of Shanghai, Yangtze River, 26–29, 2014 (in Chinese).
 - Wang, J., Gao, W., Xu, S. Y., and Yu, L. Z.: Evaluation of the combined risk of sea level rise, land subsidence, and storm surges on the coastal areas of Shanghai, China, Clim. Change, 115(3 - 4), 537 - 558, 2012.

- Wang, LiangL., -Cai, YongliY. L., Chen, HongquanH. Q., Dag, Daler, Zhao, JingminJ. M., and Yang, JuanJ.: Flood disaster in Taihu Basin, China: casual chain and policy_option analyses, Environ Earth Sci., doi DOI 10.1007/s12665-010-0786-x, 1119-1124, 2011.
- Wu, TailaiT. L.: 1999 Catastrophic Flood in Taihu Basin and the Consideration for Taihu Flood Control
- Planning, Journal of, Lake Sciences, Vol.12, No.1, 6-11, 2000 (in Chinese with English abstract). Xiao, Y., Feng, W., and Zhang, Y. Q.: Benefits of building estuarine tidal gates in China and other countries and its impact analysis, China Water Resource, 25-28, 2017.

Yao, <u>WeichengW. C.</u>: The <u>s</u>tudy on the <u>e</u>Engineering <u>d</u>Design of <u>e</u>Estuary <u>g</u>Gate at the <u>m</u>Mouth of the Huangpu River, Shanghai Water, 21-24, 2001-(in Chinese).

- 10 Yan, Kai.: China coastal engineering, Hohai University Press, 1992-(in Chinese).
 - Ye, Jianchun-J. C., and Zhang, Hanghui H. H.: Practices and thinking of flood risk management in Taihu Lake Taihu Lake Basin, Advances in Science and Technology of Water Resources, Vol. 35, No. 5, DOI:10. 3880/ j. issn. 1006 7647, 2015 (in Chinese with English abstract).
 - Yu_a X_{.-}G_a, Wu_a T_{.-}L_a, and Jiang_a J_{.-}H_a: 1999 flooding Heavy in the Taihu_Basin: investigation, analysis and future suggestions on the integrated harnessing in the basin. J Lake Sci 12(1):1–5, 2000-(in <u>Chinese with English abstract</u>).
 - Zhang, <u>ChonghuaC. H.</u>: Case Study II* Shanghai Huangpu River, Water Pollution Control A Guide to the Use of Water Quality Management Principles Edited by Richard Helmer and Ivanildo Hespanhol, Published on behalf of the United Nations Environment Programme, the Water Supply
- 20 & Sanitation Collaborative Council and the World Health Organization by E. & F. Spon, ISBN 0 419 22910 8, 1997
 - Zhou, Z.Z.-zhengzheng, Liu, ShuguangS.G., Zhong, GuihuiG.H., and Cai, Y.i: Flood Disaster and Flood Control Measurements in Shanghai. Natural Hazards, ISSN 1527-6988, 2016.

25

15



Figure 1: Location map of the Taihu lake Taihu Lake basin and the surrounding regions in the Eastern China.



Figure 1(a): Location of the Taihu lake basin



Figure 2: Schematization of the extended HOHY model (Modified from Jin et al., 2008)







Figure 4: Comparison between the observed and simulated daily discharges from June to August in the 1999 flood event at the Taipu Gate station and Wangting Siphon station (Adapted from Ou and Wu, 2001)



Figure5: A test example when the gate keeps open due to the high water lower than tide threshold in this tidal period (t.l.: tide level; w.l. water level; a negative discharge indicates the tidal water intrusions)







5

Figure 7: Conceptual drainage system along Lake Taihu – the Taipu Canal – the Huangpu River – the Yangtze River Estuary



















Figure 9: Comparison of the simulated daily water levels during the period from June to August in 1999 at four stations (corresponding to four surrounding areas shown in Figure 7) under the five scenarios considered in this study.















Cross-section 4 (at the upstream of Huangpu River)

0.47m

1

7/3 7/5 7/7 7/9 7/11

date (mn

----- hase A

— A1

A2

A3

· · · - A4

4.0

3.8

3.6

3.4

2.6

2.4

2.2

2.0

6/21 6/23 6/25 6/27 6/29 7/1







5 Figure 10: Comparison of the simulated water levels during the period from June to August in 1999 at the seven cross-section points (as shown in Figure 1) along the Taipu Canal and Huangpu River under five scenarios considered in this study.



Figure 11: Comparison of discharges at the site of the proposed gate between the scenarios base A and A1 from June 27 to July 3 in 1999 (The negative discharges means the tidal water intrusion)





Figure 3: Comparison between the observed and simulated water levels from June to August in the 1999 flood event at eight stations as shown in Figure 1 (<u>a</u>Adapted from Ou and Wu, 2001)







Figure 5: A test example when the gate keeps open due to the high water lower than tide threshold in this tidal period (t.l.: tide level; w.l. water level; a negative discharge indicates the tidal water intrusions)



5 Figure 6: A test example when the gate needs to be closed due to the high water higher than tide threshold in this tidal period (t.l.: tide level; w.l. water level; a negative discharge indicates the tidal water intrusions)



































Cross-section 5 (at the middle of Huangpu River)





Figure 10: Comparison of the simulated water levels during the period from June to August in 1999 at the
 seven cross-section points (as shown in Figure 1) along the Taipu Canal and Huangpu River under five
 scenarios considered in this study.





Table 1: The definitions of five different scenarios considered in this study.

Scenario	Definitions
base A	without the construction of the proposed estuary gate at the estuary of the Huangpu River
A1	with the gate, and it will be operated to prevent tidal intrusion 7 days in advance before the lake level reaches the peak <u>s</u> -value
A2	with the gate, and it will be operated to prevent water intrusion when the large basin-wide floods occur occur (defined as the large basin wide floods here meanthat lake level is higher than 4.50m)
A3	with the gate, and it will not <u>be</u> closed to prevent tidal water intrusion until the tide rises to <u>a pre-</u> <u>defined the tide</u> threshold (<u>defined as the tide threshold here equal to</u> 4.0m in this study)
A4	with the gate, and it will <u>always</u> be closed whenever <u>the tidal waterintrudes</u>

Table 2: Peak lake water levels and the duration (the number of days) from June to August of 1999 when the lake water levels are higher than a certain control level under five scenarios considered in this study

peak value.	flood control level	high water level	design water level	design water level
(m)	3.5m	4.0m	4.65m (1/50)	4.8m (1/100)
	(days)	(days)	(days)	(days)
5.03	81	37	12	8
4.99	81	35	11	8
5.02	81	34	11	8
5.00	81	31	11	8
4.91	70	28	10	6
	peak value. (m) 5.03 4.99 5.02 5.00 4.91	peak value. flood control level A. 3.5m (days) (days) 5.03 81 4.99 81 5.02 81 5.00 81 4.91 70	peak value. flood control level high water level A. A.0m A.0m A. A.0m Main 5.03 81 37 4.99 81 35 5.02 81 34 5.00 81 31 5.01 81 32 5.02 81 34 4.91 70 28	peak value.flood control levelhigh water leveldesign water levelA.A.0m4.65m (1/50)(main and the second secon

Table 3: Peak water levels at the four representative stations under five scenarios considered in this study (unit: m)

Scenario	Station 1	Station 2	Station 3	Station 4
base A	4.22	4.46	3.78	3.38
A1	4.00	4.31	3.43	3.38
A2	4.12	4.39	3.63	3.38
A3	4.09	4.35	3.62	3.37
A4	3.90	4.27	3.39	3.33

Table 4: Summary of the inflow volumes of the tributaries in the upstream of the Huangpu River from June to August in 1999 under five scenarios considered in this study (unit: billion m³)

	base A	A1	A2	A3	A4	
Tributaries in the	outlet of the Taipu Canal	3.93	3.99	4.11	4.43	5.00
upstream area of the Huangpu River	tributaries from the sub-area, northwest of the Huangpu River	0.59	0.62	0.64	0.77	1.05
	tributaries from the sub-area, southwest of the Huangpu River	1.50	1.63	1.83	2.24	3.25

Table 5: Summary of tide intrusion and outflow volume at the site of the proposed gate from June to August5in 1999 under five scenarios considered in this study (unit: billion m³)

Outflow volume at the gate site						
Scenario	tide intrusion	total outflow volume	net outflow volume	Times to close the gate	Special explanation about the gate close rules	
base A	17.49	24.69	7.20	/		
A1	15.58	23.03	7.45	14	from Jun. 27 th to Jul. 3 rd	
A2	14.14	21.94	7.80	30	from Jun. 30^{th} to Jul. 14^{th}	
A3	10.78	19.58	8.80	74	until high tide rises up to 4.0m	
A4	0	10.95	10.95	184	from Jun. 1 st to Aug. 31 st	