

A practical approach to lake water density from electrical conductivity and temperature

Santiago Moreira^{1,2,3,*}, Martin Schultze¹, Karsten Rahn¹ and Bertram Boehrer¹

5 ¹UFZ-Helmholtz-Centre for Environmental Research, Department Lake Research, Brueckstrasse 3a, 39114 Magdeburg, Germany.

²Laboratoire des Sciences du Climat et de l'Environnement, LSCE/IPSL, CEA-CNRS-UVSQ, Université Paris-Saclay, F-91191 Gif-sur-Yvette, France

³Institute of Hydrobiology, TU-Dresden, Zellescher Weg 40, 01217 Dresden, Germany.

10 *Correspondence to:* S. Moreira (santiago.moreira-martinez@lsce.ipsl.fr)

Abstract. Density calculations are essential to study stratification, circulation patterns, internal wave formation and other aspects of hydrodynamics in lakes and reservoirs. Currently, the most common procedure is the use of CTD profilers and the conversion of measurements of temperature and electrical conductivity into density. In limnic waters, such approaches are of limited accuracy, if they do not consider lake specific composition of solutes, as we show. A new approach is presented to correlate density and electrical conductivity, using only two specific coefficients based on the composition of solutes. First, it is necessary to evaluate the lake-specific coefficients connecting electrical conductivity with density. Once these coefficients have been obtained, density can easily be calculated based on CTD data. The new method has been tested against measured values and the most common equations used in the calculation of density in limnic and ocean conditions. The results show that our new approach can reproduce the density contribution of solutes with a relative error of less than 10% in lake waters from very low to very high concentrations as well as in lakes of very particular water chemistry, which is better than all commonly implemented density calculations in lakes. Finally, a web link is provided for downloading the corresponding density calculator.

25

1 Introduction

Density is one of main physical quantities governing the hydrodynamics, stratification, and mixing in lakes and reservoirs. Water quality in lakes is controlled by biological and biogeochemical processes which depend on the availability of oxygen in deep waters and nutrients in surface waters. Both phenomena are controlled by the duration and extension of the turnover period, which is dependent on density gradients. Therefore, density is a very important variable in numerical models for the simulation of the behaviour of lakes under changing conditions, e.g. due to management measures or phenomena related to global climate change.

The density of lake water (at atmospheric pressure) depends on temperature and dissolved water constituents. Since temperature, chemical composition and concentrations may vary over time, from lake to lake or even within a particular lake due to seasonal stratification or meromixis, numerical models of lakes calculate the density internally. There are several approaches to calculate water density in lakes. Most of them are general equations that do not always reflect specific properties of lakes. If enough measurements of density for the relevant temperature range are available and composition and concentrations of the main constituents are constant, regressions can be used to generate a mathematical formula for density in a specific lake (e.g. Jellison et al., 1999; Vollmer et al., 2002; Karakas et al., 2003). If the composition is constant and the main constituents are ions, electrical conductivity or salinity may be used as an easy to measure proxy for concentrations (Bührer and Ambühl, 1975; Chen and Millero, 1986; Pawlowicz and Feistel, 2012).

Imboden and Wüest (1996) discussed the influence of dissolved substances on (potential) density because both the concentration and chemical composition of the total dissolved solids changes considerably from lake to lake (see e.g. Boehrer and Schultze, 2008). The effects of dissolved solids on density stratification have been studied in lake specific investigations in Lake Malawi (Wüest et al., 1996) and in Lake Matano (Katsev et al., 2010). In some cases, the specific contribution of ions such as calcium, carbonate or dissolved iron can control the permanent stratification in lakes as in La Cruz (Spain) (Rodrigo et al., 2001), Cueva de la Mora (Spain) (Sanchez-España et al., 2009) or Waldsee (Germany) (Dietz et al., 2012).

Density of pure water can be calculated using mathematical expressions such as those in Kell (1975) or Tanaka et al. (2001). Density calculations of natural waters require additional terms to include the contributions of dissolved substances. Specific formulas have been developed for ocean conditions. The UNESCO equations developed by Fofonoff and Millard (1983) have been the standard for a long period. They used temperature and practical salinity based on electrical conductivity measurements. Because sea water conditions are a known reference and the approaches provide stable results over a wide range of temperatures and electrical conductivity, these have been applied in limnic systems and implemented in numerical models such as DYRESM (Imberger and Patterson, 1981; Gal et al., 2009; Imerito, 2014), ELCOM (Hodges and Dallimore,

2007), GOTM (Burchard et al., 1999; Umlauf et al., 2005) or CE-QUAL-W2 (Cole and Buchak, 1995). Recently the ocean standard was replaced by the new Thermodynamic Equation of Seawater 2010 (TEOS-10; IOC et al., 2010). However, as the composition of solutes differs greatly from the ocean, density calculation based on ocean conditions can only be of limited accuracy. Pawlowicz and Feistel (2012) have considered the application of TEOS-10 (IOC et al., 2010) in several cases
5 different from seawater, correcting the salinity values depending on the composition before applying TEOS-10 (IOC et al., 2010). Bührer and Ambühl (1975) developed an equation to calculate density based on temperature and specific conductance at 20 °C for alpine lakes. In addition, a popular approach was formulated by Chen and Millero (1986) tuning ocean approaches to freshwater conditions (salinity < 0.6 psu).

10 Higher accuracy can be achieved when site specific density equations are produced. Jellison et al. (1999) developed a density equation for Mono Lake from water samples which have been measured at different temperatures and dilutions. In the case of meromictic lakes, strong differences in the composition of the mixolimnion and monimolimnion must be reflected in the density equations in order to sustain the permanent stratification in the density calculations. Boehrer et al. (2009) and von Rohden et al. (2010) used an equation based on density measurements of the monimolimnion and mixolimnion of Lake
15 Waldsee.

Boehrer et al. (2010) evaluated the contribution of the different cations and anions separately in terms of partial molal volumes and implemented an algorithm, RHOMV (<http://www.ufz.de/webax>), to calculate density with a second order approximation for temperature dependence and ionic strength dependence. Pawlowicz et al. (2011) implemented the
20 LIMBETA method that calculates density from composition. Another approach comes from Pawlowicz et al. (2012) where the authors propose to use TEOS-10 but replace seawater salinity by specific salinities obtained and corrected for freshwaters. This limnic salinity can be calculated using the chemical composition by summing up all the dissolved solutes (Sa^{soln}) or by summing up only the dissolved ions (Sa^{ionic}) and correcting this value with the dissolved $Si(OH)_4$, $Sa^{dens} = Sa^{ionic} + 50.6 \times [Si(OH)_4]$ (mol kg⁻¹). Based on partial molal volumes (RHOMV), Dietz et al. (2012) separated the contributions of
25 solutes for freshwater lakes. Moreira et al. (2011) based density on the composition of solutes in their model to reproduce the permanent stratification of Lake Waldsee numerically using RHOMV to include the reactivity of substances in the density (see also Nixdorf and Boehrer, 2015).

These prior studies therefore highlight the necessity to include the chemical composition to obtain an accurate calculation of
30 density. However, we accept the need for a practical density approach, which can easily be implemented, such a mathematical formula that relates density to temperature and electrical conductivity. In this manuscript, we develop coefficients for such a formula from the chemical composition. We provide an algorithm RHO_LAMBDA (from ρ_s) to obtain such coefficients and demonstrate the applicability of the approach with water from Rappbode Reservoir. We also provide an appropriate assessment for the Rappbode Reservoir case and compare the accuracy with other approaches

currently in use for limnic waters. For a quantitative judgement of the general applicability of our approach, we also evaluate coefficients for two further fresh water bodies (Lake Geneva, Lake Constance), an extremely saline lake (Mono Lake), a meromictic open pit lake in the mixolimnion and the monimolimnion (Lake Waldsee) and finally sea water as a globally known example and well defined standard.

5 2 Methods: The proposed approach (RHO_LAMBDA)

We propose a simple equation for density as a numerical approximation of the (potential) density of lake water:

$$\rho \approx \rho_{\lambda}(T, \kappa_{25}) = \rho_w(T) + \kappa_{25} [\lambda_0 + \lambda_1 \times (T - 25^{\circ}\text{C})] \quad (1)$$

where the first term of the right side ρ_w is the density of pure water, which can be calculated in a very accurate way using Kell (1975) or Tanaka (2001). Our approach (Eq. (1)) correlates density to temperature (T) and electrical conductivity at 25°C (κ_{25}) of a water sample using coefficients λ_0 and λ_1 . The introduction of λ_1 reflects temperature dependence of the density contribution of the solutes, which is required for a shifting temperature of maximum density. Only two coefficients need to be determined, and thus this equation is easy to implement. Coefficients λ_0 and λ_1 can be obtained as follows.

At $T=25^{\circ}\text{C}$, the λ_1 term in Eq. (1) vanishes and λ_0 can be calculated using Eq. (2) provided that the water density at 25°C is known from other sources:

$$\lambda_0 = \frac{\rho(T=25^{\circ}\text{C}, \kappa_{25}) - \rho_w(T=25^{\circ}\text{C})}{\kappa_{25}} \quad (2)$$

If the density is also known for a temperature $T \neq 25^{\circ}\text{C}$, λ_1 can be calculated in a second step:

$$\lambda_1 = \frac{[\rho(T, \kappa_{25}) - \rho_w(T)] / \kappa_{25} - \lambda_0}{T - 25^{\circ}\text{C}} \quad (3)$$

Necessary data for equations 2 and 3 can be derived from measurements or from calculations.

20

In the remaining part of this manuscript, Eq. (1), complemented by Eq. (2) and Eq. (3), will be referenced as the RHO_LAMBDA approach.

In our RHO_LAMBDA approach, we use the Tanaka (2001) equation for pure water density, ρ_w . If the composition of solutes in the water is known, the density of water is calculated by using RHOMV (Boehrer et al., 2010) and finally κ_{25} is provided by the algorithm implemented in the PHREEQC code (Parkhurst and Appelo, 1999), whose description can be found in Atkins and de Paula (2009) and in Appelo's webpage of PHREEQC (Appelo, 2016). This method (re-implemented in Python from the original code) calculates the specific conductance of a solution from the concentration, the activity coefficient and the diffusion coefficient of all the charged species. The diffusion coefficients can be found in Millero (2001).

2.1 Rappbode Reservoir

We demonstrate our density approach with the example of Rappbode Reservoir (Germany; for details on this reservoir see Rinke et al. 2013 and references therein); its low electrical conductivity indicates low concentrations of solutes. From chemical analysis of a surface sample from 19 November 2010, we knew the major cations were calcium (13.8 mg L^{-1}) and sodium (9.3 mg L^{-1}), while major anions were bicarbonate (28.07 mg L^{-1}), sulphate (18.5 mg L^{-1}) and chloride (16.8 mg L^{-1}) (see Table 1). In addition, a considerable portion of organic matter ($3.1 \text{ mg DOC L}^{-1}$) and silicate (4.5 mg L^{-1} of Si(OH)_4) were contained in the sample. The procedure to apply the RHO_LAMBDA method in the case of Rappbode Reservoir can be summarized as follows:

- 1) For this sample, an electrical conductance $\kappa_{25} = 0.1635 \text{ mS cm}^{-1}$ was calculated by inserting given concentrations into the PHREEQC algorithm (Parkhurst and Appelo, 1999; Atkins and de Paula, 2009).
- 2) According to RHOMV, the density of this sample at $25 \text{ }^\circ\text{C}$ was $\rho_{MV}(T=25^\circ\text{C}) = 997.130 \text{ kg m}^{-3}$ and $\rho_w(T=25^\circ\text{C}) = 997.047 \text{ kg m}^{-3}$.
- 3) Putting these numbers into Eq. (2) delivered $\lambda_0 = 0.506 \text{ kg cm m}^{-3} \text{ mS}^{-1}$
- 4) Similarly, we evaluated $\lambda_l = -0.0012 \text{ kg cm m}^{-3} \text{ mS}^{-1} \text{ K}^{-1}$ by putting $\rho_w(T=5^\circ\text{C}) = 999.967 \text{ kg m}^{-3}$ and $\rho_{MV}(T=5^\circ\text{C}) = 1000.053 \text{ kg m}^{-3}$ into Eq. (3).
- 5) Finally, inserting the lambdas as coefficients into Eq. (1) delivered a density formula for Rappbode Reservoir.

25

3 Assessments

The practicability of this approach depends on its accuracy. This will first be assessed for Rappbode Reservoir water and its above evaluated coefficients. However, for limnologists working on other limnic water bodies, an assessment of accuracy in the general range of limnic water composition is of fundamental interest. In conclusion, we chose a collection of lake waters of different chemical composition and a wide range of concentrations. We included all lakes we knew of, where a reliable reference density could be provided, and the chemical composition was known.

In particular, we included two further typical freshwater lakes, Lake Geneva and Lake Constance, which are well known in the limnological literature. As an example for saline lakes, we chose Mono Lake (eg. Jellison et al., 1999). In order to include also water with rather unusual composition, we chose two water samples from a meromictic open pit lake, Lake Waldsee, which contains large amounts of sulphate and dissolved iron (e.g. Dietz et al., 2008, 2012; Boehrer et al., 2009, von Rohden et al., 2010; Moreira et al., 2011). Finally, we used seawater, of which the composition is known at high accuracy, as a reference water for a standard comparison. Table 1 presents the original chemical compositions of the different lakes considered in the testing of the RHO_LAMBDA expression. Data were derived from chemical analysis (for experimental details see Appendix A) or literature (for references see Table 1). We complemented the set using synthetically produced lake water of differing composition and concentration from the work by Gomell and Boehrer (2015) in order to test systematically the influence of composition and concentration on the values of the coefficients λ_0 and λ_l (for experimental details see Appendix).

For critical comparison with other density equations, this assessment section (Sect. 3) consists of two major parts: first we check the accuracy for different lakes and water samples and secondly we provide the lambda coefficients of several aquatic systems where we have direct measurements or a specifically obtained approach to density (e.g., Mono Lake or seawater) to check the accuracy of ρ_i in general. Table 2 presents the results of the intermediate step calculations to obtain λ_0 and λ_l . As references for the assessment, we used the measured (for details see Appendix) or published data (Figure 1 and 1b, Table 2).

The quantitative comparison between the different methods (including the here presented method, RHO_LAMBDA) and the reference values is shown in Fig. 1. Our approach mainly aimed at representing the density contribution of solutes. Hence, we related the difference to our reference with the contribution of the solutes

$$\text{Rel.Error} = (\rho_\lambda - \rho_{\text{ref}}) / (\rho_{\text{ref}} - \rho_w) \quad (4)$$

For temperatures in the range of 1-30°C, usually found in typical limnic conditions, the values of the relative error defined by Eq. (4) are displayed in the right column of Fig. 1. On purpose, we obtained the chemical composition from a different source (sample) than the density measurement. In this way, the variability of the water composition within one lake was included in the error determination in our assessment.

To judge the accuracy of our approach, we also inserted results from other formulas in common use for transferring CTD data into density: we included UNESCO (Fofonoff and Millard, 1983), TEOS-10 (IOC et al., 2010), Chen and Millero (1986) and Bührer and Ambühl (1975) (Fig. 1) as far as possible according to the defined range of applicability of the single formula.

Rappbode Reservoir: The measured conductance (κ_{25}) of our Rappbode Reservoir sample was 0.1579 mS cm⁻¹, which differed only by 4% from the value 0.1635 mS cm⁻¹ calculated using the PHREEQC electrical conductivity algorithm at 25°C (described in Atkins and De Paula 2009). This is within the measurement accuracy of the chemical analysis. Reference density was produced by measuring in a densitometer PAAR DSA 5000 from 1 to 30°C.

We can see that the RHO_LAMBDA method reproduced the reference values of the water sample from Rappbode Reservoir with a relative error ranging from -12.7% to 4.3%. The deviation from the reference was lower than 5% in the range 10 to 27 °C. Among the other compared approaches, TEOS-10 showed the best results with relative error ranging from -15.7% to 0.1%. The Bührer and Ambühl (1975) approach resulted in relative error ranging from -4.0% to 99.3% and strongly rising with temperatures increasing above 20°C. Results according to Chen and Millero (1986) ranged between -37.8% and -25.3%.

Lake Geneva: Calculated and measured electrical conductivity (κ_{25}) of a water sample from 07.11.2013 differed by less than 1% for 25°C (Table 2). Reference density was produced from this sample in a PAAR DSA 5000 densitometer. The relative error ranged from -11.5% to -4.6% for our RHO_LAMBDA approach. Bührer and Ambühl (1975) (relative error -15.3% to 21.7%), TEOS-10 (relative error -12.9% to -7.8%) and Chen and Millero (1986) (relative error -50.9% to -47.6%) showed larger deviations from the reference.

Lake Constance: The composition shown in Table 1 mainly coincided with the analysis done by Stabel (1998). The calculated conductivity at 25 °C (κ_{25}) of 0.330 mS cm⁻¹ differed from the measured value of 0.322 mS cm⁻¹ by 3 %. The

reference density was again from measurements in a PAAR DSA 5000 densitometer. The relative error ranged from -9.7% to -4.2% for RHO_LAMBDA approach. TEOS-10 (relative error -12.2% to -8.6%), Bühler and Ambühl (1975) (relative error -17.4% to 14.6%) and Chen and Millero (1986) (relative error -46.6% to -44.1%) had again larger deviations from the reference. The strong increase of the relative error of Bühler and Ambühl (1975) with temperature was smallest for Lake
5 Constance compared to the other freshwater lakes.

Mono Lake: We evaluated density for a water sample of conductivity $\kappa_{25} = 85.67 \text{ mS cm}^{-1}$ which was provided by Jellison et al. (1999) and which differed by 12 % from the calculated value 96.61 mS/cm using the PHREEQC algorithm. The density formula by Jellison et al. (1999) was used as the reference density. In this case, the relative error using RHO-LAMBDA
10 ranged from -9.5% to -1.5% even in this lake with such saline waters and unusual composition. Also in this case, TEOS-10 showed larger deviation from the reference (relative error -10.4% to -5.2%). The largest relative error was found for the UNESCO equation according to Foffonof and Millard (1983) (relative error -39.9% to -36.0%).

Lake Waldsee mixolimnion / Lake Waldsee monimolimnion: This case presented a meromictic open pit lake (Boehrer et al., 2008; Dietz et al., 2008, 2012; von Rohden et al., 2010; Moreira et al., 2011) of moderate salinity (0.22 psu in the
15 mixolimnion and 0.6 psu in the monimolimnion, Moreira et al. 2011), but its composition differed from the usual carbonate or chloride waters. Composition was obtained from Dietz et al. (2008, 2012). The DOC contribution was added according to Dietz et al. (2012). This correction increased density by 0.015 kg m^{-3} in the mixolimnion and by 0.06 kg m^{-3} in the monimolimnion.

20

The calculated κ_{25} differed by 7.0% from the reference value in the mixolimnion and by 7.6% in the monimolimnion (Table 2). This was the highest difference between reference and calculated value of all waters considered in this study. Probably, the very special chemical composition of the waters was the reason. The missing data for ammonia and silicate may also have contributed, in particular in the monimolimnion. Measurements in the work Boehrer et al. (2009) were used as density
25 reference.

The relative error of the RHO-LAMBDA approach ranged from -8.4% to -3.9% in the mixolimnion. In the monimolimnion, the relative error ranged from -11.9% to -9.8% for the RHO_LAMBDA approach. The deviation from the reference was substantially larger for all other compared approaches (Figures 1 and 1b). The averages of the absolute values of the relative
30 error were 22.8%, 52.0% and 52.3% for TEOS-10 (IOC et al., 2010), Chen and Millero (1986) and UNESCO (Foffonof and

Millard, 1983) in the mixolimnion, respectively. In the monimolimnion, the values were 35.2% for TEOS-10, 60.0% for Chen and Millero (1986) and 60.2% for UNESCO (Foffonof and Millard, 1983).

5 **Seawater:** The seawater composition was obtained from Millero et al. (2008) and we used TEOS-10 (IOC et al., 2010) as our sea water density reference. Electrical conductivity was calculated for this composition and resulted in 53.76 mS cm⁻¹, while the reference value given by Millero et al. (2008) was 53.06 mS cm⁻¹. That meant the deviation was 1.3%. As expected – both formulas were specifically designed for ocean water –, the relative error of the UNESCO approach according to Foffonof and Millard (1983) was very small, ranging between -0.02% and -0.01%. This was probably a result of numerical uncertainties of the calculations. The relative error of our RHO-Lambda approach ranged between -0.75% and 0.68%.

10 4 Discussion

In all cases, our density approach reproduced the density contribution of the salts to within 10%. This is better than most of the other approaches, which differed by up to 60% from the correct values. Even in the case of very low concentrations (Rappbode Reservoir) and very high concentrations (Mono Lake) as well as in very special water composition (mine lake Waldsee), the 10% accuracy for the salt contribution was achieved with our RHO_LAMBDA approach. The observed strong
15 increase of the relative error with temperature for Bühler and Ambühl (1975) was caused by its validity limited to 24°C. Spatial and temporal variability of solute composition could contribute to errors in density calculation. However, where we attained chemical composition separately (i.e. from another sample) than the density information, this error is intrinsically included in our assessment and hence in the value that we supply for the RHO_LAMBDA approach.

20 The first coefficient λ_0 varied by more than a factor of 2 between 0.37 to 0.88 kg cm m⁻³ mS⁻¹, see Fig.2. This explained that a density formula with constant coefficients could never be able to mimic density accurately for a larger range of lake waters. Obviously the coefficient λ_0 depended on the composition of the solutes. A dominance of double charged ions – opposed to single charged ions – lead to higher values of λ_0 . This effect was clearly visible in the inclusion of calculated values for a NaCl solution of 1g L⁻¹ and a CaSO₄ solution of 1g L⁻¹ (Fig. 2).

25

Also, the concentration of solutes had a decisive effect on the coefficients. We used density measurements of a dilution series of synthetic lake waters by Gomell and Boehrer, (2015) of 1, 3, 10, 30, or 90 g L⁻¹ of a mixture of KCl, NaHCO₃ and Na₂SO₄. We included lambda coefficients from the RHO_LAMBDA approach “Mix” together with regressions of the published measured data “Mix-M” (Fig. 2). Both empirical data as well RHO_LAMBDA results reflected the concentration

effect on λ_0 of a factor of 1.5. Although not perfect, the agreement between empirical data and RHO_LAMBDA values lay within the 10% margin we found for lake waters above.

5 Values for λ_l nearly all lay between -0.001 and $-0.002 \text{ kg cm m}^{-3} \text{ mS}^{-1} \text{ K}^{-1}$. Hence, the λ_l term delivered a small contribution in all cases, i.e. always an order of magnitude smaller compared to the λ_0 term. As a consequence, it could be neglected for most limnological applications. Though not really necessary for an absolute density calculation, λ_l was included to also represent the shift of temperature of maximum density for a given lake water composition, which could not be achieved with the λ_0 term alone. Negative values of λ_l indicated a shift of the temperature of maximum density to lower temperatures. A closer look at the λ_l values revealed that some empirical values (also Mono Lake reference derived from empirical
10 measurements) were considerably lower than expected from coefficients of physical chemistry. However, the difference posed the question of how accurately the shift of temperature of maximum density would actually be indicated by coefficients of physical chemistry literature. The largest discrepancies appeared for freshwater lakes (Rappbode Reservoir, Lake Geneva, Lake Constance) where the shift is small.

15 The values of λ_0 and λ_l have also been calculated using direct measurements of density (starred values, λ_0^* and λ_l^*). In the case of λ_0 only slight differences can be found between the values calculated from chemical composition and from direct measurements of density. However, those differences increase in the case of λ_l , as mentioned above.

5 Conclusions

20 We showed that the correlation between electrical conductivity and density depends strongly on the composition and concentration of solutes. As a consequence, the limnic range cannot be covered with one formula with constant coefficients. However, a simple mathematical addition of two terms to a pure water formula is able to represent the density contribution of solutes in all our examples with an error of less than 10%. This is sufficient for most limnological applications and is better than any other density approach based on CTD data, if not specifically designed for a given lake water.

25 Only two coefficients λ_0 and λ_l need to be evaluated: While λ_0 varies considerably between lakes, the numerical evaluation of λ_l delivers very similar values of $\lambda_l \sim -0.0015 \text{ kg cm m}^{-3} \text{ mS}^{-1} \text{ K}^{-1}$ for any lake water composition. Hence, once λ_0 has been evaluated for a lake, a rather accurate and simple density formula can be used for CTD data. The approach uses conductance κ_{25} , which can be measured in limnic waters, and thus avoids salinity, which is badly defined for limnic waters and, hence, a

precarious quantity. The inclusion of this simple and more accurate approach for potential density calculation in numerical lake models is therefore recommended.

For the convenient use and implementation, a density calculator tool is provided on <https://sourceforge.net/projects/densitycalc>

Appendix A

Measurement of samples taken for this study

All samples were taken as surface samples and stored cooled and without bubbles in polyethylene bottles until measurements and analysis in the lab.

5

Density measurements were done in 1°C steps between 1°C and 30°C using a PAAR DSA500 densitometer. Measurements of electrical conductivity were done with a MultiLab-Pilot conductivity meter (WTW, Germany).

10 pH was measured using a HQ11d pH-meter (Hach-Lange, Germany) in the lab. Sulphate (SO_4^{2-}), and chloride (Cl^-) were analysed by suppressed conductivity using an ICS-3000 ion chromatography system (Dionex, Idstein, Germany) and automatically generated potassium hydroxide eluent. Concentrations of Ca, Mg, Na, K, Al, Fe, and Mn were determined by optical emission spectroscopy with inductively coupled plasma (ICP-OES, Perkin-Elmer, OPTIMA 3000, Germany) (Baborowski, et al., 2011). Acidity and alkalinity were measured by an automatic titrator (Metrohm, Germany). Bicarbonate and carbonate were calculated based on acidity, alkalinity and pH using PHREEQC (Parkhurst and Appelo 1999).

15

Nitrate (NO_3^-) (DIN_EN_ISO_13395, 1996; Herzsprung, et al., 2005), ammonium (NH_4^+) (Krom, 1980; DIN_EN_ISO_11732, 1997), and silicate (Si(OH)_4) (Smith & Milne, 1981) were measured by continuous flow analysis (CFA, Skalar, The Netherlands) (Herzsprung, et al., 2006).

20 Fluoride (F^-) and borate (B(OH)_4^-) were not included into the analyses because they usually are not relevant for density in typical freshwater lakes.

Corrections of original chemical analyses for charge balance

25 If the charge balance between cations and anions was higher than 5% or below -5%, the concentrations of cations were increased or diminished to reach balance by keeping the ratios of the cations to each other constant. The following corrections were necessary: reduction by 16% for Lake Geneva, reduction by 10.4% for Lake Constance, increase by 15% for Mono Lake, increase by 7% for mixolimnion and reduction by 15% for monimolimnion of Lake Waldsee.

Application of TEOS10 algorithm in the Assessment

The initial algorithm of TEOS10 according to IOC et al. (2010) was applied only for seawater serving as reference. In all other cases, the adaptation for limnic systems proposed by Pawlowicz and Feistel (2012) was used since all other systems are limnic. Because the only difference between both algorithms is the calculation of the so-called absolute salinity and the equation for density is the same, “TEOS-“ was used in the legends of all diagrams in Figures 1 and 1b.

Preparation of synthetic solutions

For systematic investigation of dependencies of coefficients λ_0 and λ_1 we prepared solutions of pure NaCl (1 g L⁻¹) and pure CaSO₄ (1 g L⁻¹) and proportional mixtures of KCl, NaHCO₃ and Na₂SO₄ having overall concentrations of 1, 3, 10, 30 and 90 g L⁻¹. The water samples are labelled using the chemical formula of the salts (NaCl; CaSO₄) and as “MixN” with N being a number indicating the concentration. More detail about these prepared solutions can be found in Gomell and Boehrer (2015).

Software

All the density methods have been implemented in Python 2.7 except the TEOS-10 (IOC et al., 2010). For TEOS-10 the original Fortran 90 library has been downloaded from <http://www.teos-10.org/software.htm> and compiled using f2py. The generated Python library has been used directly for the calculations using the Python 2.7 scripts. All the results presented in this manuscript can be obtained using the “density calculator” provided in <https://sourceforge.net/projects/densitycalc>

20

Acknowledgements

We thank Ulrich Lemmin for taking and sending a water sample from Lake Geneva, and Karsten Rinke for a water sample from Lake Constance.

References

- Appelo, C.A.J.: Specific Conductance: how to calculate, to use, and the pitfalls.
<http://www.hydrochemistry.eu/exmpls/sc.html> Last access, June 2016.
- Atkins, P., de Paula, A.: Physical Chemistry, 9th ed, Oxford University Press, 2009.
- 5 Baborowski, M., Büttner, O., Einax, J. W.: Assessment of Water Quality in the Elbe River at Low Water Conditions Based on Factor Analysis, *Clean – Soil, Air, Water*, 39, 437 – 443, doi: 10.1002/clen.201000373, 2011.
- Boehrer, B., Dietz S., von Rohden, C., Kiwel, U., Jöhnk, K., Naujoks, S., Ilmberger, J., Lessmann, D.: Double-diffusive deep water circulation in an iron-meromictic lake, *Geochem. Geophys. Geosy.*, 10(6), Q06006, doi: 10.1029/2009GC002389, 2009.
- Boehrer, B., Schultze, M.: Stratification of lakes, *Rev. Geophys.*, 46, RG2005, doi: 10.1029/2006RG000210, 2008.
- 10 Boehrer, B., Herzsprung, P., Schultze, M., Millero, F. J.: Calculating density of water in geochemical lake stratification models, *Limnol. Oceanogr-Meth.*, 8, 567 – 574, doi: 10.4319/lom.2010.8.0567, 2010.
- Bührer H., Ambühl, H.: Die Einleitung von gereinigtem Abwasser in Seen, *Schweizerische Zeitschrift für Hydrologie*, 37 (2), 347 – 369, doi: 10.1007/BF02503411, 1975.
- Burchard, H., Bolding K., Villarreal M.R.: GOTM—a general ocean turbulence model. Theory, applications and test cases, 15 *Tech. Rep. EUR 18745 EN*, European Commission, 1999.
- Chen, C.-T.A., Millero, F.J.: Precise thermodynamic properties for natural waters covering only the limnological range, *Limnol. Oceanogr.*, 31, 657 – 662, 1986.
- Cole, T.M., Buchak, E.M.: CE-QUAL-W2: A Two-Dimensional, Laterally Averaged, Hydrodynamic and Water Quality Model Version 2.0, US Army Corps of Engineers, Waterways Experiment Station, 1995.
- 20 Dietz S., Seebach, A., Jöhnk, K.D., Boehrer, B., Knoller, K., Lessmann, D.: Meromixis in mining lake Waldsee, Germany: hydrological and geochemical aspects of stratification, *Verh. Int. Verein. Limnol.*, 30(3), 485 – 488, 2008.
- Dietz S., Lessmann, D., Boehrer, B.: Contribution of Solutes to Density Stratification in a Meromictic Lake (Waldsee/Germany), *Mine Water Environ.*, 31, 129 – 137, doi: 10.1007/s10230-012-0179-3, 2012.
- DIN_EN_ISO_11732. Water quality - Determination of ammonium nitrogen - Method by flow analysis (CFA and FIA) and 25 spectrometric detection (ISO 11732:2005); German version EN ISO 11732:2005. Beuth Verlag. 1997.

- DIN_EN_ISO_13395. Water quality - Determination of nitrite nitrogen and nitrate nitrogen and the sum of both by flow analysis (CFA and FIA) and spectrometric detection (ISO 13395:1996); German version EN ISO 13395:1996. Beuth Verlag, 1996.
- 5 Fofonoff, N.P., Millard Jr., R.C.: Algorithms for communication of fundamental properties of seawater, UNESCO technical papers in marine science, 44, 1983.
- Gal, G., Hipsey, M.R., Parparov, A., Wagner, U., Makler, V., Zohary, T.: Implementation of ecological modeling as an effective management and investigation tool: lake Kinneret as a case study, *Ecol. Model.*, 220, 1697 – 1718, doi: 10.1016/j.ecolmodel.2009.04.010, 2009.
- Gomell, A. and Boehrer B.: Accuracy of lake water density calculated from molar volumes: RHOMW (submitted), 2015.
- 10 Herzsprung, P., Duffek, A., Friese, K., de Rechter, M., Schultze, M., von Tuempling, W.: Modification of a continuous flow method for analysis of trace amounts of nitrate in iron-rich sediment pore-waters of mine pit lakes, *Water Research*, 39, 1887 – 1895, doi: 10.1016/j.watres.2005.02.017, 2005.
- Herzsprung, P., Bozau, E., Büttner, O., Duffek, A., Friese, K., Koschorreck, M., Schultze, M., von Tümping, W., Wendt-Potthoff, K.: Routine analysis of sediment pore water of high ionic strength, *Acta Hydroch. Hydrob.*, 34, 593 – 607, doi: 10.1002/aheh.200500656, 2006.
- 15 Hodges, B., Dallimore, C.: Estuary, lake and coastal ocean model: ELCOM, v3.0 user manual, Centre for Water Research, Univ. Western Australia, (accessed on line 12 March 2014), 2007.
- Imberger, J., Patterson, J.C.: A dynamic reservoir simulation model—DYRESM: 5, in: *Transport models for inland and coastal waters*, edited by: Fischer H., Academic Press, New York, 310 – 361, 1981.
- 20 Imboden, D.M., Wüest, A.: Mixing mechanisms in lakes, in: *Physics and chemistry of lakes*, edited by: Lerman A., Imboden D.M., Gat J.R., Springer, Berlin, 83 – 138, 1995.
- Imerito, A.: Dynamic reservoir simulation model – DYRESM v4.0: science manual [online] http://www.cwr.uwa.edu.au/software1/CWRDownloads/modelDocs/DYRESM_Science.pdf (posted 12 Mar 2014), 2002.
- IOC, SCOR, and IAPSO.: The international thermodynamic equation of seawater - 2010: Calculation and use of 25 thermodynamic properties, Manual and Guides No. 56. Intergovernmental Oceanographic Commission, UNESCO (English), <http://www.TEOS-10.org>, 2010.
- Jellison, R., Macintyre, S., Millero, F.J.: Density and conductivity properties of Na-CO₃-Cl-SO₄ from Mono Lake, California, USA, *International Journal of Salt Lake Research* 8, 41 – 53, doi:10.1007/BF02442136, 1999.

- Karakas, G., Brookland, I., Boehrer, B.: Physical characteristics of Acidic Mining Lake 111, *Aquatic Sciences* 65, 297 – 307, doi:10.1007/s00027-003-0651-z, 2003.
- Katsev, S., Crowe, S.A., Mucci, A., Sundby, B., Nomosatyo, S., Haffner, G.D., Fowle, D.A.: Mixing and its effects on biogeochemistry in the persistently stratified, deep, tropical, Lake Matano, Indonesia, *Limnol. Oceanogr.*, 55(2), 763 – 776, 5 2010.
- Nixdorf, E., Boehrer, B.: Quantitative analysis of biogeochemically controlled density stratification in an iron-meromictic lake, *Hydrol. Earth Syst. Sci.* 19 (11), 4505 – 4515, 2015
- Kell, G.S.: Density, thermal expansivity, and compressibility of liquid water from 0° to 150°C: correlations and tables for atmospheric pressure and saturation reviewed and expressed on 1968 temperature scale, *J. Chem. Eng. Data*, 20, 97 – 105, 10 10 2011/je60064a005, 1975.
- Krom, M.: Spectrophotometric determination of ammonia; a study of modified Berthelot reaction using salicylate and dichloroisocyanurate, *Analyst* 109, 305-316, doi: 10.1039/AN9800500305, 1980.
- Millero, F.J.: *Physical Chemistry of Natural Waters*; Wiley-Interscience, New York, 2001.
- Millero, F.J., Feistel, R., Wright, D.G., McDougall, T.J.: The composition of Standard Seawater and the definition of the 15 Reference-Composition Salinity Scale, *Deep Sea Res.*, 1 55, 50 – 72, doi:10.1016/j.dsr.2007.10.001, 2008.
- Moreira, S., Boehrer, B., Schultze, M., Dietz, S., Samper, J.: Modelling geochemically caused permanent stratification in Lake Waldsee (Germany), *Aquatic Geochemistry*, 17, 265 – 280, doi: 10.1007/s10498-011-9133-4, 2011.
- Parkhurst, D.L., Appelo, C.A.J.: Users guide to PHREEQC (version 2). A Computer program for speciation, batch-reaction, one-dimensional transport, and inverse geochemical calculations, Water-Resources Investigation Report 99-4259, U.S. 20 Geological Survey, 1999.
- Pawlowicz, R., Wright, D. G., Millero, F. J.: The effects of biogeochemical processes on oceanic conductivity/salinity/density relationships and the characterization of real seawater, *Ocean Sci.*, 7, 363-387, doi:10.5194/os-7-363-2011, 2011.
- Pawlowicz, R., Feistel, R.: Limnological applications of the Thermodynamic Equation of Seawater 2010 (TEOS-10), 25 *Limnol. Oceanogr-Meth.*, 10, 853–867, 2012.
- Rinke, K., Kuehn, B., Bocaniov, S., Wendt-Potthoff, K., Büttner, O., Tittel, J., Schultze, M., Herzsprung, P., Rönicke, H., Rink, K., Rinke, K., Dietze, M., Matthes, M., Paul, L., Friese, K.: Reservoirs as sentinels of catchments: the Rappbode Reservoir Observatory (Harz Mountains, Germany), *Environ. Earth Sci.*, 69 (2), 523 – 536, doi: 10.1007/s12665-013-2464-2, 2013.

- Rodrigo, M.A., Miracle, M.R., Vicente, E.: The meromictic Lake La Cruz (Central Spain). Patterns of stratification, *Aquatic Sciences*, 63, 406-416, doi: 10.1007/s00027-001-8041-x, 2001.
- Sanchez España, J., Lopez Pamo, E., Diez Ercilla, M., Santofimia Pastor, E.: Physico-chemical gradients and meromictic stratification in Cueva de la Mora and other acidic pit lakes of the Iberian Pyrite Belt, *Mine Water Env.*, 28, 15 – 29, doi: 10.1007/s10230-008-0059-z, 2009.
- Smith, J. D., Milne, P. J.: Spectrophotometric determination of silicate in natural waters by formation of small alpha, Greek-molybdosilicic acid and reduction with a tin(IV)-ascorbic acid-oxalic acid mixture, *Analytical Chimica Acta*, 123, 263 – 270, doi: 10.1016/S0003-2670(01)83179-2, 1981.
- Stabel, H. H.: Chemical composition and drinking water quality of the water from Lake Constance, *Arch. Hydrobiol. Spec. Issues Advanc. Limnol.*, 53, 31 – 38, 1998.
- Tanaka, M., Girard, G., Davis, R., Peuto, A., Bignell, N.: Recommended table for the density of water between 0°C and 40 °C based on recent experimental reports, *Metrologia*, 38, 301 – 309, doi: 10.1088/0026-1394/38/4/3, 2001.
- Umlauf, L., Burchard, H., Bolding, K.: General Ocean Turbulence Model. Scientific documentation. V3.2, Marine Science Reports no. 63, Baltic Sea Research Institute Warnemünde, Warnemünde, Germany, 2005.
- Vollmer, M. K., Weiss, R. F., Williams, R. T., Falkner, K. K., Qiu, X., Ralph, E. A., Romanovsky, V. V.: Physical and chemical properties of the waters of saline lakes and their importance for deep-water renewal: Lake Issyk-Kul, Kyrgyzstan, *Geochim. Cosmochim. Acta* 66, 4235 – 4246, doi:10.1016/S0016-7037(02)01052-9, 2002.
- von Rohden, C., Boehrer, B., Ilmberger, J.: Evidence for double diffusion in temperate meromictic lakes, *Hydrology and Earth System Sciences*, 14, 667-674, doi: 10.5194/hess-14-667-2010, 2010.
- Wüest, A., Piepke, G., Halfmann, J.D.: Combined effects of dissolved solids and temperature on the density stratification of Lake Malawi (East Africa), in: *The limnology, climatology and paleoclimatology of the East African Lakes*, edited by: Johnson T.C., and Odada E.O., Gordon and Breach, New York, 183–202, 1996.

5 **Table 1. Original chemical composition of the water in different test cases presented in the Sect. 3. All values except pH are presented in mg L⁻¹. (NA – not analysed)**

	Reservoir Rappbode	Lake Geneva	Lake Constanc e	Mono Lake	Waldsee (mixo.)	Waldsee (monimo.)	Seawater
pH	7.14	7.0	7.9	9.8.	7.1	6.7	7.0
Na⁺	9.30	11.1	5.60	32933.18	9.66	10.81	10919.56
K⁺	1.00	1.74	1.48	1610.92	7.04	10.17	404.23
Ca²⁺	13.8	44.30	51.2	6.01	61.32	89.78	417.38
Mg²⁺	3.30	6.49	9.03	31.59	12.88	17.50	1299.88
NH₄⁺	0.03	<0.010	<0.010	NA	NA	NA	NA
Fe	NA	<0.025	<0.01	NA	0.50	131.79	NA
Fe²⁺	0.00	NA	NA	NA	0.22	117.83	NA
Fe³⁺	NA	NA	NA	NA	0.28	13.96	NA
Mn²⁺	0.004	<0.010	<0.007	NA	0.22	0.88	NA
Al³⁺	0.01	<0.005	<0.02	NA	NA	NA	NA
F⁻	0.00	NA	NA	NA	NA	NA	1.31
Cl⁻	16.8	10.39	7.81	19043.74	5.67	4.96	19598.77
SO₄²⁻	18.5	44.56	33.26	10912.64	184.44	176.75	2747.05
NO₃⁻	6.50	0.483	3.37	0.00	2.85	1.24	NA
HCO₃⁻	28.07	94.58	136.68	3276.67	57.97	374.04	106.15
CO₃²⁻	NA	0.000	NA	17726.95	0.00	0.00	14.53
Si(OH)₄	4.50	0.582	4.42	NA	NA	NA	NA
B(OH)₄⁻	NA	NA	NA	752.45	NA	NA	4.23
DOC density correction (kg/m³)*	0.0	0.0	0.0	0.0	0.015	0.060	0.0
Correction**	0%	-16%	10.4%	15%	7%	-15%	0%
Data Sources	Measured	Measured	Measured	Jellison et al. (1999)	Dietz et al. (2008) Dietz et al. (2012).		Millero et al. (2008)

* Density modified by addition of this quantity expressed in kg/m³. ** Correction of cation concentrations for charge balance



Table 2. Summary of the calculated values for obtaining RHOMV_LAMBDA coefficients. Lambdas and references. λ_0 and λ_I represent the lambda values obtained using the chemical composition of Table 1 to calculate density and conductivity at 5 and 25 °C, while λ_0^* and λ_I^* represent the lambda values obtained from a linear regression of the density reference. λ_0 and λ_0^* are expressed in $\text{kg cm}^{-3} \text{mS}^{-1}$ and λ_I and λ_I^* are expressed in $\text{kg cm}^{-3} \text{mS}^{-1} \text{K}^{-1}$. Density values are expressed in kg/m^3 . Corrected Salinity shows the values of Practical salinity correct by a factor of 1.00488 for Chen and Millero (1986) method. For more details see text.

5



	Reservoir Rapphode	Lake Geneva	Lake Constanc	Mono Lake	Waldsee (mixo.)	Waldsee (monimo.)	Seawater
κ_{20} (measured) ($\mu\text{s cm}^{-1}$)	142.0	263	302	NA	NA	NA	NA
κ_{25} (measured) ($\mu\text{s cm}^{-1}$)	157.9	294	333.7	85668	550	1050	53064.9
κ_{25} (calc.) ($\mu\text{s cm}^{-1}$)	163.49	296.81	329.77	96609.50	588.50	969.93	53762.53
Practical Salinity	0.0770	0.127	0.1613	83.04	0.220	0.60	35.00
Absolute Salinity	0.0997	0.22	0.251	91.11	0.351	0.78	35.165
Corrected Salinity	0.0774	0.128	0.1621	83.45	0.221	0.6029	35.171
ρ_{MV} (T=25°C)	997.130	997.222	997.252	1075.480	997.383	997.744	1023.662
ρ_{MV} (T=5°C)	1000.053	1000.149	1000.181	1083.661	1000.316	1000.691	1028.150
ρ_{ref} (T=25°C)	997.126	997.228	997.253	1069.936	997.391	997.958	1023.344
ρ_{ref} (T=5°C)	1000.059	1000.168	1000.194	1075.447	1000.332	1000.923	1027.600
Data Sources	Measured	Measured	Measured	Jellison et al. (1999)	Dietz et al. (2008) Dietz et al. (2012) von Rohden et al. (2010) Moreira et al.(2011)		Millero et al. (2008)
λ_0	0.51	0.59	0.62	0.81	0.60	0.78	0.50
λ_I	-0.0012	-0.0013	-0.0014	-0.0027	-0.0011	-0.0014	-0.0015
λ_0^*	0.50	0.62	0.64	0.85	0.63	0.87	0.50
λ_I^*	-0.0042	-0.0034	-0.0033	-0.0015	-0.0020	-0.0022	-0.0013
A.E. ¹	4.3%	6.9%	5.9%	5.5%	5.2%	10.4%	0.4%
M.E. ²	12.7%	11.5%	9.7%	9.5%	8.4%	11.85%	0.75%

¹ Average absolute value of relative error. ² Max. Absolute value of relative error.



5



10



15



20





Figure 1: Test cases (part I). Left panel presents the density curves of the different methods and the right panel shows the relative error of the density contribution of the solutes respect to the reference. In all the cases, measured values have been used as reference except in the cases of the Mono Lake (Jellison et al., 1999) and seawater (TEOS-10, IOC et al., 2010) which use specific density equations.










Figure 1b: Test cases (part II)



5 Figure 2. Distribution of the values of λ_1 versus λ_0 . Concentrations for NaCl and CaSO₄ are 1 g/L in both cases. Chemical composition for the lakes and seawater are presented in Table 1. The water samples labelled as “Mix” are proportional mixtures of KCl, NaHCO₃ and Na₂SO₄ of 1, 3, 10, 30 and 90 g/L (Gomell and Boehrer, 2015) and the water samples labelled as “-M” correspond to the lambda coefficients obtained from direct measurements of density and conductivity.