

Impacts of future climate change on urban flood volumes in Hohhot City
in Northern China: benefits of climate mitigation and adaptations

Qianqian Zhou^{1,2}, Guoyong Leng^{2,*}, Maoyi Huang³

¹School of Civil and Transportation Engineering, Guangdong University of Technology,
Waihuan Xi Road, Guangzhou 510006, China

²Joint Global Change Research Institute, Pacific Northwest National Laboratory, College Park
MD 20740, USA

³Earth System Analysis and Modeling Group, Pacific Northwest National Laboratory, Richland,
WA 99352, USA

*Corresponding author address: Guoyong Leng, Joint Global Change Research Institute, Pacific
Northwest National Laboratory, College Park MD, 20740.

E-mail: guoyong.leng@pnnl.gov

Contents

1. Reviewer #1

Reviewer #1 Comment 1 3

Reviewer #1 Comment 2 3

Reviewer #1 Comment 3 3

Reviewer #1 Comment 4 4

Reviewer #1 Comment 5 4

2. Reviewer #2

Reviewer #2 Comment 1 6

Reviewer #2 Comment 2 7

Reviewer #2 Comment 3 8

Reviewer #2 Comment 4 8

Reviewer #2 Comment 5 9

Reviewer #2 Comment 6 9

Reviewer #2 Comment 7 10

Reviewer #2 Comment 8 10

Reviewer #2 Comment 9 11

Reviewer #2 Comment 10 12

Reviewer #2 Comment 11 12

Reviewer #2 Comment 12 12

Reviewer #2 Comment 13 13

Reviewer #2 Comment 14 14

Reviewer #2 Comment 15 14

Reviewer #2 Comment 16 15

Reviewer #2 Comment 17 16

Reviewer #2 Comment 18 16

Reviewer #2 Comment 19 16

Reviewer #2 Comment 20 17

Reviewer #2 Comment 21 17

Reviewer #2 Comment 22 18

Reviewer #2 Comment 23 18

Reviewer #2 Comment 24 19

Abstract

The author would like to thank all reviewers for their dedicated time reviewing the manuscript and for their useful and constructive suggestions. All comments by the reviewers were carefully addressed and the manuscript has substantially benefited from the proposed changes. Here below, the author would like to clarify the changes regarding all comments, which are repeated

in grey boxes. The following convention is applied to denote modification in the original manuscript: **new text**.

1 Reviewer #1

Reviewer #1 Comment 1

I see that the authors made a substantial revision of the article by addressing most of my previous comments. I think the article can become suitable for publication, provided that the comments below are adequately addressed.

Response

We greatly appreciate the reviewer for the thoughtful and encouraging comments on this manuscript. In the revision, we have tried our best to address the comments. More details of response to each specific comment are provided below.

Reviewer #1 Comment 2

Line 154: As I said in the previous review, please remove “all”, as there are more than five GCMs in CMIP5.

Response

Thanks for your suggestion. We have removed “all” in the revision.

Reviewer #1 Comment 3

Line 227: There is currently no information nor figures/tables on the outcomes of the goodness of fit tests, hence I suggest to mention at least some quantitative results in the text.

88 **Response**

89 Thanks for your comments. Please note that our test returns a decision for the null hypothesis of
90 an extreme value distribution rather than a quantitative value, based on MATLAB tool
91 (<https://www.mathworks.com/help/stats/adtest.html>). Results show that our test fails to reject the
92 null hypothesis at the 5% significance level, suggesting that the fitted extreme value distribution
93 could be used to describe the extreme precipitation distribution in the study region.

94 In the revision, the sentence “The goodness-of-fit was tested by calculating the Kolmogorov–
95 Smirnov and Anderson–Darling statistics” was revised to

96 Kolmogorov–Smirnov and Anderson–Darling statistics show that the hypothesis regarding
97 the extreme value distribution is not rejected. That is, the fitted distribution could be well
98 used to describe the extreme precipitation distribution in the study region.
99

Reviewer #1 Comment 4

Line 381: “boundary bars” are commonly referred to as “whiskers”.

100 **Response**

101 Thanks for your comments. In the revision, we have changed “boundary bars” to “whiskers”.
102

Reviewer #1 Comment 5

Figure 3: In this figure it is not clear which lines/bars refer to TFV and which other to the percent increase. Please clarify in the legend (and/or in the caption).

103 **Response**

104 Thanks for your comments. We have re-plotted the figure and added more descriptions in the
105 figure caption. Please check the updated figure and caption below.
106




Figure 3 Changes in total flood volume (TFV) as a function of precipitation intensity at various return periods under RCP8.5 scenario without mitigation and adaptations. Red solid line represents the multi-model ensemble median TFV with shaded areas denoting the ensemble range. Red dashed line is the TFV under present condition. Box plots show the relative changes in TFV by 2020–2040 relative to present condition. Box edges illustrate the 25th and 75th percentile, the central mark is the median and whiskers mark the 5th and 95th percentiles.

2 Reviewer #2

Reviewer #2 Comment 1

In this paper, the authors assessed the benefits of mitigating climate change by reducing greenhouse gas emissions and locally adapting to climate change by modifying drainage systems to reduce urban flooding under various climate change scenarios through a case study conducted in Northern China. As the authors commented, this study accounted for the effects of both climate change mitigation and adaptation together in a consistent framework different from previous studies related to this issue. It would be the most important research outcome of this paper.

Now, the paper presents specific and easily identifiable advance in knowledge, which can be usefully applicable to the profession. With the subject within the scope of the journal, the authors describe the paper's research purpose, main findings, and conclusions in a more concise way. However, I have still several concerns about the paper's method, data, results and conclusions, which need to be modified for final publication.

Response

We greatly appreciate the reviewer for the thoughtful and encouraging comments on this manuscript. In the revision, we have tried our best to address the comments. More details of response to each specific comment are provided below.

Note: line numbers in the response refer to those in the cleaned version of manuscript.

138

Reviewer #2 Comment 2

Cost-effectiveness Issue: The authors compared the reduced total flood volumes by climate change mitigation and drainage system adaptation as functions of return period in Figure 7. From this result, the authors highlight the effectiveness of system adaptations in reducing future flood volumes and comment that this has important implications for the research community and decision-makers involved in urban flood management in the ‘Summary and Conclusions’ part. Because this study only focused on the future changes in urban flood volume followed by the applied different scenarios, there still remains a limitation of this study related to ‘cost-effectiveness issue’. In the ‘Uncertainties and Limitations’ part, the authors added a sentence in lines 453-454 but it seems not enough to explain the limitation of this study. Of course, there are already many meaningful discussions in the ‘Uncertainties and Limitations’ part but I think the main discussion issue of this part should be ‘cost effectiveness’ with valuable references.

139 **Response**

140 Thanks for your comments. We agree that a limitation of this study is lack of assessment of costs
 141 and benefits of adaptation measures from the economic perspective. In the revision, we have
 142 added the following discussions in lines 454-465.

143 In particular, the cost-effectiveness of the proposed adaptation measures should be
 144 accounted for. Indeed, a major limitation of this study is lack of assessment of costs and
 145 benefits of adaptation measures from the economic perspective. In fact, besides the
 146 effectiveness of proposed adaptation measures in reducing flood volume, assessment of the
 147 associated economic costs is essential for flood risk management (Rojas et al., 2013; Veith
 148 et al., 2003; Hinkel et al., 2014; Aerts et al., 2014; Ward et al., 2017). For example, Ward
 149 et al. (2017) showed that investments in urban flood protections with dykes are not
 150 economically attractive everywhere. Higher investment and maintenance costs may
 151 prohibit the implementation of adaptation strategies as proposed in this study. Future
 152 efforts should therefore be devoted to building a framework for assessing the costs and
 153 benefits of urban flood reduction measures and examine whether the reduced losses are
 154 higher than the costs of investments and maintenance of these measures.

155

Reviewer #2 Comment 3

Introduction: The authors need to clarify each condition for other researchers' outcomes. Please pay careful attention to the summary of other researchers' outcomes. For example, Lines 64-66: For example, in Danish design guidelines for urban drainage, a 30% and 40% increase in the precipitation intensity is expected for the 10-and 100-year return periods, respectively (Arnbjerg-Nielsen, 2012). I read this reference, Arnbjerg-Nielsen (2012). but there were research outcomes about the delta change for Denmark. It seems hard to figure out where this sentence is originated from.

156 **Response**

157 Thanks for your comments. We have revised this sentence to:

158 [For example, Arnbjerg-Nielsen \(2012\) reported that the design intensities in Denmark are](#)
159 [projected to increase by 10-50% for return periods ranging from 2 to 100 years.”](#)

160

Reviewer #2 Comment 4

Lines 75-77: For example, Ashley et al. (2005) showed that flooding risks may increase by almost 30 times in comparison to current situations, and effective adaptation measures are required to cope with the increasing risks in the UK. Please refer to any information about flooding risks and current situations.

161 **Response**

162 Thanks for your comments. We have revised this sentence to:

163 [For example, Ashley et al. \(2005\) showed that flood risk \(i.e., occurrence of pluvial](#)
164 [flooding\) in four UK catchments may increase by almost 30 times by 2080s compared to](#)
165 [current conditions around the year 2000, and effective adaptation measures are required to](#)
166 [cope with the increasing risks.](#)

167

Reviewer #2 Comment 5

Lines 77-79: Larsen et al. (2009) estimated that future extreme one-hour precipitation will increase by 20%~60% throughout Europe. Please refer to more specific information about the future year.

168 **Response**

169 Thanks for your comments. We have revised this sentence to:

170 [Larsen et al. \(2009\) estimated that future extreme one-hour precipitation will increase by](#)
171 [20%~60% throughout Europe by 2071–2100 relative to 1961–1990](#)

172

Reviewer #2 Comment 6

Materials and Methods – a. Study region: The authors need to re-organize the structure of this part for helping readers understand the contents clearly (For example, 1) General comments; 2) Major flood event on 11 July 2016; 3) Necessity for adaptation policies; 4) Plan for the year 2020).

173

174 **Response**

175 Thanks for your comments. We have re-organized the structure of this sector following your
176 suggestions. Please check the revision in lines 121-146.

177

Reviewer #2 Comment 7

Materials and Methods – c. Urban drainage modeling: The authors need to summarize only important points, which are directly used for urban drainage modeling in the Storm Water Management Model. Please move several parts to the 'Supplementary Materials' or 'Appendix' part such as Table 1, Equations 1-4 and the related explanations?

178

179 **Response**

Thanks for your comments. In the revision, we have refined the methodology section and moved Table 1, Equations 1-4 and related explanations to the Supplementary Materials following your suggestion.

Reviewer #2 Comment 8

4-hour rainfall time series: Do the authors have any reasons for selecting 4-hour rainfall time series in this study? In lines 223-224, the authors commented that the annual maximum daily precipitation was determined for both historical and future periods.

Response

Thanks for your comments. In this study, a 4-hour rainfall time series was generated for each return period at 10-minute interval. The duration of design rainfalls (i.e. 4-hour rainfall) is selected based on the time of concentration (ToC) of the watershed in the study region, according to the design principles as outlined in [Butler and Davies, 2010; Chow et al., 2013]. In the revision, we have added the following explanations in Lines 197-200.

A 4-hour rainfall time series was generated for each return period at 10-minute intervals. The duration of design rainfalls (i.e., 4-hour rainfall) is selected based on the time of concentration (ToC) of the watershed in the study region, according to the design principles as outlined in Butler and Davies (2010) and Chow et al. (2013).

Yes, the annual maximum daily precipitation was determined for both historical and future periods. In this study, we used the delta change factor to derive future climate scenarios as inputs into our flood drainage model. Specifically, for each year, the annual maximum daily precipitation was determined for both historical and future periods. The generalised extreme value (GEV) distribution was then fitted separately to the two sets of daily values (Coles 2001; Katz et al. 2002). The goodness-of-fit was tested by calculating the Kolmogorov–Smirnov and Anderson–Darling statistics. The value corresponding to each return period was estimated based on the GEV distribution and the changes between future and historical periods were calculated as the change factors. The derived change factor for each return period was then multiplied by the historical design CDS rainfall time series to derive future climate scenarios as inputs into our

urban drainage model. This approach was adopted due to two reasons: 1) Future hourly rainfall data is not readily available; 2) the relative climate change signal simulated by GCMs are argued to be more reliable than the simulated absolute values (Ho et al. 2012).

More details can be found in the revised methodology section and supplementary materials. Discussions on the methodology can also be found in the section “Uncertainties and Limitations” in the revision.

Reviewer #2 Comment 9

Figure 2: The authors need to revise the explanation about Figure 2 (lines 236-245) and the title of the Figure 2 for helping readers understand the contents in a more concise way.

Response

Thanks for your comments. We have added the following descriptions about Figure 2 in Lines 226-231, and the figure caption was also revised accordingly.

A log-linear relationship is assumed to characterize the changes in flood volume with the increase in precipitation intensity as indicated by return periods (Figure 2a) following Zhou et al. (2012) and Olsen et al. (2015). Generally, more TFV (i.e., system overloading) is expected with increase in rainfall intensity. In Figure 2b, the TFVs were linked to their specific occurrence probabilities. The total grey area under the curve denotes the TFVs integrated across various return periods and represents the total expected TFVs per year. The contribution of an individual flood event to total average TFVs is dependent not only on the flood volume, but also its corresponding probability of occurrence.

Reviewer #2 Comment 10

Abbreviation: Please carefully use the word abbreviation. For example, Line 236: The TFV -> The total flood volume (TFV); Line 282: climate change -> climate change (CC).

Response

Thanks for your comments. We have added the full names for these abbreviations in the revision.

Reviewer #2 Comment 11

Weighted mean imperviousness (WMI): Please define how to calculate the WMI.

Response

Thanks for your suggestion. The WMI of a subcatchment is calculated as the average of impervious factors of all landuse types in the subcatchment, weighted by the area of landuse type as follows:

$$WMI = \sum_i IF_i \times A_i / \sum_i A_i$$

Where IF_i and A_i are the impervious factor and area for land use type i , respectively.

In the revision, we have added the equation and explanations for calculating WMI in Lines 255-261.

Reviewer #2 Comment 12

Figure 3: The authors need to revise the explanation about Figure 3 (lines 282-292) for helping readers understand the contents in a more concise way (for example, 1) max; 2) median; 3) min; 4) multi-model ensemble median). □ 1yr -> 1

Response

Thanks for your comments. In the revision, we have re-plotted figure 3 and added more details in the figure caption. Please check the updated figure below.




Figure 3 Changes in total flood volume (TFV) as a function of precipitation intensity at various return periods under RCP8.5 scenario without mitigation and adaptation. Red solid line represents the multi-model ensemble median TFV with shaded areas denoting the ensemble range. Red dashed line is the TFV under present condition. Box plots show the relative changes in TFV by 2020–2040 relative to present condition. Box edges illustrate the 25th and 75th percentile, the central mark is the median and whiskers mark the 5th and 95th percentiles.

Reviewer #2 Comment 13

Figure 4: Please add the x-axis title

Response

Thanks for your suggestion. We have added the x-axis title in the revision.

Reviewer #2 Comment 14

Ratio of flood volume (RFV) in Figure 5: Please define how to calculate the RFV.

Response

Thanks for your suggestion. The RFV is defined as the ratio of flooded volume from overloaded manholes to input rainfall volume. We have added the definition in the revision (Lines 304-305) and revised the figure caption accordingly.

Reviewer #2 Comment 15

TFV reduction (%): Please define how to calculate the TFV reduction. In Figures 4 and 7, the readers can see the related results, mainly composed of negative and positive numbers, respectively. Especially, in Figure 7, the authors need to explain about the negative values for the return periods of 100 and 200 years.

Response

Thanks for your comments. The TFV reduction is calculated as the percentage difference in TFV with mitigation or adaptation compared to that without mitigation or adaptation (i.e., $100 * (TFV_{wo} - TFV_w) / TFV_{wo}$). Here, three scenarios including two adaptation strategies (i.e., Pipe and Pipe+LID) and one climate mitigation are considered and the reduced TFV are inter-compared among the three scenarios in Figure 7 to demonstrate that the proposed adaptation strategies are more effective than climate mitigation in reducing future flooded volume.

In Figure 7, the grey, blue and red bars indicate the TFV reductions with two adaptation strategies and climate mitigation, respectively. Positive values indicate that climate mitigation and/or local adaptation are effective in reducing the system overloading, namely the TFVs, and vice versa. It is shown that climate mitigation can lead to reduction of flood volume ranging from 10 to 40% compared to the scenario without mitigation. Importantly, local adaptations are more effective than climate mitigation in reducing flood volume, as indicated by the much larger values of TFV reductions. As noted by the reviewer, there are minor negative values of TFV reductions for the return period of 100 and 200 years under climate mitigation scenario. The negative value is attributed to the slightly higher increase in precipitation intensity under climate mitigation scenario (RCP26) than the scenario without mitigation (RCP85) as simulated by two of five climate models (i.e., GFDL-ESM2m and NorESM1-M, see Table 1), which translates to a

slight increase in flood volume under climate mitigation scenario. This climate internal variability is partly cancelled by other three climate models, thus leading to very minor negative value when considering the multi-model ensemble mean. This calls for the improvement of climate model performance and the use of more climate models (GCMs) to derive more robust climate projections in the future.

In the revision, we have added relevant explanations and discussions in Lines 351-361.

Overall, climate mitigation can lead to a reduction of flood volume by 10-40% compared to the scenario without mitigation. Notably, there are minor negative values of TFV reductions for the return period of 100 and 200 years under climate mitigation scenario. The negative value is attributed to the slightly higher increase in precipitation intensity under climate mitigation scenario (i.e. RCP26) than the scenario without mitigation (i.e. RCP85) simulated by two of five climate models (i.e., GFDL-ESM2m and NorESM1-M, see Table 1), which translated to slightly larger flood volume under climate mitigation scenario. This climate internal variability is partly cancelled by other three climate models, thus leading to very minor negative value by the multi-model ensemble mean. This calls for the use of more climate models (GCMs) to derive more robust projections in the future studies.

Reviewer #2 Comment 16

Lines 83-85: There are already many journal papers related to this issue. The authors revise the 'Introduction' part to emphasize the novelty of this study.

Response

Thanks for your comments. In the revision, we have revised the introduction to emphasize the novelty of this study in Lines 85-93.

However, previous studies on the effects of climate change mitigation and adaptation are typically conducted separately, and it is unclear which strategy is more effective in reducing urban floods. This study aims to advance our understanding on urban floods within the context of change climate, through investigating the benefits of climate change mitigation (by reducing greenhouse gas emissions [GHG]) and local adaptation (by

improving drainage systems) in reducing future urban flood volumes in a consistent framework.

Reviewer #2 Comment 17

Lines 122-123: Please add the related reference here.

Response

Thanks for your comments. We have added the related reference in the revision.

Reviewer #2 Comment 18

Lines 134-136: Please add the related reference here.

Response

Thanks for your comments. We have added the related reference in the revision.

Reviewer #2 Comment 19

Lines 200-202: Please add the related reference here.

Response

Thanks for your comments. We have added the related reference in the revision. Please note that this paragraph is moved to supplementary materials following your suggestion #7.

Reviewer #2 Comment 20

Lines 251-255: If this explanation is about the adaptation plan for the year 2020, please clarify the plan for the year 2020 in the 'Introduction' part and this part to help readers understand the contents in a more concise way.

Response

Thanks for your comments. We have added relevant descriptions on this in Lines 113-115.

We then designed two plausible adaptation strategies for the study region and investigated how much urban flood volume can be reduced with the adapted systems by 2020s. We also compared the benefits of global-scale climate change mitigation and local adaptation in reducing urban flood volumes to advance our understanding of the effective measures for coping with future urban floods.

Reviewer #2 Comment 21

Lines 260-261: It seems better to start this paragraph with the explanation about the second adaptation scenario. The authors need to re-organize this paragraph.

Response

Thanks for your comments. We have added the following text in Lines 246-251.

The second adaptation scenario was designed to increase the permeable surfaces (e.g., green spaces) and reduce the regional imperviousness in the study region on the basis of pipe capacity enhancement. This scenario is referred to as the Low Impact Development (LID) scenario, and it was used to explore the effectiveness of urban green measures, such as the use of permeable pavements, infiltration trenches, and green roofs. Changes in land imperviousness in LID scenario have direct impacts on the performance of drainage system in managing surface runoff.

Reviewer #2 Comment 22

Lines 269-272: Please give additional information on this part. It is hard to understand the meaning of this sentence.

Response

Thanks for your comments. We have added more details on this in Lines 255-262.

Due to a lack of detailed information about the permeable soil and coverage rates in the study region, the effects of these specific measures cannot be modelled individually. Here,

we used a simplified approach by altering the subcatchment imperviousness to reflect the combined effects of infiltration-related measures. We derived such information by calculating the difference in land use type and imperviousness between the current and planned city maps using a geographical information system (GIS). Figure 1d shows the difference in weighted mean imperviousness ($WMI = \sum_i (IF_i \times A_i) / \sum_i A_i$, Where IF_i and A_i is the impervious factor and area for land use type i , respectively.) for each subcatchment in the current and planned maps, using the commonly applied impervious factors (Pazwash, 2011; Butler and Davies, 2004) for each land use type. The difference in WMI was used to indicate the potential for adaptation based on the city plan.

Reviewer #2 Comment 23

Lines 305-308: Please explain the main reason of these results with discussions.

Response

Thanks for your comments. We have added the following explanations and discussions in Lines 289-296.

Notably, the peak of the total TFV curve was projected to shift from the 1-year event under the RCP8.5 scenario to the 3-year event under the RCP2.6 scenario (Figure 4b), indicating a substantial reduction in the TFVs (especially at the 1-year return period) (Figure 4c). The lower total TFVs under RCP2.6 scenario could be attributed to the smaller magnitude of rainfall intensity than RCP8.5 scenario (Table 1), demonstrating the important role of climate mitigation in reducing urban flood volumes. Overall, climate change mitigation can reduce future flood volumes by 13% compared to the scenario without mitigation, as indicated by the multi-model ensemble median.

Reviewer #2 Comment 24

Line 315: Please clarify where the historical flood points are.

Response

Thanks for your comments. The historical flood points are included in Figure 5a. We have revised the figure and clarified their locations in the figure caption.




Figure 5 Spatial distribution of overloaded pipelines (red colour) induced by the 3-year (left column) and 50-year extreme events (right column) without and with adaptations. The total percentage of overloaded manholes (POM) and ratio of flood volume (RFV) to input rainfall volume are summarised for each scenario. Historical flood points and local land use, mainly the traffic network and green spaces, are shown in (a).

Reference

- Aerts, J. C., Botzen, W. W., Emanuel, K., Lin, N., de Moel, H., & Michel-Kerjan, E. O. (2014). Evaluating flood resilience strategies for coastal megacities. *Science*, 344(6183), 473-475.
- Butler, D., and J. Davies (2010), *Urban drainage*, Third Edition, CRC Press, London. ISBN: 0415455251.

- Chow, V. T., D. R. Maidment, and L. W. Mays (2013), *Applied Hydrology*, 2nd Edition, edited, McGraw-Hill, New York. ISBN: 007174391X.
- Giuntoli, I., Vidal, J. P., Prudhomme, C., Hannah, D. M. (2015). Future hydrological extremes: the uncertainty from multiple global climate and global hydrological models. *Earth System Dynamics*, 6(1), 267.
- Hinkel, J., et al. (2014). Coastal flood damage and adaptation costs under 21st century sea-level rise. *Proceedings of the National Academy of Sciences*, 111(9), 3292-3297.
- Ho, C. K., Stephenson, D. B., Collins, M., Ferro, C. A., & Brown, S. J. (2012). Calibration strategies: a source of additional uncertainty in climate change projections. *Bulletin of the American Meteorological Society*, 93(1), 21.
- Rojas, R., Feyen, L., and Watkiss, P.: Climate change and river floods in the European Union: Socio-economic consequences and the costs and benefits of adaptation, *Global Environmental Change-Human and Policy Dimensions*, 23, 1737-1751, 10.1016/j.gloenvcha.2013.08.006, 2013.
- Veith, T. L., Wolfe, M. L., and Heatwole, C. D.: Optimization procedure for cost effective BMP placement at a watershed scale, *Journal of the American Water Resources Association*, 39, 1331-1343, 10.1111/j.1752-1688.2003.tb04421.x, 2003.
- Ward, P. J., Jongman, B., Aerts, J. C., Bates, P. D., Botzen, W. J., Loaiza, A. D., ... & Winsemius, H. C. (2017). A global framework for future costs and benefits of river-flood protection in urban areas. *Nature Climate Change*. 7, 642–646

Impacts of future climate change on urban flood volumes in Hohhot City
in Northern China: benefits of climate mitigation and adaptations

Qianqian Zhou^{1, 2}, Guoyong Leng^{2,*}, Maoyi Huang³

¹School of Civil and Transportation Engineering, Guangdong University of Technology,
Waihuan Xi Road, Guangzhou 510006, China

²Joint Global Change Research Institute, Pacific Northwest National Laboratory, College Park
MD 20740, USA

³Earth System Analysis and Modeling Group, Pacific Northwest National Laboratory, Richland,
WA 99352, USA

*Corresponding author address: Guoyong Leng, Joint Global Change Research Institute, Pacific
Northwest National Laboratory, College Park MD, 20740.

E-mail: guoyong.leng@pnnl.gov

Abstract

As China has become increasingly urbanised, flooding has become a regular occurrence in its major cities. Assessing the effects of future climate change on urban flood volumes is crucial to informing better management of such disasters given the severity of the devastating impacts of flooding (e.g., the 2016 flooding across China). Although recent studies have investigated the impacts of future climate change on urban flooding, the effects of both climate change mitigation and adaptation have rarely been accounted for together in a consistent framework. In this study, we assess the benefits of mitigating climate change by reducing greenhouse gas emissions and locally adapting to climate change by modifying drainage systems to reduce urban flooding under various climate change scenarios through a case study conducted in Northern China. The urban drainage model—Storm Water Management Model—was used to simulate urban flood volumes using current and two adapted drainage systems (i.e., pipe enlargement and low-impact development), driven by bias-corrected meteorological forcing from five general circulation models in the Coupled Model Intercomparison Project Phase 5 archive. Results indicate that urban flood volume is projected to increase by 52% in 2020–2040 compared to the volume in 1971–2000 under the business-as-usual scenario (i.e., Representative Concentration Pathway (RCP) 8.5). The magnitudes of urban flood volumes are found to increase nonlinearly with changes in precipitation intensity. On average, the projected flood volume under RCP 2.6 is 13% less than that under RCP 8.5, demonstrating the benefits of global-scale climate change mitigation efforts in reducing local urban flood volumes. Comparison of reduced flood volumes between climate change mitigation and local adaptation (by improving the drainage system) scenarios suggests that local adaptation is more effective than climate change mitigation in reducing future flood volumes. This has broad implications for the research community relative

to drainage system design and modelling in a changing environment. This study highlights the importance of accounting for local adaptation when coping with future urban floods.

Keywords: Climate change, urban floods, mitigation, adaptation, drainage systems

1. Introduction

Floods are one of the most hazardous and frequent disasters in urban areas and can cause enormous impacts on the economy, environment, city infrastructure, and human society (Chang et al., 2013; Ashley et al., 2007; Zhou et al., 2012). Urban drainage systems have been constructed to provide carrying and conveyance capacities at a desired frequency to prevent urban flooding. ~~The~~However, the design of drainage systems is ~~generally~~often based on historical precipitation statistics for a certain period of time, without considering the potential changes in precipitation extremes for the designed return periods (Yazdanfar and Sharma, 2015; Peng et al., 2015; Zahmatkesh et al., 2015). ~~For example, in Danish design guidelines for urban~~It is likely that drainage, a 30% and 40% increase in the precipitation intensity is expected for the 10- and 100-year return periods, respectively (Arnbjerg-Nielsen, 2012). The systems are, however, likely to would be overwhelmed by additional runoff effects induced by climate change, which may lead to increased flood frequency and magnitude, disruption of transportation systems, and increased human health risk (Chang et al., 2013; Abdellatif et al., 2015). ~~For example, Arnbjerg-Nielsen (2012) reported that the design intensities in Denmark are projected to increase by 10-50% for return periods ranging from 2 to 100 years.~~ Therefore, it is important to investigate the performance of drainage systems in a changing environment and to assess the

potential urban flooding under various scenarios to achieve better adaptations (Mishra, 2015; Karamouz et al., 2013; Yazdanfar and Sharma, 2015; Notaro et al., 2015).

Impacts of climate change on extreme precipitation and urban flooding have been well documented in a number of case studies. For example, Ashley et al. (2005) showed that flooding risks (i.e., occurrence of pluvial floods) in four UK catchments may increase by almost 30 times in comparison by 2080s compared to current situations/conditions around the year 2000, and effective adaptation measures are required to cope with the increasing risks in the UK. Larsen et al. (2009) estimated that future extreme one-hour precipitation will increase by 20%~60% throughout Europe - by 2071–2100 relative to 1961–1990. Willems (2013) found that in Belgium the current design storm intensity for the 10-year return period is projected to increase by 50% by the end of this century. Several studies have also investigated the role of climate change mitigation and/or adaptation in reducing urban flood damages and risks under climate change scenarios (Alfieri et al., 2016; Arnbjerg-Nielsen et al., 2015; Moore et al., 2016; Poussin et al., 2012). To date, however, limited work has been done to investigate the The relationship between changes in precipitation intensity and flood volume has also been well explored to provide additional insights into drainage design strategies. More importantly, investigations (Olsson et al., 2009; Willems et al., 2012; Zahmatkesh et al., 2015). However, previous studies on the effects of climate change mitigation and adaptation are typically conducted separately, and it is unclear which strategy is more effective in reducing urban floods. This study aims to advance our understanding on urban floods within the context of change climate, through investigating the benefits of climate change mitigation (by reducing greenhouse gas emissions [GHG]) and local

adaptation (by improving drainage systems) in reducing future urban flood volumes ~~are typically~~
~~conducted separately, rather than within~~ a consistent framework.

As China has become increasingly urbanised, flooding has become a regular occurrence in its cities; 62% of Chinese cities surveyed experienced floods and direct economic losses of up to \$100 billion between 2011 and 2014 (China Statistical Yearbook 2015). The 2016 flooding affected more than 60 million people—more than 200 people were killed and \$22 billion in losses were suffered across China. Hence, assessing future changes in urban flooding is very important for managing urban floods by designing new and re-designing existing urban infrastructures to be resilient in response to the impacts of future climate change. While urban floods are speculated to increase in the future (Yang 2000; Ding et al., 2006), their magnitudes are hard to assess because of uncertainties associated with future climate change scenarios, as well as the under-representation of plausible climate change mitigation and adaptation strategies in the models.

In this study, we chose a drainage system in a typical city in Northern China to illustrate the role of climate change mitigation and local adaptation in coping with future urban flood volumes. Such an investigation of the performance of the present-day drainage system also has important implications for local governments responsible for managing urban flood disasters in the study region. Specifically, we first quantified the effects of future climate change on urban flood volumes as a result of extreme precipitation events for various return periods using the present-day drainage system. We then designed two plausible adaptation strategies for the study region and investigated how much urban flood volume can be reduced ~~by~~with the adapted systems ~~by~~

2020s. We also compared the benefits of global-scale climate change mitigation and local adaptation in reducing urban flood volumes to advance our understanding of the effective measures for coping with future urban floods.

2. Materials and Methods

a. Study region

The study region (Hohhot City) is located in the south-central portion of Inner Mongolia, China.

It lies between the Great Blue Mountains to the north and the Hetao Plateau to the south, which

has a north-to-south topographic gradient. The region is in a cold semi-arid climate zone,

characterised by cold and dry winters and hot and humid summers. The regional annual mean

precipitation is approximately 396 mm with large intra-seasonal variations. Most rain storms fall

between June and August, a period that accounts for more than 65% of the annual precipitation.

The drainage area in year 2010 was about 210.72 km² and it served a residential population of

1.793 million (Figure 1a). The land use types in the region can be classified into five categories:

agricultural land (8%), residential areas (38%), industrial land (13%), green spaces (7%), and

other facilities (34%, including municipal squares, commercial districts, institutions). ~~The~~

~~planned drainage area in 2020 is about 307.83 km², which is 50% larger than the current~~

~~drainage area. The land use categories and distribution are shown in Figure 1b.~~

~~The region is in a cold semi-arid climate zone, characterised by cold and dry winters and hot and~~

~~humid summers. The regional annual mean precipitation is approximately 396 mm and it~~

~~exhibits large intra-seasonal variations. Most rain storms fall between June and August, a period~~

~~that accounts for more than 65% of the annual precipitation.~~ According to local water authorities,
the major soil type of the area is a mixture of loam and clay.

The current drainage system can be divided into three large sub-basins (Figure 1c) and 326 sub-catchments with a total pipeline length of 249.36 km. The drainage network has a higher pipeline cover rate in the central part, but a rather low design standard for extreme rainfall events with a return period of less than 1 year. Historical records of stormwater drainage and flood damage indicate that the region has experienced an increase in flood frequency and magnitude within the context of climate change and urbanisation- (Zhou et al., 2016). During the major flood event on 11 July 2016, the city, especially the western portion of the watershed, was hit by an extreme rainfall event that featured more than 100 mm of rain in 3 hours. The flood event led to the cancellation of at least 8 flights and 17 trains, and delays of several transportation systems. In particular, in the central area, the flood event caused severe traffic jams on major streets and resulted in a number of flooded residential buildings. A new drainage system is therefore required to cope with increasing urban flood volumes and frequencies in the future. The planned drainage area for 2020s is about 307.83 km², which is 50% larger than the current drainage area (Zhou et al., 2016). The land use categories and distribution are shown in Figure 1b.

b. Climate change scenarios

Climate projections by five general circulation models (GCMs) from Phase 5 of the Coupled Model Intercomparison Project (CMIP5) archive were obtained from the Inter-Sectoral Impact Model Intercomparison Project (ISI-MIP) (Warszawski et al., 2014). The CMIP5 climate projections were bias-corrected against observed climate for the overlapping period 1950–2000

using a quantile mapping method (Piani et al., 2010; Hempel et al., 2013). The bias-corrected CMIP5 climate projections represent a complete climate change picture that includes both the mean property and variation of future climate. Several studies have demonstrated the value of the bias-corrected climate projections in quantifying climate change impacts on global and regional hydrology (e.g., Piontek et al., 2014; Elliott et al., 2014; Haddeland et al., 2014; Leng et al., 2015a,b). In this study, we used the bias-corrected climate from ~~all~~ five GCMs (HadGEM2-ES, GFDL-ESM2M, IPSLCM5A-LR, MIROC-ESM-CHEM, and NorESM1-M) under two Representative Concentration Pathways (RCPs) (i.e., RCP 2.6 and RCP 8.5). The projected urban flood volumes under the business-as-usual scenario RCP 8.5 are compared with those under the climate change mitigation scenario RCP 2.6 to explore the benefits of climate change mitigation in reducing regional urban flood volumes. The possible land-surface-atmosphere interactions that would indirectly affect rainfall and flooding are not considered in this study.

c. Urban drainage modelling

The Storm Water Management Model (SWMM 5.1) developed by the U.S. Environmental Protection Administration is a widely used urban stormwater model that can simulate rainfall-runoff routing and pipe dynamics under single or continuous events (Rossman and Huber, 2016). SWMM can be used to evaluate the variation in hydrological and hydraulic processes and the performance of drainage systems under specific mitigation and adaptation scenarios in the context of global warming. The hydrological component requires inputs of precipitation and subcatchment properties including drainage area, subcatchment width, and imperviousness. The pipe network requires inputs from manholes, pipelines, outfalls, and connections to sub-catchments (Zahmatkesh et al., 2015; Chang et al., 2013). Basic flow-routing models include

steady flow, kinematic, and dynamic wave methods. Infiltration can be described by the Horton, Green-Ampt, or Curve Number (SCS-CN) methods. The dynamics of pipe flow are calculated based on the continuity equation and Saint-Venant equations (Rossman and Huber, 2016). Overflow occurs once the surface runoff exceeds the pipe capacity and is expressed as the value of total flood volume (TFV) at each overloaded manhole; i.e., the excess water from manholes after completely filling the pipe system without taking into account the outlet discharges. Other types of model outputs include catchment peak flows, maximum flow rates of pipelines, and flooded hours of manholes. It should be noted that SWMM is not capable of simulating surface inundation dynamics and cannot provide accurate estimation of the inundated zones and depths. The TFV value is thus used to approximately reflect the flood condition and drainage system overloading status. Nevertheless, surface inundation models (e.g., Apel et al., 2009; Horritt and Bates, 2002; Vojinovic and Tutulic, 2009) are applicable if more accurate information about overland flow characteristics is available. In this study, the kinematic wave routing and the Horton infiltration model are used for model simulations. The infiltration capacity parameters for the category of "Dry loam soils with little or no vegetation" are used in the hydrological model to be consistent with the local soil type (Akan, 1993; Rossman and Huber, 2016) ([Table 4Supplementary Materials, ST1](#)).

Rainfall inputs are calculated based on the regional storm intensity formula (SIF) using historical climatic statistics (Zhang and Guan, 2012) ([see Equation 1](#)). [Application of the SIF is a standard practice for determining design rainfalls in urban drainage modelling in China, and is well documented in the National Guidance for Design of Outdoor Wastewater Engineering \(MOHURD, 2011\). In fact, the SIF represents an Intensity Duration Frequency \(IDF\)](#)

relationship, which is a common approach in literature for estimating design rainfall hydrographs using the Chicago Design Storms (CDS) approach (Berggren et al., 2014; Willems et al., 2012; Zhou et al., 2013).

$$q = \frac{A(1 + D \lg(P))}{(t + b)^c} \quad \text{Eq. (1)}$$

where q is the average rainfall intensity, and P and t are the design return period and duration of storm, respectively. The typical temporal resolution considered in SIF for urban drainage modelling is minutes. A , b , c , and D are regional parameters governing the IDF relationship among rainfall intensity, return period, and storm duration. For the study region, the values of A , b , c , and D were obtained from the local weather bureau and are equal to 635, 0, 0.61, and 0.841, respectively.

The procedure for applying SIF to obtain CDS is outlined in the National Technical Guidelines for Establishment of Intensity-Duration-Frequency Curve and Design Rainstorm Profile (MOHURD, 2014; Zhang et al., 2008; Zhang et al., 2015). Specifically, for a given return period, the SIF is fitted into the Horner's equation as:

$$i = \frac{\alpha}{(t + b)^c} \quad \text{Eq. (2)}$$

The synthetic hyetograph based on the Chicago method is computed using Equation 2 and an additional parameter r (where $0 < r < 1$), which determines the relative time step of the peak intensity, $t_p = r * t$. The time distribution of rainfall intensity is then described after the peak $t_{\alpha} = (1 - r) * t$ and before the peak $t_b = r * t$ using Equations 3 and 4, respectively, where i_b and i_{α} are the instantaneous rainfall intensity before and after the peak:

$$i_a = \frac{\alpha \left[\frac{(1-c)t_a}{(1-r)} + b \right]}{\left(\frac{t_a}{(1-r)} + b \right)^{1+\epsilon}} \quad \text{Eq. (3)}$$

$$i_b = \frac{\alpha \left[\frac{(1-c)t_b}{r} + b \right]}{\left(\frac{t_b}{r} + b \right)^{1+\epsilon}} \quad \text{Eq. (4)}$$

Supplementary Materials, Equation 1-4). In this study, we considered 10 return periods, i.e., the 1-, 2-, 3-, 10-, 20-, 50-, 100-, 200-, 500-, and 1000-year events. A 4-hour rainfall time series was generated for each return period at 10-minute intervals based on Equations 1-4. The duration of design rainfalls (i.e., 4-hour rainfall) is selected based on the time of concentration (ToC) of the watershed in the study region, according to the design principles as outlined in Butler and Davies (2010) and Chow et al. (2013). We assumed that the SIF was constant without considering the non-stationary features in a changing climate. That is, the Intensity-Duration-Frequency (IDF) relationships for estimating design rainfall hydrographs were assumed to remain stable in the future and only changes in the daily mean intensity were considered because of the limited data availability in future sub-hourly climate projections from which to derive the parameters.

As for future climate, the projected changes (i.e., change factors) in precipitation intensity at various return periods were calculated for each GCM-RCP combination (Table 21). Specifically, for each year, the annual maximum daily precipitation was determined for both historical and future periods. The generalised extreme value (GEV) distribution was then fitted separately to the two sets of daily values (Coles 2001; Katz et al. 2002). The goodness of fit was tested by calculating the Kolmogorov–Smirnov and Anderson–Darling statistics show that the hypothesis regarding the extreme value distribution is not rejected. That is, the fitted distribution could be well used to describe the extreme precipitation distribution in the study region. The value

corresponding to each return period was estimated based on the GEV distribution and the changes between future and historical periods were calculated as the change factors. The derived change factor for each return period was then multiplied by the historical design CDS rainfall time series to derive future climate scenarios. We acknowledge that the estimation of changes in extreme precipitation events involves inevitable uncertainties and therefore caution should be exercised when interpreting the relevant results.

d. Flood volume assessment

The total flood volume (TFV) values of given rainfall events were simulated by the SWMM. A log-linear relationship is assumed to characterize the changes in flood volume with the increase in precipitation intensity as indicated by return periods (Figure 2a) following Zhou et al. (2012) and Olsen et al. (2015). Generally, more intense TFV (i.e., system overloading) is expected with increase in rainfall will induce higher TFVs. The intensity. In Figure 2b, the TFVs were further linked to their specific occurrence frequencies to derive the expected flood volume for a flood event at a specific probability (Figure 2b). The probabilities. The total grey area under the curve denotes the TFVs integrated across various return periods and represents the average total expected TFVs per year for all floods at various return periods. The contribution of an individual flood event to total average TFVs is dependent not only on the flood volume, but also its corresponding probability of occurrence. Intensified precipitation is expected to increase the magnitude of system overflow, resulting in an upward trend in the TFV-return period relationship and increased total TFVs. Mitigation and adaptation are aimed at reducing or preventing the impacts of global warming on flood volumes.

e. Design of adaptation scenarios

In this study, two adaptation scenarios were designed to explore the role of adaptation in reducing urban flood volume within the context of climate change by 2020s. The first scenario ~~adapted was designed to update~~ the drainage system as planned by ~~the~~local water authorities to cope with the ~~designed-standard-of-a~~ 3-year design event. It involved two main improvements of the current drainage system—enhancing the pipeline diameter and expanding the pipe network. The design was implemented in the SWMM model as shown in Figure 1c. The number of pipelines of the present-day and adapted systems was 323 and 488, with a total pipe length of 251.6 km and 375.4 km, respectively. In the adapted scenarios, the mean pipeline diameter was about 1.73 m, which increased by 53% compared to that of the present-day system.

~~A variety of site-specific factors, such as the imperviousness of land area in the drainage basin, can also influence the performance of a drainage system in managing surface runoff.~~ The second adaptation scenario was designed to increase the permeable surfaces (e.g., green spaces) and reduce the regional imperviousness in the study region on the basis of pipe capacity enhancement. This scenario is referred to as the Low Impact Development (LID) scenario, and it was used to explore the effectiveness of urban green measures, such as the use of permeable pavements, infiltration trenches, and green roofs. Changes in land imperviousness in LID scenario have direct impacts on the performance of drainage system in managing surface runoff. Due to a lack of detailed information about the permeable soil and coverage rates in the study region, the effects of these specific measures cannot be modelled individually. Here, we used a simplified approach by altering the subcatchment imperviousness to reflect the combined effects of infiltration-related measures. We derived such information by ~~comparing~~calculating the

difference in land use type and imperviousness between the current and planned land use city maps using a geographical information system (GIS) and incorporated the changes in land use and imperviousness into the designed LID scenarios. Figure 1d shows the difference in weighted mean imperviousness (WMI) calculated $WMI = \sum_i (IF_i \times A_i) / \sum_i A_i$. Where IF_i and A_i is the impervious factor and area for land use type i , respectively. for each subcatchment in the current and planned maps, using the commonly applied impervious factors (Pazwash, 2011; Butler and Davies, 2004) for each land use type. The difference in WMI was used to indicate the area potential for adaptation based on the city plan. For example, a subcatchment with higher positive changes in the WMI indicates that the area is planned to have a land use type with lower imperviousness and therefore is assumed to be more suitable for LID planning, and vice versa.

3. Results

a. Impacts of future climate change on urban flood volumes

Figure 3 shows the projected climate change (CC) impacts on urban flooding using the present-day drainage system of the near future (i.e., 2020–2040) under the RCP 8.5 scenario. Without climate change mitigation or adaptation, the TFV was projected to increase significantly with the increase of extreme rainfall events for most of investigated return periods (Table 2). Note that the lower bounds for return periods of 1, 3, and 1000 years fall below the current TFV curve due to the decrease in precipitation intensities. Despite the large uncertainty associated with climate projections, in particular with the 1-, 10-, and 1000-year return periods, the poor service performance of the current system in coping with urban flooding was evident. Overall, the urban flood volume was projected to increase by 52% on average by the multi-model ensemble median

by 2020–2040; the largest increase (258%) was projected for the 1-year event and the smallest increase (12%) for the 100-year event.

b. Benefits of climate change mitigation in reducing urban flood volumes

Figure 4 shows the comparison of TFVs under the RCP 8.5 scenario (i.e., a business-as-usual scenario) and the RCP 2.6 scenario (i.e., a climate change mitigation scenario). Although large uncertainties exist arising from climate models, it is clear that the simulated TFVs are much smaller under the RCP 2.6 scenario than under the RCP 8.5 scenario, demonstrating the benefits of climate mitigation in reducing local urban flood volumes. Such benefits are especially evident for floods for smaller return periods. For example, an increase of 936 m³ in flood volume is projected with the increase in 1-year extreme rainfall under the business-as-usual climate change scenario (i.e., RCP 8.5), 52% of which would be reduced if climate change mitigation is in place (i.e., under RCP 2.6). ~~Overall, climate change mitigation can reduce future flood volumes by 13% compared to the scenario without mitigation, as indicated by the multi-model ensemble median.~~ Notably, the peak of the total TFV curve was ~~even~~ projected to shift from the 1-year event under the ~~RCP 8.5~~RCP8.5 scenario to the 3-year event under the ~~RCP 2.6~~RCP2.6 scenario (Figure 4b). ~~Such), indicating a shift~~substantial reduction in the ~~peak toward~~TFVs (especially at the 1-year return period) (Figure 4c). ~~The lower total TFVs under RCP2.6 scenario could be attributed to the smaller return periods combined with a flatter curve demonstrates magnitude of rainfall intensity than RCP8.5 scenario (Table 1), demonstrating~~ the important role of climate mitigation in ~~regulating local~~reducing urban flood volumes. ~~Overall, climate change mitigation can reduce future flood volumes by 13% compared to the scenario without mitigation, as indicated by the multi-model ensemble median.~~

c. Benefits of adaptation in reducing urban flood volumes

Figure 5 shows the overloaded pipelines (red colour) with and without adaptation. The simulated results under the present 3-year event (recommended service level) and 50-year event (one typical extreme event) were selected to illustrate the role of adaptation in coping with floods in the historical period. As shown in Figure 5a, the simulated locations of overloaded pipelines are in good agreement with historical flood points as recorded by local water authorities. Overall, the percentage of overloaded manholes (POM) and the ratio of flood volume (RFV) to input rainfall volume are up to 37% and 35% in the current drainage system (Figure 5a), respectively. When experiencing a 50-year extreme rainfall, the POM and RFV increase to 67% and 38%, respectively. This indicates that current pipe capacities are insufficient to cope with extreme rainfall events (Figure 5b). Spatially, the central portion of the city is the most affected region due to the low service level in the area. With proposed adaptations, urban floods can be reduced to zero under a 3-year flood event. Such benefits of local adaptations are also evident when experiencing more intense precipitation events (e.g., 50-year events), for which the POM and RFV reduced from 67% and 50% to 49% and 17%, respectively.

Figure 6 shows the future changes in urban flood volume (CTFVs) ($CTFV = (TFV_c - TFV_{nc}) / TFV_{nc}$, where c and nc represent the results with and without climate change, respectively) with changes in extreme rainfall for various return periods. The performance of the current drainage system (no adaptation) was found to be less sensitive to future climate change, as indicated by the flatter slope in Figure 6. For example, a similar magnitude of changes in flood volume was projected given changes in extreme rainfall for the return periods of 3, 50, and 500 years; the CTFV is 0.62,

0.32 and 0.35 for these periods, respectively. This is because the capacity of the current system is too small to handle extreme rainfall events with return periods larger than 1 year—a condition under which the current drainage system would be flooded completely, not to mention the situations with increased rainfall intensity in the future. Mathematically, the low sensitivity of the current drainage system to changes in extreme rainfall intensity could be attributed to the large value of the denominator in the calculation of $CTFV$.

With adaptations in place, the flood volume becomes much smaller than that in the current system due to capacity upgrading to hold more water. For example, when experiencing a 10-year extreme rainfall event, the urban flood volumes for the present period (i.e., TFV_{nc}) are 1041,230, 274,650 and 180,610 m³ in the current and two adapted systems, respectively, while in the future period, the magnitude of flood volume (i.e., TFV_c) is relatively similar among the three drainage systems. Therefore, future CTFVs relative to the historical period are much larger in the adapted systems than in the current system. The larger CTFVs in the adapted systems do not mean a worsened drainage system performance. Rather, they imply that the capacity (i.e., service level) of adapted drainage systems tends to become lower with climate change, while the current drainage system has already reached its peak capacity in handling extreme rainfall events in the historical period and thus shows a low sensitivity to future increases in rainfall intensity under climate change scenarios. Notably, the considerable increases in the CTFVs for return periods of less than 10 years in the adapted systems imply that the designed adaptations can effectively attenuate extreme rainfall events for small return periods. For more extreme rainfall events of return periods ≥ 50 years, more consistent results were found for both adaptation scenarios. This indicates that although the performances of adapted drainage systems are significantly improved

compared to that of the current system, the flood volume remains large when experiencing extreme rainfall events with return periods larger than 50 years, because flooding in such cases will push the adapted drainage systems to their upper limits.

d. Climate mitigation versus drainage adaptation

Figure 7 shows the reduced TFVs by climate change mitigation and drainage system adaptation as functions of return period. It is evident that both mitigation and adaptation measures are effective in reducing future urban flood volumes. However, such benefits are projected to weaken gradually with the increase in rainfall intensity (i.e., larger return periods). Overall, climate mitigation can lead to a reduction of flood volume by 10-40% compared to the scenario without mitigation. Notably, there are minor negative values of TFV reductions for the return period of 100 and 200 years under climate mitigation scenario. The negative value is attributed to the slightly higher increase in precipitation intensity under climate mitigation scenario (i.e. RCP26) than the scenario without mitigation (i.e. RCP85) simulated by two of five climate models (i.e., GFDL-ESM2m and NorESM1-M, see Table 1), which translated to slightly larger flood volume under climate mitigation scenario. This climate internal variability is partly cancelled by other three climate models, thus leading to very minor negative value by the multi-model ensemble mean. This calls for the use of more climate models (GCMs) to derive more robust projections in the future studies.

Importantly, our results show that the two adaptation systems proposed in this study are found to be more effective in reducing urban floods than climate change mitigation. In most cases, the benefits of local adaptation are more than double those of mitigation. In extreme cases, the

reduction in TFV achieved by adaptation is five times more than that achieved by climate change mitigation (i.e., for the return periods of 2–3 years). Such effectiveness of urban flood reduction through drainage system adaptations has profound implications for local governments charged with managing urban flooding in the future. Notably, the second scenario (LID+pipe) exhibited a higher level of flood volume reduction than the pipe scenario in coping with extreme rainfall events for all investigated return periods. This implies that implementation of LID measures to augment drainage system capacity is more effective through reducing upstream loadings compared to updating the pipe system alone.

It is noted that local soil characteristics could affect the performance of the designed adaptation systems, in particular the LID measures. However, information about soil properties was not available at the subcatchment level in the study region. Here, a set of sensitivity experiments were conducted by adopting different parameters (e.g., infiltration values) associated with possible soil conditions (i.e., dry sand, loam, and clay soils with little or no vegetation in [Table S1](#) for the area. The [boundary bars whiskers](#) in Figure 7 show the uncertainty range arising from the representation of different soil conditions in the drainage model. The benefits of the designed adaptation measures in reducing urban flood volumes were found to be robust regardless of soil conditions, and such benefits exceeded those of climate change mitigation, confirming our major conclusions found in this study.

4. Uncertainties and Limitations

A number of uncertainties and limitations arise from the model structure, parameter inputs, emission scenarios, GCMs, climate downscaling/bias-correction approaches, etc. Specifically,

climate projections by GCMs are subject to large uncertainties, in particular regarding precipitation (Covey et al., 2003) at spatial scales, which are relevant for urban flood modelling. An alternative approach is to simulate future climate using a regional climate model (RCM) nested within a GCM. Such climate projections by RCMs have added value in terms of higher spatial resolution, which can provide more detailed regional climate information. However, various levels of bias would still remain in RCM simulations (Teutschbein and Seibert 2012) and bias corrections of RCM projections would be required; e.g., the European project ENSEMBLES (Hewitt and Griggs 2004; Christensen et al. 2008). To run a RCM was not within the scope of this study; instead, we tended to use publicly available climate projections. Here, we obtained the climate projections from the ISI-MIP (Warszawski et al. 2014), which provides spatially downscaled climate data for impact models. The climate projections were also bias-corrected against observations (Hempel et al. 2013) and have been widely used in climate change impact studies on hydrological extremes such as floods and droughts (e.g., Dankers et al. 2014; Prudhomme et al. 2014; Leng et al. 2015a). It should be noted that we used the delta change factor to derive future climate scenarios as inputs into our drainage model instead of using GCM climate directly. This is because the relative climate change signal simulated by GCMs is argued to be more reliable than the simulated absolute values (Ho et al. 2012). Moreover, we used an ensemble of GCM simulations rather than one single climate model in order to characterise the uncertainty range arising from climate projections. However, disadvantages of this method are that transient climate changes cannot be represented and that changes in intra-seasonal or daily climate variability are not taken into account (Leng and Tang, 2014). Such sources of uncertainty can be explored when improved climate models at finer scales become available (Jaramillo and Nazemi 2017).

In addition, the SIF parameters were assumed to remain stable in the future and only changes in the daily mean intensity were considered, because future sub-hourly climate projections were not readily available. The full climate variability range would also be under-sampled, although we used five climate models to show the possible range. Given the above limitations, we acknowledge that the modelling results represent the first-order potential climate change impacts on urban floods. Future efforts should be devoted to the representation of dynamic rainfall changes at hourly time steps with consideration of non-stationary climate change.

Moreover, several assumptions had to be made due to limitations of the current modelling structure and approach. For example, the conveyance capacities of the drainage system and flood volume would largely depend on the state of drainage systems. Hence, a drainage system obstructed by vegetation, waste, or artefacts (cables, pipes, temporary constructions) can make the outcomes of the SWMM calculation significantly different from observations. However, quantifying the impacts of drainage system states on urban flood volumes is not trivial because of the difficulties involved in collecting field data and selecting and using appropriate methods for reasonable assessment of pipe conditions (Ana and Bauwens, 2007; Fenner, 2000), and was not within the scope of this study. With deterioration, such as ageing network, pipe deterioration, blockage, and construction failures, drainage systems were shown to become more vulnerable to extreme rainfalls as demonstrated in previous studies (Dawson et al., 2008; CIRIA, 1997; Davies et al., 2001). It is very likely that our simulated urban flood volumes would be underestimated without considering the changes in drainage conditions (Pollert et al., 2005).

Further, constrained by the one-dimensional modelling approach using SWMM, the performances of LID measures were mainly evaluated according to their effects in reducing water volume from overloaded manholes (Oraei Zare et al., 2012; Lee et al., 2013). That is, the LID adaptation measure was mainly designed to reduce the amount of water rather than slowing down the water speed, which has been demonstrated to be effective in reducing urban floods (Messner et al., 2006; Ashley et al., 2007; Floodsite, 2009). However, it should be noted that most LID measures can reduce runoff volume and flow speed at the same time, although some of the LID measures are primarily designed to slow down the flow speed, i.e., vegetated swales. To examine whether flood retention of a given event is induced by runoff volume or the internal speed control function in the model is difficult and requires detailed data for model validations. Specifically, the required information about surface roughness, soil conductivity, and seepage rate were unavailable at the subcatchment scale in the study region. Therefore, a simplified modelling approach was used to take advantage of existing data, especially for the design of LID measures. With the aid of more detailed field data and planning documents, the design of LID measures could be significantly improved by implementing more advanced approaches (Elliott and Trowsdale, 2007; Zoppou, 2001).

Evaluation of other potential adaptation strategies, such as flood retention by rain gardens and green roofs, can be explored in the future to gain additional insights into the performance of LID systems. In particular, the cost-effectiveness of the proposed adaptation measures should be accounted for. Indeed, a major limitation of this study is lack of assessment of costs and benefits of adaptation measures from the economic perspective. In fact, besides the effectiveness of proposed adaptation measures in reducing flood volume, assessment of the associated economic

costs is essential for flood risk management (Rojas et al., 2013; Veith et al., 2003; Hinkel et al., 2014; Aerts et al., 2014; Ward et al., 2017). For example, Ward et al. (2017) showed that investments in urban flood protections with dykes are not economically attractive everywhere. Higher investment and maintenance costs may prohibit the implementation of adaptation strategies as proposed in this study. Future efforts should therefore be devoted to building a framework for assessing the costs and benefits of urban flood reduction measures and examine whether the reduced losses are higher than the costs of investments and maintenance of these measures.

Nevertheless, given these limitations, this study stands out from previous climate impact assessment studies of urban flood volumes by having proposed two feasible adaptation strategies and compared their benefits to those from global-scale climate change mitigations through GHG reductions within a consistent framework. Depending on the progress on data collection and the demands of local authorities, more advanced methods for pipe assessment (e.g., considering the changing pipe conditions), LID measures (detailed modelling of LID control), and two-dimensional surface flooding for assessment of flood damage and risk are planned in a future study to provide a more comprehensive analysis of the adaptation measures.

5. Summary and Conclusions

The potential impacts of future climate change on current urban drainage systems have received increasing attention during recent decades because of the devastating impacts of urban flooding on the economy and society (Chang et al., 2013; Zhou et al., 2012; Abdellatif et al., 2015). However, few studies have explored the role of both climate change mitigation and drainage

adaptations in coping with urban flooding in a changing climate. This study investigated the performance of a drainage system in a typical city in Northern China in response to various future scenarios. In particular, we assessed the potential changes in urban flood volume and explored the role of both mitigation and adaptation in reducing urban flood volumes in a consistent manner.

Our results show significant increases in urban flood volumes due to increases in precipitation extremes, especially for return periods of less than 10 years. Overall, urban flood volume in the study region is projected to increase by 52% by the multi-model ensemble median in the period of 2020–2040. Such increases in flood volume can be reduced considerably by climate change mitigation through reduction of GHG emissions. For example, the future TFVs under 1-year extreme rainfall events can be reduced by 50% when climate change mitigation is in place. Besides global-scale climate change mitigation, regional/local adaptation can be implemented to cope with the adverse impacts of future climate change on urban flood volumes. Here, the adaptation measures as designed in this study were demonstrated to be much more effective in reducing future flood volumes than climate change mitigation measures. In general, the reduced flood volumes achieved by adaptation were more than double those achieved by climate change mitigation.

Through a comprehensive investigation of future urban floods, this study provides much-needed insights into urban flood management for similar urban areas in China, most of which are equipped with highly insufficient drainage capacities. By comparing the reduction of flood volume by climate change mitigation (via reduction of GHG emissions) and local adaptation (via

improvement of drainage systems), this study highlights the effectiveness of system adaptations in reducing future flood volumes. This has important implications for the research community and decision-makers involved in urban flood management. We emphasise the importance of accounting for both global-scale climate change mitigation and local-scale adaptation in assessing future climate impacts on urban flood volumes within a consistent framework.

Acknowledgements

This research was supported by [the Public Welfare Research and Ability Construction Project of Guangdong Province, China \(Grant No. 2017A020219003\)](#), the [Water Conservancy Science and Technology Innovation Project of Guangdong province, China \(Grant No. 201710\)](#), the Natural Science Foundation of Guangdong Province, China (No. 2014A030310121) and the Scientific Research Foundation for the Returned Overseas Chinese Scholars, State Education Ministry. G. Leng and M. Huang were supported by the Integrated Assessment Research program through the Integrated Multi-sector, Multi-scale Modeling (IM³) Scientific Focus Area (SFA) sponsored by the Biological and Environmental Research Division of Office of Science, U.S. Department of Energy. The Pacific Northwest National Laboratory (PNNL) is operated for the U.S. DOE by Battelle Memorial Institute under contract DE-AC05-76RL01830

References

- Abdellatif, M., Atherton, W., Alkhaddar, R., and Osman, Y.: Flood risk assessment for urban water system in a changing climate using artificial neural network, *Natural Hazards*, 79, 1059-1077, 2015.
- [Aerts, J. C., Botzen, W. W., Emanuel, K., Lin, N., de Moel, H., & Michel-Kerjan, E. O. \(2014\). Evaluating flood resilience strategies for coastal megacities. *Science*, 344\(6183\), 473-475.](#)
- Akan, O. A.: Urban stormwater hydrology: a guide to engineering calculations, CRC Press, 1993.

- 1000 Alfieri, L., Feyen, L., and Di Baldassarre, G.: Increasing flood risk under climate change: a pan-
1001 European assessment of the benefits of four adaptation strategies, *Climatic Change*, 136, 507-
1002 521, 10.1007/s10584-016-1641-1, 2016.
- 1003 Ana, E., and Bauwens, W.: Sewer network asset management decision-support tools: a review,
1004 International Symposium on New Directions in Urban Water Management, 12-14 September
1005 2007, UNESCO Paris, 2007.
- 1006 Apel, H., Aronica, G. T., Kreibich, H., and Thieken, A. H.: Flood risk analyses-how detailed do
1007 we need to be?, *Natural Hazards*, 49, 79-98, 2009.
- 1008 Arnbjerg-Nielsen, K.: Quantification of climate change effects on extreme precipitation used for
1009 high resolution hydrologic design, *Urban Water Journal*, 9, 57-65, 2012.
- 1010 Arnbjerg-Nielsen, K., Leonardsen, L., and Madsen, H.: Evaluating adaptation options for urban
1011 flooding based on new high-end emission scenario regional climate model simulations, *Clim.*
1012 *Res.*, 64, 73-84, 10.3354/cr01299, 2015.
- 1013 Ashley, R., Garvin, S., Pasche, E., Vassilopoulos, A., and Zevenbergen, C.: Advances in Urban
1014 Flood Management, in, edited by: Ashley, R., Garvin, S., Pasche, E., Vassilopoulos, A., and
1015 Zevenbergen, C., Taylor & Francis/Balkema, London, UK, 2007.
- 1016 Ashley, R. M., Balmforth, D. J., Saul, A. J., and Blanskby, J. D.: Flooding in the future -
1017 predicting climate change, risks and responses in urban areas, *Water Science and Technology*, 52,
1018 265-273, 2005.
- 1019 Berggren, K., Packman, J., Ashley, R., and Viklander, M.: Climate changed rainfalls for urban
1020 drainage capacity assessment, *Urban Water Journal*, 11, 543-556,
1021 10.1080/1573062X.2013.851709, 2014.
- 1022 Butler, D., and Davies, J.: Urban drainage, [Third Edition](#), CRC Press, London. ISBN:
1023 [0203149696, 20040415455251, 2010](#).
- 1024 China Statistical Yearbook: National Bureau of Statistics of China, China Statistics Press,
1025 Beijing, 2015.
- 1026 Chang, H. K., Tan, Y. C., Lai, J. S., Pan, T. Y., Liu, T. M., and Tung, C. P.: Improvement of a
1027 drainage system for flood management with assessment of the potential effects of climate change,
1028 *Hydrological Sciences Journal*, 58, 2013.
- 1029 [Chow, V. T., Maidment, D. R., and Mays, L. W.: Applied Hydrology, 2nd Edition, in, McGraw-](#)
1030 [Hill, New York. ISBN: 007174391X, 2013.](#)
- 1031 CIRIA: Risk Management for Real Time Control in Urban Drainage Systems: Scoping Study,
1032 Project Report 45. CIRIA, London., 1997.
- 1033 Coles S, An Introduction to Statistical Modeling of Extreme Values, Springer Series in Statistics
1034 (Springer, London), 2001.
- 1035 Covey, C., et al.: An overview of results from the Coupled Model Intercomparison Project,
1036 *Global and Planetary Change*, 37(1), 103-133, 2003.
- 1037 Dankers, R., et al.: First look at changes in flood hazard in the Inter-Sectoral Impact Model
1038 Intercomparison Project ensemble, *Proceedings of the National Academy of Sciences*, 111(9),
1039 3257-3261, 2014.

- 1040 Davies, J. P., Clarke, B. A., Whiter, J. T., and Cunningham, R. J.: Factors influencing the
1041 structural deterioration and collapse of rigid sewer pipes, *Urban Water*, 3, 73-89, 2001.
- 1042 Dawson, R. J., Speight, L., Hall, J. W., Djordjevic, S., Savic, D., and Leandro, J.: Attribution of
1043 flood risk in urban areas, *Journal of Hydroinformatics*, 10, 275-288, 2008.
- 1044 Ding, Y., Ren, G., Shi, G., Gong, P., Zheng, X., Zhai, P., Zhang, D., Zhao, Z., Wang, S., Wang,
1045 H., Luo, Y., Chen, D., Gao, X., and Dai, X.: National assessment report of climate change (I):
1046 climate change in China and its future trend. *Adv Clim Change Res* 2:3–8 (in Chinese), 2006.
- 1047 Elliott, A. H., and Trowsdale, S. A.: A review of models for low impact urban stormwater
1048 drainage, *Environmental Modelling & Software*, 22, 394-405, 2007.
- 1049 Elliott, J., et al.: Constraints and potentials of future irrigation water availability on agricultural
1050 production under climate change, *Proceedings of the National Academy of Sciences*, 111, 3239–
1051 3244, 2014.
- 1052 Fenner, R. A.: Approaches to sewer maintenance: a review, *Urban Water*, 2, 343-356, 2000.
- 1053 Floodsite: Flood risk assessment and flood risk management. An introduction and guidance
1054 based on experiences and findings of FLOODsite (an EU-funded Integrated Project),
1055 Deltares|Delft Hydraulics. ISBN 978 90 8 |4067|0, 2009.
- 1056 Haddeland, I., et al.: Global water resources affected by human interventions and climate change,
1057 *Proceedings of the National Academy of Sciences*, 111, 3251–3256, 2014.
- 1058 Hempel, S., Frieler, K., Warszawski, L., Schewe, J., and Piontek, F.: A trend-preserving bias
1059 correction—the ISI-MIP approach, *Earth System Dynamics*, 4(2), 219-236, 2013.
- 1060 [Hinkel, J., Lincke, D., Vafeidis, A. T., Perrette, M., Nicholls, R. J., Tol, R. S., ... & Levermann,](#)
1061 [A. \(2014\). Coastal flood damage and adaptation costs under 21st century sea-level rise.](#)
1062 [Proceedings of the National Academy of Sciences, 111\(9\), 3292-3297.](#)
- 1063 Horritt, M. S., and Bates, P. D.: Evaluation of 1D and 2D numerical models for predicting river
1064 flood inundation, *Journal of Hydrology*, 268, 87-99, 2002.
- 1065 Ho, C. K., Stephenson, D. B., Collins, M., Ferro, C. A., and Brown, S. J.: Calibration strategies:
1066 a source of additional uncertainty in climate change projections, *Bulletin of the American*
1067 *Meteorological Society*, 93(1), 21-26, 2012.
- 1068 Jaramillo, P., and Nazemi, A.: Assessing Urban Water Security under Changing Climate:
1069 Challenges and Ways Forward. *Sustainable Cities and Society*, 2017.
- 1070 Karamouz, M., Nazif, S., and Zahmatkesh, Z.: Self-Organizing Gaussian-Based Downscaling of
1071 Climate Data for Simulation of Urban Drainage Systems, *Journal of Irrigation Drainage*
1072 *Engineering*, 139, 98-112, 2013.
- 1073 Katz, R. W., Parlange, M. B., Naveau, P.: Statistics of extremes in hydrology, *Advances in*
1074 *Water Resources*, 25, 1287–1304, 2002.
- 1075 Larsen, A. N., Gregersen, I. B., Christensen, O. B., Linde, J. J., and Mikkelsen, P. S.: Potential
1076 future increase in extreme one-hour precipitation events over Europe due to climate change,
1077 *Water Science and Technology*, 60, 2205-2216, 2009.
- 1078 Lee, J. M., Hyun, K. H., and Choi, J. S.: Analysis of the impact of low impact development on
1079 runoff from a new district in Korea, *Water Science and Technology*, 68, 1315-1321,, 2013.

- 1080 Leng, G., and Tang, Q.: Modeling the impacts of future climate change on irrigation over China:
1081 Sensitivity to adjusted projections, *Journal of Hydrometeorology*, 15(5), 2085-2103, 2014.
- 1082 Leng, G., Tang, Q., and Rayburg, S.: Climate change impacts on meteorological, agricultural and
1083 hydrological droughts in China, *Global and Planetary Change*, 126, 23-34, 2015a.
- 1084 Leng, G., Huang, M., Tang, Q., and Leung, L. R.: A modeling study of irrigation effects on
1085 global surface water and groundwater resources under a changing climate, *Journal of Advances*
1086 *in Modeling Earth Systems*, 7(3), 1285-1304, 2015b.
- 1087 Messner, F., Penning-Rowsell, E., Green, C., Meyer, V., Tunstall, S., and Van der Veen, A.:
1088 Guidelines for Socio-economic Flood Damage Evaluation, Report Nr. T9-06-01, in, FLOOD site,
1089 HR Wallingford, UK, 2006.
- 1090 Mishra, A.: A study on the occurrence of flood events over Jammu and Kashmir during
1091 September 2014 using satellite remote sensing, *Natural Hazards*, 78, 1463-1467, 2015.
- 1092 MOHURD: AQSIQ. Code for Design of Outdoor Wastewater Engineering (GB 50014-2006),
1093 Ministry of Housing and Urban-Rural Development, General Administration of Quality
1094 Supervision, Inspection and Quarantine of the People's Republic of China: Beijing, China (In
1095 Chinese), 2011.
- 1096 MOHURD: Technical Guidelines for Establishment of Intensity-Duration-Frequency Curve and
1097 Design Rainstorm Profile (In Chinese), Ministry of Housing and Urban-Rural Development of
1098 the People's Republic of China and China Meteorological Administration, 2014.
- 1099 Moore, T. L., Gulliver, J. S., Stack, L., and Simpson, M. H.: Stormwater management and
1100 climate change: vulnerability and capacity for adaptation in urban and suburban contexts,
1101 *Climatic Change*, 138, 491-504, 10.1007/s10584-016-1766-2, 2016.
- 1102 Notaro, V., Liuzzo, L., Freni, G., and La Loggia, G.: Uncertainty Analysis in the Evaluation of
1103 Extreme Rainfall Trends and Its Implications on Urban Drainage System Design, *Water*, 7,
1104 6931-6945, 2015.
- 1105 Olsen, A., Zhou, Q., Linde, J., and Arnbjerg-Nielsen, K.: Comparing Methods of Calculating
1106 Expected Annual Damage in Urban Pluvial Flood Risk Assessments, *Water*, 7, 255-270, 2015.
- 1107 [Olsson, J., Berggren, K., Olofsson, M., and Viklander, M.: Applying climate model precipitation](#)
1108 [scenarios for urban hydrological assessment: A case study in Kalmar City, Sweden, *Atmospheric*](#)
1109 [Research](#), 92, 364-375, <http://dx.doi.org/10.1016/j.atmosres.2009.01.015>, 2009.
- 1110 Oraei Zare, S., Saghafian, B., Shamsai, A., and Nazif, S.: Multi-objective optimization using
1111 evolutionary algorithms for qualitative and quantitative control of urban runoff, *Hydrology and*
1112 *Earth System Sciences*, 9, 777-817, 2012.
- 1113 Pazwash, H.: *Urban Storm Water Management*, CRC Press, Taylor and Francis, Boca Raton, FL,
1114 2011.
- 1115 Peng, H. Q., Liu, Y., Wang, H. W., and Ma, L. M.: Assessment of the service performance of
1116 drainage system and transformation of pipeline network based on urban combined sewer system
1117 model, *Environmental Science And Pollution Research*, 22, 15712-15721, 2015.

- 1118 Piani, C., Weedon, G. P., Best, M., Gomes, S. M., Viterbo, P., Hagemann, S., and Haerter, J. O.:
 1119 Statistical bias correction of global simulated daily precipitation and temperature for the
 1120 application of hydrological models, *Journal of Hydrology*, 395, 199–215, 2010.
- 1121 Piontek, F., et al.: Multisectoral climate impact hotspots in a warming world, *Proceedings of the*
 1122 *National Academy of Sciences*, 111(9), 3233–3238, 2014.
- 1123 Pollert, J., Ugarelli, R., Saegrov, S., Schilling, W., and Di Federico, V.: The hydraulic capacity
 1124 of deteriorating sewer systems, *Water Science and Technology*, 52, 207–214, 2005.
- 1125 Poussin, J. K., Bubeck, P., Aerts, J., and Ward, P. J.: Potential of semi-structural and non-
 1126 structural adaptation strategies to reduce future flood risk: case study for the Meuse, *Natural*
 1127 *Hazards and Earth System Sciences*, 12, 3455–3471, 2012.
- 1128 Prudhomme, C., et al.: Hydrological droughts in the 21st century, hotspots and uncertainties
 1129 from a global multimodel ensemble experiment, *Proceedings of the National Academy of*
 1130 *Sciences*, 111(9), 3262–3267, 2014.
- 1131 [Rojas, R., Feyen, L., and Watkiss, P.: Climate change and river floods in the European Union:
 1132 Socio-economic consequences and the costs and benefits of adaptation, *Global Environmental*
 1133 *Change-Human and Policy Dimensions*, 23, 1737–1751, 10.1016/j.gloenvcha.2013.08.006, 2013.](#)
- 1134 Rossman, L. A., and Huber, W. C.: Storm Water Management Model Reference Manual
 1135 EPA/600/R-15/162A, 2016.
- 1136 [Veith, T. L., Wolfe, M. L., and Heatwole, C. D.: Optimization procedure for cost effective BMP
 1137 placement at a watershed scale, *Journal of the American Water Resources Association*, 39, 1331-
 1138 1343, 10.1111/j.1752-1688.2003.tb04421.x, 2003.](#)
- 1139 Vojinovic, Z., and Tutulic, D.: On the use of 1D and coupled 1D-2D modelling approaches for
 1140 assessment of flood damage in urban areas, *Urban Water Journal*, 6, 183–199, 2009.
- 1141 [Ward, P. J., Jongman, B., Aerts, J. C., Bates, P. D., Botzen, W. J., Loaiza, A. D., ... &
 1142 Winsemius, H. C. \(2017\). A global framework for future costs and benefits of river-flood
 1143 protection in urban areas. *Nature Climate Change*, 7, 642–646.](#)
- 1144 Warszawski, L. et al.: The Inter-Sectoral Impact Model Intercomparison Project [ISI-MIP]:
 1145 Project framework, *Proceedings of the National Academy of Sciences*, 111(9), 3228–3232, 2014.
- 1146 Willems, P., Arnbjerg-Nielsen, K., Olsson, J., and Nguyen, V. T. V.: Climate change impact
 1147 assessment on urban rainfall extremes and urban drainage: Methods and shortcomings,
 1148 *Atmospheric Research*, 103, 106–118, 2012.
- 1149 Willems, P.: Revision of urban drainage design rules after assessment of climate change impacts
 1150 on precipitation extremes at Uccle, Belgium, *Journal of Hydrology*, 496, 166–177, 2013.
- 1151 Yang, G.: Historical change and future trends of storm surge disaster in China's coastal area.
 1152 *Journal of Natural Disasters* 9, 23–30 (in Chinese), 2000.
- 1153 Wu, H., Huang, G., Meng, Q., Zhang, M., and Li, L.: Deep Tunnel for Regulating Combined
 1154 Sewer Overflow Pollution and Flood Disaster: A Case Study in Guangzhou City, China, *Water*,
 1155 8, 329, 2016.
- 1156 Yazdanfar, Z., and Sharma, A.: Urban drainage system planning and design-challenges with
 1157 climate change and urbanization: a review, *Water Science & Technology*, 72, 165–179, 2015.

- 1158 Yin, J., Yu, D. P., Yin, Z., Liu, M., and He, Q.: Evaluating the impact and risk of pluvial flash
1159 flood on intra-urban road network: A case study in the city center of Shanghai, China, *Journal of*
1160 *Hydrology*, 537, 138-145, 2016.
- 1161 Zahmatkesh, Z., Karamouz, M., Goharian, E., and Burian, S. J.: Analysis of the Effects of
1162 Climate Change on Urban Storm Water Runoff Using Statistically Downscaled Precipitation
1163 Data and a Change Factor Approach, *Journal of Hydrologic Engineering*, 20, 11, 2015.
- 1164 Zhang, B., and Guan, Y.: *Watersupply & Drainage Design Handbook*, China Construction
1165 Industry Press, ISBN: 9787112136803, Beijing, China, 2012.
- 1166 Zhang, Y.-q., Lv, M., and Wang, Q.-g.: Formula method design of drainage pipe network and
1167 analysis of model simulation, *Water Resour. Power*, 33, 105-107, 2015.
- 1168 Zhang, D., Zhao, D. q., Chen, J. n., and Wang, H. z.: Application of Chicago approach in urban
1169 drainage network modeling, *Water & Wastewater Engineering*, 34, 354-357, 2008.
- 1170 Zhou, Q., Mikkelsen, P. S., Halsnaes, K., and Arnbjerg-Nielsen, K.: Framework for economic
1171 pluvial flood risk assessment considering climate change effects and adaptation benefits, *Journal*
1172 *of Hydrology*, 414, 539-549, 2012.
- 1173 Zhou, Q., Panduro, T., Thorsen, B., and Arnbjerg-Nielsen, K.: Adaption to Extreme Rainfall
1174 with Open Urban Drainage System: An Integrated Hydrological Cost-Benefit Analysis,
1175 *Environmental Management*, 51, 586-601, 2013.
- 1176 [Zhou, Q., Ren, Y., Xu, M., Han, N., and Wang, H.: Adaptation to urbanization impacts on](#)
1177 [drainage in the city of Hohhot, China, *Water Science and Technology*, 73, 167-175,](#)
1178 [10.2166/wst.2015.478, 2016.](#)
- 1179 Zoppou, C.: Review of urban storm water models, *Environmental Modelling & Software*, 16,
1180 195-231, 2001.

Table 1 Infiltration parameters for three categories of soil in the SWMM simulation

Soil category	Infiltration parameters			
	MaxRate	MinRate	Decay rate	DryTime
	[in/hr]	[in/hr]	[1/hr]	[days]
Dry loam with little or no vegetation	3	0.5	4	7
Dry sand with little or no vegetation	5	0.7	5	5
Dry clay with little or no vegetation	1	0.3	3	9

Table 2 Projected changes in precipitation intensity under return periods ranging from 1 year to 1000 years by five Global Climate Models under two Representative Concentration Pathways (RCPs)

		1	2	3	10	20	50	100	200	500	1000
GFDL-ESM2M	RCP8.5	2.12	1.23	1.34	1.25	1.27	1.21	1.08	1.12	1.24	1.23
	RCP2.6	1.74	1.08	1.03	1.11	1.07	1.15	1.14	1.15	1.19	1.16
HadGE M2-ES	RCP8.5	0.62	1.08	1.09	1.06	1.01	1.03	1.17	1.26	1.23	1.14
	RCP2.6	0.36	1.2	1.19	1.04	1.02	1.11	1.31	1.26	1.37	1.24
IPSL-CM5A-LR	RCP8.5	1.44	1.17	1.28	1.17	1.08	1.09	1.02	1.1	1.12	1.13
	RCP2.6	0.74	1.04	1.18	1.01	1.06	1.03	1.01	0.99	0.95	1
MIROC-ESM-CHEM	RCP8.5	2.13	1.38	1.3	1.51	1.32	1.23	1.17	1.27	1.16	1.31
	RCP2.6	0.71	1.12	1.14	1.18	1.1	1.07	1.01	1.09	1.01	1.09
NorES M1-M	RCP8.5	2.11	0.96	0.8	1.63	1.35	1.15	1.08	1.01	1.04	0.97
	RCP2.6	0.11	1.09	1.05	1.28	1.17	1.08	1.1	1.18	1.09	1.2

List of Figures

Figure 1 Land use of the study region for the year 2010 (a) and 2020 (b). Pipe network description of current and planned drainage systems (c). Difference in Weighted Mean Imperviousness (WMI) between year 2010 and 2020 (d).

Figure 2 Illustration of ~~flood volume and average total expected~~ total flood volume (TFVs) as a function of return ~~period under a stationary drainage system~~. The grey area denotes the periods (a) ~~and estimation of~~ average total expected TFVs per year ~~considering all kinds of floods (i.e., the~~ grey area in b) under a stationary drainage system.

Figure 3 ~~Projected TFV with changes in~~ Changes in total flood volume (TFV) as a function of precipitation intensity at various return periods under ~~the RCP8.5 scenario for without mitigation~~ and adaptation. Red solid line represents the multi-model ensemble median TFV with shaded areas denoting the ~~period of ensemble range~~. Red dashed line is the TFV under present condition. Box plots show the relative changes in TFV by 2020–2040, relative to present condition. Box edges illustrate the 25th and 75th percentile, the central mark is the median and whiskers mark the 5th and 95th percentiles.

Figure 4 Comparison of (a) flood volume, (b) total TFVs (i.e., the piece-wise integral of flood volume versus the expected frequency with changes in precipitation intensity of various return periods under RCP8.5 (blue) and RCP2.6 (red). (c) is ~~for the reduced TFVs in~~ TFV reduction calculated as the percentage ~~(i.e., difference in TFVs under RCP2.6 compared to RCP8.5 (i.e.,~~ benefits of climate mitigation) in RCP2.6 relative to RCP8.5 at various return periods.

Figure 5 Spatial distribution of overloaded pipelines (red colour) induced by the 3-year (left column) and 50-year extreme events (right column) without and with adaptations. The total percentage of overloaded manholes (POM) and ratio of flood volume (RFV) to input rainfall volume are summarised for each scenario. ~~Descriptions of Historical flood points and~~ local land use, mainly the traffic network and green spaces, are ~~provided as the background images shown~~ in (a).

Figure 6 Future changes in flood volumes (CTFVs) relative to historical conditions under the current drainage system (yellow) and two adaptation scenarios (i.e., Pipe in red and Pipe+LID in green) at various return periods.

Figure 7 Comparison of benefits of climate mitigation and two adaptation strategies in reducing urban flood volumes with changes in precipitation intensities for various return periods, and with related variations (boundary bars) as a result of uncertainty arising from local soil conditions.




Figure 1 Land use of the study region for the year 2010 (a) and 2020 (b). Pipe network description of current and planned drainage systems (c). Difference in Weighted Mean Imperviousness (WMI) between year 2010 and 2020 (d).





Figure 2 Illustration of total flood volume and average total expected total flood volumes (TFVs) as a function of return period under a stationary drainage system. The grey area denotes the periods (a) and estimation of average total expected TFVs per year considering all kinds of floods (i.e., the grey area in b) under a stationary drainage system.



Formatted: Font:

1232
1233





Figure 3 Projected TFV with changes in Changes in total flood volume (TFV) as a function of precipitation intensity at various return periods under the RCP8.5 scenario for without mitigation and adaptation. Red solid line represents the multi-model ensemble median TFV with shaded areas denoting the period of ensemble range. Red dashed line is the TFV under present condition. Box plots show the relative changes in TFV by 2020–2040, relative to present condition. Box edges illustrate the 25th and 75th percentile, the central mark is the median and whiskers mark the 5th and 95th percentiles.



1243





Figure 4 Comparison of (a) flood volume, (b) total TFVs (i.e., the piece-wise integral of flood volume versus the expected frequency with changes in precipitation intensity of various return periods under RCP8.5 (blue) and RCP2.6 (red). (c) is for the reduced TFVs in TFV reduction calculated as the percentage difference in TFVs under RCP2.6 compared to RCP8.5 (i.e., benefits of climate mitigation) in RCP2.6 relative to RCP8.5 at various return periods.



1251
1252




Figure 5 Spatial distribution of overloaded pipelines (red colour) induced by the 3-year (left column) and 50-year extreme events (right column) without and with adaptations. The total percentage of overloaded manholes (POM) and ratio of flood volume (RFV) to input rainfall volume are summarised for each scenario. Descriptions of Historical flood points and local land use, mainly the traffic network and green spaces, are provided as the background images shown in (a).




Figure 6 Future changes in flood volumes (CTFVs) relative to historical conditions under the current drainage system (yellow) and two adaptation scenarios (i.e., Pipe in red and Pipe+LID in green) at various return periods.




Figure 7 Comparison of benefits of climate mitigation and two adaptation strategies in reducing urban flood volumes with changes in precipitation intensities for various return periods, and with related variations (boundary bars) as a result of uncertainty arising from local soil conditions.