Satellite-Derived Light Extinction Coefficient and its Impact on Thermal Structure Simulations in a 1-D Lake Model

Kiana Zolfaghari¹, Claude R. Duguay¹, Homa Kheyrollah Pour¹

¹Interdisciplinary Centre on Climate Change and Department of Geography & Environmental Management, University of Waterloo, Waterloo, Canada

Correspondence to: Kiana Zolfaghari (kzolfagh@uwaterloo.ca)

Abstract. One essential optical parameter to specify in lake models is water clarity, which is parameterized based on the light extinction coefficient (K_d). A global constant value of K_d is usually specified in lake models. One-dimensional (1-D) lake models are most often used as lake parameterization schemes in numerical weather prediction and regional climate models. This study aimed to improve the performance of the 1-D Freshwater Lake (FLake) model using satellite-derived K_d for Lake Erie. The CoastColour algorithm is applied to MERIS satellite imagery to estimate K_d and evaluated against K_d derived from Secchi disk depth (SDD) field-based measurements collected during Lake Erie cruises. A good agreement is found between field and satellite-derived K_d (RMSE = 0.63 m⁻¹, MBE = -0.09 m⁻¹, $I_d = 0.65$) (in situ data was collected in 2004, 2005, 2008, 2011, 2012). The constant (0.2 m⁻¹) and satellite-derived K_d values as well as radiation fluxes and meteorological station observations are then used to run FLake at the location of a buoy where lake surface water temperature (LSWT) was measured in 2008. Results improved compared to using a constant K_d value (0.2 m⁻¹) (lake-specific yearly average K_d value: RMSE=1.54 °C, MBE= -0.08 °C; constant K_d value: RMSE=1.76 °C, MBE= -1.26 °C). No significant improvement is found in FLake simulated LSWT when K_d variations in time are considered using a monthly average. Therefore, results suggest that a time-independent, lake-specific, and constant satellite-derived K_d value can reproduce LSWT with sufficient accuracy for Lake Erie NDBC station.

A sensitivity analysis is also performed to assess the impact of various K_d values on the simulation of LSWT, mean water column temperature (MWCT), lake bottom water temperature (LBWT), mixed layer depth (MLD), water temperature isotherms as well as ice dates and thickness. Results show that FLake is sensitive to variations in K_d to estimate the thermal structure of Lake Erie. Dark waters result in warmer spring and colder fall temperatures compare to clear waters. Dark waters always produce warmer MWCT, shallower MLD, longer ice cover duration, and thicker ice. The sensitivity of FLake to K_d variations is more pronounced in the simulation of MWCT, LBWT, and MLD. The model is particularly sensitive to K_d values below 0.5 m^{-1} . This is the first study to assess the value of integrating K_d from the satellite-based CoastColour algorithm into the FLake model. Satellite-derived K_d is found to be a useful input parameter for simulations with FLake and possibly other lake models, and with potential for applicability to other lakes where K_d is not commonly measured.

Keywords: Water clarity, extinction coefficient, MERIS, CoastColour, FLake, Lake Erie, lake water temperature

1 Introduction

There has been significant progress made in recent years in the representation of lakes in regional climate models (RCM) and numerical weather prediction (NWP) models. Lakes are known to be an important continental surface component affecting weather and climate, especially in lake-rich regions of the northern hemisphere (Eerola et al., 2010; Martynov et al., 2012; Samuelsson et al., 2010). They can influence the atmospheric boundary layer by modifying the air temperature, wind and precipitation. Therefore, consideration of lakes in NWP/RCM is essential (Kheyrollah Pour et al., 2012, 2014b; Martynov et al., 2010). In order to account for lakes in NWP/RCM, a description of energy exchanges between lakes and the atmosphere is required (Eerola et al., 2010). Lake Surface Water Temperature (LSWT) is one of the key variables when investigating lakeatmosphere energy exchanges (Kheyrollah Pour et al., 2012). There are various approaches to obtaining LSWT and integrating it in NWP models, such as through climatic observations, assimilation and/or lake parameterization schemes (Eerola et al., 2010; Kheyrollah Pour et al., 2014a). Currently, LSWT is broadly modelled in NWP models using one-dimensional (1-D) lake models as lake parameterization schemes (Martynov et al., 2012). For instance, the 1-D Freshwater Lake (FLake) model performs adequately for various lake sizes, shallow to relatively deep (artificially limited to 40-60 m depth (Kourzeneva et al., 2012a)), located in both temperate and warm climate regions (Kourzeneva, 2010; Martynov et al., 2010, 2012; Mironov, 2008; Mironov et al., 2010, 2012; Samuelsson et al., 2010; Kourzeneva et al., 2012a; Kourzeneva et al., 2012b). One of the optical parameters required as input in the FLake model is water clarity. This variable is considered as an apparent optical property and is parameterized using the light extinction coefficient (K_d) to describe the absorption of shortwave radiation within the water body as a function of depth (Heiskanen et al., 2015). A global constant value of K_d is usually used to run lake models, including FLake. For example, Martynov et al. (2012) coupled FLake in the Canadian Regional Climate Model (CRCM) by specifying a K_d value equal to 0.2 m⁻¹ (Martynov, pers. comm., 2015) for all North American Lakes, including Lake Erie for years 2005-2007. Heiskanen et al. (2015) evaluated the sensitivity of two 1-D lake models, LAKE and FLake, to seasonal variations and the general level of K_d for simulating water temperature profiles and turbulent fluxes of heat and momentum in a small boreal Finnish lake. Modelled values were compared to those measured for the lake during the icefree period of 2013. The study found a critical threshold for K_d (0.5 m⁻¹) in 1-D lake models. Heiskanen et al. (2015) concluded that for too clear waters ($K_d < 0.5 \text{ m}^{-1}$), the model is much more sensitive to K_d . The study recommends a global mapping of K_d to run the FLake model for regions with clear waters ($K_d < 0.5 \text{ m}^{-1}$) for future use in NWP models. The authors also suggest that this global mapping can be time-independent (i.e. with a constant value per lake) (Heiskanen et al., 2015), and this can be derived from satellite imagery. Potes et al. (2012) used empirically derived water clarity from space-borne Medium Resolution Imaging Spectrometer (MERIS) measurements to test the sensitivity of FLake to this parameter. The sensitivity analysis was conducted using two K_d values, representing the expected extreme water clarity cases for their study (1.0 m⁻¹ for clear water and 6.1 m⁻¹ for dark water). The importance of lake optical properties was evaluated based on the evolution of LSWT and heat fluxes. Their results show that water clarity is an essential parameter affecting the simulated LSWT. The daily mean LSWT

range increased from 1.2 °C in clear water to 2.4 °C in dark water (Potes et al., 2012). Water clarity measurements are included

in water quality monitoring programs; however, global measurements of clarity are not yet available. Satellite remote sensing can provide water clarity observations to the modelling communities at higher spatial and temporal resolutions, to fill the gap of field measurements.

In recent years, a number of algorithms have been devised to retrieve different water optical parameters, including water clarity,
from satellite observations for coastal (ocean) and lake waters (Attila et al., 2013; Binding et al., 2007, 2015; Olmanson et al.,
2013; Potes et al., 2012; Wu et al., 2009; Zhao et al., 2011). Turbid inland and coastal waters are optically more complex
compared to open ocean, and large optical gradients exist. There is more than only one component (phytoplankton species,
various dissolved and suspended matters with non-covarying concentrations) in coastal waters and lakes that determines the
variability of water-leaving reflectance. Considering this complexity, the development of algorithms for coastal waters and
lakes is more challenging. MERIS, which operated from March 2002 to April 2012, collected data from the European Space
Agency's (ESA) Envisat satellite. The spatial resolution and spectral bands settings were carefully selected in order to meet
the primary objectives of the mission; addressing coastal monitoring from space. The best possible signal-to-noise ratio,
additional channels to measure optical signatures as well as the relatively high spatial resolution of 300 m are some of the
specific instrument characteristics (Ruescas et al., 2014). In 2010, ESA launched the CoastColour project to fully exploit the
potential of MERIS instrument for remote sensing of coastal zone waters. CoastColour (CC) is providing a global dataset of
MERIS full resolution data of coastal zones that are processed with the best possible regional algorithms to produce waterleaving reflectance and optical properties (Ruescas et al., 2014).

The objectives of this study are to: 1) evaluate satellite-derived K_d values for a large lake in the Great Lakes region; 2) apply the evaluated satellite-derived K_d in FLake model to investigate the improvement of model performance to reproduce LSWTs. Three different values of K_d are used in the simulations: yearly average, monthly average, and a constant value to demonstrate the impact of a time-independent, lake-specific K_d value in simulating LSWT; and 3) understand the sensitivity of the FLake model to K_d values based on simulated LSWT, mean water column temperature (MWCT), lake bottom water temperature (LBWT), mixed layer depth (MLD), and water temperature isotherms during the ice-free season on Lake Erie (from April to November). The impact of K_d variations on ice dates (freeze-up, break-up, and duration) and ice thickness is also evaluated.

25 **2 Data and Methods**

2.1 Study Site and Station Observations

Lake Erie (42° 11′N, 81° 15′W; Fig. 1) is a large shallow temperate freshwater lake covering a surface area of 25,700 km². The lake is characterized by three basins: shallow western, central, and deep eastern basins with maximum depths of 19 m, 25 m, and 64 m, respectively. Lake Erie is monomictic with occasional dimictic years (Bootsma & Hecky, 2003). It is the shallowest and smallest by volume of the Laurentian Great Lakes (Daher, 1999). These characteristics make Lake Erie unique from the other Great Lakes.

The meteorological forcing variables required for FLake model runs include solar (shortwave) and longwave irradiance, air temperature, air humidity, wind speed, and cloudiness. Mean daily air temperature, wind speed and water temperature measurements were obtained from the National Data Buoy Center (NDBC) of NOAA, station 45005 (2003-2012). The station location is shown in Fig. 1 (41°40' N, 82°23' W, and depth: 12.6 m). Air temperature is measured 4 m above the water surface and an emometer height is 5 m above the water surface to measure the wind speed, whereas the water surface is at 173.9 m above mean sea level. Water temperature is also measured at 0.6 m below the water line. The NDBC station was selected to perform simulations with FLake, since water temperature observations collected at the buoy station can be used to evaluate the model output. The other meteorological forcing variables required for model simulations at the NDBC station were obtained from nearby stations. Air humidity, and cloudiness were available in a daily format from EC-Ontario Climate Center (OCC) for the Windsor station (climate ID: 6139525) (2003-2012). The location of this station is shown in Fig. 1, which is a near-shore station close to the NDBC station. The distance between OCC and NDBC stations is less than 81 km. Incoming radiation fluxes data was supplied by the National Water Research Institute (NWRI), Environment Canada (EC), from a station located in the western basin of Lake Erie (see Fig. 1). Daily shortwave irradiance measurements were available only for 2004 and 2008. Therefore, a daily time series of solar irradiance for the entire study period (2003-2012) was completed for the NDBC station using solar irradiance model data (see Sect. 2.2). Longwave irradiance was measured only in 2008 at the NWRI-EC station. An empirical equation (see Sect. 2.2) was therefore employed to obtain longwave irradiance for the full period of study (2003-2012).

FLake requires information on water transparency (downward light K_d) as input for model runs. MERIS satellite imagery was used to derive K_d for the NDBC station during the study period. The method is described in details in Sect. 2.3. Available Secchi disk depth (SDD) field measurements were collected by EC research cruises on board the Canadian Coast Guard Ship *Limnos* and utilized in this study to evaluate the satellite-derived water clarity. The cruise visited Lake Erie at a total of 89 distributed stations in five different years (September 2004; May, July, and September 2005; May and June 2008; July and September 2011; and February 2012). The location of stations is shown in Fig. 1.

2.2 Shortwave and Longwave Irradiance

The SUNY model, a satellite solar irradiance model, has been developed to exploit Geostationary Operational Environmental Satellites (GOES) for deriving solar irradiance using cloud, albedo, elevation, temperature, and wind speed observations (Kleissl et al., 2013). The basic principles of solar-irradiance modelling based on inputs from geostationary satellites and atmospheric models are described in Kleissl et al. (2013). Data from these sources are used to generate site and time specific high-resolution maps of solar irradiance with the SUNY model. The daily mean solar irradiance data for the present study was obtained from the second version of the SUNY model (Version 2.4), available in SolarAnywhere® (https://www.solaranywhere.com). The model provides a gridded data set with a spatial resolution of one tenth of a degree (ca. 10 km). The solar irradiance data was extracted from a tile corresponding to the NWRI station (see Fig. 1) for 2004 and 2008, when observations were available for evaluation, and also for FLake model run on Lake Erie for the full study period (2003-

2012). There is a strong agreement ($R^2 = 0.93$) between model-derived and measured solar irradiance at the NWRI station. The SUNY model slightly underestimates observations by 2.18 Wm⁻² (N = 362, RMSE = 21.58 Wm⁻², MBE = -2.18 Wm⁻², I a = 0.88; see Sect. 2.5 for details).

5 Longwave irradiance was computed on a daily basis using the equation of Maykut and Church (1973), as implemented in the Canadian Lake Ice Model (CLIMo) (Duguay et al., 2003):

$$E = \sigma T^4 (0.7855 + 0.000312G^{2.75})$$
 Eq. (1)

10 where T is the air temperature at screen height (°K) and G is the cloudiness in tenth from meteorological stations.

Longwave irradiance calculated from Eq. 1 was evaluated against observations from the NWRI-EC station, only available in 2008. The two datasets are highly correlated ($R^2 = 0.74$) with the equation underestimating measured irradiance by 0.86 Wm⁻² (N = 194, RMSE = 17.74 Wm⁻², MBE = -0.86 Wm⁻², I_a = 0.76). Model-derived incoming shortwave and longwave fluxes were used as input in FLake model simulations for subsequent analyses in NDBC station over the 2003-2012 period.

2.3 Satellite-Derived Extinction Coefficient

MERIS operated on-board the ESA Envisat polar-orbiting satellite until April 2012. The sensor was a push-broom imaging spectrometer which measured solar radiation reflected from the Earth's surface high spectral and radiometric resolutions with a dual spatial resolution (300 m and 1200 m). Measurements were obtained in the visible and near-infrared part of the electromagnetic spectrum (across the 390 nm to 1040 nm range) in 15 spectral bands during daytime, whenever illumination conditions were suitable, and with a full spatial resolution of 300 m at nadir, with a 68.5° field-of-view. MERIS scanned the Earth with a global coverage of every 2-3 days.

In this study, a total of 326 full resolution archived MERIS images encompassing the NDBC station in Lake Erie (see Fig. 1) were acquired from CC (Version 2) products through the Calvalus on-demand processing service for the period of 2003-2012.

CC Level2W products are the result of in-water processing algorithms to derive optical parameters from the water leaving reflectance. These parameters include inherent optical properties (IOPs), concentrations of water constituents, and other optical water parameters such as spectral vertical K_d . The IOP parameters are first derived applying two different inversion algorithms: neural network (NN) and Quasi Analytical Algorithm (QAA). The derived IOPs are then converted to estimate constituents' concentrations and apparent optical properties (AOP), including diffuse K_d for different spectral bands applying Hydrolight simulations (Ruescas et al., 2014).

The diffuse K_d product (the average value between visible spectral bands) in CC MERIS L2W data was extracted for the pixel at the geographic location of the NDBC station. The satellite-derived K_d values were also extracted for pixels on the same day and location as the *Limnos* cruise stations to evaluate the CC-derived diffuse K_d values against SDD in situ data collected

during *Limnos* cruises. A valid pixel expression was defined in all pixel extraction steps that excluded pixels with properties listed in Table 1.

2.4 FLake Model and Configuration

The FLake model is a self-similar parametric representation (assumed shape) of the temperature structure in the four media of the lake including water column, bottom sediments, and in the ice and snow. The water column temperature profile is assumed to have two layers: a mixed layer with constant temperature and a thermocline that extends from the base of mixed layer to the lake depth. The shape of thermocline temperature is parameterized using a fourth-order polynomial function of depth that also depends on a shape coefficient C_T . The value of C_T lies between 0.5 and 0.8 so that the thermocline can neither be very concave nor very convex. FLake has an optional scheme for the representation of bottom sediments layer, which is based on the same parametric concept (De Bruijn et al., 2014; Martynov et al., 2012). The system of prognostic equations for parameters is described in Mironov (2008).

The prognostics ordinary differential equations are solved to estimate the thermocline shape coefficient, the mixed layer depth, bottom, mean and surface water column temperatures, and also parameters related to the bottom sediment layers (Martynov et al., 2012; Mironov, 2008; Mironov et al., 2010). The same parametric concept is applied for the ice and snow layers, using linear shape functions (Martynov et al., 2012). The mixed layer depth is calculated considering the effects of both convective and mechanical mixing, also accounting for volumetric heating which is through the absorption of net shortwave radiation (Thiery et al., 2014). The non-reflected shortwave radiation is absorbed after penetrating the water column in accordance with the Beer-Lambert law (Martynov et al., 2012; Mironov, 2008; Mironov et al., 2010).

Stand-alone FLake simulations were conducted for the NDBC station. The setup condition of NDBC buoy station, such as height of wind measurement (5 m), height of air temperature sensor (4 m), and the geographic location and depth of this site (41°40′ N, 82°23′ W, and depth: 12.6 m) were used to configure the model. The measured meteorological parameters and model-derived irradiance were also used to force the FLake model. A fetch value of 100 km was used to run all simulations. It was found that there is only little sensitivity to modifications in this parameter for Lake Erie. The same result was found for Lake Kivu in Thiery et al. (2014). The bottom sediments module was switched off in all simulations and the zero bottom heat flux condition is adopted. The initial temperature value for the upper mixed layer and the lake bottom were 4°C. Mixed layer thickness had the initial value of 3 m. The simulations were run in a daily time step (using daily forcing data) for 2003-2012. The ability of FLake to reproduce the observed temperature variations using different K_d values was tested by comparing the simulated LSWT to the corresponding in situ observations in the NDBC station. Also, the model sensitivity to variations in water clarity was assessed studying the LSWT, MWCT, LBWT, MLD, isotherms, ice phenology, and ice thickness.

2.5 Accuracy Assessment

To assess the model outputs, three statistical indices were calculated: the root mean square error (RMSE), the mean bias error (MBE), and the index-of-agreement (I_a). RMSE is a comprehensive metric that combines the mean and variance of model

errors into a single statistic (Moore et al., 2014). The MBE is calculated as the modelled values minus the in situ observations. Therefore, a positive (negative) value of this error shows an overestimation (underestimation) of the parameter of interest. La is a descriptive measure of model performance. It is used to compare different models and also modelled against observed parameters. La was originally developed by Willmott in the 1980s (Willmott, 1981) and a refined version of it was presented by Willmott et al. (2012). The refined version, which was adopted in this study, is dimensionless and bounded by -1.0 (worst performance) and 1.0 (the best possible performance). These statistical indices are considered as robust measures of model performance (e.g., Hinzman et al., 1998; Kheyrollah Pour et al., 2012; Willmott and Wicks, 1980).

3 Results and Discussion

3.1 Satellite-Derived K_d

3.1.1 Variations of K_d at NDBC Station

Fig. 2 shows the variations of CC-derived K_d for the NDBC station during the full study period (2003-2012). In the shallow section of Lake Erie, re-suspension of bottom sediments is the most important factor that leads to lower water clarity. Therefore, the highest K_d values are related to the turn-over times in spring and fall. The results from applying the CC algorithm on MERIS satellite imagery show that the maximum value of K_d is 3.54 m⁻¹, estimated in April 2003. A minimum value of 0.58 m⁻¹ is estimated in June 2007. The average value of K_d during the study period is 0.90 m⁻¹ with a standard deviation of 0.38 m⁻¹. Hence, these values, identified as the average, the lower, and the upper limits of clarity at the NDBC station were used to carry out a sensitivity analysis with FLake (see Sect. 3.2.2).

3.1.2 Evaluation of CoastColour Kd

The validation of satellite observations against in situ data is important, because the in situ data are still considered as the most accurate measurement of water clarity. The assessment of the satellite-derived K_d retrieval reliability highly depends on the comparison with independent in situ SDD measurements. The general form of the relationship between K_d and SDD was established by the pioneer study of Poole and Atkins (1929):

$$SDD \times K_d = K$$
 Eq. (2)

where *K* is a constant value of 1.7 (Poole and Atkins, 1929). Following this important work, there were other studies that derived an empirical relationship between the two parameters. Studies have found a high variability of the constant value (*K*) depending on the type of the lake considered (Koenings and Edmundson, 1991). Armengol et al. (2003) also show that K_d and SDD are negatively correlated and they developed an empirical relation between these two parameters using Eq. (2). In this study, applying a cross validation approach, an empirical relation was developed between in situ measured SDD and CC-derived K_d. SDD measurements were conducted 117 times during cruises on Lake Erie from 2004 to 2012. These spatially-distributed measurements have minimum, maximum, mean, and standard deviation values of 0.2, 11, 3.69, and 2.68 m,

respectively. CC L2W satellite products were acquired on the same day as the in situ measurements. Applying defined flags produced 49 data pairs (matchup dataset) of CC observations of K_d and SDD in situ data that were collected on the same day and location.

The matchup dataset was divided into training and testing data in 100 iterations. In each iteration, the data used for the equation's training and evaluation were kept independent, where 70% of the sample was used for equation calibration and 30% for evaluation. Ordinary least square regression was used in the calibration step of each iteration to relate the in situ measurements of SDD to the CC-derived K_d. Locally tuned equations were derived from this step and applied on SDD observations to predict K_d in testing matchup data. The statistical parameters of the model performance were derived between the estimated K_d from SDD observations and the paired CC-derived values. These steps were repeated for 100 iterations; and the final statistical indices, slope and power of the locally tuned equation was reported as the average of the ones derived over all iterations.

Results from the above procedure show that K_d can be derived from SDD, using the equation $K_d = 1.64 \times SDD^{-0.76}$, with a strong determination of coefficient value ($R^2 = 0.78$). Arst et al. (2008) obtained a similar regression formula between SDD and K_d for the boreal lakes in Finland and Estonia representing different types of water, expanding from oligotrophic to hypertrophic. Because there is a good agreement between K_d and the corresponding ones estimated from in situ measured SDD (N = 49, $RMSE = 0.63 \text{ m}^{-1}$, $MBE = -0.09 \text{ m}^{-1}$, $I_a = 0.65$; Fig. 3), the satellite-derived water clarity are deemed to be correct and were used in the modelling for this study.

However, SDD is not always describing K_d values. SDD is a suitable characteristic to describe water transparency for small values of K_d . For high values of K_d (ranging above 4 m⁻¹), Arst et al. (2008) and Heiskanen et al. (2015) suggest that SDD is unable to describe any changes in K_d . Fig. 3 also shows that SDD cannot describe the scatter of K_d for values above 4 m⁻¹. Therefore, the estimation of K_d from SDD should be used with caution, motivating the investigation on the potential of integrating satellite-based estimations of K_d into lake models.

3.2 FLake Model Results

3.2.1 Improvement of LSWT Simulations with Satellite-Derived K_d

Martynov et al. (2012) focused on 2005 to 2007 to run FLake at the NDBC station using a constant value of 0.2 m⁻¹ for K_d. They simulated the lake using both realistic and excessive depths of 20 and 60 m, respectively, for a grid tile corresponding to the NDBC station. They showed that applying a more realistic lake depth parameterization improved the performance of the model to reproduce the observed surface temperature. In this section, K_d values were derived from the CC algorithm for different months during the same years (2005-2007) as in Martynov et al. (2012).

Table 2 displays the average K_d values for each month of these years. The monthly averaged values are only focused on the months of the year when both LSWT observations and CC-derived K_d values were available. The average value of K_d in these months in each year is considered as the average value of K_d for that year.

Fig. 4 compares the results of different LSWT FLake simulations with observations at the NDBC station. LSWT observations have maximum values of 27.53 °C, 26.48 °C, and 25.46 °C in August during 2005, 2006 and 2007. The minimum values of 2.71 °C, 7.3 °C, and 3.42 °C were observed in December 2005, and April in 2006 and 2007. The average LSWT observations in 2005, 2006, and 2007 have values of 18.45 °C, 17.12 °C, and 17.75 °C, respectively. The simulated LSWT values in Fig. 4 are produced by first applying K_d = 0.2 m⁻¹ from Martynov et al. (2012) using both the real lake depth at the station (12.6 m: CRCM-12.6) and also a tile depth corresponding to the station in their study (20 m: CRCM-20). Then, simulations using the yearly average CC-derived K_d for each year of study are plotted (Avg). The K_d values derived from the monthly average of each year were used to simulate the surface water temperature and produce a merged LSWT product (Merged). Both Avg and Merged simulations used the real lake depth at NDBC station (12.6 m).

Comparing LSWT in situ observations (Obs) with the modelled values in Fig. 4 demonstrate that in Avg and Merged simulations for 2005-2007, surface temperature in spring (April-June) is modelled warmer and colder in summer (July-September) and fall (October-November) than in situ observations (spring: MBE Avg = 1.31 °C, MBE Merged = 1.25 °C; summer: MBE Avg = -0.72 °C; MBE Merged = -0.75 °C; fall: MBE Avg = -1.82 °C, MBE Merged = -1.99 °C; see Fig. 5 for seasonal-based performance of simulations). CRCM-12.6 and CRCM-20 are reproducing a colder LSWT in average with maximum underprediction in July-August (for 2005-2007: -2.93 °C <MBE_{July-August}<-0.99 °C). Simulation with a larger depth (CRCM-20) tends to more slowly gain (lose) heat in spring (fall), compared to all other simulations.

The performance of each simulation is summarized in Table 3 during the period of data availability. For all years, the average and merged simulations perform better than simulations using K_d (0.2 m⁻¹) as in Martynov et al. (2012), with improvement in RMSE and MBE for both real depth and tile depth. In all three years, LSWT simulated from the K_d value employed in Martynov et al. (2012) results in an underestimation (CRCM-12.6: MBE= -1.52 °C, -0.98 °C, -1.08 °C; CRCM-20: MBE= -1.54 °C, -1.09 °C, -1.35 °C; during years 2005, 2006, and 2007, respectively). In 2005, the average of K_d for the year demonstrates a better performance compared to the merged results; contrary to the results of 2007. However, for the merged results in 2006, the MBE is improved compared to the simulation using the average K_d ; whereas its performance decreases in terms of RMSE. The extent of K_d variations in each month might not be captured by the available MERIS images due to cloud coverage in MERIS images or the absence of any satellite overpass. Therefore, a yearly-average K_d can be potentially closer to the actual value of K_d . For this reason, the merged results cannot always perform better than average simulations.

Fig. 5 illustrates the scatterplots of simulated LSWT for all four different runs including three years of data (2005-2007), in comparison with the corresponding in situ observations. All simulated results are in a high agreement with in situ measurements. CRCM simulations (both depths of 12.6 and 20 m) under-predict LSWT with MBE values of -1.26 °C and -1.37 °C, respectively. The under-prediction of these model runs is stronger, particularly for LSWT above 12°C, which can be explained by the K_d value used. This is because, no matter what depth is used in simulations (either actual or tile depth), both CRCM runs have larger MBE compared to Avg and Merged simulations. However, the CRCM-20 simulation tends to produce the coldest LSWT (the most under-prediction; MBE = -1.37 °C). This is due to the lake depth value considered for the model run which corresponds to the tile depth as opposed to the other simulations that were based on using the actual depth at station.

Fig. 5-a and -b show that the resulting LSWT from yearly average (Ave) and monthly average (Merged) K_d are not significantly different, whereas simulations with yearly average K_d reproduces LSWT with improved RMSE and MBE values compared to monthly average (Avg: RMSE=1.54 °C, MBE=-0.08 °C; Merged: RMSE=1.57 °C, MBE=-0.14 °C). It is possible that the actual K_d value is best represented by the yearly average value. Therefore, using a constant annual open water season value for K_d could be potentially sufficient to simulate LSWT in 1-D lake models with relatively high accuracy (the range of K_d variations that brings the most sensitivity for the modelling is discussed in Sect. 3.2.2). The time-dependent (monthly average) K_d does not improve simulation results for Lake Erie (K_d ranging from 0.58 to 3.54 m⁻¹ with average value of 0.90 m⁻¹ during open water seasons of 2003-2012). However, comparing results from Fig. 5-a and –c shows improvement in LSWT simulations when a lake-specific value of K_d is used (Avg: RMSE=1.54 °C, MBE=-0.08 °C; CRCM-12.6: RMSE=1.76 °C, MBE= -1.26 °C). Under-prediction of LSWT decreases when the yearly-average CC-derived K_d values are used, rather than a generic constant value (0.2 m⁻¹). Heiskanen et al. (2015) suggest that the effect of K_d seasonal variations on LSWT simulations are not significant for lakes with K_d values higher than 0.5 m⁻¹ (e.g. Lake Erie). Therefore, in the absence of reliable values of the temporal evolution of K_d , a lake-specific, time-independent, and constant value of K_d can be used in 1-D lake models when the K_d values are higher than 0.5 m⁻¹.

Martynov et al. (2012) conclude that applying a more realistic lake depth parameterization improves the FLake model performance. Using the realistic lake depth (12.6 m) at the NDBC station slightly improves the model performance in reproducing LSWT compared to simulation employing the corresponding tile depth (20 m) (CRCM-12.6: RMSE=1.76 °C, MBE=-1.26 °C; CRCM-20: RMSE=1.88 °C, MBE=-1.37 °C) (Fig. 5-c and -d).

3.2.2 Sensitivity of FLake to K_d Variations

The sensitivity of FLake to different values of K_d to reproduce LSWT, MWCT, LBWT, MLD, isotherm, ice phenology and thickness is investigated in this section for year 2008. As indicated previously (Sect. 2.1), shortwave irradiance measurements were available in that year and longwave irradiance was also measured from May to October 2008. Therefore, longwave irradiance for the other months of 2008 was modelled as described in Sect. 2.2 to fill the temporal gaps. Fig. 6 presents simulation results for LSWT, MWCT, and LBWT using the real lake depth at NDBC station, and the lowest, average, and highest values of K_d observed in the study period (minimum K_d=0.58 m⁻¹, average K_d=0.90 m⁻¹, maximum K_d=3.54 m⁻¹). The water temperature simulation from CRCM-12.6 (using K_d=0.2 and realistic depth at station) simulation is also plotted. In the case of extreme clear water (CRCM-12.6), LSWT shows smoother variations during the open water season in 2008 as opposed to the darkest water simulation (maximum or Max) which displays more abrupt LSWT variations (Fig. 6). This is because solar radiation is absorbed more in dark waters due to existing particles in water. It penetrates less deeply and warms up only the shallow surface layer (lower LBWT; see Fig. 6-c) causing thinner mixing depth (Fig. 8). The high temperature of this shallow layer causes an increase in latent and sensible heat fluxes. Therefore, the shallow mixed layer exchanges heat faster with the atmosphere, resulting in sudden surface water temperature variations as opposed to clear waters. The fast heat exchange with atmosphere results in warmer LSWT during spring (start of heating season) and colder LSWT in fall for dark

water as opposed to clear one. On average, the darkest water simulation (Max) resulted in 0.09 °C higher LSWT compared to the average (Avg) simulation, whereas the clear water (minimum or Min) simulation produced on average 0.02 °C colder LSWT during 2008. CRCM-12.6 simulation with K_d value of 0.2 resulted in a larger difference compared to Avg simulation, 0.55 °C colder LSWT. The comparison of the simulated LSWT results show that FLake simulated LSWT is not significantly sensitive to K_d values when this value varies in the range of our Min to Max K_d. However, the sensitivity increases rapidly for K_d values less than our Min (0.58 m⁻¹). This result supports the study of Rinke et al. (2010) that the thermal structure of lakes is particularly sensitive to changes in K_d when its value is below 0.5 m⁻¹. More recently, Heiskanen et al. (2015) confirmed the critical threshold of K_d (ca. 0.5 m⁻¹). They suggest that the response of 1-D lake models to K_d variations is nonlinear. The models are much more sensitive if the water is estimated to be too clear. Heiskanen et al. (2015) recommend to use a value of K_d that is too high rather than too low in lake simulations, if the clarity of lake is not known exactly.

The MWCT and LBWT in the darkest condition (Max) are less than for all other clear water simulations. This is because the lower layers in dark waters accumulate less heat during the heating season as opposed to clear waters which results in less heat storage and lower water column temperature in dark waters (Heiskanen et al., 2015; Potes et al., 2012). The MWCT decreases by 0.94 0 C (increases by 0.63 0 C) when maximum (minimum) K_{d} value is used instead of its average value during the study period. The MWCT increases by 2.25 0 C when using K_{d} value of 0.2 m⁻¹ rather than the average value. Changes in K_{d} value from its maximum (minimum) to its average value also causes decrease (increase) of -0.67 0 C (0.67 0 C) in the LBWT. The increase in LWBT is even larger when K_{d} value of 0.2 m⁻¹ is used instead of its average value (6.96 0 C). Therefore, K_{d} variations have a larger impact on MWCT and LBWT than on LSWT, and the largest difference is when K_{d} is estimated to be extremely clear.

Fig. 7 displays the simulated isotherms derived from using different K_d values. It shows that the mixed layer in dark waters is warmer in spring and summer and colder in fall. There are a number of factors determining the mixed layer temperature in lakes, including the radiation fluxes (sensible heat, latent heat, and longwave radiation), and cooling effects from the water below. Persson and Jones (2008) conclude that for dark waters, the combination of these heating and cooling effects leads to a warmer epilimnion initially. The radiation is used to warm up a thinner layer in dark waters leading to higher (lower) temperatures in spring and summer (fall). However, a lower temperature in the mixed layer is followed due to the gradual lessening of the radiative absorption and increased effect of cooling from the layers below. Fig. 7 also supports observations by Persson and Jones (2008) and Heiskanen et al. (2015) that the depth of the thermocline layer is always deeper in clear waters due to the faster heat distribution between different underneath layers. The deepening of the thermocline layer in clear waters is faster compared to dark waters. The reason is that the heat transfer in dark waters is slower between water layers.

Fig. 8 is derived from isotherm to only focus on the variations of the MLD in 2008, using different values of K_d (Min, Ave, and Max K_d, and CRCM-12.6) in simulations. All simulations show two turnover (complete mixing) events, spring and fall. Full mixing in spring is at the same time for all simulations; however, fall full mixing occurs at different dates for each simulation. Fall turnover in CRCM-12.6 is at the end of summer (August 28), while the other three runs show that the fall

turnover takes place in late fall, before ice forms. Full mixing in the Min simulation is in early November (November 3), earlier than the Avg and Max simulations (November 21).

In the darkest water simulation (Max), the MLD is shallower than the other simulations (an average difference of 4.94 m in 2008 between two simulations of Max and CRCM-12.6, with extreme K_d values). Clear waters have a deeper mixed layer when the solar radiation can penetrate further and distribute to a larger volume in the water column. CRCM-12.6 produces a MLD of 3.47 m deeper compared to Avg simulation, whereas the Min (Max) simulations result in MLD of 1.15 m (1.47 m) deeper (shallower) compared to the Avg simulation. Hence, clear water simulates deeper MLD; and the effect of K_d on the MLD is larger when the K_d value is estimated to be too clear.

Fig. 9 shows the impact of K_d variations on lake ice phenology and thickness in winter 2008 (January-March). Freeze-up corresponds to the earliest date that the NDBC station is completely covered by ice, and the earliest date the station is completely free of floating ice is defined as break-up. The Avg simulation reproduces similar ice phenology as the Max simulation, whereas Min and CRCM-12.6 result in the similar break-up/freeze-up dates. The break-up in CRCM-12.6 and Min simulations are on March 23, one day earlier than Max and Avg simulations and freeze-up occurs on January 24, two days after Max and Avg simulations. CRCM-12.6 and Min simulations reproduce 1.28 and 1.27 cm thinner ice than Avg simulation in 2008, respectively. The darkest water (Max) reproduces 0.21 cm thicker ice in 2008 compared to the Avg simulation. The ice sheet forms later in clear waters (CRCM-12.6 and Min) and disappears earlier compared to dark waters (Max and Avg), resulting in a shorter ice cover duration (3 days) and hence thinner ice in clear water simulations.

Lake morphological properties determine ice cover as well as climatic factors. Among morphological aspects, lake depth is the most important factor that can impact the ice cover by influencing the amount of heat storage in the water and hence the time needed for the lake to cool and ultimately freeze (Brown and Duguay, 2010). For a given depth and climatic condition, however, the amount of heat storage is determined by water clarity. Dark waters store more heat in a shallower layer. Therefore, the heat can be transferred faster to the atmosphere through the lake surface, resulting in an earlier freeze-up as mentioned in Heiskanen et al (2015) that freeze-up occurs earlier in darker waters. However, as shown by simulations with 12.6 m, ice phenology in NDBC station is minimally affected by K_d value in FLake. For a larger depth or in a different model, the impact of K_d values in ice onset should be investigated.

3.3 Spatial and Temporal Variations in K_d

As it was described in the previous section, variations in water clarity plays an important role in defining lake heat budget and thermal stratification and thus is a significant parameter for processes in the air-water interface. However, the long term spatial and temporal trends of water clarity cannot be achieved through discontinuous conventional point-wise in situ sampling. These observations can be provided from satellite measurements. This section demonstrates the strength of satellite observations to detect the spatial and temporal variations of K_d in Lake Erie. Spatial variations of K_d derived from the CC algorithm are shown in Fig. 10 for a selected day (3 September 2011). This particular day of 2011 is selected as the lake experienced its largest algal bloom in its recorded history in that year, before the new recent record of 2015 (Michalak et al., 2013; NOAA, 2015).

The bloom was expanding from the western basin into the central basin. Algal bloom is one of the factors affecting the water clarity of Lake Erie (NOAA, 2015). Other parameters include the concentrations of suspended and dissolved matters in the lake. The western basin is the shallowest region of the lake; and therefore is the most vulnerable to sediment re-suspension that also results in reducing water clarity. The map shows that Lake Erie experienced different levels of clarity in various locations with an average K_d value of $0.90\pm0.80~\text{m}^{-1}$ over the entire lake on this particular day. The NDBC station is also shown on the satellite-derived map as a reference (with $K_d = 0.87~\text{m}^{-1}$ on 3 September 2011).

Since fully cloud-free MERIS satellite images for consecutive months were only available in 2010, four months (May-August 2010) are selected to illustrate variations in K_d on a monthly-basis for one selected year (Fig. 11). The spatial average of K_d over the full lake for the specific days in May, June, July, and August is $0.82\pm0.85~\text{m}^{-1}$, $0.72\pm1.10~\text{m}^{-1}$, $0.73\pm1.20~\text{m}^{-1}$, $0.78\pm0.55~\text{m}^{-1}$, respectively. The western basin is always experiencing the lowest levels of water clarity in comparison to other regions of the lake, with a maximum K_d in May. This can be the result of a spring algal bloom, and also wind-driven re-suspension of sediments. K_d at the NDBC station for these selected days varies between $0.68~\text{m}^{-1}$, $0.62~\text{m}^{-1}$, $0.66~\text{m}^{-1}$, and $0.85~\text{m}^{-1}$ from May to August 2010, respectively.

Two MERIS images with full coverage of Lake Erie were only available in the month of May for two selected consecutive years (2008 and 2009). Hence, the MERIS images of May 2008 and May 2009 were selected to show variations in K_d between the two years. Although the images are for the same month of the year, K_d still varies across the lake (Fig. 12). In the selected day of May 2008, a spatial average value of $0.77\pm0.49~\text{m}^{-1}$ is estimated for the entire lake, while on 17 May 2009 the spatial average value is $0.90\pm0.93~\text{m}^{-1}$. Comparing the estimated maps for the two years suggests that the spring bloom in 2009 was stronger than the one in 2008 for the western basin. However, algal bloom in all basins of Lake Erie for the complete year of 2008 was recorded as the third largest that the lake experienced before the occurrence of the breaking record blooms in 2011 and 2015 (Michalak et al., 2013; NOAA, 2015). K_d value estimated for the NDBC station is 0.69 and 0.62 m⁻¹ in 29 May 2008 and 17 May 2009, respectively.

4 Summary and Conclusion

Spatial and temporal variations of K_d in Lake Erie were derived from the globally available satellite-based CC product during open water seasons 2002-2012. The CC product was evaluated against SDD in situ measurements. CC-derived K_d values, modelled incoming radiation flux data, in addition to complementary meteorological observations during the study period, were used to force the 1-D FLake model. The model was run for a selected site (NDBC buoy station) on Lake Erie, a large shallow temperate freshwater lake.

FLake was run with the range of clarity values acquired from satellite observations. Results were compared to a previous study which assumed a constant K_d value due to the lack of data. Results clearly showed that applying satellite-derived K_d values improves FLake model simulations using a derived yearly average value as well as monthly averaged values of K_d . Although K_d varies in time, a time-invariant (constant) annual value is sufficient for obtaining reliable estimates of lake surface water

temperature (LSWT) with FLake for Lake Erie NDBC station. It was also shown that the model is very sensitive to variations in K_d when the value is less than 0.5 m⁻¹. This finding is in agreement with the study of Rinke et al. (2010) and the recent study of Heiskanen et al. (2015) who determined that the impact of seasonal variations of K_d on the simulated thermal structure is small, for a lake with K_d values larger than 0.5 m⁻¹. The studies suggest that the response of 1-D lake models to K_d variations is nonlinear. The models are much more sensitive if the water is estimated to be too clear. Results of our study showed that the sensitivity to K_d variations was more pronounced in simulation results for mean water column temperature (MWCT), lake bottom water temperature (LBWT), and mixed layer depth (MLD) compared to LSWT.

Results of this study have important implications for understanding the thermal regime of lakes and show that the transparency of lakes can impact physical processes by influencing changes in seasonal mixing regime. Integrating lake specific K_d values can improve the performance of 1-D lake models. Although field measurements of K_d are not widely available, this study demonstrates the strength of satellite observations and introduces them as a reliable data source to provide lake models with global estimates of K_d with high spatial and temporal resolutions. However, the weakness of this method is that the availability of satellite-derived K_d product can be limited due to cloud coverage or satellite overpass. Also, the in situ measurements are still required for validating satellite observations, because the in situ data collection remains the most accurate solution for water clarity measurement. The accuracy of the satellite-derived K_d product has to be verified for the water body of interest, especially for the ones with complex optical properties. After validation, the on-demand globally available CC product can be simply used for the water body of interest, as a source to fill the gaps in K_d in situ observations, and improve the performance of parameterization schemes and, as a result, further improve the NWP and climate models. Although MERIS is no longer active, the Ocean and Land Colour Instrument (OLCI) to be operated on the ESA Sentinel-3 satellite (launched on February 16, 2016) will provide continuity of MERIS-like data. OLCI has MERIS heritages and improves upon it with an additional six spectral bands. Therefore, investigation of the Sentinel-3 potential to provide lake modelling community with the water clarity information is the next step of the current study. Also, the possible improvement in Flake output, when forcing the model with air humidity data collected directly at the station, can be examined in the future studies.

Author Contribution

The presented research is the direct result of a collaboration with the listed co-authors. All materials in composition of the research article is the sole production of the primary investigator listed as first author. Dr. Claude R. Duguay and Dr. Homa Kheyrollah Pour supported this research through comments and advice related to the FLake model. The manuscripts were edited for content and composition by the co-authors.

Acknowledgment

The authors would like to thank Dr. Caren Binding (Environment and Climate Change Canada) for providing the optical in situ data of Lake Erie, Dr. Ram Yerubandi (Environment and Climate Change Canada) for providing the meteorological station data for Lake Erie, and Dr. Andrey Martynov for providing advice related to running the FLake model. Financial assistance was provided through a Discovery Grant from the Natural Sciences and Engineering Research Council of Canada (NSERC) to Claude Duguay.

References

- Arst, H., Erm, A., Herlevi, A., Kutser, T., Leppäranta, M., Reinart, A. and Virta, J.: Optical properties of boreal lake waters in Finland and Estonia, Boreal Environ Res, 13, 133–158, 2008.
- Attila, J., Koponen, S., Kallio, K., Lindfors, A., Kaitala, S. and Ylostalo, P.: MERIS Case II water processor comparison on coastal sites of the northern Baltic Sea, Remote Sens Environ, 128, 138–149, 2013.
 - Binding, C. E. and Jerome, J.: Trends in water clarity of the lower Great Lakes from remotely sensed aquatic color, J Great Lakes Res, 33, 828–841, 2007.
- Binding, C. E., Greenberg, T. A., Watson, S. B., Rastin, S. and Gould, J.: Long term water clarity changes in North America's Great Lakes from multi-sensor satellite observations, Limnol Oceanogr, 60, 1967–1995, 2015.
- Brown, L. C. and Duguay, C. R.: The response and role of ice cover in lake-climate interactions, Prog Phys Geog, 34, 671–704, 2010.
 - De Bruijn, E. I. F., Bosveld, F. C. and Van Der Plas, E. V.: An intercomparison study of ice thickness models in the Netherlands, Tellus A, 66, 21244–21255, 2014.
- Cano, D., Monget, J. M., Albuisson, M., Guillard, H., Regas, N. and Wald, L.: A method for the determination of the global solar radiation from meteorological satellite data, Sol Energy, 37, 31–39, 1986.
 - Daher, S.: Lake Erie LaMP Status Report, 1–230, 2004.
 - Dise, J., Kankiewicz, A., Schlemmer, J., Hemker, K., Kivalov, S., Hoff, T. and Perez, R.: Operational improvements in the performance of the SUNY satellite-to-solar irradiance model using satellite infrared channels, Conference Record of the IEEE
- 25 Photovoltaic Specialists Conference, 960–963, 2013.
 - Duguay, C. R., Flato, G. M., Jeffries, M. O., Ménard, P., Morris, K. and Rouse, W. R.: Ice-cover variability on shallow lakes at high latitudes: Model simulations and observations, Hydrol Process, 17, 3465–3483, 2003.
 - Eerola, K., Rontu, L., Kourzeneva, E. and Shcherbak, E.: A study on effects of lake temperature and ice cover in HIRLAM, Boreal Environ Res, 15, 130–142, 2010.
- Gueymard, C., Perez, R., Schlemmer, J., Hemker, K., Kivalov, S. and Kankiewicz, A.: Satellite-to-Irradiance Modeling A New Version of the SUNY Model, 42nd IEEE PV Specialists Conf, (JUNE), 2015.

- Heiskanen, J. J., Mammarella, I., Ojala, A., Stepanenko, V., Erkkilä, K.-M., Miettinen, H., Sandström, H., Eugster, W., Leppäranta, M., Järvinen, H., Vesala, T. and Nordbo, A.: Effects of water clarity on lake stratification and lake-atmosphere heat exchange, J Geophys Res-Atmos, 120, 7412–7428, 2015.
- Hinzman, L. D., Goering, D. J. and Kane, D. L.: A distributed thermal model for calculating soil temperature profiles and depth of thaw in permafrost regions, J Geophys Res, 103, 28975–28991, 1998.
 - Kheyrollah Pour, H., Duguay, C. R., Martynov, A. and Brown, L. C.: Simulation of surface temperature and ice cover of large northern lakes with 1-D models: A comparison with MODIS satellite data and in situ measurements, Tellus A, 64, 17614–17633, 2012.
- Kheyrollah Pour, H., Duguay, C., Solberg, R. and Rudjord, Ø.: Impact of satellite-based lake surface observations on the initial state of HIRLAM. Part I: evaluation of remotely-sensed lake surface water temperature observations, Tellus A, 66, 21534–21546, 2014a.
 - Kheyrollah Pour, H., Rontu, L. and Duguay, C.: Impact of satellite-based lake surface observations on the initial state of HIRLAM. Part II: Analysis of lake surface temperature and ice cover, Tellus A, 66, 21395–21413, 2014b.
 - Kleissl, J., Perez, R., Cebecauer, T. and Šúri, M.: Solar Energy Forecasting and Resource Assessment, Elsevier, 2013.
- 15 Koenings, J. P. and Edmundson, J. a.: Secchi disk and photometer estimates of light regimes in Alaskan lakes: Effects of yellow color and turbidity, Limnol Oceanogr, 36, 91–105, 1991.
 - Kourzeneva, E.: External data for lake parameterization in Numerical Weather Prediction and climate modeling, Boreal Environ Res, 15, 165–177, 2010.
- Kourzeneva, E., Martin, E., Batrak, Y. and Moigne, P. Le: Climate data for parameterisation of lakes in Numerical Weather Prediction models, Tellus A, 64, 17226–17243, 2012.
 - Kourzeneva, E., Asensio, H., Martin, E. and Faroux, S.: Global gridded dataset of lake coverage and lake depth for use in numerical weather prediction and climate modelling, Tellus A, 64, 15640–15654, 2012.
 - Martynov, A., Sushama, L. and Laprise, R.: Simulation of temperate freezing lakes by one-dimensional lake models: Performance assessment for interactive coupling with regional climate models, Boreal Environ Res, 15, 143–164, 2010.
- Martynov, A., Sushama, L., Laprise, R., Winger, K. and Dugas, B.: Interactive lakes in the Canadian Regional Climate Model, version 5: The role of lakes in the regional climate of North America, Tellus A, 64, 16226–16248, 2012.
 - Maykut, G. A. and Church, P. E.: Radiation Climate of Barrow Alaska, 1962–66, J Appl Meteor, 12, 620–628, 1973.
 - Michalak, A. M., Anderson, E. J., Beletsky, D., Boland, S., Bosch, N. S., Bridgeman, T. B., Chaffin, J. D., Cho, K., Confesor, R., Daloglu, I., DePinto, J. V., Evans, M. A., Fahnenstiel, G. L., He, L., Ho, J. C., Jenkins, L., Johengen, T. H., Kuo, K. C.,
- LaPorte, E., Liu, X., McWilliams, M. R., Moore, M. R., Posselt, D. J., Richards, R. P., Scavia, D., Steiner, A. L., Verhamme, E., Wright, D. M. and Zagorski, M. A.: Record-setting algal bloom in Lake Erie caused by agricultural and meteorological trends consistent with expected future conditions, Proceedings of the National Academy of Sciences, 110, 6448–6452, 2013.
 - Mironov, D.: Parameterization of Lakes in Numerical Weather Prediction. Description of a Lake Model, Reports COSMO, 47, 2008.

- Mironov, D., Heise, E., Kourzeneva, E., Ritter, B., Schneider, N.and Terzhevik, A.: Implementation of the lake parameterisation scheme FLake into the numerical weather prediction model COSMO, Boreal Environ Res, 15, 218–230, 2010.
- Mironov, D., Ritter, B., Schulz, J.-P., Buchhold, M., Lange, M. and Machulskaya, E.: Parameterisation of sea and lake ice in numerical weather prediction models of the German Weather Service, Tellus A, 64, 17330–17346, 2012.
 - Moore, T. S., Dowell, M. D., Bradt, S. and Ruiz-Verdu, A.: An optical water type framework for selecting and blending retrievals from bio-optical algorithms in lakes and coastal waters, Remote Sens Environ, 143, 97–111, 2014.
 - NOAA, National Centre for Coastal Ocean Science and Great Lakes Environmental Research Laboratory: Experimental Lake Erie Harmful Algal Bloom Bulletin, 2015.
- Nottrott, A. and Kleissl, J.: Validation of the NSRDB–SUNY global horizontal irradiance in California, Sol Energy, 84, 1816–1827, 2010.
 - Olmanson, L., Brezonik, P. and Bauer, M.: hyperspectral remote sensing to assess spatial distribution of water quality characteristics in large rivers: The Mississippi River and its tributaries in Minnesota, Remote Sens Environ, 130, 254–265, 2013.
- 15 Perez, R., Ineichen, P., Moore, K., Kmiecik, M., Chain, C., George, R. and Vignola, F.: A new operational model for satellite-derived irradiances: Description and validation, Sol Energy, 73, 307–317, 2002.
 - Perez, R., Kivalov, S., Schlemmer, J., Hemker, K. J. and Zelenka, A.: Improving the performance of satellite-to-irradiance models using the satellite's infrared sensors, American Solar Energy Society Annual Conference, 2010.
 - Persson, I. and Jones, I.: The effect of water colour on lake hydrodynamics: A modelling study, Freshwater Biol, 53, 2345-2355, 2008.
 - Poole, H. H. and Atkins, W. R. G.: Photo-electric measurements of submarine illumination throughout the year, Mar Biol, 16, 297-394, 1929.
 - Potes, M., Costa, M. J. and Salgado, R.: Satellite remote sensing of water turbidity in Alqueva reservoir and implications on lake modelling, Hydrol Earth Syst Sc, 16, 1623–1633, 2012.
- 25 Rinke, K., Yeates, P. and Rothhaupt, K. O.: A simulation study of the feedback of phytoplankton on thermal structure via light extinction, Freshwater Biol, 55, 1674–1693, 2010.
 - Ruescas, A., Brockmann, C., Stelzer, K., Tilstone, G. H. and Beltrán-Abaunza, J. M.: DUE Coastcolour Final Report, version 1, 2014.
- Samuelsson, P., Kourzeneva, E. and Mironov, D.: The impact of lakes on the European climate as simulated by a regional climate model, Boreal Environ Res, 15, 113–129, 2010.
 - Thiery, W., Martynov, A., Darchambeau, F., Descy, J. P., Plisnier, P. D., Sushama, L. and Van Lipzig, N. P. M.: Understanding the performance of the FLake model over two African Great Lakes, Geosci Model Dev, 7, 317–337, 2014.
 - Vignola, F., Harlan, P., Perez, R. and Kmiecik, M.: Analysis of satellite derived beam and global solar radiation data, Sol Energy, 81, 768–772, 2007.

- Wilcox, S.: National Solar Radiation Database 1991 2010 Update: User's Manual, 2012.
- Willmott, C. J.: On the validation of models, Phys Geogr, 2, 184–194, 1981.

20

25

- Willmott, C. J. and Wicks, D. E.: An Empirical Method for the Spatial Interpolation of Monthly Precipitation within California, Phys Geogr, 1, 59–73, 1980.
- Wu, G., Leeuw, J. De and Liu, Y.: Understanding Seasonal Water Clarity Dynamics of Lake Dahuchi from In Situ and Remote Sensing Data, Water Resour Manag, 23, 1849–1861, 2008.
 - Zelenka, A., Perez, R., Seals, R. and Renné, D.: Effective accuracy of satellite-derived hourly irradiances, Theor Appl Climatol, 62, 199–207, 1999.
- Zhao, D., Cai, Y., Jiang, H., Xu, D., Zhang, W. and An, S.: Estimation of water clarity in Taihu Lake and surrounding rivers using Landsat imagery, Adv Water Resour, 34, 165–173, 2011.

Table 1 Flags of excluded pixels

Level 1	Level 1P	Level 2
Glint_risk	Land	AOT560_OOR (Aerosol optical thickness at 550 nm out of the training range)
Suspect	Cloud	TOA_OOR (Top of atmosphere reflectance in band 13 out of the training range)
Land_ocean	Cloud_ambigious	TOSA_OOR (Top of standard atmosphere reflectance in band 13 out of the training
		range)
Bright	Cloud_buffer	Solzen (Large solar zenith angle)
Coastline	Cloud_shadow	NN_WLR_OOR (Water leaving reflectance out of training range)
Invalid	Snow_ice	NN_CONC_OOR (Water constituents out of training range)
	MixedPixel	NN_OOTR (Spectrum out of training range)
		C2R_WHITECAPS (Risk of white caps)

Table 2 CC-derived average values of Kd for each month (2005-2007). The values correspond to the time of year when water LSWT observations, as well as the CC derived Kd values, are available.

Year	Apr.	May	June	July	Aug.	Sep.	Oct.	Nov.	Avg.
2005		0.69	0.62	0.63	0.79	1.07	0.92	0.97	0.81
2006	0.82	0.70	0.62	0.65	0.77				0.71
2007	0.86	0.72	0.64	0.65	0.76				0.73

Table 3 Simulated LSWT compared to in situ observations (2005 – 2007). Period corresponds to the time of year when LSWT and K_d values were available.

Period	K _d	RMSE	MBE	I_a
	Avg2005	1.69	-0.86	0.87
2005	Merged	1.76	-0.95	0.86
May-Nov	CRCM-12.6	1.88	-1.52	0.85
	CRCM-20	2.12	-1.54	0.83
	Avg2006	1.40	0.59	0.89
2006	Merged	1.42	0.54	0.89
Apr-Aug	CRCM-12.6	1.50	-0.98	0.89
	CRCM-20	1.47	-1.09	0.89
	Avg2007	1.37	0.62	0.90
2007	Merged	1.35	0.57	0.91
Apr-Aug	CRCM-12.6	1.78	-1.08	0.86
	CRCM-20	1.80	-1.35	0.87




Fig. 1 Maps showing Lake Erie in Laurentian Great Lakes and the location of stations where different parameters were measured.




Fig. 2 Variations of CC-derived K_d for the selected location during the study period (2003-2012).






Fig. 3 Relation between satellite-derived K_{d} and in situ SDD matchups.








Fig. 4 LSWT simulation results for 2005 - 2007; from: CRCM-12.6, CRCM-20, CC-derived average for K_d during selected month of each year (0.81, 0.71, and 0.73 m⁻¹; respectively), and the merged simulations based on each month average K_d . The corresponding observations for LSWT, and CC-derived K_d values are also plotted. Missing lines mean no data.




Fig. 5 Modelled (y-axis) versus observed (x-axis) LSWT for yearly average, merged, CRCM-12.6, and CRCM-20 simulations during the ice-free seasons in 2005-2007. A linear fit (dashed line) and its coefficients are shown on the plot. The statistics related to the regression of parameters, and a 1:1 relationship (solid line) are also shown. The average LSWT values of Obs, Avg, Merged CRCM-12.6, and CRCM-20 simulations are 18.64 °C, 18.56 °C, 18.50 °C, 17.38 °C, 17.27 °C.




Fig. 6 LSWT (a), MWCT (b), and LBWT (c) simulation results in 2008 for CRCM-12.6 (K_d =0.2 m⁻¹) simulation and the lowest (Min, K_d =0.58 m⁻¹), average (Avg, K_d =0.90 m⁻¹), and the highest (Max, K_d =3.54 m⁻¹) K_d values are shown.




Fig. 7 Isotherms in open water period 2008 for CRCM-12.6 (K_d =0.2 m⁻¹) simulation and the lowest (Min, K_d =0.58 m⁻¹), average (Avg, K_d =0.90 m⁻¹), and the highest (Max, K_d =3.54 m⁻¹) K_d values are shown.




Fig. 8 MLD simulation results in 2008 for CRCM-12.6 (K_d =0.2 m⁻¹) simulation and the lowest (Min, K_d =0.58 m⁻¹), average (Avg, K_d =0.90 m⁻¹), and the highest (Max, K_d =3.54 m⁻¹) K_d values are shown.




Fig. 9 Ice thickness during 2008 for CRCM-12.6 (K_d =0.2 m⁻¹) simulation and the lowest (Min, K_d =0.58 m⁻¹), average (Avg, K_d =0.90 m⁻¹), and the highest (Max, K_d =3.54 m⁻¹) K_d values are shown. CRCM-12.6 and Min (Avg and Max) simulations reproduce similar ice thicknesses.




Fig. 10 Spatial variation of satellite-derived K_d in Lake Erie, on 3 September 2011. Location of NDBC station is shown on the map as a solid dot.




Fig. 11 Temporal and spatial variation of satellite-derived K_d in Lake Erie for different months of a year: May- August 2010. Location of NDBC station is shown on the map as a solid dot.




Fig. 12 Temporal and spatial variation of K_d in Lake Erie during May of two consecutive years: 2008 and 2009. Location of NDBC station is shown on the map as a solid dot.