- Minimum forest cover required for sustainable water flow regulation of a watershed: a
 case study in Jambi Province, Indonesia."
- 3 Suria Tarigan¹, Kerstin Wiegand², Sunarti³, Bejo Slamet⁴
- ⁴ ¹Department of Soil Sciences and Natural Resource Management, Bogor Agricultural
- 5 University, Indonesia
- ⁶ ²Department of Ecosystem Modeling, University of Göttingen, Büsgenweg 4, 37077
- 7 Göttingen, Germany
- ³Faculty of Agriculture, University of Jambi, Jambi, Indonesia
- 9 ⁴Faculty of Agriculture, North Sumatra University, Medan, Indonesia
- 10 Correspondence to: Suria Tarigan (E-mail: <u>sdtarigan@apps.ipb.ac.id</u>)

11 Abstract

In many tropical regions, the rapid expansion of monoculture plantations has led to a sharp 12 decline in forest cover, potentially degrading the ability of watersheds to regulate water flow. 13 Therefore, regional planners need to determine the minimum proportion of forest cover that is 14 required to support adequate ecosystem services in these watersheds. However, to date, there 15 has been little research on this issue, particularly in tropical areas where monoculture 16 plantations are expanding at an alarming rate. Therefore, in this study, we investigated the 17 influence of forest cover and oil palm (*Elaeis guineensis*) and rubber (*Hevea brasiliensis*) 18 19 plantations on the partitioning of rainfall into direct runoff and subsurface flow in a humid, tropical watershed in Jambi Province, Indonesia. To do this, we simulated a streamflow with 20 a calibrated Soil and Water Assessment Tool (SWAT) model and observed several 21 22 watersheds to derive the direct runoff coefficient (C) and baseflow index (BFI). The model had a satisfactory performance, with Nash-Sutcliffe efficiency values of 0.80-0.88 23 (calibration) and 0.80-0.85 (validation), and percent bias values of -2.9 to 1.2 (calibration) 24 and 7.0–11.9 (validation). We found that the percentage of forest cover in a watershed was 25 significantly negatively correlated with C and significantly positively correlated with BFI, 26 whereas the rubber and oil palm plantation cover showed the opposite pattern. Our findings 27 also suggested that at least 30 % of the forest cover was required in the study area for 28 sustainable ecosystem services. This study provides new adjusted crop parameter values for 29

monoculture plantations, particularly those that control surface runoff and baseflow
processes, and also describes the quantitative association between forest cover and flow
indicators in a watershed, which will help regional planners in determining the minimum
proportion of forest and the maximum proportion of plantation to ensure that a watershed can
provide adequate ecosystem services.

35 1 Introduction

In recent years, monoculture plantations has rapidly expanded in Southeast Asia, and the 36 areas under oil palm (Elaeis guineensis) and rubber (Hevea brasiliensis) plantations are 37 expected to further increase (Fox et al., 2012; Van der Laan et al., 2016). In Indonesia, which 38 is currently the largest palm oil producer worldwide, the oil palm plantation area increased 39 40 from 0.7 million ha in 1990 to 11 million ha in 2015 (Ditjenbun, 2015; Tarigan et al., 2016), and a further 1-28 million ha are projected to be required for palm oil production in 2020-41 2050 (Wicke et al., 2011; Afrivanti et al., 2016). This rapid expansion of oil palm plantations 42 has been partly triggered by an increased demand for biofuel production (Mukherjee and 43 Sovacoo, 2014). In addition, rubber plantations, which are also prevalent in Southeast Asia 44 45 (Ziegler et al., 2009), currently cover 3.5 million ha of land in Indonesia (Ditjenbun, 2015).

Although oil palm is of economic value to farmers and the local regions in which it is grown, it has received environmental and social criticism, often being held responsible for deforestation (Wicke et al., 2011; Vijay et al., 2016; Gatto et al., 2017), biodiversity loss

(Fitzherbert et al., 2008; Koh and Wilcove, 2008; Wilcove and Koh, 2010; Carlson et al., 49 2012; Krashevska et al., 2015), decreased soil carbon stocks (Guillaume et al., 2015, 2016; 50 Pransiska et al., 2016), and increased greenhouse gas emissions (Allen et al., 2015; Hassler et 51 al., 2017). Similarly, rubber plantations have environmental impacts such as reducing the soil 52 infiltration capacity, accelerating soil erosion, increasing stream sediment loads (Ziegler et 53 al., 2009; Tarigan et al., 2016), and decreasing soil carbon stocks (Ziegler et al., 2011). 54 Furthermore, the conversion of tropical rainforest into oil palm and rubber plantations affects 55 the local hydrological cycle by increasing transpiration (Ziegler et al., 2009; Sterling et al., 56 57 2012; Röll et al., 2015; Hardanto et al., 2017), increasing evapotranspiration (ET) (Meijide et al., 2017), decreasing infiltration (Banabas et al., 2008; Tarigan et al., 2016), increasing the 58 flooding frequency (Tarigan, 2016), and decreasing low flow levels (Yusop et al., 2007; 59 60 Adnan and Atkinson, 2011; Comte et al., 2012; Merten et al., 2016). These climatic impacts that occur owing to land use change are expected to be stronger under maritime conditions, 61 such as those in Indonesia, than under continental conditions because 40 % of the global 62 tropical latent heating of the upper troposphere occurs over the maritime continent (Van der 63 Molen et al., 2006). 64

The forests in Jambi Province, Indonesia have been largely transformed into plantations (Drescher et al., 2016), resulting in inhabitants experiencing water shortages during the dry season and a dramatic increase in flooding frequency during the wet season (Merten et al.,

2016; Tarigan, 2016) because plantations promote higher levels of direct runoff than forested lands (Bruijnzeel, 1989, 2004; Tarigan et al., 2016; Dislich et al., 2017). However, this negative impact of plantation expansion could be minimized by maintaining an adequate proportion of forested land as a watershed, which raises the question, what is the minimum proportion of forest cover that is required in a watershed to support adequate water flow regulation?

The water flow regulation function of watersheds represents their ability to retain rain 74 water and is one of the most important soil hydrological processes in tropical regions where 75 76 rainfall is highly seasonal (Lele, 2009). Functional water flow regulation by a watershed reduces flood peaks by moderating direct runoffs (Le Maitre et al., 2014; Ellison et. al, 2017) 77 via soil water infiltration through the soil surface and percolation through the soil profile. 78 79 This vertical movement of water through the soil determines how much water flows as direct runoffs and how much reaches the water table where it sustains as baseflow or groundwater 80 (Hewlett and Hibbert, 1967; Bruijnzeel, 1990; Le Maitre et al., 2014; Tarigan et al., 2016). 81 82 Forest vegetation provides organic matter and habitat for soil organisms, thereby facilitating higher levels of infiltration than other land uses (Hewlett and Hibbert, 1967). 83

A number of empirically based and process-based approaches can be used for assessing the impacts of expanding rubber and oil palm plantations on hydrological characteristics in the Southeast Asia region. Empirically based approaches use long-term historical data to

correlate land use changes with corresponding streamflow data (Adnan and Atkinson, 2011; 87 Rientjes et al., 2011; Mwangi et al., 2016) or paired catchment studies (Bosch and Hewlett, 88 1982; Brown et al., 2005), whereas process-based approaches use physically based 89 hydrological models in which the impact of land use changes is determined by varying the 90 land use/cover settings (Khoi and Suetsugi, 2014; Guo et al., 2016; Zhang et al., 2016; 91 Marhaento et al., 2017; Wangpimool et al., 2017). Process-based approaches have the 92 drawback of requiring more data to be input and having high uncertainty in parameter 93 estimation (Xu et al., 2014; Zhang et al., 2016). However, there is currently an absence of 94 95 long-term historical data for Jambi Province, precluding the use of an empirically based approach. 96

Distributed hydrological models are useful for understanding the effects of land use 97 98 changes on watershed flow regulation. Once such model is the Soil and Water Assessment Tool (SWAT) ecohydrological model (2012), which quantifies the water balance of a 99 watershed on a daily basis (Neitsch et al., 2011) and has been recommended for evaluating 100 the hydrological ecosystem services of a watershed (Vigerstol and Aukema, 2011). The 101 SWAT model approach is one of the most widely used and scientifically accepted tools for 102 assessing water management in a watershed (Gassman et al., 2007). Consequently, its 103 popularity has also increased in Southeast Asia; Marhaento et al. (2017) recently used the 104 SWAT model to analyze the impact of forest cover and agriculture land use on the runoff 105

coefficient (C) and baseflow index (BFI) on Java Island, Indonesia and found that a decrease 106 in forest cover from 48.7 % to 16.9 % and an increase in agriculture area from 39.2 % to 45.4 107 % increased C from 35.7 % to 44.6 % and decreased BFI from 40 % to 31.1 %. Meanwhile, 108 Wangpimool et al. (2017) found that the expansion of rubber plantations in Thailand between 109 2002 and 2009 led to an annual reduction of approximately 3 % in the average water yield of 110 the basin, whereas Babel et al. (2011) found that the expansion of oil palm plantations in 111 Thailand increased nitrate loading (1.3 %-51.7 %) in the surface water based on SWAT 112 simulations. Tarigan et al. (2016) also used the SWAT model to simulate the impact of soil 113 114 and water conservation practices on low flow levels in oil palm-dominated watersheds in This study aimed to quantify the minimum proportion of forest Jambi Province, Indonesia. 115 cover that is required to allow a watershed to provide adequate ecosystem services. We 116 117 selected Jambi Province as our study area because of the rapid expansion of oil palm and rubber plantations in that area. The study findings provide new adjusted values for crop 118 parameters of monoculture plantations, particularly those that control surface runoff and 119 baseflow processes, and describe the quantitative association between forest cover and flow 120 indicators in a watershed, which will help regional planners in determining the minimum 121 proportion of forest that needs to be conserved to ensure that a watershed can provide 122 adequate ecosystem services. 123

124

125 **2** Methods

126 2.1 Study area

The study area was located in Jambi Province, Sumatra (1° 54' 31.4" S, 103° 16' 7.9" E, Fig. 127 1). There has been a rapid expansion of plantations in this area, particularly oil palm and 128 rubber (Drescher et al., 2016). The area has a tropical humid climate, with an average 129 temperature of 27 °C and an average rainfall of 2700 mm vear⁻¹. The rainy season occurs 130 from October to March. The area under oil palm plantation in the study area (Jambi Province) 131 increased from 150 000 ha in 1996 to 600 000 ha in 2011, representing an almost 400 % 132 increase (Setiadi et al., 2011), whereas the area under rubber plantation increased from 500 133 000 to 650 000 ha over the same period (Ditjenbun, 2015). In 2013, only 30 % of Jambi 134 Province was covered with rainforest (mainly located in mountainous regions), with 55 % of 135 the land having been converted into agricultural land, of which 10 % was degraded/fallow 136 and will potentially be converted into monoculture plantations (Drescher et al., 2016). 137

The study area consists of two macro watersheds for the simulation of the C and BFI values with the SWAT model, namely Batanghari Hulu (BH; Fig. 1a) and Merangin Tembesi (MT; Fig. 1b) watersheds, which cover areas of 18 415 km² and 13 452 km², respectively. The dominant land uses in both watersheds are forest (BH, 50 %; MT, 30 %) and plantation (BH, 18 %; MT, 48 %). Tropodult and Dystropept dominate soils in the study area with medium to heavy texture.

To ensure that the C and BFI values obtained from the macro watershed simulations (particularly those sub-watersheds that were dominated by oil palm or rubber) reflected the real observed values in the field, we carried out the direct C measurements in two small watersheds in the study area (Fig. 1c). These small watersheds were covered with 90 % oil palm and 80 % rubber plantations, respectively.



149

150 Figure 1. Locations of the (a, b) macro and (c) small watershed experiments in Jambi

151 Province, Sumatra, Indonesia.

Oil palm and rubber are perennial crops that have a life cycle of 25 years. Both crops are 152 planted in rows at planting distances of 8 and 4 m, respectively. In oil palm plantations, there 153 are two types of paths between the planting rows: the harvest path, which is used to transport 154 freshly harvested fruit bunches, and the so-called death path, which is used for piling pruned 155 leaf fronds, which occupy approximately 2 m or one-quarter of this path. Both oil palm and 156 rubber require very intensive harvesting activities, which occur twice per month for oil palm 157 and almost daily for rubber; thus, soils along the harvest path and part of the death path are 158 very compacted. The soils under oil palm and rubber plantations remain unploughed for the 159 160 entire growing period. Weeds in the oil palm plantations are regularly eradicated using herbicides or mechanical equipment. Intensive inorganic fertilization (1000 kg ha^{-1} year⁻¹) 161 also occurs, contributing to the degradation of the soil structure and fauna 162

163 **2.2 SWAT model**

The SWAT model is a continuous long-term yield model that was developed to simulate the impact of different land cover/management practices on streamflow in complex watersheds with varying soil, land use, and management conditions over long time periods. The major model components include weather, hydrology, soil temperature, soil properties, plant growth, nutrients, and land management (Neitsch et al., 2011; Arnold et al., 2012).

During the modeling process, the watershed is subdivided into several sub-watersheds, which are themselves further partitioned into hydrological response units (HRUs) that are

defined by their topography, soil, and land use characteristics. The hydrological outputs of HRUs are calculated using the water balance equation and include total streamflow, surface flow and baseflow. These output components can then be used to calculate indicators of the water flow regulation functions of a watershed, namely C, which is the ratio of direct runoff to rainfall, and BFI, which is the proportion of baseflow in the streamflow.

Because the SWAT model was designed for temperate regions, adapting crop parameter inputs for use in tropical regions is necessary (Van Griensven et al., 2014). To avoid incorrect parameterization of sensitive values, we carried out field measurements for interception, infiltration, and surface runoff to adapt the parameter values, particularly those that control surface runoff and baseflow processes. We then performed SWAT model simulation in two study watersheds and conducted small watershed experiments to compare the observed C values with those obtained from simulations.

183 **2.2.1 Model setup**

Delineation of watersheds and their sub-watersheds in our study area was automatically performed by the SWAT model and was based on a digital elevation model (DEM) with a 30 m resolution. During this automatic delineation, we pre-defined 50 000 ha as a threshold for the minimum sub-watershed area, based on which the BH and MT watersheds were subdivided into 25 and 23 sub-watersheds, respectively.

189 Crop parameters

190 Oil palm plantations exhibit specific characteristics, particularly with respect to rainfall

191 partitioning. These characteristics include high interception, high ET, low soil infiltration,

192 high proportion of surface runoff, and absence of leaf litter, of which the first four can

193 potentially reduce baseflow. Therefore, to consider these specific characteristics, we

194 conducted field measurements and adjusted several crop parameters that are related to flow

195 components, including canopy storage (CANMX), plant uptake compensation factor (EPCO),

196 hydrologic soil group (HSG) and Soil Conservation Service (SCS) curve number (CN).

197 a) Interception

CANMX is the maximum amount of water that can be stored in the canopy and trunks of 198 fully developed trees. Thus, an increase in this parameter reflects a reduction in the amount of 199 rainfall that reaches the ground. In oil palms, rainfall is intercepted not only by leaves and 200 branches but also by water reservoirs in leaf axils along the trunk. Therefore, we measured 201 the water storage capacity of leaf axils along the trunks of four 10–12 years old oil palm trees 202 with 10 replications per tree. We found that the leaf axils along the trunk can store up to 20 L 203 or 8.4 mm of water (Table 1), which matches previous reports that the leaf axils along oil 204 palm trunks have a high water storage capacity (Merten et al., 2016; Meijide et al., 2017). 205

Doplicato	/	Vater stor	age (mm))
Replicate	Tree 1	Tree 2	Tree 3	Tree 4
1	14.2	10.8	4.4	6.2
2	10.6	10.2	4.2	5.9
3	9.4	10.5	5.9	7.9
4	8.1	10.4	5.4	7.4
5	8.8	11.5	3.8	9.8
6	9.4	10.9	6.0	8.0
7	9.3	10.6	5.9	7.5
8	10.1	11.0	5.2	7.3
9	8.9	11.2	4.7	10.5
10	9.5	11.3	4.9	7.2
	Avera	ge = 8.4 r	nm	

Table 1. Water storage capacity of the leaf axils along the trunks of oil palm trees

We also measured the canopy interception by oil palm, rubber, agroforest, and forest 207 canopies between November 2012 and February 2013. Rainfall interception was assessed by 208 measuring throughfall and stemflow and subtracting these from the incident rainfall. In total, 209 there were 30 rainfall events during this time, representing light-to-heavy rain. We found that 210 oil palm plantations tended to exhibit higher levels of canopy interception (Fig. 2), with our 211 estimates falling within the range of values that were previously reported for tropical forests 212 in Southeast Asia (commonly 10 %–30 %; Kumagai et al., 2005; Dietz et al., 2006). These 213 interception assessments were used to adjust the CANMX parameter of the SWAT model 214 (Table 2). 215



Figure 2. Canopy interception of rainfall under different land uses. Different letters indicate significant differences between the means (Bonferroni-corrected post hoc t-test based on ANOVA; p < 0.05).

220 b) ET

Actual ET was determined by measuring the daily depletion of soil moisture content at a distance of 2 m from the trunks of oil palm trees. Soil moisture measurements were made on consecutive no rain days over the 16-day period from 25 July, 2012 to 10 August, 2012. On an average, soil moisture decreased by 6 % (vol) over this period, which is equivalent to 72 mm or 4.5 mm day⁻¹ and is relatively high compared with the average land use in the study area. Similarly, Meijide et al. (2017) also reported a yearly oil palm ET of 1216 mm (4.7 mm day⁻¹) using Edy covariance measurements in the study area. This ET rate is similar to or



even higher than ET rates for forests in Southeast Asia (Kumagai et al., 2005), despite oil
palm having a much lower stand density and biomass per hectare. Therefore, we accordingly
adjusted EPCO, which is related to ET (Table 2).

231 c) Infiltration and surface runoff

234

One important parameter of the SWAT model that is related to surface runoff is CN (Arnold et al., 2012), which determines the proportion of rainfall that becomes surface runoff (range,

0–100, with a higher value reflecting a higher level of surface runoff). The CN value is

grouped into four HSGs (i.e., A, B, C, and D) according to the soil infiltration capacity. To 235 236 adjust the CN value, we measured soil infiltration and surface runoff in each land use type (i.e., oil palm, rubber, agroforest, and forest) using a double-ring infiltrometer and 237 multidivisor runoff collectors mounted at the lower end of each plot, respectively. The 238 infiltration rate in different land-use types increases in the following order: oil palm harvest 239 path (3 cm h^{-1}) < oil palm circle (3 cm h^{-1}) < rubber harvest path (7 cm h^{-1}) < between rubber 240 trees $(7.8 \text{ cm h}^{-1}) < \text{forest} (47 \text{ cm h}^{-1})$. The infiltration in the oil palm, rubber plantations were 241 markedly lower than those at the forest. Low infiltration rate in the oil palm is associated with 242 the soil compaction due to the intensive harvest activities. 243

For all HRUs with oil palm and rubber land uses, we selected HSG category D (Table 2) owing to its high surface runoff and low infiltration rate. We assumed that CN values of the

forest and agroforest were similar to those of the evergreen and mixed forest, respectively, inthe SWAT crop database.

248 d) Litter fall

In the oil palm plantations, we hardly found any litter outside the frond piles. Litter fall in oil palm plantations does not naturally occur, but leaves are cut during fruit harvest and piled up in a frond pile, which occupies only 12 % of the entire oil palm plantation area. Consequently, the ground surface of oil palm plantations is mostly clean without litter, leading to higher surface runoffs. There was also hardly any understory vegetation (grasses) because herbicides were routinely sprayed. The absence of the litter fall affected Manning's "n" value for overland flow (OV N).

SWAT parameter Definition Oil palm Rubber Agroforest Forest Maximum trunk storage 8.4 CANMX (mm) 0 0 0 Maximum canopy storage 4.7 2.7 4.3 5.8 HYDGRP Hydrologic soil group D D В С CN2 Curve number 45 83 83 65 $SOL_BD (g cm^{-3})$ 1.2-1.3 0.9 Soil bulk density 1.2-1.3 1 EPCO Plant uptake compensation 1 1 1 1 factor OV N Manning's "n" value for 0.07 0.14 0.4 0.5 overland flow SOL K (mm h^{-1}) Saturated hydraulic 30 470 78 400 conductivity SOL AWC ($mm mm^{-1}$) Available water capacity 0.1 0.1 0.2 0.2 BLAI $(m^2 m^{-2})$ Maximum potential leaf 3.6^a 5 2.6 5 area index

256 Table 2. Adapted crop parameter inputs for the study area

CHTMX (m)	Maximum canopy height	12	13	14	20
T_BASE	Base temperature	20	20	20	20
T_OPT	Optimal temperature	28	28	30	30

^aFan et al., 2015

258 e) Baseflow

The baseflow recession constant (ALPHA_BF) was calculated by plotting the daily streamflow hydrograph on semi-log paper and determining the average values from several individual rainfall events. Several previous studies have shown that ALPHA-BF ranges from

262 0.9 to 0.95 in Indonesia.

263 General input data

The SWAT model required additional input data to the crop parameters described above,

such as the climate, topography, soil type, and land use for each sub-watershed (Table 3).

Data type	Resolution	Description	Source ^a
Topography	30 m	DEM with a resolution of 30 m per pixel	LAPAN
Soil	1:250 000	Soil hydraulic conductivity, bulk density, available water content, and	Soil Research Institute, Ministry of
		texture were resampled in the field	Agriculture
Land use	1:100 000	Land use map with intensive ground	Regional Planning
		check	office (BAPPEDA)
Rainfall and	Daily	Rainfall and meteorological stations at	BMG office and
climate		Rantau Pandan, Siulak Deras, Muara	CRC990
		Hemat, Padang Aro, Depati Parbo,	

Table 3. Model input data sources

		Bangko Bungo, Pematang Kabau, and	
		Bungku	
Streamflow	Daily discharge data	Stations at Muara Tembesi, Air Gemuruh, Batang Tabir, Batang Pelepat, and Muara Kilis	Ministry of Public Works (BBWS)

^aLAPAN, National Aeronautics and Space Agency (*Lembaga Antarikasa dan Penerbangan Nasional*); BAPPEDA, Regional Planning Agency (*Badan Perencanaan Daerah*); BMG,
Meteorology and Geophysics Agency (*Badan Meteorologi dan Geofisika*); CRC990,
Collaborative Research Centre 990; BBWS, Catchment Regional Agency (*Balai Besar Wilayah Sungai*).

DEM with a resolution of 30 m per pixel was obtained from the National Aeronautics and 273 274 Space Agency, rainfall and climate data were sourced from the Meteorology and Geophysics Agency, and streamflow data were provided by the Ministry of Public Works. All these data 275 are freely available for research purposes on official request to the corresponding institutions. 276 The streamflow time series and rainfall records for the small catchments and the resampled 277 soil hydraulic conductivity, bulk density, available water content, and texture data have been 278 279 deposited by the first author at Bogor Agricultural University and in the EFForTS Database (https://efforts-is.uni-goettingen.de). The land use and soil map for the study area was 280 obtained from Jambi Province Regional Planning and Agricultural Plantation offices 281 282 (Ditjenbun, 2015).

283 2.2.2 Model validation and calibration

284

285 the parameters that control surface runoff and baseflow using a previously reported procedure (Moriasi et al. 2012; Van Griensven et al., 2006; Arnold et al., 2012). The sensitivity analysis 286 was performed using the SWAT Calibration and Uncertainty Procedure (SWAT-CUP) 287 package, which is an interface for auto-calibration that was specifically developed for SWAT 288 and which links any calibration/uncertainty or sensitivity program to SWAT (Abbaspour, 289 2015). 290 Following the sensitivity analysis, we calibrated the SWAT model using the Latin 291 hypercube sampling approach of the SWAT-CUP software. We first determined parameter 292 ranges based on the minimum and maximum values allowed in SWAT. We then performed 293 calibration and validation of the SWAT model by comparing the simulated monthly 294

Prior to model calibration and validation, we performed a sensitivity analysis, particularly for

streamflows with observed data at the Muara Kilis and Muara Tembesi gauging stations from

2007 to 2009 for calibration and 2012 to 2014 for validation. Moriasi et al. (2012)

297 recommended the use of three quantitative statistics for model evaluation: the Nash–Sutcliffe

efficiency (NSE), percent bias (PBIAS), and ratio of the root mean square error to the

standard deviation of measured data. In this study, we used NSE and PBIAS to evaluate the

300 model performance. NSE is a normalized statistic that determines the relative magnitude of

the residual variance ("noise") compared with the measured data variance ("information")

(Nash and Sutcliffe, 1970). PBIAS measures the average tendency of simulated data to be
larger or smaller than that of observational data (Gupta et al., 1999), with an optimum value
of zero and lower values that indicate better simulations. Positive values of PBIAS indicate
model underestimation, whereas negative values indicate model overestimation.

2.3 Simulated C and BFI values and the proportion of land use types in a watershed

The output of the validated SWAT model consisting of flow components for each sub-307 308 watershed was used to calculate indicators of the water flow regulation functions of a watershed, namely C, which is the ratio of direct runoff to rainfall, and BFI, which is the 309 310 proportion of baseflow in the streamflow. To analyze the association between the C and BFI values and the proportion of each land-use type in a watershed, we derived data vectors from 311 the BH and MT watersheds. Each of these vectors corresponded to the percentage of land use 312 types, C and BFI in each of the 25 sub-watersheds from the BH watershed and 23 sub-313 watersheds from the MT watershed (Fig. 3a and b; Table 4). 314



Figure 3. Land use types and sub-watershed number of the (a) BH and (b) MT watersheds.

317	Table 4. The percentage of land use types, C and BFI in each sub-watershed within the BH
318	and MT watersheds

Sub-	Perc	entage	of land	use typ	oes			Sub-	Perc	entage	of land	use typ	oes	C	
wat. nr.	F	AF	RP	OP	S	С	BFI	wat. nr.	F	AF	RP	OP	S	C	BFI
			BH	waters	hed			24	66	5	25	5	0	0.14	0.76
1	56	0	17	0	26	0.21	0.71	25	44	32	0	7	17	0.04	0.93
2	46	0	26	0	26	0.27	0.63				MT	waters	shed		
3	90	0	0	0	0	0.00	0.99	1	0	13	0	85	0	0.59	0.11
4	76	0	0	0	0	0.18	0.75	2	56	0	0	44	0	0.36	0.45
5	16	0	67	0	17	0.40	0.32	3	0	16	0	82	0	0.58	0.13
6	0	0	67	0	34	0.41	0.23	4	21	20	12	48	0	0.45	0.32
7	68	0	0	0	19	0.17	0.76	5	32	0	19	38	12	0.40	0.29
8	100	0	0	0	0	0.01	0.98	6	0	46	0	52	0	0.43	0.37
9	80	0	0	0	0	0.15	0.79	8	0	0	15	86	0	0.54	0.01
11	55	0	0	0	0	0.31	0.57	9	48	0	0	53	0	0.59	0.11
12	61	0	23	0	0	0.23	0.62	10	0	0	0	96	0	0.34	0.37
13	30	0	41	0	18	0.32	0.42	11	0	0	19	69	0	0.67	0.00
14	84	0	0	0	16	0.04	0.91	12	0	0	13	88	0	0.66	0.01
15	49	0	0	0	0	0.31	0.58	14	0	0	20	80	0	0.54	0.01

21

16	0	20	39	0	24	0.36	0.35	15	0	27	14	57	0	0.65	0.01
17	59	0	0	0	24	0.16	0.71	16	70	0	0	0	31	0.53	0.22
18	0	0	82	19	0	0.48	0.03	17	0	28	11	57	0	0.28	0.65
19	19	30	0	0	52	0.13	0.75	19	0	12	31	57	0	0.53	0.23
20	69	0	0	0	0	0.22	0.69	20	0	0	63	37	0	0.60	0.10
21	45	24	0	0	32	0.08	0.87	21	48	0	0	36	16	0.65	0.01
22	0	26	16	58	0	0.35	0.28	22	36	0	17	17	16	0.32	0.42
23	0	48	33	0	20	0.23	0.61	23	100	0	0	0	0	0.40	0.32

Sub-wat. nr, sub-watershed number (see Fig. 3a and b); F, forest; AF, agroforest; RP, rubber
plantation; OP, oil palm; S, shrubland.

321 2.4 Measured C values

We carried out the direct C measurements from two small watersheds (Fig. 1c) between 2013 322 and 2015 using rectangular weirs and water recorders for comparison with simulated C 323 values. The land uses in the small watersheds are similar to the proportions found in several 324 of the sub-watersheds shown in Table 4 (e.g., BH 18, MT 1, MT 8, MT 10, MT 11, MT 12, 325 MT 14, and MT 20). The direct runoff components of the hydrographs were separated using 326 the straight-line method described by Blume et al. (2007), following which C was calculated. 327 We did not calculate BFI values along with C values in the small watershed experiments 328 because BFI calculation requires hydrograph records over a longer period. 329

330 3 Results and Discussion

331 **3.1 Measured C values**

- 332 The average C value was based on nine individual rainfall events during the field experiment.
- 333 The observed C values that were measured during two small watershed experiments was 0.59

334 (Table 5). This value was comparable with the averaged simulated values of 0.60 for sub-

- watersheds with comparable proportions of land use type with those of the small watershed 335
- experiment (Table 6). 336
- Table 5. Observed C values obtained from field experiments in two small watersheds that 337 were dominated by plantation cover 338

Event	Rainfall	Rainfall v	Rainfall volume (m³)Runoff (m³)				С		
Nr.	$(\operatorname{cm} \operatorname{h}^{-1})$	Small wat. 1	Small wat. 2	Small wat. 1	Small wat. 2	Small wat.1	Small wat. 2		
1	6.0	8960	3136	4500	1320	0.50	0.42		
2	3.0	5180	1813	2625	840	0.51	0.46		
3	1.4	4095	1433	3000	810	0.73	0.57		
4	0.6	1456	509.6	1080	255	0.74	0.50		
5	10.7	14923	5223	11250	3900	0.75	0.75		
6	3.1	6006	2102	4050	1020	0.67	0.49		
7	2.3	8188	2885	6150	1584	0.75	0.55		
8	2.2	4416	1465	2400	780	0.54	0.53		
9	9.6	8916	3121	5400	1650	0.61	0.53		
Averag	e					0.65	0.53		
Total						0.59			

Table 6. Simulated C values for the sub-watersheds used in the SWAT simulation (Table 4) 339

that had similar percentages of plantation cover to the two small watersheds used in the field 340 experiments

341

Sub-watershed code	Percentage of	plantation cover	С
$(\text{see Table 4})^{a}$	Oil palm	Rubber	
BH-18	82	19	0.49
MT-1	85	0	0.59
MT-8	86	15	0.54
MT-10	96	0	0.67
MT-11	69	19	0.67
MT-12	88	13	0.54
MT-14	80	20	0.65
MT-20	37	63	0.65
Average			0.60

- ^aSub-watersheds were selected that had >80 % plantation (oil palm and rubber) cover,
- allowing a comparison to be made with the small watersheds used in the field experiment

344 **3.2 SWAT model performance**

- 345 The sensitive parameters that were included in the calibration of the SWAT model are ranked
- in Table 7. Some of these parameters play an important role in controlling the initial
- abstraction of rainfall (e.g., CANMX), rainfall partitioning into surface runoff (e.g., CN2 and
- 348 OV_N), and vertical movement of water through the soil (e.g., SOL_BD, SOL_K, and
- 349 SOL_AWC).
- Table 7. Sensitivity rank, initial and final values of the calibration parameters that were used
- in the study for the BH and MT watersheds

		Sensitivity	Initial value		
Parameter	Description	rank	range	Best-fit v	alues
			BH and MT	BH	MT
ALPHA_BF	Baseflow recession constant	1	0.0 to 1.0	0.94	0.91
	SCS runoff curve number for	2			
CN2	moisture condition II		-0.2 to 0.2 (V) ^a	0.14	0.12
GW_DELAY	Groundwater delay time (days)	3	30 to 450	62.5	57.2
CANMX	Maximum canopy storage (mm)	4	-0.2 to 1.0 (V) ^a	0.95	0.76
SOL_BD	Soil bulk density	5	-0.5 to 0.6 (V) ^a	0.46	0.47
	Water depth in a shallow aquifer	6			
GWQMN	for a return flow (mm H ₂ O)		0.0 to 2.0	0.99	0.95
SOL_K	Saturated hydraulic conductivity $(mm h^{-1})$	7	-0.8 to 0.8 (V) ^a	0.71	0.62
	Manning's "n" value for the main	8			
CH_N2	channel		0.0 to 0.3	0.05	0.15
SOL_AWC	Available water capacity of the soil (mm H ₂ O/mm soil)	9	-0.2 to 0.4 (V) ^a	0.09	0.04
OV_N	Manning's "n" value for overland	10	-0.2 to $1.0 (V)^{a}$	0.51	0.3





- Figure 4. Observed vs. simulated streamflow and 95 % uncertainty interval (95PPU; see
- Abbaspour, 2015) with P factors of 0.83 and 0.76 and R factors of 0.65 and 0.69 for the (a)
- BH and (b) MT watersheds, respectively (defined as simulations with NSE > 0.5).

362 3.3 Simulated C and BFI values and the proportion of land use types in a watershed

The proportion of a particular land use type in a sub-watershed was significantly correlated 363 with C and BFI values obtained from 48 data vectors (Table 4). C values significantly 364 decreased as the percentage of forest cover increased ($R^2 = 0.73$; p < 0.05; Fig. 5a) and 365 significantly increased as the percentage of plantation cover increased ($R^2 = 0.74$; p < 0.05; 366 Fig. 5b). Low infiltration capacity in oil palm and rubber plantations was the reason for 367 higher C values in the sub-watersheds with high proportions of the plantation land use. There 368 were no significant associations between C values and any of the other land use types such as 369 shrubland (Fig. 5c), agroforest (Fig. 5d), and dryland farming (data not shown). Some sub-370 watersheds had low C values despite having low levels of forest cover (e.g., BH 19). This can 371 be explained by the fact that BH 19 had no oil palm or rubber plantations and had 52 % of 372 shrubland, which will have helped in reducing the C value. Furthermore, some watersheds 373 had 100 % forest cover but a low BFI value (e.g., MT 23). This is the only sub-watershed in 374 the MT watershed to have a high proportion of steeper slopes (76 % of the sub-watershed), 375 which will increase C and decrease BFI. Among the 48 sub-watersheds we considered, only 376 two had these slope characteristics. 377



Figure 5. Association between simulated C values and the percentage of each land use type in
a particular sub-watershed. Dotted lines indicate the maximum acceptable C value according
to the Ministry of Forestry Decree (2013).

The Ministry of Forestry of Indonesia considers C values of <0.35 to be adequate for supporting the required ecosystem services of Indonesian watersheds (Ministry of Forestry Decree, 2013). Based on our findings, at least 30 % of the forest covers (Fig. 5a) and no more than 40 % of the plantation cover (Fig. 5b) are required in the sub-watershed to achieve the required C value.



388

Figure 6. Association between simulated BFI values and the percentage of each land use typein a particular sub-watershed.

BFI values significantly increased as the percentage of forest cover increased ($R^2 = 0.78$; p < 0.05; Fig. 6a) and significantly decreased as the percentage of plantation cover increased ($R^2 = 0.83$; p < 0.05; Fig. 6b). BFI was not significantly related to any other land use types such as shrubland (Fig. 6c), agroforest (Fig. 6d), and dryland farming (data not shown).

According to Neitsch et al. (2009), the SWAT model considered only shallow groundwater in the stream flow simulation. Therefore, we expected that the SWAT model underestimated the simulated BFI value in our study area. To improve the performance of the



SWAT model for deep groundwater flow (low flow) simulation, Pfannerstill et al. (2014)
modified groundwater module by splitting the active groundwater storage into a fast and a
slow contributing aquifer. The result of this modification leads to better prediction of low
flow.

402 **3.4 Application of the research findings**

The conversion of tropical rainforest into oil palm and rubber plantations affects the local 403 hydrological cycle by increasing ET, decreasing infiltration, decreasing low flow levels, and 404 increasing flooding frequency. In Jambi Province, Indonesia, forested areas have been largely 405 406 transformed into plantations, resulting in inhabitants experiencing water shortages during the dry season and dramatic increases in flooding frequency during the wet season. One way in 407 which this problem could be mitigated is by maintaining an adequate proportion of forested 408 409 and plantation areas in a particular watershed, but this raises the question about what is the minimum percentage of forest area and the maximum proportion of plantation area in a 410 watershed that will allow the maintenance of adequate water flow regulation. This study is 411 the first to describe the quantitative association between forest and plantation areas and the 412 flow indicators C and BFI; this understanding is required by spatial planners if they are to 413 balance the ecology and socioeconomic functions of a landscape with the rapid expansion of 414 plantation crops. In addition, our study provides data regarding how SWAT input parameters 415 related to tropical plantations such as oil palm and rubber should be adjusted, particularly 416

those that play an important role in controlling rainfall initial abstraction (e.g., CANMX),
rainfall partitioning into surface runoffs (e.g., CN2, OV_N), and vertical movement of water
through (e.g., SOL_BD, SOL_K, and SOL_AWC).

420 **4 Summary**

421 We found that ALPHA BF, CN2, GW DELAY, CANMX, SOL BD, GWQMN, SOL K,

422 CH_N2, SOL_AWC, and OV_N were sensitive parameters in our model, some of which play

423 an important role in controlling the initial abstraction of rainfall (e.g., CANMX), rainfall

424 partitioning into surface runoff (e.g., CN2, OV_N), and vertical movement of water through

425 the soil (e.g., SOL_BD, SOL_K, and SOL_AWC).

Overall, the SWAT model performance was satisfactory, with NSE values of 0.80–0.88 426 (calibration) and 0.80-0.85 (validation) and PBIAS values of -2.9 to 1.2 (calibration) and 427 7.0–11.9 (validation). We found that the percentage of forest cover in a watershed was 428 significantly negatively correlated with C and positively correlated with BFI, whereas the 429 percentage of rubber and oil palm plantation cover showed the opposite pattern. Finally, our 430 findings suggest that a watershed should contain at least 30 % forest cover and a maximum of 431 40 % plantation cover for maintaining sustainable water flow regulation ecosystem services. 432 The quantitative association between forest cover and flow indicators, which was derived 433 in this study, will help regional planners in determining the minimum proportion of forest 434 cover that needs to be maintained to ensure effective water flow regulation in a watershed. 435

436 **5. Data availability**

437 The land use data are freely available for research purposes upon official request to the corresponding institutions: the Digital Elevation Model with a resolution of 30 m per pixel 438 can be obtained from the National Aeronautics and Space Agency; the rainfall and climate 439 data can be obtained from the Meteorology and Geophysics Agency; the streamflow data of 440 the six macro watersheds can be obtained from the Ministry of Public Works; and the land 441 use data can be obtained from the Regional Planning office. The streamflow time series and 442 rainfall records for the small catchments and data for the resampled soil hydraulic 443 conductivity, bulk density, available water content and texture have been deposited by the 444 first author at Bogor Agricultural University and in the EFForTS Database (https://efforts-445 is.uni-goettingen.de). 446

447 Acknowledgments

448 This study was performed in the framework of the joint Indonesian-German research project

EFForTS-CRC 990 (<u>http://www.uni-goettingen.de/crc990</u>) and was funded by the Directorate

450 General of Higher Education (DIKTI), Indonesia.

451 **References**

- 452 Abbaspour, K. C.: SWAT-CUP 2012: SWAT Calibration and Uncertainty Programs A User
- 453 *Manual*, 2012, Eawag–Swiss Federal Institute of Aquatic Science and Technology, 2015.
- 454 Adnan, N. A. and Atkinson, P. M.: Exploring the impact of climate and land use changes on
- 455 streamflow trends in a monsoon catchment, Int. J. Climatol., 31, 815–831, 2011.
- 456 Afriyanti, D., Kroeze, C., and Saad, A.: Indonesia palm oil production without deforestation
- 457 and peat conversion by 2050, Sci. Total. Environ., 557-558, 562–570, 2016.
- 458 Allen, K., Corre, M., Tjoa, A., and Veldkamp, E.: Soil nitrogen-cycling response to
- 459 conversion of lowland forests to oil palm and rubber plantations in Sumatra, Indonesia,
- 460 PLoS One, 10, e0133325, 2015.
- 461 Arnold, J. G., Moriasi, D. N., Gassman, P. W., Abbaspour, K. C., White, M. J., Srinivasan,
- 462 R., Santhi, R. C., Harmel, R. D., van Griensven, A., Van Liew, M. W., Kannan, N., and
- Jha, M. K.: SWAT: Model use, calibration, and validation, Trans. ASABE., 55, 1491–
 1508, 2012.
- Babel, M. S., Shrestha, B., and Perret, S. R.: Hydrological impact of biofuel production: a
 case study of the Khlong Phlo Watershed in Thailand, Agric. Water. Manag.,101, 8–26,
- 467 doi:10.1016/j.agwat.2011.08.019, 2011.

- Banabas, M., Turner, M. A., Scotter, D. R., and Nelson, P. N.: Losses of nitrogen fertilizer
 under oil palm in Papua New Guinea: 1. Water balance, and nitrogen in soil solution and
- 470 runoff, Aust. J. Soil Res., 46, 332–339, 2008.
- 471 Blume, T., Zehe, E., and Bronstert, A.: Rainfall-runoff response, event-based runoff
- 472 coefficients and hydrograph separation, Hydrol. Sci. J., 52, 5, 2007.
- 473 Bosch, J. M. and Hewlett, J. D., A review of catchment experiments to determine the effect
- of vegetation changes on water yield and evapotranspiration, J. Hydrol., 55, 3–23, 1982.
- Brown, A. E., Zhang, L., McMahon, T. A., Western, A. W., and Vertessy, R. A., A review of
- 476 paired catchment studies for determining changes in water yield resulting from alterations
- 477 in vegetation, J. Hydrol., 310, 28–61, 2005.
- Bruijnzeel, L. A.: (De)forestation and dry season flow in the tropics: a closer look, J. Trop.
 For. Sci., 1, 229–243, 1989.
- 480 Bruijnzeel, L. A.: Hydrology of moist tropical forests and effects of conversion: a state of
- 481 knowledge review, UNESCO International Hydrological Programme, A publication of the
 482 Humid Tropics Programme, UNESCO, Paris, 1990.
- Bruijnzeel, L. A.: Hydrological functions of tropical forests: not seeing the soil for the trees?
 Agric. Ecosyst. Environ., 104, 185–228, 2004.
- 485 Carlson, K. M., Curran, L. M., Ratnasari, D., Pittman, A. M., Soares-Filho, B. S., and Asner,
- 486 G.P.: Committed carbon emissions, deforestation, and community land conversion from

- 487 oil palm plantation expansion in West Kalimantan, Indonesia, Proc. Nat. Acad. Sci., 109,
 488 7559–7564, 2012.
- Comte, I., Colin, F., Whalen, J. K., Gruenberger, O., and Caliman, J. P.: Agricultural
 practices in oil palm plantations and their impact on hydrological changes, nutrient fluxes
 and water quality in Indonesia: a review, Adv. Agron., 116, 71–124, 2012.
- 492 Dietz, J., Hölscher, D., and Leuschner, C.: Rainfall partitioning in relation to forest structure
- 493 in differently managed montane forest stands in Central Sulawesi, Indonesia. For. Ecol.
 494 Manage., 237, 170–178, 2006.
- 495 Ditjenbun: Indonesian plantation statistics. Directorate General for Plantations, Ministry of
 496 Agriculture Indonesia, 2015.
- 497 Dislich, C., Faust, H., Kisel, Y., Knohl, A., Otten, F., Meyer. K., Pe'er, G., Salecker, J.,
- Steinebach, S., Tarigan, S., Tölle, M., and Wiegand, K.: A review of the ecosystem
 functions in oil palm plantations, using forests as a reference system, Biol. Rev., 92, 1539–
 1569, doi:10.1111/brv.12295, 2017.
- 501 Drescher, J., Rembold, K., Allen, K., Beckschäfer, P., Buchori, D., Clough, Y., Faust, H.,
- 502 Fauzi, A. M., Gunawan, D., Hertel, D., Irawan, B., Jaya, I. N. S., Klarner, B., Kleinn, C.,
- 503 Knohl, A., Kotowska, M. M., Krashevska, V., Krishna, V., Leuschner, C., Lorenz, W.,
- 504 Meijide, A., Melati, D., Nomura, M., Pérez-Cruzado, C., Qaim, M., Siregar, I. Z.,
- 505 Steinebach, S., Tjoa, A., Tscharntke, T., Wick, B., Wiegand, K., Kreft, H., and Scheu, S.:

- Ecological and socioeconomic functions across tropical land-use systems after rainforest
 conversion, Phil. Trans. R. Soc., B 371, 20150275, 2016.
- Ellison, D., Morris, C.E., Locatelli, B., Sheil, D., et. al.,: Trees, forests and water: Cool
 insights for a hot world. Global Environmental Change, 43, 51–61, 2017.
- 510 Fan, Y., Roupsard, O., Bernoux, M., Le Maire, G., Panferov, O., Kotowska, M. M., and
- 511 Knohl, A.: A sub-canopy structure for simulating oil palm in the Community Land Model
- 512 (CLM-Palm): phenology, allocation and yield, Geosci. Model. Dev., 8, 3785–3800, 2015.
- 513 Fitzherbert, E. B., Struebig, M. J., Morel, A., Danielsen, F., Brühl, C. A., Donald, P. F., and
- Phalan, B.: How will oil palm expansion affect biodiversity? Trends. Ecol. Evol., 23, 538–
 545, 2008.
- 516 Fox, J., Vogler, J. B., Sen, O. L., Giambelluca, T. W., and Ziegler, A. D.: Simulating land-
- 517 cover change in Montane mainland Southeast Asia, Environ. Manage., 49, 968–979,
- 518 doi:10.1007/s00267-012-9828-3, 2012.
- 519 Gassman, P. W., Reyes, M. R., Green, C. H., and Arnold, J. G.: The soil and water
- 520 assessment tool: historical development, applications, and future research direction, Amer.
- 521 Soc. Agric. Bio. Eng., 50, 1211–1250, 2007.
- 522 Gatto, M., Wollni, M., Asnawi, R., and Qaim, M.: Oil palm boom, contract farming, and rural
- 523 economic development: village-level evidence from Indonesia, World Development, 95,
- 524 127–140, 2017.

- Guillaume, T., Damris, M., and Kuzyakov, Y.: Losses of soil carbon by converting tropical
 forest to plantations: erosion and decomposition estimated by δ 13 C. Glob. Chang. Biol.,
 21, 3548–3560, 2015.
- Guillaume, T., Holtkamp, A.M., Damris, M., Brümmer, B., and Kuzyakov, Y.: Soil
 degradation in oil palm and rubber plantations under land resource scarcity. Agric.
 Ecosyst. Environ., 232, 110–118, 2016.
- Guo, J., Su, X., Singh, V.P., and Jin, J.: Impacts of climate and land use/cover change on
 streamflow using SWAT and a separation method for the Xiying River basin in
 Northwestern China, Water, 8, 192, doi:10.3390/w8050192, 2016.
- Gupta, H. V., S. Sorooshian, and P. O. Yapo.: Status of automatic calibration for hydrologic
 models: Comparison with multilevel expert calibration. J. Hydrologic Eng., 4,2, 135-143,
 1999.
- Hardanto, A., Röll, A., Niu, F., and Meijide, A.: Oil palm and rubber tree water use patterns effects of topography and flooding, Front. Plant. Sci., 8, 452, 2017.
- 539 Hassler, E., Röll, A., Corre, M. D., Kurniawan, S., and Veldkamp, E.: Soil nitrogen oxide
- 540 fluxes from lowland forests converted smallholder rubber and oil palm plantations in
- 541 Sumatra, Indonesia, Biogeosci. Discuss., 14, 2781, 2017.

- Hewlett, J. D. and Hibbert, A. R.: Factors affecting response of small watersheds to
- 543 precipitation in humid areas, in: Forest Hydrology, Sopper, W. E. and Lull, H.W. (Eds.),

544 Pergamon Press, New York, 1967

545 Khoi, D.N. and Suetsugi, T.: Impact of climate and land-use changes on hydrological
546 processes and sediment yield—a case study of the Be River catchment, Vietnam, Hydrol.

547 Sci. J., 59, 5, 2014.

- Koh, L. P. and Wilcove, D. S.: Is oil palm agriculture really destroying tropical biodiversity?
 Conserv. Lett., 1, 2, 60–64, 2008.
- Krashevska, V., Klarner, B., Widyastuti, R., Maraun, M., and Scheu, S.: Impact of tropical
 lowland rainforest conversion into rubber and oil palm plantations on soil microbial
- communities, Biol. Fertil. Soils., 51, 697–705, 2015.
- 553 Kumagai, T., Saitoh, T. M., Sato, Y., Takahashi, H., Manfroi, O. J., Morooka, T., Kuraji, K.,
- Suzuki, M., Yasunari, T., and Komatsu, H.: Annual water balance and seasonality of
 evapotranspiration in a Bornean tropical rainforest, Agric. For. Meteorol. 128, 81–92,
 2005.
- 557 Lele, S.: Watershed services of tropical forests: from hydrology to economic valuation to
- integrated analysis, Curr. Opin. Environ. Sustain., 1, 148–155, 2009.

- Le Maitre, D. C., Kotzee, I. M., and O'Farrell, P. J.: Impacts of land-cover change on the
- 560 water flow regulation ecosystem service: Invasive alien plants, fire and their policy
- 561 implications, Land. Use. Policy., 36, 171–181, 2014.
- 562 Marhaento, H., Booij, M. J., Rientjes, T. H. M., and Hoekstra, A. Y.: Attribution of changes
- in the water balance of a tropical catchment to land use change using the SWAT model,
- 564 Hydrol. Process., 31, 11, 2029–2040. doi:10.1002/hyp.11167, 2017.
- 565 Meijide, A., Röll, A., Fan, Y., Herbst, M., Niu, F., Tiedemann, F., June, T., Rauf, A.,
- 566 Hölscher, D., and Knohl, A.: Controls of water and energy fluxes in oil palm plantations:
- environmental variables and oil palm age, Agric. For. Meteorol., 239, 71–85, 2017.
- Merten, J., Röll, A., Guillaume, T., Meijide, A., Tarigan, S., Agusta, H., Dislich, C., Dittrich,
- 569 C., Faust, H., Gunawan, D., and Hein, J.: Water scarcity and oil palm expansion: social 570 views and environmental processes. Ecol. Soc., 21, 5–16, 2016.
- 571 Ministry of Forestry Decree Permenhut/Menhut-V/2013.: Criteria for watershed
- 572 classification (Kriteria Penetapan Klassifikasi Daerah Aliran Sungai), Ministry of
- 573 Forestry, Republic of Indonesia, 2013.
- 574 Moriasi, D.N., Wilson, B.N., Douglas-Mankin, K.G., Arnold, J.G., Gowda, P.H.: Hydrologic
- and water quality models: use, calibration, and validation. Trans. ASABE, 55,4, 1241-
- 576 1247, 2012.

- 577 Mukherjee, I. and Sovacool, B. K.: Palm oil-based biofuels and sustainability in southeast
- Asia: a review of Indonesia, Malaysia, and Thailand, Renew. Sustainable. Energy. Rev.,
- 579 37, 1–12, doi:10.1016/j.rser.2014.05.001, 2014.
- 580 Mwangi, H. M., Julich, S., Pati, S. D., McDonald, M. A., and Feger, K. H.: Relative
- 581 contribution of land use change and climate variability on discharge of upper Mara River,
- 582 Kenya, J. Hydrol., 5, 244–260, 2016.
- Nash, J. and Sutcliffe, J. V.: River flow forecasting through conceptual models, 1, A
 discussion of principles, J. Hydrol., 10, 282–290, 1970.
- Neitsch, S. L., Arnold, S. G., Kiniry, J. R., and Williams, J. R.: Soil and water assessment
- tool theoretical documentation, Version 2009. *Texas Water Resources Institute Technical*
- *Report No. 406.* Texas A&M University System, College Station, Texas, 77843-2118,
 2011.
- Pfannerstill, M., Guse, B., Fohrer, N.: A multi-storage groundwater concept for the swat
 model to emphasize non- linear groundwater dynamics in lowland catchments. Hydrological Processes, 28, 5599-5612, DOI: 10.1002/hyp.10062, 2014.
- Pransiska, Y., Triadiati, T., Tjitrosoedirjo, S., Hertel, D., and Kotowska, M. M.: Forest
 conversion impacts on the fine and coarse root system, and soil organic matter in tropical
 lowlands of Sumatera (Indonesia). For. Ecol. Manage., 379, 288–298, 2016.

595	Rientjes, T. H. M., Haile, A. T., Kebede, E., Mannaerts, C. M., Habib, E., and Steenhuis, T.
596	S.: Changes in land cover, rainfall and stream flow in Upper Gilgel Abbay catchment,
597	Blue Nile basin-Ethiopia, Hydrol. Earth. Syst. Sci., 15, 1979–1989, 2011.
598	Röll, A., Niu, FR., Meijide, A., Hardanto, A., Hendrayanto, Knohl, A., and Hölscher, D.:
599	Transpiration in an oil palm landscape: effects of palm age. Biogeosciences, 12, 9209-
600	9242, 2015.
601	Setiadi, B., Diwyanto, K., Puastuti, W., Mahendri, I.G.A.P., Tiesnamurti, B.: Peta Potensi dan
602	Sebaran Areal Perkebunan Kelapa Sawit di Indonesia. Pusat Penelitian dan
603	Pengembangan Peternakan, BadanLitbang Pertanian, Kementerian Pertanian (Area
604	distribution of oil palm plantation in Indonesia, Center for Research and Development,
605	Ministry of Agriculture Indonesia). ISBN 978-602-8475-45-7, 2011.
606	Sterling, S. M., Ducharne, A., and Polcher, J.: The impact of global land cover change on the
607	terrestrial water cycle, Nat. Clim. Change. 3, 385–390. doi:10.1038/nclimate1690, 2012.
608	Tarigan, S. D.: Land cover change and its impact on flooding frequency of Batanghari
609	Watershed, Jambi Province, Indonesia, Procedia. Environ. Sci., 33, 386-392, 2016.
610	Tarigan, S. D., Wiegand, K., Dislich, C., Slamet, B., Heinonen, J., and Meyer K.: Mitigation
611	options for improving the ecosystem function of water flow regulation in a watershed with

rapid expansion of oil palm plantations, Sustainability of Water Quality and Ecology, 8, 612

4–13, 2016. 613

- Van der Laan, C., Wicke, B., Verweij, P. A., and Faaij, A. P. C.: Mitigation of unwanted
 direct and indirect land-use change-an integrated approach illustrated for palm oil,
 pulpwood, rubber and rice production in North and East Kalimantan, Indonesia. Glob.
 Change. Biol. Bioenergy., 9, 429–444, doi:10.1111/gcbb.12353, 2016.
- Van der Molen, M. K., Dolman, A. J., Waterloo, M. J., and Bruijnzeel, L. A.: Climate is
 affected more by maritime than by continental land use change: a multiple scale analysis.
- 620 Glob. Planet. Change., 54, 128–149, 2006.
- 621 Van Griensven, A., Meixner, T., Grunwald, S., Bishop, T., Diluzio, M., and Srinivasan, R.
- A.: Global sensitivity analysis tool for the parameters of multi-variable catchment models,
 J. Hydrol., 324, 10–23, 2006.
- Van Griensven, A., Maharjan, S., and Alemayehu, T.: Improved simulation of
 evapotranspiration for land use and climate change impact analysis at catchment scale,
 International Environmental Modelling and Software Society (iEMSs) 7th International
 Congress on Environmental Modelling and Software, 2014.
- Vigerstol, K. L., Aukema, J. E.: A comparison of tools for modeling freshwater ecosystem
 services, J. Environ. Manage., 92, 2403–2409, 2011.
- 630 Vijay, V., Pimm, S.L., Jenkins, C.N., and Smith, S.J.: The impacts of oil palm on recent
- deforestation and biodiversity loss, PLoS One, 11, e0159668,
 doi:10.1371/journal.pone.0159668, 2016.

- Wangpimool, W., Pongput, K., Tangtham, N., Prachansri, S., and Gassman, P. W.: The
 impact of para rubber expansion on streamflow and other water balance components of the
 Nam Loei River Basin, Thailand, Water, 9, 1, doi:10.3390/w9010001, 2017.
- 636 Wicke, B., Sikkema, R., Dornburg, V., and Faaij, A.: Exploring land use changes and the role
- of palm oil production in Indonesia and Malaysia, Land. Use. Policy., 28, 193–206, 2011.
- Wilcove, D. S. and Koh, L. P.: Addressing the threats to biodiversity from oil-palm
 agriculture, Biodivers. Conserv., 19, 999–1007, 2010.
- Ku, X., Yang D., Yang, H., and Lei, H., Attribution analysis based on the Budyko hypothesis
- for detecting the dominant cause of runoff decline in Haihe basin, J. Hydrol., 510, 530–
 540, 2014.
- Yusop, Z., Chan, C. H., and Katimon, A.: Runoff characteristics and application of HECHMS for modelling stormflow hydrograph in an oil palm catchment, Water. Sci. Technol.,
 56, 41–48, 2007.
- Zhang, L., Nan, Z., Xu, Y., and Li, S., Hydrological impacts of land use change and climate
 variability in the headwater region of the Heihe river basin, Northwest China, PLoS One.,
- 648 11, e0158394. doi:10.1371/journal.pone.0158394, 2016.
- 649 Ziegler, A. D., Fox, J. M., and Xu, J., The rubber juggernaut, Science., 324, 1024–1025. doi:
 650 10.1126/science.1173833, 2009.

- 651 Ziegler , A. D., Fox, J. M., Webb, E. L., Padoch, C., Leisz, S. J., Cramb, R. A., Mertz, O.,
- Bruun, T. B., and Vien, T. D., Recognizing contemporary roles of swidden agriculture in
- transforming landscapes of Southeast Asia, Conserv. Biol., 25, 846–848, 2011.