

Response for reviewer 1

General: This paper shows a very interesting model analysis of water transport in a snow sample. Both the experimental data and the model have been presented earlier and this paper now compares the model with the data set. This new comparison offers interesting insight into the process and offers a technically correct analysis. The presentation is concise, state of the art is presented in a balanced way and conclusions supported by the analysis. The paper is in scope and quality suitable for HESS.

One major suggestion concerns the SNOWPACK simulations. I understand that the reason for using the SNOWPACK version without preferential flow parameterization in order to show the differences caused by the preferential flow. However, I don't understand why not additional simulations are shown, which use the SNOWPACK preferential flow parameterization. This would add value to the paper and increase its impact for two reasons: i) The 3D model is (computationally) limited to small domains (see also next comment below) and if the reader is provided with an analysis that allows to judge how much of the effect is covered by the SNOWPACK parameterization, then this has a lot of practical value for scientist that need to do larger-scale simulations.

ii) The analysis would already give a first indication on how the slightly different treatment of preferential flow path initiation (entry suction) in the 3D model vs. SNOWPACK compares and would therefore add substance to the discussion of the entry suction problem, which is well executed in the paper otherwise. My suggestion is further supported by the fact that the current paper has not already too many new elements or this too long and this additional analysis should be easy to execute.

Response: Thank you for these constructive comments. The second reviewer also suggested to add SNOWPACK simulations with the dual domain approach and we agree with both of you that including this scheme would enhance the impact of the work. We therefore included SNOWPACK with dual-domain approach in our approach (SNOWPACK DDA-model). Also, SNOWPACK without preferential flow is now named SNOWPACK RE-model to distinguish it from DDA-model. The resolution of SNOWPACK simulations was changed to 5mm to match with the resolution of 3D model. Thickness of water ponding layer, water content profiles and liquid water arrival

at the snow base, were compared. These discussions are reported in section 4.1. Figure 6 in revised manuscript now includes the water profile of DDA-model. Also, a comparison figure about arrival time for models was added as Figure 7.

One additional (major) comment concerns the missing discussion of the domain size effect. While domain sizes have been chosen congruently between measurements and simulations, the generalization of the results may still be suffering from the small lateral extent in both. The dye experiments we know from snow (e.g. the ones from Schneebeli mentioned in the paper) show very significant lateral spreading of flow paths much beyond the scale of the experiments presented here. This aspect should be properly discussed.

Response: We agree with you. In the revised manuscript, we will add a discussion about the domain size effect. This discussion is here reported as a reply for minor comment at P4 l32 (see below)

Detailed (minor) comments:

p.3 l.27ff: Maybe mention additional snow characteristics (grain type) and how you produced the snow samples?

Response: The details about production of snow samples are already reported in Avanzi et al (2016). However, we will add some information about the preparation method and grain type.

“In these experiments, snow samples were prepared in a cold room at -20°C using refrozen melt forms. Snow was packed in a cylindrical container composed of several acrylic rings; the height and diameter of the rings were 20 mm and 50 mm, respectively. Each sample was composed of two layers: the upper layer was 10 cm thick, the lower layer was either 8 or 10 cm thick (see Avanzi et al., 2016). Then, samples were moved to a second cold room at 0°C and stored for at least 12 h to reach initial conditions of dry snow at 0°C . All samples were characterized by a finer-over-coarser layering (i.e. the upper layer was created using a smaller grain size than the lower one), which aimed

to reproduce capillary barriers. The three classes of snow grain size included fine (0.25–0.5 mm), medium (1.0–1.4 mm), and coarse (2.0–2.8 mm).”

p.4 l.14: “of” breakthrough on breakthrough

Response: We clarified the sentence as reported below:

“The evaluation of simulations focused on the thickness of the ponding layer at the textural interface, on the liquid water distribution, on the wet snow fraction at different heights, and on different timings that are relevant for liquid water movement in snow. These include water arrival at the interface between layers, breakthrough of preferential flow in the lower layer, and arrival of liquid water at sample base.”

p.4 l.19: Maybe grid points or elements instead of “meshes”

Response: We clarified the sentence as reported below. Also, in revised manuscript, we will check words and replace, “meshes” with “elements” in the entire manuscript.

“The simulated timings of water arrival at the interface, entering the lower layer, and arrival at the snow base refer to the lowest elements in the upper layer, the top three elements in lower layer, and the lowest elements of the sample, respectively.”

p.4 l.21: “expended” ?

Response: We clarified the sentence as reported below:

“The water content in the top three elements of the lower layer was used to determine the timing of breakthrough because preferential flow began immediately after the water content of one of these elements became larger than zero.”

p.4 l.29: “anticipated” measured

Response: We clarified the sentence as reported below:

“Some images of the development of capillary barriers and preferential flow for FC1 are shown in Fig. 1. These figures show the front surfaces 20 s after the beginning of the experiment (a and e), at the arrival time of water at the interface between layers (b and f), at the time of breakthrough of preferential flow into the lower layer (c and g) and at the arrival time at the snow base (d and h). The simulation results showed faster than measured arrival of water at the boundary (Table 2), which implied an overestimation of vertical velocity in the model’s preferential flow for this experiment (Fig. 1).”

p.4 l.32: Here you could add some discussion on the effect of domain size (see above)

Response: We agree with you and have included some discussion on this point as reported below:

“The size of laboratory experiments was restricted by the time needed to prepare and perform each of them. Also, the diameter of samples was consistent with the thickness of similar experiments in soils (see e.g. Hill and Parlange, 1972), whereas Avanzi et al. (2017) showed that preferential flow may be intrinsically coupled with wet-snow metamorphism at grain scale. This suggests that small-scale experiments are appropriate to understanding the physics of this process in snow. Nonetheless, the relatively small scale of these experiments may introduce some domain size effect. In natural snow, water flow shows lateral spreading, especially at capillary barriers, whereas experiments with small size may partially perturb the natural flow on snow and therefore change vertical flow owing to artificial edges. This may increase the ratio of preferential flow path area, decrease the arrival time at the base, and decrease natural ponding amount at the capillary barrier. In terms of comparison between simulations and experiments, this effect was offset by using the same domain conditions.”

p.5 l.4: “85” add minutes

Response: This information was added to the manuscript.

p.5 l.7ff: By comparing to Walter I think you compare two different things: Velocity of

water in an existing preferential flow path (Walter) vs. propagation speed of path initiation. Please discuss appropriately

Response: As you suggested, the velocity in an existing preferential flow path is likely different from propagation speed of path initiation. This difference makes this comparison unsuitable. Therefore, we removed the sentence “This is one order of magnitude supply rate (3600 mm/h).” from the manuscript. Thank you.

p.5 l.14: Please mention the reason of why it could not be determined

Response: We were not be able to measure the exact timing of preferential flow initiation using a frontal movie when preferential flow formed at the posterior side of samples with respect to the position of the camera. On the other hand, horizontal spreading of water at sample base always allowed to detect the arrival time with a reasonable precision. We clarified this in the manuscript.

“As timings were measured using frontal movies, we were sometimes unable to evaluate the timing of preferential flow formation within a sample. For example, in the case of MC1, preferential flow formed on the side of the sample that was not visible from the frontal position of the camera. Thus, the frontal movie did not show the preferential flow path in lower layer, whereas horizontal spreading of water at the sample base allowed us to detect the arrival time with a reasonable precision. It follows that for this sample we cannot determine the timing of preferential flow initiation. Therefore, estimated timings from laboratory experiments may contain a delay.”

p.7 l.1ff: I would suggest to add a general comment that deviations of both models from measurements have the same order of magnitude

Response: We quantified the magnitude of deviation for each simulation. While both SNOWPACK schemes yield the same RMSE, the 3D model returns a slightly smaller value. So we described about deviations as follows.

“The RMSE for liquid water content profiles at (measured) arrival time are 0.107, 0.107

and 0.094 for SNOWPACK RE-model, DDA-model and 3D model, respectively. While both SNOWPACK schemes yield the same RMSE, the 3D model returns a slightly smaller value.”

p.7 l.21: Why “in practice”?

Response: “In practice” is not suitable to use here. So it was removed.

p.8 l.8: “too vertically strict” is a funny expression and I suggest to try to explain it (maybe domain size as mentioned above?)

Response: As we replied to your major comment, we expect domain size effects to possibly perturb real dynamics of liquid water flow by increasing wet snow area. This effect is, nonetheless, in contrast with the observed underestimation of wet snow area by the model. We elaborated on this sentence and connected it to the next paragraph.

“Nevertheless, the simulated mean wet snow area was small even for fine snow (e.g. 4.8% in FC1 and 22% in FC3, excluding the ponding area). As the simulated wet snow area is smaller than the measured one, this model may still underestimate the effective cross-sectional area of infiltration. This will be the subject of future research.”

p.8 l.13ff: Here you should discuss that the model does not predict any structural changes in the snow grains. This is discussed further below but this is not sufficient. In reality, grains will grow quickly in contact with water at the walls of preferential flow paths and this will also promote lateral spreading of water, I think

Response: Although this model includes grain growth following Brun et al. (1989) and Tusima (1977), modeling some specific conditions such as wet snow metamorphism at the boundaries between preferential flow paths and drier snow is still an open issue. This is important to improve the model. Thank you for this advice. We will add a discussion about it.

“Neglecting quick metamorphism in preferential flow paths (Avanzi et al. 2017) may

represent another cause of underestimation of preferential flow path size as grain growth promotes lateral spreading of water and expansion of paths. Although this model includes grain growth following Brun et al. (1989) and Tusima (1977), modelling some specific conditions such as wet snow metamorphism at the boundaries between preferential flow paths and drier snow is still an open issue. Also, existing observations of wet-snow metamorphism have been mainly performed in static conditions, which means that the coupling between grain growth and flowing water is still poorly understood. This represents a further unknown for models of liquid water in snow.”

p.9 l.4ff: Metamorphism could help to explain lateral spreading

Response: We agree with your opinion. We will add the following discussion at the end of Section 4.3.

“Extending the existing parameterizations of wet snow metamorphism for small timescales will improve simulation accuracy with regards to the development and disappearance of water ponding by capillary barriers. Also, a correct simulation of grain growth will lead to correctly estimating the lateral spreading of water, which will improve the accuracy of the prediction of preferential flow path size.”

Figure 1 legend: Explain the term “front grid”

Response: We thought using phrase “front elements” is better than “front grid”. So we replaced it in the manuscript. Also, we will improve the figure to explain the term “front elements” (see below). This will also be mentioned in the caption.

“Figure 1: Development of capillary barrier and preferential flow path for FC1 during experiments (a–d) and simulations (e–h). A blue dye tracer was used in the experiment. In the simulation images, blue denotes the liquid water content at the front elements (see: right figure), while grey denotes that the front elements are dry, but some liquid water is present within the sample at that position. The grey-scale represents the maximum liquid water content for each location. Captured times were at: (a) 20 s, (b) 35 min, (c) 1 hour 25 min, (d) 1 hour 29 min, (e) 20 s, (f) 17 min, (g) 1 hour 19 min,

and (h) 1 hour 20 min.”

Response for Reviewer 2

This paper presents model simulations performed with a recently developed 3D model for water movement through snow (published by the authors in 2014), to simulate recently published detailed experiments by Avanzi et al., 2016. These simulations show good agreement with the experimental results, for water content, timing, preferential flow, and ponding of water at capillary barriers. The results demonstrate that the recently developed model represents the complex physics of unsaturated flow in snow quite well, as long as the snow material properties (grain size, density, etc) are known. There are a few additional steps that the authors could likely easily take, which would greatly improve this manuscript. I would highly recommend these improvements before publication:

1) The authors compare their simulations to simulations using the operational SNOWPACK model, and argue that their representation of preferential flow allows more accurate estimates of water flow timing and liquid water content. However, they use the SNOWPACK model without the recent improvements in this area (e.g. Wever et al, 2016; Wurzer et al, 2017), although these papers are cited. To complete this study, they should compare their small scale 3-D model with the most recent SNOWPACK model, which includes these improvements.

Response: Thank you for these constructive comments. The first reviewer also suggested to add SNOWPACK simulations with the dual domain approach and we agree with both of you that including this scheme would enhance the impact of the work. We therefore included SNOWPACK with dual-domain approach in our discussion (SNOWPACK DDA-model). Also, SNOWPACK without preferential flow is now named SNOWPACK RE-model to distinguish it from DDA-model. The resolution of SNOWPACK simulations was changed to 5mm to match with the resolution of 3D model. Thickness of water ponding layer, water content profiles and liquid water arrival at the snow base, were compared. These discussions are reported in section 4.1. Figure 6 in revised manuscript now includes the water profile of DDA-model. Also, a comparison figure about arrival time for models was added as Figure 7.

2) A sensitivity analysis would be very helpful. The authors use the measured grain sizes (from sieving) used in the experiment, and report these values to 0.001 mm. In nature, grain sizes are typically measured to 0.1mm, and models of grain growth are unlikely to be accurate to better than 0.5mm. It would be very helpful to see how sensitive their model results are to variations in grain size on the order of 0.1mm.

Response: We agree with you. We performed additional simulations with changes in grain size in the order of 0.1 mm for both layers. A new sub-section (4.3) was added to discuss changes in thickness of water ponding layer, water content distribution, and arrival time at sample base due to fluctuations of grain sizes. Figure 8 and Figure S5 were also added to show the result of sensitivity experiment. Sensitivity experiments showed large influence of grain size fluctuation of upper fine snow and suggested the importance of careful measurement of grain size for fine snow.

3) A recent similar paper using a different model, by a different group, also used the Avanzi et al, 2016 experiments and attempted to reproduce their results with a 2-D snow heat and mass flow model: Nicolas R. Leroux , John W. Pomeroy , Modelling capillary hysteresis effects on preferential flow through melting and cold layered snowpacks, Advances in Water Resources (2017), doi:10.1016/j.advwatres.2017.06.024.

While the Leroux and Pomeroy paper was not published at the time this paper was submitted, now that it is accepted and online, it would be useful for the authors to cite and discuss the differences between their model and this one.

Response: In the revised manuscript, we will consider the Leroux and Pomeroy paper and add a discussion about the difference between those and our results as follows:

“Similarly, Leroux and Pomeroy (2017) developed a 2D water transport model basing on the scheme of Hirashima et al. (2014a), but considering melt-freeze processes. Reproducing heterogeneous processes in a 1D or 2D model requires several assumptions. In natural snow, water flow shows lateral spreading, especially at capillary barriers, which creates complex 3D stratigraphic features at a grain/layer scale. Furthermore, when 3D preferential flow paths form in dry snow, wet snow area is

proportional to the square of preferential flow size and inversely proportional to the square of the distance between paths (see Fig. S1). For a 2D simulation, wet snow area is, e.g., proportional to preferential flow size and inversely proportional to the distance between paths (see Fig. S1). Considering a 3D geometry can, therefore, help to define the necessary parameterizations of preferential flow effects needed to inform models with a reduced number of dimensions. Note that, while Leroux and Pomeroy's model also includes temperature and melt-freeze processes, this is not expected to play a role here as the validation experiments were performed under isothermal conditions. “

This discussion is supported by the figure, which was added as Fig. S1 in the Supplement.

4) A more thorough discussion of model resolution would be appropriate. At the resolution of this model, it is unlikely modeling could be performed at the basin scale. How do the authors envision this new understanding of liquid water movement in snow, to impact large scale snow models? How could this understanding be implemented (empirically?) in operational modeling contexts?

Response: Thank you for this important advice. We agree with you that the scale of this model is still not suitable for direct applications at the basin scale. We will include a specific discussion about this in sub-section 4.3, or in an additional sub-section about future work.

“Our results show that this model is capable of reproducing detailed water infiltration at sample scale (i.e., considering micro-scale heterogeneity). On the other hand, the intrinsic scale of this process and computational efforts mean that it is still not suitable for basin-scale simulations. This limitation could be overcome by synergies with existing physics-based hydrologic models for snow-dominated catchments; for example, Alpine 3D (Lehning et al., 2006). Currently, SNOWPACK is used as a part of Alpine3D for simulation of accumulation/ablation patterns of snowpack. In this study, comparisons between laboratory experiments, a 3D model, and SNOWPACK were performed and contributed to highlighting model limitations and possible avenues of future developments (e.g. an underestimation of flow path cross-sections). While a 3D

model cannot reproduce the entire range of natural variability of liquid water flow in snow, it can help to replicate and understand this process in conditions that are difficult for experiments (e.g., larger sample sizes and/or a more complex stratigraphy). This may contribute to defining new parameterizations for dual domain approaches that could be then fully included in catchment-scale models. Also, we will try to apply this model at the basin scale by increasing the element size. While this will hamper the representation of single preferential fingers, we expect the model to be able to correctly reproduce other relevant features of water flow at slope scale such as lateral flow. This could help to understand liquid water flow around concave/convex portions of the landscape. ”

Detailed line-by-line edits/suggestions are in the attached PDF.

Please also note the supplement to this comment:
[*https://www.hydrol-earth-syst-sci-discuss.net/hess-2017-200/hess-2017-200-RC2-supplement.pdf*](https://www.hydrol-earth-syst-sci-discuss.net/hess-2017-200/hess-2017-200-RC2-supplement.pdf)

Response: Thank you for detailed suggestions. We have welcomed your suggestions in the manuscript and are going to address your comments in the revised paper.

Liquid water infiltration into a layered snowpack: evaluation of a 3D water transport model with laboratory experiments

Hiroyuki Hirashima¹, Francesco Avanzi^{2*}, Satoru Yamaguchi¹

¹Snow and Ice Research Center, National Research Institute for Earth Science and Disaster Resilience, Suyoshi-machi, Nagaoka-shi, Niigata-ken, 940-0821, Japan

²Department of Civil and Environmental Engineering, Politecnico di Milano, Milano, Italy

*Now at: Department of Civil and Environmental Engineering, University of California, Berkeley, Berkeley, USA

Correspondence to: Hiroyuki Hirashima (hirashima@bosai.go.jp)

h h 2017/9/18 11:07

削除: .

10 **Abstract.** The heterogeneous movement of liquid water through the snowpack during precipitation and snowmelt leads to complex liquid water distributions that are important for avalanche and runoff forecasting. We reproduced the formation of capillary barriers and the development of preferential flow through snow using a three-dimensional water transport model, which was then validated using laboratory experiments of liquid water infiltration into layered, initially dry snow. Three-dimensional simulations assumed the same column shape and size, grain size, snow density, and water input rate as the 15 laboratory experiments. Model evaluation focused on the timing of water movement, thickness of the upper layer affected by ponding, water content profiles and wet snow fraction. Simulation results showed that the model reconstructs relevant features of capillary barriers including ponding in the upper layer, preferential infiltration far from the interface, and the timing of liquid water arrival at the snow base. In contrast, the area of preferential flow paths was usually underestimated and consequently the averaged water content in areas characterized by preferential flow paths was also underestimated. 20 Improving the representation of preferential infiltration into initially dry snow is necessary to reproduce the transition from a dry-snow-dominant condition to a wet-snow-dominant one, especially in long-period simulations.

h h 2017/7/22 17:10

削除: multi

h h 2017/9/16 18:20

削除: the

h h 2017/9/16 18:21

削除: and on

h h 2017/9/16 18:21

削除: the

h h 2017/9/18 11:10

削除: some

h h 2017/9/18 11:10

削除: water

1 Introduction

The heterogeneous movement of liquid water through the snowpack during precipitation and snowmelt leads to complex liquid water distributions that impact the snow structure through wet snow metamorphism. Furthermore, grain growth and 25 subsequent changes in pore sizes and pore size distribution under wet conditions decrease snow strength (Wakahama, 1968; Raymond and Tsushima, 1979; Colbeck, 1983; Brun and Ray, 1987; Marsh, 1987; Brun et al. 1989; Lehning et al., 2002; Yamanoi and Endo, 2002; Ito et al., 2012) and can lead to wet snow avalanches (Kattelmann, 1984; Fierz and Föhn, 1994; Baggi and Schweizer, 2008; Mitterer et al. 2011; Mitterer and Schweizer, 2013; Takeuchi and Hirashima, 2013; Wever et al.,

hirashima hiroyuki 2017/7/24 9:47

削除: on

h h 2017/9/16 18:24

削除:

2016a). Liquid water movement through the snowpack also controls the lag between rain events or snowmelt and water arrival at the snow base.

In the early theories of liquid water movement, capillary gradients in snow were usually neglected (Colbeck, 1972; Colbeck and Davidson, 1972; Colbeck, 1974a, 1974b, 1976; Dunne et al., 1976; Wankiewicz, 1978). For example, Marsh and Woo (1985) developed a model of flow channels but neglected the gradient term of capillary pressure. A two-dimensional (2D) model by Illangasekare et al. (1990) considered the gradient of capillary pressure, but focused on the effects of ice layers without considering the dependency of capillary pressure on grain size and density. A 2D model by Daanen and Nieber (2009) adopted a van-Genuchten model with dependence on grain size. For each of these models, the main cause of heterogeneous water movement was attributed to refreezing and ice layers. In porous media (e.g. soil), water can pond owing to capillary barrier, which consequently delays infiltration (e.g. Clifford and Stephen, 1998; Kämpf et al., 2003); however, water can also pond and consequently form preferential flow in layered snow, even when no ice layer forms (Waldner et al., 2004; Eiriksson et al., 2013; Katsushima et al., 2013; Avanzi et al., 2016).

Capillary barriers form owing to differences in the matrix potential between layers. Hirashima et al. (2010) replicated capillary barrier formation in the SNOWPACK model using parameters of matrix potential obtained from gravity drainage column experiments performed by Yamaguchi et al. (2010). Wever et al. (2014) incorporated the Richards Equation into the SNOWPACK model and obtained a good correlation with observed runoff. [Wever et al. \(2015\)](#) compared upGPR data with lysimeter data and showed that, even if the simulated waterfront did not arrive at the snow base, runoff was still initiated. This was interpreted to reflect the effect of preferential flow, which was not included in the model (Wever et al., 2015).

More recent studies have explicitly modelled preferential flow; for example, Katsushima et al. (2013) used laboratory experiments in vertically homogeneous snow to show that water entry suction, which in turn is related to grain size, affects the formation of preferential flow. On the basis of this work, Hirashima et al. (2014a) developed a three-dimensional (3D) water transport model for snowpack that is able to reproduce preferential flow as a function of water entry suction and validated it using the results of Katsushima et al. (2013). However, as snowpacks typically contain multiple layers of snow with different densities and grain sizes, simulations and laboratory experiments of water infiltration for different snow layers remain necessary. Furthermore, because simulation results for layered snow have not yet been validated using real data (Hirashima et al., 2013; Hirashima et al., 2014b), the accuracy of the model remains uncertain. Avanzi et al. (2016) performed infiltration experiments for multi-layered snowpacks with different combinations of grain size and infiltration rate and measured liquid water distribution, thickness of the capillary barrier, and arrival time. In this study, simulations of liquid water infiltration into layered snowpacks were performed by reproducing the laboratory experiments of Avanzi et al. (2016).

The purpose of this study was: (1) to evaluate the accuracy of a 3D water transport model in reproducing infiltration patterns in layered snow; (2) to gain further insight into the 3D infiltration process into layered snow by comparing simulation results with data from laboratory experiments; and (3) to identify future avenues of development for 3D water transport schemes in snow.

hirashima hiroyuki 2017/9/12 12:01
削除: b

h h 2017/9/16 18:24
削除: ,

hirashima hiroyuki 2017/7/24 10:20
削除: They also

hirashima hiroyuki 2017/7/24 10:34
削除: s

h h 2017/9/18 15:54
削除: multiple-layer

hirashima hiroyuki 2017/7/24 10:40
削除: an

h h 2017/9/18 15:58
移動(挿入) [1]

Recently, a dual domain approach has been suggested to consider preferential flow effects in 1D (Wever et al., 2016b; Würzer et al. 2017). Similarly, Leroux and Pomeroy (2017) developed a 2D water transport model basing on the scheme of Hirashima et al. (2014a), but considering melt-freeze processes. Reproducing heterogeneous processes in a 1D or 2D model requires several assumptions. In natural snow, water flow shows lateral spreading, especially at capillary barriers, which creates complex 3D stratigraphic features at a grain/layer scale. Furthermore, when 3D preferential flow paths form in dry snow, wet snow area is proportional to the square of preferential flow size and inversely proportional to the square of the distance between paths (see Fig. S1). For a 2D simulation, wet snow area is, e.g., proportional to preferential flow size and inversely proportional to the distance between paths (see Fig. S1). Considering a 3D geometry can, therefore, help to define the necessary parameterizations of preferential flow effects needed to inform models with a reduced number of dimensions. Note that, while Leroux and Pomeroy's model also includes temperature and melt-freeze processes, this is not expected to play a role here as the validation experiments were performed under isothermal conditions.

2 Simulation method

2.1 Model

Details of the multi-dimensional water transport model are provided in Hirashima et al. (2014a). Models of liquid water movement in porous media use the Richards' equation and the Darcy-Buckingham law, which require knowledge of capillary pressure gradients and hydraulic conductivity. However, while the equation parameters depend on porosity, pore shape, pore connectivity, size distribution, and tortuosity, they are frequently estimated from a combination of snow density and grain size (Jordan et al., 2008).

In the three-dimensional model used here (Hirashima et al., 2014a), the relationship between capillary pressure, water content, grain size, and snow density (the so-called water retention curve) was determined based on gravity drainage column experiments performed by Yamaguchi et al. (2012). The relationship between saturated hydraulic conductivity, snow density, and grain size was estimated from the results of Calonne et al. (2012), who considered snow microstructure using the equivalent sphere radius estimated from specific surface area (SSA, instead of grain size). We considered grain size to be equal to equivalent sphere radius (Hirashima et al., 2014a) assuming grain shapes are round. If the grain shape is dendritic, an alternative method to estimate saturated hydraulic conductivity is necessary, including a simulation of SSA (Carmagnola et al., 2014). Unsaturated hydraulic conductivity was estimated using the van Genuchten-Mualem model (Mualem, 1976; van Genuchten, 1980). Water entry suction, which is necessary to reproduce preferential flow (Hirashima et al., 2014a), was measured and formulated as a function of grain size following the approach of Katsushima et al. (2013).

h h 2017/9/18 16:13
削除: a, ... [1]
h h 2017/8/27 17:45
書式変更: フォント:(英) Times New Roman, フォントの色: 自動
h h 2017/9/18 15:58

上へ移動 [1]: In this study, simulations of liquid water infiltration into layered snowpacks were performed by reproducing the laboratory experiments of Avanzi et al. (2016).

hirashima hiroyuki 2017/7/26 10:47
削除: multi

hirashima hiroyuki 2017/9/12 16:50
削除: .

2.2 Comparative simulation

Hirashima et al. (2014a) performed infiltration simulations within columns with only one layer of snow. A number of multi-layer simulations were also tested (Hirashima et al., 2013, 2014b); however, they were performed in 2D and were not validated with observations. In this study, validation of the water transport model for layered snow was performed using

5 observations of infiltration patterns performed using dye trace experiments (Avanzi et al., 2016). In these experiments, snow samples were prepared in a cold room at -20°C using refrozen melt forms. Snow was packed in a cylindrical container composed of several acrylic rings; the height and diameter of the rings were 20 mm and 50 mm, respectively. Each sample was composed of two layers: the upper layer was 10 cm thick, the lower layer was either 8 or 10 cm thick (see Avanzi et al., 2016). Then, samples were moved to a second cold room at 0°C and stored for at least 12 h to reach initial conditions of dry
10 snow at 0°C . All samples were characterized by a finer-over-coarser layering (i.e. the upper layer was created using a smaller grain size than the lower one), which aimed to reproduce capillary barriers. The three classes of snow grain size included fine (0.25–0.5 mm), medium (1.0–1.4 mm), and coarse (2.0–2.8 mm). While this definition is convenient for the scope of this study, it is not consistent with the International Classification proposed by Fierz et al. (2009). Three water input rates were considered: 10 mm/h, 30 mm/h, and 100 mm/h. In total, 9 experiments were performed (i.e., one for each grain
15 size/input rate combination).

The 3D simulations had dimensions of 5, 5, and 20 cm in the x, y, and z directions, respectively. The voxels were 5 mm on the sides. Voxels of more than 2.5 cm from the central axis were treated as an impermeable wall, which ensured that the simulated shape was columnar. Snow densities, grain sizes, and rates of water supply were set to the same values as in the laboratory experiments. Grain size distributions were not measured: instead, for fine and medium snow we used the median 20 grain sizes obtained by Katsushima et al. (2013) using the same sieves (0.4₁ and 1.5 mm, respectively). Grain size for coarse snow was determined assuming it to be two times the median medium grain size (2.9 mm). Note that grain size is expressed in two-digit accuracy, but the simulations were performed using a four-digit accuracy, as in Avanzi et al. (2016). As a measurement of horizontal structural heterogeneity, we estimated the standard deviation following the approach of Hirashima et al. (2014a), who estimated that the standard deviation of grain size is 20% of the median grain size 25 (Katsushima et al., 2013). In this simulation, heterogeneity of snow density was not provided. As with the cases of laboratory experiments, grain size combinations in the simulation were fine-over-coarse snow (FC), fine-over-medium snow (FM), and medium over coarse snow (MC). Values of snow density and water supply rates are shown in Table 1.

The evaluation of simulations focused on the thickness of the ponding layer at the textural interface, on the liquid water distribution, on the wet snow fraction at different heights, and on different timings that are relevant for liquid water 30 movement in snow. These include water arrival at the interface between layers, breakthrough of preferential flow in the lower layer, and arrival of liquid water at sample base. Data of liquid water content, wet snow fraction, and thickness of the ponding layer were measured by Avanzi et al. (2016), whereas timings were obtained from available video recordings of the experiments. A small difference (mean of 0.5 min, maximum of 3 min for FC1) was found between the arrival times from

h h 2017/8/27 12:06
削除: In these experiments, snow was packed in a cylindrical container composed of several acrylic rings (height equal to 20 mm, diameter equal to 50 mm). Nine or ten acrylic rings were stacked to store 10 cm of upper layer snow and 8 or 10 cm of lower layer snow. All samples were characterized by finer-over-coarser layering (i.e., the upper layer was created using a smaller grain size than the lower layer), which aimed to reproduce capillary barriers. Three types of snow grain size included fine (0.25–0.5 mm), medium (1.0–1.4 mm), and coarse (2.0–2.8 mm).
h h 2017/9/16 18:43
削除: , (
h h 2017/9/16 18:43
削除:)
h h 2017/8/27 18:15
削除: 06
h h 2017/8/27 18:15
削除: 463
h h 2017/9/16 18:44
削除: as
h h 2017/8/27 18:16
削除: 26
h h 2017/8/27 12:08
削除: The evaluation of simulations focused on the thickness of the ponding layer at the textural interface, on the liquid water distribution, on the wet snow fraction at different heights, and on the timing of water arrival at the interface between layers, of breakthrough of preferential flow in the lower layer, and of arrival of liquid water at sample base.
h h 2017/9/16 18:45
削除: utes
h h 2017/9/16 18:46
削除: utes

video recordings and those in Avanzi et al. (2016); data from videos were used here for consistency with the other timings (see Table 2). The simulated timings of water arrival at the interface, entering the lower layer, and arrival at the snow base refer to the lowest elements in the upper layer, the top three elements in lower layer, and the lowest elements of the sample, respectively. The water content in the top three elements of the lower layer was used to determine the timing of breakthrough because preferential flow began immediately after the water content of one of these elements became larger than zero.

3 Simulation results

3.1 Water percolation through preferential flow paths and capillary barrier

Some images of the development of capillary barriers and preferential flow for FC1 are shown in Fig. 1. These figures show the front surfaces 20 s after the beginning of the experiment (a and e), at the arrival time of water at the interface between layers (b and f), at the time of breakthrough of preferential flow into the lower layer (c and g) and at the arrival time at the snow base (d and h). The simulation results showed faster than measured arrival of water at the boundary (Table 2), which implied an overestimation of vertical velocity in the model's preferential flow for this experiment (Fig. 1). In Fig. 1b and 1f, elapsed times were indeed 35 and 17 min, in the laboratory experiment and simulation, respectively. One possible cause is the underestimation of the area of preferential flow path, which was also considered by Hirashima et al. (2014a). A smaller path area would increase conductivity because liquid water would be more concentrated and push water towards the boundary faster. After arrival at the boundary, we found that liquid water ponded above the boundary owing to a capillary barrier. In images from just before the formation of preferential flow in the lower layer (Fig. 1c and g), the elapsed time was 85 min, in the laboratory experiment and 79 min, in the simulation (relative difference of 7% of the measurement value, i.e. in good agreement).

The size of laboratory experiments was restricted by the time needed to prepare and perform each of them. Also, the diameter of samples was consistent with the thickness of similar experiments in soils (see e.g. Hill and Parlange, 1972), whereas Avanzi et al. (2017) showed that preferential flow may be intrinsically coupled with wet-snow metamorphism at grain scale. This suggests that small-scale experiments are appropriate to understanding the physics of this process in snow. Nonetheless, the relatively small scale of these experiments may introduce some domain size effect. In natural snow, water flow shows lateral spreading, especially at capillary barriers, whereas experiments with small size may partially perturb the natural flow on snow and therefore change vertical flow owing to artificial edges. This may increase the ratio of preferential flow path area, decrease the arrival time at the base, and decrease natural ponding amount at the capillary barrier. In terms of comparison between simulations and experiments, this effect was offset by using the same domain conditions.

The times of liquid water arrival at the base following the formation of preferential flow through the lower layer were 4 and 1 min, in the laboratory experiment and simulation, respectively. On this basis, we calculated the propagation rate of the preferential flow path to be 0.4 and 1.6 mm/s for the laboratory experiment and simulation, respectively.

hirashima hiroyuki 2017/8/8 19:18
削除: meshes
h h 2017/9/16 18:47
削除: 3
hirashima hiroyuki 2017/8/8 19:18
削除: meshes
hirashima hiroyuki 2017/8/8 19:19
削除: meshes
h h 2017/8/27 15:43
削除: 3
hirashima hiroyuki 2017/8/8 19:18
削除: meshes
hirashima hiroyuki 2017/7/28 16:56
削除: expended
hirashima hiroyuki 2017/8/8 19:19
削除: meshes
h h 2017/9/18 16:19
削除: As an example, s
hirashima hiroyuki 2017/8/3 17:03
削除: after
h h 2017/9/16 19:17
削除: ec
hirashima hiroyuki 2017/8/3 17:03
削除: from
h h 2017/8/27 16:48
削除: anticipated
h h 2017/9/16 19:18
削除: s
h h 2017/9/16 19:18
削除: utes
h h 2017/9/16 19:18
削除: utes
h h 2017/9/16 19:18
削除: utes
h h 2017/9/16 19:19
削除: ,
h h 2017/9/16 19:19
削除: ,
h h 2017/9/17 13:28
削除: utes
hirashima hiroyuki 2017/8/4 9:46
削除: This is one order of magnitude smaller than mean speed of preferential flow (11.2 mm/s) measured by Walter et al. (2013) using fluorescent particle tracking velocimetry; however, this was tested with a much larger water supply rate (3600 mm/h).

In the other experiments, the temporal dynamics of preferential flow formation and water ponding at the interface were generally well reproduced (Table 2; Fig. 2). The root mean square error (RMSE), the slope of a regression line with intercept equal to 0, and the correlation coefficient (r^2) between the simulated and measured timings were 7.8 min., 0.97 and 0.93, respectively. As timings were measured using frontal movies, we were sometimes unable to evaluate the timing of preferential flow formation within a sample. For example, in the case of MC1, preferential flow formed on the side of the sample that was not visible from the frontal position of the camera. Thus, the frontal movie did not show the preferential flow path in lower layer, whereas horizontal spreading of water at the sample base allowed us to detect the arrival time with a reasonable precision. It follows that for this sample we cannot determine the timing of preferential flow initiation. Therefore, estimated timings from laboratory experiments may contain a delay. Overall, simulated and measured timings were consistent, which confirms that if snow parameters (e.g., snow density and grain size) are known, the arrival time of liquid water can be predicted using this model.

h h 2017/9/17 13:29
削除: R
h h 2017/9/17 13:29
削除: M
h h 2017/9/17 13:29
削除: S
h h 2017/9/17 13:29
削除: E
h h 2017/8/27 17:06
削除: (e.g., experiment MC1);
h h 2017/8/27 17:06
削除: t
h h 2017/9/17 13:35
削除: coincided wel
h h 2017/9/17 13:37
削除: ,

3.2 Thickness of the water ponding layer

Avanzi et al. (2016) measured the thickness of the upper layer affected by ponding at the end of each experiment. In their results for FC and FM experiments, the liquid water content on the layer boundary was about 33% to 36% (2-cm vertical resolution). The volume of ponded water was smaller for MC experiments. Laboratory experiments also showed that the thickness of the water ponding layer is not strongly connected to the water input rate. In our simulations, the influence of water input rate on the thickness of the water ponding layer was also small; however, the influence of grain size was significant (Table 3). The thickness of ponded water at the interface was well reproduced for the FC experiments, but was overestimated for FM experiments and underestimated for MC experiments. For MC experiments, up to 1 cm of ponding was shown in laboratory experiments, while simulated results showed a thickness of less than 0.5 cm.

h h 2017/9/17 13:37
削除: -
h h 2017/9/17 13:38
削除: of data
h h 2017/9/18 16:20
削除: confirmed
h h 2017/9/18 16:20
削除: Here

3.3 Horizontal cross section

During laboratory experiments, Avanzi et al. (2016) measured wet snow fractions at the boundary between consecutive rings using photos of the top surface of the ring below the boundary. Samples were likely slightly compressed during experiments owing to increased densification caused by wetting (Marshall et al. 1999), even though this was not noticeable. Because the model does not include settling, we chose to compare data with simulations of the inferior surface of the ring above the boundary, which returned more consistent results. At the interface between layers, most of the area of each section was wet, except for the medium over coarse samples (Fig. 3). For the other sections, only a fraction was found to be wet. This pattern was well simulated (Fig. 4); although simulated wet snow areas were smaller than those measured especially in areas characterized by preferential flow. Similar underestimation by the model was also observed by Hirashima et al. (2014a).

3.4 Water content distribution

Our simulations were performed with 5 mm voxels. Simulated water contents from all voxels at a given height were averaged to obtain the water content profile. In laboratory experiments, water content profiles were obtained with a resolution of 2 cm (Fig. 5). The results showed that for the FC and FM experiments, the liquid water content was overestimated near the interfaces between snow layers in the upper fine layer but underestimated in other areas. The impact of water supply rate on the water content in capillary barriers was small in both simulations and experiments. Overall, simulations and observations showed good agreement in that liquid water content increased with depth in the finer layer, peaked at the interface between layers, and decreased in the lower layer.

10 4 Discussion

4.1 Comparison with SNOWPACK

The numerical snowpack model SNOWPACK can also be used to reproduce dynamics observed during laboratory experiments. While Avanzi et al. (2016) compared their results with SNOWPACK-3.3.0 simulations at the end of each 15 experiment (i.e. at the observed/modelled arrival time of water at the snow base), a direct comparison between models can be made for any point of time. Here, we compared temporal changes in the simulated water content profiles for SNOWPACK and the 3D model in order to assess the role played by a simulation of preferential flow in controlling liquid water distribution in snow (Fig. 6; Fig. S1); therefore, we used both the matrix-flow multi-layer implementation of the Richards 20 Equation RE-model (Wever et al., 2015) and a dual domain approach considering preferential flow, henceforth DDA-model (Wever et al., 2016b; Würzer et al., 2017). Resolution of SNOWPACK was set to 5 mm to match with the resolution of the 3D model.

In the SNOWPACK RE-model simulations, liquid water content in the upper layer gradually increased with time at all 25 positions (Fig. 6a; Fig. S2), and the water content near the boundary was relatively large. The difference in water content between the layer interface and the upper part was underestimated when compared with experimental results, which confirms a marked spatial heterogeneity in liquid water distribution. On the other hand, 3D simulation showed that liquid water quickly ponds at the boundary, which is consistent with the experimental observations (Fig. 6e and f; Fig. S4). Such an effect is obtained owing to preferential flow, which allowed water to move in small fingers and to reach deeper locations, even when most of the upper snow remained dry. The water ponding layer thickened until the formation of a preferential flow path in the lower layer. After preferential flow arrived at the snow base, expansion of the water ponding layer stopped. 30 The difference in water content between layer interface and the upper part was overestimated in comparison with the experimental observations. In case of the SNOWPACK DDA-model (Fig. 6c and d), liquid water arrived quickly at the

hirashima hiroyuki 2017/9/20 16:34
削除: a matrix-flow multi-layer model

h h 2017/9/18 16:24
削除: the

h h 2017/9/18 16:25
削除: chose an approach of the
h h 2017/9/18 16:26
削除: in SNOWPACK

hirashima hiroyuki 2017/9/11 9:53
削除: that did not consider preferential flow as a benchmark (i.e., the matrix-flow multi-layer implementation of the Richards Equation in SNOWPACK; Wever et al., 2015).

h h 2017/9/17 13:45
削除: the
hirashima hiroyuki 2017/9/11 9:56
削除: S1
h h 2017/9/18 16:29
削除: s
h h 2017/9/17 13:49
削除: thanks
h h 2017/9/18 16:29
削除: s

boundary and started to pond. Then, infiltration in matrix flow started. During ponding, infiltration into the lower layer was started in preferential flow area with a very small water content (about 0.01% initially, and then gradually increasing). Although liquid water arrival at the snow base was faster than that in the RE-model, water ponding continued even after the liquid water arrival because the infiltration rate was too small in the lower layer. After a large amount of water ponded above the layer boundary, liquid water infiltration in matrix flow in the lower layer was started and the volume of water ponded in the upper layer started to decrease (e.g. in FM3, water content in upper layer at 2t was decreased from 5/3t; Fig. S3d). The RMSE for liquid water content profiles at (measured) arrival time are 0.107, 0.107 and 0.094 for SNOWPACK RE-model, DDA-model and 3D model, respectively. While both SNOWPACK schemes yield the same RMSE, the 3D model returns a slightly smaller value.

For arrival times, the 3D and SNOWPACK DDA-model obtained greater accuracy than the SNOWPACK RE-simulations (Fig. 7), which again suggests the importance of considering preferential flow. Causes of delay in 1D models include both slow infiltration of matrix flow and overestimation of water ponding at the capillary barrier (Fig. 6). In terms of arrival time, delay was resolved to some degree by considering preferential flow in the SNOWPACK model. However, SNOWPACK-DDA-model is still prone to overestimating the total amount of water that pond at the interface between layers. These comparisons between the SNOWPACK, 3D model and laboratory experiments demonstrate the need to improve existing theories of water infiltration in snow.

The theory of water transport in the SNOWPACK RE-model is based on gravity drainage column experiments that neglect water entry suction (i.e., experiments performed using wet snow; Yamaguchi et al., 2012). In contrast, the 3D model and SNOWPACK DDA-model includes an attempt to simulate the infiltration process into initially dry snow using water entry suction (where we define dry snow as that with a lower liquid water content than the irreducible water content), which is key to reproducing fingers (Hirashima et al., 2014a). Under these conditions, the van Genuchten model could only be used with additional assumptions (Hirashima et al., 2014a). Accordingly, we assumed that dry snow had a threshold suction equal to water entry suction. Future work will focus on improving this approach; for example, water entry suction may be related to the suction-wetness profile of a wetting water retention curve (Avanzi et al., 2016), which has not yet been parameterized. Furthermore, unsaturated conductivity tends towards zero in dry conditions, but extensive observations of unsaturated conductivity in snow are missing.

4.2 Wet snow ratio and preferential flow path area.

The main purpose of the development of this model is to better understand 3D patterns of water infiltration in snow and, thus, resolve the delay of the arrival time as a limitation of matrix-flow models. The simulation results showed that the model can reproduce preferential flow and capillary barriers and, consequently, provide reliable estimations of the arrival time of water at the sample base. On the other hand, the model underestimated the simulated preferential flow area. In terms of effect on arrival time, this underestimation is not a serious problem because the travel time through the preferential flow area was

hirashima hiroyuki 2017/9/20 16:40

削除: s,we .

hirashima hiroyuki 2017/9/11 11:15

削除:

hirashima hiroyuki 2017/9/11 11:18

削除: A more detailed comparison of arrival times between models will be, however, the object of a future study that includes the dual-domain approach, which considers preferential flow in 1D; this process is expected to play a key role for arrival times.

h h 2017/9/17 14:14

削除: ,

h h 2017/9/17 14:17

削除:

h h 2017/9/17 14:19

削除:

h h 2017/9/17 14:19

削除:

h h 2017/9/18 16:43

削除: in

h h 2017/8/27 17:13

削除: In practice, t

h h 2017/9/17 14:32

削除: is

h h 2017/9/18 16:43

削除: include

h h 2017/9/17 14:33

削除: (see the previous section)

h h 2017/9/18 16:44

削除: it

short (Table 2); however, it may represent a problem for long-term simulations, especially when estimating the transition from a predominantly dry snow to a predominantly wet snow.

According to the simple model of Baker and Hillel (1990), the wetted fraction of the sublayer in a finer-over-coarser transition depends on water input rate and unsaturated conductivity during steady vertical infiltration. Horizontal expansion 5 of preferential flow also depends on infiltration along the horizontal direction. As the direction of water flow depends on gravity (vertical) and capillarity, movement in the horizontal direction may be impeded if simulated capillary gradients are small. For example, the fact that fine snow in experiments had larger preferential flow paths than coarse snow was probably due to a greater heterogeneity in capillarity in fine snow (Avanzi et al., 2016).

We performed sensitivity tests to estimate the relevance of vertical and horizontal movement for different types of snow, in 10 which we calculated which voxel (left, right, front, back, up, down) was easiest to infiltrate from a generic voxel as a function of gravity or water entry suction. We found that the ratios of the water moving to the lower voxel were 24.3%, 15 38.8% and 60.7% for fine, medium and coarse snow, respectively. When this ratio is large (e.g. coarse snow), water moves downward, and consequently the preferential flow path areas become small. Where there is no gravitational force, the ratio would be 16.7% while for fine snow the ratio of water moving to the lower voxel was 24.3%. Nevertheless, the simulated mean wet snow area was small even for fine snow (e.g. 4.8% in FC1 and 22% in FC3, excluding the ponding area). As the simulated wet snow area is smaller than the measured one, this model may still underestimate the effective cross-sectional area of infiltration. This will be the subject of future research.

In this model, water entry suction was used as a threshold for liquid water infiltration into dry snow. However, in the measured water absorption curve of Adachi et al. (2012), the relationship between suction and liquid water content was non- 20 linear and hysteretic (see Section 4.1). This simplified condition for infiltration into dry snow may lead to an underestimation of the expansion of preferential flow. Neglecting quick metamorphism in preferential flow paths (Avanzi et al. 2017) may represent another cause of underestimation of preferential flow path size as grain growth promotes lateral spreading of water and expansion of paths. Although this model includes grain growth following Brun et al. (1989) and Tusima (1977), modelling some specific conditions such as wet snow metamorphism at the boundaries between preferential flow paths and 25 drier snow is still an open issue. Also, existing observations of wet-snow metamorphism have been mainly performed in static conditions, which means that the coupling between grain growth and flowing water is still poorly understood. This represents a further unknown for models of liquid water in snow.

The number of preferential flow paths can also promote the expansion of the wet snow area (Schneebeli, 1995). In our model, liquid water preferred to infiltrate snow along the same path; therefore, preferential flow paths did not increase unless the 30 amount of liquid water supply also increased. Also, compaction by wet snow metamorphism could change the balance of force distribution and create new pathways for liquid water. This underestimation may also be related to uncertainties in the computation of unsaturated water conductivity in initially dry snow and/or in the rule used to calculate the conductivity between voxels. New techniques to measure the development of preferential flow paths can help to model these processes and further experiments in this direction are, therefore, highly needed.

h h 2017/9/17 14:34
削除: the
h h 2017/9/18 16:45
削除: difference
h h 2017/9/17 14:35
削除: ity by
h h 2017/9/18 16:46
削除: heterogeneity
h h 2017/9/17 14:37
削除: as
h h 2017/9/17 14:37
削除: ,
h h 2017/8/27 17:16
削除: not large
hirashima hiroyuki 2017/9/13 11:33
削除: the
h h 2017/8/27 17:17
削除: These results suggest that infiltration for dry snow is too vertically strict in this version of the model.

4.3 Impact of grain size on water infiltration process

5 Grain size is one of the key parameters for water infiltration process. Nevertheless, grain sizes cannot be measured at high resolution in nature (typically measured to 0.1mm); therefore, the sensitivity of model results with fluctuation in grain size is informative. In this discussion, sensitivity experiments for grain sizes fluctuating by 0.1mm for the upper layer and lower layers were performed. Simulation results of in terms of thickness of water ponding layer, water content profile, and arrival time are shown in Fig. 8.

10 The thickness of water ponding over the interface between layers is usually increased in cases of smaller upper grain size and greater lower grain size (Fig. 8a). Grain size thus significantly influences the water ponding layer. Differences in water ponding thickness between an real and decreased grain size on the upper layer ranged from 7% to 48% in case of fine over coarse and fine over medium. On the other hand, differences for fluctuations of the lower layer were less than 8% in eight out of nine cases (Fig. 8a), sample MC1 being the only exception (22%). This difference suggests that the upper layer plays a pivotal role in capillary barriers. An increase in the water ponding layer in the case of decreased upper fine grains can also be clearly identified in the water content profile (Fig. 8b). Decreasing the size of upper fine grains not only increases the thickness of the water ponding layer, but also increases water content outside of the water ponding layer. For example, decreasing upper layer grain size in FC1 (Fig 8b) yields a total water contents from 15.5–19.5 cm height that is about 2.6 times those of the original, non-fluctuating case. This reflects the increasing area of wet snow in the upper layer. The area of the preferential flow path is sensitive to both grain sizes, especially for fine snow (Katsushima et al., 2013; Hirashima et al., 2014). Fluctuations in water content profile driven by grain size were also seen in case of MC1, but were not significant (see Fig. 8c). Figures of water content profiles for other cases are shown in the supplement (Fig. S5).

15 Variations in grain size also affect arrival time at the snow base (Fig. 8d). Differences in arrival time between increasing grain size and decreasing grain size for the upper layer was more than 50% in the cases of FC1 and FM1. These results suggest that the accuracy of measured grain size is important to estimate water infiltration, especially for fine grains. In the parameterizations for water entry suction used in our 3D model and dual domain approach, grain size was determined 20 circumstantially providing a grain size distribution measured from individual grains. Since measuring individual grain size requires great care, methods requiring less care and the ability to obtain grain size parameters with high degrees of accuracy are necessary for more accurate models. Development of measuring methods for specific surface area may improve estimation accuracy and contribute the study of water infiltration processes.

hirashima hiroyuki 2017/9/20 16:53

削除: generally

h h 2017/9/2 13:33

削除: 3

h h 2017/9/18 16:57

削除: Recently, a dual domain approach has been developed to consider the effects of preferential flow in 1D models (Wever et al., 2016b; Würzer et al., 2017). While this approach has proven useful for avalanche prediction and hydrological simulations, some assumptions are needed to model heterogeneous processes using 1D models. As these assumptions are aimed at parameterizing 3D processes in 1D, t

h h 2017/9/18 16:58

削除: model

improve the parameterization of preferential flow area, as in Wever et al. (2016b). In the future, a thorough parameterization of hysteresis in snow and the better reconstruction of the expansion of preferential flow path area will improve the accuracy of 3D models and allow for an advanced estimation of preferential flow area in 1D models. Wever et al. (2016b) also suggested that 3D models should analyse heat exchange around the preferential flow path; therefore, future developments of our model will consider heating and melt-freeze processes (e.g., the model of Leroux and Pomeroy, 2017). For this, laboratory experiments of ice layer formation will be needed for validation.

Another possible improvement to the model would be the parameterization of quick grain growth at saturation, which would be necessary for simulating the structural evolution of areas affected by ponding. Grain growth causes an abrupt decrease in suction and consequently reduces the water content at the ponding layer. The water content of the upper layer at $2t$ was smaller than that at $5t/3$ (Fig. 6a) owing to a decline of suction due to grain growth. In the first version of the SNOWPACK model, the Brun et al. (1989) equation was used for estimating grain growth; however, this formula is based on data with small water content and application to saturated conditions may overestimate grain growth. To avoid this, Hirashima et al. (2010, 2014a), used the equation of Tusima (1978) to constrain the upper limit of grain growth rate. Although this formula is based on data measured under saturated conditions, grain growth remains limited for a short time scale, such as occurred during these experiments. The grain growth equation of Tusima (1978) was formulated using data for 200 hours, but it did not focus on the first 1 hour; therefore, grain growth over short time periods and under saturated conditions remain unclear. Raymond and Tusima (1979), Wakahama (1968), and Colbeck (1973) all focused on wet snow metamorphism under saturated conditions, but they did not focus on the first hour of the experiments. Extending the existing parameterizations of wet snow metamorphism for small timescales will improve simulation accuracy with regards to the development and disappearance of water ponding by capillary barriers. Also, a correct simulation of grain growth will lead to correctly estimating the lateral spreading of water, which will improve the accuracy of the prediction of preferential flow path size. Our results show that this model is capable of reproducing detailed water infiltration at sample scale (i.e., considering micro-scale heterogeneity). On the other hand, the intrinsic scale of this process and computational efforts mean that it is still not suitable for basin-scale simulations. This limitation could be overcome by synergies with existing physics-based hydrologic models for snow-dominated catchments; for example, Alpine 3D (Lehning et al., 2006). Currently, SNOWPACK is used as a part of Alpine3D for simulation of accumulation/ablation patterns of snowpack. In this study, comparisons between laboratory experiments, a 3D model, and SNOWPACK were performed and contributed to highlighting model limitations and possible avenues of future developments (e.g. an underestimation of flow path cross-sections). While a 3D model cannot reproduce the entire range of natural variability of liquid water flow in snow, it can help to replicate and understand this process in conditions that are difficult for experiments (e.g., larger sample sizes and/or a more complex stratigraphy). This may contribute to defining new parameterizations for dual domain approaches that could be then fully included in catchment-scale models. Also, we will try to apply this model at the basin scale by increasing the element size. While this will hamper the representation of single preferential fingers, we expect the model to be able to correctly reproduce other

h h 2017/9/18 17:08

削除: more exhaustive

h h 2017/9/17 18:38

削除: a

h h 2017/9/17 18:38

削除: ,

h h 2017/8/27 17:58

削除: [

h h 2017/8/27 17:58

削除: 6]

h h 2017/9/17 18:42

削除: , t is the measured arrival time

h h 2017/9/17 18:45

削除: s

h h 2017/9/17 18:45

削除: also

relevant features of water flow at slope scale such as lateral flow. This could help to understand liquid water flow around concave/convex portions of the landscape.

5 Conclusions

5 Validation of simulations for capillary barrier formation and subsequent preferential flow development was performed using a 3D water transport model. Overall, the infiltration process into dry snow was well reproduced, and in particular the timing of liquid water arrival at the snow base was accurate. A detailed comparison of wet conditions in the snow column was performed to check accuracy and identify shortcomings in the model. The model accurately reproduced: (a) the onset of preferential flow in initially dry snow; (b) the ponding of liquid water above the boundary of snow layers by a capillary barrier, for which the ponded water volume was larger at the boundary of fine over coarse and fine over medium snow layers than it was at the boundary of medium over coarse snow layers.

10 Model discrepancies included: (a) an underestimation of liquid water content and wet snow area in preferential flow path areas, and (b) overestimation of water ponding volume at the layer boundary in experiments FC and FM, but underestimation in experiment MC. Future improvements to the model will include improving the water entry process for dry snow,

15 measurements of water content profile for capillary rise, and direct measurements of preferential flow path formation.

The advantage of this model over 1D models is the consideration of 3D heterogeneous infiltration into dry snow. An explicit simulation of preferential flow also returns a reliable estimation of liquid water arrival at the snow base. However, improvements are needed to ensure that the model works over both long and short time periods. An accurate reproduction of the transition from a dry-snow dominant to a wet-snow dominant condition is an important step in upgrading this model to a

20 full 3D numerical snowpack model.

h h 2017/9/18 10:46
削除: .
h h 2017/9/18 10:46
書式変更: 見出し 3
h h 2017/9/18 10:48
削除: threemulti-dimensional

Acknowledgement

This study was part of the Research on Advanced Snow Information and its Application to Disaster Mitigation project, and was supported by JSPS, KAKENHI (Grant Numbers JP15H01733). Fruitful discussions about this work with Y. Ishii and T. 25 Katsushima are acknowledged. We would like to acknowledge N. Wever, who helped with the SNOWPACK simulations with preferential flow. We thank the members of the Snow and Ice Research Center for their advice and discussion. We are grateful to M. Miura, who assisted with our research.

h h 2017/9/18 10:48
削除: “
h h 2017/9/18 10:48
削除: ”

References

Adachi, S., Yamaguchi, S., Ozeki, T., and Kose, K.: Hysteresis in the water retention curve of snow measured using an MRI system, Proceedings, International Snow Science Workshop, Anchorage, Alaska, 918-922, 2012.

Avanzi, F., Hirashima, H., Yamaguchi, S., Katsushima, T., and De Michele, C.: Observations of capillary barriers and preferential flow in layered snow during cold laboratory experiments, *The Cryosphere*, 10 (5), 2013–2026, doi:10.5194/tc-10-2013-2016.

[Avanzi, F., Petrucci, G., Matzl, M., Schneebeli, M., and De Michele, C.: Early formation of preferential flow in a homogeneous snowpack observed by micro-CT, *Water Resour. Res.*, doi: 10.1002/2016WR019502, 2017.](#)

Baggi, S. and Schweizer, J.: Characteristics of wet-snow avalanche activity: 20 years of observations from a high alpine valley(Dischma, Switzerland), *Natural Hazards*, 50, 97-108, 2008.

[Baker, R. S., and Hillel, D.: Laboratory tests of a theory of fingering during infiltration into layered soils, *Soil Sci. Soc. Am. J.* 54, 20-30, 1990.](#)

Brun, E., Martin, E., Simon, V., Gendre, C., and Coleou, C.: An energy and mass model of snow cover suitable for operational avalanche forecasting, *J. Glaciol.*, 35, 333–342, 1989.

15 Brun, E., and Ray, L.: Field study on snow mechanical properties with special regard to liquid water content, in Avalanche formation, movement and effects, Proceedings of the Davos Sympsiun, September 1986, IAHS, publ, 162, 1987.

Calonne, N., Geindreau, C., Flin, F., Morin, S., Lesaffre, B., Rolland du Roscoat, S., and Charrier, P.: 3-D image-based numerical computations of snow permeability: links to specific surface area, density, and microstructural anisotropy, *The Cryosphere*, 6, 939–951, doi:10.5194/tc-6-939-2012, 2012.

20 [Carmagnola, C. M., Morin, S., Lafaysse, M., Domine, F., Lesaffre, B., Lejeune, Y., Picard, G., and Arnaud, L.: Implementation and evaluation of prognostic representations of the optical diameter of snow in the SURFEX/ISBA-Crocus detailed snowpack model, *The Cryosphere*, 8, 417–437, doi:10.5194/tc-8-417-2014, 2014.](#)

Clifford, K. H. and Stephen, W.: Capillary barrier performance in heterogeneous porous media, *Water resources research*, 34, 603-609, 1998.

25 Colbeck, S. C.: A theory of water percolation in snow, *J. Glaciol.*, 11, 369–385, 1972.

Colbeck, S. C. and Davidson, G.: Snow percolation through homogeneous snow, in: Int. Symp. on the Role of Snow and Ice in Hydrology, Banff, AB, Canada, 1972.

Colbeck S. C.: Theory of metamorphism of wet snow, CRREL Res. Rep. 313, 1973

Colbeck, S. C.: The capillary effects on water percolation in homogeneous snow, *J. Glaciol.*, 13(67), 85–97, 1974a.

30 Colbeck, S. C.: Water flow through snow overlying an impermeable boundary, *Water Resour. Res.*, 10, 119–123, doi:10.1029/WR010i001p00119, 1974b.

Colbeck, S. C.: An analysis of water flow in dry snow, *Water Resour. Res.*, 12, 523-527, doi:10.1029/WR012i003p00523, 1976.

Colbeck, S. C.: Theory of metamorphism of dry snow, *J. Geophys. Res.*, 88, 5475-5482, 1983.

Daanen, R. P. and Nieber, J. L.: Model for Coupled Liquid Water Flow and Heat Transport with Phase Change in a Snowpack, *J. Cold Reg. Eng.*, 23, 43-68, 2009.

Dunne, T., Price, A.G., and Colbeck, S.C.: The Generation of Runoff From Subarctic Snowpacks, *Water Resour. Res.*, 12, 5 677-685, 1976.

[Eiriksson, D., Whitson, M., Luce, C. H., Marshall, H. P., Bradford, J., Benner, S. G., Black, T., Hetrick, H., and McNamara, J. P.: An evaluation of the hydrologic relevance of lateral flow in snow at hillslope and catchment scales, *Hydrol. Process.*, 27, 640-654, doi:10.1002/hyp.9666, 2013.](#)

[Fierz, C. and Fo'hn, Paul M. B.: Long-Term observation of the water content of an alpine snowpack, Proceedings of the 10 International Snow Science Workshop; Snowbird, Utah, USA; pp. 117-131, 1994.](#)

Fierz, C., Armstrong, R. L., Durand, Y., Etchevers, P., Greene, E., McClung, D. M., Nishimura, K., Satyawali, P. K., and Sokratov, S. A.: The International Classification for Seasonal Snow on the Ground, Tech. rep., IHP-VII Technical Documents in Hydrology N 83, IACS Contribution N 1, UNESCO-IHP, Paris, 2009.

[Hill, D. E., and Parlange, J-Y.: Wetting front instability in layered soils. *Soil Sci. Soc. Am. J.*, 36, 697-702, 1972.](#)

15 Hirashima, H., Yamaguchi, S., Sato, A., and Lehning, M.: Numerical modeling of liquid water movement through layered snow based on new measurements of the water retention curve. *Cold Reg. Sci. Technol.*, 64, 94-103, doi:10.1016/j.coldregions.2010.09.003, 2010.

Hirashima, H., Yamaguchi, S. and Katsushima, T.: A multi-dimensional water transport model to reproduce preferential flow in the snowpack, International Snow Science Workshop Grenoble-Chamonix Mont-Blanc, 31-37, 2013.

20 Hirashima, H., Yamaguchi, S. and Katsushima, T.: A multi-dimensional water transport model to reproduce preferential flow in the snowpack, *Cold Reg. Sci. Technol.*, 108, 80-90, 2014a.

Hirashima, H., Yamaguchi, S., and Ishii, Y.: Simulation of liquid water infiltration into layered snowpacks using multi-dimensional water transport model, ISSW proceedings, Banff, 48-54, 2014b.

Illangasekare, T.H., Walter, Jr., R.J., Meier, M.F., and Pfeffer, W.T.: Modeling of meltwater infiltration in subfreezing snow.

25 Water Resour. Res., 26, 1001-1012, doi:10.1029/WR026i005p01001, 1990.

Ito, Y., Matsushita, H., Hirashima, H., Ito, Y., and Noro, T.: Change in snow strength caused by rain, *Ann. Glaciol.*, 53 (61), 1-5, 2012.

Jordan, R., Albert, M.R., and Brun, E.: Physical processes within the snow cover and their parameterization. In: Armstrong, R., Brun, E. (Eds.), *Snow and Climate*. Cambridge University Press, 12-69, 2008.

30 [Kämpf, M., Holfelder, T. and Montenegro, H.: Identification and parameterization of flow processes in artificial capillary barriers. *Water Resour. Res.*, 39, doi:10.1029/2002WR001860, 2003.](#)

Katsushima, T., Yamaguchi, S., Kumakura, T., and Sato, A.: Experimental analysis of preferential flow in dry snowpack, *Cold Reg. Sci. Technol.*, 85, 206-216, doi:10.1016/j.coldregions.2012.09.012, 2013.

Kittelmann, R.: Wet slab instability, in: Proceedings of the 1984 International Snow Science Workshop, 102-108, 1984.

hirashima hiroyuki 2017/7/24 10:15

削除:

hirashima hiroyuki 2017/9/12 12:14

下へ移動 [2]: Kämpf, M., Holfelder, T. and Montenegro, H.: Identification and parameterization of flow processes in artificial capillary barriers, *Water Resour. Res.*, 39, doi:10.1029/2002WR001860, 2003.

hirashima hiroyuki 2017/9/12 12:14

移動(挿入) [2]

Lehning, M., Bartelt, P., Brown, B., Fierz, C., and Stayawali, P.: A physical SNOWPACK model for the Swiss avalanche warning Part II. Snow microstructure, *Cold Reg. Sci. Technol.*, 35, 147-167, 2002.

Lehning, M., Völksch, I., Gustafsson, D., Nguyen, T. A., Stähli, M., and Zappa, M.: ALPINE3D: a detailed model of mountain surface processes and its application to snow hydrology. *Hydrol. Process.* 20, 2111–2128, 2006.

5 Leroux, N. R. and Pomeroy, J. W.: Modelling capillary hysteresis effects on preferential flow through melting and cold layered snowpacks, *Adv. Water Resour.*, 107, 250-264, doi: 10.1016/j.advwatres.2017.06.024, 2017.

Marsh, P., and Woo, M.: Meltwater movement in natural heterogeneous snow covers, *Water Resour. Res.*, 21, doi:10.1029/WR021i011p01710, 1710-1716, 1985.

Marsh, P.: Grain Growth in a wet arctic snow cover, *Cold Reg. Sci. Technol.*, 14, 23-31, 1987.

10 Marshall, H.P., Conway, H., Rasmussen, L.A.: Snow densification during rain. *Cold Reg. Sci. Technol.*, 30, 1-3, 35-41, doi: 10.1016/S0165-232X(99)00011-7, 1999.

Mitterer, C., Hirashima, H., and Schweizer, J.: Wet-snow instabilities: comparison of measured and modelled liquid water content and snow stratigraphy, *Ann. Glaciol.*, 52, 201–208, 2011.

Mitterer, C. and Schweizer, J.: Analysis of the snow-atmosphere energy balance during wet-snow instabilities and 15 implications for avalanche prediction, *The Cryosphere*, 7, 205 – 216, 2013.

Mualem, Y.: A new model for predicting the hydraulic conductivity of unsaturated porous media, *Water Resour. Res.*, 12, 513-522, 1976.

Raymond, C. F. and Tsushima, K.: Grain coarsening of water-saturated snow, *J. Glaciol.* 22, 83-105, 1979.

Schmid, L., Koch, F., Achim, H. Monika, P., Olaf, E., Wolfram, M., and Jürg, S.: A novel sensor combination (upGPR-GPS) 20 to continuously and nondestructively derive snow cover properties, *Geophys. Res. Lett.*, 3397-3405, 2015.

Schneebeli, M.: Development and stability of preferential flow paths in a layered snowpack, *Biogeochemistry of seasonally snow-covered catchments (proceedings of a boulder symposium, July 1995)*, IAHS Publ., 228, 89-95, 1995.

Takeuchi, Y. and Hirashima, H.: Snowpack estimations in the starting zone of large-scale snow avalanches in the Makunosawa valley, Myoko, Japan, *Ann. Glaciol.*, 54(62), 19-24, 2013.

25 Tusima, K.: Grain coarsening of ice particles immersed in pure water (in Japanese, with English Abstr.), *Seppyo*, 40, 155-164, 1978.

van Genuchten, M.Th.: A closed-form equation for predicting the hydraulic conductivity of unsaturated soils, *Soil Sci. Soc. Am. J.*, 44, 892–898, 1980.

Wakahama, G.: The metamorphism of wet snow, in: IAHS Publ., 79, 370–379, 1968.

30 Waldner, P.A., Schneebeli, M., Schultze-Zimmermann, U., and Flühler, H.: Effect of snow structure on water flow and solute transport, *Hydrol. Proc.*, 18, 1271–1290, doi:10.1002/hyp.1401, 2004.

Wankiewicz, A.: A review of water movement in snow, in: *Modeling of snow cover runoff*, edited by Colbeck, S. C. and Ray, M., U.S. Army Cold Regions Research and Engineering Laboratory, Hanover, New Hampshire, 1978.

h h 2017/8/27 17:59
削除: A 2D model for simulating heterogeneous mass and energy fluxes through melting snowpacks, *The Cryosphere Discussion*

h h 2017/8/27 18:05
削除: 10.5194/tc-2016-55

h h 2017/8/27 18:04
削除: 6

hirashima hiroyuki 2017/9/12 12:07
削除: Walter, B., Horender, S., Gromke, C., and Lehning, M.: Measurements of the pore-scale water flow through snow using Fluorescent Particle Tracking Velocimetry, *Water Resour. Res.*, 49, 7448–7456, doi:10.1002/2013WR013960, 2013. .

Wever, N., Fierz, C., Mitterer, C., Hirashima, H., and Lehning, M.: Solving Richards Equation for snow improves snowpack meltwater runoff estimations in detailed multi-layer snowpack model, *The Cryosphere*, 8, 257-274, doi:10.5194/tc-8-257-2014, 2014.

Wever, N., Schmid, L., Heilig, A., Eisen, O., Fierz, C., and Lehning, M.: Verification of the multi-layer SNOWPACK model with different water transport schemes, *The Cryosphere*, 9, 2655-2707, doi:10.5194/tcd-9-2655-2015, 2015.

Wever, N., Vera Valero, C., and Fierz, C.: Assessing wet snow avalanche activity using detailed physics based snowpack simulations, *Geophys. Res. Lett.*, doi:10.1002/2016GL068428, 2016a.

Wever, N., Würzer, S., Fierz, C., and Lehning, M.: Simulating ice layer formation under the presence of preferential flow in layered snowpacks, *The Cryosphere*, doi:10.5194/tc-10-2731-2016, 2016b.

10 Würzer, S., Wever, N., Juras, R., Lehning, M., and Jonas, T.: Modeling liquid water transport in snow under rain-on-snow conditions – considering preferential flow, *Hydrol. Earth Syst. Sci.*, 21, 174101756, doi:10.5194/hess-21-1741-2017, 2017.

Yamanoi, K. and Endo, Y.: Dependence of shear strength of snow cover on density and water content (in Japanese, with English Abstr.), *Seppyo*, 64, 443-451, 2002.

Yamaguchi, S., Katsushima, T., Sato, A., and Kumakura, T.: Water retention curve of snow with different grain sizes, *Cold Reg. Sci. Technol.*, 64(2), 87–93, doi:10.1016/j.coldregions.2010.05.008, 2010.

15 Yamaguchi, S., Watanabe, K., Katsushima, T., Sato, A., and Kumakura, T.: Dependence of the water retention curve of snow on snow characteristics, *Ann. Glaciol.*, 53(61), 6-12, 2012.

20

25

16

Table 1: Experimental conditions after Avanzi et al. (2016).

Sample ID	W (mm h ⁻¹)	ρ_{DU} (kg m ⁻³)	ρ_{DL} (kg m ⁻³)
FC1	11.9	417	465
FC2	28	449	483
FC3	113	433	470
FM1	11.9	444	484
FM2	27.7	442	487
FM3	110	455	510
MC1	11	472	487
MC2	27.3	498	480
MC3	111	494	478

h h 2017/9/18 10:50

削除: .

Table 2: Timings of infiltration in laboratory experiments and simulations^a

experiment ID	experiment			simulation		
	arrival at boundary	preferential flow formation	arrival at snow base	arrival at boundary	preferential flow formation	arrival at snow base
FC1	34.8	85.0	89.0	16.7	79.0	79.7
FC2	15.2	48.5	49.8	8.7	38.7	39.0
FC3	7.1	12.3	14.0	4.0	11.7	12.0
FM1	20.0	79.0	89.5	17.0	72.3	109.0
FM2	11.3	33.3	39.8	10.7	37.3	58.3
FM3	6.7	11.2	13.0	4.3	11.3	15.7
MC1	5.3	-	9.5	9.0	11.0	11.7
MC2	3.0	5.0	8.0	4.7	5.3	5.3
MC3	0.8	2.5	4.5	1.7	1.7	1.7

5 a. All the timings were ~~estimated~~ from the video recording of the experiment. The '-' represents points where timings could not be ~~estimated~~ from the video recording.

h h 2017/9/18 17:11
削除: process
h h 2017/9/18 10:50
削除: .

h h 2017/9/18 17:19
削除: retrieved
h h 2017/9/18 17:12
削除: .
h h 2017/9/18 17:20
削除: extracted
h h 2017/9/18 17:13
削除: of the experiment

Table 3: Thickness of upper layer affected by ponding at the layer boundary^a

Sample ID	experiment (cm)	simulation (cm)
FC1	2-3	2.8 (± 0.5)
FC2	3-4	3.3 (± 0.5)
FC3	2-3	4.1 (± 0.4)
FM1	2-3	4.0 (± 0.3)
FM2	2-3	5.1 (± 0.3)
FM3	1-2	4.8 (± 0.4)
MC1	0-1	0.1
MC2	1-1	0.3
MC3	0.5-1	0.3

a. For each pixel at the interface between layers, simulated thickness was first determined by computing the number of voxels above with liquid water content (LWC) of >10%. These data were then used to calculate a mean value and its standard deviation.

h h 2017/9/18 17:13

削除: .

hirashima hiroyuki 2017/9/6 13:40

削除: .

hirashima hiroyuki 2017/9/6 13:40

Sample ID	experiment (cm)
FC1	2-3
FC2	3-4
FC3	2-3
FM1	2-3
FM2	2-3
FM3	1-2
MC1	0-1
MC2	1-1
MC3	0.5-1

削除: .

Unknown

書式変更: フォント:9 pt, 太字

Unknown

書式変更: フォント:9 pt, 太字

h h 2017/9/18 17:14

削除: .




Figure 1: Development of capillary barrier and preferential flow path for FC1 during experiments (a-d) and simulations (e-h). A blue dye tracer was used in the experiment. In the simulation images, blue denotes the liquid water content at the front elements (see: right figure), while grey denotes that the front elements are dry, but some liquid water is present within the sample at that position. The grey-scale represents the maximum liquid water content for each location. Captured times were at: (a) 20 s, (b) 35 min, (c) 1 hour 25 min, (d) 1 hour 29 min, (e) 20 s, (f) 17 min, (g) 1 hour 19 min, and (h) 1 hour 20 min.

h h 2017/9/18 17:14
削除: ... [2]
h h 2017/8/27 17:25
削除: grid
h h 2017/8/27 17:25
削除: grid is




Figure 2: Timings of water arrival at the interface between layers (red squares), formation of preferential flow path (green triangles), and arrival at snow base (blue diamonds) for experiments and simulations.




Figure 3: Liquid water distribution (blue shading) at the end of each experiment and simulation. The coordinate on the right denotes the depth of the section from the top surface.




Figure 4: Profiles of wet area for experiments (red line) and simulations (black line): (a) FC1, (b) FC2, (c) FC3, (d) FM1, (e) FM2, (f) FM3, (g) MC1, (h) MC2, and (i) MC3.




Figure 5: Profiles of volumetric water content for experiments (red line) and simulations (black line): (a) FC1, (b) FC2, (c) FC3, (d) FM1, (e) FM2, (f) FM3, (g) MC1, (h) MC2, (i) MC3.

h h 2017/9/18 17:14

削除: .





Figure 6: Temporal evolution of simulated water content profiles: (a) FC1 in SNOWPACK RE-model, (b) FC3 in SNOWPACK RE-model, (c) FC1 in SNOWPACK DDA-model (d) FC3 in SNOWACK DDA-model, (e) FC1 in 3D model, and (f) FC3 in 3D model. Six profiles are shown in units of the arrival time at snow base in experiment, t (see Table 2).








Figure 7: Comparison of water arrival between laboratory experiment, a 3D-model and two SNOWPACK models.




a



b

c



d

Figure 8: Influence of grain size fluctuations on the thickness of the water ponding layer (a), water content profiles (b and c) and arrival time at the snow base (d). NF: no fluctuation, IU: increase 0.1 mm for the upper layer, DU: decrease 0.1 mm for the upper layer, IL: increase 0.1 mm for the lower layer and DL: decrease 0.1 mm for the lower layer.

a

Recently, a dual domain approach has been suggested to consider preferential flow effects in one-dimension (1D; Wever et al., 2016b; Würzer et al. 2017); however, considering a heterogeneous processes in a 1D model requires several assumptions. Simulations of multi-dimensional water transport models and laboratory experiments can provide the data needed to develop exhaustive parameterization of 3D processes for 1D models. In this study, simulations of liquid water infiltration into layered snowpacks were performed by reproducing the laboratory experiments of Avanzi et al. (2016). The purpose of this study was: (1) to evaluate the accuracy of a 3D water transport model in reproducing infiltration patterns in layered snow; (2) to gain further insight into the 3D infiltration process into layered snow by comparing simulation results with data from laboratory experiments; and (3) to identify future avenues of development for 3D water transport schemes in snow.