

Mean Transit Times in Headwater Catchments: Insights from the Otway Ranges, Australia

William Howcroft¹, Ian Cartwright^{1,2} and Uwe Morgenstern³

¹School of Earth, Atmosphere and Environment, 9 Rainforest Walk, Monash University, Clayton, VIC 3800, Australia.

²National Centre for Groundwater Research and Training, GPO Box 2100, Flinders University, Adelaide, SA 5001, Australia.

³GNS Science, 1 Fairway Drive, Avalon, PO Box 368, Lower Hutt 5040, New Zealand.

Correspondence to: william.howcroft@monash.edu

Abstract

Understanding the timescales of water flow through catchments and the sources of stream water at different flow conditions is critical for understanding catchment behaviour and managing water resources. Here, tritium (^3H) activities, major ion geochemistry and streamflow data were used in conjunction with Lumped Parameter Models (LPMs) to investigate mean transit times (MTTs) and the stores of water in six headwater catchments in the Otway Ranges of southeast Australia. ^3H activities of stream water ranged from 0.20 to 2.14 TU, which are significantly lower than those of modern local rainfall (2.4 to 3.2 TU). The ^3H activities of the stream water are lowest during low summer flows and increase with increasing streamflow. The concentrations of most major ions vary little with streamflow which, together with the low ^3H activities, imply that there is no significant direct input of recent rainfall at the streamflows sampled in this study. Instead, shallow younger water stores in the soils and regolith are most likely mobilised during the wetter months.

MTTs vary from approximately 7 to 230 years. Despite uncertainties of several years in the MTTs that arise from having to assume an appropriate LPM, macroscopic mixing, and uncertainties in the ^3H activities of rainfall, the conclusion that they are years to decades is robust. Additionally, the relative differences in MTTs at different streamflows in the same catchment are estimated with more certainty. The MTTs in these and similar headwater catchments in southeast Australia are longer than in many catchments globally. These differences may reflect the relatively low rainfall and high evapotranspiration rates in southeast Australia compared with headwater catchments elsewhere.

The long MTTs imply that there is a long-lived store of water in these catchments that can sustain the streams over drought periods lasting several years. However, the catchments are likely to be vulnerable to decadal changes in landuse or climate. Additionally, there may be considerable delay in contaminants reaching the stream. An increase in nitrate and sulphate concentrations in several catchments at high streamflows may represent the input of contaminants through the shallow groundwater that contributes to streamflow during the wetter months. Poor correlations between ^3H activities and catchment area, drainage density, landuse, and average slope imply that the MTTs are not controlled by a single parameter but a variety of factors, including catchment geomorphology and the hydraulic properties of the soils and aquifers.

1. Introduction

30 Determining the timescales over which precipitation is transmitted from a recharge area through a catchment to where it discharges into rivers or streams (the transit time) is important for understanding catchment behaviour and is of inherent interest to resource managers. Streams with long MTTs are connected to relatively large stores of water in the underlying aquifers (Maloszewski and Zuber, 1982; Morgenstern et al., 2010) that may sustain streamflow during droughts that last up
35 to a few years. However, longer-term changes, such as deforestation, agricultural development, climate change, and/or landscape change following bushfires is likely to affect both the quality and the quantity of river flows.

Headwater streams are important as they commonly support diverse ecosystems, provide recreational opportunities and in many catchments contribute a significant proportion of the total
40 river flow (Freeman et al., 2007). Headwater streams also differ from lowland rivers in terms of their potential water inputs. Unlike lowland rivers, which typically receive groundwater inflows from regional aquifers or near-river floodplain sediments, the sources of water within headwater streams are far less well understood. Headwater streams are commonly developed at elevations well above those of the regional water tables and/or occur on relatively impermeable bedrock. Yet such streams
45 continue to flow even during prolonged dry periods. There are several potential water stores that could contribute to stream flow, including the soil zone, weathered or fractured basement rocks, and/or perched aquifers at the soil-bedrock interface (e.g. Sklash and Farvolden, 1979; Kennedy et al., 1986; Swistock et al., 1989; Bazemore et al., 1994; Fenicia et al., 2006; Jensco and McGlynn, 2011).

Estimates of MTTs in headwater catchments range from a few months to several decades (e.g. Soulsby
50 et al., 2000; McGuire and McDonnell, 2006; Hrachowitz et al., 2009; McDonnell et al., 2010; Stewart and Fahey, 2010; Stewart et al., 2010; Mueller et al., 2013; Stockinger et al., 2014; Atkinson, 2014; Cartwright and Morgenstern, 2015, 2016a, 2016b; Duvert et al., 2016). However, in many regions globally the range of MTTs in headwater catchments is not well known. Additionally, it is not always clear why MTTs vary between different areas. This lack of knowledge limits our abilities to protect and
55 manage headwater catchments.

1.1. Estimating Mean Transit Times (MTTs)

Groundwater follows a myriad of flow paths between the recharge areas to where it discharges into streams or rivers. Consequently, groundwater discharge does not have a discrete age but rather has a distribution of transit times. MTTs are commonly estimated using Lumped Parameter Models (LPMs) that describe the distribution of water with different ages or tracer concentrations in simplified aquifer geometries (Maloszewski and Zuber, 1982, 1996; Maloszewski et al., 1983; Cook and Bohlke, 2000; Maloszewski, 2000; Zuber et al., 2005). LPMs represent a viable and commonly-used alternative to estimating MTTs using numerical groundwater models that rely upon hydraulic parameters that are seldom known with certainty and which vary spatially. However, the LPMs are only approximations of actual flow systems and the MTTs may be broad estimates rather than specific values.

The LPMs may be utilised with stable (O, H) isotopes or major ions if the concentrations vary seasonally in rainfall (e.g., Soulsby et al., 2000; McGuire and McDonnell, 2006; Tetzlaff et al., 2007, 2009, Hrachowitz et al., 2009, 2010; Kirchner et al., 2010). Determining MTTs from stable isotope ratios or major ion concentrations relies on tracking the delay and dampening of the seasonal variations between precipitation and discharge. However, use of these tracers typically requires sub-weekly sampling over time periods equal to or exceeding that of the transit times (Timbe et al., 2015). In addition, these tracers become ineffective when transit times exceed 4 to 5 years as the initial variations in rainfall are progressively dampened to below where they can be detected (Stewart et al., 2010).

Gaseous tracers (e.g. ^3He , chlorofluorocarbons, SF_6) are effective in determining residence times of groundwater (Cook and Bohlke, 2000) but are difficult to apply to surface water due to gas exchange. With a half-life of 12.32 years, tritium (^3H) has been used to estimate MTTs of up to 150 years (e.g. Morgenstern et al., 2010; Stewart et al., 2010). Unlike other radioactive tracers (e.g., ^{14}C), ^3H is part of the water molecule and its activities are affected only by radioactive decay and dispersion and not by geochemical or biogeochemical reactions in the soils or aquifers. Because ^3H activities are not affected by processes in the unsaturated zone, the MTTs reflect both recharge through the unsaturated zone and flow in the groundwater system.

Utilisation of ^3H as a tracer is facilitated by the fact that the ^3H activities of rainfall have been measured globally for several decades (International Atomic Energy Agency, 2016). Due to atmospheric nuclear testing, ^3H activities of rainfall peaked during the 1950s and 1960s (the “bomb-pulse”). The bomb-pulse ^3H activities in the Southern Hemisphere were much lower than in the Northern Hemisphere (Tadros et al., 2014) and have now largely declined to below those of modern rainfall (Morgenstern et al., 2010). As a consequence, MTTs can generally be determined from single ^3H measurements (Morgenstern et al., 2010; Morgenstern and Daughney, 2012) in an analogous manner to how other radioactive isotopes (e.g., ^{14}C or ^{36}Cl) are used in regional groundwater systems. This also allows MTTs at different streamflows to be estimated (Morgenstern et al., 2010; Duvert et al., 2016; Cartwright and Morgenstern, 2015, 2016a, 2016b).

Using LPMs to estimate MTTs has a number of uncertainties. Due to the attenuation of the ^3H bomb-pulse in the Southern Hemisphere, the suitability of the LPM can no longer be evaluated by time-series ^3H measurements (Cartwright and Morgenstern, 2016a) as is still possible in the Northern Hemisphere (e.g. Blavoux et al., 2013). Hence, LPMs must be assigned based upon knowledge of the geometry of the flow system and/or information from previous time-series studies in similar catchments. While not being able to assess the form of the LPM results in uncertainties in the calculated MTTs, the MTTs are less sensitive to the choice of LPM than is the case in the Northern Hemisphere (e.g. Blavoux et al., 2013).

Rivers can receive water from numerous stores, including groundwater, tributaries, soil water, and perched aquifers, each of which may have different MTTs. The mixing of water from different flow systems potentially produces water samples with a residence time distribution that does not correspond to those in the LPMs and calculated MTTs are lower than actual MTTs. This is known as the aggregation error (Kirchner, 2016; Stewart et al., 2017) and it increases as the difference between the transit times of the individual end-members increases. For transit times estimated from single ^3H activities, the aggregation error decreases with an increasing number of end-members as the mixing of numerous aliquots water with different transit times is similar to what is represented by the LPMs (Cartwright and Morgenstern, 2016a).

110 Despite the uncertainties in calculating MTTs, because the ^3H activities of the remnant bomb-pulse waters have largely decayed, Southern Hemisphere waters with low ^3H activities have longer MTTs than waters with high ^3H activities. This permits relative mean transit times to be readily assessed. Because ^3H is radioactive, there is no requirement for flow in the catchment to be time-invariant as long as the flow path geometry remains relatively constant.

115 1.2. Predicting Mean Transit Times

Fundamentally, MTTs are a function of the recharge rate, length of groundwater flow paths, and rates of groundwater flow, and parameters that control those factors will control the MTTs. Large catchments may have some long groundwater flow paths and consequently have long MTTs (e.g. McGlynn et al., 2003; Hrachowitz et al., 2010). Catchments with higher drainage densities (i.e., higher
120 total stream length per unit area) may contain numerous short groundwater flow paths and consequently have short MTTs (e.g. Hrachowitz et al., 2009). Large groundwater storage volumes will likely also result in long MTTs (e.g. Ma and Yamanaka, 2016). Groundwater flow is likely to be more rapid through steeper catchments due to the higher hydraulic gradients, resulting in shorter MTTs (e.g. McGuire et al., 2005). Forested catchments may have higher evapotranspiration and lower recharge
125 rates than cleared catchments (Allison et al., 1990), and the degree of forest cover exerts a control on MTTs (e.g. Tetzlaff et al., 2007). The hydraulic conductivities of the bedrock and soils are also important in controlling the timescales of water movement through catchments (e.g. Tetzlaff et al., 2009; Hale and McDonnell, 2016).

Identify the controls on MTTs is important for understanding catchment functioning. It also potentially
130 allows first order estimates of MTTs to be made in similar catchments for which detailed geochemical tracer data do not exist. In some catchments, correlations between ^3H activities and major ion geochemistry or the runoff coefficient (the proportion of rainfall exported from the catchment by the stream) also allow first order estimates of MTTs to be made (Morgenstern et al., 2010; Cartwright and Morgenstern, 2015, 2016a).

135 1.3. Objectives

This study evaluates the range of and controls on MTTs in headwater streams from the upper Gellibrand catchment of the Otway Ranges in southeast Australia. Specifically, we test the following hypotheses. Firstly that, in common with headwater catchments elsewhere in southeast Australia, the MTTs are several years to decades. Secondly, that the MTTs are most likely controlled by catchment attributes such as land cover, slope, or drainage density. Lastly, that shallower water stores within the catchment become progressively mobilised during higher rainfall periods contribute to streamflow at those times. We also use this study to evaluate whether there are geochemical proxies that could be used to make first order predictions of MTTs at times when no ^3H data is available. Documenting MTTs is critical to understanding and protecting headwater catchments and, while this study is based on a specific area, the results have relevance to catchments globally. There is not a complete understanding of the range of MTTs in headwater catchments, nor what controls these. Thus, these are important gaps in our understanding of headwater catchments.

2. Study Area

The Otway Ranges are located in southern Victoria, Australia, approximately 150 km southwest of Melbourne (Fig. 1). The region has a temperate climate, with average rainfall varying from approximately 1,000 mm yr⁻¹ at Gellibrand and Forrest to approximately 1,600 mm yr⁻¹ at Mount Sabine (Department of Environment, Land, Water and Planning, 2017) (Fig. 1) with the majority of rainfall occurring during the austral winter (July to September). Average potential evapotranspiration is 1,000 to 1,100 mm yr⁻¹ and exceeds precipitation during the summer months (Bureau of Meteorology, 2016). The Otway Ranges occur within the Great Otway National Park, and hold ecological, cultural, historical and recreational significance. Much of the area is dominated by eucalyptus forest but also includes some commercial forestry, much of which is also eucalyptus.

The geology of the study area is described by Tickell et al. (1991). The basement comprises the Early Cretaceous Otway Group, which consists primarily of volcanogenic sandstone and mudstone with minor amounts of shale, siltstone, and coal. The Otway Group is considered to be a poor aquifer and

crops out across most of the Lardners Creek and Gellibrand River Catchments, as well as within the higher elevation areas of the Yahoo Creek and Ten Mile Creek catchments (Fig. 1).

The Otway Group is unconformably overlain by Tertiary sediments of the Eastern View Formation, Demons Bluff Formation, Clifton Formation and Gellibrand Marl. The Eastern View Formation is composed of three sand and gravel units that collectively form the Lower Tertiary Aquifer. These sediments crop out at various locations across the study area including at the Barongarook High (Fig. 1), which is the primary recharge area for the aquifer (Stanley, 1991; Petrides and Cartwright, 2006). The Eastern View Formation is overlain by the Demons Bluff Formation, which is a calcareous silt having negligible permeability. The formation crops out sparsely within the study area, mainly along Yahoo and Ten Mile Creeks. Overlying this unit is the Clifton Formation, which is a limonitic sand and gravel aquifer. This unit crops out along Porcupine, Ten Mile, Yahoo and Love Creeks. The Clifton Formation is overlain by the Gellibrand Marl, which consists of approximately 200 to 300 m of calcareous silt. The Gellibrand Marl crops out extensively within the Love Creek and Porcupine Creek catchments and acts as a regional aquitard. Along Love Creek and parts of the Gellibrand River, the Tertiary units have been intruded by the Yaugher Volcanics, which consist primarily of basalt, tuff and volcanic breccia. Deposits of alluvium are present along most of the stream courses, particularly Porcupine Creek and Love Creek.

Regional groundwater flows from the recharge area in the Barongarook High to the south and southwest (Leonard et al., 1981; Stanley, 1991; Atkinson et al., 2014). Additionally, localised recharge may occur elsewhere across the study area (Atkinson et al., 2014), particularly where the Eastern View Formation crops out. Regional groundwater discharges into the Gellibrand River, Love Creek, Porcupine Creek, Ten Mile Creek and Yahoo Creek (Hebblethwaite and James, 1990; Atkinson et al., 2013; Costelloe et al., 2015). In the higher elevations of the study area, including the upper reaches of Lardners Creek, the regional water table is likely to be below the base of the streambed (Costelloe et al., 2015). Based upon ^{14}C and ^3H activities, residence times of the regional groundwater are between 100 and 10,000 years (Petrides and Cartwright, 2012; Atkinson et al., 2014).

The Gellibrand River (Fig. 1) flows west-southwest for approximately 100 km from its highest point in the Otway Ranges before discharging into the Southern Ocean. This study focuses on six headwater

catchments of the upper Gellibrand River: Lardners Creek, Love Creek, Porcupine Creek, Ten Mile
190 Creek, Yahoo Creek and the Gellibrand River upstream of James Access (Fig. 1). The Lardners Creek
catchment includes the whole catchment (Lardners Gauge) and a smaller upper subcatchment (Upper
Lardners) (Fig. 1). Similarly, Love Creek includes the whole catchment (Love Creek Wonga) and a
smaller portion of the upper catchment (Love Creek Kawarren). Porcupine Creek, Ten Mile Creek and
Yahoo Creek are also tributaries to Love Creek. Love Creek and Lardners Creek flow into the Gellibrand
195 River near Gellibrand (Fig. 1). These headwater streams contribute a significant portion of flow to the
Gellibrand River, which in turn provides water for several towns, supports important aquatic and
terrestrial fauna, and provides water for agriculture. Current landuse in the upper Gellibrand
catchment, including the cleared agricultural land which replaced the native eucalyptus forest, has
been established for several decades. Despite their significance, the headwater catchments of the
200 Otway Ranges face a number of threats, including urbanisation, further clearing of native vegetation,
drought and bushfire, all of which have the potential to impact the quantity and quality of water within
the streams.

The six catchments have areas ranging from 9.6 km² (Porcupine Creek) to 91.7 km² (Love Creek Wonga)
(Table 1). Drainage densities are relatively similar and range from 8.7x10⁻⁴ m m⁻² at Yahoo Creek to
205 1x10⁻³ m m⁻² at Lardners Gauge and Upper Lardners (Table 1). Forest cover is lowest in the Love Creek
Wonga (78%) and Love Creek Kawarren (82%) catchments. Forest cover in the other catchments is 88%
in the Porcupine Creek and Ten Mile Creek catchments, 91 to 92% in the Lardners Gauge and Upper
Lardners catchments, and 95% in the Gellibrand River and Yahoo Creek catchments. Average slopes
range from 5.7° (Ten Mile Creek) to 11.3° (at James Access).

210 3. Methods

3.1. Sampling and streamflow

River water samples were collected from eight locations in the catchments (Fig. 1). Lardners Creek
was sampled at an active gauging station (Lardners Gauge) that is maintained by the Department of
Environment, Land, Water and Planning (DELWP) (Site 235210) and from the Lardners Creek East
215 Branch (Upper Lardners), approximately 3.5 km upstream from Lardners Gauge. Love Creek was

sampled at Kawarren (Love Creek Kawarren), approximately 1 km upstream of DELWP gauging station 235234 and at the Wonga Road crossing (Love Creek Wonga), approximately 4.5 km downstream of Kawarren. River water samples were collected from the Gellibrand River, Porcupine Creek, Ten Mile Creek and Yahoo Creek at the sites of former DELWP gauging stations (Sites 235235, 235241, 235239 and 235240, respectively).

Streamflow at the time of sampling was determined for each of the eight locations with the exception of Upper Lardners, which is ungauged. Sub-daily streamflow is currently measured at Lardners Gauge (Site 235210) and at Love Creek (Site 235234) (Department of Environment, Land, Water and Planning, 2017) (Fig. 1). Streamflow at James Access on the Gellibrand River was estimated using a correlation ($R^2 = 0.97$, $p\text{-value} = 10^{-8}$) between streamflow at the former gauging station at this location and that at the existing Upper Gellibrand River gauging station (Site 235202), approximately 7 km upstream (Fig. 1). Likewise, streamflow at the Porcupine Creek, Ten Mile Creek and Yahoo Creek sampling sites was estimated using correlations ($R^2 = 0.95$; $p\text{-value} = 10^{-6}$; $R^2 = 0.77$, $p\text{-value} = 10^{-195}$ and $R^2 = 0.84$, $p\text{-value} = 10^{-15}$, respectively) between streamflow at the former gauging stations at these locations and the Love Creek gauging station.

River water samples were collected from each site in July 2014, September 2014, March 2015 and September 2015. An additional round of river water samples was collected from Lardners Gauge, Porcupine Creek, Ten Mile Creek and Love Creek Kawarren in November 2015. The water samples were collected from close to the centre of the streams using a polyethylene container fixed to an extendable pole. Additional data for James Access is from Atkinson (2014). A single precipitation sample was collected from Birnam in the Otway Ranges near Ten Mile Creek (Fig. 1) in September 2014 using a rainfall collector. The collector consisted of a polyethylene storage container equipped with a funnel positioned approximately 0.5 m above ground level. Prior to collection of the precipitation sample, the collector had been in the field for 78 days, during which time approximately 198 mm of rainfall was recorded at Forrest while 431 mm of rainfall was recorded at Mount Sabine (Department of Environment, Land, Water and Planning, 2017).

3.2. Geochemical analyses

The electrical conductivity (EC) and pH of the river water and precipitation samples was measured in the field using a calibrated TPS® hand-held water quality meter and probes. The EC measurements
245 have a precision of 1 $\mu\text{S}/\text{cm}$. Cation concentrations were measured at Monash University using a Thermo Fischer ICP-OES on samples that had been filtered through 0.45 μm cellulose nitrate filters and acidified to a pH <2 using double-distilled 16 M HNO_3 . Anion concentrations were measured at Monash University on filtered, unacidified samples using a Metrohm ion chromatograph. The precision of the cation and anion analyses, based upon replicate sample analysis, is $\pm 2\%$ while accuracy
250 based on analysis of certified water standards is $\pm 5\%$. HCO_3^- concentrations were measured by colorimetric titration with H_2SO_4 using a Hach digital titrator and reagents and are precise to $\pm 5\%$. Total dissolved solids (TDS) concentrations were determined by summing the concentrations of cations and anions. Geochemical data is presented in the Supplement.

^3H analysis was conducted at the GNS Water Dating Laboratory in Lower Hutt, New Zealand. The
255 samples were vacuum distilled and electrolytically enriched prior to analysis by liquid scintillation counting, as described by Morgenstern and Taylor (2009). Following further improvements the sensitivity is now further increased to a lower detection limit of 0.02 TU via tritium enrichment by a factor of 95, and reproducibility of tritium enrichment of 1% is achieved via deuterium-calibration for every sample. ^3H activities are expressed as absolute values in tritium units (TU) where 1 TU represents
260 a $^3\text{H}/^1\text{H}$ ratio of 1×10^{-18} . The precision (1σ) is $\sim 1.8\%$ at 2 TU.

3.3. Catchment Attributes

Catchment attributes (Table 1) were determined using ArcGIS 10.2 (ESRI, 2013) and datasets from (DataSearch Victoria, 2015). The Hydrology Modelling tools in ArcGIS were used to generate the stream network from a 20 m digital elevation model. A threshold catchment area of 50 Ha reproduces
265 the observed perennial stream network of the area. Catchment areas upstream of each sampling site and drainage densities were determined using the watershed tool. Mean slopes were calculated using the Spatial Analysis tools. Vector-based landuse datasets were converted to raster formats and reclassified. Landuse was assigned as forest (native vegetation and plantations) and cleared land,

270 which includes urban and agricultural regions. Runoff coefficients were calculated using streamflow data for each of the catchments (except Upper Lardners) for March 1986 to July 1990 (Department of Environment, Land, Water, and Planning, 2017), the only interval for which contiguous streamflow data are available for each catchment. The runoff coefficient calculations assumed a uniform average annual rainfall of 1.3 m for each catchment (Bureau of Meteorology, 2017). Correlations between catchment attributes and other parameters are considered to be strong where $R^2 \geq 0.7$

275 3.4. Calculating Mean Transit Times

The lumped parameter models implemented in the TracerLPM Excel workbook (Jurgens et al., 2012) were used to estimate MTTs. The ^3H activity of water sampled from a stream at time t ($C_0(t)$) is related to the input (C_i) of ^3H via the convolution integral:

$$C_0(t) = \int_0^{\infty} C_i(t-T)g(T)e^{-\lambda T} dT \quad (1)$$

280 where T is the transit time, $t - T$ is the time that the groundwater entered the flow system, λ is the decay constant (0.0563 yr^{-1} for ^3H) and $g(T)$ is the exit age distribution function, for which closed form analytical solutions have been derived (e.g. Maloszewski and Zuber, 1982; Maloszewski and Zuber, 1996; Kinzelbach et al., 2002). MTTs were estimated by matching the predicted ^3H activities from the LPMs to the observed ^3H activities of the samples.

285 As discussed earlier, the use of single ^3H activities to estimate MTTs requires that an LPM be assigned. Here two LPMs were utilised: the Exponential Piston-Flow model (EPM) and the Dispersion model (DM), which are among the most commonly used LPMs (McGuire and McDonnell, 2006; Stewart et al., 2010). The EPM describes flow in aquifers with both exponential and piston-flow portions. This model may be applied to unconfined aquifers where recharge through the unsaturated zone resembles
290 piston flow and flow within the aquifer resembles exponential flow (Morgenstern et al., 2010). TracerLPM defines an EPM ratio, which represents the relative contribution of exponential and piston flow (Jurgens et al., 2012). The EPM ratio is $1/f - 1$, where f is the proportion of aquifer volume exhibiting exponential flow.

The Dispersion Model (DM) is based on the one-dimensional advection-dispersion equation for a semi-
295 infinite medium (Jurgens et al., 2012). While this model can be applied to a wide variety of aquifer
configurations, conceptually it is probably less realistic than other LPMs. Nonetheless, it has been
successfully used to predict tracer concentrations over time in a number of flow systems (e.g.
Maloszewski, 2000). Utilisation of this model requires defining a dispersion parameter, D_p , which
represents the ratio of dispersion to advection.

300 The ^3H input is based on the ^3H activities of rainfall in Melbourne, which is approximately 150 km from
the study area (International Atomic Energy Agency, 2016; Tadros et al., 2014). The data of Tadros et
al. (2014) suggest that modern rainfall in the study area has a slightly lower annual weighted average
 ^3H activity (~ 2.8 TU) than that in Melbourne, which has a ^3H activity ~ 3.0 TU. Hence, 2.8 TU was used
as the average annual ^3H activity of modern (2010 to 2016) rainfall as well as for the years prior to the
305 atmospheric nuclear tests (pre-1951). ^3H activities of 9 to 17 month rainfall samples from elsewhere
in Victoria are between 2.70 and 2.99 TU (Atkinson, 2014; Cartwright and Morgenstern, 2015 and
unpublished data), suggesting that the ^3H activity of 2.8 TU is reasonable. The ^3H activities for rainfall
between 1950 and 2009 are those of Melbourne rainfall decreased by 6.7% to account for the
expected difference in ^3H activities in the rainfall between the Otway Ranges and Melbourne.

310 There are several uncertainties in the MTT calculations. The analytical uncertainty ranges between
0.02 and 0.04 TU (Supplement). Tadros et al. (2014) proposed that average annual modern rainfall ^3H
activities were 2.4 to 2.8 TU to the west of the study area and 2.8 to 3.2 TU to the east. To assess the
effect of uncertainties in rainfall ^3H activities, MTTs were recalculated assuming that modern and pre-
1950 rainfall had an average ^3H activity of either 2.4 TU or 3.2 TU with the ^3H activities of the
315 intervening years adjusted proportionally.

The aggregation or macroscopic mixing of waters also introduces uncertainties (Kirchner, 2016;
Stewart et al., 2017). Consider a stream fed by several tributaries. The expected MTT (MTT_e) can be
calculated using the streamflow data, ^3H activities, and MTTs of each tributary via:

$$\text{MTT}_e = a \text{MTT}_1 + b \text{MTT}_2 + c \text{MTT}_3 + \dots \quad (2)$$

320 (Stewart et al., 2017). In Eq. (2), a, b, c, represent the fraction of total flow contributed by tributaries
1, 2, 3. If the aggregation is minimal, MTT_e will be similar to that estimated from the measured 3H
activity via the LPM. The successful application of Eq. (2) relies on the MTTs of the different tributaries
being defined by their 3H activities (which in itself may not be straightforward due to aggregation
within those subcatchments). Nevertheless, it provides a broad estimate of the error due to
325 macroscopic mixing that is otherwise difficult to assess.

3.5. Groundwater Volumes

The volume (V in m^3) of groundwater stored within an aquifer that interacts with the stream
(sometimes referred to as the turnover volume) is related to the MTT by:

$$V = Q * MTT \quad (3),$$

330 where Q is streamflow ($m^3 yr^{-1}$) (Maloszewski and Zuber, 1982; Morgenstern et al., 2010).

4. Results

4.1. Streamflow

Streamflow was highest during July 2014 (Supplement), ranging from $8.6 \times 10^3 m^3 day^{-1}$ at Ten Mile
Creek to $255 \times 10^3 m^3 day^{-1}$ at James Access. Discharge was lowest during March and November 2015,
335 ranging from $0.1 \times 10^3 m^3 day^{-1}$ at Ten Mile Creek to $8.8 \times 10^3 m^3 day^{-1}$ at James Access. Figure 2 illustrates
the streamflows for the sampling rounds relative to the flow duration curves for the catchments.
Samples were generally collected between the 10th and 100th percentiles of streamflow, which
encompasses a wide range of flow conditions. Samples were collected during the recession periods
after high flow events that follow rainfall or during baseflow conditions (Fig. 3). Overland flow was not
340 observed during any of the sampling events and small ephemeral tributaries in the catchments were
dry.

Runoff coefficients range from 33% and 39% at Lardners Gauge and James Access, respectively, to
between 9% and 12% at Porcupine Creek, Ten Mile Creek, Yahoo Creek Wonga and Love Creek
Kawarren (Table 1). The higher runoff coefficients at Lardners Gauge and James Access relative to the

345 other catchments may be due to the fact that these rivers drain steeper catchments and are underlain almost entirely by low hydraulic conductivity Otway Group basement rocks (Fig. 1).

4.2. Tritium Activities

The precipitation sample collected from near Ten Mile Creek in September 2014 had a tritium activity of 2.45 TU, which is near the low end of the predicted range (2.4 to 3.2 TU) of ^3H activities of modern
350 rainfall for this area (Tadros et al., 2014). This ^3H activity is also below the values of 2.70 and 2.76 TU from 9 to 12 month rainfall samples in the Melbourne area (Atkinson, 2014; Cartwright, unpublished data), and 2.85 to 2.99 TU from 9 to 17 month rainfall samples in the Ovens River catchment in northern Victoria (Cartwright and Morgenstern, 2015). The lower than expected ^3H activity from the Otway sample is probably due to the sample representing rainfall of only part of the year.

355 Tritium activities in the rivers are uniformly lower than those of modern rainfall and ranged from 0.20 TU at Porcupine Creek in March 2015 to 2.14 TU at Yahoo Creek in July 2014 (Fig. 4). The maximum ^3H activity (2.14 TU) in the rivers is within the range of ^3H activities of 1.80 to 2.25 TU for soil pipe water in higher elevations in the Gellibrand Catchment (Atkinson, 2014). In general, ^3H activities were highest at high streamflow (July 2014) and lowest at low streamflow (March and November 2015).

360 The ^3H activities of Love Creek at the upstream (Love Creek Kawarren) and downstream (Love Creek Wonga) locations in individual events varied by <0.1 TU. The ^3H activities in Lardners Creek between Upper Lardners and Lardners Gauge were slightly more variable (up to 0.17 TU). The range of ^3H activities between the events was most variable at Porcupine Creek (0.20 to 1.97 TU), followed by Yahoo Creek (0.43 to 2.14 TU), Love Creek Kawarren (0.48 to 1.91 TU), Love Creek Wonga (0.55 to 1.88
365 TU), Ten Mile Creek (0.44 to 1.74 TU), Upper Lardners (1.54 to 1.99 TU), James Access (1.73 to 2.08 TU) and Lardners Gauge (1.64 to 1.97 TU) (Fig. 4). Overall, the highest ^3H activities were similar across all catchments but the lower ^3H activities varied considerably. The ^3H activities increase with increasing streamflow up to approximately $10^4 \text{ m}^3 \text{ day}^{-1}$, above which ^3H activities do not increase appreciably (Fig. 4). Despite differences in catchment size, slope, geology, and, landuse, there is a strong
370 correlation between ^3H activities and streamflow across the catchments ($^3\text{H} = 0.2613 \ln(Q) + 0.8973$; $R^2 = 0.75$, $p\text{-value} = 0.15$).

4.3. Major Ion Geochemistry

River water geochemistry is similar across all catchments and is dominated by Na, Cl and HCO₃ (Supplement). TDS concentrations are generally less than 100 mg/L at Lardners Gauge, Upper Lardners and James Access but typically exceed 200 mg/L in Love Creek Wonga, Love Creek Kawarren, Porcupine Creek, Ten Mile Creek and Yahoo Creek. TDS concentrations increase downstream in Lardners and Love Creeks and are inversely correlated with streamflow in all catchments.

At Love Creek, Ten Mile Creek, Yahoo Creek and Upper Lardners, there is no correlation between ³H activities and EC, TDS or major ion concentrations (Fig. 5). However, at Porcupine Creek, there is a strong correlation ($R^2 > 0.95$, p-values < 0.01) between ³H activities and EC, TDS, and all major ion concentrations with the exception of chloride, nitrate and sulphate. In addition, there is a strong correlation ($R^2 = 0.84$, p-value = 0.002) between ³H activities and TDS at Lardners Gauge (Fig. 5).

At Upper Lardners, James Access and Ten Mile Creek, there is a strong correlation ($R^2 > 0.90$, p-value < 0.15) between nitrate concentration and ³H activities (Fig. 6a). The range of nitrate concentrations (0.08 to 2.0 mg/L) were relatively similar during each sampling event across all catchments except for in July 2014, when nitrate concentrations exceeded 3 mg/L at Love Creek Kawarren and Love Creek Wonga. A similar correlation exists between sulphate concentrations and ³H activities at James Access and at Upper Lardners, but not at Ten Mile Creek (Fig 6b). However, sulphate concentrations at these locations are lower than they are in the other catchments.

5. Discussion

The combination of streamflow, ³H activities, major ion geochemistry, and catchment attributes allows aspects of the behaviour of the upper Gellibrand catchments to be understood. This section addresses the changing stores of water in the catchments, the range and uncertainties of MTTs, and whether MTTs can be predicted from catchment attributes or geochemical data.

5.1. Sources of River Inflows

It is important to determine how the water stores that contribute to streamflow change between high and low flows. Groundwater inflows are most probably the dominant source of water during the

summer months. However, at times of higher streamflow there may be mobilisation of younger shallower water stores (e.g., water from the soils or the regolith) as the catchment wets up (c.f. Hrachowitz et al., 2013; Cartwright and Morgenstern, 2015, 2016a) or mixing between baseflow and recent rainfall (c.f., Morgenstern et al., 2010). The river water samples were collected during baseflow conditions or during recession periods after high streamflows that follow rainfall (Fig. 3) when recent rainfall is less likely to directly contribute to streamflows. That the major ion geochemistry varies little with streamflow also suggests that there is not significant dilution of groundwater inflows with recent rainfall during the sampling periods (c.f. Sklash and Farvolden, 1979; Kennedy et al., 1986; Jensco and McGlynn, 2011; Cartwright and Morgenstern, 2015). Additionally the ^3H activities plateau at ~ 2.0 TU, which is significantly lower than those of modern rainfall (Fig. 4).

Together, these observations suggest that there is no significant direct input of recent rainfall during the sampling periods. The flow system may be concluded to be a continuum that is dominated by older groundwater inflows at low flows while progressively shallower and younger stores of water (such as soil water or perched groundwater) are mobilised during wetter periods. The observations that nitrate and sulphate concentrations in several of the catchments are higher at high streamflows (Fig. 6) may reflect the input of contaminants from recent agricultural activities to the streams. This observation agrees with the conceptualisation that shallower stores of water in the catchment, which are more likely to be impacted by contamination, are mobilised during the wetter periods of the year.

5.2. Mean Transit Times

If the conceptualisation of the flow system is correct, MTTs may be calculated using a single LPM. If there were some dilution by recent rainfall, using a single LPM yields the minimum MTT of the baseflow component (Morgenstern et al., 2010). MTTs in the headwaters catchments were estimated using the EPM and the DM. For the EPM, EPM ratios of 0.33 (75% exponential flow), 1.0 (50% exponential flow) and 3.0 (25% exponential flow) were adopted. The EPM model accords with the expected geometry of flow in the catchment (vertical recharge through the unsaturated zone followed by flow along flow paths of varying length), and EPM models with these EPM ratios have reproduced the ^3H time series in headwater catchments with similar geometries elsewhere (Maloszewski and Zuber, 1982; Morgenstern and Daughney, 2012; Blavoux et al., 2013; Morgenstern et al. 2010). For

the DM, D_p values of 0.05 and 0.5 were adopted, which are appropriate for kilometre-scale flow systems (Zuber and Maloszewski, 2001; Gelhar et al., 1992). Utilisation of a variety of LPMs allows the impact of the assumed model on the MTTs to be assessed.

430 Calculated MTTs ranged from approximately 7 years at Yahoo Creek in July 2014 to 230 years at Porcupine Creek in March 2015 (Table 3). In general, the lowest MTTs were estimated from the EPM with an EPM ratio = 3.0 while the highest MTTs were estimated using the DM with $D_p = 0.5$. Because of the remnant bomb pulse ^3H , a few samples with ^3H activities between 1.2 to 1.7 TU yield MTTs that are non-unique for models with high piston flow components (i.e., the EPM with EPM ratio = 3.0 and the DM with $D_p = 0.05$; Table 3, Fig. 8). The choice of the LPM has little impact on MTTs for ^3H activities
435 greater than 1 TU (Fig. 8). However, as ^3H activities decrease, the relative difference between the MTTs from the different LPMs increases. At the lowest ^3H activity of 0.20 TU, the difference between the MTT estimates is approximately 164 years.

MTTs for Lardners Gauge, Upper Lardners and James Access were similar, and are between 7 and 26 years. In contrast, MTTs for Porcupine Creek ranged from approximately 7 to 230 years, while those
440 for Ten Mile Creek, Yahoo Creek, Love Creek Wonga, and Love Creek Kawarren ranged from approximately 13 to 150, 7 to 15, and 10 to 140 years, respectively. In all catchments, the longest MTTs are recorded at the lowest streamflows (March 2015) while the shortest MTTs occur at the highest streamflows (July 2014 and September 2015) (Fig. 9). At Lardners Gauge, James Access, Porcupine Creek and Love Creek, the samples collected at the highest flow rates have MTTs that are
445 slightly longer than that of the samples collected at the second highest streamflow (Fig. 9). Whether this reflects changes to the flow system or is due to uncertainties in the MTT estimates is not certain.

5.3. Uncertainties in MTT Estimates

The uncertainties in the MTTs arising from the analytical uncertainties (Supplement) range from ± 0.9 years for the sample with the highest ^3H activity to ± 10 years for the sample with the lowest ^3H activity.
450 These equate to relative uncertainties of $\sim \pm 10\%$. Having to assume an LPM reflects a major uncertainty for calculating the MTTs, especially for waters with ^3H activities < 1 TU (Fig. 8). For a water with a ^3H activity of 2 TU, the uncertainty in MTTs is ± 1.2 years ($\pm 13\%$), while for waters with ^3H activities of 1

TU and 0.5 TU they are ± 5 years ($\pm 8\%$) and ± 31 years ($\pm 30\%$), respectively. The EPM with an EPM ratio of 3.0 and the DM with a D_p value of 0.05 have a large component of piston flow and are possibly less realistic representations of the flow systems; however, the differences between the MTTs estimated using the other LPMs are still considerable.

The influence of uncertainties in the ^3H input was assessed by varying the ^3H activities to encompass the spatial variability described by Tadros et al. (2014) as discussed in Section 2.4. These calculations used the EPM with an EPM ratio of 1.0 but the effect is similar in the other models. The relative difference between MTTs is generally highest when ^3H activities exceed 1 TU (Fig. 10). For ^3H activities of 2 TU, the uncertainty in MTTs is ± 5 years ($\pm 54\%$), while for waters with ^3H activities of 1 TU and 0.5 TU they are ± 10 years ($\pm 15\%$) and ± 5 years ($\pm 5\%$), respectively.

^3H activities in rainfall can vary seasonally. If recharge has a strong seasonality, its ^3H activities may be different from those of annual rainfall. Rainfall in the Otway Ranges is distributed throughout the year and it is likely that some recharge occurs throughout the year. Less recharge probably occurs during summer due to some rainfall being lost to evapotranspiration. However, as is the case elsewhere in the Southern Hemisphere (Morgenstern et al., 2010), the ^3H activities in summer rainfall are closely similar to the average annual ^3H activities (Tadros et al., 2014; International Atomic Energy Agency, 2017). The observation that the ^3H activities of summer (December to February) rainfall at Mount Buffalo in northeast Victoria were similar (2.86 TU) to those of two annual rainfall samples (2.99 and 2.85 TU) support this assertion (Cartwright and Morgenstern, 2015). With such a seasonal distribution of ^3H activities, the uncertainties in MTTs resulting from using the average annual ^3H activities are less than those that arise from the general uncertainty in the ^3H input function.

The impact of macroscopic mixing was estimated using Eq. (3) and the streamflow data and MTTs for Porcupine, Ten Mile and Yahoo Creeks that flow into Love Creek upstream of Love Creek Kawarren (Fig. 1). The analysis used the EPM with an EPM ratio of 1.0 (Table 3), but again similar results were obtained with the other LPMs. Based on the streamflow data, these three streams contribute 77 to 82% of total stream flow at Love Creek Kawarren (Table 3). The remaining portion of flow in Love Creek is assumed to be contributed by undefined inputs such as groundwater inflow and inputs from smaller tributaries. It was assumed that there was one unidentified input, the ^3H activity of which was

estimated by the difference between the weighted ^3H activities of Porcupine, Ten Mile and Yahoo Creeks and the ^3H activity at Love Creek Kawarren. The MTT of this input was determined from the ^3H activity using the EPM.

485 March 2015, the estimated MTT calculated using the LPM at Love Creek Kawarren was higher than MTT_e calculated using Eq. (3) by 3.7 years or 4% (Table 4). At other times, the differences were 3.9 to 7.4 years (18 to 37%). These calculations may not truly address aggregation as there may be more than one unidentified additional store of water and there may be aggregation within the individual subcatchments (which impacts their estimated MTTs). Nevertheless, they do indicate that the potential uncertainties in MTTs due to aggregation are potentially several years (as discussed by 490 Stewart et al., 2017). For waters with similar ^3H activities, Cartwright and Morgenstern (2016a) estimated that the aggregation error may be up to 20% where two waters with MTTs of 10 and 50 years or 1 and 5 years mixed but noted that this error became progressively lower if more stores of water with a similar range of MTTs mixed.

495 If the uncertainties are uncorrelated, the overall uncertainty is given by the square root of the sum of the squares of the individual uncertainties. Assuming that uncertainties due to analytical uncertainties and aggregation are uniformly 10% and 20%, respectively, and the uncertainties from the range of LPMs and the ^3H input of rainfall are as discussed above. For a water with a ^3H activity of 2 TU, the overall uncertainty in MTTs are approximately $\pm 60\%$ (± 5.4 years), whereas for waters with ^3H activities of 1 TU and 0.5 TU they are $\pm 28\%$ (± 17 years) and $\pm 38\%$ (± 35 years), respectively.

500 While these uncertainties are considerable, the observation that the ^3H activities of the streams are locally 10% of those of modern rainfall (and far less than the rainfall ^3H activities at the peak of the bomb-pulse) necessitates that the MTTs must be several decades. Because the aggregation error, which is probably the most difficult to assess, results in MTTs being underestimated (Kirchner et al., 2016; Stewart et al., 2017) some MTTs may be longer than calculated. Relative differences in MTTs 505 between and within catchments may be estimated with more certainty. Because the catchments are located in a relatively small area, the ^3H inputs are likely to be closely similar. Thus, uncertainties in the ^3H input are thus less likely to impact the comparison of MTTs between catchments. Additionally, as the geometry of the flow system in each catchment is unlikely to vary substantially at different

streamflows, not being able to assess the suitability of the LPM has less impact on the relative
510 differences in MTTs at different streamflows in the same catchment.

5.4. Predicting Mean Transit Times

There are weak ($R^2 \leq 0.7$) or no correlations between ^3H activities and catchment area, drainage
density or forest cover (Table 2). There is a strong correlation between ^3H activities and average slope
($R^2 = 0.87$, p-value 0.01) during March 2015, when streamflow was lowest but not at other times. The
515 variability of MTTs from James Access, Lardners Gauge, and Upper Lardners (which occur on the Otway
Group: Fig. 1) and from Porcupine Creek, Yahoo Creek, Love Creek, and Ten Mile Creek (which have
similar lithologies in their catchments: Fig. 1) indicates the MTTs are not simply related to the geology.
A combination of the catchment properties together with the hydraulic properties of the soils and
aquifers or evapotranspiration rates that are probably spatially variable and which are difficult to
520 estimate likely controls the MTTs. The observation that relationship between ^3H activities and
streamflow in all the catchments are similar (Fig. 4) suggests that the MTTs at high flows reflect the
inflow of water from the shallower water stores which will be largely independent of the catchment
attributes.

There is a strong positive correlations between ^3H activities and the runoff coefficient ($R^2 = 0.94$, p-
525 value = 0.27) (Fig. 7). This may be due to both the runoff coefficient and MTTs being controlled by the
rates of recharge and groundwater flow. The Lardners Gauge and James Access sites have much higher
runoff coefficients than the other catchments, and the correlation with ^3H activities may reflect the
difference between the two groups of catchments. If this is the case, the runoff coefficient may be
useful in determining gross rather than subtle differences in MTTs.

530 EC and streamflow were measured on a monthly basis at the gauging station on Porcupine Creek (Site
235241) between January 1990 and January 1994 (Department of Environment, Land, Water and
Planning, 2017). A strong correlation between MTTs and EC at this location ($\text{MTT} = 1.362e^{0.0061*EC}$; R^2
= 0.96, p-value = 10^{-8}) allows MTTs at this site to be estimated over this four year period (Fig. 11). The
estimated MTTs range from 3 to 50 years with the longest MTTs corresponding to low summer flows
535 and the shortest MTTs during high winter flows. Although based upon a limited number of samples,

these results demonstrate the high variability of transit times within the catchment and the value of finding proxies for ^3H .

5.5. Groundwater volumes

The volume of water in the aquifers that contributes to the streamflow may be estimated from Eq. (3).
540 Both the Lardners Gauge and the Love Creek Wonga catchments have active streamflow monitoring, and the calculations are carried out for these catchments. Using the relationships between MTT and streamflow (Fig. 9) and streamflow data for 2014 and 2015 (Department of Environment, Land, Water, and Planning, 2017), the average MTT for the two catchments is estimated as 29.7 years (Love Creek Wonga) and 10.8 years (Lardners Gauge). For the average annual streamflow over those two years,
545 the turnover volumes are $2.6 \times 10^5 \text{ m}^3$ (Love Creek Wonga) and $4.5 \times 10^5 \text{ m}^3$ (Lardners Gauge). These volumes are small relative to the likely volumes of water stored in the catchments. For the catchment areas (Table 1) and a porosity of 0.1 to 0.3, which is appropriate for most soils and aquifers, this volume of water could be stored in a layer that is 0.01 to 0.1 m thick.

6. Summary and Conclusions

550 The calculated MTTs in the six headwater catchments in the Upper Gellibrand catchment of Otway Ranges vary from approximately 7 to 230 years, verifying one of the hypotheses. While there are significant uncertainties in the MTT estimates, the conclusion that they range from years to several decades and are longer at low streamflows is robust. Similar MTTs are recorded in other catchments in southeast Australia (e.g., Cartwright and Morgenstern, 2015, 2016a, 2016b). Especially at low
555 streamflows, the MTTs are far longer than in most headwater catchments worldwide (e.g., Stewart et al., 2010) and are some of the longest yet recorded. The average MTT of 15 ± 22 years calculated by Stewart et al. (2010) was for MTTs based on ^3H activities, which makes it directly comparable with MTTs from the south Australian catchments.

Understanding the reasons for the difference in MTTs between catchments is important for
560 understanding catchment behaviour. The catchments in southeast Australia have similar dimensions, slopes, and stream densities to those elsewhere making it unlikely that the differences in MTTs result from catchment geomorphology. The Gellibrand catchments have only thin near-river alluvial

sediments thus diminishing the likelihood of bank storage and return flows of young waters during the recession from the high streamflows. However, many headwater catchments globally lack extensive alluvial sediments. The hydraulic properties of the soils and aquifers may also result in slow recharge rates and long MTTs. These are very poorly known and it is difficult to assess their influence. Due to the high transpiration rates of eucalyptus forests, recharge rates in Australian catchments are generally lower than elsewhere globally (Allison et al., 1990). However, the observation that there is no correlation between the percentage of forest cover and MTTs in the upper Gellibrand catchments where land clearing occurred several decades ago is problematic for proposing this as a simple control. Despite being in the more temperate region of southeast Australia, the average rainfall in the Otway Ranges of 1,000 to 1,600 mm yr⁻¹ is modest compared with upland areas in many parts of the world and the average evapotranspiration rate of 1,000 to 1,100 mm yr⁻¹ includes a sizeable component of evaporation (which is more prevalent on the cleared land) (Bureau of Meteorology, 2016). The long MTTs in the catchments from southeast Australia may, therefore, reflect the low rainfall and high evaporation and/or transpiration rates that limit recharge.

The long MTTs are significant for understanding and managing the catchments. Firstly, there are likely to be long-lived stores of water in these catchments that can sustain the streams during droughts that last up to a few years, although longer-term changes (such as land use change or climate change) may eventually affect the streamflows. The long MTTs also imply that any contaminants in groundwater are likely to be released into the streams over years to decades (c.f. Morgenstern and Daughney, 2012). The locally higher nitrate and sulphate concentrations at high streamflows may reflect the input of contaminants from recent agricultural activities to the streams via the younger groundwater that is mobilised at those times.

Even at baseflow conditions, it was not possible to simply predict the MTTs across the catchments from catchment attributes or the geochemistry, although local correlations exist (this refutes one of the hypotheses). The MTTs are most likely controlled by a combination of catchment attributes and also soil properties, hydraulic conductivities, and evapotranspiration rates. This is in keeping with the observation that previous studies have identified correlations between a range of parameters and MTTs (i.e. no single attribute appears to provide the dominant control on MTTs across different

regions). Characterising hydraulic properties and evapotranspiration rates on a catchment-wide scale is difficult, which limits the ability to predict MTTs. The runoff coefficient that is a reasonable indicator of MTTs elsewhere in southeast Australia (Cartwright and Morgenstern, 2015) was the best predictor of MTTs. This may reflect the fact that both the runoff coefficient and MTTs are controlled by recharge and groundwater flow rates.

This study illustrates that, while broad ranges of MTTs may be estimated using ^3H , precise determination of MTTs is difficult. Additionally, it highlights the challenge in understanding the reasons for the long MTTs in the Australian catchments compared with headwater catchments elsewhere. The potential controls on MTTs in catchments are numerous and more studies in catchments with different climate, landuse, geomorphology, and geology are needed if the desire to be able to predict catchment behaviour regionally or globally is to be realised.

Data Availability

All geochemistry data utilised in this study are contained in the Supplement. Streamflow data and historic EC data for Porcupine Creek are publicly available from the Victorian State Government, Department of Environment, Land, Water & Planning (DELWP), Water Measurement Information System (<http://data.water.vic.gov.au/monitoring.htm>).

Author Contributions

William Howcroft undertook the sampling program and oversaw the analysis of the geochemical parameters and the MTT calculations. Uwe Morgenstern was responsible for the ^3H analysis. The manuscript was prepared by William Howcroft, Ian Cartwright and Uwe Morgenstern.

Acknowledgements

Field work and laboratory analyses were conducted with the help of Massimo Raveggi, Rachelle Pearson, Wang Dong, Kwadwo Osei-Bonsu and Lei Chu. Funding for this project was provided by Monash University and the National Centre for Groundwater Research and Training (NCGRT). NCGRT is an Australian Government initiative supported by the Australian Research Council and the National Water Commission via Special Research Initiative SR0800001. We also thank two anonymous reviewers and the editor Markus Hrachowitz for their perceptive and helpful comments.

References

- Allison, G.B., Cook, P.G., Barnett, S.R., Walker, G.R., Jolly, I.D., and Hughes, M.W.: Land clearance and
620 river salinisation in the western Murray Basin, Australia, *J. Hydrol.*, 119, 1-20, doi: 10.1016/0022-
1694(90)90030-2, 1990.
- Atkinson, A.P.: Surface water – groundwater interactions in an upland catchment (Gellibrand River,
Otway Ranges, Victoria, Australia), Ph.D. Thesis, Monash University, Australia, 2014.
- Atkinson, A.P., Cartwright, I., Gilfedder, B.S., Hoffman, H., Unland, N.P., Cendon, D.I., and Chisari, R.:
625 A multi-tracer approach to quantifying groundwater inflows to an upland river; assessing the
influence of variable groundwater chemistry, *Hydrol. Process.*, 24, 1-12, doi: 10.1002/hyp.10122.,
2013.
- Atkinson, A.P., Cartwright, I., Gilfedder, B.S., Cendon, D.I., Unland, N.P., and Hoffman, H.: Using ¹⁴C
and ³H to understand groundwater flow and recharge in an aquifer window, *Hydrol. Earth Syst. Sci.*,
630 18, 4951-1964, doi: 10.5194/hess-18-4951-2014, 2014.
- Bazemore, D.E., Eshleman, K.N., and Hollenbeck, K.J.: The role of soil water in storm flow generation
in a forested headwater catchment: Synthesis of natural tracer and hydrometric evidence, *J.*
Hydrol., 162, 47-75, doi: 10.1016/0022-1694(94)90004-3, 1994.
- Blavoux, B., Lachassagne, P., Henriot, A., Ladouche, B., Marc, V., Beley, J.-J., Nicoud, G., Olive, P.: A
635 fifty-year chronicle of tritium data for characterising the functioning of the Evian and Thonon
(France) glacial aquifers, *J. Hydrol.*, 494, 116-133, doi: 10.1016/j.jhydrol.2013.04.029, 2013
- Bureau of Meteorology: Commonwealth of Australia, Bureau of Meteorology, <http://www.bom.gov.au>,
last access: 21 January 2016.
- Cartwright, I., and Morgenstern, U.: Transit times from rainfall to baseflow in headwater catchments
640 estimated using tritium: the Ovens River, Australia, *Hydrol. Earth Syst. Sci.*, 19, 3771-3785, doi:
10.5194/hess-19-3771-2015, 2015.
- Cartwright, I., and Morgenstern, U.: Contrasting transit times of water from peatlands and eucalypt
forests in the Australian Alps determined by tritium: implications for vulnerability and the source
of water in upland catchments, *Hydrol. Earth Syst. Sci.*, 20, 4757-4773, doi: 10.5194/hess-20-4757-
645 2016, 2016a.

- Cartwright, I., and U. Morgenstern, U.: Using tritium to document the mean transit time and source of water contributing to a chain-of-ponds river system: Implications for resource protection, *Appl. Geochem.*, 75, 9-19, doi: 10.1016/j.apgeochem.2016.10.007, 2016b.
- 650 Cartwright, I., Weaver, T.R., Stone, D. and Reid, M.: Constraining modern and historical recharge from bore hydrographs, ^3H , ^{14}C , and chloride concentrations: Applications to dual-porosity aquifers in dryland salinity, Murray Basin, Australia. *J. Hydrol.*, 332, 69-92, doi: 10.1016/j.jhydrol.2006.06.034, 2007.
- Cook, P.G., and Bohlke, J.K.: Determining timescales for groundwater flow and solute transport, in: *Environmental Tracers in Subsurface Hydrology*, Kluwer, Boston, USA, 1-30, 2000.
- 655 Cook, P.G., Jolly, I.D., Leaney, F.W., Walker, G.R., Allan, G.L, Fifield, L.K., and Allison, G.B.: Unsaturated zone tritium and chlorine 36 profiles from southern Australia: Their use as tracers of soil water movement. *Water Resour. Res.*, 30, 1709-1719, doi: 10.1029/94WR00161, 1994.
- Costelloe, J.F., Peterson, T.J., Halbert, K., Western, A.W., and McDonnell, J.J.: Groundwater surface mapping informs sources of catchment baseflow, *Hydrol. Earth Syst. Sci.*, 19, 1599-1613, doi: 660 10.5195/hess-19-1599-2015, 2015.
- DataSearch Victoria: Victoria Department of Sustainability and Environment Spatial Warehouse: <http://services.land.vic.gov.au/SpatialDatamart/index.jsp>, last access: 10 June 2015.
- Department of Environment, Land, Water and Planning: Water Measurement Information System, <http://data.water.vic.gov.au/monitoring.htm>, last access: 10 February 2017.
- 665 Duvert, C., Stewart, M.K., Cendon, D.I., and Raiber, M.: Time series of tritium, stable isotopes and chloride reveal short-term variation in groundwater contribution to a stream, *Hydrol. Earth Syst. Sci.*, 20, 257-277, doi: 10.5194/hess-20-257-2016, 2016.
- ESRI. ArcGis Desktop: Release 10.2. Redlands, CA: Environmental Systems Research Institute, 2013.
- Fenicia, F., Savenije, H.H.G., Matgen, P., and Pfister, L.: Is the groundwater reservoir linear? Learning 670 from data in hydrologic modelling, *Hydrol. Earth Syst. Sci.*, 10, 139-150, doi: 10.5194/hess-10-139-2006, 2006.
- Freeman, M.C., Pringle C.M., and Jackson, C.R.: Hydrologic connectivity and the contribution of stream headwaters to ecologic integrity at regional scales, *J. Am. Water Resour. Ass.*, 43, 5-14, doi: 10.1111/j.1752-1688.2007.00002.x, 2007.

- 675 Gelhar, L.W., Welty, C., and Rehfeldt, K.R.: A critical review of data on field-scale dispersion in aquifers, *Water Resour. Res.*, 28, 1955-1974, doi: 10.1029/92WR00607, 1992.
- Hale, V.C., and McDonnell, J.J.: Effect of bedrock permeability on stream base flow mean transit time scaling relationships: 1. A multiscale catchment intercomparison, *Water Resour. Res.*, 52, 1358-1374, doi: 10.1002/2014WR016124, 2016.
- 680 Hebblethwaite, D., and James, B.: Review of surface water data, Kawarren, Hydrology & Surface Water Resources Section, Investigations Branch, Technical Services Division, Rural Water Commission of Victoria, Investigations Report No. 1990/45, 1990.
- Hrachowitz, M., Savenije, H., Bogaard, T.A., Tetzlaff, D., and Soulsby, C.: What can flux tracking teach us about water age distribution patterns and their temporal dynamics? *Hydrol. Earth System Sci.*, 17, 533-564. doi: 10.5194/hess-17-533-2013, 2013
- 685 Hrachowitz, M., Soulsby, C., Tetzlaff, D., Dawson, J.J.C., and Malcom, I.A.: Regionalization of transit time estimates in montane catchments by integrating landscape controls. *Water Resour. Res.*, 45, WR05421, doi: 10.1029/2008WR007496, 2009.
- Hrachowitz, M., Soulsby, C., Tetzlaff, D., and Speed, M.: Catchment transit times and landscape controls – does scale matter? *Hydrol. Process.*, 24, 117-125, doi: 10.1002/hyp.7510, 2010.
- 690 International Atomic Energy Agency: Global Network of Isotopes in Precipitation, available at: <http://www.iaea.org/water>, last access: March, 2016.
- Jensco, K.G., and McGlynn, B.: Hierarchical controls on runoff generation: Topographically driven hydrologic connectivity, geology and vegetation. *Water Resour. Res.*, 47, W11527, doi: 10.1029/2011WR010666, 2011.
- 695 Jurgens, B.C., Bohkle, J.K., and Eberts, S.M.: TracerLPM (Version 1): An Excel® workbook for interpreting groundwater age distributions from environmental tracer data, US Geol. Surv., Techniques and Methods Report 4-F3, US Geological Survey, Reston, USA. 60 pp., 2012.
- Kennedy, V.C., Kendall, C., Zellweger, G.W., Wyerman, T.A., and Avanzino, R.J.: Determination of the components of storm flow using water chemistry and environmental isotopes, Mattole River Basin, California, *J. Hydrol.*, 84, 107-140, doi: 10.1016/0022-1694(86)90047-8, 1986.
- 700 Kinzelbach, W., Aeschbach, W., Alberich, C., Goni, I.B., Beyerle, U., Brunner, P., Chiang, W. H., Rueedi, J., and Zoellmann, K.: A survey of methods for groundwater recharge in arid and semi-arid regions:

- early warning and assessment report series: Nairobi, Kenya, Division of Early Warning and
705 Assessment, United Nations Environment Programme, 101 pp., 2002.
- Kirchner, J.W., Tetzlaff, D., and Soulsby, C.: Comparing chloride and water isotopes as hydrologic
tracers in two Scottish catchments, *Hydrol. Process.*, 24, 1631-1645, doi: 10.1002./hyp.7676, 2010.
- Kirchner, J.W. Aggregation in environmental systems – Part 1: Seasonal tracer cycles quantify young
water fractions, but not mean transit times, in spatially heterogeneous catchments, *Hydrol. Earth
710 Syst. Sci.*, 20, 279-297, doi: 10.5194/hess-20-279-2016, 2016.
- Leonard, J., Lakey, R., and Cumming, S.: 1981. Gellibrand groundwater investigation interim report,
December 1981, Geological Survey of Victoria, Department of Minerals and Energy, Unpublished
Report 1981/132, 1981.
- Ma, W., and Yamanaka, T.: Factors controlling inter-catchment variation of mean transit time with
715 consideration of temporal variability, *J. Hydrol.*, 534, 193-204, doi: 10.1016/j.jhydrol.2015.12.061,
2016.
- Maloszewski, P.: Lumped-parameter models as a tool for determining the hydrologic parameters of
some groundwater systems based on isotope data, IAHS-AISH Publication 262, Vienna, Austria, pp.
271-276, 2000.
- 720 Maloszewski, P., and Zuber, A.: Determining the turnover time of groundwater systems with the aid
of environmental tracers: 1. Models and their applicability, *J. Hydrol.*, 57, 207-231, doi:
10.1016/0022-1694(82)90147-0, 1982.
- Maloszewski, P., and Zuber, A.: On the calibration and validation of mathematical models for the
interpretation of tracer experiments in groundwater, *Adv. Water Resour.*, 15, 47-62, doi:
725 10.1016/0309-1708(92)90031-V, 1992.
- Maloszewski, P., and Zuber, A.: Lumped parameter models for the interpretation of environmental
tracer data, in: International Atomic Energy Agency, Manual on mathematical models in isotope
hydrogeology, TECDOC-910: Vienna, Austria, International Atomic Energy Agency Publishing
Section, 9-58, 1996.
- 730 Maloszewski, P., Rauert, W., Stichler, W., and Herrmann, A.: Application of flow models in an alpine
catchment area using tritium and deuterium data, *J. Hydrol.*, 66, 319-330, doi: 10.1016/0022-
1694(83)90193-2, 1983.

- McDonnell, J.J., McGuire, K., Aggarwal, P., Beven, J., Biondi, D., Destouni, G., Dunn, S., James, A., Kirchner, J., Kraft, P., Lyon, S., Maloszewski, P., Newman, B., Pfister, L., Rinaldo, A., Rodhe, A., Sayama, T., Seibert, J., Solomon, K., Soulsby, C., Stewart, M., Tetzlaff, D., Tobin, C., Troch, P., Weiler, M., Western, A., Worman, A., and Wrede, S.: How old is streamwater? Open questions in catchment transit time conceptualization, modelling and analysis, *Hydrol. Process.*, 24, 1745-1754, doi: 10.1002/hyp.7796, 2010.
- 735
- McGlynn, B., McDonnell, J., Stewart, M., and Seibert, J.: On the relationship between catchment scale and streamwater residence time, *Hydrol. Process.*, 17, 175-181, doi: 10.1002/hyp.5085, 2003.
- 740
- McGuire, K.J., and McDonnell, J.J.: A review and evaluation of catchment transit time modelling, *J. Hydrol.*, 330, 543-563, doi: 10.106/j.jhydrol.2006.04.020, 2006.
- McGuire, K.J., McDonnell, J.J., Weiler, M., Kendall, C., McGlynn, B.L., Welker, J.M. and J. Seibert, 2005. The role of topography on catchment-scale water residence time. *Water Resources. Research*, Vol. 41, W05002, doi: 10.1029/2004WR003657, 2005.
- 745
- Morgenstern, U., and Daughney, C.J.: Groundwater age for identification of baseline groundwater quality and impacts of land-use intensification – The National Groundwater Monitoring Programme of New Zealand, *J. Hydrol.*, 456-457, 79-93, doi: 10.1016/j.jhydrol.2012.06.010, 2012.
- Morgenstern, U., and Taylor, C.B.: Ultra low-level tritium measurement using electrolytic enrichment and LSC, *Isot. Environ. Health Stud.*, 45, 96-117, doi: 10.1080/10256010902931194, 2009.
- 750
- Morgenstern, U., Stewart, M.K., and Stenger, R.: Dating of streamwater using tritium in a post nuclear bomb pulse world: continuous variation of mean transit times with streamflow, *Hydrol. Earth Syst. Sci.*, 14, 2289-2301, doi: 10.5194/hess-14-2289-2010, 2010.
- Mueller, M.H., Weingartner, R., and Alewell, C.: Importance of vegetation, topography and flow paths for water transit times of baseflow in alpine headwater catchments, *Hydrol. Earth Syst. Sci.*, 17, 1661-1679, doi: 10.5194/hess-17-1661-2013, 2013.
- 755
- Petrides, B., and Cartwright, I.: The hydrogeology and hydrogeochemistry of the Barwon Downs Graben aquifer, southwestern Victoria, Australia, *Hydrogeol. J.*, 14, 809-826, doi: 10.1007/s10040-005-0018-8, 2006.
- 760
- Sklash, M.G., and Farvolden, R.N.: The role of groundwater in storm runoff, *J. Hydrol.*, 43, 45-65, doi: 10.1016/0022-1694(79)90164-1, 1979.

- Soulsby, C., Malcolm, R., Helliwell, R., Ferrier, R.C., and Jenkins, A.: Isotope hydrology of the Allt a' Mharcaidh catchment, Cairngorms, Scotland: implications for hydrologic pathways and residence time, *Hydrol. Process.*, 14, 747-762, doi: 10.1002/(SICI)1099-1085(200003)14, 2000.
- 765 Stanley, D.R.: Resource evaluation of the Kawarren Sub-Region on the Barwon Downs Graben, RWC Investigations Branch Unpublished Report 1991/36, Rural Water Commission of Victoria, 1991.
- Stewart, M.K., and Fahey, B.D.: Runoff generating processes in adjacent tussock grassland and pine plantation catchments as indicated by mean transit time estimation using tritium, *Hydrol. Earth Syst. Sci.*, 14, 1021-1032, doi: 10.5194/hess-14-1021-2010, 2010.
- 770 Stewart, M.K., Morgenstern, U., and McDonnell, J.J.: Truncation of stream residence times: how the use of stable isotopes has skewed our concept of streamwater age and origin, *Hydrol. Process.*, 24, 1646-1659, doi: 10.1002/hyp.7576, 2010.
- Stewart, M.K., Morgenstern, U., Gusyev, M.A., and Maloszewski, P.: Aggregation effects on tritium-based mean transit times and young water fractions in spatially heterogeneous catchments and groundwater systems, and implications for past and future applications of tritium, *Hydrol. Earth Syst. Sci.*, 21, 4615-4627, doi: 10.5194/hess-21-4615-2017, 2017.
- 775 Stockinger, M.P., Bogena, H.R., Lucke, A., Diekkruger, B., Weiler, M., and Vereecken, V.: Seasonal soil moisture patterns: Controlling transit time distributions in a forested headwater catchment, *Water Resour. Res.*, 50, 5270-5289, doi: 10.1002/2013WR014815, 2014.
- 780 Swistock, B.R., DeWalle, D.R., and Sharp, W.E.: Sources of acidic storm flow in an Appalachian headwater stream, *Water Resour. Res.*, 25, 2139-2147, doi: 10.1029/WR025i010p02139, 1989.
- Tadros, C.V., Hughes, C.E., Crawford, J., Hollins, S.E., and Chisari, R.: Tritium in Australian precipitation: a 50 year record, *J. Hydrol.*, 513, 262-273, doi: 10.1016/j.jhydrol.2014.03.031, 2014.
- Teng, M.L.: Modelling the seasonal variation of groundwater yield and recharge of the Barwon Downs Aquifer, South-Western Victoria, MS Thesis, University of Melbourne, Australia, 1996.
- 785 Tetzlaff, D., Malcolm, I.A., and Soulsby, C.: Influence of forestry, environmental change and climatic variability on the hydrology, hydrochemistry and residence times of upland catchments, *J. Hydrol.*, 346, 93-111, doi: 10.1016/j.jhydrol.2007.08.016, 2007.

- 790 Tetzlaff, D., Seibert, J., and Soulsby, C.: Inter-catchment comparison to assess the influence of topography and soils on catchment transit times in a geomorphic province; the Cairngorm mountains, Scotland, *Hydrol. Process.*, 23, 1874, doi: 10.1002/hyp.7318, 2009.
- Tickell, S.J., Cummings, S., Leonard, J.G., and Withers, J.A.: Colac: 1:50 000 Map Geological Report, Geological Survey Report No. 89, Victoria Department of Manufacturing and Industry Development, 1991.
- 795 Timbe, E., Windhorst, D., Celleri, R., Timbe, L., Crespo, P., Frede, H.-G., Feyen, J., and Breuer, L.: Sampling frequency trade-offs in the assessment of mean transit times of tropical montane catchment waters under semi-steady-state conditions. *Hydrol. Earth Syst. Sci.*, 19, 1153-1168, doi: 10.5194/hess-19-1153-2015, 2015.
- Witebsky, S., Jayatilaka, C., and Shugg, A.: Groundwater development options and environmental
800 impacts – Barwon Downs Graben South-western Victoria, Department of Water Resources, Victoria, Draft Report, 1992.
- Yang, Q., Xiao, H., Zhao, L., Yang, Y., Li, C., Zhao, L., and Yin, L.: Hydrological and isotopic characterization of river water, groundwater and groundwater recharge in the Heihe River basin, northwest China, *Hydrol. Process.*, 25, 1271-1283, doi: 10.1002/hyp.7896, 2011.
- 805 Zuber, A., and Maloszewski, P.: Lumped Parameter Models, Environmental Isotopes in Hydrological Cycle, Vol. VI, Modelling, IAEA/UNESCO, Paris, Technical Document, 2001.
- Zuber, A., Witczak, S., Rozanski, K., Sliwka, I., Opoka, M., Mochalski, P., Kuc, T., Karlikowska, J., Kania, J., Jackowicz-Korczynski, M., and Dulinski, M.: Groundwater dating with ^3H and SF_6 in relation to mixing patterns, transport modelling and hydrochemistry, *Hydrol. Process.*, 19, 2247-2275, doi: 810 10.1002/hyp.5669, 2005.

Figure Captions

Fig. 1. Map of study area showing catchments, sampling locations and bedrock geology. Inset map shows location of study area in Australia. Source: DataSearch Victoria (2015). LG = Lardners Gauge, 815 UL = Upper Lardners, JA = Gellibrand River at James Access, PC = Porcupine Creek, TC = Ten Mile Creek, YC = Yahoo Creek, LK = Love Creek Kawarren, and LW = Love Creek Wonga. Current or discontinued gauging stations exist at all sites except for Upper Lardiners.

Fig. 2. Streamflows at which samples were collected relative to flow duration curves for Lardners Gauge (**2a**), Gellibrand River at James Access (**2b**) – additional data (black circles) from Atkinson 820 (2014), Porcupine Creek (**2c**), Ten Mile Creek (**2d**), Yahoo Creek (**2e**) and Love Creek (**2f**) Streamflow data from Department of Environment, Land, Water and Planning (2017).

Fig. 3. Hydrographs for Lardners Gauge (**3a**) and Love Creek (**3b**) together with the timing of sample collection. Data from Department of Environment, Land, Water and Planning (2017).

Fig. 4. ^3H activities of stream water as a function of streamflow for all catchments except Upper 825 Lardners which is ungauged. ^3H data from Supplement, streamflow data from Department of Environment, Land, Water and Planning (2017) or calculated as discussed in the text. Shaded boxes show predicted range of rainfall ^3H activities from Tadros et al. (2014) and soil waters from Atkinson (2014).

Fig. 5. ^3H activities as a function of TDS for all catchments (data from Supplement). Strong inverse 830 correlations between ^3H activities and TDS exist for Lardiners Gauge and Porcupine Creek.

Fig. 6. ^3H activities as function of nitrate concentrations (**6a**) and sulphate concentrations (**6b**). Data from Supplement. Strong ($R^2 > 0.7$) correlations indicated.

Fig. 7. ^3H activities vs. runoff coefficients for the March 2015 samples (data from Table 1 and Supplement). Although a strong correlation ($R^2 = 0.94$) exists, it may be a result of the grouping of 835 the samples.

Fig. 8. Estimated MTTs vs. ^3H activities in the stream waters calculated using the Exponential Piston Flow Model (EPM) with EPM ratios of 0.33, 1.0 and 3.0 and the Dispersion Model (DM) with D_p values of 0.05 and 0.5. Data from Supplement and Table 3.

840 **Fig. 9.** MTTs calculated using the EPM model with an EPM ratio of 1.0 (Table 3) as a function of streamflow (Q) for Lardners Gauge (**9a**), Gellibrand River at James Access (**9b**) - black circles are data from Atkinson (2014), Porcupine Creek (**9c**), Ten Mile Creek (**9d**), Yahoo Creek (**9e**), and Love Creek (**9f**) - blue circles are Love Creek Kawarren and red circles Love Creek Wonga. Curves are exponential trend lines. Streamflow data from Department of Environment, Land, Water and Planning (2017) or calculated as discussed in the text

845 **Fig. 10.** Impact of varying rainfall ^3H inputs on MTTs calculated using the EPM model with an EPM ratio of 1.0. The three rainfall inputs modern and pre bomb-pulse ^3H activities of 2.4, 2.8, and 3.2 TU and the ^3H activity of the bomb-pulse rainfall was varied by a similar proportion as discussed in the text.

850 **Fig. 11:** Variation in MTT as a function of streamflow at Porcupine Creek for January 1990 to January 1994 calculated using the relationship between EC and ^3H activity (Supplement) and monthly EC data from the Department of Environment, Land, Water and Planning (2017). Streamflow data also from Department of Environment, Land, Water and Planning (2017).

Table 1. Summary of the attributes of the upper Gellibrand River catchments

| Catchment (Fig. 1) | Drainage Area (km²) | Drainage Density (m m⁻²) | Forest Cover (%) | Average Slope (°) | Runoff Coefficient (%) |
|--------------------------------------|---------------------------------------|--|-------------------------|--------------------------|-------------------------------|
| Upper Lardners (UL) | 20.0 | 1.0 x 10 ⁻³ | 92 | 11.0 | - |
| Lardners Gauge (LG) | 51.6 | 1.1 x 10 ⁻³ | 91 | 11.0 | 33.0 |
| Gellibrand River at James Access(JA) | 81.0 | 9.2 x 10 ⁻⁴ | 95 | 11.3 | 39.0 |
| Porcupine Creek (PC) | 33.6 | 9.5 x 10 ⁻⁴ | 88 | 5.9 | 11.4 |
| Ten Mile Creek (TC) | 9.6 | 8.8 x 10 ⁻⁴ | 88 | 5.7 | 12.0 |
| Yahoo Creek (YC) | 16.6 | 8.7 x 10 ⁻⁴ | 95 | 8.6 | 10.5 |
| Love Creek Kawarren (LK) | 74.4 | 9.3 x 10 ⁻⁴ | 82 | 6.4 | 10.6 |
| Love Creek Wonga (LW) | 91.7 | 9.2 x 10 ⁻⁴ | 78 | 6.7 | 8.6 |

Table 2. Correlation between catchment attributes and ³H activities for the upper Gellibrand River catchments

| Catchment Attribute | Sampling Date | R ² |
|---------------------|---------------|----------------|
| Area | Jul 2014 | 0.01 |
| | Sep 2014 | 0.26 |
| | Mar 2015 | 0.06 |
| | Sep 2015 | 0.57 |
| Drainage Density | Jul 2014 | 0.00 |
| | Sep 2014 | 0.58 |
| | Mar 2015 | 0.40 |
| | Sep 2015 | 0.40 |
| Runoff Coefficient | Jul 2014 | 0.10 |
| | Sep 2014 | 0.66 |
| | Mar 2015 | 0.94 |
| | Sep 2015 | 0.19 |
| Forest Cover | Jul 2014 | 0.51 |
| | Sep 2014 | 0.15 |
| | Mar 2015 | 0.24 |
| | Sep 2015 | 0.01 |
| Slope | Jul 2014 | 0.39 |
| | Sep 2014 | 0.55 |
| | Mar 2015 | 0.87 |
| | Sep 2015 | 0.15 |

Table 3. Summary of calculated mean transit times (MTT) for the upper Gellibrand River catchments

| Location (Fig. 1) | Date | Q ^a 10 ³ m ³ day ⁻¹ | ³ H (TU) | MTT (years) | | | | |
|---------------------------------------|------------|--|------------------------|------------------|------|--------------|-----------------|------|
| | | | | EPM ^b | | | DM ^c | |
| | | | | 0.33 | 1.0 | 3.0 | 0.05 | 0.5 |
| Upper Lardners (UL) | 10/07/2014 | - | 1.99 | 9.9 | 9.6 | 8.8 | 9.0 | 11.2 |
| | 28/09/2014 | - | 1.77 | 15.7 | 12.9 | 11.8 | 12.2 | 17.6 |
| | 20/03/2015 | - | 1.54 | 24.2 | 18.5 | (16.2, 41.4) | 16.3 | 26.2 |
| | 10/09/2015 | - | 1.99 | 8.8 | 8.2 | 8.6 | 8.3 | 9.9 |
| Lardners Gauge (LG) | 10/07/2014 | 151.3 | 1.94 | 10.8 | 10.2 | 9.3 | 9.6 | 12.3 |
| | 28/09/2014 | 32.8 | 1.94 | 10.6 | 10.1 | 9.2 | 9.5 | 12.1 |
| | 20/03/2015 | 5.0 | 1.64 | 19.8 | 15.4 | (14.1, 45.7) | 14.2 | 21.6 |
| | 10/09/2015 | 116.6 | 1.97 | 9.1 | 8.5 | 8.7 | 8.6 | 10.2 |
| | 4/11/2015 | 12.7 | 1.77 | 13.8 | 12.4 | 11.2 | 11.6 | 15.8 |
| Gellibrand River at James Access (JA) | 13/03/2012 | 18.5 | 1.90 | 15.5 | 12.3 | 11.8 | 11.7 | 17.7 |
| | 26/04/2012 | 30.4 | 1.80 | 19.2 | 14.8 | 13.1 | 13.4 | 21.4 |
| | 10/07/2014 | 255.2 | 2.04 | 8.7 | 8.7 | 8.1 | 8.2 | 9.7 |
| | 28/09/2014 | 39.1 | 1.93 | 10.8 | 10.2 | 9.4 | 9.7 | 12.4 |
| | 20/03/2015 | 8.8 | 1.73 | 16.2 | 13.5 | 12.2 | 12.6 | 18.2 |
| | 10/09/2015 | 204.4 | 2.08 | 7.3 | 6.8 | 7.7 | 7.0 | 8.1 |
| Porcupine Creek (PC) | 10/07/2014 | 50.4 | 1.97 | 10.3 | 9.8 | 9.0 | 9.2 | 11.7 |
| | 27/09/2014 | 3.3 | 1.68 | 19.3 | 14.9 | (13.9, 44.7) | 13.8 | 21.0 |
| | 20/03/2015 | 1.0 | 0.20 | 179 | 100 | 69.5 | 89.6 | 234 |
| | 10/09/2015 | 9.7 | 2.08 | 7.3 | 6.8 | 7.7 | 7.0 | 8.1 |
| | 4/11/2015 | 0.6 | 0.40 | 137 | 94.8 | 68.4 | 78.7 | 162 |
| Ten Mile Creek (TC) | 10/07/2014 | 8.6 | 1.74 | 17.1 | 13.6 | 12.5 | 12.7 | 18.8 |
| | 27/09/2014 | 0.6 | 1.00 | 58.3 | 68.5 | 62.5 | 60.1 | 66.3 |
| | 20/03/2015 | 0.2 | 0.44 | 128 | 92.5 | 67.2 | 76.4 | 150 |
| | 10/09/2015 | 1.7 | 1.09 | 48.3 | 55.5 | 62.0 | 57.0 | 53.5 |
| | 4/11/2015 | 0.1 | 0.53 | 109 | 90.3 | 67.2 | 73.3 | 130 |
| Yahoo Creek (YC) | 11/07/2014 | 23.0 | 2.14 | 6.9 | 6.8 | 7.2 | 7.0 | 7.6 |
| | 28/09/2014 | 1.2 | 1.19 | 44.7 | 52.0 | (60.6, 27.4) | (55.3, 24.8) | 49.2 |
| | 20/03/2015 | 0.4 | 0.43 | 132 | 93.1 | 67.4 | 77.2 | 154 |
| | 10/09/2015 | 3.9 | 1.30 | 34.8 | 31.3 | (34.3, 60.0) | (27.6, 50.7) | 37.9 |
| Love Creek Kawarren (LK) | 10/07/2014 | 102.9 | 1.85 | 13.3 | 11.5 | 10.5 | 10.9 | 15.0 |
| | 27/09/2014 | 6.7 | 1.34 | 35.3 | 33.5 | (32.3, 59.2) | (24.8, 51.2) | 38.4 |
| | 20/03/2015 | 2.0 | 0.48 | 121 | 91.2 | 67.0 | 75.1 | 141 |
| | 10/09/2015 | 18.6 | 1.91 | 10.4 | 9.8 | 9.5 | 9.5 | 11.9 |
| | 4/11/2015 | 1.2 | 0.58 | 100 | 88.6 | 66.8 | 71.5 | 120 |
| Love Creek Wonga (LW) | 10/07/2014 | 103.5 | 1.86 | 13.1 | 11.4 | 10.4 | 10.8 | 14.8 |
| | 28/09/2014 | 6.0 | 1.34 | 35.7 | 34.2 | (32.1, 59.3) | (24.8, 51.4) | 38.8 |
| | 20/03/2015 | 2.0 | 0.55 | 109 | 89.4 | 66.4 | 72.6 | 127 |
| | 10/09/2015 | 19.6 | 1.88 | 11.0 | 10.4 | 9.8 | 9.9 | 12.6 |

a: Discharge

b: Exponential-Piston Flow model with EPM parameter of 0.33, 1 and 3

c: Dispersion model with Dispersion parameter of 0.05 and 0.5

Table 4. Estimates of the difference between calculated mean transit times (MTT) and that estimated from the mixing of waters from different tributaries at Love Creek Kawarren.

| Sample Date | MTT (years) | |
|-------------|-------------------------------|------|
| 10/07/2014 | MTT _e ^a | 15.4 |
| | Sample MTT ^b | 11.5 |
| | Difference (years) | 3.9 |
| | Difference (%) | 25.5 |
| 27/09/2014 | MTT _e | 40.9 |
| | Sample MTT | 33.5 |
| | Difference (years) | 7.4 |
| | Difference (%) | 18.1 |
| 20/03/2015 | MTT _e | 87.4 |
| | Sample MTT | 91.2 |
| | Difference (years) | 3.8 |
| | Difference (%) | 4.4 |
| 10/09/2015 | MTT _e | 15.5 |
| | Sample MTT (years) | 9.8 |
| | Difference (years) | 5.7 |
| | Difference (%) | 36.7 |

a: Estimated from the tributary inputs (Eq. 2)

b: Estimated using the EPM (1.0) lumped parameter model (Table 3).



















