

# Technical note: Stage and water width measurement of a mountain stream using a simple time-lapse camera

Pauline Leduc <sup>1</sup>, Peter Ashmore <sup>1</sup>, and Darren Sjogren <sup>2</sup>

<sup>1</sup>University of Western Ontario, Department of Geography, London, Ontario, Canada


<sup>2</sup>University of Calgary, Department of Geography, Calgary, Alberta, Canada

*Correspondence to:* Pauline Leduc (pleduc3@uwo.ca)

**Abstract.** Remote sensing applied to river monitoring adds complementary information useful to understand the system behavior. In this paper we present a method for visual stage gauging and width measurement method water surface width measurement using a ground-based time-lapse camera and a fully automatic image analysis algorithm for flow monitoring at a river cross-section of a steep bouldery channel. The remote stage measurement was coupled with a water level logger (pressure transducer) on site and shows that the image-based method gives a reliable estimate of the water height variation and daily flow record when validated against the pressure transducer ( $R = 0.91$ ). From the remotely sensed pictures, we also extract extracted the water width and show that it is possible to extract correlation between correlate water surface width and stage. The images also provide valuable ancillary information for interpreting and understanding flow hydraulics and site weather conditions. This image-based gauging method is a reliable, informative and inexpensive alternative or adjunct to conventional stage measurement especially for remote sites.

## 1 Introduction

Conventionally river discharge is gauged using continuous measurement of stage (typically, at temporary sites, using a pressure transducer and data logger) that is converted to continuous discharge data using a stage-discharge curve established for the site. In some cases installation of a stage recorder is problematic and in complex flows interpretation of stage fluctuations may be uncertain. These conditions may arise, for example in steep, bouldery or rock bed channels. Image-based measurements may provide equivalent data to the pressure transducer record while giving additional information such as water width, state of flow, water surface configuration and indications of flow hydraulics. For larger rivers, satellite or aerial images may provide useful stream gauging data (e.g. Smith et al. (1996); Gleason and Smith (2014)Smith et al. 1996; Gleason and Smith 2014) but for small streams and very high frequency (minutes) over extended periods, satellite and airborne platforms do not provide sufficient resolution or temporal frequency (Gleason et al., 2015). Ground-based remote sensing increasingly is providing a wide range of data for many applications for monitoring river flow and morphology especially in smaller channels or where high frequency data are needed for extended time periods (Bertoldi et al., 2012; Wheaton et al., 2013; Javernick et al., 2014; Gleason et al., 2015  
(Bertoldi et al., 2012; Williams et al., 2011; Javernick et al., 2014; Gleason et al., 2015)).



**Figure 1.** Map of the site location (left) and view of the Dome stream (right), image attribution - J.T. Gardner.

Remote sensing based on photogrammetry technology provides an efficient topographic tool and access to topography and hydraulic characteristics (Javernick et al., 2014). However, the large amount of data needed to generate topography make it difficult to apply on small streams with a high sampling frequency (Gleason et al., 2015).

In relation to flow characteristics, water surface width can be measured from ground-based cameras (Ashmore and Sauks, 5 2006; Gleason et al., 2015) and correlated with discharge to establish a width-discharge curve in some types of rivers, and local flow velocity has been measured using particle image velocimetry

([Creutin et al., 2003](#); [Hauet et al., 2008](#); [Tsubaki et al., 2011](#); [MacVicar et al., 2012](#))

([Creutin et al., 2003](#); [Hauet et al., 2008](#); [Tsubaki et al., 2011](#); [MacVicar et al., 2012](#); [Ran et al., 2016](#); [Stumpf et al., 2016](#)). Direct measurement of stage is less well developed although Young et al. (2015) obtained a water level and discharge record using 10 manual image processing on a small, steep channel using inexpensive ground-based cameras combined with ~~known~~ channel geometry and roughness ~~assumption~~ assumptions. A more automated method that does not require manual image classification and channel geometry and hydraulic assumptions would be useful.

Methods for automated image selection and measurement are also needed in order to process  $10^3$  or  $10^4$  images that may come from high frequency time-lapse RGB imagery (Gleason et al., 2015). Here we test a simple time-lapse ~~cameras~~ camera 15 system for directly measuring stage and water surface width using image classification, and develop automated image selection and classification processes that retain a much larger proportion of the images than the process described by Gleason et al. (2015). We apply the method to monitor flow in a steep, ~~boulder~~ bouldery glacier-fed mountain stream which presents challenges for any form of flow gauging.

## 2 Measurement method

### 20 2.1 Site

The study site is located on a small, steep, bouldery reach of a stream, approximately 100 m downstream of the outlet from the small pro-glacial lake of the Dome Glacier, in Jasper National Park, Alberta, Canada (Fig. 1). Site elevation is about 1800 m above sea level and the upstream drainage area is primarily the subglacial drainage of the Dome Glacier which is about 3 km in area. The stream is a left bank tributary of the Sunwapta River and the primary larger purpose of the study is to better estimate


the total discharge of a braided section of the river downstream of the Sunwapta–Dome Glacier tributary confluence by directly monitoring the Dome Glacier streamflow during the summer meltwater flow season. The Water Survey of Canada gauging station on Sunwapta River, at the outlet of the pro-glacial Sunwapta Lake, a few hundred meters upstream of the confluence with the Dome Glacier stream (Fig. 1) provides detailed discharge records for the braided reach but does not account for the tributary contribution. Ashmore and Sauks (2006) measured water surface width from oblique time-lapse ~~oblique~~ images on the braided reach of Sunwapta River downstream of this tributary and established a relationship with discharge at the Water Survey of Canada gauging station using a small number of gauging measurements in the braided reach. But continuous measurement of the discharge of the Dome Glacier stream has not previously been used for monitoring this narrow, steep tributary to directly measure its contribution, daily flow variation and timing of daily peak flow relative to the Sunwapta River discharge. The stream flow is mainly controlled by snow and glacier melt in summer producing a regular diurnal hydrograph with ~~long-wave~~ ~~long-period~~ changes due to average air temperature and synoptic weather conditions in the summer. A straight, single thread reach of the channel was chosen for the gauging location.

## 2.2 Field setting


The main objective of the study was to use ground based remote sensing to measure the flow characteristics (flow stage and water surface width) and peak flow periods in the daily flow cycle in this pro-glacial stream and assess the flow and timing of peaks relative to the flow of Sunwapta River. Standard pressure transducer measurement of stage is possible at this site (and is used here for comparison with image-based measurements) but we are interested in testing whether reliable image-based measurements are possible to complement or replace stage-only data with water level, water surface width and state of flow information from remote camera monitoring. A Reconyx Hyperfire camera was set on the right side of the reach (Fig. 2), clamped to a pole hammered into the rocky ground, facing an almost vertical face of a large boulder on the opposite bank of the river. The entire stream width is visible in the pictures (Fig. 3).

Pictures were taken every 15 minutes during daylight (typically 6 a.m. – 10 p.m. at this location in the summer and the daily peak is usually 4 p.m. – 7 p.m. ) which corresponds to the sampling interval and timing of the gauging station on the Sunwapta River. During the study period, from June 13<sup>th</sup> to September 22<sup>nd</sup> 2015, 7284 pictures were taken, saved on ~~the an~~ SD card and downloaded at the end of the study period. Two stage boards were installed one on each side of the stream (Fig. 3). On the left bank a water level logger was installed in a vertical pipe in the stream bed next to the stage board with stage recorded at 15 minute intervals throughout the study period for comparison with the image-based stage data. Level data were compensated for atmospheric pressure. The boulder has an almost vertical surface, facing the camera and it was ~~also~~ calibrated for stage measurement in addition to the stage boards.

In the rest of the paper, the phrase “transducer data-set” and the notation  $H_{transducer}$  correspond to the stage coming from the pressure transducer and the phrase “camera data-set” and notation  $H_{camera}$  correspond to the stage coming from the image analysis.



**Figure 2.** Camera set up. The camera is set on the right bank of the stream, a few meters above the water level. The camera is clamped to a pole hammered into the ground.



**Figure 3.** Reconyx raw picture showing the installation of stage boards, pressure transducer and boulder used for gauging (center of picture). Black lines represent the 3 different tested profiles.

### 3 Stage and water width measurement

#### 3.1 Picture quality

A goal of this method is to minimize any manual treatment of the images to select an analysis set of images and to estimate water stage and water width from those images. Consequently a screening treatment was applied to remove unusable pictures prior 5 to analysis. The initial RGB picture size is ~~1536\*2048-2048\*1536~~ pixels, which was saved in ~~.jpg~~ format and converted into ~~grey-scale~~. Dark pictures corresponding to twilight ~~and night~~ were identified using a very low standard deviation of the grey intensity of the picture and automatically deleted from the data set. Over the summer, weather conditions also negatively impacted image quality. During rain or snow episodes, the images are blurrier and water drops on the camera block the view. Snow cover on the ground is a lighter shade than the water, the opposite of the normal weather conditions. In the 10 late afternoon and evening, the sun shines into the camera and induces two kinds of issues. First, sun light directly hits the camera and the picture is almost entirely saturated. Second the water surface is saturated by reflections and the boulder facing the camera creates a large dark shadow on the water surface. Each of these issues interferes with the image processing and had to be compensated for.


For all the previous reasons (rain, drops on the lens, snow, sun effects) and as mentioned in Gleason et al. (2015) and Young 15 et al. (2015), pictures have to be ~~sorted~~classified. We developed automatic ~~sorting~~classification processes and set two different output options : 1. the image is removed from the data set or 2. The image is retained but different processes of classification and water surface detection are used for particular conditions (see section 3.2).

#### 3.2 Picture ~~sorting~~classification


Image quality issues arise throughout the process of water detection and width estimation: poor weather conditions (Fig. 4 (a)), 20 shadows (Fig. 4 (b)), emerged rocks in the stream (Fig. 4 (c)) and light snow cover on the edge on the stream (Fig. 4 (d)). To deal with those four issues, four different selection tests based on different target zones in the images were applied before or during the stage and water width measurements. All four tests were applied to the ~~grey-scale~~grey-scale pictures and in the following descriptions standard deviation or averages refer to calculations on pixel intensity.

The first test was made to remove pictures taken under bad weather conditions (heavy snow or rain episodes, and sunlight 25 directly into the camera) and it is based on the rocky zone target on the left of the picture (Test 1, area 1 on Fig. 5). The standard deviation of this surface is high due to the apparent roughness coming from the rocky surface. Under adverse weather conditions, that area is smoother and the standard deviation drops (snow cover with normal weather condition is not included in that test because even with snow, the roughness from the block elevation makes the standard deviation high enough) and the picture was removed from the data sets. Over the 6717 pictures, 12% were removed after this test (Fig. 6).

30 During the water surface detection, a significant boulder shadow sometimes interfered with the ~~ea~~leuationdetection. Figure 5 shows the target zones 2 and 3 that were used to detect the boulder shadow (Test 2), combining a height reflectance of the water (on zone 2) and a dark zone on the boulder face (on zone 3). A different water detection threshold was applied for those pictures (see section 3.3).




**Figure 4.** Images illustrating the main issues affecting image quality and measurements during the stage and width calculation: (a) heavy weather conditions (b) boulder shadow and intense water reflection (c) emerged rocks on the main channel at low flows (d) light snow cover on the edge of the stream.



**Figure 5.** The eight different target zones used in the picture [sorting-classification](#) process.

Two main issues interfering with the water edge detection arise: the rocky bottom of the stream (Test 3) and the snow on the river banks (Test 4). On Figure 5, target zone 4 is used as a water reference, because this part of the stream always had water even at a very low stage. Target zone 5 and 6 are located where rocks are emerged emerge at low flows. The mean value of both target zones is compared to the mean value of the reference zone, the target value less than half the reference zone corresponds to submerged rocks. The threshold based on half the value of the reference zone was set empirically after going through a



**Figure 6.** The picture [sorting classification](#) process: four different tests are used to remove heavy weather conditions or night pictures from the data-set (Test 1), to detect pictures with an important boulder shadow (Test 2), or emerged rocks on the main channel at low flow (Test 3) and finally a light snow cover on the edge of the stream (Test 4).

substantial portion [of](#) the data set. As described in section 3.6, width estimate is based on cross sections and the profile with emerged rocks is re-sized based on the rock emergence/submergence.

Test number	Target area (Fig. 4)	Picture issue	Conditions (the test is failed if the condition is fulfilled)	Action if test failed
1	1	Night time, heavy rain, snow...	Standard deviation lower than 20	Removed from the data set
2	2 - 3	Boulder shadow	Area 2: mean value higher than 235 - indicating almost direct reflection on the water surface Area 3: mean value lower than 95 - indicating a dark area on the boulder surface	The water detection is based on the second highest gradient point instead of the first
3	4 - 5 - 6	Emerged rocks on the main stream	Area 4 is the water colour reference value Area 5 and 6: the mean value is less than half of the reference value	The width calculation profile is re-sized
4	7 - 8	Light snow cover on the edge of the stream	Area 7 and 8: the mean value is higher than the average of the entire picture and the standard deviation of both area is less than 50 (indicating a smooth area)	The width calculation profile is re-sized


**Table 1.** The 4 different picture classification tests. The standart deviation ranges from 0 to 255. Threshold are set using both particular and normal conditions pictures. The different areas have been choosen to avoid parameter distribution overlap between normal and particular conditions (see Supplementary material).

The snow cover on the edge of the stream is detected using Test 4 and target zone 7 and 8. The test is based on the lighter color of the snow, mean values on zone 7 and 8 are compared to the mean value of the picture, and snow cover corresponds to brighter values on the target zone. As for the case of emerged rocks, the cross section used for the width detection is re sized.

The 4 tests are summarized in Table 1.

### 5 3.3 Water level

Stage was measured by detecting the water surface line on the images. Instead of a global, manual approach using edge detection (Young et al., 2015), we based the analysis on local site conditions. Black lines on Figure 3 on both stage boards and




**Figure 7.** Grey-scale profiles for water surface measurement. (a) the first stage board on the right side of the stream, (b) the second stage board, on the left side of the river, and (c) on boulder vertical surface. The red and blue line shows 2 different water elevations days apart.

the vertical surface of the boulder represent each location where grey-scale profiles from the images were extracted to detect the transition from water to stage board or boulder surface in the image (Fig. 7) and so locate the water surface in image space.

The water and boulder/stage board transition signal is clear for each water level location. On both stage boards the image signal is smoother on the water than on the board itself (Fig. 7). However, the transition between rock and water is more obvious 5 on the boulder site (Fig. 7 (c)) than on the left bank stage board (Fig. 7 (b)). On the board located on the right bank of the stream the transition between the board and the water is not as clear and the flow stage rise is more difficult to detect. Furthermore, at low stage the bottom of the scale emerged above the water and the measurement was then impossible. Consequently this stage 10 board was removed from the analysis. Without the boulder we would have used the remaining stage board as the water stage estimation but in this particular site the stage board on the far side is used as an independent visual check because the boulder surface gave a clearer signal. We mainly used the boulder station to estimate the flow depth but the boulder is not a requirement for the method and any natural or artificial almost-vertical surface located on the stream could be used.

On the boulder the water transition corresponds to an obvious inflection point in the image intensity (Fig. 8 (a)) and a local peak in the gradient of the smoothness profile (Fig. 8 (b)). The inflection point is detected using two conditions. The first, on the gradient profile, was used to pick high gradient values. The second condition was based on a grey shade threshold so that 15 only the lowest values in the grey-scale profile are considered since because higher values represent the rock becoming darker when it is wet. Using this combined method, the water line position in pixel coordinates can be automatically detected for each picture. In pictures with the boulder shadow issue (see section 3.2), the second highest gradient point is considered instead of the first.



**Figure 8.** The boulder gauging station profile. The dashed lines represent the water surface. Water is located below those lines. (a) the grey-scale profile, and (b) the gradient of the profile, the calculation step is 2 pixels. The gradient plot makes the inflection point and the water level detection easier.

### 3.4 Water depth calibration

Given that the boulder surface is almost vertical, and roughly perpendicular to the axis of the camera lens, we assume a linear relationship between the stage and the water surface position in pixel coordinates: Eq. 1, where  $H_m$  is the stage in meters,  $d_{pixel}$  the water surface position on the picture in ~~pixel~~ pixels.


$$5 \quad H_m = a \cdot d_{pixel} + b \quad (1)$$

The slope  $a$  of Eq. 1 is given by the millimeters/pixel (mm/px) relationship extracted from the pictures. The camera is fixed, therefore the value is consistent through the entire picture set. Using ~~the board stage~~ ~~a measuring device (large ruler)~~ on the boulder surface, we get  ~~$a = 6 \text{ mm/px}$~~   $a = 6 \text{ mm/px}$ .

To determine the intercept  $b$  of Eq. 1, which is the ground reference of the flow stage, we used part of the stage logger data-set, taking randomly 100 values, to extract the intercept  $b = -1.6 \cdot 10^{-3} \text{ mm}$   $b = -1.6 \cdot 10^{-3} \text{ mm}$ . This gives a local datum ~~for the boulder stage~~. We also calibrated the stage board located on the side of the boulder on the far side of the picture. This water depth calibration is relative ~~the our site and depends on the site~~ ~~particular setting~~ to this gauging station and particular to ~~the site~~.

### 3.5 Stage validation

15 Figure 9 (a) shows the comparison between the transducer data-set ( $H_{transducer}$ ) and the camera data-set ( $H_{camera}$ ). The stage prediction from picture analysis is a good estimation of the transducer water level ( $R = 0.91$ ). The water measurement using the stage board located on the side of the boulder ~~with a proper calibration~~ has a lower correlation coefficient ( $R = 0.71$ ). The




**Figure 9.** Comparison of the transducer data-set ( $H_{transducer}$ ) and the camera data-set ( $H_{camera}$ ) (a) the scatter plot, the cluster of outliers points represented with open symbols has been manually checked and corresponds to [wave-waves](#) at the pressure transducer, (b) the error distribution, the normal distribution is set with a mean value of  $0.00m$  and a standard deviation of  $0.02m$  and (c) the residual plot  $H_{transducer}$ - $H_{camera}$  regarding  $H_{transducer}$ , the red line represents the linear regression showing a tilt on the water depth estimation: at high discharges the camera data set underestimates the transducer data set and at low discharges the camera data set overestimates the transducer data set.

mean value of the difference of the transducer data-set and the camera data-set is  $\mu = 0.00m$   $\mu = 0.00 m$  and a standard deviation is  $\sigma = 0.02m$   $\sigma = 0.02 m$ . Considering a normal distribution (Fig. 9 (b)), the 95% confidence interval on the error estimation is  $[-0.04; 0.04]$  m (the error estimation for the stage board measurement is  $[-0.06; 0.06]$  m). Pictures corresponding to the cluster of outliers have been manually checked. Those points correspond to pictures where the water surface is correctly detected but

5 corresponds to waves at the gauging station or at the pressure transducer.

At very low discharge, boulder clusters emerge near the left bank creating pools and small channels. This channel configuration creates a pond at the water level logger at very low discharge and probably disconnects the water stage measured using the image analysis from that of the pressure transducer. Based on this result the stage measured from image analysis gives a good estimation of the water stage. The high and low frequency variations (i.e. daily or monthly variations) on the transducer 10 signal are well reproduced by the camera data-set (Fig. 10). The daily snow/ice melt hydrograph which is characteristic of the site, with consistent times of low and high flow each day in the absence of rainstorms, are also shown in Figure 10. While the results show that the image-based time-lapse method works well, there are some errors that could be reduced. The hypothesis for our stage measurement and the water depth calibration equation is the constant millimeters/pixel (mm/px) relationship over the boulder surface. The underlying assumptions are that the vertical surface is flat and the camera distortion doesn't induce 15 a large variation. Realistically, as the boulder is a natural rock, the vertical face is not exactly vertical and we are not able to estimate the distortion variation. The probable inconstant mm/px relationship may induce the tilt on the scatter plot (Fig. 9 (a) and (c)). The comparison with the transducer data set shows that at high discharges the camera data set underestimates the transducer data set and at low discharges the camera data set overestimates the transducer data set. The mm/px variations could induce the slightly curved shape of the scatter plot (Fig. 9) but only a better camera resolution (or image scale) [and a more](#) 20 [precise geometry between camera and vertical calibration surface](#) would improve the mm/px relationship.



**Figure 10.** Summer 2015 stage time series. The black line represents the transducer data-set ( $H_{transducer}$ ) and the dashed red line is the camera data-set ( $H_{camera}$ ). The estimated error on the camera stage relative to pressure transducer is around 3 cm. (a) is from mid June to end of July 2015. The camera data-set fits the transducer data-set. The daily trend as well as the general monthly trend are reproduced (b) from August July 5<sup>th</sup> to August July 10<sup>th</sup> 2015. At hourly resolution, the trend of the camera stage follows the transducer data closely. However, on rising stage, the camera data-set underestimates the transducer water stage, and on falling stage, the picture data-set slightly overestimates the transducer stage.




**Figure 11.** The width measurement at low (a) and high (b) discharges. The left line is the water level at the boulder station. The dashed line is the cross section and the right ticks are the detected flow edges.

### 3.6 Water width measurement

Using the time-lapse images we also estimated the water surface width. As we did for the stage, width was measured by detecting the threshold between the river and the rocks on both banks. During the field work, flow width was also calibrated on one cross section. For picture analysis, considering the rocks masking the view of the water surface and standing waves in 5 the flow, the measurement cross section was moved about 2 m downstream keeping the same angle across the channel as the calibrated profile (Fig. 11).

On both sides of the stream some boulders appear at low discharges that are too large to be mobilized by daily high flows. On both rocky areas, a test was done to detect if the rocks had emerged (Test 3 and 4, Fig. 6). If they had, the interrogation



**Figure 12.** The pixel - meter conversion.  $D_{pixel}$  is the flow width in ~~pixel~~pixels and  $D_m$  is the flow width in meters. The rating curve was established using a measuring tape across the flow width. The data set has been ~~fit~~fitted using Eq. 2.

area was changed accordingly. On the profile, and as with the water stage, the highest gradient of the grey-scale plot profile was used to detect water edges.


### 3.7 Water width calibration

A measuring tape was extended across the entire Dome stream. The distance across the channel was measured in 0.5 m intervals and the image distance in pixels was converted to meters (Fig. 12). The conversion from distance in pixels to distance in meters is done using Eq. 2, where  $D_{pixel}$  is the distance in ~~pixel~~pixels extracted from the picture analysis and  $D_m$  the distance in meters. The measuring tape was not perfectly straight due to the inherent limitations of field work such as the ~~of~~flow conditions and channel structure, therefore the conversion into meters may be slightly inconsistent, which could induce the shift on Figure 10 around  $D_{pixel} = 200$ .

$$10 \quad D_m = 0.05 * (D_{pixel} - 10)^{0.95} + 0.45 \quad (2)$$

The width measurement faces two principal issues: the water edge detection and the calibration. The width measurement is tightly linked to the boulders on the side of the stream. As the stream widens, the boulders at the channel edge are submerged and the grey-scale shift at the edge of the water is less sharp. Inaccurate detection cannot be corrected because of a lack of field validation data for the water width.

15 The calibration is very sensitive to the camera position. Additional information on camera angle and geometry would increase the calibration accuracy and improve the width measurement. Furthermore, moving the cross section a small distance away from the calibrated cross section induced some error on the conversion length in meters from length in ~~pixel~~pixels. Nevertheless with some refinement, as the distortion of the picture (due to the angle, camera setting which defines the pixel/meters conversion) is a monotone function, there is no major effect on the relative width variations.




**Figure 13.** The distribution of measured width. The median class ranging from 4 m to 7 m is underrepresented because boulders clusters on each side of the stream make the transition between narrow flows and wide flows fast and nonlinear.

### 3.8 The width observations

At very low discharges the stream bed is covered by large boulders, clearly seen in the pictures, and rocks are fully submerged at high flows, creating large surface waves. The transition between low and high flows creates secondary channels and we chose to only consider the main channel and not the side channels at low and medium flows. This induces an underestimation 5 of the width at low discharges. The flow widening is also strongly impacted by those boulder clusters, at. At low discharge the main channel is contained in the center of the bed, and water stage has to be quite high to be over both clusters. The transition between wide and narrow channels is fast and therefore intermediate widths (between 4 and 7 meters wide) are underrepresented in the width data (Fig. 13). The image information reveals these aspects of the hydraulics of the channel (and that affect stage changes) that would not be known with stage data alone.

### 10 3.9 The width stage relationship

In braided channel studies the wetted surface measurement has been used as a substitute for stage to estimate the discharge (Smith et al., 1996; Ashmore and Sauks, 2006; Gleason et al., 2015). Previous studies have shown the correlation between the wetted surface and the discharge with an exponent from 0.5 (Smith et al., 1996) to 1 (Ashmore and Sauks, 2006). The width response to discharge change are is much higher in these braided channels than in many other streams and this gives the 15 potential for using width in addition to, or instead of, stage changes as the primary variable for estimating discharge. In the Dome stream case, although it is not a braided stream, the relatively shallow cross-section also gives significant widening of flow with increasing stage and the positive trend is clear with an exponent close to 0.6 (Fig. 14). However, the trend is not linear and data scatter is quite large because of the irregular geometry of the cross-section, and the bouldery channel edges (especially at low discharge). Nevertheless, the width estimation could be a reliable approximation to the stage measurement. Even if not



**Figure 14.** The water surface width as a function of the water height. The stage is taken from the camera data-set. The flow width is taken from the width detection and Eq. 2. The trend line equation is  $W = 19.19H_{camera}^{0.58}$ .

used directly as a discharge surrogate, the width data give additional information on the hydraulic geometry of the channel that would be difficult to predict theoretically for this type of channel. The width data also reveal some interesting hysteresis in the flow hydraulics. On 67% of the 81 daily flow peaks on the Dome ~~river~~ ~~stream~~ for which there are data, the mean value of the stream width over the water stage range ~~0.5~~ ~~from strictly higher than  $\frac{1}{2}H_{max}$  and  $H_{max}$~~ ,  $H_{max}$  ~~H<sub>max</sub>~~ being the daily 5 maximum water stage, is higher on the falling limb of the daily hydrograph than on the rising limb. The width increase ranges from 0.5% to 26 % with a mean value of 13.9% and a median value of 9.1%.


This produces an obvious hysteresis loop in the width-stage plot (Fig. 15), as can often be found in the stage-discharge relationship (Petersen-Øverleir, 2006). ~~This adds further information for interpretation of the flow and reveals an important aspect of the channel hydraulics that may be the result of the complexity of the flow over and around the boulder clusters, so that the~~ ~~The width data derived from image analysis add further information about the channel hydraulics resulting from the complexity of flow associated with the~~ macro-roughness ~~has an important effect on the flow detected from the image analysis.~~ elements in this type of flow.

### 3.10 Practical aspects of implementing the method

~~The method we are presenting here requires some field work and some post-processing on the pictures.~~

15 ~~The field work, including the site choice, the installation of the equipment, and the on-site calibration, can be done in a few hours using two people.~~

~~Our method is strongly dependent of the picture classification to retain those that are most reliable for water stage and water width detection. The picture classification is based on interest zones linked to environmental and lighting conditions (night, rain/snow, shadows, water reflection and snow cover) and 8 different areas were necessary to classify pictures at our site. Each 20 area has to be chosen related to a particular image issue. For example, to detect night time the entire picture can be used,~~



**Figure 15.** The water surface width as a function of water stage, for falling flows (+), rising flows (●) and the discharge peak (⊕). The curve has a loop, for the same water stage the flow is wider on a falling flow than on a rising flow. The end of the falling flows usually happen at night, therefore the data are missing.

while detection of exposed rocks in the stream channel requires specific small areas of the images. These characteristics are site-specific and it takes some trials to identify appropriate criteria and thresholds. But once established the actual classification can be done in a few hours and can be used for the same site for extended time periods and repeated installations.

#### 4 Discussion

- 5 The method described in this paper is similar to two recent studies proposed by Gleason et al. (2015); Young et al. (2015), but it differs in both general approach, field data and image selection, and processing. Young et al. (2015) assumed a V-shape of their studied cross section, so that the edge coordinate is linearly related to the water stage. They estimate the water level from the water edge, without on-site validation data and use a statistical estimation procedure combined with assumed channel geometry to derive water level changes. In the Dome stream case and with width measurement, the water stage and water width 10 are not linearly related, which gives information on the stream cross section despite the lack of topographic survey and shows that assumptions of the type used by Young et al. (2015) would not be reliable in this case. It also points to the difficulty of reliably predicting flows using a standard resistance assumption in this type of channel. In addition Young et al. (2015) use manual methods to identify water edges on all images. Gleason et al. (2015) focus on water area detection in a large braided channel and not on direct water stage measurements or on small, steep channels.
- 15 The environmental conditions (e.g. sun position, fog, rain) are the main common difficulties that reduce the picture quality and make picture filtering therefore picture filtering as an important step in the process. Gleason et al. (2015); Young et al. (2015) identify similar issues but adopt different approaches. Young et al. (2015) use manual image selection in contrast to our automated selection procedures which makes it possible to process a much larger image set and derive much higher frequency data (15 minutes vs. 4 hours). Gleason et al. (2015) adopt semi-automated image procedures which differ in detail from ours

but their procedures result in either retention or rejection of images for measurement whereas we derive alternative detection criteria (cross section resizing, peak detection... see Table 1 ) for a subset of images rather than eliminating them completely from the data set. Consequently we are able to retain much higher frequency monitoring relative to Gleason et al. (2015). Field data on the site characteristics avoids having to make assumptions about the site such as the cross section shape (Young et al., 5 2015) or working without any ground data for validation (Gleason et al., 2015).

Improved image acquisition is the key component for improving remote sensing accuracy and time coverage. The use of inexpensive time-lapse cameras introduces some limitations that can be mitigated. A higher image resolution and a better camera position (reducing sunlight effects, or improving the position relative to the boulder face calibration surface for example) would improve the measurement accuracy for both the water stage and the channel width. These refinements are easy to implement 10 and test.

Another obvious limitation is the restriction to day time images. In the Dome case, night and twilight represent roughly 1/3 of the day in the summer meltwater period for which data are needed. Using a night vision camera may extend the effective monitoring times but we have not tested this. The limitation may be less significant if only certain flow information is needed rather than a 24 hour continuous signal. Even without continuous data, useful information on channel hydraulics can also be 15 obtained from this type of monitoring. These procedures and image processing steps may be changed to fit site characteristics or data needs. In this case the method provided the necessary seasonal stage signal and timing of daily peaks needed for the study objective of comparison between the ungauged tributary and the main channel flow.

## 5 Conclusions

The results demonstrate the effectiveness of a simple measurement apparatus for flow stage and water surface width: low-cost 20 time-lapse camera and a few simple field measurements. Fully automatic image processing to select images and to detect the water level and edges makes it possible to process a large number of images to produce a long, high temporal resolution, data set. It shows that reliable water stage and water width measurement can be measured at ~~a~~ small (minutes) time steps over 3 months in this case. The estimated hydraulic parameters reliably reproduce the hourly, daily and monthly variation in flow of 25 this pro-glacial river compared to pressure-transducer stage data. The low cost of the camera (approximately \$600) and the very easy data collection makes the image processing a powerful tool for this type of river monitoring especially on small headwater streams. Image analysis produced a larger variety of data and information than a simple water stage transducer alone can yield. Indeed pictures provide visible data such as weather conditions (snow cover, freezing conditions, rain), and water surface conditions (surface waves, eddies, jumps) and details of the flow hydraulics and geometry over the full range of discharge. Image analysis ~~can~~ could also be extended to other hydraulic measurements such as the water slope. The method 30 extends the available methods for inexpensive terrestrial remote sensing of river flow at high frequency and extended time periods applicable especially to small channels with complex flow.

*Acknowledgements.* This research was supported by a Natural Sciences and Engineering Research Council of Canada ~~Discover~~Discovery Grant to Ashmore. We thank Sarah Peirce, Lara Middleton and Matilde Welber for field work assistance and Tobi Gardner for help with the water level logger.

## References

- Ashmore, P. and Sauks, E. (2006). Prediction of discharge from water surface width in a braided river with implications for at-a-station hydraulic geometry. *Water Resources Research*, 42(3), 2006.
- Bertoldi, W., Piégay, H., Buffin-Bélanger, T., Graham, D., and Rice, S. (2012). *Applications of close-range imagery in river research*. In: *Applications of Close-Range Imagery in River Research*, in: *Fluvial Remote Sensing for Science and Management*, pages 341–366. pp. 341–366, John Wiley & Sons, Ltd, doi:10.1002/9781119940791.ch15, 2012.
- Creutin, J., Muste, M., Bradley, A., Kim, S., and Kruger, A. (2003). River gauging using PIV techniques: a proof of concept experiment on the Iowa River. *Journal of Hydrology*, 277, 182 – 194, doi:[http://dx.doi.org/10.1016/S0022-1694\(03\)00081-7](http://dx.doi.org/10.1016/S0022-1694(03)00081-7), 2003.
- Gleason, C. J. and Smith, L. C. (2014). Toward global mapping of river discharge using satellite images and at-many-stations hydraulic geometry. *Proceedings of the National Academy of Sciences*, 111(13), 4788–4791, doi:10.1073/pnas.1317606111, 2014.
- Gleason, C. J., Smith, L. C., Finnegan, D. C., LeWinter, A. L., Pitcher, L. H., and Chu, V. W. (2015). *Technical note*: *Technical Note*: Semi-automated effective width extraction from time-lapse RGB imagery of a remote, braided Greenlandic river. *Hydrology and Earth System Sciences*, 19(6), 2963–2969, doi:10.5194/hess-19-2963-2015, 2015.
- Hauet, A., Kruger, A., Krajewski, W. F., Bradley, A., Muste, M., Creutin, J.-D., and Wilson, M. (2008). Experimental system for real-time discharge estimation using an image-based method. *Journal of Hydrologic Engineering*, 13(2), 105–110, 2008.
- Javernick, L., Brasington, J., and Caruso, B. (2014). Modeling the topography of shallow braided rivers using Structure-from-Motion photogrammetry. *Geomorphology*, 213, 166 – 182, doi:<http://dx.doi.org/10.1016/j.geomorph.2014.01.006>, 2014.
- MacVicar, B. J., Hauet, A., Bergeron, N., Tougne, L., and Ali, I. (2012). *River monitoring with ground-based videography*. In: *River Monitoring with Ground-Based Videography*, in: *Fluvial Remote Sensing for Science and Management*, pages 367–383. pp. 367–383, John Wiley & Sons, Ltd, doi:10.1002/9781119940791.ch16, 2012.
- Petersen-Øverleir, A. (2006). Modelling stage-discharge relationships affected by hysteresis using the Jones formula and nonlinear regression. *Hydrological Sciences Journal*, 51(3), 365–388, 2006.
- Ran, Q.-h., Li, W., Liao, Q., Tang, H.-l., and Wang, M.-y. Application of an automated LSPIV system in a mountainous stream for continuous flood flow measurements. *Hydrological Processes*, 30, 3014–3029, doi:10.1002/hyp.10836, <http://dx.doi.org/10.1002/hyp.10836>, hYP-15-0557.R2, 2016.
- Smith, L. C., Isacks, B. L., Bloom, A. L., and Murray, A. B. (1996). *Estimation of discharge from three braided rivers using synthetic aperture radar satellite imagery: Potential application to ungaged basins*. *Estimation of Discharge From Three Braided Rivers Using Synthetic Aperture Radar Satellite Imagery: Potential Application to Ungaged Basins*. *Water Resources Research*, 32(7), 2021–2034, doi:10.1029/96WR00752, 1996.
- Stumpf, A., Augereau, E., Delacourt, C., and Bonnier, J. Photogrammetric discharge monitoring of small tropical mountain rivers: A case study at Rivière des Pluies, Réunion Island. *Water Resources Research*, 52, 4550–4570, doi:10.1002/2015WR018292, <http://dx.doi.org/10.1002/2015WR018292>, 2016.
- Tsubaki, R., Fujita, I., and Tsutsumi, S. (2011). Measurement of the flood discharge of a small-sized river using an existing digital video recording system. *Journal of Hydro-environment Research*, 5(4), 313 – 321, doi:<http://dx.doi.org/10.1016/j.jher.2010.12.004>, 2011.

35

Wheaton, J

- Williams, R., Brasington, J., Darby, S., Kasprak, A., Sear, D., Vericat, D., Hicks, M., Labrosse, F., and Vericat, D. (2013). Morphodynamic signatures of braiding mechanisms as expressed through change in sediment storage in a gravel-bed river. *Journal of Geophysical Research F: Earth Surface*, 118(2):759–779.
- Neal, M.: Chapter twenty-monitoring braided river change using terrestrial laser scanning and optical bathymetric mapping, *Developments in Earth Surface Processes*, 15, 507–532, 2011.
- 5 Young, D. S., Hart, J. K., and Martinez, K. (2015). Image analysis techniques to estimate river discharge using time-lapse cameras in remote locations. *Computers & Geosciences*, 76: 1 – 10. doi:<http://dx.doi.org/10.1016/j.cageo.2014.11.008>, 2015.

# Interactive comment on “Technical note: Stage and water width measurement of a mountain stream using a simple time-lapse camera” by Pauline Leduc et al. (HESS 2017-285)

---

We thank the three referees for their comments. Our responses below are organised to respond to each review in sequence. Where the response is that we agree with suggested minor edits we have indicated that we will make those the changes in the final version of the paper. The focus of this response is on the more substantial comments.

The following main changes have been made to the paper :

- A new part (section 3.10) has been added to explain the practical aspects of implementing the method.
- Clarifications have been added to explain that the boulder is not essential.
- Distribution plots for the threshold setting have been added as Supplementary material.

*Answers are in italic font.*

---

## Answers to : Anonymous Referee 1

### General comment :

This technical note provides the imaging approach to quantify the width and level of running water in a mountainous area using a commercially available time-lapse camera. To categorize the image quality/characteristics, the image taken by the camera was analyzed using the (eight) target zones, and this point differed from the approaches described in Gleason et al. (2015) and Young et al. (2015). Utilization of image to quantify the hydrological parameters is active topics. The manuscript provides the experience of the authors and this is potentially beneficial to strengthen our understanding of hydrological processes. In my view, the manuscript is worthy of publication after some modification and clarification.

### Specific comments :

The caption of Figure 3, the locations of the pressure transducer is better to be specified in the figure.

*Agreed*

Page 5, line 4 and others, Authors used 'sorted' but I suggest to use 'classify' or 'categorize' since 'sorted' has another meaning, the arrangement of data in a prescribed sequence.

*Agreed*

Page 5, line 18 and following paragraph. It is better to refer 'Test 1' and 'Test 2' in the main text as like did for Test 3 and Test 4 to make clearer the link between the discussion in the main text and the contents of Figure 6.

*Agreed*

Figure 7 : Please explain the meaning/definition of red and blue lines.

*The 2 lines represent 2 different water stages. Caption will be clarified.*

Page 13, line 9, I think it is better to insert some conjunction before 'rocks are fully...'

*Agreed*

Page 14, line 14, I can not understand the meaning of '] $0.5 \cdot H_{max}, H_{max}$ ]

*The sentence has been rephrased to clarify this.*

Page 14, lines 18-20. This sentence is not clear. Please rephrase.

*Done*

Page 15, line 13 'make picture filtering an important step in the process' is not clear.  
Please rephrase.

*Done*

Page 16, line 6, the importance of camera angle was considerably discussed in Tsubaki et al. (2011) and please consider to cite here.

*We have looked at the paper and decided that it is not directly relevant to our work..*

Reference suggestions (not must but suggested to refer) (1) Stumpf, A., E. Augereau, C. Delacourt, and J. Bonnier (2016), Photogrammetric discharge monitoring of small tropical mountain rivers : A case study at Rivière des Pluies, Réunion Island, Water Resour. Res., 52, 4550–4570 (2) Ran, Q., Li, W., Liao, Q., Tang, H., and Wang, M. (2016) Application of an automated LSPIV system in a mountainous stream for continuous flood flow measurements.

*Thank you for the citation suggestions. These have been added.*

Technical corrections :

*These have been done.*

Page 1. line 19, "Ground-based remote sensing 'increasingly' is providing", 'increasingly' seems improper here.

Page 2, line 24, 'oblique time-lapse oblique image' There are two oblique and please rephrase the sentence.

Page 4, line 12, 1536 by 2048 would be 2048 by 1536. '.jpg' would be '.jpg'.

Page 5, lines 8-9. Remove space between 'estimation' and ' :'. The parentheses '(' before Figs 4(a) to 4(c) were not closed by corresponding ')' so please edit the sentence.

Figure 5, Change color of box and text to increase the contrast between the background picture and additional information.

Page 10, lines 3, 5, 11 and 12 : Insert small space between number and unit. The unit should be the regular font, not the italic typeface. Remove space before '%':

Figure 10. The dashed blue line and the solid black line are difficult to distinguish. Please arrange the figure to be easier to distinguish two lines. In the caption, 'August' may be 'July'.

Figure 11, Lines in figures are difficult to identify. Please change color or/and style to highlight the information.

## Answers to : D. Young (Referee)

This paper builds on previous work to further demonstrate the value of an inexpensive, portable and easily-sited time-lapse camera for making frequent (potentially continuous) measurements of stage and water width. The system is applied to a mountain stream with an irregular bed, where other technologies might be difficult to deploy. Particular contributions of this paper include : (a) the validation of an image-based system against a pressure-based system for measuring stage ; (b) automation of detection of the water edge in the images ; (c) observations of the detailed relationship between stage as measured on the rock surface and as measured by pressure ; (d) a demonstration of the successful deployment of this novel type of system in a new site. The work is closely related to that reported in Young et al. (2015). (I am the first author of that paper.) Our paper lacked an independent measure for comparison, and this paper addresses this problem and provides interesting (and reassuring) results. The image-based approach has thus been validated using a separate measurement, which we were unable to do. The authors take the data further, observing some phenomena such as differences depending on whether the flow is increasing or decreasing, which merit further investigation in the future. I have two relatively minor criticisms. The first is that the significance of automation of water edge detection is a little overstated ; the second is that stage and width measurements are treated as separate problems, rather than integrated into a single model. The approach depends on detection of the water/rock boundary in the images. It is important to automate this if large amounts of data are to be processed (and one can imagine a study in which many cameras are deployed over an extended period, all collecting many images per hour). However, Leduc et al.'s method depends on having a large rock surface such that the water surface lies across it for all stages of interest, and where the water/rock boundary exhibits the highest contrast (or second-highest in certain lighting conditions). Given such a situation, our method could also have been fully automated - we used manual intervention to select the correct edge in a much more cluttered image, using a selection of smaller rocks. Leduc et al.'s images show strong contrast between the water and the rock (the water is very bright in the images that appear in the paper) and it is not clear that their method will work well in situations where the water is flowing more smoothly, or the river channel is more complex. Their image analysis algorithm has some ad hoc elements which may not generalise well. It would be worth noting that selection of the maximum grey-level gradient along a vertical profile is almost the same as Canny edge detection in a narrow strip - the only real difference is that Canny uses some Gaussian smoothing to reduce noise. Thus both this paper and ours use(not surprisingly)rather similar image analysis techniques. I think it would be useful to include some more discussion of the trade off between automatic analysis and the need for careful site selection, and also of the limitations of using a single surface for the stage measurement. Our approach of combining measurements on multiple surfaces (both near-vertical and near-horizontal) allows for a larger range of stages to be covered and for estimates to be made of the consistency and statistical reliability of the measurements, as well as providing a rough estimate of the channel geometry. Leduc et al.'s approach relies on a more carefully chosen camera position and

a suitable large rock, which allows automated image processing and a simpler analysis of the image measurements. In my view, the merits of the two approaches are complementary, and future work should draw on both. The water width measurement is interesting, but again I am concerned about how well this would generalise to other settings. A little more needs to be said about how the nonlinear fit in Eq 2 was arrived at - is this a purely empirical equation or is there a model behind it? The final paragraph of section 3.7 does, however, provide a good summary of the issues. Section 3.9 is novel and interesting, going significantly beyond our work, and reveals how the technique can give results that would not be available in any other way. I feel that section 4 of the paper raises interesting questions, and I agree strongly with the conclusions reached in section 5. Overall, I think this is a very strong contribution and I am happy to recommend publication.

*Thank you for your comments. As you can tell, your paper was a help to us although we discovered it only after we had done our field work. The general comment on needing a vertical rock surface is a slight misunderstanding that we can clarify in the revisions. Our original intent was to use the stage boards which could be installed at almost any site. The stage boards worked but in the analysis we discovered that the boulder face, a serendipitous feature of the site which we calibrated while we were there, actually gave us slightly better results. The boulder face is not a requirement for the method we applied – any vertical calibrated surface could be used. Further testing by others in different environments would help the community to assess how widely applicable this approach is. Thank you also for giving more detail on how the two methods relate to each other and pointing out the matter of whether a single vertical or a length of channel is preferable. We can revise the discussion section to draw this out more. We agree also that more work on width (and other hydraulic parameters) is needed and the edge detection method from your paper may be better suited to this for some channels.*

*Equation 2 is an empirical fit.*

Technical comments :

*Thank you for these. We have made all of these changes in the final paper.*

p 1, l 17 : Extra parentheses in reference (cf l 21)

p 2, l 6 : We didn't know the channel geometry - we assumed a V-shaped section and estimated the slopes from the data.

p 2, l 12 : boulder -> bouldery

p 2, l 24 : too many 'oblique's

p 4, Fig 3, and subsequent figures : can the figures be made bigger? When the paper is printed, the details are hard to see. This is particularly the case for Figs 9, 10 and 11, and the central element of Fig 1.

p 6, l 11-14 : This section could be a little and more explicit. I didn't understand how the re-sizing operation worked, or what its basis is.

Table 1 : the values for SDs assume, I think, a brightness range of 0-255. This ought

to be stated explicitly (it's common, but not universal)

p 10, l 2 : Should "board stage" be "stage board" for the calibration ? If not, I don't understand what is meant.

p 14, l 5 : are much higher -> is much higher

p 14, l 14 : First bracket backward

## Answers to : Anonymous Referee 3


This paper seeks to define a methodology for retrieving pertinent river variables from time lapse imagery. At its core, this methodology relies on site selection to be effective : the authors were quite clever to notice different image regions and exploit these for filtering. This is a great idea that could be adopted to other studies. The authors also rely heavily on a ‘nearly vertical’ boulder for stage and width measurements. This is also rather clever, but acts as a double edged sword : What if no boulder can be found with a flat face orthogonal to the camera plane ?

*As in our response to the second reviewer : the rock face was fortunate but the method works for stage boards (or other surfaces) installed at a site (which was the original intent), so the method is not reliant on the boulder surface. Any calibrated near-vertical surface will work. The flat boulder is indeed convenient, but in the paper, we also show satisfactory the result using one of the stage boards. The results could be refined and made more precise for particular installation.*


The authors need to elaborate, at paragraph length or longer, the considerations of site selection for this method. Is it serendipity that the image regions and boulders emerged, or were they chosen ? In addition, the authors MUST quantify their method much more accurately- descriptions of quantities are too vague and not replicable. If I want to apply this method and need to find classification regions, what distributions of intensity should I seek ? How should I define my different image regions, or will this method only work at this one site with this unique assemblage of morphologies ?

*We illustrate the method for the particular site for which we sought a stage record. We did not choose the site for its particular characteristics, we were trying to get a stage record for the site given the characteristics that it had. We are not sure what is vague in our descriptions. One need not seek particular site characteristics for this method, but the image selection criteria would need to be customized for the site. This is partly a ‘trial and error’ method but once established for a site, which is not a lengthy process, it is automated. The threshold issue is the key point of our picture classification. However, we don’t want to focus too much on the 4 threshold settings for this particular site as they would need calibration for a different site. Our focus was to show the method. We can add an appendix with the threshold curves if this would be useful (see below, figure 1).*


Therein lies my main concern-the clever filtering techniques that are an improvement on Gleason et al may not work everywhere. The authors need to more clearly define their threshold values, and I think distributions of intensity in each of the eight regions should be shown at multiple flow levels to prove their utility beyond taking the authors’ word for it. Precise values are given in Table 1, but not in the text, and no distributions are shown. The reported wave issues are also troubling for the site selection issues discussed above. How much of an issue would these be in a different site ?



(a) Boulder shadow - Test 2



(b) Exposed rocks - Test 3



(c) Light snow cover - Test 4

FIGURE 1 – The different distribution used to set the thresholds

*We are not sure what is being requested here. The filtering will need to be customized for a particular site (as it was in Gleason et al.) but the process is general. As the comment says, we have given values in Table 1, so we are not sure why repetition in the text is necessary. Note that the image regions are well outside the channel so are not affected by flow level except in the case of removing mid-channel rocks from the width estimation which would not be an issue in channels with large relative depth. We are not sure what the concern is with waves. We have explained this feature of the flow and one would need to be aware of it, but the stage signal can be filtered to account for these if necessary (as it is in any stage recording in an open channel) and we show coherence between the open water level and the logger level in a pipe.*

The photogrammetry here is effective, and I do not quibble with the empirical functions for stage and width. However, these do require calibration that makes this procedure time consuming. Could the authors comment on the amount of time needed to make measurements for sufficient calibration ? i.e. could I set up 50 of these stations, all well-calibrated, in a summer in remote terrain ? This is an important discussion left out of the manuscript that should be added, as the authors propose that this method should be adopted for such streams. The use of precise rotation matrix measurements and classic photogrammetry would obviate the need for this calibration, as would establishing several cameras in stereo. Overall, I recommend this paper for publication, provided the authors write several new sections detailing the concerns discussed above-all of which relate to the role of site selection in this method.

*We are not suggesting what should be adopted, only showing another possibility for flow monitoring. Time needed for installation would obviously depend on local circumstances. The physical installation and calibration can be done at a site in 1-2 hours without a pressure transducer using two people (possibly less with experience). We did not think of whether this was useful for a large monitoring network but it is clearly a feasible option for selected research sites. Post-processing to apply image selection criteria can be done in a few hours and with experience some criteria (e.g. dark, sun, water droplets etc.) may be generalizable. We agree that stereo applications are another option, as are PTV applications, but we sought a simple low-cost option equivalent to standard stage recording. We would be pleased to see somebody develop the photogrammetric approaches proposed. We can add these points to the discussion.*

Some minor comments :

*Thank you. We have made the minor corrections*

The English writing is sloppy at times- needless plurals, .jpg instead of .jpg, backward brackets, etc. This needs to be amended and made more professional.

*The backward brackets are deliberate to indicate the semi open interval, we didn't include 0.5.Hmax in our interval. We will, of course, proofread the final text for minor*

errors.

Page 4, line 13 : What is this standard deviation ? It is insufficient to say 'very low.' Also, this is a filter, correct ? It should be identified as such.

*The standard deviation is here referring to the standard deviation of the picture (or of a cropped area of the picture) of the grey scale which indicates the noise of the picture. A standard deviation of 0 indicates a one color picture while a high standard deviation (eg > 50 on our site) indicates a very large range of color of the picture. The 'very low' threshold is easy to set, the darkness makes the color pretty much even on the picture surface in contrast to daylight when the different color shades make the standard deviation high. The definition of 'low' and 'high' is site dependent. Indeed, the standard deviation of a "normal" weather condition depends on the river background, the picture setting (if there is a lot of sky on the picture or not), rocks color... The 'very low' threshold has to be set relative to the site and the picture components.*

Page4->page5 : This writing is redundant- section 3.1 should be eliminated and combined into section 3.2.

*In those two sections we want first to explain all the issues we have to face and secondly we want to present the different tests we made to get around those issues. This clarification was requested by the associate editor prior to distribution to referees.*

Page 5, line 15+ : again, what is the threshold of SD ? Also, this writing is unclear words like 'high' and 'drops' and 'smoother' are used, which are imprecise. Since this paper proposes an algorithm for installation and monitoring, it must be specific so as to be reproduced.

*We are not sure why these are problematic. We are only descriptively establishing a sense of the direction of change or difference. See our response above to the issues of image selection criteria and site selection and image standard deviation.*