

# Shallow water table effects on water, sediment and pesticide transport in vegetative filter strips: Part B. model coupling, application, factor importance and uncertainty

Claire Lauvernet<sup>1</sup> and Rafael Muñoz-Carpena<sup>2</sup>

<sup>1</sup>Irstea, UR MALY, centre de Lyon-Villeurbanne, 5 rue de la Doua-CS 70077, F-69626 Villeurbanne cedex, France.

<sup>2</sup>University of Florida, Agricultural and Biological Engineering, 287 Frazier Rogers Hall, PO Box 110570 Gainesville, FL 32611-0570, USA

*Correspondence to:* Claire Lauvernet (claire.lauvernet@irstea.fr)

**Abstract.** Vegetative filter strips are often used for protecting surface waters from pollution transferred by surface runoff in agricultural watersheds. In Europe, they are often prescribed along the stream banks, where a seasonal shallow water table (WT) could decrease the buffer zone efficiency. In spite of this potentially important effect, there are no systematic experimental or theoretical studies on the effect of this soil boundary condition on the VFS efficiency. In the companion paper, we developed a physically-based numerical algorithm (SWINGO) that allows representing soil infiltration with a shallow water table. Here we present the dynamic coupling of SWINGO with VFSSMOD, an overland flow and transport mathematical model to study the WT influence on VFS efficiency in terms of reductions of overland flow, sediment and pesticide transport. This new version of VFSSMOD was applied to two contrasted benchmark field studies in France (sandy-loam soil under Mediterranean semi-continental climate, and silty-clay under temperate Oceanic climate), where limited testing of the model with field data on one of the sites showed promising results. The application showed that for the conditions of the studies, VFS efficiency decreases markedly when the water table is 0 to 1.5 m from the surface. In order to evaluate the relative importance of WT among other input factors controlling VFS efficiency, global sensitivity and uncertainty analysis (GSA) was applied on the benchmark studies. The most important factors found for VFS overland flow reduction were saturated hydraulic conductivity and WT depth, added to sediment characteristics and VFS dimensions for sediment and pesticide reductions. The relative importance of WT varied as a function of soil type (most important at the silty-clay soil) and hydraulic loading (rainfall + incoming runoff) at each site. The presence of WT introduced more complex responses dominated by strong interactions in the modelled system response, reducing the typical predominance of saturated hydraulic conductivity on infiltration under deep water table conditions. This study demonstrates that when present, WT should be considered as a key hydrologic factor in buffer design and evaluation as a water quality mitigation practice.

## 28    **1 Introduction**

29    Today, surface waters are threatened by pesticide pollution at the local, regional and global scales (Malaj et al., 2014; Stehle  
30    and Schulz, 2015). Agricultural surface runoff is an important contributor to this contamination (Louchart et al., 2001). Grass  
31    buffer zones or vegetative filter strips (VFS), are a typical environmental control practice to protect aquatic ecosystems from  
32    sediment, and agrichemicals from agricultural fields (Roberts et al., 2012). While VFS are recommended in the USA and  
33    other regions, in Europe they are often mandatory along rivers due to their potential to limit surface pesticide runoff and  
34    aerial spray drift from entering adjacent surface water bodies (Asmussen et al., 1977; Rohde et al 1980; USDA-NRCS, 2000;  
35    Dosskey, 2001; Syversen and Bechmann, 2004; Poletika et al., 2009). However, the effectiveness of edge-of-field buffer  
36    strips to reduce runoff transport of pesticides can be very different as a function of many local characteristics (land use, soil,  
37    climate, vegetation and pollutant). For example, based on 16 field studies (Reichenberger et al., 2007), the 25th percentile of  
38    VFS pesticide reduction efficiency ranges from 45 to 75 % of the amount coming into the filter from the field edge.

39    Moreover, VFS are typically located down the hillslope along the hydrographic network. As a result, the filter is often  
40    bounded by a seasonal shallow or perched water table, which may significantly inhibit their function and must be taken into  
41    account when designing VFS and evaluating their efficiency (Lacas et al., 2005). Dosskey et al. (2001, 2006) identified  
42    presence of shallow water table (<1.8 m) as an important factor that should be considered for VFS design and evaluation.  
43    Simpkins et al. (2002) also report that the hydrogeologic setting, specifically the direction of groundwater flow and the  
44    position of the water table in thin sand aquifers underlying the buffers, is probably the most important factor in determining  
45    buffer efficiency. Arora et al. (2010), in a review on VFS pesticide retention from agricultural runoff present that soil  
46    saturation from a shallow water table may be a reason for negative runoff volume retention. Other studies also identify the  
47    potential effects of location of the buffers where shallow water table is present (Ohliger and Schulz, 2010; Borin et al., 2004)  
48    but do not quantify or study its effects (Lacas et al., 2005).

49    The processes occurring in the VFS interact in a complex manner in space and time, thus they must be simulated by dynamic  
50    models accounting for hydrologic (Gatel et al., 2016) and sedimentological variability (Fox et al., 2005). The Vegetative  
51    Filter Strip Modeling System (VFSSMOD) (Muñoz-Carpena et al., 1993, 1999; Muñoz-Carpena and Parsons, 2004) is a  
52    storm-based numerical model coupling overland flow, water infiltration and sediment trapping in a filter considering  
53    incoming surface flow and sediment from an upslope field (Fig. 1). VFSSMOD also includes a generalized empirical pesticide  
54    trapping equation as a function of soil and sediment sorption, dissolved phase infiltration, and sorbed phase sedimentation  
55    (Sabbagh et al., 2009). Pesticide degradation on the filter is included between runoff events for long-term pesticide  
56    assessments (Muñoz-Carpena et al., 2015), but neglected during events due to their short duration (min to h). VFSSMOD has  
57    been successfully tested against measured data for predictions of flow, infiltration, and sediment trapping efficiency (Muñoz-  
58    Carpena et al., 1999, Abu-Zreig, 2001, Dosskey et al., 2002, Fox et al., 2005, Han et al., 2005, Pan et al., 2017), tracers and

59 multi-reactive reactive solutes (Perez-Ovilla, 2010), phosphorus (Kuo and Muñoz-Carpena, 2009), pesticides (Poletika et al.,  
60 2009; Sabbagh et al, 2009; Winchell et el., 2011), and colloids (Yu et al., 2013). Previous work studied the global sensitivity  
61 of simulated outflow, sediment and pesticide trapping to VFSMOD input factors (Muñoz-Carpena et al., 2007, 2010, 2015;  
62 Fox et al. 2010). At the watershed scale, VFSMOD has been included in methods or frameworks to optimize filter placement  
63 and design (Dosskey et al., 2006; Tomer et al., 2009; White and Arnold, 2009; Balderacchi et. al, 2016; Carluer et al., 2017).  
64 Sabbagh et al. (2010) integrated VFSMOD within higher-tier, US-EPA long-term pesticide exposure framework  
65 (PRZM/VFSMOD/EXAMS) to estimate changes in aquatic concentrations when VFS are adopted as a runoff pollution  
66 control practice. Recently, the German EPA (UBA) developed the GERDA software package as a pesticide regulatory tool  
67 for surface water that includes VFSMOD simulations with a shallow water table where present (Brinke et al., 2017).

68 The extended Green-Ampt soil infiltration component (Skaggs and Khaheel, 1982) used in VFSMOD does not account for  
69 the presence of a shallow water table. In a companion paper, a physically-based algorithm was developed to describe soil  
70 infiltration under shallow water table conditions (SWINGO: Shallow Water table Infiltration alGOrithm). Dynamic coupling  
71 of this new infiltration algorithm to VFSMOD will allow for mechanistic description of interactions between surface and  
72 subsurface hydrology under shallow water table boundary conditions and ensuing effects on VFS sediment and pesticide  
73 transport.

74 Thus, the objective of this work is to study the effects that the change in infiltration introduced by the presence of shallow  
75 water table has on VFS runoff reduction, sediment and pesticide trapping. This was done by a) dynamic coupling of  
76 SWINGO in VFSMOD; b) applying the coupled model on two contrasted and realistic benchmark study sites (sandy-loam  
77 soil vs silty-clay soil) and events (Mediterranean semi-continental vs temperate oceanic climates); and c) global sensitivity  
78 and uncertainty analysis to ascertain the actual global importance of shallow water table depth on the efficiency of the VFS  
79 when compared to other input factors.

## 80 **2 Material and methods**

### 81 **2.1 Dynamic coupling of shallow water table infiltration algorithm (SWINGO) with VFSMOD overland flow,** 82 **sediment and pesticide components**

83 The overland flow submodel in VFSMOD (Muñoz-Carpena et al., 1993a) (Fig. 1) is based on the kinematic wave equation  
84 numerical, upwinding Petrov-Galerkin finite element (FE) solution (Lighthill and Whitham, 1955),

$$85 \begin{cases} \frac{\partial h}{\partial t} + \frac{\partial q}{\partial x} = i - f = i_e \\ S_f \approx S_o \rightarrow q = \frac{\sqrt{S_o}}{n} h^{\frac{5}{3}} \end{cases} \quad (1)$$

86 with initial and boundary conditions

$$\begin{cases} h = 0; 0 \leq x \leq VL, t = 0 \\ h = h_o; x = 0, t \geq 0 \end{cases} \quad (2)$$

88 where  $h=h(x,t)$  [L] is the flow depth,  $t$  is time (L),  $q=q(x,t)$  [ $L^2T^{-1}$ ] is discharge per unit width,  $x$  [L] is the surface flow  
89 direction axis,  $i=i(t)$  [ $LT^{-1}$ ] is rainfall intensity,  $f=f(t)$  [ $LT^{-1}$ ] is soil infiltration rate,  $i_e=i_e(t)$  [ $LT^{-1}$ ] is rainfall excess,  $S_o$  and  $S_f$   
90 [ $LL^{-1}$ ] are the bed and water surface friction slopes at each node of the system,  $n$  is Manning's surface roughness coefficient,  
91  $VL$  [L] is the filter length, and  $h_o=h_o(0,t)$  [L] represents the field runoff hydrograph entering the filter as a boundary condition  
92 (Fig. 2).

93 Originally, the overland flow component was coupled for each time step with a modified Green-Ampt infiltration algorithm  
94 for unsteady rainfall (GAMPT, see Fig. 1) for soils without (or with deep) water table (Chu, 1978; Mein and Larson, 1971,  
95 1973; Skaggs and Khaheel, 1982; Muñoz-Carpena et al., 1993b). The infiltration component provides the rainfall excess,  $i_e$   
96 in Eq. (1), based on a given unsteady rainfall distribution (hyetograph) for each FE node and time step. The field conditions  
97 can be well represented since the program handles field inflow hydrographs and hyetographs, and spatial variability of the  
98 filter over the nodes of the grid (Fig. 2).

99 In the sediment component (Fig. 1), based on sediment mechanics (transport and deposition) in shallow flow, the model  
100 divides the incoming sediment into bed load (coarse particles, with diameter  $>37 \mu m$ ) and suspended load (fine particles,  
101 diameter  $<37 \mu m$ ). Bed load deposition is dynamically calculated based on Einstein bed-load transport equation successfully  
102 tested for variable shallow flow through non-submerged dense vegetation (Barfield et al., 1978). Transport and deposition of  
103 suspended particles is calculated for non-submerged dense vegetation conditions (Tollner et al., 1976; Wilson et al., 1981).  
104 Flow characteristics needed for sediment calculations are provided for each time step by the overland flow component. The  
105 particle deposition pattern on the filter is predicted based on a conceptual sediment wedge, mass-balance approach (Fig. 2a).

106 Pesticide reduction and transport in the filter during the runoff event is calculated within the water quality/pollutant module  
107 (Fig. 1) based on a generalized regression-based approach developed from on a large database of field studies by Sabbagh et  
108 al. (2009) and further tested by others (Poletika et al., 2009; Winchell et al., 2011). The equation considers reduction of  
109 dissolved pesticide through infiltration, deposition of sediment-bound pesticide, and pesticide adsorption characteristics. The  
110 integration of the mechanistic (flow and sedimentation from VFSMOD) and empirical pesticide approaches allows for  
111 identification of important site-specific factors determining the efficiency of pesticide removal (or lack of thereof) under  
112 realistic field conditions (Muñoz-Carpena et al., 2010; Fox et al., 2010).

113 In this work, to simulate VFS water, sediment and pesticide dynamics under realistic unsteady rainfall-runoff conditions for

114 shallow water table conditions, we dynamically couple the new algorithm SWINGO (developed in the companion paper) as  
 115 an alternative, user-selected infiltration submodel (Fig. 1). Full details of SWINGO are provided in the companion paper.  
 116 Briefly, SWINGO is a time-explicit infiltration solution based on a combination of approaches by Salvucci and Entekhabi  
 117 (1995) and Chu (1997) with the assumption of a horizontal wetting front. Proposed integral formulae allow estimation of the  
 118 singular times: time of ponding ( $t_p$ ), shift time ( $t_o$ ), and time ( $t_w$ ) when the wetting front depth is equal to  $z_w$  (capillary fringe  
 119 above the water table, Fig. 2b). As with GAMPT, the algorithm provides the infiltration rate  $f$  (Eq. 1) for each FE node and  
 120 time step in VFSMOD as,

$$121 \quad \begin{cases} f = i & 0 < t < t_p \\ f = f_p = K_s + \frac{1}{z_F} \int_0^{L-z_F} K(h) dh & t_p < t < t_w \\ f = \min(f_w, i) & t \geq t_w \end{cases} \quad (3)$$

122 where (Fig. 2b),  $z$  [L] is the vertical axis,  $z_F$  [L] is wetting front depth from the surface,  $L$  [L] the depth to the water table,  
 123  $K=K(h)$  [ $\text{MT}^{-1}$ ] the soil water hydraulic conductivity function of soil matric suction  $h$  [L] (non uniform with depth),  $K_s$  [ $\text{MT}^{-1}$ ]  
 124  $^1$ ] is the saturation soil water content, and  $f_w$  [ $\text{MT}^{-1}$ ] is the end vertical boundary condition when the wetting front reaches the  
 125 water table (or its capillary fringe) typically assumed as vertical saturated flow or lateral drainage (see companion paper for  
 126 details). For real VFS field situations, unsteady rainfall without initial ponding must be considered and  $t_p$  and  $t_o$  calculated.  
 127 For each time step increment,  $\Delta t = t_j - t_{j-1}$ , the surface water balance at each VFS FE node (neglecting evaporation during the  
 128 event) (Chu, 1997) is,

$$129 \quad \Delta P = \Delta F + \Delta s + \Delta RO \quad (4)$$

130 where  $\Delta P$ ,  $\Delta F$ ,  $\Delta s$ , and  $\Delta RO$  [L] are changes for each  $\Delta t$  of cumulative precipitation ( $P$ ), cumulative infiltration ( $F$ ), surface  
 131 storage and cumulative runoff ( $RO$ ). Notice that  $i_e = \Delta RO / \Delta t$  for each time step. Unsteady rainfall is described by a  
 132 hyetograph of constant  $i_j$  for each rainfall period. If surface storage becomes  $s=0$  then  $t_p$  and  $t_o$  are re-calculated at the next  
 133 rainfall period as,

$$134 \quad t_p = \frac{1}{i} (\theta_s z_p - \int_0^{z_p} \theta(L-z) dz) \quad (5)$$

$$135 \quad t_o = \int_0^{z_p} \frac{1}{f_p} [\theta_s - \theta(L-z)] dz \quad (6)$$

136 where  $\theta_s$ ,  $\theta(h)$  [ $\text{L}^3 \text{L}^{-3}$ ] are the soil water saturated content and the soil water characteristic curve, and  $z_p$  [L] is the equivalent  
 137 wetting front depth at  $t_p$ , and for periods after the first,  $z_F(t)$  (Fig. 2b) is calculated explicitly from the Newton-Raphson  
 138 iterative solution ( $k$  iteration level),

$$\begin{aligned}
139 \quad G(z_F) &= t - t_p + t_0 - \int_0^{z_F} \frac{\theta_s - \theta(L-z)}{K_s - \frac{1}{z_F} \int_L^{z_F} K(L-z) dz} dz \Bigg| \quad z_F^{k+1} = z_F^k - \frac{G(z_F^k)}{G'(z_F^k)} \quad \text{with} \quad |z_F^{k+1} - z_F^k| < \varepsilon \\
G'(z_F) &= - \frac{\theta_s - \theta(L-z)}{K_s - \frac{1}{z_F} \int_L^{z_F} K(L-z) dz}
\end{aligned} \tag{7}$$

140 Finally, the algorithm computes  $t_w$ , the time to reach column saturation as,

$$141 \quad t_w = t_p - t_0 + \int_0^{z_w} \frac{1}{f_p} [\theta_s - \theta(L-z)] dz \tag{8}$$

142 Similarly, this singular time  $t_w$  has to be obtained again each time  $t_p$  and  $t_o$  are computed. When initial ponding is present we  
143 get  $t_p = t_0 = 0$ . Additional details are provided in the companion paper, and Supp. Materials **S1** provides instructions for  
144 downloading the free VFSMOD open source code, documentation and sample applications.

## 145 **2.2 Benchmark field studies**

146 VFSMOD extended for shallow water table was applied to two experimental VFS sites in France (Fig. 3, Table 1), selected  
147 because they represent contrasting agronomic, pedological and climatic conditions (Fontaine 2010). The first site in a  
148 Beaujolais vineyard (Rhône-Alpes) consists of a vegetative filter strip on a steep hillslope (20-30%) located along the river  
149 Morcille (affluent of the Saône river). The site was instrumented from 2001 to 2008 for long-term experiments of  
150 infiltration-percolation of crop protection products (Boivin et al., 2007; Lacas, 2005; Lacas et al., 2012). The region has a  
151 semi-continental climate, with Mediterranean influence, where intense seasonal runoff events can induce erosion. The soil is  
152 a very permeable granitic sandy-clay. The water table is deep in summer and shallow in winter after intense storm events,  
153 from 0.60 m deep at the downstream part of the strip near the river to 4.0 m deep at the field upstream side of the strip  
154 (Lacas, 2005).

155 The site of Jaillièrre (Loire-Atlantique, close to Brittany) is an experimental farm maintained by ARVALIS–Institut du  
156 Végétal where soils are shallow and hydromorphic, and climate is temperate oceanic with mild and rainy winters and cool  
157 and wet summers (Madrigal-Monarrez, 2004). Buffer zone experiments were conducted at the site under natural rainfall  
158 (Patty et al., 1997) and simulated runoff (Souiller et al., 2002). Crops are mainly wheat and maize, typically under tile  
159 drainage conditions, with slopes of around 3%. Silty clay soils overlay a virtually impermeable layer of alterite shales,  
160 typically leading in winter to the formation of seasonal shallow water table from 0.5 m to 2 m and the appearance of runoff  
161 by subsaturation (Adamiade, 2004). This site is also the basis for the EU pesticide regulatory scenario for surface water  
162 FOCUS<sub>sw</sub> D5 (EU-FOCUS, 2001).

163 Among the pesticides used at the experimental sites, a soluble and low sorption (mobile) herbicide (isoproturon) used on  
164 both sites was selected for simulations, contrasted by a less mobile product chosen at each site, i.e. the fungicide

tebuconazole at Morcille and the herbicide diflufenican at Jaillière (Madriral et al 2002) (Table 1).

While both Morcille and Jaillière provide sufficient details for application of the coupled model (field parameters, initial and boundary conditions), VFS outflow was only available for Morcille. In particular, Lacas (2005) and Lacas et al. (2012) monitored the effectiveness of the VFS at Morcille, but because of the high permeability of the soil and deeper shallow water conditions, only 5 out of the 24 natural rainfall events recorded generated outflow from the VFS. From these 5, the one closer to the average for the high water table season was selected for application of the model (Fig. 4a). Earlier studies at Jaillière by Patty et al. (1997) monitored VFS efficiency in the same site but in the absence of a shallow water table. Although they provide some of the model inputs they are not directly applicable for this WT model application. Later, working on the same watershed Branger et al. (2009) and Fontaine (2010) studied the shallow water table effects on runoff at the edge-of-the-field and a receiving drainage ditch, but did not monitor the efficiency of the VFS. We selected one average event (dynamics and volume) in the middle of the high-water season based on Fontaine (2010) for our model application (Fig. 4b).

To our knowledge there are no VFS experimental studies with a shallow water table present that can be used for systematic model testing. While this paper focuses on coupling of the new infiltration algorithm with VFSSMOD and the analysis of the important factors controlling VFS efficiency in the presence of WT, we used the single event with sufficient hydrological data at Morcille to get a preliminary assessment if the model responds in the same range as the measured field data. Uncalibrated or “cold” testing of the model (without initial calibration using field values) was performed and the 95% confidence interval (grey area in Fig. 4a) was obtained by varying only  $K_s$  within measured field values (Table 2). The model performance was assessed against the measured data based on FitEval software (Ritter and Muñoz-Carpena, 2013). FitEval uses block-bootstrapping of the observed and predicted paired values to approximate the underlying distributions of goodness-of-fit statistics (Nash and Sutcliffe Efficiency- NSE and Root Mean Square Error -RMSE). From these distributions, median values and 95% confidence intervals (95CI) are provided for both NSE and RMSE. NSE provides a dimensionless metric of goodness-of-fit, and RMSE an indicator of absolute error, with the same dimensions as model outputs. The uncertainty in the observed data is accounted for in FitEval using the modification of the NSE based on the probable error range (PER) method (Harmel et al, 2007). FitEval evaluation files are included in Supp. Materials.

## 2.3 Global sensitivity analysis

Global sensitivity (GSA) and uncertainty analysis (UA) of the coupled model allows for the systematic study of the influence of the input factors and their interactions on VFS performance for surface runoff, sediment and pesticide removal. The “global” term denotes that GSA studies output variability when all input factors vary globally, within their validity domain defined by probability distribution functions (PDF), as opposed to locally, (one at a time), *i.e.* around an arbitrary range from

195 a base value. GSA allows for simultaneous estimation of the factors individual importance and interactions (Saltelli et al.,  
196 2004). In this study, two complementary sensitivity methods were used: the qualitative Morris' (1991) elementary effects  
197 screening method, and the quantitative variance-decomposition extended Fourier Amplitude Sensitivity Test (eFAST)  
198 (Cukier et al., 1978; Saltelli et al., 1999). In both methods, input factors are sampled, the model is evaluated on the sample  
199 sets, and global sensitivity indices are computed. Morris is generally used as a first, qualitative step to identify a group of  
200 important input factors, where in a second step a variance-based method is applied on the selected input factors (Saltelli et  
201 al., 2007, 2008).

202 Morris method uses in its original form a regular discretization of the  $k$  input factors space defined by their PDFs, requiring a  
203 total number of simulations ( $N$ ) on the order of  $N=r(k+1)$  where  $r > 8$  is the number of sampling trajectories, typically taken  
204 as 10 used here (Campolongo et al., 2007). Each factor influence, called Elementary Effects (EE), is evaluated by  
205 comparison of simulations where this factor is changed alternatively among the others. Morris is a robust, low-cost  
206 sensitivity analysis that allows identifying quickly the most influent input factors without prior model assumptions (i.e.  
207 linearity, additivity) (Campolongo et al., 2007; Faivre et al., 2013; Khare et al., 2015). Sensitivity indices for each factor  $X_i$   
208 ( $i=1, k$ ) are computed based on the EE: (i)  $\mu_i^*$  (mean of absolute values of EE) that measures *direct effects* of each factor on  
209 the output of interest, and (ii)  $\sigma_i$  (standard deviation of EE) that provides a measure of *interactions and non-linearities*. The  
210 method compares the input factors' indices relatively to the others, making possible to visually classify the inputs on a ( $\mu^*$ ,  
211  $\sigma$ ) Cartesian plane in 4 groups as a function of their relative effect on the model: (1) negligible effect (low  $\mu^*$  and low  $\sigma$ ); (2)  
212 important direct effects and small interactions (high  $\mu^*$  and low  $\sigma$ ); (3) important non-linear and/or interactions (high  $\mu^*$  and  
213 high  $\sigma$ ); and (4) interacting factors with low sensitivity (low  $\mu^*$  and high  $\sigma$ ).

214 The eFAST method is a quantitative global sensitivity method based on high-dimensional variance decomposition. A  
215 pseudo-random multivariate sampling scheme is conducted across the  $k$ -dimensional space, informed by the input factors  
216 PDFs, requiring  $N=M*k$  simulations with  $M$  between 512 and 1024 (8 or 9 binary factor combinations) (Saltelli et. al, 2004).  
217 The model total output  $Y$  variance is decomposed in parts attributed to each factor direct effects or to factor interactions.  
218 First order sensitivity indices ( $S_i$ ) for each factor  $X_i$  are defined by the fraction of the output variance associated to the direct  
219 effect of that factor and represents the average output variance reduction that can be achieved when the input factor  $X_i$  is  
220 fixed (Tarantola et al., 2002; Yang, 2011). Total sensitivity indices ( $S_{Ti}$ ) are calculated as the fraction of variance associated  
221 with that factor and its interactions. The largest values of the sensitivity indices correspond to the highest influence of these  
222 inputs on the corresponding output variable (Saltelli et al., 2008; Faivre et al., 2013). eFAST was chosen on this study  
223 because it is robust and overcomes the initial limitation of the Fourier Amplitude Sensitivity Test (Cukier et al., 1978)  
224 applicable only for mostly additive models (i.e.  $\sum S_i > 0.6$ ) (Faivre et al., 2013). The dense variance-based multivariate  
225 sampling and ensuing model simulations allow for quantification of the model uncertainty analysis through output



226 probability density functions and statistics (median, quantiles, confidence intervals) (Saltelli et al. 2004, Muñoz-Carpena et al.  
227 2007).

228 Morris indices ( $\mu^*$ ,  $\sigma$ ) have been found to provide a good approximation to the eFAST indices ( $S_{Ti}$ ,  $S_{Ti}-S_i$ ) at a much lower  
229 computational cost (Saltelli et al. 2004, Campolongo et al. 2007) making it ideal for large and computationally expensive  
230 models. However, for models with strong non-linear outputs or discontinuities in the output space, the low density of Morris  
231 sampling can result in inaccurate sensitivity analysis results. In this study, both methods were run with the full set of inputs  
232 as a check for the consistency and robustness of the GSA results. For conciseness, Morris results are presented in detail and  
233 eFAST results are summarized briefly with additional details in Supplementary Materials.

## 234 **2.4 Selection of inputs and outputs for GSA simulations**

235 The first step of GSA is to define output variables and input factors. In this study, changes in VFS efficiency were selected  
236 as output variables: reduction of water (dQ), sediments (dE) and pesticides (dP). Both model versions, with water table  
237 (SWINGO algorithm) and without water table (GAMPT algorithm), were compared on each site. The input factors (Table 2)  
238 were selected considering previous GSA performed on VFSMOD (Fox et al., 2010; Muñoz-Carpena et al., 2007, 2010), with  
239 new inputs for the water table case (OR, VGALPHA and VGN, L). Input factors distributions (Table 2) are assigned based  
240 either on experimental measurements on the case study plots, scientific publications, or expert knowledge.

241 Although the VFS dimensions FWIDTH and VL were measured on the field (Table 1), the effective dimensions are known  
242 to be different in practice as the runoff does not follow perfectly uniform sheet flow (Abu-Zreig, 2001). Thus, the measured  
243 values were chosen to vary uniformly within -10% and +10% for FWIDTH and VL, respectively (Muñoz-Carpena et al.,  
244 2010). The slope (SOA) uniform distribution represents field measured spatial variation across the VFS. PDFs for filter  
245 roughness and vegetation factors were assigned based on vegetation type (Table 1) (Haan et al. 1994; Muñoz-Carpena et al.  
246 2007).

247 For the infiltration components, log-normal PDFs were assigned to the soil saturated hydraulic conductivity (VKS) from  
248 measured values at each site (Madrigal-Monarez, 2004; Souiller et al., 2002; Lacas, 2005) based on effective field values  
249 calculated from the harmonic mean of the topsoil horizons (Bouwer, 1969). The Green-Ampt infiltration OI and OS inputs  
250 were fitted distributions based on values measured at the sites, and the average suction at the wetting front (SAV) was  
251 considered to vary uniformly based on ranges for soil texture at each site (Rawls et al., 1983). Soil water characteristics  
252 parameters (VGALPHA, VGN, OR in Table 2) needed for calculation of infiltration under shallow water table (Eq. 3-8)  
253 were assigned normal PDF based on the soil texture (Meyer et al., 1997). Hourly water table depths (L) that were  
254 automatically monitored on Morcille during the case study event (Lacas, 2005) followed a uniform distribution. On Jaillièrè,

the average water depth and variation was measured manually at the site (Adamiade, 2004) and a uniform distribution around these values assigned.

Sediment particle characteristics from the upper field (COARSE and DP) were assigned uniform distributions based on USDA textural class (Woolhiser et al., 1990), and truncated to respect the relationship between DP and COARSE (Muñoz-Carpena et al., 1999).

For pesticide inputs, field measurements of the percentage of clay (PTC) and organic carbon (PCTOC) of the upper field followed a uniform PDF (Lacas, 2005; Benoit et al., 1998; Madrigal-Monarez, 2004). The triangular distribution for KOC for the pesticides evaluated at each site is based on measurements; in Jaillière for the base value and boundaries (Benoit et al., 1998; Souiller et al., 2002), and in Morcille for the base value (Lacas, 2005) but using boundaries from PPDB database (IUPAC, 2007).

In all, for the two sites, two infiltration options (GAMPT without shallow water table with  $k=18$ , and SWINGO with shallow water table with  $k=20$ , Table 2) and 2 pesticides at each site, the total number of GSA simulations performed were 75544 for eFAST ( $M=497\sim 500$ ) and 1600 for Morris. The procedure was repeated 3 times to ensure the robustness of the results.

### 3. Results

#### 3.1 Model application on benchmark studies

The effect of water table on simulated VFS efficiency using SWINGO was first tested on the two contrasted benchmark study sites Morcille (Fig. 4a) and Jaillière (Fig. 4b). Since a stream at the bottom of the VFS was present on both sites, the lateral Dupuit-Forscheimer option was selected for the end vertical bottom boundary condition  $f_w$  (Eq. 3) (see section 2.1 in companion paper), hereon referred to as vertical boundary condition. The detailed outflow hydrograph from the VFS measured during the event at Morcille is compared with a direct simulation with base values (no calibration) (Fig. 4a). The dashed line for  $L=2.5$  m corresponds to average measured VKS for the top soil horizons ( $4.58 \times 10^{-5}$  m/s), and the grey envelope represents outflow variability due to uncertainty of measured hydraulic conductivity (between  $3.89 \times 10^{-5}$  m/s from direct measurement on the soil surface horizon 10-30 cm and  $5.29 \times 10^{-5}$  m/s computed by harmonic mean of measurements on 0-10 cm and 10-30 cm horizons). In addition to the measured water table depth at the sites, each event was tested with different water table conditions to study the response to these conditions (Fig. 4a,b). The large differences in VFS surface outflow found between shallow and deeper water table clearly illustrates the hydrological importance of shallow water table presence on VFS at these sites.

Direct simulation of the VFS surface outflow at Morcille fits observations well for the end of the second rain period (4000 to

6000s) but misses the rest (Fig. 4a). The differences between simulated and observed values could come from measurement or parametrization errors at the site, since runoff was expected early on for an event with such hydraulic loading (rainfall + incoming runoff). The intrinsic spatial variability of  $K_s$  represents also a significant source of uncertainty in the simulations (grey area in Fig. 4a). Nash-Sutcliffe efficiency (NSE) and root mean square error (RMSE) ranges for the model uncertainty bounds in Fig. 4a were median NSE = 0.610 and 95CI [0.448 - 0.943], and RMSE=  $4.284 \times 10^{-5}$  [ $1.179 \times 10^{-5}$  -  $7.472 \times 10^{-5}$ ]  $\text{m}^3/\text{s}$ . Within those uncertainty bounds, the model is classified as ‘unacceptable’ to ‘very good’ based on the FitEval methodology (Ritter and Muñoz-Carpena, 2013). In all, considering that the model was run with base values and without calibration, these preliminary results are deemed satisfactory.

The effect of water table change (from 0-2 m) on VFS changes in runoff (dQ), sediment (dE) and pesticide (dP) reductions for the two case studies is presented in Fig. 5. In general, dQ and dP are sensitive to the shallow water table depth until a threshold (~1.5 m for the case study sites) beyond which there are no effects and the filter achieves maximum efficiency for the event. The two-step curves for Morcille are due to the two storm periods, where relative contributions to surface flow between the first and second events will vary with the depth of the shallow water table. Sediment retention (dE) does not exhibit similar changes because the relatively low flow conditions experienced likely result in low transport capacity available and high sediment deposition on the VFS. The difference in effects introduced by the chemical characteristics of the pesticide is observed in the curves for diflufenican (high sorption) and isoproturon (low sorption) at Jaillière. This local study does not take into account all effects and interactions between input factors, but only the water table depth variation effect. A global sensitivity analysis presented in section 3.2 will address this.

The simulation results for Morcille and Jaillière confirm that a shallow water table can affect the VFS surface hydrological response by generating saturation surface runoff, depending on the soil characteristics and the hydraulic loading. Conversely, for deep water table, surface hydrology processes are effectively decoupled after a threshold controlled by the soil characteristics and hydraulic loading. Interestingly, simulations with the no shallow-water table option (GAMPT, Fig. 1) for the case study conditions closely matched those for SWINGO for the deeper water tables in Fig. 4, providing additional physical consistency to both components.

### 3.2 Global sensitivity analysis of water, sediment and pesticide reductions

A combination of shallow water table (“WT”, run with SWINGO) and no shallow water table (“no WT”, run with GAMPT) simulations (Fig. 1) for Jaillière and Morcille conditions with two pesticides at each site (Table 1) were selected for GSA Morris and eFAST methods. For simplicity, GSA results are presented only for one pesticide, isoproturon, which is a common herbicide with average sorption properties. A comparison of the different pesticides effects is presented in the uncertainty analysis section later.

313 Morris sensitivity analysis indices (Table S1 in Supp. Materials) are presented in Fig. 6, where important input factors for  
314 each output are separated from the origin of the ( $\mu^*$ ,  $\sigma$ ) Cartesian planes. Distinct patterns on the important factors  
315 controlling the shallow water table effects on the efficiency of the VFS (dQ, dE, dP) are identified by comparing the  
316 different soil (fine at Jaillière and coarse at Morcille) and hydraulic loading across the study sites. The differences can be  
317 interpreted in terms of the interplay between excess rainfall (controlled mainly by the saturated hydraulic conductivity VKS  
318 and hydraulic loading) and sub-saturation (controlled by the water table depth  $L$ ).

319 Finer soils typically exhibit lower permeability but a higher capillarity fringe above a water table (Terzaghi, 1943; Lane and  
320 Washburn, 1946; Parlange et al., 1990). For no WT, excess rainfall (controlled by VKS) leads to relatively more water on  
321 the surface compared to coarse soils. Morris results (Fig. 6a) show the strong sensitivity of dQ to VKS for this case. With  
322 WT the soil readily saturates from the bottom and it is less sensitive to VKS. This is shown by the strong direct effect of  $L$   
323 on dQ (Fig. 6d). For dE in finer soils, more runoff present at the surface typically results in higher transport capacity  
324 available, and sediment and surface characteristics become a limiting factor for transport and deposition (Muñoz-Carpena et  
325 al., 2010). This is shown by the importance of DP and interaction with VKS (Fig. 6b). With WT, the infiltration is limited  
326 even further in these fine soils, where excess rainfall no longer controls surface flow and VKS falls in importance while  
327 sediment and surface characteristics dominate the response (Fig. 6e). In general, pesticide reduction (dP) is controlled by  
328 factors controlling the liquid (dQ) and solid (dE) phase transport (Sabbagh, et al., 2009). For no WT and for this moderately  
329 adsorbed chemical, the effect of excess rainfall on dQ (controlled by VKS) also becomes the most important process for dP  
330 (Fig. 6c). With WT, the dominance of  $L$  in dQ is also present in dP, with some sediment and pesticide characteristics also  
331 showing importance (Fig. 6f).

332 In contrast, the coarser soil in Morcille exhibits higher permeability and small capillary fringe and under no WT runoff is  
333 typically controlled by excess rainfall (importance of VKS on Fig. 6g). With WT, the soil might sub-saturate depending on  
334 position  $L$  and this input gains importance interacting with VKS (Fig. 6j). For dE and no WT (Fig. 6h), with more  
335 permeability the surface water flow (controlled by VKS) is the main limiting factor controlling sedimentation (Muñoz-  
336 Carpena et al., 2010). With WT, again the VKS and  $L$  that control surface flow also interact strongly to control  
337 sedimentation, and sediment soil water characteristics are of secondary importance (Fig. 6k). Control of infiltration  
338 propagates also into dP, and for this moderately sorbed pesticide, dQ factors also control dP (Fig. 6i,l).

339 Interestingly, introduction of WT increases the number of factors and interactions (i.e. more input factors show higher  $\sigma$   
340 values and are separated near or above the dashed 1:1 line). This indicates an increase in complexity of the VFS response  
341 when the shallow water table is present. This suggests that simple relationships to simulate water, sediment and pesticide  
342 behavior are not able to represent all complex processes that interact in a VFS.

Comparison of Morris and eFAST indices (Fig. 6, and Supp. Mat. Table S2 and Fig. S1) for interactions and first order effects,  $S_{Ti}-S_i \sim \sigma$  and  $S_{Ti} \sim \mu^*$ , respectively, shows good consistency among the methods (Saltelli et al, 2004; Campolongo et al, 2007) and further corroborates the results. The importance of VKS for both soils under no WT identified by Morris is quantified by eFAST with more than 90% of the dQ and dP output variance being controlled by first order (direct) effects of this factor (Fig. S1a,g and c,i). Similarly, the importance of DP for dE for the fine soil is apparent where more than 60% of the variance is explained by first order and interaction effects of this factor (Fig. S1b,e). For the case of WT, the effect of L on dQ and dP is predominant, with 60-90% of the output controlled by this factor and its interactions (Fig. S1d,j,l).

## Uncertainty Analysis

The model runs from eFAST dense multivariate input sampling allows realizing a quantitative uncertainty analysis of the model outputs water (dQ), sediment (dE), pesticide (dP) reductions for the 2 contrasted pesticides at each site (Fig. 7 and Table S3 in Supp. Materials). As expected, the reduction in infiltration and increase in surface flow introduced by the shallow water table translates into a distinct decrease in dQ values, with median dQ changing from 81% to 7% and 65% to 45% in Jaillière (Fig. 7a, b) and Morcille (Fig. 7c,d), respectively (Table S3, Supp. Materials). For dE, for the coarser soil at Morcille the smaller change in dQ with WT does not visibly change the high sediment retention, whereas for the finer soil of Jaillière the changes in flow introduce marked changes in median dE from 99% to 64%. Again, changes in dQ and dE with WT affect the VFS pesticide retention at both sites, with median reductions from dP = 99% to 38% and 97% to 84% in Jaillière and Morcille, respectively. Since the VFS pesticide retention is also directly related to pesticide sorption characteristics (Sabbagh et al., 2009), some differences are expected for different chemicals. Reduction of diflufenican at Jaillière (dP-Dif) (Fig. 7b) and tebuconazole at Morcille (dP-Teb) (Fig. 7d) is higher than reductions of the other two pesticides because of their affinity for sediment (higher KOC values in Table 1) and high sediment retention in the VFS.

These results further support the GSA findings that changes in surface and subsurface hydrological responses introduced by the shallow water table, can translate into important reductions on the expected pesticide retention and uncertainty controlled by field conditions (soils, hydraulic loading, pesticide characteristics).

## 4. Summary and conclusions

In this study, we coupled a new infiltration algorithm under shallow water table conditions (SWINGO, developed in companion paper) with a commonly used event based vegetative filter strips model (VFSMOD). The coupled model takes into account the dynamic interactions among water table, surface runoff, sediment and pesticide filtration in a vegetative filter strip. The model was applied to two different experimental sites with contrasted soils and rainfall conditions. The direct testing of the uncalibrated model under limited experimental conditions showed promising results. Simulations varying the

water table depth for two experimental sites provided interesting insights on the effect on VFS efficiencies to reduce overland flow, sediment and pesticides. While the VFS surface flow, sediment and pesticide reduction responses are very sensitive when the water table is close to the surface, the effect is lost after a threshold depth around 1.5 m for the experimental sites condition, consistent with previous field studies (Dosskey et al., 2006, Lacas et al., 2012). For depths larger than the threshold, the model showed physical consistency when compared to a common Green-Ampt solution (with no water table assumptions). More comprehensive global sensitivity and uncertainty analyses (GSA) for the two sites revealed that the effectiveness of the VFS was markedly reduced in the presence of the shallow water table, and in this case the VFS response is more complex, dominated by interactions between surface, subsurface and transport processes. The most important factors controlling the expected variability of water and pesticide reductions are water table depth and saturated hydraulic conductivity of the soil, but their importance also depends on sediment characteristics controlled by the soil type and hydraulic loading of the event. Uncertainty in the pesticide reduction, driven by water or sediment reduction, also depends on the pesticide sorption properties (Koc).

This work suffers from some limitations. Firstly, limited field experimental data is available for detailed studies of the response of a VFS under alternative conditions of deep and shallow water table. Further laboratory and field research should address this limitation, where exhaustive experimental datasets must be compiled to reduce the uncertainty in the identification of sensitive input factors controlling the measured and simulated responses studied here. Secondly, although two contrasting case studies were selected, the results presented here are limited to these studies, and further analysis will be needed for other local, regional and larger scales.

The application of the improved VFSMOD under contrasting set of conditions, and physical consistency with other models indicate the robustness of the model for use in VFS sizing and evaluation of potential losses of efficiency under shallow water table conditions. Since VFS are commonly placed near streams and these areas can suffer seasonal shallow water conditions, this tool fills an important gap in environmental management and analysis. For example, in Europe VFS are often prescribed along river drainage networks without objective assessment of their efficiency during winter wet periods (Carluer et al., 2017; Brinker et al., 2017). In the US, the historical topography-based approach, which links priority for buffers to locations where runoff water converges from uplands and saturates the soil, often results in placement on bottomlands next to streams (Dosskey and Qiu 2011). Alternative targeted placement of buffers based on soil characteristics and conductivity can improve the efficiency of the buffers (Dosskey et al., 2006). However, both placement methods disregard seasonal shallow water table effects that can now be mechanistically assessed with the improved physical model developed herein. For the case of the regulatory assessment of pesticides, currently long-term exposure frameworks in Europe and the USA disregard the potential effects that shallow water effects might have in reducing the effectiveness of in-label mitigation practices like VFS. Results from this study support the critical need to incorporate in these environmental

403 exposure assessments the effects of a shallow water table when present.

404 **Author contribution**

405 CL and RMC participated in the model coupling, coding the GSA application, analysis and interpretation of the results and  
406 writing of the manuscript.

407 **Acknowledgements**

408 The authors wish to thank Nadia Carluer for the field testing dataset and selection of the study sites, and review of the paper.  
409 Marilisa Letey helped with the literature review for this manuscript. Axel Ritter helped in the FitEval evaluation of the  
410 experimental data. CL acknowledges TOPPS-PROWADIS for partial project funding. The second author received support  
411 from the UF Research Foundation Professorship, UF Water Institute Fellowship, and USDA NIFA Award No: 2016-67019-  
412 26855. The authors also thank the University of Florida Research Computing (<http://researchcomputing.ufl.edu>) for  
413 providing high performance computational resources and support that have contributed to the research results reported in this  
414 publication.

415 **References**

- 416 Abu-Zreig, M.: Factors Affecting Sediment Trapping in Vegetated Filter Strips: Simulation Study Using VFSSMOD, Hydrol.  
417 Proc., 15, 1477, doi:10.1002/hyp.220, 2001.
- 418 Adamiade, V: Influence d'un fossé sur les écoulements rapides au sein d'un versant. Université Pierre et Marie Curie,  
419 Spécialité Géosciences - Ressources Naturelles, Paris VI., 2004.
- 420 Arora, K., Mickelson, S.K., Helmers, M.J., Baker, J.L.: Review of Pesticide Retention Processes Occurring in Buffer Strips  
421 Receiving Agricultural Runoff1. JAWRA Journal of the American Water Resources Association 46, 618–647,  
422 doi:10.1111/j.1752-1688.2010.00438.x, 2010.
- 423 Asmussen, L.E., White, A.W., Hauser, E.W., Sheridan, J.M.: Reduction of 2,4-D Load in Surface Runoff Down a Grassed  
424 Waterway. J. Environ. Qual., 6, 159. doi:10.2134/jeq1977.00472425000600020011x, 1977.
- 425 Balderacchi, M., Perego, A., Lazzari, G., Muñoz-Carpena, R., Acutis, M., Laini, A., Giussani, A. , Sanna, M., Kane, D.  
426 Trevisan, M.. Avoiding social traps in the ecosystem stewardship: The Italian Fontanile lowland spring. Sci. Total Env. 539,  
427 526-535, doi:10.1016/j.scitotenv.2015.09.029, 2016.
- 428 Barfield, B. J., E. W. Tollner, and J. C. Hayes: The use of grass filters for sediment control in strip mining drainage. Vol. I:  
429 Theoretical studies on artificial media. Pub. No. 35–RRR2–78. Lexington, Ky.: University of Kentucky, Institute for Mining  
430 and Minerals Research, 1978.
- 431 Benoit, P., Barriuso, E., Vidon, P., Réal, B.: Isoproturon Sorption and Degradation in a Soil from Grassed Buffer Strip. J.  
432 Environ. Qual., doi:10.2134/jeq1999.00472425002800010014x, 28,121, 1998.
- 433 Boivin, A., Lacas, J.G., Carluier, N., Margoum, C., Gril, J.-J., Gouy, V.: Pesticide leaching potential through the  
434 soil of a buffer strip in the river Morcille catchment (Beaujolais). XIII Symposium Pesticide Chemistry -  
435 Environmental Fate and Human Health, Piacenza, Italie, 2007.
- 436 Bouwer, H.: Infiltration of water into nonuniform soil. Journal of Irrigation and Drainage Division 95:451–462, 1969.
- 437 Branger, F., Tournebize, J., Carluier, N., Kao, C., Braud, I., Vauclin, M., 2009. A simplified modelling approach for pesticide  
438 transport in a tile-drained field: The PESTDRAIN model. Agricultural Water Management 96, 415–428.  
439 doi:10.1016/j.agwat.2008.09.005



440 Brinke M., B. Bänsch-Baltruschat, M. Keller, E. Szöcs, Ralf B. Schäfer, K. Foit, M. Liess. Umsetzung des Nationalen  
 441 Aktionsplans zur nachhaltigen Anwendung von Pestiziden. Bestandsaufnahme zur Erhebung von Daten zur Belastung von  
 442 Kleingewässern der Agrarlandschaft. Oktober 2017. ISSN 1862-4359 Dessau-Roßlau, URL  
 443 <https://www.umweltbundesamt.de/publikationen/bewertung-des-eintrags-von-pflanzenschutzmitteln-in>

444 Carluer, N., Lauvernet, C., Noll, D., Muñoz-Carpena, R.: Defining context-specific scenarios to design vegetated buffer  
 445 zones that limit pesticide transfer via surface runoff, *Sci. Total Environ.*, 575, 701-712, doi:10.1016/j.scitotenv.2016.09.105,  
 446 2017.

447 Chu, S.T.: Infiltration during unsteady rain. *Water Resour. Res.*, 14, 3, 461-466, doi:197810.1029/WR014i003p00461, 1978.

448 Cukier, R.I., Levine, H.B., Shuler, K.E.: Nonlinear sensitivity analysis of multiparameter model systems. *J. Comput.*  
 449 *Physics*, 26, 1, 1978.

450 Dosskey, M.G.: Toward quantifying water pollution abatement in response to installing buffers on crop land. *Environ*  
 451 *Manage* 28, 577–598, doi: 10.1007/s002670010245, 2001.

452 Dosskey, M.G., Helmers, M.J., Eisenhauer, D.E.: An Approach for Using Soil Surveys to Guide the Placement of Water  
 453 Quality Buffers. *Journal of Soil and Water Conservation* 61, 344–354, 2006.

454 Dosskey, M.G., M.J. Helmers, D.E. Eisenhauer, T.G. Franti and K.D. Hoagland: Assessment of concentrated flow through  
 455 riparian buffers. *Journal of Soil and Water Conservation*, 57:336–343, 2002.

456 Dukes, M.D., Evans, R.O., Gilliam, J.W., Kunickis, S.H.: Effect of Riparian Buffer Width and Vegetation Type on Shallow  
 457 Groundwater Quality in the Middle Coastal Plain of North Carolina, *Trans. of ASABE* 45:327, 2002.

458 EU-FOCUS. 2001. FOCUS Surface Water Scenarios in the EU Evaluation Process under 91/414/EEC. Report of the  
 459 FOCUS Working Group on Surface Water Scenarios, EC Document Reference SANCO/4802/2001 –rev .2. 245pp, Version  
 460 1.0, January 2011.

461 EU-JRC. 2004. SIMLAB Version 2.2.1. Simulation Environment for Uncertainty and Sensitivity Analysis. Joint Research  
 462 Centre of the European Commission, Ispra, Italy. <https://ec.europa.eu/jrc/en/samo/simlab> (accessed July 2017)

463 Faivre, R., Iooss, B., Mahévas, S., Makowski, D., Monod, H.: Sensitivity Analysis and Exploration of Models. Editions  
 464 Quae, in French, 2013.

Fontaine, A.: Optimizing the size of grassed buffer strips to limit pesticides transfer from land to surface water in overland flow », Cranfield University, UK, MSc Thesis, 2010.

Fox, A.L., D.E. Eisenhauer, M.G. Dosskey: Modeling water and sediment trapping by vegetated filters using VFSSMOD: comparing methods for estimating infiltration parameters. ASAE Paper, 052118. Joseph, 2005.

Fox, G., Muñoz-Carpena, R., Sabbagh, G.: Influence of flow concentration on parameter importance and prediction uncertainty of pesticide trapping by vegetative filter strips. *J. Hydrol.*, 384, 164-173, doi:10.1016/j.jhydrol.2010.01.020, 2010.

Gatel, L., Lauvernet, C., Carluier, N., and Paniconi, C.: Effect of surface and subsurface heterogeneity on the hydrological response of a grassed buffer zone, *Journal of Hydrology*, 542, 637-647, 10.1016/j.jhydrol.2016.09.038, 2016.

Haan CT, Barfield BJ, Hayes JC.: Design hydrology and sedimentology for small catchments. San Diego, Calif.: Academic Press, 1994.

Han, J., Wu, S., Allan, C.: Suspended sediment removal by vegetative filter strip treating highway runoff. *Journal of Environmental Science and Health*, 40:1637–1649, doi:10.1081/ESE-200060683, 2005.

Harmel, R. D., and P. K. Smith. 2007. Consideration of measurement uncertainty in the evaluation of goodness- of- fit in hydrologic and water quality modeling. *J. Hydrol.* 337(3- 4): 326- 336.

Johnson, S.R., Burchell, M.R. R.O. Evans, D.L. Osmond, Gilliam, J.W.: Riparian Buffer Located in an Upland Landscape Position Does Not Enhance Nitrate-Nitrogen Removal, *Ecol. Engineering*, 52, 252, doi:10.1016/j.ecoleng.2012.11.006, 2013.

Khare, Y.P., R. Muñoz-Carpena., R.W. Rooney. and C.J. Martinez: A multi-criteria trajectory-based parameter sampling strategy for the screening method of elementary effects. *Environ. Modell. Softw.* 64,230-239, doi:10.1016/j.envsoft.2014.11.013, 2015.

Kuo, Y.M. and R. Muñoz-Carpena: Simplified modeling of phosphorus removal by vegetative filter strips to control runoff pollution from phosphate mining areas, *J. of Hydrol.*, 378, 343-354, doi:10.1016/j.jhydrol.2009.09.039, 2009.

Lacas, J.-G., 2005. Processus de dissipation des produits phytosanitaires dans les zones tampons enherbées. Etude expérimentale et modélisation en vue de limiter la contamination des eaux de surface. Université Montpellier II. Sciences et techniques du Languedoc.

491 Lacas, J.-G., Voltz, M., Gouy, V., Carluer, N., Gril, J.-J.: Using grassed strips to limit pesticide transfer to surface water: a  
492 review. *Agron. Sustain. Dev.* 25, 253–266, doi:10.1051/agro:2005001, 2005.

493 Lacas, J.-G., Carluer, N., Voltz, M.: Efficiency of a Grass Buffer Strip for Limiting Diuron Losses from an Uphill Vineyard  
494 Towards Surface and Subsurface Waters. *Pedosphere*, 22, 580-592, doi:10.1016/S1002-0160(12)60043-5, 2012.

495 Lane, K. S., and Washburn, S. E.: Capillary tests by capillarimeter and by soil filled tubes. *Proc. Highway Research Board*,  
496 26, 460–473, 1946.

497 Lighthill, M.J., Whitham, C.B.: On kinematic waves: flood movement in long rivers. *Proc. R. Soc. London Ser. A* , 22, 281 -  
498 316, 1955.

499 Louchart, X., M. Voltz, P. Andrieux, et R. Moussa: Herbicide Transport to Surface Waters at Field and Watershed Scales in  
500 a Mediterranean Vineyard Area, *Journal of Environmental Quality*, 30:982, 2001.

501 Madrigal-Monarez, I.: Sorption of pesticides in soil from grassed and forested buffer zones: the role of organic matter.  
502 INAPG PhD Thesis (AgroParisTech), 2004.

503 Malaj E., P.C. von der Ohe, M. Grote, R. Kühne, C.P. Mondy, P. Usseglio-Polatera, W. Brack, and R.B. Schäfer. Organic  
504 chemicals jeopardize the health of freshwater ecosystems on the continental scale. *PNAS* 111, 26, 9549-9554.  
505 doi:10.1073/pnas.1321082111, 2014.

506 Mein, R.G., Larson, C.L.: Modelling the infiltration component of the rainfall-runoff process, *Bulletin 43*, University of  
507 Minnesota, MN, Water Resources Research Center, 1971.

508 Meyer, P.D.; Rockhold, M.L. & Gee, G.W. Uncertainty analyses of infiltration and subsurface flow and transport for SDMP  
509 sites, report, September 1, 1997; Washington D.C.. (digital.library.unt.edu/ark:/67531/metadc690558/: accessed July 7,  
510 2017), University of North Texas Libraries, Digital Library, digital.library.unt.edu; crediting UNT Libraries Government  
511 Documents Department.

512 Muñoz-Carpena, R., C.T. Miller, and J.E. Parsons: A Quadratic Petrov-Galerkin Solution for Kinematic Wave Overland  
513 Flow. *Water Resour. Res.* 29, 8, 2615-2627, 1993a.

514 Muñoz-Carpena, R., Parsons, J.E., Gilliam, J.W.: Numerical Approach to the Overland Flow Process in Vegetative Filter  
515 Strips, *Trans. of ASABE* 36, 3, 761-770, 1993b.

516 Muñoz-Carpena, R., Parsons, J.E., Gilliam, J.W.: Modeling hydrology and sediment transport in vegetative filter strips. J.  
 517 Hydrol., 214, 111–129. doi:10.1016/S0022-1694(98)00272-8, 1999.

518 Muñoz-Carpena, R. and Parsons, J. E.: A design procedure for vegetative filter strips using VFSSMOD-W, Transactions of  
 519 the ASAE 47(6), 1933—1941, doi :10.13031/2013.17806, 2004.

520 Muñoz-Carpena, R., Z. Zajac, et Y.-M. Kuo: Global sensitivity and uncertainty analyses of the water quality model  
 521 VFSSMOD., Trans. of ASABE 50:1719–1732, 2007.

522 Muñoz-Carpena, R., Fox, G., Sabbagh, G.: Parameter Importance and Uncertainty in Predicting Runoff Pesticide Reduction  
 523 with Filter Strips. Journal of Environmental Quality, 39,630, doi:10.2134/jeq2009.0300, 2010.

524 Muñoz-Carpena, R. A. Ritter, G.A. Fox and O. Perez-Ovilla: Does mechanistic modeling of filter strip pesticide mass  
 525 balance and degradation affect environmental exposure assessments? Chemosphere 139:410-421.  
 526 [doi:10.1016/j.chemosphere.2015.07.010](https://doi.org/10.1016/j.chemosphere.2015.07.010), 2015.

527 Ohliger, R., Schulz, R.: Water body and riparian buffer strip characteristics in a vineyard area to support aquatic pesticide  
 528 exposure assessment, Sci. Total Environ., 408, 5405-5413, doi:scitotenv.2010.08.025, 2010.

529 Pan, D.; Gao, X.; Dyck, M.; Song, Y.; Wu, P., Zhao, X.: Dynamics of runoff and sediment trapping performance of  
 530 vegetative filter strips: Run-on experiments and modeling Science of The Total Environment, 593–594, 54-64, 2017.

531 Parlange, J.-Y., Haverkamp, R., Starr, J. L., Fuentes, C., Malik, R. S., Kumar, S., and Malik, R. K.: Maximal capillary rise  
 532 flux as a function of height from the water table. Soil Sci., 150, 6, 896–898, 1990.

533 Patty, L., Réal, B., Gril, J.J.: The use of grassed buffer strips to remove pesticides, nitrate and soluble phosphorus  
 534 compounds from runoff water. Pesticide science, 243:251, 1997.

535 Perez-Ovilla, O.: Modeling runoff pollutant dynamics through vegetative filter strips: a flexible numerical approach. Ph.D.  
 536 Thesis, University of Florida, Gainesville, 195pp, 2010.

537 Poletika, N.N., Coody, P.N., Fox, G.A., Sabbagh, G.J., Dolder, S.C., White, J.: Chlorpyrifos and Atrazine Removal from  
 538 Runoff by Vegetated Filter Strips: Experiments and Predictive Modeling. J. Environ. Qual., 38, 1042–1052.  
 539 doi:10.2134/jeq2008.0404, 2009.

540 Rawls WJ, Brakensiek DL, Miller N.: Green-Ampt infiltration parameters from soils data. J. Hydraul. Eng., 109(1), 62-70,  
 541 1983.

542 Reichenberger S, Bach M, Skitschak A, Frede H-G.: Mitigation strategies to reduce pesticide inputs into ground- and surface  
543 water and their effectiveness: a review. *Sci. Total Environ.*, 384, 1-35, doi:10.1016/j.scitotenv.2007.04.046, 2007.

544 Ritter, A. and R. Muñoz-Carpena. 2013. Predictive ability of hydrological models: objective assessment of goodness-of-fit  
545 with statistical significance. *J. of Hydrology* 480(1):33-45. doi:10.1016/j.jhydrol.2012.12.004

546 Roberts, W.M., M.I. Stutter, and P.M. Haygarth: Phosphorus Retention and Remobilization in Vegetated Buffer Strips: A  
547 Review. *J. Environ. Qual.* 41:389–399 (2012) doi:10.2134/jeq2010.0543, 2012.

548 Rohde, W.A., L.E. Asmussen, E.W. Hauser, R.D. Wauchop: Trifluralin movement in runoff from a small agricultural  
549 watershed. *J. Environ. Qual.*, 9, pp. 37–42, 1980.

550 Sabbagh, G.J., Fox, G.A., Kamanzi, A., Roepke, B., Tang, J.-Z.: Effectiveness of Vegetative Filter Strips in Reducing  
551 Pesticide Loading: Quantifying Pesticide Trapping Efficiency. *J. Environ. Qual.* 38, 762. doi:10.2134/jeq2008.0266, 2009.

552 Saltelli A., S. Tarantola, F. Campolongo, M. Ratto: *Sensitivity Analysis in Practice: A Guide to Assessing Scientific Models.*  
553 John Wiley & Sons, Chichester, 2004.

554 Saltelli, A., Annoni, P., Azzini, I., Campolongo, F., Ratto M., Tarantola, S.: Variance Based Sensitivity Analysis of Model  
555 Output. Design and Estimator for the Total Sensitivity Index. *Computer Physics Communications* 181:259, 2010.

556 Saltelli, A., Ratto, M., Andres, T., Campolongo, F., Cariboni, J., Gatelli, D., Saisana, M., Tarantola, S.: *Global Sensitivity*  
557 *Analysis: The Primer.* John Wiley & Sons, Chichester, 2008.

558 Saltelli, A., Tarantola, S., Chan, K.P.-S.: A Quantitative Model-Independent Method for Global Sensitivity Analysis of  
559 Model Output, *Technometrics* 41:39, 1999.

560 Simpkins, W., Wineland, T., Andress, R., Johnston, D., Caron, G., Isenhardt, T., Schultz, R. : Hydrogeological constraints on  
561 riparian buffers for reduction of diffuse pollution: examples from the Bear Creek watershed in Iowa, USA, *Water Science*  
562 *and Tech.* 45, 9, 2002.

563 Skaggs, R.W., Khaheel, R., 1982. Infiltration, Ch. 4, In: *Hydrologic modeling of small watersheds.* C.T. Haan, H.P. Johnson,  
564 D.L. Brakensiek, Eds., St. Joseph, MI, ASAE. pp. 121–168.

565 Souiller, C., Y. Coquet, V. Pot, P. Benoit, B. Réal, C. Margoum, B. Laillet, C. Labat, P. Vachier, A. Dutertre: Capacités de  
566 stockage et d'épuration des sols de dispositifs enherbés vis-à-vis des produits phytosanitaires. Première partie : Dissipation

des produits phytosanitaires à travers un dispositif enherbé ; mise en évidence des processus mis en jeu par simulation de ruissellement et infiltrométrie. *Etude et Gestion des Sols*, 9,269, 2002.

Stehle, S., and R. Schulz: Agricultural insecticides threaten surface waters at the global scale. *PNAS* 112, 18, 5750-5755, doi:10.1073/pnas.1500232112, 2015.

Syversen, N. and M. Bechmann: Vegetative buffer zones as pesticide filters for simulated surface runoff. *Ecological Engineering* 22:175–184, 2004.

Tarantola, S., N. Giglioli, J. Jesinghaus, et A. Saltelli: Can Global Sensitivity Analysis Steer the Implementation of Models for Environmental Assessments and Decision-Making? *Stochastic Environmental Research and Risk Assessment*, 16, 63, 2002.

Terzaghi, K.: *Theoretical soil mechanics*, Wiley, New York, 1943.

Tollner, E.W., Barfield, B.J, Haan, C.T., Kao, T.Y.: Suspended sediment filtration capacity of simulated vegetation. *Trans. ASAE* 19, 4, 678-682, 1976.

Tomer, M.D., M.G. Dosskey, M.R. Burkart, D.E. James, M.J. Helmers and D.E. Eisenhauer: Methods to prioritize placement of riparian buffers for improved water quality. *Agroforestry Systems* 75, 1, 17-25, 2009.

IUPAC: The PPDB Pesticide Properties Database. International Union of Pure and Applied Chemistry (IUPAC), AERU, University of Hertfordshire, UK. <http://sitem.herts.ac.uk/aeru/ppdb/en/index.htm>), 2007.

Winchell, M.F., Jones, R.L., Estes, T.L.: Comparison of models for estimating the removal of pesticides by vegetated filter strips. *ACS Symp. Ser.* 273-286, 2011.

Woolhiser, D.A., R.E. Smith, et D.C. Goodrich: *KINEROS, A kinematic runoff and erosion model: documentation and user manual*, 1990.

Yang, J.: Convergence and uncertainty analyses in Monte-Carlo based sensitivity analysis. *Environ. Modell. Softw.* 26:444, 2011.

Yu, C., R. Muñoz-Carpena, B. Gao and O. Perez-Ovilla: Effects of ionic strength, particle size, flow rate, and vegetation type on colloid transport through a dense vegetation saturated soil system: Experiments and modeling. *J. of Hydrology*, 499, 316-323, doi:10.1016/j.jhydrol.2013.07.004, 2013.

592 White, M. J. and Arnold, J. G.: Development of a simplistic vegetative filter strip model for sediment and nutrient retention  
593 at the field scale, *Hydrol. Proc.*, 23, 11, doi:10.1002/hyp.7291, 2009.

594

595

Table 1. Characteristics of the field studies utilized for sensitivity–uncertainty analyses of shallow water table effects on VFS performance

Study	Authors	Lacas (2005); Lacas et al. (2012)	Madrigal-Monarrez (2004), Adamiade (2004)
	Location, climate	Morcille, Mediterranean semi-continental	Jaillère, Temperate oceanic
Event description	Rainfall (mm)	15	10.7
	Rainfall duration (hr)	2.1	3
	Inflow volume (mm)	0.847	6.347
	Inflow duration (hr)	2.1	7.9
	Hydraulic loading (rainfall + incoming runoff) (m <sup>3</sup> )	2.48	25.9
	Shallow water table depth (m)	2.5 (0.4-2.5)	0.8 (0.4-2)
	Source field area (m <sup>2</sup> )	2500	4000
Soil description	USDA Soil Taxonomy	Cambisol-luvic	Stagnic-luvisol
	USDA texture	Sandy-loam	Silty-clay
VFS description	Length (direction of flow)×width	6 x 4m	5 x 10m
	slope	28%	4%
	Field-to-filter area ratio	110	100
	Vegetation	Ray-grass (20 years)	Ray-grass (7 years)
Pesticides (K <sub>oc</sub> , ml/g)		isoproturon (144)	isoproturon (144)
		tebuconazole (769)	diflufenican (3000)



Input factor (units)	Description	Morcille		Jailli�re	
		Base value	Distribution	Base value	Distribution
Hydrological inputs					
FWIDTH (m)	Effective flow width of the strip	4.0	$U(4.0, 4.4)$	10.0	$U(9.0, 10.0)$
VL (m)	Length in the direction of the flow	6.0	$U(5.4, 6.0)$	5.0	$U(5.0, 5.5)$
RNA (s m <sup>-1/3</sup> )	Filter Manning’s roughness $n$ for each segment	0.2	$T(0.1, 0.2, 0.3)$	0.2	$T(0.1, 0.2, 0.3)$
SOA (–)	Filter slope for each segment	0.25	$U(0.20, 0.30)$	0.03	$U(0.02, 0.04)$
VKS (m s <sup>-1</sup> )	Soil vertical saturated hydraulic conductivity in the VFS	4.58E-5	$LN(-10.6676, 0.69)$	2.50E-6	$LN(13.0, 0.69)$
SAV (m)	Green-Ampt’s average suction at wetting front	0.110	$U(0.088, 0.132)$	0.1668	$U(0.13, 0.20)$
OI (–)	Initial soil water content, $\theta_i$	0.22	$U(0.1, 0.35)$	0.15	$U(0.12, 0.18)$
OS (–)	Saturated soil water content, $\theta_s$	0.4	$N(0.4, 0.03)$	0.4	$N(0.4, 0.03)$
SCHK (–)	Relative distance from the upper filter edge where check for ponding conditions is made (i.e., 1 = end; 0 = beginning)	0.5	$U(0, 1)$	0.5	$U(0, 1)$
L (m) <sup>†</sup>	Shallow water table depth from soil surface	1.0	$U(0.4, 2.5)$	0.8	$U(0.4, 2)$
OR (–) <sup>†</sup>	Residual soil water content, $\theta_i$	0.038	$N(0.038, 0.03)$	0.07	$N(0.07, 0.03)$
VGALPHA (m <sup>-1</sup> ) <sup>†</sup>	van Genuchten soil characteristic curve parameter ( $\alpha$ )	10.0	$N(10, 2)$	1.18	$N(1.18, 0.05)$
VGN (–) <sup>†</sup>	van Genuchten soil characteristic curve parameter ( $n$ ), $m=1-1/n$	1.52	$N(1.52, 0.05)$	1.45	$N(1.45, 0.05)$
Vegetation inputs					

SS (cm)	Average spacing of grass stems	1.6	$U(1.3,2.1)$	1.6	$U(1.3,2.1)$
VN ( $\text{s cm}^{-1/3}$ )	Filter media (grass) modified Manning's $n_m$ (cylindrical $=0.012$ )	0.012	$T(0.0084,0.012,0.016)$	0.012	$T(0.0084,0.012,0.016)$
H (cm)	Filter grass height	15.0	$U(10,35)$	15.0	$U(10,35)$
<b>Sedimentation inputs</b>					
VN2 ( $\text{s m}^{-1/3}$ )	Bare surface Manning's $n$ for sediment inundated area in VFS	0.013	$T(0.011,0.013,0.04)$	0.02	$T(0.011,0.02,0.04)$
DP (cm)	Sediment particle size diameter ( $d_{50}$ )	0.0099	$U(3.80\text{E-}3,1.60\text{E-}2)$	0.0029	$U(2.00\text{E-}4,3.69\text{E-}3)$
COARSE (–)	Fraction of incoming sediment with particle diameter $> 0.0037$ cm (coarse fraction routed through wedge as bed load) [unit fraction, i.e. 100% = 1.0]	0.55	$U(0.51,0.6)$	0.45	$U(0.4,0.49)$
<b>Pesticide inputs</b>					
KOC (ml/g)	Organic carbon sorption coefficient for simulated pesticide				
Isoproturon		144	$T(36,144,241)$	144	$T(36,144,241)$
Tebuconazole		769	$T(102, 769,1249)$	–	–
Diflufenican		–	–	3000	$T(1622,3000,7431)$
PCTOC (%)	Percentage of organic carbon in the soil	1.2	$U(1.18,2.5)$	3.78	$U(1.4,7)$
PCTC (%)	Percentage clay in the soil	12	$U(11,15)$	22	$U(19.8,25.5)$

598 † Parameters of the new infiltration under shallow water table component (SWINGO); ‡Statistics of the assigned distributions, uniform:  $U(\text{mix},\text{max})$ , triangular:  
599  $T(\text{min},\text{mean},\text{max})$ , log-normal:  $LN(\mu_y,\sigma_y)$ , normal:  $N(\mu_x,\sigma_x)$ . LN and N distributions are truncated between (0.001,0.999).

## Figure captions

Figure 1: Conceptual model of VFSMOD showing the coupling between overland flow, soil infiltration and redistribution, sediment and pesticide components. Solid lines indicate required processes and their interactions, and dashed lines are optional, user selected components. The selection of infiltration under either a) deep water table (extended Green-Ampt, GAMPT), or b) shallow water table (SWINGO) is highlighted.

Figure 2: Details of the dynamic coupling of (a) the overland flow and sediment and pesticide transport through the VFS (contained in VFSMOD), with (b) the new infiltration and soil water redistribution with shallow water component (SWINGO). Colors indicate water (blue), sediment (brown) and pesticide (red) components.  $V$ ,  $M$  and  $m$  indicate water, sediment and pesticide mass moving through the filter, where subscripts indicate incoming ( $i$ ), outgoing ( $o$ ), in sediment ( $sed$ ), on the filter ( $f$ ), infiltrated ( $F$ ), in mixing-layer ( $ml$ ) and in runoff ( $ro$ ). Other symbols are defined in the text.

Figure 3: Location of experimental VFS sites: Jailli re, North-West of France, maize crops on a flat silty-clay soil under Temperate oceanic climate; Morcille, South-East of France, vineyards on a sandy-loam soil under Mediterranean semi-continental climate. Morcille is located at 46 10'31.3"N - 4 38'11.2"E and Jailli re at 47 27'6.25"N - 0 57'58.37"O, in GPS coordinates.

Figure 4: Hydrological response of the VFS at the study sites. (a) Event at Morcille Aug. 17, 2004 with  $L=2.5$  m, showing comparison of measured outflow (symbols) and VFSMOD simulations (lines). The dashed Qout line for  $L=2.5$  m corresponds to average conditions for that event ( $K_s = 4.58E-05$  m/s), and the grey envelope represents outflow variability due to uncertainty of measured hydraulic conductivity. (b) Event at Jailli re on February 16, 1997 with  $L=0.8$  m, without outflow measurements. Qin and Qout represent surface inflow and outflow at the VFS. The potential effect on overland outflow of alternative water table depths in those events is represented by the dotted lines for  $L=0.4$  (a) and 4.0 m (b).

Figure 5: Change in dQ (reduction of surface water), dE (reduction of sediment) and dP (reduction of pesticide isoproturon) with water table depth for experimental events in Fig. 4a-b. Grey area indicates water table depths where influence over surface outputs on the VFS is no longer observed.

Figure 6: Morris elementary effects results for dQ (reduction of surface water), dE (reduction of sediment) and dP (reduction of pesticide isoproturon) on Jailli re (a-f) and Morcille (g-l) sites, without water table (no WT) and with water table (WT) present. Factors that have not negligible effects are named.

Figure 7: Probability density functions from the uncertainty analysis of eFAST simulations on output variables dQ (reduction of surface water), dE (reduction of sediment), dP (reduction of pesticides) for the Jailli re (a-b) and Morcille (c-d) sites, without water table (no WT) and with water table (WT). Pesticides are isoproturon (Iso), diflufenican (Dif) and tebuconazole (Teb).