Dear Mrs. Riva,

We have decided to revise the paper according to the comments from the two anonymous reviewers. It should be mentioned that the author list has been rearranged so the degree of contribution of the different co-authors is reflected accordingly, which was not previously the case.

In particular, the paper has been revised in regards to both referees mentioning their interest in expanding the section related to the section 4.3. Emphasis on the significance of the test case has been increased, while the issue related to reducing the size of the TI are described in the discussion. A list of miscellaneous corrections has also been composed and can be found in the "point-by-point reply" found below. Regarding the considerations of implementing a new figure with the ensemble averages of each of the 51 realizations for the different MPS methods, we chose to not include this figure since it did not change the conclusions of the paper.

Kind regards, Adrian A.S. Barfod

# Point-by-point reply, hess-2017-413

Firstly, the authors would like to thank the two anonymous referees for taking their time to read the manuscript and providing detailed and constructive comments. The comments, questions and suggestions are addressed in the following sections.

# **\*AC:** Author Comments **\*RC:** Referee Comments

NOTE: All of the line numbers in this document refer to the revised manuscript and not the "manuscript changes" document

## Response to anonymous referee #1

## **General comments:**

`The paper applies and compares three multiple point statistics (MPS) methods (snesim, DS and iqsim) for hydrostratigraphic modelling using geological and geophysical data. This research is very relevant as (1) three MPS methods, including very recent methods, are compared to evaluate the advantages and disadvantages of each method which is very useful for users that want to select one of the different available MPS methods and (2) since these methods are all applied on a real-world case with realistic geological complexity and data availability.'

**RC1:** 'The authors first apply the three MPS methods on their case study where the training image is actually identical to the model they want to simulate. This part is very extensive: the three MPS methods are used and different ways of validating the results are compared. The results of this part are according to me not so interesting since in a real case you never have the model you want to simulate but only one or more training images depicting some general geological concepts of the area. The results are also not surprising: iqsim better reproduces the TI which is logical since iqsim uses relatively large patches instead of pixels. In real cases, however, you don't want an exact reproduction of the TI but you want to simulate another area with similar patterns.'

**AC1:** We disagree that from a practical point of view the first set of tests are not as interesting since the model we wish to simulate is usually not available. Instead, we consider this case a "pseudo synthetic test case" where the TI provides an accurate rendition of the 3D patterns relevant to the given model.

Regarding the concern that you would never have the model you wish to simulate available to use as a TI, this is simply a case where the TI, synthetic or an actual real-world model, is a precise rendition of the expected hydrostratigraphic architecture.

Some of the authors have recently submitted a research paper to HESS, which is currently in open discussion. The paper focuses on the uncertainty related to the MPS setup, as well as a presentation of a more practical application, where a 3D geological model from another area is used as TI to simulate a hydrostratigraphic model using SkyTEM data and lithology logs (hess-2017-734; https://doi.org/10.5194/hess-2017-734).

**AC2:** Regarding the iqsim results, we were actually quite surprised that they performed the best in resembling the cognitive geological model based on the Modified Hausddorff distance ( $D_{MH}$ ). If the individual iqsim realizations are studied (FIGURE 8D) it is seen that the overall placement of the hydrostratigraphic units are not very precise, compared to snesim and DS (FIGURE 8B&C). In fact by looking at the vertical cross-sections the sporadic nature of the upper part of the realizations becomes clear, where the valleys (filled with 'sand & gravel'

and 'glacial clay' can be covered by 'hemipelagic clay', which is not possible in the TI. Looking at the borehole distance results, iqsim has the highest average borehole distances for 'sand & gravel' and 'glacial clay' units.

### **Resulting corrections:**

Line 18-19: The main case is introduced as a "synthetic test case", so that it is made clear that it is a controlled environment in which we can test the different MPS methods against each other

Line 116: the halfsim case is no longer referred to as a "practical example"

Line 120-122: The main case is introduced as a "synthetic test case"

<u>Line 128</u>: the halfsim case is no longer referred to as a practical example, but instead just as an example <u>Table 4</u> – "row average" column added which relates to the borehole distances, and describes the trade-off relationship between the borehole distances respective of the individual hydrostratigraphic units. <u>Line 639</u>: The "row average" column of Table 4 is referred to in the text

**RC2:** 'In the last part of their paper, the left half of the existing geological model is used as a TI to simulate the right half of the model. For me, this second part is much more interesting. However, this part is very short: only one MPS method is used and different aspects of validation (such as comparison with boreholes) are not shown or discussed. I would like to see an application of the three MPS methods here and a more thorough description and discussion of the results as for the first part where the TI is equal to the result you want to obtain. For clarity and compactness of the paper, I would even propose to only do the full analysis on the second problem where another area is modeled and to remove the part where the TI is identical to the model.'

# **AC3:** As stated above in **AC1**, we disagree with the statement that the second part is "more" interesting than the first part. Again, we consider the first case a "pretend case" where the TI contains the actual 3D patterns of the target model and is therefore a "best case scenario".

Furthermore, focusing on the second case, the half-sim case, a problem occurs since the TI is cut in half. Cutting the TI in half, results in a reduction of the patterns contained in the TI, and, as discussed by e.g. Emery and Lantuéjoul (2014), if the size of the patterns contained in the TI are too small we do not properly reproduce the desired patterns. If they become too small the information is simply not available. In this case some of the valleys are cut in half and only part of the valley structures are present in the half TI. Therefore, although the second half sim case is interesting from a practical point of view, it is simply not an ideal setup for making such tests. The discussion text has been edited to reflect these issues.

A recent paper has been submitted to HESS (hess-2017-734; <u>https://doi.org/10.5194/hess-2017-734</u>) and is currently in the public discussion phase. In the paper, snesim is used to test if it is possible to use a 3D hydrostratigraphic models from a different survey area to create 3D hydrostratigraphic models. The exact same half sim case, with the exact same data, was also presented for iqsim by Hoffimann *et al.* (2017) We will add a reference to Hoffimann *et al.* 

(2017). We will add a reference to Hoffimann *et al.* (2017) in the section describing the half-sim case and include the results by Hoffimann *et al.* (2017) in the discussion of the half-sim case.

## **Resulting corrections:**

<u>Line 777-782:</u> The issue related to cutting patterns from the TI is addressed. <u>Line 680-681:</u> The Hoffimann *et al.* (2017) study is mentioned

**RC3:** 'Abstract, line 13 + introduction, lines 32-37: I would replace "hydrological" models by "hydrogeological models" or "groundwater models" as "hydrological" models could also refer to surface water modelling, rainfall-runoff modelling or river modelling which do not involve inclusion of geological and/or geophysical data.'

AC4: Good point, this has been edited

**Resulting corrections:** 

<u>Line 13:</u> "hydrological models" has been replaced with "groundwater models" <u>Line 34:</u> "hydrological modeling" has been replaced with groundwater modeling <u>Line 35:</u> "hydrological modeling" has been replaced with groundwater modeling

## Response to anonymous referee #2

## **General comments:**

`This paper provides an exhaustive comparison of three Multiple-Point-Statistics (MPS) methodologies - namely, Single normal equation simulation (snesim), Direct Sampling Simulation (DS) and Image quilting simulation (iqsim) - for the generation of random distributions of hydrofacies on a specific field site. For each methodology, the diverse realizations of hydrostratigraphic categories are obtained on the basis of 51 stochasticallyreconstructed resistivity grids, to include the effect of uncertain conditioning (soft) data. The generated hydrostratigraphic models are compared against each other and against the Training Image (TI) (i) by visual inspection, (ii) in terms of the modified Hausdorff distance and (iii) in terms of the distance from borehole (hard) data. The paper is clearly written and the results will have wide application in the con-text of field-scale stochastic facies reconstruction. I recommend the paper for publication in HESS, after that the authors address the questions/comments in the following itemized list.'

**RC1:** *Advantages and disadvantages of each methodology are extensively discussed, and can be summarized as follows:* 

(i) snesim is the best one in conditioning the simulations with soft data, thanks to the implicit Resistivity Atlas histograms. This methodology provides the best results in borehole distance for 2 out of 3 hydrostratigraphic categories. However, the resulting stochastics models are affected by unrealistic small scale variability, which implies a larger distance from the TI.

(ii) iqsim is the fastest algorithm amongst the three. It provides the smallest distance from the TI and the largest variability between realizations. On the other hand, it suffers from an improper conditioning from soft-data grids, as indicated by poor borehole distance results.

(iii) DS is the most computationally expensive, it suffers from small-scale variability (line 56) and hydrostratigraphic units are not conditioned properly (line 753). It provides intermediate results in terms of all comparison metrics considered.

*So, why did the authors choose DS as the unique methodology in the "Hydrostratigraphic modelling of new surveys", in Sect. 4.3? I would recommend to integrate this section also with the results of the other two methodologies for the simulation of "Area B"."* 

**AC1:** The choice of method was not crucial here since the "Hydrostratigraphic modelling of new surveys" was only meant as an experiment to portray the practical applications of MPS in relation to 3D hydrostratigraphic voxel modelling. Since the DS method is easy to parameterize and easy to setup for running in parallel on a computer cluster it was chosen over using the SGeMS implementation of snesim. This is now reflected in the paper.

Regarding integrating the other methods in Sect. 4.3, see author comment 3 and 4 in the response to anonymous referee #1.

## **Resulting corrections:**

Line 678-681: the choice of the DS method for the halfsim case is elaborated

**RC2:** 'The absence of small-scale variability in single realization (iqsim) is regarded as an advantage. But, (1) as discussed in lines 733-741, this reconstructions can be regarded as the most realistic only if the TI is actually reproducing the correct scale of variability; (2) it is the model ensemble, and not the individual random

realization, that is supposed to reflect the behavior of the whole system. Small-scale variations effect seem indeed to be reduced when evaluating the mode over the 10 realizations in sect. 4.3. The ensemble modes evaluated over each one of the three sets of 51 simulations analyzed in the first part of the study should be also reported.'

**AC2:** The absence of small-scale variability of a single realization seems to be part of the reason for the smaller MHD<sub>cog</sub>-distances in the iqsim realizations. So, in comparison with the TI, which does not contain small-scale variability, the iqsim realizations are the most similar, not realistic. The text has been revised to make it clear that small-scale variability does not mean less realistic realizations. Furthermore, a new figure presenting the ensemble modes for each of the three algorithms will be considered strongly for the final draft.

## **Resulting corrections:**

Line 550, 551, 562, 563, 688 and 756: The usage of the word "unrealistic" in tandem with "short scale variability" is avoided

The ensemble modes for each of the three algorithms was not implemented since it did not change the results and conclusions of the paper.

**RC3:** 'It is not explored in this context how the three algorithms behave when generating random simulations with fixed conditioning data. What are the effects of the methods themselves on, e.g., the variability between realizations?'

**AC3:** We are not sure what the referee means by "generating random realizations with fixed conditioning data". We assume what is meant is to run realizations with borehole data as hard conditioning data. The usage of hard borehole data for conditioning was not important for the goal of this paper, which was focused on comparing MPS algorithms using an extensive soft SkyTEM data set. However, a recent paper has been submitted to HESS (hess-2017-734), where snesim realizations are conditioned to both soft SkyTEM data and hard borehole data.

**RC4:** *`line 458: "Here, sand & gravel and glacial clay were categorized into a single category, and hemipelagic clay was used as a background variable". The Modified Hausdorff distance is evaluated on binary images. Did the authors try to evaluate a MHD array separately for each category (similarly to what it is done for AEBD)?'* 

**AC4:** This is a good observation, and in the revised paper it is stated more clearly why we make an evaluation based on binary images. The reason for this was the computational overhead of computing the Modified Hausdorff Distance for 51 models containing 1,187,823 cells (229x133x39). Even after representing the geometric objects of each realization as outlines only, the computational burden was still too large for computing the D<sub>MH</sub> for each separate category.

## **Resulting corrections:**

<u>Line 454-457:</u> computational burden related to D<sub>MH</sub> is mentioned <u>Line 594-595:</u> The combining of *glacial clay* and *sand & gravel* units is mentioned <u>Line 599:</u> The binary classification of the realizations is emphasized <u>Line 602:</u> The fact that the D<sub>MH</sub> simply measures the location of the valleys due to the binary classification of the realizations is emphasized

**RC5:** *'line 726: "The borehole distances of the iqsim realizations revealed exceedingly small hemipelagic clay distances, with average of 0.2 m"; line 730: "(...) the ample near surface hemipelagic clay decreases the hemipelagic clay borehole distance". If the presence of near-surface hemipelagic clay is an artifact of the algorithm (i.e. is not consistent with borehole data), why should it results in a decrease of the borehole distance?'* 

**AC5:** The text has been revised and now reflects that if hemipelagic clay is present at the surface then the average  $D_{MH}$  increases, and the reason for the low hemipelagic clay distances should be found elsewhere. Instead, in the revised paper, it is made clear that there is a trade-off relationship between the borehole distances of each of the three lithological categories. In the iqsim case the average distance is low for hemipelagic clay (0.2 m) while increased for the glacial clay (3.5 m) and sand & gravel (5.8 m) categories. The row average of the three lithological categories is therefore 9.5 m for iqsim, while the summed distance for DS is 8.5 m and for snesim the distance is 7.5 m.

## **Resulting corrections:**

<u>Table 4</u> – "row average" column added <u>Line 748-756:</u> The trade-off relationship is elaborated upon

**RC6:** *Figure 2: the figure caption and the references to the figure in the manuscript are not consistent with the letters (a-g) indicating the diverse frames of the picture.* 

**AC6:** This is not intended and the figure caption has been edited so it corresponds to the actual figure.

## **Resulting corrections:** <u>Figure 2:</u> caption has been edited

**RC7:** *`Eq. 2: Symbols a\_i and b\_i represent position vectors, but they are written as scalar quantities.'* 

**AC7:** The symbols are now italic to indicate that they are vectors in the revised version.

## Resulting corrections:

Equation 2: corrected

**RC8:** `*line 536: "where binlog\_i is the ith cell in the binary log grid" should be changed into "where binlog\_i is the ith ACTIVE cell in the binary log grid".*'

## AC8: Noted, the text has been edited

## **Resulting corrections:**

Line 531: The word "active" has been inserted

## **Miscellaneous corrections:**

- The author list has been changed, since the order was previously not representative of the degree of contribution of the different co-authors
- The Høyer *et al.* 2016 reference has been updated since the paper has now official been published
- An additional reference to the cognitive modeling approach has been added (Line 44)
- "Modelling" has been corrected to "modeling" throughout the revised paper to correspond with grammar rules related to writing English (United Stated)
- MHD has been changed to D<sub>MH</sub> throughout the revised paper in accordance with the HESS guidelines
- AEBD has been changed to D<sub>AEB</sub> throughout the revised paper in accordance with the HESS guidelines
- The following words are no longer written in *Italics*: snesim, DS and iqsim.

- In Figure 7 the reference to meltwater silt has been corrected to meltwater sand
- The final paragraph of the discussion was removed since it did not really discuss anything in particular
- The discussion of short scale variability and the usage of post-processing has been removed from the last paragraph of section 4.3, since post-processing is generally not considered in this paper.

## Hydrostratigraphic <u>modellingmodeling</u> using multiple-point statistics and airborne transient electromagnetic methods

Adrian A.S. Barfod<sup>1,2</sup>, Julien Straubhaar<sup>4</sup>, Ingelise Møller<sup>1</sup>, Anders V. Christiansen<sup>2</sup>, Anne-Sophie Høyer<sup>1</sup>, Júlio Hoffimann<sup>3</sup>, Anders V. Christiansen<sup>2</sup>, Ingelise Møller<sup>4</sup>Julien Straubhaar<sup>4</sup>, Jef Caers<sup>3</sup>

 <sup>1</sup>Department of Groundwater and Quaternary Geology Mapping, Geological Survey of Denmark and Greenland (GEUS), C.F. Møllers Allé 8, 8000 Aarhus C
 <sup>2</sup>Hydrogeophysics group, Department of Geoscience, Aarhus University, C.F. Møllers Allé 4, 8000 Aarhus C
 <sup>3</sup>Stanford Center for Reservoir Forecasting, School of Earth, Energy & Environmental Sciences, Stanford University, Green Earth Sciences, 367 Panama St, Stanford, CA 94305

10 <sup>4</sup>Centre d'Hydrogéologie et de Géothermie (CHYN), Université de Neuchâtel, Switzerland

Correspondence to: Adrian A.S. Barfod (adrian.s.barfod@gmail.com)

Abstract. Creating increasingly realistic hydrologicalgroundwater models involves the inclusion of additional geological and geophysical data in the hydrostratigraphic modellingmodeling procedure. Using Multiple Point Statistics (MPS) for stochastic
 hydrostratigraphic modellingmodeling provides a degree of flexibility that allows the incorporation of elaborate datasets and

- provides a framework for stochastic hydrostratigraphic modellingmodeling. This paper focuses on comparing three MPS methods: snesim, DS and iqsim. The MPS methods are tested and compared on a real-world hydrogeophysical survey from Kasted in Denmark, which covers an area of 45 km<sup>2</sup>. A controlled test environment, similar to a synthetic test case, is constructed from the Kasted survey and is used to compare the modeling results of the three aforementioned MPS methods.
- 20 The comparison of the stochastic hydrostratigraphic MPS models is carried out in an elaborate scheme of visual inspection, mathematical similarity and consistency with boreholes. Using the Kasted survey data, <u>a practicalan</u> example for <u>modellingmodeling</u> new survey areas is presented. A cognitive hydrostratigraphic model of one area is used as Training Image to create a suite of stochastic hydrostratigraphic models in a new survey area. The advantage of stochastic <u>modellingmodeling</u> is that detailed multiple point information from one area can be easily transferred to another area considering uncertainty.
- 25 The presented MPS methods each have their own set of advantages and disadvantages. The DS method had average computation times of 6-7 h, which is large, compared to jqsim with average computation times of 10-12 min. However, jqsim generally did not properly constrain the near-surface part of the spatially dense soft data variable. The computation time of 2-3 h for snesim was in between DS and jqsim. The snesim implementation used here is part of the Stanford Geostatistical Modeling Software, or SGeMS. The snesim setup was not trivial, with numerous parameter settings, usage of multiple grids and a search tree database. However, once the parameters had been set it yielded comparable results to the other methods. Both, jqsim and DS, are easy to script and run in parallel on a server, which is not the case for the snesim implementation in SGeMS.

#### **1** Introduction

Recent advances in hydrologygroundwater modeling have shown the importance of accurate hydrologiehydrogeologic models
for management of increasingly sparse groundwater resources. Hydrologic modellingGroundwater modeling predictions are sensitive to geologic heterogeneity (e.g. Freeze 1975, Gelhar 1984, Fogg et al. 1998, LaBolle and Fogg 2001, Zheng and Gorelick 2003, Feyen and Caers 2006, Fleckenstein et al. 2006, Zhao and Illman 2017). However, geological units include complexities not directly related to hydrofacies (Klingbeil et al. 1999). Instead, the concept of *hydrostratigraphic units* is used throughout this study, which effectively combines geological units and reduces the total number of units resulting in a closer
relation to the hydrologic units. Improving the realism and quantification of uncertainty around hydrostratigraphic models is

Formatted: Height: 29,7 cm

-{	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic
Υ	Formatted: Font: Not Italic

Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted, Font: Not Italia
Formatted: Font: Not Italic

therefore an important step towards accurate groundwater modellingmodeling predictions. Hydrostratigraphic models are created using several approaches. A common approach is a manual co-interpretation of available geophysical, geological and/or hydrologic data. The geoscientist cognitively uses his/her refined knowledge of geological processes combined with the provided datasets to create a detailed cognitive geological model (e.g. Jørgensen et al. 2013).(e.g. Jørgensen et al. 2013, Royse 2010). The cognitive geological model is then simplified to a hydrostratigraphic model. Even though the 45 hydrostratigraphic model encapsulates the complexities related to geologic architecture, it does not reflect the hydrostratigraphic uncertainty. It is a so-called deterministic model, *i.e.* one version of the hydrostratigraphic subsurface. An alternative to cognitive modellingmodeling is stochastic modellingmodeling using geostatistical methods. The field of geostatistical modellingmodeling focuses on creating models depicting subsurface hydrogeology and/or reservoir properties. 50 Geostatistics is currently applied in a number of geoscience fields, such as petrology (e.g. Okabe and Blunt 2005), petroleum reservoir modelling modeling (e.g. Journel and Zhang 2006, Strebelle et al. 2002), hydrogeology (e.g. Huysmans and Dassargues 2009), hydrology (e.g. Michaelides and Chappell 2009). Overall geostatistical methods provide a framework in which multiple equiprobable hydrostratigraphic models can be created in a semi-automated fashion. The individual stochastic models do not reflect the modellingmodeling uncertainty, but the model ensemble does. The multiple hydrostratigraphic 55 models can be used as a set of input parameters for the groundwater model. By running the groundwater model several times with different hydrostratigraphic models, multiple predictions can be made, yielding an estimate of the prediction uncertainty. The ability to understand how the hydrostratigraphic uncertainty is related to the prediction uncertainty will help in understanding where to improve the hydrostratigraphic models in order to reduce the prediction uncertainty. This study will however not focus on groundwater modellingmodeling predictions, but on the presentation of a stochastic modellingmodeling 60 framework for reconstructing subsurface hydrostratigraphic architecture.

Today *state-of-the-art* geostatistical tools are readily available to geoscientists. Traditional two-point statistics, or variogram based methods, *e.g.* sisim (Journel 1983) and sgsim (Deutsch and Journel 1998), have been widely used in both research and in practice (*e.g.* Seifert and Jensen 1999, Caers 2000, Juang et al. 2004, Delbari et al. 2009). However, variogram based techniques depend on two-point statistics for simulation of complex geological features. Depending on the complexity of the geological setting, such two-point statistical methods cannot re-create complex curvilinear geological features of the

subsurface which are common in fluvial and glaciofluvial environments (e.g. Arpat and Caers 2005, Hu and Chugunova 2008, Journel and Zhang 2006, Journel 1993, Liu 2006, Sánchez-Vila et al. 1996, Strebelle and Journel 2001). An additional geostatistical modellingmodeling tool which should be mentioned is T-PROGS (Carle 1999). T-PROGS is based on transition probabilities between categories and generates geostatistical realizations based on such constraints. In comparison with

65

- 70 indicator method, sisim, it allows for better integration of these transition probabilities and hence, the spatial cross-correlations of soil/rock type architecture into the groundwater models. However, T-PROGS also has difficulties in re-constructing curvilinear geological features. Kessler *et al.* (2013) made a detailed comparison between T-PROGS realizations and real-world cross-sections in a gravel pit in Denmark. The result reveals a suboptimal pattern reproduction, in comparison to other simulation tools such as Multiple-Point statistics (MPS) (Mariethoz and Caers 2014b). MPS is a recent alternative to classic
- 75 two-point statistics. Here, additional multiple-point (MP) information from a training image (TI) is used to condition the simulations. The usage of MP information allows for reconstruction of more complex geological features, such as curvilinear features (Strebelle 2002). A TI is any 2D/3D image containing geometrical information relevant to the hydrostratigraphic model. The crux of the MPS approach is finding a relevant TI. Some examples of 2D/3D TIs are: categorical images of outcrops (2D), categorical drawings of a geological system created by a geoscientist (2D), cognitive geological or hydrostratigraphic
- 80 voxel models (3D) (e.g. Høyer et al. 2015a) etc. Today, MPS techniques are widely used in geoscientific research and studies, a few examples are: Maharaja (2005), Meerschman et al. (2013), Hermans et al. (2014). The MPS framework allows for

Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted: Font: Not Italic

conditioning of geological architecture/patterns, a stochastic framework and spatially constraining to both soft data and hard data (Arpat and Caers 2005, Guardiano and Srivastava 1993, Journel 1993, Strebelle and Journel 2001).

Within the geostatistics framework the creation of hydrostratigraphic models requires the inclusion of data from multiple sources, often geophysical models (soft data), borehole data (hard data) and a TI. The different data sources each provide relevant information. Geophysical models provide information regarding the large-scale hydrostratigraphic architecture. Boreholes, on the other hand, provide detailed yet usually sparse information regarding hydrostratigraphic units. Each data source is a piece of the puzzle, combining the individual pieces improves the resulting hydrostratigraphic models. The inclusion of several types of data is, however, not trivial since information regarding their mutual relationships, *e.g.* the

- 90 hydrostratigraphic-petrophysical relationship, is required. An important source of information which helps to combine the different sources of data is geologic knowledge. Geologic knowledge can be defined as information regarding geologic processes, geomorphologic patterns, structural geology *etc.* Incorporating geological knowledge into hydrostratigraphic models is often difficult and done *ad-hoc.* Geologic information, as described above, complements the soft data and helps to create more realistic hydrostratigraphic models. However, within the MPS framework this type of information can be of implemented with TL
- 95 implemented via the TI.

This study focuses on comparing and testing three MPS methods on a real-world dataset from a groundwater survey in Kasted, Denmark. An important part of the dataset is the airborne geophysical survey, providing a set of resistivity models containing information regarding the large-scale hydrostratigraphic architecture of the area. The MPS tools are used to reconstruct an intricate system of interconnected buried valleys. The end result is an ensemble of hydrostratigraphic models. A 3D

- 100 hydrostratigraphic voxel model of the area is used as a TI, containing detailed MP information regarding the hydrostratigraphic features of the survey area. Information regarding the geological architecture and the relationship between hydrostratigraphy and petrophysical properties are contained in the TI. The hydrostratigraphic-petrophysical relationship is explicitly known since the hydrostratigraphic model spatially overlaps with the geophysical and borehole lithology logs. Spatially constraining the simulation to the soft data, consisting of the resistivity models, ensures that simulated geological patterns are placed
- 105 concurrently to the real-world. However, such geophysical soft data have several types of related uncertainty, *e.g.* spatial uncertainty related to incomplete datasets, resolution capabilities, signal-to-noise ratio decrease with depth *etc.* Incomplete geophysical datasets is a common problem and are typically reconstructed using geostatistics; often in a deterministic fashion. A common approach is to use variogram based geostatistics, such as Kriging interpolation, to reconstruct the incomplete resistivity grid (Isaaks and Srivastava 1989). We have used the stochastic direct sampling (DS) grid reconstruction routine
- 110 proposed by Mariethoz and Renard (2010). Here, the grid reconstruction uncertainty is reflected by multiple resistivity grids, yielding variable patterns in the multiple reconstructed grids. The reconstructed grids are then used in conjunction with the hydrostratigraphic TI to create a set of stochastic hydrostratigraphic realizations of the hydrostratigraphy of the modeled area.

In relation to the Danish Groundwater mapping campaign (Thomsen et al. 2004) detailed geophysical datasets (Møller et al. 2009) and hydrostratigraphic models exist. A selection of the 3D geologic and hydrostratigraphic voxel models are reported

- 115 in the literature, *e.g.* Høyer *et al.* (2015a), Høyer *et al.* (2015b) and Jørgensen *et al.* (2015). Additionally, the study by Høyer *et al.* (2016) presents a framework for making large-scale MPS models based on geological 3D voxel models, and seismic and borehole data. In this study, we will show a practical application where anhow MPS methods can be utilized to model a new survey area. An existing cognitive model from anone area is used as a TI for simulating a newanother survey area with similar geological characteristics.
- 120 To our knowledge, no vigorous studies comparing multiple MPS methods have been carried out on real-world hydrogeophysical datasets. By applying several measures to assess and compare the modeling results, the selected MPS tools are tried, tested and compared on real-world data. The MPS methods are tested in a pseudo synthetic environment, where an

actual 3D hydrostratigraphic model of the Kasted survey area is used as a TI. This guarantees a controlled modeling environment in which the TI contains highly relevant hydrostratigraphic architecture. The main contributions of this study are: 1) a practical real-world example of stochastic reconstruction of incomplete geophysical datasets, 2) Comparison of three MPS methods for integrating geophysical data: snesim (Liu 2006, Strébelle and Journel 2000), direct sampling (DS) (Mariethoz et al. 2010) and image quilting (iqsim) (Hoffimann et al. 2017, Mahmud et al. 2014), 3) validation of the comparison results by: a) visual inspection, b) a mathematical comparison method called the "analysis of distance" (ANODI) (Tan et al. 2014), c) comparison of the simulation results against the borehole lithology logs, 4) to show the strengths/weaknesses of a stochastic

130 hydrostratigraphic modellingmodeling framework, and 5) a practicalan example using the direct sampling method and showing how to use the cognitive hydrostratigraphic interpretation of one area to directly generate hydrostratigraphic models of new areas, using only the soft data from the new area.

#### 2 Study area and data

125

The Kasted survey area is located in Denmark, in the eastern part of Jutland, close to the city of Aarhus (Figure 1a). The 45
km<sup>2</sup> area has been surveyed in detail and contains 453 boreholes; as well as a SkyTEM survey of 333 line km. A detailed geologic model of the area has been created by Høyer *et al.* (2015a). The dataset was collected and compiled in relation to the HyGEM project. The local geology consists of an intricate system of interconnected Quaternary buried valleys, infilled with till and meltwater deposits. The buried valleys are incised into thick hemipelagic Paleogene clay, which dominates the area (Høyer et al. 2015a). Many such pre-glaciated areas are dominated by buried valleys, which have proven important subsurface
features in regard to groundwater flow (Jørgensen and Sandersen 2006, Seifert et al. 2008). These noteworthy geological features have received a lot of attention in research through the years (e.g. Destombes et al. 1975, Jørgensen and Sandersen 2009, Kehew et al. 2012, Ritzi et al. 1994).



# Figure 1: An overview map of the Kasted survey area; a) shows the geographic location of the survey area, which is marked as a black box, and b) shows a close-up view of the Kasted survey area with the related datasets and infrastructure overlay.

The dataset used in this study consists of a dense airborne geophysical SkyTEM survey, near-surface boreholes from the Danish borehole database, and a cognitive geologic model created by an experienced geoscientist. In the following we will summarize the key features of these datasets.

The SkyTEM system (Sørensen and Auken 2004), is a helicopter Transient Electromagnetic system allowing for rapid collection of large geophysical datasets, with high spatial density. The Kasted SkyTEM survey contains 333 line km with a

Formatted: Font: Not Italic	]
Formatted: Font: Not Italic	]
Formatted: Font: Not Italic	Ì

line spacing of roughly 100 m (Figure 1b). The SkyTEM data are inverted and modeled according to the scheme described by Viezzoli *et al.* (2008), the end result being a collection of spatially constrained inversion models. In Denmark it is standard protocol to calibrate the SkyTEM system at an official calibration site, as described by Foged et al. (2013), ensuring data of high-quality and reproducible results. Therefore, the resistivity values from a calibrated SkyTEM survey are comparable to

155 other calibrated SkyTEM surveys. The SkyTEM system is sensitive towards large-scale conductive trends in the subsurface, especially when a significant contrast between a conductive and a resistive feature exists. In the eastern part of Jutland it is common that the lower confining boundaries of the buried valleys are well resolved since these buried valleys are often quite resistive and are eroded into conductive hemipelagic Paleogene clays.

The Danish borehole database, JUPITER (Hansen and Pjetursson 2011), contains about 280.000 shallow boreholes which have been drilled for a variety of purposes, mainly in relation to drinking water, and raw materials exploration, but also in relation to research, and geotechnical studies. The JUPITER database contains information on location, drilling method, lithology, geologic age, filter position, water chemistry, *etc*.

165

170

The cognitive geologic model was created using all available data, including the 333 line km of SkyTEM data, information from 435 boreholes and prior geological knowledge of the area. The model was created using the cognitive modellingmodeling scheme, which is introduced by Jørgensen et al. (2013). The geological model is described in great detail by Høyer et al. (2015a). The geologic model is detailed and contains a set of 21 interconnected buried valleys. The final 3D voxel model contains 42 unique geological units, which are simplified into three overall hydrostratigraphic units in this study. The three hydrostratigraphic units are chosen for the purpose of covering the overall hydrological hydrogeological features of the groundwater modellingmodeling area. The cognitive hydrostratigraphic model will act as the TI as well as a base-line for assessing the performance of the three MPS methods, and the stochastic modeling results will be compared against the cognitive model.

#### 3 Methods

MPS provides a degree of flexibility, which assists the modeler in creating geologically realistic hydrostratigraphic models. The idea is to create a suite of hydrostratigraphic models, which span a realistic subset of possible model architectures, as opposed to a deterministic model, which spans a single possible model architecture. The term realistic refers to models, which comply with the underlying data sets mentioned above, *i.e.* borehole lithological logs, geophysical resistivity models, and the cognitive geological model. The underlying datasets have associated uncertainties describing ranges of possible models. The suite of equiprobable hydrostratigraphic models can be used as input to a groundwater model, making it straightforward to test the sensitivity of specific groundwater model predictions.

#### 180 3.1 MPS methodologies

MPS methods use a training image (TI) to condition a model simulation to a prior geological conceptualization. As opposed to two-point statistics, the joint variabilities of multiple-points (MP) are assessed at the same time during simulation. The MP joint variabilities cannot be inferred from sparse data and are therefore taken from a relevant exhaustive TI. The justification that a given TI can be used to infer the joint variability of MPs heavily lies on the choice of a relevant TI. A TI should always contain geologically realistic and relevant information (Journel and Zhang 2006). Finding and/or creating a realistic TI is thus important to the MPS methodology. A TI is essentially any categorical or continuous image, which contains the geological conceptualization of the target variable (Mariethoz and Caers 2014a). It is not a subsurface model itself, but a quantitative conceptual depiction of it. The user chooses the TI based on his/her prior understanding of the local hydrogeological system. The TI does not need to carry any locally accurate information, *i.e.* it does not need to contain the actual geographical positions

190 of the hydrostratigraphic architecture, just the general patterns. It needs to reflect a prior geological- or structural concept (Strebelle and Journel 2001).

The MPS methods chosen in this study have been selected to reflect recent advances in MPS methods. The MPS methods in this study include: the "single normal equation simulation" (snesim) (Strébelle and Journel 2000) implemented in the Stanford Geostatistical Modeling Software (SGeMS), "direct sampling simulation" (DS) (Mariethoz et al. 2010) implemented in DeeSse (Straubhaar 2011), and "image quilting simulation" (iqsim) (Hoffimann et al. 2017) implemented in ImageQuilting.jl.

#### 3.1.1 Single normal equation simulation - snesim

The snesim method is a traditional MPS method. It fits into the so-called "probability framework" where geophysical models (not data) are considered soft information, and as such needs to be converted into probabilities. Suppose we have a categorical random variable S which has K possible states  $(s_k, k = 1, ..., K)$ , *i.e.* there are K hydrostratigraphic units. For each cell in the target sampling grid a probability  $prob\{s_k\}$  is defined for each of the K states, so that for a given grid cell, denoted  $cell_i$ : (1)

 $prob{cell_i} = \sum_{k=1}^{K} prob{s_k} = 1,$ 

where  $i \in \{1, ..., N\}$ , and the sampling grid has a total of N cells. The crux is then to translate the geophysical data into the probabilities described in equation (1). The collection of all probabilities for the entire sampling grid is also referred to as a probability map (2D) or probability grid (3D). The translation of the soft data is usually carried out based on a prior 205 understanding of the petrophysical-hydrostratigraphic relationship, and will be discussed further later in the paper. For a detailed description of the more general petrophysical-lithological relationship, the reader is referred to e.g. Barfod et al. (2016) and Beamish (2013). The probability grids are used to constrain the simulation using the so-called tau model (Journel 2002). The probability grid approach is intuitive, and allows the modeler to incorporate any desired datasets or variables into the probability map. Examples of soft data are any type of geophysical soft data and/or prior information, which can be translated

210 into probabilities.

225

195

200

In snesim, the TI is stored in a dynamic data structure called a search tree. The search tree is a database and can be seen as a condensed summary of the full TI. It contains the spatial information to which the simulation is conditioned; for more detail see Strebelle (2002). To avoid repetitive scanning of the TI, which is computationally expensive, the TI is stored in a search tree database ahead of the simulation (Roberts 1998). This is done once. TI patterns can then be retrieved from the database

without scanning the entire TI. Depending on the amount of detail stored in the search-tree this can be quite CPU intensive, 215 since the entire search tree is stored in memory, and therefore there is an upper limit to the size of the search-tree pattern database. However, advances in computers have increased the upper limit for available CPU.

Another caveat of snesim is the usage of multiple-grids (Tran 1994). Due to limitations in relation to the search neighborhood, the simulation of structures on all scales requires the usage of multiple grids. The simulation is carried out on a series of 220 multiple simulation grids with varying density, ensuring pattern reproduction at all scales. The search tree formulation and multiple grid approach add to the overall complexity of parameterization in snesim, but at the same time ensure stable and reliable MPS modeling results. The increased number of user-defined parameters makes it less intuitive, since it is relatively difficult to determine the optimal parameter values for a given dataset.

#### 3.1.2 Direct sampling simulation - DS

The Direct Sampling Simulation (DS) method consists, for the simulation of each cell, in randomly scanning the TI until a pattern similar to the pattern centered at the simulated cell is found, and then in copying the value in the center of the pattern from the TI to the simulation grid. As a consequenceConsequently, contrary to snesim, no probability is explicitly computed to draw a value at a simulation grid cell. In this paper, we use the DeeSse implementation of DS, presented by Straubhaar

Formatted: Font: Not Italic	
Formatted: Font: Not Italic	
Formatted: Font: Not Italic	
Formatted: Font: Not Italic	

Formatted: Space After: 0 pt	
Formatted: Font: Not Italic	

Formatted: Font: Not Italic

Formatted: Font: Not Italic							

-(	Formatted: Font: Not Italic
-(	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
Å	Formatted: Font: Not Italic

(2011). This bypasses the necessity of saving spatial patterns in a search tree database; instead<sub>2</sub> spatial patterns are conditioned 230 by directly scanning the TI.

One issue which needs to be solved is how to constrain a soft data variable. In <u>DS</u>, this is accomplished by introducing an auxiliary variable. The auxiliary variable is roughly a translation of the TI into a soft data variable. Suppose a forward operator, denoted by *G*, represents the physical model, which translates the subsurface hydrostratigraphic units into the continuous soft data variable, as when scanning the near surface with a geophysical instrument and subsequently process and interpret the data 235 into the actual petrophysical parameter. Then we can define an approximate forward operator G<sup>\*</sup> (Mariethoz and Caers 2014b).

- The  $G^*$  operator is an operator which is used to translate the TI into a spatially overlapping soft data variable. However, in practice creating a  $G^*$  operator requires several steps. Based on the modeling setup of this study, we will briefly review the required steps. Firstly, the TI needs to be populated with relevant resistivity values. The resulting populated resistivity grid does, however, not reflect the physical model, G, which translates the subsurface hydrostratigraphic units into subsurface bulk
- 240 resistivity. To properly reflect the G operator additional complexity needs to added, such as: smooth layer boundaries, loss of resolution with depth, limited resolution capabilities, the instrument footprint *etc*. This can be achieved by using either an approximate 1D or a full 3D forward modeling code to translate the populated resistivity models into synthetic data reflecting actually measured field data. These data, the forward responses then need to be processed and inverted back to resistivity models, which now constitute an auxiliary variable, which reflects the complexities involved with the SkyTEM system. The
- 245 auxiliary variable and the categorical hydrostratigraphic variable are combined to create a multivariate, or bivariate TI. The bivariate TI consists of a categorical variable, *e.g.* the three hydrostratigraphic units, and the geographically overlapping continuous auxiliary variable, representing the soft data variable. The setup used in this paper, avoids the usage of the G<sup>\*</sup> operator to create the auxiliary variable, since the reconstructed resistivity grids and cognitive hydrostratigraphic model grids geographically overlap. The reconstructed resistivity grids can thus directly be used as an auxiliary variable for the cognitive
- 250 hydrostratigraphic model TI. The bivariate TI constituted of collocated categorical hydrostratigraphic units (cognitive model / primary variable) and resistivity values (auxiliary variable) contains information regarding the relationship between these variables. The simulation is then conditioned against the bivariate TI by using a so-called distance measure. Distance measures are designed to compare the similarity of two sets of spatial patterns to each other. The idea is that similar patterns have relatively small distances, while dissimilar patterns have relatively large distance values. Conditioning against the <u>MP</u> information contained in the bivariate TI enables the ability to find probable spatial patterns, which also agree with the soft data variable.

DS is more flexible than traditional MPS methods, such as snesim. As no search-tree database is required, the multiple grid formulation used in *snesim* is not required in DS, which effectively reduces the number of parameters and makes the parametrization relatively simple. Furthermore, one can simulate continuous variables, and/or discrete variables with no limitation to the maximum number of categories (*e.g.* hydrostratigraphic units). In our case, any number of geophysical datasets collocated or not, can be included as long as a corresponding auxiliary variable is added to the multivariate TI. However, it

can be a cumbersome process generating the auxiliary variable. Furthermore, it is even possible to use probability grids in place of the actual soft data variable, as in snesim, if desired (Mariethoz et al. 2015). Depending on the setup and dataset, DS can be computationally as fast as snesim. Moreover, the DS implementation used in this work is amenable to scripting yielding
 the possibility of improving computation times on computer clusters or servers, if available.

#### 3.1.3 Image quilting simulation - iqsim

The image quilting simulation (iqsim) method has been borrowed from the computer vision literature (Efros and Freeman 2001). The algorithm is originally designed to synthesize and/or replicate patterns from 2D images, but has since been modified to accommodate conditioning data and 3D geoscience problems (Mahmud et al. 2014). The concept of the iqsim method is

Formatted: Font: Not Italic

Formatted: Font: Not Italic

-	Formatted: Font: Not Italic
-{	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic

-	Formatted: Font: Not Italic
$\neg$	Formatted: Font: Not Italic
$\neg$	Formatted: Font: Not Italic
Υ	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic



270 straightforward. In essence, iqsim cuts the TI into user defined patches or blocks, and then reassembles the patches to create a simulation. The difficult part is how to re-assemble the patches, to create meaningful and seamless realization results, which can be constrained to a soft data variable. These difficulties have been solved, and for more detail see *e.g.* Hoffimann *et al.* (2017)<sup>1</sup>. A great advantage of the iqsim method is its computation time. It has a similar setup to DS, regarding the usage of auxiliary variables. The iqsim method is new within the field of groundwater and environmental modellingmodeling, and for this paper the open-source Julia implementation by Hoffimann *et al.* (2017) is utilized. So far, this code contains the ability to use masked grids, *i.e.* grids where only specified grid cells are simulated, conditioning hard and soft data, and running simulations on the computer *Graphics Processing Unit* (GPU), yielding computationally fast simulation of hydrostratigraphic models on a personal computer. As with DS, there are no limitations to the number of data events, since the search-tree structure is avoided, no multiple-grids are required, effectively making for a simple parameterization.

#### 280 3.2 Reconstructing incomplete dense geophysical datasets

A common problem in hydrogeophysics is that datasets, albeit spatially dense, do not cover the entire modellingmodeling grid. In electromagnetic methods human infrastructure causes electromagnetic interference with the signal. Such noisy soundings, referred to as coupled soundings, are removed during processing, as presented by Auken *et al.* (2009), resulting in an incomplete dataset with gaps scattered throughout the survey area (Figure 1b). Several approaches to manage with incomplete

- 285 datasets exist. One approach is to leave the incomplete dataset as is; meaning gaps are reconstructed during simulation of the hydrostratigraphic model without spatially constraining the simulation gaps. The gaps are filled out solely by conditioning to the TI. Alternatively, dataset gaps can be filled prior to simulation, which is primarily done if the dataset has a high spatial density and/or the underlying random variables describing the data are not assumed to be especially complicated. The soft data utilized for constraining in this study are SkyTEM models. The raw SkyTEM data undergo processing and inversion (Auken
- et al. 2009), resulting in a series of spatially constrained 1D resistivity models at the sounding locations (Viezzoli et al. 2008) (Figure 1b). The SkyTEM resistivity models are then assigned to the nearest sampling grid cells by Simple Kriging with a 50 m search radius. The end result is a spatially dense incomplete 3D resistivity grid (Figure 2a). The high spatial density makes it possible to reconstruct the dataset using geostatistical tools, such as pixel based Kriging techniques, a so-called two-point statistical tool, for reconstructing incomplete datasets (Goovaerts 1997). Another approach for reconstruction of incomplete
- 295 datasets is the method using DS presented by Mariethoz & Renard (2010). Since the density of the data points is sufficiently large, the resistivity grid itself can be used as both a TI and soft data variable to stochastically simulate the missing values in the resistivity grid, *i.e.* the gaps in Figure 2a. The MPS dataset reconstruction approach (Figure 2c) is advantageous over the variogram based Kriging estimation (Figure 2b) since it only requires setting up a few parameters. Furthermore, the DS approach uses MP information to condition the reconstruction of the dataset. Here, it is important to note that the Kriging
- 300 method is an estimation method, while the DS approach is a simulation method. An estimation method estimates a "best" value, while a simulation method makes a stochastic ensemble of equiprobable guesses. The end result of the DS reconstruction approach is an ensemble of stochastic resistivity grids, of which one realization is compared against a corresponding Kriging reconstructed grid in Figure 2b and c. The close ups of Figure 2b and c reveal some key differences in the reconstruction of gaps using Kriging and DS. The resistive peak fringing the border of the gap in the westernmost resistive buried valley is smeared into the gap in the Kriging reconstructed grid; see close up in Figure 2b. However, the single DS reconstruction
  - presented here does not smear the resistive peak into the gap; see close up in Figure 2c. The usage of MP information in DS allows the possibility that the resistive peak is not part of the gap.

Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted: Font: Not Italic

_				
Foi	rmatted: Font	: Not Italic		
(Fai	manthed. Cont	Not Itolia		-
FOI	matted: Font	: NOT ITAIIC		_
Foi	rmatted: Font	: Not Italic		
For	matted. Font	· Not Italic		
	mattear	. Not Italic		_

-	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic

<sup>&</sup>lt;sup>1</sup> Software is available at https://github.com/juliohm/ImageQuilting.jl.

The uncertainty related to the stochastic resistivity grids is different from the Kriging resistivity grid uncertainty. The standard deviation (STD) related to the Kriging reconstructed grid is closely related to the distance to the nearest data point (Figure 2d),
whereas the uncertainty on the stochastic resistivity grids reveals values much more correlated to the patterns of the geophysical information.



Figure 2: Comparison of the deterministic Kriging and stochastic DS resistivity grid reconstruction and their corresponding standard deviation. The presented horizontal slice is centered on 20 mbsl. a) shows the incomplete resistivity grid using simple
 Kriging with a Kriging radius of 50m, b) shows a close-up of the reconstructed resistivity grid using Kriging with a close-up of a reconstructed resistive valley, ec) shows the reconstructed resistivity grid using DS, d) shows the full reconstructed resistivity grid using Kriging, e) a single realization of the reconstructed resistivity grid using DS with the same close-up df the standard deviation from the reconstructed resistivity grid using Kriging, and eg) the standard deviation calculated from an ensemble of 51 stochastic reconstructed resistivity grid using DS.

- 320 It is important to note that the resistivity parameter uncertainty has neither been included in the Kriging nor the <u>DS</u> reconstruction, enabling the comparison of the STD maps. As an example, a gap present in the homogeneous conductive units with resistivity values between ~2-8 Ωm, has a low STD. According to the TI there is a high probability of finding a conductive unit in a gap surrounded by only conductive units due to the homogeneity of such conductive units. However, gaps fringing the border of two contrasting resistivities have large STD values, since information regarding the exact location of the boundary is missing in the TI; *e.g.* the large STD value at the eastern border of the survey area seen in Figure 2e.
  - In summary, the uncertainty of the DS reconstruction provides additional information regarding the reconstructed resistivity patterns over for instance a kriging approach. Also, the MPS reconstruction of the incomplete dataset is less smooth, easier to parameterize, stochastic, and the uncertainty is related to pattern reconstruction and not the distance to the nearest data point.

#### 3.3 Hydrostratigraphic modellingmodeling setup

330

The MPS grid reconstruction procedure is used to generate an ensemble of resistivity grids without gaps (Mariethoz and Renard 2010). The reconstructed resistivity grids are used as soft data for constraining the simulation of the hydrostratigraphic models, with the cognitive 3D hydrostratigraphic model used as a TI. The full cognitive geological model contains a total of 42 different

Formatted: Font: Not Italic
Formatted: Font: Not Italic

geological units (Høyer et al. 2015a), which have been grouped together to form three key hydrostratigraphic categories. The three categories are as follows:

350

355

360

365

1. *sand & gravel*: Miocene sand, Quaternary meltwater sand and sand till, within and above the Quaternary buried valleys.

- 2. glacial clay: Quaternary clay till and, meltwater clay within and above the buried valleys.
- 3. hemipelagic clay: Hemipelagic, fine grained Paleogene and Oligocene clays.

The simplified cognitive hydrostratigraphic model is used as a TI, and contains the most significant hydrostratigraphic units.
Such 3D voxel TIs are usually not readily available, and in most cases 3D TIs are fabricated *ad-hoc*, and are merely conceptual. However, in this case the TI is actually the model we wish to simulate. The justification for this choice of TI lies in that this study is a *proof-of-concept* study, where three different MPS methods are compared against each other. Using a detailed TI containing the desired hydrostratigraphic concepts showcases how well the MPS methods perform in a stochastic hydrostratigraphic modeling workflow with a relevant TI.

345 The overall workflow can be seen in Figure 3. In detail, the steps are:

- The SkyTEM resistivity grids are reconstructed using the methodology of Mariethoz & Renard (2010) as described in section 3.2 "Reconstructing incomplete dense geophysical datasets".
- The ensemble of reconstructed SkyTEM resistivity grids is used as soft data for constraining the three MPS methods:
  - a. A reconstructed resistivity grid and the TI are used in the *snesim* framework:
    - Using histograms created using the Resistivity Atlas approach presented by Barfod *et al.* (2016) (Figure 4c and d) a single reconstructed resistivity grid is translated into a set of probability maps (Figure 5)
    - ii. The TI is used for conditioning in conjunction with the probability maps<sub>2</sub> which are used for spatially constraining the *snesim* simulations using the tau model (Journel 2002). The end result is a realization of a hydrostratigraphic model
    - b. A reconstructed resistivity grid is selected and used in combination with the TI for running <u>DS</u>:

       The soft data variable (the resistivity grid) is used for both constraining and as the auxiliary variable. The soft data grid is directly available as an auxiliary variable since it geographically overlaps with the categorical TI variable. The combination of the cognitive hydrostratigraphic
      - ii. The bivariate TI is used together with the soft data grid to simulate a realization of the hydrostratigraphic model
    - c. A reconstructed resistivity grid is used together with the TI for running jqsim:

model and auxiliary variable create a bivariate TI

i. As with DS, the soft data grid is used as an auxiliary variable, and for spatially constraining **Formatted:** Font: Not Italic the simulations. The TI and auxiliary variable are combined into a bivariate TI.

ii. The bivariate TI is used to create a simulation of the hydrostratigraphic model.

Steps 2a-c are repeated N times, once for each reconstructed resistivity grid. In this study N=51. For each of the 51 reconstructed soft data grids three simulations have been run, one simulation per MPS methods: snesim, DS and iqsim, yielding
 a total of 153 hydrostratigraphic realizations.

-	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic
Y	Formatted: Font: Not Italic

Formatted: Font: Not Italic



Figure 3: Workflow diagram showing the stochastic modellingmodeling procedure for a single realization. Each simulation is run with snesim, DS and iqsim.

#### 3.4 The hydrostratigraphic-resistivity relationship

Spatially constraining the simulations to the soft data requires information regarding the relationship between hydrostratigraphic units and, in this case, resistivity values. In DS and jqsim the information is contained in the bivariate TI, which in this case consists of a categorical and a continuous auxiliary variable. As discussed in section *3.1.2 Direct sampling simulation* - DS, the setup used in this paper avoids using the G\* operator due to the geographically overlapping resistivity and cognitive hydrostratigraphic model grids. This also enables summarizing the hydrostratigraphic-resistivity relationship as a set
of histograms (Figure 4a and b). The histograms summarizing the hydrostratigraphic-resistivity relations used in DS and jqsim are seen in Figure 4a, and the corresponding summary statistics are found in Table 1. These histograms are created by selecting one of the reconstructed resistivity grid and combining it with the TI. The same relationship is seen in Figure 4b, however, instead of using the DS reconstructed resistivity grid the Kriging reconstructed grid is used instead. The main difference between the two sets of histograms are a slightly larger separation of the *sand & gravel* and the *glacial clay* for the Kriging reconstructed grid (Figure 4a and b) (Table 1). For the DS reconstructed grid the median values for *sand & gravel* and glacial *clay* histograms are 48 Ωm and 32 Ωm, respectively. While for the Kriging reconstructed grid the median values are 46 Ωm

and 27  $\Omega$ m, respectively. Furthermore, the Kriging *sand & gravel* histogram is wider with an interquartile range of 38  $\Omega$ m, which for the DS grid was 31  $\Omega$ m.

Formatted: Font: Not Ital	ic
Formatted: Font: Not Ital	ic
Formatted: Font: Not Ital	ic
Formatted: Font: Not Ital	ic
Formatted: Font: Not Ital	ic
Formatted: Font: Not Ital	ic
Formatted: Font: Not Ital	ic



390 Figure 4: The hydrostratigraphic-resistivity relation shown as a series of histograms; a) shows the histograms created by categorizing the DS reconstructed resistivity grid according to the simplified hydrostratigraphic model created by Høyer et al. (2015a), b) the histograms created by categorizing a resistivity grid which has been reconstructed using Kriging, c) the histograms resulting from the Resistivity Atlas approach presented by Barfod et al. (2016), and d) the Resistivity Atlas histograms have been reproduced based on the summary statistics from c) to create a set of lognormal histograms.

Formatted: Font: Not Italic

- 395 In the *snesim* framework constraining to the soft data requires a translation of the soft resistivity data into a set of probability maps, one for each of the hydrostratigraphic units. This is achieved by using prior information regarding the hydrostratigraphic-resistivity relationship. Often this information is difficult to obtain, unless a large number of boreholes are available. If boreholes are readily available the Resistivity Atlas framework (Barfod et al. 2016) can be utilized. The raw Resistivity Atlas histograms are seen in Figure 4c. Due to the general coarse nature of the histograms the mean and interquartile range from the coarse histograms (Figure 4c) were computed and used to create a set of smooth histograms with identical summary statistics (Figure 4d). By comparison the Resistivity Atlas histograms are quite similar to the Kriging grid histograms (Figure 4b). However, the separation between the *sand & gravel* and *glacial clay* histograms is even larger in the Resistivity Atlas histograms. The respective median values are 59 Ωm and 34 Ωm. The *sand & gravel* histogram also has a quite large spread
- 405 Table 1: The summary statistics table for the histograms in Figure 4. The first section, named DS, shows summary statistics for the three histograms seen in Figure 4a. The second section, named Kriging, shows the summary statistics for the histograms in Figure 4b. The last section, labelled Resistivity Atlas, shows the summary statistics for the Resistivity Atlas histograms Figure 4c and d. All the values presented in the table are resistivities [Ωm].

	25 <sup>th</sup> percentile	Median	75 <sup>th</sup> percentile	IQR
DS				
Sand & gravel	34.2	47.6	65.5	31.3
Glacial clay	21.1	31.8	42.9	21.8
Hemipelagic clay	2.2	2.6	3.7	1.5
Kriging				
Sand & gravel	29.7	46.4	67.9	38.2
Glacial clay	17.2	26.6	38.2	21.0
Hemipelagic clay	1.9	2.4	3.6	1.8
Resistivity Atlas				
Sand & gravel	38.4	59.2	81.4	43.0
Glacial clay	24.2	33.9	46.7	22.5
Hemipelagic clay	2.1	2.5	3.4	1.3

- The *hemipelagic clays* have unique properties. They are aquitards with low hydraulic conductivity and often used as a hydraulically confining no-flow boundary at the bottom of a groundwater model in parts of Denmark. When *hemipelagic clay* is encountered during drilling, the drilling is halted and generally *hemipelagic clay* is sparse in Danish borehole lithology logs. For this reason the Resistivity Atlas based on Transient Electromagnetic data does not provide a lot of information on *hemipelagic clays*. However, the hemipelagic clays are regionally extensive and homogeneous. From wireline resistivity logs in eastern Jutland they are found to be conductive, with median resistivities ranging between 4-7 Ωm. Based on this knowledge
- 415 the *hemipelagic clay* histograms in Figure 4c and d are created.

with an interquartile range of 43  $\Omega$ m (Figure 4c and d) (Table 1).

- The model setup is different for the three MPS methods. When running <u>DS</u> and <u>iqsim</u> the hydrostratigraphic-resistivity relationship is explicitly given due to the geographically overlapping resistivity grid and hydrostratigraphic TI. Normally the auxiliary variable has to be created for the given TI using the G<sup>\*</sup> operator. The full G<sup>\*</sup> approach has been elaborated in section *3.1.2 Direct sampling simulation - DS*, and requires prior knowledge regarding the hydrostratigraphic-resistivity relationship, much like when creating the probability grid for *snesim*. The snesim setup, however, avoids using the G<sup>\*</sup> operator approach,
- and in place the Resistivity Atlas histograms (Figure 4c and d) can be used to directly translate the resistivity grid into probability grids (Figure 5).

-{	Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted Table



Figure 5: The SkyTEM soft data grids are translated into three sets of probability grids, one for each lithological category to be simulated; a) shows one of the reconstructed SkyTEM grids, the top frame is a horizontal slice in the 3D grid at 20 mbsl, the second frame is a horizontal slice of the grid layer at 60 mbsl and the bottom frame shows the vertical cross-section intersecting at UTMY coordinate 6230150 m, b) shows the sand & gravel probability grid, c) shows the glacial clay probability grid, and d) shows the hemipelagic clay probability grid. The horizontal slices and the vertical cross sections of b), c) and d) are the same as the ones presented in a).

#### 430 3.5 The modified Hausdorff Distance – a measure for similarity

point sets. Then the MHDDML between point sets A and B is defined as follows:

Comparing 153 3D models each with 1,187,823 grid cells is not trivial. Visual comparison is used mainly to check if the results are geologically realistic, but a detailed visual comparison would be time consuming and subjective. Therefore, a set of tools are used to compare how similar the simulation results are to each other, and how different they are from the TI.

In this study, a distance measure is used as a measure of similarity between 3D model simulations. The chosen distance measure 435 is the modified Hausdorff Distance (MHDDMH), which is a measure for similarity between two binary images, *i.e.* dissimilar images have relatively large distances (Figure 6e), while similar images have relatively small distances (Figure 6c). Identical images have a distance of exactly zero (Figure 6b). Firstly, the images we wish to study are summarized as binary images. The pixels for each object we wish to compare are set to one, while the remaining pixels are disregarded as a background variable and set to zero. For a pair of images,  $Im_A$  and  $Im_B$ , to be compared, two point sets are defined:  $A = \{a_1, a_2, ..., a_{N_a}\}$  and B =440  $\{b_1, b_2, ..., b_{N_b}\}$ , where  $a_i, i \in \{1, 2, ..., N_a\}$  and  $b_j, j \in \{1, 2, ..., N_b\}$  are positional vectors containing the x, y and z positional coordinates in  $Im_A$  and  $Im_B$  for the binary object pixels only, *i.e.* the background variable positions are not included in the

-{	Formatted: Subscript
$\neg$	Formatted: Subscript
-1	Formatted: Subscript
$\neg$	Formatted: Subscript
$\neg$	Formatted: Subscript

$$\begin{split} \frac{MHD(A,B) = max\left(\frac{1}{N_{a}}\sum_{a\in A}min_{b\in B}||a-b||,\frac{1}{N_{b}}\sum_{b\in B}min_{a\in A}||b-a||\right)}{\sum_{b\in B}min_{a\in A}||b-a||}D_{MH}(A,B) &= max\left(\frac{1}{N_{a}}\sum_{a\in A}min_{b\in B}||a-b||,\frac{1}{N_{b}}\sum_{b\in B}min_{a\in A}||b-a||\right), \end{split}$$
 (2)

- where  $N_a$  and  $N_b$  is the total number of points in point sets A and B, respectively. In the context of this paper, A and B are our 3D voxel models containing the objects we wish to compare. The Euclidian distances between a given point, a from point set A, and all points in point set B are computed, and min(...) selects the smallest of these distances. This is repeated for all points in point set A, and the average is computed. The same operations are performed for point set B. The maximum value of these two results is then returned.
- 450 Dubuisson and Jain (1994) found that the MHDD<sub>MH</sub> was the best performing distance measure out of 24 different Hausdorff based distance measures in relation to objects matching of images. In order to make the pairwise MHDD<sub>MH</sub> computation tractable in 3D, we approximate the MHDD<sub>MH</sub> between solid geobodies by the MHDD<sub>MH</sub> between their boundaries. In short, the boundary is the selection of the edges or outlines of the geometric objects, such that the objects are now represented by their outlines instead of the entire objects; see Figure 6b-e. The Roberts Cross Operator (Roberts 1998, Senthilkumaran and
- Rajesh 2009) is used to select the boundary. Instead of defining the point sets based on the geometric objects themselves, only their outlines are included in the point sets. The point sets containing the outline of the geometric objects are then compared using the MHDD<sub>MH</sub>.

A 2D example is presented to illustrate the overall <u>MHDD\_MH</u> concept in Figure 6. The 3D hydrostratigraphic model and the <u>DS modellingmodeling</u> results are simplified into 2D horizontal cross-sections from the <u>modellingmodeling</u> grid layer centered on 20 mbsl. The initial step is to create a binary version of the hydrostratigraphic simulation model (Figure 6a and b).

Here,Ideally, it would be optimal to compute the D<sub>MH</sub> between each of the hydrostratigraphic categories of the model.
However, due to computational limitations of the utilized D<sub>MH</sub> implementation, the valley categories, *i.e. sand & gravel* and *glacial clay*, were re-categorized intoas a single categoryunit, and *hemipelagic clay* was used as the background variable. After categorization, the Roberts cross operator is used to find the boundary of the objects (Figure 6b). The procedure of creating the binary image and outlines is carried out for all the 51 DS simulations. For illustration purposes, this example is only computed for the horizontal cross-section centered on 20 mbsl. The MHDD<sub>MH</sub> is calculated between each of the 51 horizontal binary maps, representing the DS simulations, and the binary hydrostratigraphic model. The resulting MHDsD<sub>MH</sub> are then

460

sorted in ascending order and the binary version of the realizations corresponding to the 1<sup>st</sup>, 25<sup>th</sup>, and 51<sup>st</sup>  $\frac{\text{MHDD}_{\text{MH}}}{\text{MHDD}_{\text{MH}}}$  values are presented in Figure 6c-e.

-	Formatted: Font: Not Italic
_	Formatted: Subscript
_	Formatted: Font: Not Italic



Figure 6: A 2D example of the binary categorization of the hydrostratigraphic models and example of the Roberts cross operator for edge-tracing; a) a horizontal slice of the hydrostratigraphic model at elevation interval centered on 20 mbsl, b) the result of the binary categorization of the hydrostratigraphic model into two categories: 1) Non hemipelagic clay (black) and 2) hemipelagic clay (white). The boundary of the objects in the binary image is shown in red. c) shows the object and boundary of the objects for the DS simulation which has the smallest Modified Hausdorff Distance (MHDDMI), i.e. is the most similar to b). The MHDDMI value is shown in d) shows the DS simulation, which has the 25<sup>th</sup> largest MHDDMI and e) shows the DS simulation with the largest MHDDMI and therefore is least similar to the hydrostratigraphic model in b).

From here on, we leave the 2D example, and consider the entire 3D model. In this study, the MHDDMH is used as a global distance measure. A more in-depth analysis of the MHDDMH results is gained by using the "analysis of distance" (ANODI)
method (Tan et al. 2014). The overall goal of ANODI is to provide a framework for comparing realizations from different stochastic MPS methods. The framework presented by Tan *et al.* (2014) uses the following definition of 'best': "one algorithm A is better than an algorithm B if the training image statistics are reproduced better while at the same time the space of uncertainty (the variability between realizations) is larger". In the particular MPS setup used in this study, the TI is a relevant cognitive hydrostratigraphic model and geographically overlaps with the hydrostratigraphic MPS realization grids. Hence, the MPS realizations should portray similarity to the cognitive model. In this study, a further complexity to the definition of best is added. An algorithm with a large space of uncertainty is not necessarily better, if the resulting models do not reflect the

underlying datasets. The initial step is to create a matrix containing all <u>MHDDMH</u> values between all 153 realizations, and between the individual realizations and the cognitive model. It is similar to a covariance matrix, but instead of containing covariance values, it contains

490 MHDDMH values. The usage of bold letters refers to a matrix. The full MHDDMH is definedcomputed as follows:

$MHD_{ij} = MHD(real_i, real_j), where \begin{cases} i = 1,, (N_{reals} + 1) \\ j = 1,, (N_{reals} + 1) \end{cases}$	(3)
	(3)

<u>Where</u>  $D_{MH}^{(i,j)}$  denotes the  $D_{MH}$  at position (i,j) of the  $D_{MH}$ -matrix,  $real_i$  and  $real_j$  denotes the individual hydrostratigraphic realizations,  $N_{reals}$  is the total number of realizations, in this case  $N_{reals} = 153$ , and last row and column of <u>MHDD\_MH</u> 15 Formatted: Default Paragraph Font, Font: English (United Kingdom), Subscript
Formatted: Default Paragraph Font, Font: English (United Kingdom), Subscript

495 contains the distances between the realizations and the cognitive model, *i.e.*  $real_{N_{reals}+1}$  represents the cognitive model. One <u>MHDD\_MH</u> matrix is created for all three MPS methods. For each of the three MPS methods, the <u>MHDD\_MH</u> can be evaluated by itself by calculating the <u>MHDD\_MH</u> variability, <u>MHD\_WAF</u>  $D_{MH,var}$ :

MHD <sub>var</sub> :	$=\frac{1}{(N_{reals}/3)^2}\sum_{i=MPS_{start,i}}^{MPS_{end,i}}\sum_{j=MPS_{start,i}}^{MPS_{end,i}}$	<del>البان</del> (MHD) الم	(4)
$D_{\rm MH,var} =$	$\frac{1}{(N_{\text{reals}/3})^2} \sum_{i=MPS_{\text{start},i}}^{MPS_{\text{end},i}} \sum_{j=MPS_s}^{MPS_{\text{end},i}}$	$_{\text{tart},j}^{j} \left( \mathbf{D}_{\text{MH}}^{(\text{i},\text{j})} \right)_{$	(4)

500 where N<sub>reats</sub> N<sub>reals</sub> is the size of MHDD<sub>MH</sub>, in this study N<sub>reals</sub> = 3 \* 51 = 153, MPS<sub>start,i</sub> MPS<sub>start,i</sub> and MPS<sub>end,i</sub> MPS<sub>end,i</sub> are the start and end indexes for the entries related to the given MPS method, MHD<sub>H</sub>D<sup>(i,j)</sup> is MHD(real<sub>i</sub>, real<sub>j</sub>)D<sub>MH</sub>(real<sub>i</sub>, real<sub>j</sub>). Note that the distances between the individual realizations and the cognitive model are not included in the MHD<sub>par</sub>, D<sub>MH,var</sub>. The MHD<sub>par</sub>, D<sub>MH,var</sub> equates to computing the average of the MHDD<sub>MH</sub> values between the realizations of a single MPS method. The larger the MHD<sub>par</sub>, D<sub>MH,var</sub> the more dissimilar the simulation results, 505 meaning they portray a large set of possible hydrostratigraphic architectures. Using equation (4) it is also possible to compute the distances between the realizations of different MPS methods, *e.g.* the average MHDD<sub>MH</sub> between *snesim* and DS.

The other evaluation measure, which can be calculated from <u>MHD</u> <u> $D_{MH_a}$ </u> is the distance between the realizations and the cognitive hydrostratigraphic model, or TI, which is summarized by the <u> $MHD_{eeg}$ </u>, <u> $D_{MH,cog}$ </u>, which is computed as follows:

$$\frac{MHD_{cog}}{MHL_{cog}}D_{MH,cog} = \frac{1}{\frac{1}{N_{reals}/3}} \sum_{i=MPS_{start,i}}^{MPS_{end,i}} (MHD_{I,N_{real}+1}) \frac{1}{N_{reals}/3} \sum_{i=MPS_{start,i}}^{MPS_{end,i}} (\mathbf{D}_{MH}^{(i,N_{real}+1)})$$
510 (5)

where, again,  $N_{reals}N_{reals} = 153$ ,  $MPS_{start,i}MPS_{start,i}$  and  $MPS_{end,i}MPS_{end,i}$  are the start and end indexes for the entries related to the given MPS method and  $MHD_{i,N_{real}+1}D_{MH}^{(i,N_{real}+1)}$  is the  $MHD(real_i, cog.model), D_{MH}(real_i, cog.model)_{i}$ The  $MHD_{cog}$   $D_{MHcog}$  is the average  $MHDD_{MH}$  between each individual realization and the cognitive hydrostratigraphic model. The larger the average  $MHDD_{MH}$  the more dissimilar the hydrostratigraphic realizations are from the cognitive hydrostratigraphic model. The reason we wish to compare the distance to the cognitive model, is that the cognitive model, geographically overlaps with the hydrostratigraphic MPS realizations.

515

520

It is also possible to evaluate the  $\underline{MHDD}_{MH}$  using dimensional reduction techniques. Such techniques help us view the high dimensional  $\underline{MHDD}_{MH}$  in a 2D and/or 3D map. Such a plot gives us a visual representation of the most significant structures of the  $\underline{MHDD}_{MH}$ . For dimensional reduction we use a variation of so-called Stochastic Neighbor Embedding (SNE) (Hinton and Roweis 2002). The technique is called t-distributed Stochastic Neighbor Embedding, or t-SNE (Maaten and Hinton 2008). The t-SNE method is advantageous over other SNE techniques, since it is easier to optimize and produces better visualizations. The idea is to visualize the level of similarity of individual entries, or distances in the  $\underline{MHDD}_{MH}$ . The overall goal is to place each  $\underline{MHDD}_{MH}$  value as a point in a 2D space where the relative distances between the point values reflect the degree of similarity. Similar points are close to each other, while dissimilar points are far from each other. This is achieved by t-SNE.

#### 525 3.6 Distance to boreholes

In reservoir modellingmodeling, boreholes are considered to be hard information, due to their overall high quality. However, in many surveys related to groundwater modellingmodeling, boreholes cannot be considered as reliable hard data due to variable quality. Such as seen in Barfod *et al.* (2016) and He *et al.* (2014) where boreholes were divided into quality groups. Therefore, the simulations are run without constraining against boreholes, and then the realizations are compared against the 530 boreholes as an independent measure of geological realism. A method for comparing similarity between the simulated hydrostratigraphic models and the boreholes was developed. The method does not use the MHDD<sub>MH</sub>, which has previously

```
Formatted: Font: Not Bold, Subscript
Formatted: Subscript
```

been used for measuring distances. Instead, the simple Euclidean distance is used to measure the average distance between each individual hydrostratigraphic realization and the borehole dataset. The first step is to sort the borehole lithology logs according to the respective hydrostratigraphic units, to create a hydrostratigraphic log; see left half of Figure 7. Once this has

been carried out three sets of binary and regularized logs are created from the hydrostratigraphic log; see right half of Figure 7. For each sampling grid interval, the presence of the given hydrostratigraphic category, say sand & gravel, is saved in the binary log. The end result is a log which states whether or not sand & gravel is present within the given sampling grid interval; active if present and inactive if not present. Three such binary logs are created, one for each of the hydrostratigraphic categories, i.e. sand & gravel, glacial clay and hemipelagic clay (Figure 7). A binary log grid is created by simply assigning the binary active values to the grid cell in which they are present. The Average Euclidian Borehole Distance, AEBDDAEB, between the

binary logs and a given realization, *real\_real*, for a given hydrostratigraphic category, *hydro. cat<sub>j</sub>* where  $j \in \{1, ..., N_{hydro. cats}\}$ , is calculated as follows:

$$AEBD(hydro. cat_{j}) = \frac{1}{N_{active}} \sum_{i=1}^{N_{active}} \min(\|binlog_{i} - real(hydro. unit_{j})\|)$$

$$D_{AEB}(hydro. cat_{j}) = \frac{1}{N_{active}} \sum_{i=1}^{N_{active}} \min(\|binlog_{i} - real(hydro. unit_{j})\|)$$
(6)

545 where  $binlog_i$  is i<sup>th</sup> active cell in the binary log grid,  $N_{active}$  is the number of active cells in the binary log grid, ED is the Euclidian Distance, and  $real(hydro.\ unit_j)$  is the binary realization grid containing only the j<sup>th</sup> hydrostratigraphic unit, where in this case  $N_{hydro.\ cats} = 3$ .

The end result is three arrays, one for each hydrostratigraphic unit, each containing one average distance per realization for the given MPS method. The distance arrays for each individual MPS method can then be compared to the distance arrays of the 550 other MPS methods.



Figure 7: An example of how a single lithology log is categorized and sorted for the purpose of calculating the borehole distance. The first step is to translate the raw lithology log into a hydrostratigraphic log, which is achieved by categorizing the multiple lithological categories into a subset of three hydrostratigraphic categories corresponding to the target categories we wish to model. Note that some categories do not fit into the overall hydrostratigraphic categories and are therefore not translated, e.g. the meltwater siltsand category in this example. The final step is then to assign the hydrostratigraphic logs to the regularized sampling grid and create one binary log for each of the three target modellingmodeling categories. This is done by simply asking whether or not the given hydrostratigraphic category is present (True) or not (False) for the given sampling grid interval.

#### 4 Results

555

1	Formatted: Font: Not Italic
. <	Formatted: Font: Not Italic
5	Formatted: Font: Not Italic
2	
+	
-<	
	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
i	Formatted: Font: Not Italic
e	Formatted: Font: Not Italic
1	
1	
,	
y -1	
-	Formatted: Font: Not Italic
3	
	Formatted: Font: Not Italic
s	
1	Formatted: Font: Not Italic
r	Formatted: Font: Not Italic
t	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
,	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Font: Not Italic

560 The hydrostratigraphic simulation results include 153 3D hydrostratigraphic realizations, each containing 1,187,823 grid cells. The models can be subdivided into 51 snesim realizations, 51 DS realizations and 51 jqsim realizations. A visual presentation of the hydrostratigraphic model or TI, and two realizations for each of the three different MPS methods is seen in Figure 8. The cognitive hydrostratigraphic model (Figure 8a) shows clear-cut and smooth buried valley architecture with almost no unrealistic short scale variability. Comparing the cognitive hydrostratigraphic model to the stochastic MPS hydrostratigraphic models reveals the more erratic nature of both snesim and DS, *i.e.* both MPS methods yield models containing unrealistic short

Overall snesim (Figure 8b) and DS (Figure 8c) realizations are similar in nature. In the example provided, Figure 8c, the West-Northwest - East-Southeast trending *glacial clay* valley (see box in Figure 8a) is uninterrupted in one realization, but intersected by *hemipelagic clay* in the other realization. In 47 of the 51 snesim realizations, the *glacial clay* valley is uninterrupted, in the remaining 4 realizations the valley is intersected by *hemipelagic clay*. The presented soft data grid in Figure 5d shows a small probability of approximately 10% for *hemipelagic clay* at the position of the valley gap. The 4 realizations which yielded an interrupted *glacial clay* valley amount to 8% of the 51 realizations, which is close to the probability found in the probability grids. The DS realizations shows valley architecture with less resemblance to the soft data, *i.e.* the valleys are not conditioned in accordance to the soft data grids. In 11 of the 51 simulation results the valley is intersected by *hemipelagic clay*, amounting

575 to 22% of the 51 realizations.

580

scale variability (Figure 8b and c).

The jqsim results are the most similar to the cognitive hydrostratigraphic model with regards to unrealistic-short scale variability, which is generally non-existent. Generally, realizations will reflect the TI, and unrealistic-short scale variability is only introduced if present in the TI. This is due to the nature of jqsim, which is not a pixel based algorithm, like *snesim* and DS. Instead, jqsim cuts the TI into patches and then reassembles the patches, which means that noise patterns which are smaller than the patch size cannot be fabricated, unless actually present in the TI. The jqsim realizations show smooth and clear-cut valley architecture. The main issue with the jqsim realizations is that artifacts are introduced near the surface of the model, evident if the vertical jqsim cross-sections (Figure 8d) are compared to the remaining vertical cross-sections of the TI, snesim and DS (Figure 8a-c). This is neither reflected in the resistivity grid (Figure 5) nor in the TI (Figure 8a). Close to terrain hydrostratigraphic layers consist of either glacial clays or sand & gravel, and conductive hemipelagic clays are not evident.

585 Since the soft data does not support the presence of the *hemipelagic clays* in the upper part of the hydrostratigraphic model, the soft data can be concluded to being improperly constrained with this specific setup. Another observation is that in 43 out of the 51 realizations, amounting to 84%, the referenced *glacial clay* valley is intersected by *hemipelagic clay*.



Figure 8: The hydrostratigraphic MPS realizations are presented as horizontal slices centered on 20 mbsl and vertical cross-sections intersecting at UTMY 6230150m; a) shows the cognitive hydrostratigraphic model, with a West-Northwest - East-Southeast trending glacial clay valley marked by a box, b) shows two *snesim* realizations, c) shows two *DS* realizations, and d) shows two iqsim realizations.

An advantage of the jqsim implementation used (Hoffimann et al. 2017)(Hoffimann et al. 2017) is the favorable computation time. On an Intel® HD Graphics Skylake ULT GT2 GPU of a Dell XPS 13 laptop, jqsim runs with an average simulation time of 10-12 min per realization with the attempted setup. On a different laptop running a 64bit64-bit Windows system, with 8GB RAM, an SSD hard disk, with an Intel core i7-3520 M CPU at 2.9 GHz, the computation times for snesim were on average between ½-1 h. Since the DS computation times were significantly larger at 6 h 15 min per realization, the DS simulations were run on a 64 bit Windows server with 64 AMD Opteron processor 5376 at 2.3 GHz each, with a total of 128 GB RAM

and a SSD hard disk. The implementation of DS used in this paper is called DeeSse (Straubhaar 2011) and is easy to script and run in parallel on a server or computer cluster. The total time required for 51 simulations running in parallel was approximately

-	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic

32h, without enabling parallelization, which is available in DeeSse. One DS simulation took between 6-7 h. For more detailed information see Table 2 which summarizes the computation timetimes for the three MPS methods.

Table 2: A table presenting the average computation times per realization for each of the three MPS methods and the approximated605computation times needed for running 51 realizations with the setup used in this study. \*indicates that the given realizations were<br/>run in parallel on a server; other realizations were generated on a personal laptop.

	snesim	DS	iqsim	
Comp times pr realization	1/2 1 h	67h*	10.12 min	-
Comp. times pr. realization	/2-1 11	0-7 11	10-12 1111	
Approx. comp. times 51 realizations	38 h 15 min	32 h*	9 h 21 min	

Formatted: Font: Not Italic

# Formatted: Font: Not Italic Formatted Table

#### 4.1 Modified Hausdorff distance results

The full MHDThe D<sub>MH</sub> is computed for a binary case where the glacial clay and sand & gravel have been combined into one category. Therefore, the  $D_{MH}$  measures differences in the overall buried valley architecture. The full  $D_{MH}$  matrix is presented in Figure 9a and b. Using eq. (4) and (5) the MHDDMH is summarized in Table 3, without the usage of dimensional reduction 610 techniques. The method with the largest variability, *i.e.* least similar hydrostratigraphic realizations, is jqsim with a MHD<sub>var</sub>  $\underline{D_{MH,var}}$  of 1.79. The snesim and DS models show generally lower  $\underline{MHD_{pare}}\underline{D_{MH,var}}$  values of 0.48 and 0.78, respectively. This means that the jqsim results span the largest set of possible models-, when measuring on the binary classification in hemipelagic clay and not hemipelagic clay. The iqsim realizations also have the smallest average MHDD<sub>MH</sub> between the individual 615 realizations and the cognitive hydrostratigraphic model, with a <u>MHD<sub>eog</sub> D<sub>MH,cog</sub></u> of 2.65, meaning on average iqsim realizations resemble the cognitive hydrostratigraphic model the most-, when it comes to the location of the valleys. The snesim and DS MHDeegDMHcog are 3.01 and 2.80, respectively. On average, the DS realizations are more similar to the cognitive hydrostratigraphic model in comparison to the snesim realizations, while both are more dissimilar than the agim realizationsagain, when it comes to the location of the valleys. The two MPS methods which had the smallest distances, and therefore 620 were most similar, were snesim and DS with an inter  $\underline{\text{MHDD}_{MH}}$  distance of 1.05. The distance between DS and iqsim was larger, with a value of 2.19, while the largest inter MHDD<sub>MH</sub> distance was between snesim and jqsim with a MHDD<sub>MH</sub> value 2.37.

-	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
_	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
_	Formatted: Font: Not Italic
_	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
$\langle$	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
//	Formatted: Font: Not Italic
//	Formatted: Font: Not Italic
)	Formatted: Font: Not Italic

625 Table 3: Summary of the Modified Hausdorff Distance (MHDD\_MH) matrix portraying the MHDD\_MH results.  $MHD_{pugr}$  represents  $D_{MH,var}$  presents the variability of the given MPS method or between the different MPS methods, e.g. - the value in the  $MHD_{pugr}D_{MH,var}$  column and the *snesim*  $\rightarrow$  *DS* row represents the average distance between the snesim and DS realizations. The MHDcogD\_MH.cog is the average distance from the simulation results to the cognitive model.

	MHD <sub>var</sub> D <sub>MH,var</sub>	<u>MHD<sub>cog</sub>D<sub>MH,cog</sub></u>	4	(	Formatted Table
snesim	0.48	3.01		(	Formatted: Font: Not Italic
DS	0.78	2.80		(	Formatted: Font: Not Italic
iqsim	1.79	2.65			Formatted: Font: Not Italic
<i>snesim → DS</i> snesim	1.05				
$\rightarrow$ DS					Formatted: Font: Not Italic
<del>snesim</del>	2.37				
<i>→ iqsim</i> snesim					
→ iqsim					Formatted: Font: Not Italic



#### 630

Figure 9: The MHDD<sub>MH</sub> results presented without and with dimensional reduction. a) the full Modified Hausdorff Distance (MHDD<sub>MH</sub>) matrix showing the distances between individual realizations, and between individual realizations and the cognitive hydrostratigraphic model. The last column and row of the distance matrix of a) represent the distances between the realizations and the cognitive model. b) shows a scatter plot of these distances between the realizations and the cognitive model, revealing greater detail than can be seen with naked eye from the MHDD<sub>MH</sub> matrix itself. c) shows the 2D t-SNE plot of the MHDD<sub>MH</sub> matrix.

The *MHDD*<sub>MH</sub> can also be evaluated by applying the aforementioned t-SNE method. Here, each realization is visually represented as a point in 2D space. Similar values, with small <u>MHDD<sub>MH</sub></u> values, are closely spaced, while dissimilar values, with large <u>MHDD<sub>MH</sub></u> values, are separated from each other. Firstly, the t-SNE results show snesim and <u>DS</u> point clouds, which are closer to each other relative to the iqsim point cloud (Figure 9c). This means that they are similar in nature; as reflected in Table 3. The iqsim point cloud is isolated in the 2D space since the iqsim realizations are significantly different from the snesim and <u>DS</u> results. Furthermore, the iqsim point cloud is also the largest, which reflects the larger dissimilarity of the output realizations. On average, the iqsim point cloud is closer to the cognitive model, which is also reflected in Figure 9b and Table 3.

#### 4.2 Borehole validation results

645 The final comparison of the MPS methods regards the average Euclidean distance between the simulation results and the regularized binary hydrostratigraphic logs. The sorted average distances between each individual simulation and the boreholes are seen in Figure 10.

-	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
Ν	Formatted: Font: Not Italic
Ľ	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
	Formatted: Font: Not Italic



Figure 10: The borehole distance results are presented for each of the three MPS methods: snesim, DS, and iqsim; a) shows the snesim borehole distance results for the three hydrostratigraphic units, b) shows the DS borehole distance results for the three hydrostratigraphic units.

The average distance between the simulated hydrostratigraphic models and the boreholes are presented according to the three key hydrostratigraphic units. The average distance between *sand & gravel* units in the hydrostratigraphic realizations and *sand & gravel* units in the boreholes seems to be the largest for the modellingmodeling results of all three MPS methods (Figure 10), *i.e.* the red curve is always on top. The average values of the individual curves in Figure 10 are computed and presented in Table 4. An overall borehole distance average for each of the three MPS methods is computed as the average of each row in Table 4. The *sand & gravel* average in Table 4 reflects the large distances between resistive *sand & gravel* units in the realizations and the hydrostratigraphic logs. By comparing the individual frames of Figure 10 it is seen that the average value for the hydrostratigraphic models created using jqsim have a higher average distance. The jqsim averages for *sand & gravel* is centered on 5.8 m, while for snesim and DS it is centered on 3.8 m and 4.9 m, respectively. The jqsim average distance to *glacial clay* is centered on a relatively large value of 3.5 m, as opposed to 2.1 m and 2.8 m for snesim and DS, respectively. The *hemipelagic clay* units show a different pattern where jqsim has the lowest average distance of 0.2 m, while the *snesim* and DS distances are 1.6 m and 0.8 m, respectively. The snesim method has the smallest borehole distance row average of 2.5 m, while DS and iqsim have row averages of 2.8 m and 3.2 m, respectively.

665

	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
$\neg$	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
$\backslash$	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
$\langle \rangle$	Formatted: Font: Not Italic
	Formatted: Font: Not Italic

using the concept presented in section 3.6 "Distance to Boreholes". The presented distance values are the averages of the curve shown in Figure 10, one average for each of the individual hydrostratigraphic units for each of the presented methods: snesim, DS	3	For
and iqsim realizations. The last column shows the average distances for each of the three MPS methods.		

Table 4: The borehole distance results are summarized in this table. The borehole distances are the 3D Euclidean distances calculated

	sand & gravel	glacial clay	hemipelagic clay	<u>row average</u>	4	Formatted Table
	<i>[m]</i>	<i>[m]</i>	<i>[m]</i>	<u>[m]</u>		Inserted Cells
snesim	3.8	2.1	1.6	2.5		Formatted: Font: Not Italic
DS	4.9	2.8	0.8	2.8		Formatted: Font: Not Italic
iqsim	5.8	3.5	0.2	3.2		Formatted: Font: Not Italic

#### 4.3 Hydrostratigraphic modellingmodeling of new surveys

670

675

680

685

In areas of groundwater interest, the initial step is to collect different types of data relevant to the hydrologicalhydrogeological properties of the subsurface. Among these data are dense geophysical datasets, *e.g.* SkyTEM, which can be collected quickly and usually cover a significant part of the survey area. The different datasets are processed and modeled, and used in conjunction with the borehole lithology logs to create a single geological and/or hydrostratigraphic model. This model is only one version of the subsurface, encasing only part of the complexity related to the given hydrological system. We present **a** practicalan example of stochastic simulation of hydrostratigraphic models. The<u>end</u> result is<u>consists of</u> multiple hydrostratigraphic realizations, covering a larger span of possible models. Using the cognitive hydrostratigraphic model from area A as a TI, another hydrostratigraphic model from survey area B is simulated, using only the geophysical data in area B for spatial constraining. An important assumption is that the geological settings of area A and B are similar, since the hydrostratigraphic information is shared through the TI from area A. Furthermore, the hydrostratigraphic-resistivity relationships are statistically comparable.

The example presented in this study is synthesized from the Kasted dataset. The dataset is divided in two along the UTMX ecordinate 569025m (Figure 11a). The left half of the cognitive hydrostratigraphic model is then used as a TI to simulate the right half of the model. The reconstructed resistivity grid is also cut in half Figure 11b). The left half of the resistivity grid is used as an auxiliary variable describing the hydrostratigraphic resistivity relationship, as seen in Figure 4a, while the right half is used for spatially constraining the simulation. In this example 10 stochastic hydrostratigraphic realizations are created using DS-A single hydrostratigraphic realization is seen in Figure 11c, while the mode of the hydrostratigraphic model ensemble is seen in Figure 11d.



Formatted: Font: Not Italic



[690 Figure 11: An overview of the setup for simulating new survey areas and the hydrostratigraphic modellingmodeling results using the Kasted dataset. The presented horizontal slices are centered on 20 mbsl, and the vertical cross-section intersects at UTMY 6230150m. a) the cognitive hydrostratigraphic model is cut in half to simulate having two survey areas, one area with a cognitive hydrostratigraphic model (training image) available and the other without. The white area represents the new survey we wish to simulate. b) the horizontal slices and vertical cross-sections of the soft data used to simulate the new area. The left half is the auxiliary 695 variable, while the right half constrains the simulation of the new survey area. c) a single hydrostratigraphic realization. The left half is exactly the same as the cognitive model, see a), while the right half is simulated using <u>DS. d</u>) the mode of an ensemble of 10 hydrostratigraphic model realizations. Again, the left haft is the same as the training image and the right half shows the ensemble mode of 10 realizations.

The example presented in this study is synthesized from the Kasted dataset. The dataset is divided in two along the UTMX coordinate 569025m (Figure 11a). The left half of the cognitive hydrostratigraphic model is then used as a TI to simulate the right half of the model. The reconstructed resistivity grid is also cut in half Figure 11b). The left half of the resistivity grid is used as an auxiliary variable describing the hydrostratigraphic-resistivity relationship, as seen in Figure 4a, while the right half is used for spatially constraining the simulation. In this example 10 stochastic hydrostratigraphic realizations are created using DS. The DS method was selected since it is both easy to parameterize and to run in parallel on a computer cluster. A single

705 <u>hydrostratigraphic realization is seen in Figure 11c, while the mode of the hydrostratigraphic model ensemble is seen in Figure 11d. Using the same data from the Kasted survey area, the half-sim case is also presented using iqsim by Hoffimann *et al.* (2017).</u>

The simulation results show that one hydrostratigraphic realization represents the overall architecture of the resistivity grid; compare Figure 11Figure 11c and b. Comparing the single hydrostratigraphic realization (Figure 11Figure 11c) to the original cognitive model (Figure 11Figure 11a) reveals that one realization largely reflects the variability in the soft data grid. The mode of the model ensemble on the other hand (Figure 11d) has a closer resemblance to the cognitive hydrostratigraphic model; compare Figure 11a and d. This means that the individual realizations do on average resemble the original cognitive model. The end goal is not to create a set of hydrostratigraphic models, which match the cognitive hydrostratigraphic model. The goal is to create a suite of realistic hydrostratigraphic models.

715 Generally, unrealistic short scale variability is introduced in both the single hydrostratigraphic realization as well as in the ensemble mode model, but is generally not present in either the TI or the resistivity grid. These short-scale variation patterns are artifacts from the DS method itself and can be removed by using post-processing tools (Pyrcz and Deutsch 2014). Such tools are generally run on the realizations to remove artifacts that were introduced due to the algorithms. Since post-processing is a separate step, it was not used for any of the simulations in this study, making all the simulation results comparable to each other.

#### 5 Discussion

implementation of the algorithms.

The snesim setup is different from the DS and iqsim setups. The snesim setup differs in the usage of the probability framework, and in the choice of the implicit Resistivity Atlas histograms (Barfod et al. 2016). The implicit histograms (Figure 4d) are used to directly translate the resistivity grids into probability grids. This illustrates the utility of the Resistivity Atlas framework in relation to geostatistical modellingmodeling. The DS and iqsim frameworks would normally, in real-world cases, require the usage of a G\* operator since no auxiliary variable exists which geographically overlaps with a conceptual TI. As explained in section *3.1.2 Direct sampling simulation - DS*, applying a realistic G\* operator requires several steps and can be a complicated affair. In this study, however, the TI was an actual cognitive geological model of Kasted study area, meaning a resistivity grid which geographically overlaps with the TI exists. Using the SkyTEM resistivity grid as an auxiliary variable resulted in the application of different resistivity-hydrostratigraphic relationships in the *DS* and iqsim approach – compare the explicit histograms used in *DS* and iqsim, Figure 4a, with the implicit Resistivity Atlas histograms used in snesim, Figure 4d, or see Table 1. Even though there are some differences in the setups of the different *MPS* algorithms, the snesim and DS realizations are still similar in nature; compare Figure 8b and c. The differences mentioned here are mainly due to the differences of the

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Tab stops: 0,5 cm, Left

 Formatted: Font: Not Italic

 Formatted: Font: Not Italic

-	Formatted: Font: Not Italic
-{	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
Υ	Formatted: Font: Not Italic

- 735 The snesim and DS realizations portray some differences, which are related to the choice of the implicit Resistivity Atlas histograms for translating the resistivity grid. This can help us understand some of the basic differences in the information provided by the implicit Resistivity Atlas histograms and the explicit auxiliary variable. In DS probable hydrostratigraphic units are not conditioned properly. An example of this is the aforementioned West-Northwest - East-Southeast trending glacial clay valley (see Figure 8a), which is uninterrupted in 78% of the DS realizations. The same valley is clearly represented in the
- 740 resistivity grid (Figure 5a) and in the cognitive model (Figure 8a). However, the explicit auxiliary variable histograms show increased overlapping resistivity values for the glacial clay and sand & gravel histograms (Figure 4a,d). The auxiliary variable histograms (Figure 4a) reveals approximately equal probability of glacial clay and sand & gravel resistivities lying close to 40-45 Ωm. The histogram also shows that hemipelagic clay has a resistive tail, resulting in a small probability for hemipelagic clay in the areas of intermediate resistivity values of 10-50 Ωm. The Resistivity Atlas histograms (Figure 4d), on the other
- 745 hand, favor the glacial clay in the 40-45 Ωm range, with a 0% probability for *hemipelagic clay*. The snesim realizations show an uninterrupted glacial clay valley in ~90% of the realizations in the horizontal cross-section centered on 20 mbsl. The probability grid for snesim reveals a ~75% probability for glacial clay at the location of the West-Northwest East-Southeast trending glacial clay valley at 20 mbsl (Figure 5c). At 20 mbsl the sand & gravel probability ~15-20% while *hemipelagic clay* has a low probability of ~0-5% (Figure 5b,d). The underlying hydrostratigraphic-petrophysical relationship which holds
- 750 information on how to condition the simulations to the soft data, is important to the <u>MPS</u> modeling results, especially when extensive and spatially dense geophysical datasets are available. The presented practical example, showing the simulation of a new survey, has the two aforementioned requirements: 1) the geological environments of the two areas need to be similar and 2) the statistical hydrostratigraphic-petrophysical relations also need to be similar. Since the Resistivity Atlas histograms are created using only local data, *i.e.* boreholes and SkyTEM resistivity models, they represent the local relationship. Since stationarity in the hydrostratigraphic-petrophysical relations is not guaranteed (Barfod et al. 2016), it is necessary to check for
- stationarity, which is possible within the Resistivity Atlas framework. Here, histograms can be created for each area and compared. If statistically similar, stationarity can be inferred for the hydrostratigraphic-petrophysical relations.
- The MHDD<sub>MH</sub> results revealed some interesting trends between the MPS realizations. The MHD<sub>ear</sub> D<sub>MH,var</sub> for snesim, DS
  and iqsim were 0.48, 0.78, and 1.79, respectively. The low snesim MHD<sub>ears</sub> D<sub>MH,var</sub> is related to the soft data conditioning, which is dependent on the choice of histograms for translating the resistivity grids into probability grids. For this translation, as mentioned, the implicit Resistivity Atlas histograms were used. Overall, the implicit histograms show a larger separation between the *glacial clay* and *sand & gravelhemipelagic clay* histograms compared to the explicit histograms; compare Figure 4a and d. This results in less ambiguity in the transition from *glacial clay* to *sand & gravelhemipelagic clay* in the probability grids, yielding a smaller subset of possible models. This also results in snesim realizations, which closely resemble the soft data variable, compared to DS and iqsim. The borehole distance results are also influenced by choosing the implicit histograms. Generally, the snesim realizations show the smallest borehole distances with respect to *glacial clay* and *sand & gravel* units, while the corresponding *hemipelagic clay* distances are the largest. The increased separation of the *glacial clay* and *sand & gravel*.
  770 units, while *hemipelagic clay* seems to be underestimated.

It can be concluded thatIn conclusion snesim and DS yield similar realizations, portrayed by the relatively small MHDD<sub>MH</sub> values between snesim and DS. This is reflected in the t-SNE plot (Figure 9c), where the jqsim point cloud is isolated from the snesim and DS point clouds, and is closer to the cognitive model. The isolation of the jqsim point cloud agrees with a lack of short scale variabilityiqsim being imprecise in its simulation of the *iqsim* realizationsyalley architecture compared to snesim and DS. However, the abundance of *hemipelagic clay* close to terrain is clear and undesired in iqsim realizations; see the vertical cross-sections of the models (Figure 8). Evidence of abundant near surface *hemipelagic clay* is also found indirectly

775

Formatted: Font: Not Italic	
Formatted: Font: Not Italic	
Formatted: Font: Not Italic	

Formatted:	Font:	Not	Italic

formatted: Font: Not Italic
-----------------------------

Formatted: Font: Not Italic

-{	Formatted: Font: Not Italic
-(	Formatted: Font: Not Italic
$\neg$	Formatted: Font: Not Italic
Y	Formatted: Font: Not Italic

	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
_	Formatted: Font: Not Italic
_	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
-	Formatted: Font: Not Italic
_	Formatted: Font: Not Italic
$\neg$	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
$\square$	Formatted: Font: Not Italic
	Formatted: Font: Not Italic
	Formatted: Font: Not Italic

in the borehole distance results. The borehole distances of the jqsim realizations revealed exceedingly small *hemipelagic clay* distances, with an average of 0.2m. In comparison, snesim and DS had *hemipelagic clay* borehole distance averages of 0.8m and 1.6m, respectively. This shows that jqsim produces realizations where *hemipelagic clay* units are, on average, closer to the

- borehole hydrostratigraphic logs. However, it is important to also notice the relatively large iqsim borehole distances for glacial clay and sand & gravel units. This indicates that the ample near surface hemipelagic clay, decreases the hemipelagic clay borehole distances, while increasing increase the glacial clay and sand & gravel borehole distances (Figure 10) (Table 4). Here, it is important to understand the trade-off relationship between the different hydrostratigraphic categories. As more hemipelagic clay is introduced at the surface of the iqsim realizations, it does not increase the average borehole distance for
- 785 hemipelagic clay, since the algorithm only measures the distance from the borehole cell to the nearest cell in a realization with the same hydrostratigraphic category. Instead, the *sand & gravel* and *glacial clay* distances increase, since the realizations no longer match with the borehole lithology logs, which only reveal the presence of *sand & gravel* and *glacial clay* close to the surface. The trade-off relationship is also evident from the row averages presented in Table 4. It is clear that even though iqsim has a low *hemipelagic clay* borehole distance of 0.2 m, the row average is still the largest with a value of 3.2 m, while Table 4 reports corresponding snesim and DS row averages of 2.5 m and 2.8 m, respectively.

Unrealistic shortShort scale variability is found throughoutpresent in the snesim and DS realizations. This iscan be seen as an artifact introduced by the algorithms themselves, and do not reflect the underlying datasets, *i.e.* the soft data or TI. As Linde *et al.* (2015) discuss, fine-scale patterns are present in the real-world hydrostratigraphic subsurface, but are not presentonly slightly resolved in geophysical models. Two of the three presented stochastic MPS methods introduce fine-scale variations in

- 795 the form of short scale variability to the overall hydrostratigraphic architecture, with the overall architecture resembling the underlying datasets. This adds complexity to the realizations and the resulting equiprobable hydrostratigraphic models span a larger subset of possible models. The question, however, is whether this short-scale variability is similar to the real-world short-scale variability missing from our geophysical data, which is difficult to answer. The importance of short-scale variability also depends on the type of prediction for which the hydrostratigraphic model is to be used.
- 800 An important difference in the iqsim realizations, compared to snesim and DS, is the lack of fine-scale variability. The MHD and the resulting valley architecture. The D<sub>MH</sub> results reveal that the iqsim realizations were the most similar to the cognitive model, and that they were different from the snesim and DS realizations. It can be concluded that since The iqsim realizations do not contain fine scale have a high D<sub>MH,var</sub> of 1.79, which means that each realization is significantly different from one another, which indicates a large variability, in the MHD<sub>coa</sub> is smaller realizations. However, the overall placement of the
- 805 <u>valleys agrees with the cognitive model, which results in a small D<sub>MH,cog</sub> and the most significant <u>valley</u> features of the cognitive model are reproduced. <u>It is notedNote</u> that the <u>MHDs areD<sub>MH</sub> is</u> not sensitive towards the hydrostratigraphically unrealistic placement of *hemipelagic clay* at the surface in the iqsim realizations. The presented <u>MHDD<sub>MH</sub></u> results reveal that iqsim performs "best", according to the definition of "best" introduced in section "3.5 The modified Hausdorff Distance a measure for similarity". The TI statistics are <u>better</u> reproduced<u>-better</u> and the space of uncertainty is large. However, the jqsim realizations do not reflect all complexities of the underlying datasets, which is also reflected by the poorer borehole distance</u>
- results for glacial clay and sand & gravel units.

In relation to the new survey example, it is worth mentioning a caveat. When cutting the TI in half the 3D objects are reduced in size and some of the 3D objects are entirely removed. Generally the TI should contain the objects which are to be conditioned during simulation (e.g. Emery & Lantuéjoul 2014; Journel & Zhang 2007; Strebelle 2002). If the 3D objects are not fully represented in the TI it cannot be guaranteed that they will be reproduced in the resulting realizations (Emery & Lantuéjoul 2014). It is therefore important to state that the example simply just exemplifies an important application of MPS in relation

to dense geophysical datasets, but is not a valid practical application.

815

Formatted: Font: Not Italic
Formatted: Font: Not Italic

Formatted: Font: Not Italic
Formatted: Font: Not Italic

-	Formatted: Font: Not Italic	ļ
4	Formatted: Font: Not Italic	J
_	Formatted: Font: Not Italic	ì

The snesim and DS realizations portray some differences, which are related to the choice of the implicit Resistivity Atlas histograms for translating the resistivity grid. This can help us understand some of the basic differences in the information

- 820 provided by the implicit Resistivity Atlas histograms and the explicit auxiliary variable. In DS probable hydrostratigraphie units are not conditioned properly. An example of this is the aforementioned West Northwest – East Southeast trending *glacial elay* valley (see Figure 8a), which is uninterrupted in 78% of the DS realizations. The same valley is clearly represented in the resistivity grid (Figure 5a) and in the cognitive model (Figure 8a). However, the explicit auxiliary variable histograms show increased overlapping resistivity values for the *elacial clay* and *sand & eravel* histograms (Figure 4a,d). The auxiliary variable
- 825 histograms (Figure 4a) reveals approximately equal probability of glacial elay and sand & gravel resistivities lying close to 40-45 Ωm. The histogram also shows that hemipelagic clay has a resistive tail, resulting in a small probability for hemipelagic elay in the areas of intermediate resistivity values of 10-50 Ωm. The Resistivity Atlas histograms (Figure 4d), on the other hand, favor the glacial elay in the 40-45 Ωm range, with a 0% probability for hemipelagic clay. The gnesim realizations show an uninterrupted glacial clay valley in ~90% of the realizations in the horizontal cross section centered on 20 mbsl. The
- 830 probability grid for snesim reveals a --75% probability for *glacial clay* at the location of the West-Northwest East-Southeast trending *glacial clay* valley at 20 mbsl (Figure 5c). At 20 mbsl the *sand & gravel* probability --15-20% while *hemipelagic clay* has a low probability of --0-5% (Figure 5b,d). The underlying hydrostratigraphic-petrophysical relationship which holds information on how to condition the simulations to the soft data, is important to the MPS-modelling results, especially when extensive and spatially dense geophysical datasets are available.
- 835 The presented practical example, showing the simulation of a new survey, has the two aforementioned requirements: 1) the geological environments of the two areas need to be similar and 2) the statistical hydrostratigraphic petrophysical relations also need to be similar. Since the Resistivity Atlas histograms are created using only local data, *i.e.* boreholes and SkyTEM resistivity models, they represent the local relationship. Since stationarity in the hydrostratigraphic petrophysical relations is not guaranteed (Barfod et al. 2016), it is necessary to check for stationarity, which is possible within the Resistivity Atlas Framework. Here, histograms can be created for each area and compared. If statistically similar, stationarity can be inferred for the hydrostratigraphic-petrophysical relations.

The hydrogeophysical dataset is processed and modeled for the purpose of creating a petrophysical model. The practical example has the advantage of an explicit implementation of hydrostratigraphic resistivity relationship by using the resistivity grid as an auxiliary variable. The relationship is indirectly modeled during the cognitive modelling process. During modeling the geoscientist makes qualitative decisions regarding the relations between geophysical and borehole data. Experienced geoscientists have a general understanding of how geophysical data reflect the geological features. That knowledge is used to create geologically realistic hydrostratigraphic models, resembling both the geophysical and the sparse borehole data. The

explicit hydrostratigraphic and petrophysical grids; as presented in Figure 4a.

#### 850 6 Conclusion

The three MPS methods snesim, DS and jqsim are used for stochastic hydrostratigraphic modellingmodeling. The modellingmodeling results are compared in an elaborate framework of comparing the modellingmodeling results visually, mathematically and against boreholes. Each individual MPS method has its own set of advantages/disadvantages which are covered in this study. Overall the *DS* method had the highest computation times. An average <u>DS</u> realization taketakes 6-7 h, while for snesim the number isit takes 2-3 h and for jqsim the number is-10-12 min. We emphasize that these times are for a specific setup, and that they will likely change for different configurations. Both the snesim and DS methods yield realizations

Formatted: Font: Not Italic
Formatted: Font: Not Italic
Formatted: Font: Not Italic

-{	Field Code Changed
1	Formatted: Font: Not Italic
1	Field Code Changed
Y	Field Code Changed
Y	Field Code Changed
1	Field Code Changed
-(	Field Code Changed
-	Formatted: Font: Not Italic

-{	Formatted: Font: Not Italic
-{	Field Code Changed
-{	Field Code Changed
-1	Formatted: Font: Not Italic

-{	Formatted: Font: Not Italic
$\mathbb{T}$	Formatted: Font: Not Italic
Υ	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic
-1	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic
1	Formatted: Font: Not Italic
Y	Formatted: Font: Not Italic

with sufficient soft data conditioning, as reflected byin the low MHD variability of 0.48 and 0.78, respectively. modelling

<u>results in Figure 8a-c</u>. The josim realizations showed a <u>MHD variability of 1.79erratic results in regards to the overall valley</u> <u>architecture, compare</u> Figure 8a,d, which was due to insufficient soft data conditioning.

- 860 The presented practical example for modellingmodeling new survey areas uses a cognitive hydrostratigraphic model from one area as a TI to simulate the new area without a pre-existing cognitive model. The requirements are two-fold: 1) the geological settings of the two areas need to be similar and 2) the statistical hydrostratigraphic-petrophysical relationship needs to be stationary between the two areas. The presented example shows a case where the two requirements are true, and the set of stochastic models are consistent with the cognitive geological model.
- 865 Finally, the importance of the underlying resistivity-hydrostratigraphic relationship has been shown. The relationship contains information on the translation of the continuous soft data variable into subsurface hydrostratigraphic units, and is indirectly used for soft data conditioning. The MPS modellingmodeling results are therefore sensitive towards the resistivityhydrostratigraphic relationship, and the more information acquired regarding the relationship, the better the realizations.
- 870 Acknowledgements. IWe would like to thank Jan Gunninkthe two anonymous referees for introducing me to the world of geostatistics, and for sparkingtheir contributions towards improving the interest that led to further research into Multiple-Point Statisticsenclosed in this paper. This study is supported by HyGEM, Integrating geophysics, geology, and hydrology for improved groundwater and environmental management, project no. 11- 116763. The funding for HyGEM is provided by The Danish Council for Strategic Research.

#### 875 References

Arpat, G. B. and Caers, J.: A multiple-scale, pattern-based approach to sequential simulation, in: Geostatistics Banff 2004, Springer, 255-264, 2005.

 Auken, E., Christiansen, A. V., Westergaard, J. H., Kirkegaard, C., Foged, N. and Viezzoli, A.: An integrated processing scheme for high-resolution airborne electromagnetic surveys, the SkyTEM system, Exploration Geophysics, 40, 184-192, 2009.

Barfod, A. A., Møller, I. and Christiansen, A. V.: Compiling a national resistivity atlas of Denmark based on airborne and ground-based transient electromagnetic data, J. Appl. Geophys., 2016.

Beamish, D.: The bedrock electrical conductivity map of the UK, J. Appl. Geophys., 96, 87-97, 2013.

Caers, J.: Direct sequential indicator simulation, Geostats, 39-48, 2000.

885 Carle, S. F.: T-PROGS: Transition probability geostatistical software, University of California, Davis, CA, 1999.

Delbari, M., Afrasiab, P. and Loiskandl, W.: Using sequential Gaussian simulation to assess the field-scale spatial uncertainty of soil water content, Catena, 79, 163-169, 2009.

Destombes, J., Shephard-Thorn, E. and Redding, J.: A buried valley system in the Strait of Dover, Philosophical Transactions of the Royal Society of London A: Mathematical, Physical and Engineering Sciences, 279, 243-253, 1975.

890 Deutsch, C. V. and Journel, A.: Geostatistical software library and user's guide, Oxford University Press, New York, 1998.

Dubuisson, M. and Jain, A. K.: A modified Hausdorff distance for object matching, in: Pattern Recognition, 1994. Vol. 1-Conference A: Computer Vision & Image Processing., Proceedings of the 12th IAPR International Conference on, 1994.

Efros, A. A. and Freeman, W. T.: Image quilting for texture synthesis and transfer, in: Proceedings of the 28th annual conference on Computer graphics and interactive techniques, 2001.

- 895 Feyen, L. and Caers, J.: Quantifying geological uncertainty for flow and transport modeling in multi-modal heterogeneous formations, Adv. Water Resour., 29, 912-929, 2006.
- Fleckenstein, J. H., Niswonger, R. G. and Fogg, G. E.: Riveraquifer<u>River-aquifer</u> interactions, geologic heterogeneity, and low-flow management, Ground Water, 44, 837-852, 2006.
- Foged, N., Auken, E., Christiansen, A. V. and Sørensen, K. I.: Test-site calibration and validation of airborne and groundbased TEM systems, Geophysics, 78, E95-E106, 2013.

Fogg, G. E., Noyes, C. D. and Carle, S. F.: Geologically based model of heterogeneous hydraulic conductivity in an alluvial setting, Hydrogeol. J., 6, 131-143, 1998.

Freeze, R. A.: A stochastic-conceptual analysis of one-dimensional groundwater flow in nonuniform homogeneous media, Water Resour. Res., 11, 725-741, 1975.

905 Gelhar, L. W.: Stochastic analysis of flow in heterogeneous porous media, in: Fundamentals of transport phenomena in porous media, Springer, 673-717, 1984.

Goovaerts, P.: Geostatistics for natural resources evaluation, Oxford University Press on Demand, 1997.

Guardiano, F. B. and Srivastava, R. M.: Multivariate geostatistics: beyond bivariate moments, in: Geostatistics Troia'92, Springer, 133-144, 1993.

- 910 Hansen, M. and Pjetursson, B.: Free, online Danish shallow geological data, Geological Survey of Denmark and Greenland Bulletin, 23, 53-56, 2011.
- He, X., Koch, J., Sonnenborg, T. O., Jørgensen, F., Schamper, C. and Christian Refsgaard, J.: Transition probabilitybasedprobability-based stochastic geological modeling using airborne geophysical data and borehole data, Water Resour. Res., 50, 3147-3169, 2014.
- 915 Hermans, T., Nguyen, F. and Caers, J.: Uncertainty in Training-Image Based Inversion of Hydraulic Head Data Constrained to ERT Data: Workflow and Case Study, in: AGU Fall Meeting 2014, 2014.

Hinton, G. and Roweis, S.: Stochastic neighbor embedding, in: NIPS, 2002.

Hoffimann, J., Scheidt, C., Barfod, A. A. and Caers, J.: Stochastic Simulation by Image Quilting of Deterministic Processbased Geological Models [submitted], Computers & Geosciences, 2017.

920 Høyer, A. S., Jørgensen, F., Sandersen, P. B. E., Viezzoli, A. and Møller, I.: 3D geological modelling of a complex buriedvalley network delineated from borehole and AEM data, J. Appl. Geophys., 122, 94-102, 2015a.

Høyer, A. S., Jørgensen, F., Foged, N., He, X. and Christiansen, A. V.: Three-dimensional geological modelling of AEM resistivity data—A comparison of three methods, J. Appl. Geophys., 115, 65-78, 2015b.

Høyer, A. S., Vignoli, G., Hansen, T. M., Keefer, D. A. and Jørgensen, F.: Multiple-point statistical simulation for
 hydrogeological models: 3D training image development and conditioning strategies, Hydrology and Earth System Sciences Discussions, 2016.

Hu, L. and Chugunova, T.: Multiple-point geostatistics for modeling subsurface heterogeneity: A comprehensive review, Water Resour. Res., 44, 2008.

Huysmans, M. and Dassargues, A.: Application of multiple-point geostatistics on modelling groundwater flow and transport 930 in a cross-bedded aquifer (Belgium), Hydrogeol. J., 17, 1901, 2009.

Isaaks, E. H. and Srivastava, R. M.: Applied geostatistics, 1989.

Jørgensen, F., Høyer, A. S., Sandersen, P. B., He, X. and Foged, N.: Combining 3D geological modelling techniques to address variations in geology, data type and density–An example from Southern Denmark, Comput. Geosci., 81, 53-63, 2015.

935 Jørgensen, F., Møller, R. R., Nebel, L., Jensen, N., Christiansen, A. V. and Sandersen, P. B.: A method for cognitive 3D geological voxel modelling of AEM data, Bull. Eng. Geol. Env., 72, 421-432, 10.1007/s10064-013-0487-2, 2013.

Jørgensen, F. and Sandersen, P. B.: Buried valley mapping in Denmark: evaluating mapping method constraints and the importance of data density [Kartierung eiszeitlicher Rinnen in Dänemark: Bewertung methodischer Grenzen und Bedeutung der Datendichte], Zeitschrift der Deutschen Gesellschaft für Geowissenschaften, 160, 211-223, 2009.

940 Jørgensen, F. and Sandersen, P. B.: Buried and open tunnel valleys in Denmark—erosion beneath multiple ice sheets, Quaternary Science Reviews, 25, 1339-1363, 10.1016/j.quascirev.2005.11.006, 2006.

Journel, A.: Combining knowledge from diverse sources: An alternative to traditional data independence hypotheses, Math. Geol., 34, 573-596, 2002.

Journel, A. G.: Nonparametric estimation of spatial distributions, Journal of the International Association for Mathematical 945 Geology, 15, 445-468, 1983.

Journel, A. G.: Geostatistics: roadblocks and challenges, in: Geostatistics Troia'92, Springer, 213-224, 1993.

Journel, A. and Zhang, T.: The necessity of a multiple-point prior model, Math. Geol., 38, 591-610, 2006.

Juang, K., Chen, Y. and Lee, D.: Using sequential indicator simulation to assess the uncertainty of delineating heavy-metal contaminated soils, Environmental Pollution, 127, 229-238, 2004.

950 Kehew, A. E., Piotrowski, J. A. and Jørgensen, F.: Tunnel valleys: Concepts and controversies—A review, Earth-Sci. Rev., 113, 33-58, 2012.

Kessler, T. C., Comunian, A., Oriani, F., Renard, P., Nilsson, B., Klint, K. E. and Bjerg, P. L.: Modeling Fine-Scale Geological Heterogeneity—Examples of Sand Lenses in Tills, Groundwater, 51, 692-705, 2013.

Klingbeil, R., Kleineidam, S., Asprion, U., Aigner, T. and Teutsch, G.: Relating lithofacies to hydrofacies: outcrop-based hydrogeological characterisation of Quaternary gravel deposits, Sediment. Geol., 129, 299-310, 1999.

LaBolle, E. M. and Fogg, G. E.: Role of molecular diffusion in contaminant migration and recovery in an alluvial aquifer system, in: Dispersion in Heterogeneous Geological Formations, Springer, 155-179, 2001.

Linde, N., Renard, P., Mukerji, T. and Caers, J.: Geological realism in hydrogeological and geophysical inverse modeling: A review, Adv. Water Resour., 86, 86-101, 2015.

960 Liu, Y.: Using the Snesim program for multiple-point statistical simulation, Comput. Geosci., 32, 1544-1563, 2006.

Maaten, L. v. d. and Hinton, G.: Visualizing data using t-SNE, Journal of Machine Learning Research, 9, 2579-2605, 2008.

Maharaja, A.: Stochastic Modeling of the Rhine-Meuse Delta using Mutiple-point Geostatistics, in: Geostatistics Banff 2004, Springer, 653-659, 2005.

Mahmud, K., Mariethoz, G., Caers, J., Tahmasebi, P. and Baker, A.: Simulation of Earth textures by conditional image 965 quilting, Water Resour. Res., 50, 3088-3107, 2014.

Mariethoz, G. and Caers, J.: Multiple-point geostatistics: stochastic modeling with training images, John Wiley & Sons, 2014a.

Mariethoz, G. and Caers, J.: Training Image construction, in: Multiple-point geostatistics: stochastic modeling with training images, First Edition, Mariethoz, G. and Caers, J. (Eds.), John Wiley & Sons, 221, 2014b.

970 Mariethoz, G. and Renard, P.: Reconstruction of incomplete data sets or images using direct sampling, Mathematical Geosciences, 42, 245-268, 2010.

Mariethoz, G., Renard, P. and Straubhaar, J.: The Direct Sampling method to perform multiple-point geostatistical simulations, Water Resour. Res., 46, 2010.

Mariethoz, G., Straubhaar, J., Renard, P., Chugunova, T. and Biver, P.: Constraining distance-based multipoint simulations to proportions and trends, Environmental Modelling & Software, 72, 184-197, 2015.

Meerschman, E., Van Meirvenne, M., Van De Vijver, E., De Smedt, P., Islam, M. M. and Saey, T.: Mapping complex soil patterns with multiple-point geostatistics, Eur. J. Soil Sci., 64, 183-191, 2013.

Michaelides, K. and Chappell, A.: Connectivity as a concept for characterising hydrological behaviour, Hydrol. Process., 23, 517-522, 2009.

980 Møller, I., Søndergaard, V., Jørgensen, F., Auken, E. and Christiansen, A. V.: Integrated management and utilization of hydrogeophysical data on a national scale, Near Surface Geophysics, 7, 647-659, 10.3997/1873-0604.2009031, 2009.

Okabe, H. and Blunt, M. J.: Pore space reconstruction using multiple-point statistics, Journal of Petroleum Science and Engineering, 46, 121-137, 2005.

Pyrcz, M. J. and Deutsch, C. V.: Geostatistical reservoir modeling, Oxford university press, 2014.

985 Ritzi, R. W., Jayne, D. F., Zahradnik, A. J., Field, A. A. and Fogg, G. E.: Geostatistical Modeling of Heterogeneity in Glaciofluvial, Buried-Valley Aquifers, Ground Water, 32, 666-674, 1994.

Roberts, E. S.: Programming abstractions in C: A second course in computer science, Addison-Wesley, 819, 1998.

Royse, K. R.: Combining numerical and cognitive 3D modelling approaches in order to determine the structure of the Chalk in the London Basin, Comput. Geosci., 36, 500-511, 2010.

900 Sánchez-Vila, X., Carrera, J. and Girardi, J. P.: Scale effects in transmissivity, Journal of Hydrology, 183, 1-22, 1996.

Seifert, D. and Jensen, J.: Using sequential indicator simulation as a tool in reservoir description: Issues and uncertainties, Math. Geol., 31, 527-550, 1999.

Seifert, D., Sonnenborg, T. O., Scharling, P. and Hinsby, K.: Use of alternative conceptual models to assess the impact of a buried valley on groundwater vulnerability, Hydrogeol. J., 16, 659-674, 2008.

995 Senthilkumaran, N. and Rajesh, R.: Edge detection techniques for image segmentation-a survey of soft computing approaches, International journal of recent trends in engineering, 1, 2009.

Sørensen, K. I. and Auken, E.: SkyTEM-a new high-resolution helicopter transient electromagnetic system, Exploration Geophysics, 35, 194-202, 10.1071/EG04194, 2004.

Straubhaar, J.: MPDS technical reference guide, Centre d'hydrogeologie et geothermie, University of Neuchâtel, Neuchâtel, 2011.

Strebelle, S.: Conditional simulation of complex geological structures using multiple-point statistics, Math. Geol., 34, 1-21, 2002.

Strebelle, S. B. and Journel, A. G.: Reservoir modeling using multiple-point statistics, in: SPE Annual Technical Conference and Exhibition, 2001.

1005 Strébelle, S. and Journel, A.: Sequential simulation drawing structures from training images, 2000.

Strebelle, S., Payrazyan, K. and Caers, J.: Modeling of a deepwater turbidite reservoir conditional to seismic data using multiple-point geostatistics, in: SPE Annual Technical Conference and Exhibition, 2002.

Tan, X., Tahmasebi, P. and Caers, J.: Comparing training-image based algorithms using an analysis of distance, Mathematical Geosciences, 46, 149-169, 2014.

1010 Thomsen, R., Søndergaard, V. and Sørensen, K.: Hydrogeological mapping as a basis for establishing site-specific groundwater protection zones in Denmark, Hydrogeol. J., 12, 550-562, 2004. Tran, T. T.: Improving variogram reproduction on dense simulation grids, Comput. Geosci., 20, 1161-1168, 1994.

Viezzoli, A., Christiansen, A. V., Auken, E. and Sørensen, K.: Quasi-3D modeling of airborne TEM data by spatially constrained inversion, Geophysics, 73, F105-F113, 10.1190/1.2895521, 2008.

1015 Zhao, Z. and Illman, W. A.: On the importance of geological data for three-dimensional steady-state hydraulic tomography analysis at a highly heterogeneous aquifer-aquitard system, Journal of Hydrology, 544, 640-657, 2017.

Zheng, C. and Gorelick, S. M.: Analysis of solute transport in flow fields influenced by preferential flowpaths at the decimeter scale, Ground Water, 41, 142-155, 2003.