HESS-2017-537

How downstream sub-basins depend on upstream inflows to avoid scarcity: typology and global analysis of transboundary rivers

Responses to Editor's comments to the Author:

In general I agree with the way in which the authors have addressed the comments by the two reviewers and the editor. The result is that large parts of the text have been modified, and that the argument has been made more straightforward, yet the essence of the original paper has remained. In my view the paper is nearly ready for acceptance. However, I have still the following concerns that need to be addressed:

Response:

We sincerely thank the editor for his valuable comments and feedback. Below we present the point-by-point responses to the editor's specific concerns.

Comment 1: I do not find the new names of the concepts of "unbroken dependency" (was "intervened") and "broken dependency" (was "continuous") felicitous, and even counter intuitive. (Isn't a broken dependency a dependency that has been broken, i.e. a dependency that no longer exist? So for me an utterly confusing combination of words). So I urge the authors to find a more straightforward nomenclature. When reading the revised document, I came up with "hidden" and "open" dependency. In fact the manuscript frequently equates unbroken dependency with hidden dependency in the text (6 times, on pages 2, 3, 9, 13 (2x) and 14), apparently because "hidden" clearly conveys its meaning.

Response 1:

Thank you for the suggestion. We agree with the assessment that a downstream sub-basin is still dependent on upstream in the "broken dependency" case, even though they now experience scarcity: the upstream sub basin could alleviate downstream water scarcity by reducing their water use. The term "broken" is indeed inappropriate in that case, and we have adopted the terms "hidden" and "open" throughout the manuscript.

Table 1 has also been edited to emphasis that "open dependency" contrasts with "hidden dependency". The new definition of 'No dependency' reads:

"Upstream inflows do not influence whether or not a region experiences scarcity, i.e. if a region experiences scarcity or not with only local runoff, additional water from upstream does not change this situation, nor do the upstream water withdrawals. Note that the severity of scarcity may still be affected by upstream inflows and water withdrawals."

The new definition of 'hidden dependency' reads:

"Scarcity category is altered by upstream inflows but not by upstream water withdrawals, i.e. Local runoff is not enough to meet the local demand but additional water from upstream means the region experiences no scarcity instead of scarcity. Upstream withdrawals are small enough not to change the scarcity status."

The new definition of 'open dependency' reads:

"Scarcity category is altered after accounting for upstream water withdrawals, i.e. while upstream inflows in the hidden dependency allowed the region to avoid scarcity, upstream withdrawals now mean that the SBA does experience scarcity and more intense water management regimes are needed downstream."

Comment 2: The definitions of dependency must be formalised and unambiguously defined (Table 1 does not provide definitions, merely descriptions). I propose something as follows (using the definitions of discharge runoff as in Table 1; but please check whether my rendering is correct):

No dependency: local demand < local runoff OR local demand > actual discharge Dependency: local runoff < local demand < actual discharge Unbroken (hidden) dependency: local demand < actual discharge Broken (open) dependency: local demand < natural discharge

Response 2:

We agree it is useful to add formal definitions in Table 1, to complement visual definitions in Figure 4 in terms of avoidance of scarcity and Figure 5 in terms of water availability thresholds. The correct definitions are:

No dependency: local demand \leq local runoff OR local demand \geq natural discharge Dependency: local runoff < local demand < natural discharge Hidden dependency: local runoff < local demand \leq actual discharge Open dependency: actual discharge < local demand < natural discharge

They have been added to table 1, Page 3 L100.

These definitions are, however, derived from our analysis rather than being pre-determined. We have therefore modified the caption of *Table 1* to say-

"Note: definitions in terms of water availability volumes emerge from our analysis, as described in Section 2 & summarised visually in Figure 4. Our analysis method did not consider the case where actual discharge may be greater than natural discharge." (Page 3, L98)

Comment 3: Section 2.2.1 describes the method of expressing water availability, but it only deals with the spatial dimension. The temporal dimension is entirely missing. So the reader can only guess what temporal resolution is used. This must be included.

Related to this, I would add a sentence on page 7 lines 210-211, namely that these annual values may mask water scarcity during the dry season(s)

Response 3:

Thank you for the suggestion. We have now added the temporal dimension in sec. 2.2.1, Page 6, L175-

"Three types of average annual water availability (for 1981-2010) were calculated in each of these SBAs, corresponding to local water (local runoff), total inflows including upstream areas (natural discharge), and total inflows after upstream WWs (actual discharge) (see detailed definitions in Table 1)."

And also in L180-

"WW for each SBA was calculated separately (referred to as WW.local) by summing up the three water use sectors (industrial, domestic and agriculture) for the year 2010 and aggregating to SBA scale."

We also added the suggested line by the Editor in section 2.2.2, Page 7, L213-214-

"Using annual values may mask water scarcity during the dry season."

Comment 4: I find Fig 2 confusing and ambiguous with respect to applying the SBA concept: are there three SBASs ("upstream" "middle stream" and "downstream") or are there four SBAs (OdSBAcz, OdSBApoa, OdSBAge, and OdSBApob)? I guess you mean the latter, if so omit the former. If not, clarify and avoid ambiguity.

Response 4:

In this article SBAs (sub-basin areas) were obtained by breaking up the drainage direction map where it flows across country (and shared zone) boundaries, effectively yielding a mesh of river basin and country boundaries. Upstream-downstream relationships between these SBAs were defined by the flow direction dataset as we mentioned in page 5, L166-L169. Afterwards, we categorized the SBAs according to three different types - "upstream", "middle stream" and "downstream". The identified 4 SBAs of the ODER river basin fall under these 3 different types as-

 $OdSBA_{CZ}$ -Upstream, $OdSBA_{PO-A}$ - Middle stream, $OdSBA_{GE}$ - Middle stream, $OdSBA_{PO-B}$ - Downstream.

We agree that Figure 2 is not clearly distinguishing the 4 different SBAs currently. In the revised manuscript, we have made the country border more prominent so the definition of the SBAs is more obvious (see below). We also have changed the legend caption from *Sub basin areas (SBAs)* to *Sub basin area (SBA) types*. We hope this will clarify the confusion.



Comment 5: I would combine the last sentence of section 2.2.2 (p. 7 lines 346-347) ("As illustrated in Fig.4.") with lines 226-227 on the same page, adding a clarifying remark, for example thus:

"The water scarcity status was categorized as No scarcity (N) and Scarcity (S) using average annual water availability from 1981 to 2010. We now can define the earlier defined four different dependency categories in terms of scarcity an SBA can face: NNN, SNN, SNS, and SSS. This is shown in Fig.4."

Response 5:

We agree with moving the last sentence of section 2.2.2 earlier, but did not want to introduce the three letter names of the categories before explaining how they are obtained. We therefore now added text in page 7, L233-234 as:

"Figure 4 defines the four possible different dependency categories in terms of scarcity a SBA can face, as illustrated by the discussion below:"

Comment 6: Fig 3: in the caption the concept of "water requirements" is used, but this is not defined in the text. Do you simply mean "WW". Please be consistent and parsimonious with concepts! Also Falkenmark's threshold value should have the unit of m3/cap/year.

Response 6:

We agree that "water requirements" was an extra concept, only used for the purpose to visualize water availability a SBA required to avoid stress. To be precise, "water requirements" referred to the water availability required to achieve a water stress value of 0.2 (the threshold used in the paper). We have the following derivation:

stress = WW/avail avail = WW/stress avail = WW/0.2

This provided an easy visualization of how water availabilities relate to the stress threshold, but is not a crucial concept otherwise in the paper. To avoid introducing new terms, we have reworded the legend item to read:

"Water availability required to achieve stress=0.2, given local water withdrawals in year 2010"

We hope this will clear the confusion. We have also corrected the unit of the Falkenmark's threshold in the caption. Thank you for pointing this out.

Comment 7: The last paragraph of section 4.1 (p. 13, lines 400-410) could also refer to the no harm principle (article 7) of the UN Watercourses Convention of 1997.

Response 7:

Thank you for the suggestion. Reference has been added in section 4.1 (Page 14, L 410-412)-

"The UN Watercourses Convention of 1997 also refers to the no harm principle (article 7), which works in tandem with consideration as to whether a given water use is reasonable and equitable (UN 2018)."

Comment 8: The last two sentences of section 4.2 seem to contradict each other. Please clarify.

Response 8:

Thank you for pointing this out. The sentences have been reworded as:

"This point has been made in existing literature (e.g. related to social construction of scarcity) but is not yet widely recognized." (Page-15, L443)

How downstream sub-basins depend on upstream inflows to avoid scarcity: typology and global analysis of transboundary rivers

Hafsa Ahmed Munia^{1*}, Joseph H.A. Guillaume¹, Naho Mirumachi², Yoshihide Wada³, Matti Kummu^{1*}

- 1. Water and Development Research Group, Aalto University, Tietotie 1E, Espoo 02150, Finland
- 2. Department of Geography, King's College London, Strand, London WC2R 2LS, UK
- 3. International Institute for Applied Systems Analysis, Schlossplatz 1-A-2361, Laxenburg, Austria
- * Correspondence to: Hafsa Ahmed Munia (hafsa.munia@aalto.fi) and Matti Kummu (matti.kummu@aalto.fi)

Abstract: Countries sharing river basins are often dependent upon water originating outside their boundaries; meaning that without that upstream water, water scarcity may occur, with flow-on implications for water use and management. We develop a formalisation of this concept drawing on ideas about transition between regimes from resilience literature, using water stress and water shortage as indicators of water scarcity. In our analytical framework, dependency occurs if water from upstream is needed to avoid scarcity. This can be diagnosed by comparing different types of water availability on which a sub-basin relies, in particular local runoff and upstream inflows. At the same time, possible upstream water withdrawals reduce available water downstream, influencing the latter water availability. By developing a framework of scarcity and dependency, we contribute to understanding on transitions between system regimes. We apply our analytical framework to global transboundary river basins at the scale of subbasin areas (SBAs). Our results show that 1175 million people live under water stress (42% of the total transboundary population). Of these, the majority (1150 million) suffer from stress only due to their own excessive water use and possible water from upstream does not have impact on the stress status - i.e. they are not dependent on upstream water to avoid stress – but could still impact on the intensity of the stress. At the same time, 386 million people (14%) live in SBAs that can avoid stress owing to available water from upstream and have thus upstream dependency. In the case of water shortage, 306 million people (11%) live in SBAs dependent on upstream water to avoid possible shortage. The identification of transitions between system regimes sheds light on how SBAs may be affected in future, potentially contributing to further refined analysis of inter and intrabasin hydro-political power relations and strategic planning of management practices in transboundary basins.

1 Introduction

While water is a renewable resource, its availability is finite. As population and water demand grow, water becomes scarce. If local precipitation is insufficient to meet needs, a region may draw on external water resources, both physical and virtual (through food and goods trade) (Hoekstra and Chapagain 2011). External water resources constitute a considerable part of the total renewable water of some countries, and create hydrological, social and economic interdependencies between countries (Hoekstra and Mekonnen 2012). Transboundary water resources crossing national borders are a high-profile example. In basins like the Nile and Rio Grande, water availability of the downstream countries (Sudan, Egypt, Mexico) is highly dependent on upstream precipitation patterns and upstream water use (Drieschova et al. 2008). Transboundary waterbodies cover almost half of the earth's land surface, and are home to about 1/3 of the world's population (UN Water 2013).

'Hydro-political dependency' in transboundary river basins is an important geopolitical issue bound up with concerns of sovereignty, affecting the power relations between riparian countries (Brochmann and Gleditsch 2012, Giordano and Wolf 2003, Gleick 2014, Jägerskog and Zeitoun 2009, Mirumachi 2013, Mirumachi 2015, Wolf 1998, Wolf 2007,

Wolf 1999). Increase in water demand is among the main factors responsible for water scarcity in most transboundary river basins (Degefu et al. 2016). Uncontrolled land and water development in upstream regions can escalate risk of water supply uncertainty in the downstream region (Al-Faraj and Scholz 2015, Drieschova et al. 2008, Veldkamp et al. 2017). Concerns about water availability are already considered one of the most important issues for international co-operation and conflict concerning shared water basins (Beck et al. 2014). Regional and global studies already show that upstream water use has considerable impact on downstream water scarcity (Munia et al. 2016, Nepal et al. 2014, Scott et al. 2003, Veldkamp et al. 2017). When population (or water withdrawals) grow, downstream countries eventually become more reliant on the water available from upstream parts of a basin in order to satisfy their needs.

In this study, we aim to explore one particular definition of 'upstream dependency'. Intuitively, one could say that upstream water dependency occurs if water from upstream is needed to avoid water scarcity. Dependency therefore involves a sharp transition between cases where water scarcity is or is not experienced depending on whether water from upstream is or is not available. Transitions between cases is a key idea in resilience thinking, which therefore provides a promising way of approaching this problem.

1.1 A resilience perspective on upstream dependency

'Resilience' of a socio-ecological system is defined as "the capacity of a system to absorb disturbance and reorganize while undergoing change so as to still retain essentially *the same function, structure, identity, and feedbacks*" (Walker et al. 2004, p.01). Changes in the system are tracked in terms of 'state variables', such that thresholds in those state variables are used to define the points at which change occurs in the system function, structure, identity and feedbacks. When a threshold is crossed and changes occur, we say that the system has moved to a different 'basin of attraction', that there has been a 'regime shift', or a 'transition between system regimes'. While some studies aim to quantify resilience, we focus on identifying circumstances in which these regime shifts occur.

Understanding thresholds and regime shifts is considered critical to adaptability and transformations in transboundary basin management (Green et al. 2013). In the case of upstream dependency, we would distinguish between different system regimes depending on whether or not water scarcity occurs and whether or not dependency occurs and its implication in the prevention of scarcity. Dependency occurs in a region when there is a transition between scarcity system regimes when considering cases where water is or is not available from upstream. We therefore compare whether scarcity occurs when water availability is calculated using solely local runoff, natural discharge (sum of local runoff and upstream runoff), and actual discharge (subtracting upstream water withdrawals from natural discharge). System regimes categorized as 'Scarcity' and 'No scarcity' are distinguished by a change in *function* of the system water becomes insufficient in some sense. For the purpose of developing our analytical framework, occurrence of scarcity is determined using commonly used water shortage and water stress indicators (further discussed in Sect. 2.2.2). Water scarcity can also be socially induced. That is, social systems rather than climatic or hydrological factors are determining, disadvantaging groups within society, often those marginalised (Mehta 2013). Management actions may enable water to become sufficient and demonstrates a case where structural changes occur, and therefore also a transition between system regimes. However, as a first step to operationalize the concept of physical dependency over water, we focus on thresholds of physical scarcity, following existing studies (Brown and Matlock 2011, Kummu et al. 2010, Porkka et al. 2012).

Transitions in system regimes in terms of dependency can occur over time, and regions can be classified according to their dependency category. Based on the role of upstream inflows and withdrawals, a region might experience: i) no dependency if scarcity is not affected by upstream inflows, ii) *unbrokenhidden* dependency if scarcity category is altered by upstream inflows but not by upstream water withdrawal, or iii) *brokenopen* dependency if scarcity is altered after accounting for upstream water withdrawals. If a system transitions into an unbrokena hidden dependency regime, the *structure* of the system changes – upstream withdrawals can now alter the scarcity category. An unbrokenThe "hidden" nature of the dependency is potentially *hidden*:refers to the observation that a downstream part of a basin might be avoiding water scarcity only thanks to upstream inflows, and water users may not actually realise this causal factor unless those inflows are no longer available, due to increased upstream withdrawals or lower upstream runoff due to climate change or variation. The dependency becomes "open" when the role of upstream inflows becomes obvious because water scarcity does eventuate. That is, there is a transition to a brokenan open

dependency regime, which can also occur due to further increases in local demand. The system may then have a loss of function (insufficient water), or change in structure (due to management actions). Examining these system regimes helps to understand possible transitions of a region, and the actions that may be needed to avoid or control transition processes, e.g. negotiating water treaties to prevent or smooth transition to a broken open dependency regime. We emphasise repeatedly throughout this article that upstream withdrawals may also affect the *intensity* of scarcity – our focus here is specifically on transitions between regimes.

A summary of the key terms used in the analysis is given in Table 1.

 Table 1. Key terminology used in the analysis and their definitions. Note: definitions in terms of water availability volumes

 emerge from our analysis, as described in Section 2 & summarised visually in Figure 4. Our analysis method did not consider

 the case where actual discharge may be greater than natural discharge

Term	Definition					
Water stress	Demand driven water scarcity, calculated as use to availability ratio					
Water shortage	Population driven water scarcity, calculated as water availability per capita					
Local runoff	Runoff occurring internally within a region (in this paper a sub-basin).					
Upstream runoff	Runoff of the possible upstream region (in this paper a sum of runoff of upstream sub-basins)					
Natural discharge	Total water availability before taking into account possible upstream water withdrawals, here calculated as local runoff + upstream runoff.					
Actual discharge	Total water availability after upstream water withdrawals; calculated as natural discharge – upstream withdrawals (local runoff + upstream runoff – upstream withdrawals).					
No dependency	Upstream inflows do not influence whether or not a region experiences scarcity, i.e. if a region experiences scarcity or not with only local runoff, additional water from upstream does not change this situation, nor do the upstream water withdrawals. Note that the severity of scarcity may still be affected by upstream inflows and water withdrawals. No dependency can be expressed as: local demand $\leq local runoff OR local demand \geq natural discharge$					
Dependency	Upstream inflows influence whether a region experiences scarcity or not, i.e. how water is managed upstream can change the type of water management regime needed downstream. Dependency can be expressed as:					
	<u>local runoff < local demand < natural discharge</u>					
	Two sub-types of dependency can be distinguished (as follows).					
Unbroken <u>Hidden</u> denendency	scarcity category is altered by upstream inflows but not by upstream water withdrawais, i.e. Local runoff is not enough to meet the local demand but additional water from upstream means the					
uepenuency	region experiences no scarcity instead of scarcity-and-upstream. Upstream withdrawals doare					
	small enough not to change this the scarcity status. Hidden dependency can be expressed as:					
	<u>local runoff < local demand < actual discharge</u>					
Broken <u>Open</u> dependency	Scarcity category is altered after accounting for upstream water withdrawals, i.e. <u>while upstream</u> inflows in the hidden dependency allowed the region to avoid scarcity, <u>upstream</u> withdrawals <u>now</u> mean that the advantages gained by upstream inflows are reduced or eliminated, <u>SBA does</u> experience scarcity and more intense water management regimes are needed downstream. <u>Open dependency can be expressed as:</u>					
	<u>uctuut uisenut ge < tocut uemunu < nutur ui uisenut ge</u>					

These definitions of upstream water dependency and dependency categories form the basis of our quantitative analytical framework. The framework is used to conduct a global analysis that quantitatively distinguishes different scarcity and dependency regimes at a transboundary sub-basin (SBA) scale, i.e. parts of basins that belong to different countries. Figure 1 summarises the key ideas of this paper. Specifically, we aim to answer the following research questions:

- What is the current dependency category of each sub-basin?
- How do climate, upstream withdrawals, and local demand influence dependency category? What transitions to other dependency categories are possible, that should perhaps be considered in planning for the future?
- How do regime shifts involving unbroken (hidden) and brokenopen dependencies relate to negotiations in transboundary basins?

Our analysis is based on modelled water availability and water use data (Sect. 2.1). Our method section builds up our analytical framework, defining sub-basins and calculating the different types of water availability (Sect. 2.2.1), interpreting upstream dependency in terms of water scarcity (Sect. 2.2.2), and unpacking determinants of dependency categories and transitions between them (Sect. 2.2.3). Applying this method to global transboundary basins, our results describe dependency categories in year 2010 and how they affect the problems faced by the sub-basins (Sect. 3). We then describe how the transitions between scarcity (Sect. 4.1). We conclude with discussion of opportunities for further work building on and improving this method and dependency typology (Sect. 4.2& 4.3).



Fig. 1 Key ideas of this study: our definition of dependency and themes addressed by our research questions.

2 Data and Methods

To operationalise our definition of upstream water dependency, we used the global hydrological model PCRaster Global Water Balance (PCR-GLOBWB) to simulate water use and water availability at grid cell resolution (30 arcmin or roughly 50 km by 50 km at the equator). A basin-country mesh was used to sub divide the transboundary basins into sub-basin areas (SBAs). We then examine differences in the scarcity of available water of the different types in order to provide a first explanation of why dependency occurs. Below we present in more detail the data, methods and analytical framework used for the assessment.

<u>2.1</u> Data

The data used for the study is summarized in Table 2. Runoff and water withdrawals (WWs) were calculated using the PCR-GLOBWB 30 arc-min model (Wada et al. 2011a, Wada et al. 2013). PCR-GLOBWB is a conceptual, process-based water balance model. In brief, it simulates for each grid cell and for each time step (daily) the water balance in two vertically stacked soil layers and an underlying ground water layer, as well as the water exchange between the layers and between the top layer and the atmosphere (rainfall, evaporation and snowmelt) (Wada et al. 2013). Discharge estimates from the model are extensively validated against observations from the Global Runoff Data Centre (GRDC) in existing publications by Wada et al. (2013, 2014). The return flows from industrial and domestic sectors have been taken into account in PCR-GLOBWB and the recycling ratios for industrial and domestic sectors have been estimated (roughly 40-80%) at a country level and validated based on Wada et al. (2011a, 2014).

Table 2.	Datasets	used in	the study	together	with	their i	source.
----------	----------	---------	-----------	----------	------	---------	---------

Data	Year	Source	Description
Drainage direction	-	Döll (2002)	Global grid with 30 arc-min resolution
Runoff	1981–2010	Wada et al. (2011a; 2013)	Monthly data at global grid with 30 arc- min resolution
Irrigation water withdrawal	1981-2010	Wada et al. (2011a; 2013)	Monthly data at global grid with 30 arc- min resolution
Industrial water withdrawal	1981-2010	Wada et al. (2011a; 2013)	Monthly data at global grid with 30 arc- min resolution
Domestic water withdrawal	1981-2010	Wada et al. (2011a; 2013)	Monthly data at global grid with 30 arc- min resolution
Population density data	1981-2010	Klein Goldewijk et al. (2010)	HYDE data set

Total WW were calculated for each SBA as the sum of three water use sectors: irrigation, domestic and industrial. The water use data for these sectors were obtained from the same model as the discharge simulations (Wada et al. 2011a, Wada et al. 2013). Water use estimates have also been previously validated against reported country data, notably FAO AQUASTAT, by Wada et al (2011a). In this analysis, water withdrawals refer to the total amount of water withdrawn, but not necessarily consumed, by each sector_{7.2} much of which is returned to the water environment where it may be available to be withdrawn again. However, estimation of return flows is uncertain and they may not necessarily be available to downstream users, for example because of pollution, timing of the flows or infiltration to groundwater (Wada et al. 2011a, Wada et al. 2011b). Thus, the return flows were not subtracted from withdrawals in this analysis.

To provide an indication of need for water (rather than withdrawals), population density information was obtained from the HYDE 3.2 dataset for each year from 1981 to 2010 (Klein Goldewijk et al. 2010). The data were first aggregated from 5 arc-min to 30 arc-min resolution and then for each SBA for every year over the 30-yr period.

The 30 arc-min raster dataset DDM30 (Döll 2002) described drainage direction for both surface flow routing in PCR-GLOBWB and definition of upstream-downstream links.

Country boundaries were first rasterized from Natural Earth Admin 0 boundaries (Natural earth 2017). Border cells were then manually assigned to countries to provide meaningful hydrological relationships. In general, single cell SBA were avoided. Cells where country borders follow a river were treated as separate "shared" zones. What we refer to as a "country" raster therefore includes both countries and shared zones.

2.2 Methods

2.2.1 Sub-basin definition and calculation of water availability

To explain the methods and analytical framework used for the global assessment, we use the Oder, a river in central Europe, as an example case study (Fig. 2). Oder is a transboundary river that rises in the Czech Republic and flows through western Poland, later forming the border between Poland and Germany. We chose the Oder River Basin as an example case study because: i) it has non-trivial but sufficiently easy hydrological connections for illustrative purposes, ii) it includes upstream, middle stream and downstream SBAs, and iii) the water stress levels and downstream dependencies illustrate well the use of our analytical framework.

SBAs (i.e. sub-basin areas) were defined by breaking up the drainage direction map where it flows across country (and shared zone) boundaries, effectively yielding a mesh of river basin and country boundaries. Upstreamdownstream relationships between these SBAs were defined by the flow direction dataset. The construction of the country raster (see Sect. 2.1) ensured that the SBAs provide a meaningful representation of the hydrological system. A country can have multiple SBAs in order to capture different flow paths. In general, the drainage direction raster captures major tributaries even if finer details are missing. In the case of the Oder Basin, Fig. 2 presents the four identified SBAs (OdSBA_{CZ}, OdSBA_{PO-A}, OdSBA_{PO-B}, OdSBA_{GE}) and the direction of flow between these SBAs. Czech Republic (OdSBA_{CZ}) has been identified as the most upstream, part of Poland (OdSBA_{PO-A}) and Germany (OdSBA_{GE}, where the river forms the border) as middle stream, and part of Poland (OdSBA_{PO-B}) as the most downstream (Fig 2).

Three types of <u>average annual</u> water availability (for 1981-2010) were calculated in each of these SBAs, corresponding to local water (local runoff), total inflows including upstream areas (natural discharge), and total inflows after upstream WWs (actual discharge) (see detailed definitions in Table 1). We approximate discharge as the sum of local runoff in local and upstream SBAs, such that there is an arithmetic relationship between the two. This provides an easy to follow abstraction of the problem that emphasises upstream-downstream relationships while ignoring issues of land use change, timing of flows, and conveyance losses.

WW for each SBA was calculated separately (referred to as *WW.local*) by summing up the three water use sectors (industrial, domestic and agriculture) for the year 2010 and aggregating to SBA scale. Local runoff for each SBA (*avail.local*) was given by its average runoff. Natural discharge (*avail.natural*) for each SBA was calculated by summing together the local runoff of the SBA and all its upstream SBAs.

Actual discharge (*avail.actual*) was calculated from the SBA WWs and total water availability. We identified the entire upstream area for each SBA based on the upstream-downstream hierarchy; i.e. in cases when an SBA has more than one upstream SBA, the total upstream water withdrawalsWWs are summed (*WW.upstream*). The drainage network used here to identify upstream-downstream relationships has a clear hierarchical relation, with no distributaries, so water only flows to one immediately downstream SBA and there is no risk of double counting. These water withdrawalsWWs were then subtracted from natural discharge for the corresponding year, i.e. *avail.actual* = *avail.natural* – *WW.upstream*. In some cases, *avail.actual* in excess of *avail.local* is considered to be fossil ground water or other available water that is not included in the calculation. In these cases, we set *avail.actual* to be equal to *avail.local* for that SBA.



Fig 2. Upstream-downstream relationship between sub-basin areas (SBAs) in the Oder basin and average simulated annual water availability for 1981-2010. Drainage network and sub-basin division are based on DDM30 (Döll 2002) and country borders (Natural Earth 2017) with additional manual assignment of border cells.

2.2.2 Interpretation of upstream dependency in terms of water scarcity

Looking at the average availability of water (1981-2010) for the SBAs of the Oder basin provides an illustration of the concept of upstream dependency (Fig 2). The headwater SBA (OdSBA_{CZ}) obviously has no upstream dependency; the three types of water availability are the same. But in the case of SBAs OdSBA_{PO-A}, OdSBA_{PO-B}, OdSBA_{GE} upstream water availability and withdrawals influence water availability. These are the SBAs we are most interested in.

Dependency on upstream water can be assessed by comparing an SBA's scarcity category across the different water availability types (i.e. local runoff, natural discharge, actual discharge – see definitions in Table 1). We calculated scarcity using water stress and water shortage indices. Water stress refers to impacts from high use of water while water shortage refers to impacts from insufficient water availability per person (Falkenmark et al. 2007, Kummu et al. 2016).

The stress indicator was calculated as *WW.local/avail* and the shortage indicator is calculated as *avail/population.local*. The stress indicator includes environmental flow requirements (EFRs), assuming 30% of the water is needed to satisfy the EFRs (Falkenmark et al. 2007). To determine whether water stress or shortage occurs, we respectively used the thresholds 0.2 and 1000 m³/capita/yr, as defined by Falkenmark et al (2007) and used by other research too (Liu et al. 2017). Crossing this threshold leads to impacts from insufficient water availability per person, potentially limiting economic development, and human health and well-being (Falkenmark et al. 2007). <u>Using annual values may mask water scarcity during the dry season</u>. Falkenmark's per capita water availability as a measure of water scarcity has limitations as an indicator. Nevertheless, both stress and shortage are useful indicators of the more general concept of scarcity. Shortage, measured by per capita water availability, captures an important intuition that sufficiency of water availability depends on population. Even though the thresholds are arbitrary, using both indicators provides a useful balance to understand the development of water scarcity (Kummu et al. 2016), as well as illustrating the generality of the analysis framework. The use of these thresholds is in line with existing studies and while interpretation of the results is limited by the simplicity of the indicators, they provide a first step in understanding upstream dependency.

Annual stress and shortage were calculated using WWs and population for 2010 with 1) local runoff, 2) natural discharge and 3) actual discharge. Equations for water stress:

1.
$$\frac{WW.local}{avail.local}$$
; 2. $\frac{WW.local}{avail.natural}$; 3. $\frac{WW.local}{avail.natural-WW.upstream}$.

Equations for water shortage:

1. $\frac{avail.local}{population.local}$; 2. $\frac{avail.natural}{population.local}$; 3. $\frac{avail.natural - WW.upstream}{population.local}$.

The water scarcity status was categorized as No scarcity (N) and Scarcity (S) using average annual water availability from 1981 to 2010. The 30-year period was used to capture the current hydro climatic characteristics. Fig. 3a represents scarcity for the three water availability types for the Oder basin under average conditions, shown within the Falkenmark matrix (Falkenmark et al. 2007, Kummu et al. 2016) which shows stress and shortage together. Archetypes in the Falkenmark matrix describe the water scarcity status (corresponding to position on the plot) and where both shortage and stress occur, according to which occurs first (Kummu et al. 2016). Figure 4 defines the four possible different dependency categories in terms of scarcity a SBA can face, as illustrated by the discussion below.

None of the SBAs have any shortage as the per capita water availability has never dropped below 1000 m³ cap⁻¹ yr⁻¹. OdSBA_{PO-A} is stressed (S) under all three water availability types, and OdSBA_{CZ} is not stressed (N). OdSBA_{GE} and OdSBA_{PO-B} would both be stressed (S) only if they were restricted to their local runoff (Fig. 3a). After accounting for inflows from upstream (natural discharge), the stress level decreased from 0.25 to 0.01 (N) for OdSBA_{GE} and from 0.35 to 0.01 (N) for OdSBA_{PO-B} (Fig. 3a). This change in stress category means that both these SBAs is dependent on

upstream water to avoid stress. We further see that upstream WW increases the stress level relative to natural conditions (to 0.02 for both) (Fig. 3a & c), but the threshold for stress was not crossed. The stress level changed without changing the stress category, such that the category of the dependency was not affected; we have an *'unbroken'a 'hidden*' rather than '*broken'open*' dependency (definitions in Table 1). In the case of OdSBA_{PO-A}, local runoff is not sufficient to meet needs and that upstream water availability and water withdrawals<u>WWs</u> do not influence the scarcity category of this SBA. This SBA is under the same scarcity conditions regardless of upstream influence (Fig. 3a & b), and it is thus categorized as '*No dependency*', though the intensity of scarcity is still affected by upstream WW. The dependency category of an SBA can then be summarised using three letter codes representing the scarcity category using local runoff, natural discharge and actual discharge respectively: OdSBA_{GE} and OdSBA_{PO-A} is SSS, and OdSBA_{CZ} is NNN (Fig. 3a). As illustrated by the above discussion, we can interpret possible scarcity an SBA faces using four different dependency categories as shown below in Fig **4**.



Fig 3. Scarcity and dependency category for the Oder sub-basin areas (SBAs) under annual average conditions. The Falkenmark matrix (a) and plot of water availability required to avoid stress (b), show changes in stress and shortage under different types of water availability (see definitions in Table 1). Inset map represents the Oder SBAs' corresponding dependency categories. Scarcity and dependency categories for each SBA for the year 2010 were calculated using a water stress threshold value of 0.2 and water shortage threshold value of 1000 $m^3/cap/year$.

Scarcity under local water availability (local runoff)		Scarcity including upstream water (natural discharge)		Scarcity after accounting for upstream withdrawals (actual discharge)		Dependency category		
No scarcity —	-	No scarcity		No scarcity	• •	NNN	(no dependency)	
Scarcity	→	No scarcity		No scarcity	••••	SNN	(hidden dependency)	
				Scarcity		SNS	(open dependency)	
	-	Scarcity	\rightarrow	Scarcity	· >	SSS	(no dependency)	
Scarcity and dependency category								
No dependency Dependency Hidden dependency Open dependency		N = No S S = Scar	Scarcity r city					

Fig 4. Definition of potential upstream water dependency categories. Dependency categories are obtained by summarizing three letter codes representing the scarcity category using local runoff, natural discharge and actual discharge respectively (see definitions in Table 1).

2.2.3 Determinants of dependency category and possible transitions in them

In order to evaluate possible responses to dependency, we need to understand what determines a dependency category and what can be done to achieve or to avoid change. Annual water availability can be thought of as a constraint on the environment in which a society operates. Society is able to influence that constraint, for example by building reservoirs (Veldkamp et al. 2017) – captured to some extent by the model. However, for a given hydro-climate and state of development, it is useful to think of the current water availability regime as an integral, defining characteristic of a system regime. As population and WW increase in a region, the occurrence of shortage, stress and upstream dependency is determined by the volumes of the three types of water availability. A region will face scarcity or dependency as a result of:

- Insufficient local runoff (avail.local)
- Insufficient discharge, from local runoff and possible upstream inflows (avail.natural)
- Insufficient discharge after upstream WW (i.e. water withdrawals) (avail.actual)

From a resilience perspective, these volumes of water can be thought of as thresholds, where an SBA would be under 'no scarcity' category when its average local runoff (*avail.local*) is sufficient to meet the water demand in a given year and 'scarcity' category when its average natural discharge (*avail.natural*) is insufficient in relation to its water demand. In this study, 'demand' is used as a high-level umbrella term covering both actual withdrawals (for the stress indicator) and need for water (population, for the shortage indicator).

Fig 5 shows the ordering of possible thresholds for an SBA based on water availability, and how the shortage and stress categories vary as demand changes. To allow comparison, water availability, population, and withdrawal are all expressed as percentages respectively of *avail.natural*, carrying capacity (*avail.natural*/1000) and sustainable yield (*avail.natural* × 0.2). The current status of OdSBA_{GE} and OdSBA_{PO-B} is shown in the figure. Currently OdSBA_{GE} and OdSBA_{PO-B} are in the 'SNN' category for stress and 'NNN' category for shortage (Fig 3). They have unbrokenhidden dependencies (avoiding stress), as the average year inflows after upstream WW are sufficient to meet water demand. If the water demand in these SBAs were to increase to a level where the average year inflows after upstream WW (*avail.actual*) would not be enough to meet demand, the SBA would next transition from SNN to SNS category. Thus, with the increase in demand, the dependency category (e.g. 'SNS') would change based on the thresholds it crosses and ultimately the basin would become SSS, indicating that an SBA would be under scarcity under each type of water availability considered. The same thing would happen with shortage as the population increases (Fig 5). Over time, this change in dependency category could go forward and backward as water demand of the SBA increases or

decreases. This order of thresholds determines the transition in dependency category for $OdSBA_{GE}$ and $OdSBA_{PO-B}$ as local demand increases or decreases.

So far, we have conceptualised change in dependency category in the context of a fixed set of water availability thresholds, obtained directly from estimated water availability volumes. The order of thresholds determines the transition in dependency category as local demand increases or decreases. In fact, even if upstream WW changes the values of the thresholds, their order will remain the same. These scarcity thresholds are naturally ordered because local water necessarily becomes insufficient before upstream water availability types respectively: local \leq actual \leq natural. We do, however, distinguish between headwaters vs middle stream and downstream SBAs.

Headwaters are the simplest case. Given they are the most upstream SBAs, they rely solely on local runoff, Increases in an SBA's demand cause transition from 'no scarcity' to 'scarcity' category. Decrease in demand would have the opposite effect (Fig 5).

In the case of middle stream and downstream SBAs, transition occurs between four scarcity categories, which are connected by a simple map of transitions: NNN-SNN-SNS-SSS. Transition in the scarcity category depends on both local demand and upstream WW. The experience of dependency in the Oder basin is therefore generally applicable to all middle and downstream SBAs. As the local demand increases, the SBA moves from NNN to SNN, exposing it to a 'hidden dependency' as local runoff become insufficient, but the SBA still receives sufficient upstream inflows to meet the local demand. The next transition between SNN to SNS is dependent on both local demand and upstream WW until local demand increases to the level where all available water become insufficient - the SBA becomes SSS. The decrease in local demand and upstream WW will have the opposite effect.

Thus SBA crosses thresholds which not only change the scarcity category, but also change the dependency category, considered in this study as transitions between different 'system regimes'. Note that we focus on the effect of increasing or decreasing local demand and upstream water withdrawal<u>WW</u>, leaving changes in water availability to future work.



Fig 5. Typology of possible transitions in dependency category, as local water demand or upstream water withdrawals (WW) increase/decrease (a). Upstream WWs decrease the downstream water availability, while local water demand increases the pressure on available resources. Current (2010) status of $OdSBA_{GE}$ and $OdSBA_{PO-B}$ (for both stress and shortage) is shown in the transition map (b). See definitions of terminology in Table 1.

3 Results: Global analysis of dependency categories

The analysis was applied to 246 international transboundary basins to understand the dependency category of these basins and possible future transitions, using water withdrawal<u>WW</u> and population data from 2010.

The 246 transboundary basins were divided into 886 SBAs based on country borders (as well as shared zones along those borders). As shown in Table 3, in the case of stress, most SBAs had no dependency in 2010 (93%, 824 SBAs), while 52 SBAs have an <u>unbrokenhidden</u> dependency – water available from upstream lifts the SBA from scarcity and upstream WWs do not change the scarcity category (though they may still intensify scarcity where it occurs, see Discussion). In total 10 (1%) SBAs are identified where the dependency was 'broken'open', meaning that upstream water withdrawals change the downstream stress category (Table 3). In the case of shortage, 35 SBAs were under <u>unbrokenhidden</u> dependency and only 2 under <u>brokenopen</u> dependency. Upstream water withdrawalsWWs thus only rarely play a role in causing low water availability per capita.

	Dependency	Stress		Shortage	
	category	No of sub-basins	Population (×10 ⁶)	No of sub-basins	Population $(\times 10^6)$
No upstream	NNN	688 (78%)	1231 (44%)	799 (90%)	2312 (83%)
dependency	SSS	136 (15%)	1150 (41%)	50 (6%)	172 (6%)
UnbrokenHidd en dependency	SNN	52 (6%)	386 (14%)	35 (4%)	306 (11%)
BrokenOpen dependency	SNS	10 (1%)	25 (0.9%)	2 (0.2%)	2 (0.7%)
Total		886	2792	886	2792

Table 3. Number of SBAs under different dependency categories in the year 2010.

'No dependency' is observed in 93% of cases for stress and 96% of cases for shortage (Table 3). It is worth noting that scarcity can still be experienced without a dependency – it simply means that current upstream inflows (and WWs) do not influence whether scarcity occurs. For example, in the case of water stress, 41% of the population living in SBAs under 'no dependency' are under stressed conditions (Table 3). Further, even if an SBA in question is under no dependency category, upstream WW might still intensify the possible scarcity. In this category, there is not currently a problem with relationships with upstream SBAs, but to plan ahead, we need to understand how the situation could evolve, as is discussed in Sect. 4.1.

^cUnbrokenHidden dependency' is observed for both stress and shortage mostly in Africa, and some parts of Southeast Asia, and Europe (Fig. 6a, b). <u>UnbrokenHidden</u> dependency means that maintaining good relationships and assessing water use and potential changes with upstream basins are important to avoid scarcity. A number of SBAs in which currently no scarcity is observed (Fig. 6), are actually subject to upstream dependency. If inflows were to decrease sufficiently due to increased upstream WWs, scarcity could occur. In these SBAs, this has not yet happened, though upstream WWs may be influencing the intensity of scarcity and the level of development (population or use) at which thresholds occurs. Therefore, understanding of how the situation can evolve is needed to know how to manage the relationship with upstream water users.

^{(BrokenOpen} dependency' occurred notably in central Asia and some parts of North America for stress and for shortage, only in areas categorised as shared zones as part of the Jordan basin (Israel, Syria, and Lebanon) and the intermittent Wadi Al-Batin (forming the border between Kuwait and Iraq) (Fig. 6a, b). BrokenOpen dependency indicates that scarcity occurs and could be attributed to upstream water use, such that there is a potential for tension with upstream water users over water allocation as things currently stand. But while there would be no scarcity if it were not for upstream WWs, reducing local water needs or WWs could also avoid shortage or stress. As a result, avoiding scarcity in these SBAs requires cooperation rather than uncoordinated competition between the upstream and the downstream region. Such a situation is already evident in the case of Central Asia (Dukhovny 2014). However, understanding of the evolution of the situation may show that small decreases in local or upstream WWs may not be sufficient to avoid scarcity or dependency. It may be necessary to find means to reduce needs or adapt to impacts from high water use.



(a) Sub-basins under different dependency category in case of water stress

(b) Sub-basins under different dependency category in case of water shortage



Fig 6. Dependency categories for each sub-basin area (SBA) for the year 2010 using a) Water stress threshold value of 0.2; and b) Water shortage threshold value of 1000 m^3 /year/capita. See definitions of dependency categories in Fig. 4 and definitions of key terminology in Table 1.

4 Discussion

In this analysis, transboundary water dependency was examined based on the concept that an SBA is dependent on upstream inflows if it requires those inflows to avoid water scarcity (e.g. stress, shortage as used here) and associated impacts. We proposed that regime shifts discussed in the resilience literature provide a useful way of thinking about this problem, and we provide a first exploration of how this concept can be analysed.

We aimed to address three research questions. Firstly, we identified the current dependency category of each SBA. Examining occurrence of scarcity with different types of water availability allows classification of ways in which

upstream and downstream SBAs are dependent on each other (Sect. 2.2.2, and Sect. 3). To answer the second question, we further developed the analytical framework by explaining how climate, upstream withdrawals and local demand influence the dependency categories (Sect. 2.2.3). This yields a sequence of transitions between system regimes that describe what future changes in scarcity and dependency are possible. This leads to our third research question: how does this relate to water management and negotiations in transboundary basins?

4.1 What are the implications for mitigation and prevention of scarcity?

The literature on resilience and complex adaptive systems emphasises that it is difficult to predict what will happen in future, but we can identify what are the transitions that *might* occur to prepare ourselves such that the system either avoids or manages those transitions. According to our framework, the starting point is a system regime with low water demand, easily satisfied by local runoff (NNN). There is no need to use upstream inflows, such that upstream withdrawals have no effect on local water scarcity. The need to engage with upstream water users begins with an increase in local water demand, transitioning to a system regime where scarcity depends on upstream withdrawals (SNN). It is in the interest of both downstream and upstream to avoid breaking thistransitioning to an open dependency (SNS), which could happen because of either increases in local demand or upstream WW (as well as changes in climate). Despite the invisible consequences of transition to SNN, it would be worthwhile to expose the hidden dependency. Negotiation to reduce water withdrawalsWWs may fix a brokenan open dependency, but there is also another possible outcome. If local water demand continues to increase, the dependence on upstream withdrawals can no longer solely cause scarcity, even if they contribute to its severity. In this system regime, negotiation with upstream regions is not sufficient to avoid scarcity, so it may be more worthwhile to look for other solutions, such as those within the political economy (Allan 2002).

Understanding these transitions provides a basic level of guidance for a region. In a no dependency system regime (e.g. most SBAs analysed), efforts can be made to keep water demand at low enough levels to be self-sufficient. If water demand is expected to increase, monitoring is useful to avoid being surprised by the breaking of a hidden dependency. While our analysis shows relatively few brokenopen or unbrokenhidden dependencies in 2010, population growth and associated water demand means that the need for water scarcity-related negotiation in transboundary basins could become a much greater issue in future. It is specifically the emergence of dependencies that introduces the need for negotiation. Treaties have an indirect effect on physical upstream water dependency by limiting or coordinating development of water resources locally and upstream. Treaty design can be innovated to include functions that improve the stability of the dependency and hence prevent scarcity from occurring. If decision makers cannot avoid a transition to scarcity (i.e. a brokenan open dependency), perhaps due to factors outside their control, then coordination can at least facilitate adaptation to cope with physical water scarcity. There are regions where physical water scarcity is to some extent expected – development is limited by water availability, such that fully utilising other resources (e.g. land) requires more water than is available. In addition, it should be pointed out that negotiation for rights to upstream inflows is only one strategy among many to try to meet water demand. In such cases, treaties can focus on mitigating the severity of impacts of scarcity.

Downstream areas with increasing water demand should be mindful that, in a way, they are 'choosing' to have to deal with dependencies and potential scarcity. If upstream withdrawals are stable, it can be argued that any conflict is effectively of their own making. Scarcity and dependency only emerge as problems when local demand crosses a threshold. This gives the impression that it is the local user that is responsible for the new problem, even though it may simply be that they are late to the game. On the other hand, if upstream withdrawals later increase, downstream regions might argue that they would not need to deal with scarcity, were it not for upstream actions. These interpretations of responsibility rely on the idea of precedence. The precedence paradigm is visible in prior appropriations regimes in USA, while negotiated allocations are arguably implemented by water markets in Australia and elsewhere (Grafton et al. 2011). Even in a negotiated approach, however, existing water needs and WWs are often taken into account, including at an international level – hybrid approaches are common. The UN Watercourses Convention of 1997 also refers to the no harm principle (article 7), which works in tandem with consideration as to

whether a given water use is reasonable and equitable (UN 2018). These examples illustrate the close connection between water allocation and different views about responsibility for transitions.

4.2 Relation to existing work

Our work distinguishes between dependency and scarcity and recognizes that dependency is primarily about potential for future scarcity, which transboundary cooperation aims to mitigate. To judge the importance of transboundary cooperation, it is more important to look at areas under no scarcity which are dependent on upstream inflows. The "brokenopen dependency" category (SNS) and SSS only include cases where institutional arrangements have failed to prevent scarcity from occurring. Our work, however, highlights that negotiation to avoid needing to cope with scarcity is only part of the issue. As demand increases, negotiation among riparian countries will eventually turn to discussion of intensity and frequency of scarcity, and the level of demand at which it occurs. Other existing work also distinguishes different types of rivers and basins to help understand why some riparian on international rivers have been able to successfully negotiate treaties and others have not – taking into account, for example, size of population, GDP, upstream-downstream relationship, and asymmetries in economic and political power among riparian states (Delbourg and Strobl 2012, Song and Whittington 2004, Wolf et al. 2003). Increasing water scarcity has been identified as a risk factor, but has not previously been systematically explored in terms of upstream dependency. Our dependency category typology complements this existing work, and relations to other typologies could be explored in future.

One of the main advantages of our analytical framework, compared to existing knowledge, is that it highlights the possible 'hidden' dependency of upstream water, which has not been assessed in these terms before. Previous studies on transboundary river basins identified clear evidence of the impacts of upstream water use to downstream water availability and water scarcity level (Al-Faraj and Scholz 2015, Munia et al. 2016, Nepal et al. 2014, Veldkamp et al. 2017). It has already been found that about 0.95–1.44 billion transboundary people are under stress because of local water use, while upstream water withdrawalsWWs increased the stress level by at least 1 percentage-point for 30-65 SBAs, affecting 0.29–1.13 billion people (Munia et al. 2016). Our analysis provides a different view of the issue by revealing that 386 million people (14% of the total transboundary population) are dependent on upstream water to avoid possible stress because of their own water demand and 306 million people (11% of the total transboundary population) are dependent on upstream water to avoid possible shortage (Table 3). Along with previous work, including broader discussion of hydro-political dependency (Brochmann et al. 2012, Giordano and Wolf 2003, Gleick 2014, Jägerskog and Zeitoun 2009, Mirumachi 2013, Mirumachi 2015, Wolf 1998, Wolf 2007, Wolf 1999), our analysis highlights the importance of local demand in causing scarcity and dependency. If local demand stays low enough and local water resources are sufficient to meet the demand, neither scarcity nor dependency occurs, and transboundary cooperation is not needed. This point has been made in existing literature (e.g. related to social construction of scarcity). These are fundamental ideas that are) but is not yet widely recognized in existing literature.

4.3 Limitations and future work

In our analysis, we used water withdrawalsWWs, which refer to the total amount of water withdrawn, but not necessarily consumed, by each sector; much of which is returned to the water environment where it may be available to be withdrawn again. The return flows from industrial and domestic sectors have been taken into account in PCR-GLOBWB and the recycling ratios for industrial and domestic sectors have been estimated and validated at a country level based on Wada et al. (2011a, 2014). However, in this paper, estimation of return flows is uncertain and they may not necessarily be available to downstream users, for example because of pollution, timing of the flows or infiltration to groundwater (Wada et al. 2011a). We therefore did not include return flows when calculating water stress, but those could be taken into account in future.

EFRs (i.e. environmental flow requirements) are important in transboundary water management. The stress indicator used in the analysis includes EFRs, assuming 30% of the water is needed to satisfy the EFRs (Falkenmark et al. 2007). We do not account for EFR in a spatially disaggregated way as the analysis is conducted in the SBA scale, where

spatially variable EFRs influences the dependency category, adding additional complexity to the transition map. EFRs are in any case a rather complex issue and not easy to quantify (Pastor et al. 2014). Global scale EFR methods could be criticized for not adequately capturing on the ground conditions –our treatment of environmental flows is fit for purpose given that our focus is on the resilience-based analytical framework.

Nuances of water availability were not taken into account in this analysis. Industrial or domestic pollution may occur in upstream parts of a basin, which might make water unusable for irrigation or domestic purposes (Thebo et al. 2017). Availability of green water has not been considered either. Green water increases the amount of locally available water by including soil water in addition to runoff. This affects scarcity, as the need for blue water should vary in response to changing green water availability, e.g. when there is less green water available, more blue water is needed. Decreases in availability of blue water (e.g. due to upstream withdrawals) may also push a region to use more green water. While green water is an important part of the local water availability, it does not affect inflows from upstream, by definition. Water is called "green water" when evapotranspiration occurs directly from rain or soil water, without runoff occurring. There is no additional effect on *avail.natural*, other than that on *avail.local*. Incorporating green water into the analysis will not affect *avail.actual* data either, as upstream withdrawals are in principle already accounted for in the water use model (including the effects of green water availability). The thresholds for both water shortage and stress are highly uncertain, so the effect of green water on the results is difficult to anticipate.

The main emphasis of the paper was the development of the analytical framework to understand the concept of upstream dependency from a resilience perspective. In this study, we provide the first attempt to link the dependency order to management strategies that could be taken to ease the possible scarcity situation. In future studies, in order to evaluate which transitions are actually plausible in future, the analytical framework could also be applied to water availability and demand scenarios based on future climate change scenarios (Representative Concentration Pathways, RCPs) (Van Vuuren et al. 2011) as well as Shared Social Pathway scenarios (SSP) (O'Neill et al. 2014). In doing so, the scarcity criteria could also be revisited, given the simplicity of the indicators and thresholds used here, as acknowledged in Sect. 2.2.2. The analysis can be integrated with the concept of 'adaptation tipping points (ATP)' to understand what strategies are needed (Kwadijk et al. 2010) to cope up with the scarcity status. Additional insights may be gained using other thresholds and/or other water scarcity indicators, such as food self-sufficiency (Gerten et al. 2011, Kummu et al. 2014) or sustainability of water withdrawals (Wada and Bierkens 2014). Future work could also quantify "distance" from a threshold, which would further address the distinction between how close these basins are to scarcity.

Our method was applied here at the basin scale, considering only international transboundary basins. It can, however, also be applied to understand the dependency at different scales to interpret, for example, more localised water dependencies, e.g. between states within countries (Garrick 2015). Moreover, instead of using average water availability, analysis can be performed using water availability for each year to capture variability. Thus, the evolution of scarcity and dependency of an SBA for a given climate can be categorized into different transition pathways along which a SBA progresses as its water demand or water availability changes. An early attempt at this was made in the "discussion paper" version of this article (Munia et al. 2017). In connecting to management, the relevance of frequency of scarcity could be further examined in order to provide a more meaningful distinction between scarcity that occurs every year and scarcity that occurs in some year: at what frequency of scarcity do management options need to be implemented permanently rather than only adaptively e.g. trading of temporary vs permanent water allocations (Bjornlund 2003).

5 Conclusions

In this paper, we aimed to explore the relationships between SBAs (i.e. sub-basin areas) of global transboundary river basins, in terms of dependency of downstream on upstream inflows to meet water demand and avoid shortage and stress. Transboundary water dependency was examined through changes in scarcity category across different types of water availability (runoff, naturalised discharge and actual discharge). We used the idea of regime shifts to illustrate the importance of dependency for basin management. The advantage of thinking in terms of thresholds is that we can reason about how scarcity and dependency might change in future. In this paper, we focused on the effect of local

demand and upstream water withdrawals, leaving possible changes in water availability, due to climate change for example, to future work. Understanding of the dependency category of an SBA has important policy implications regarding negotiation and redistribution of water among stakeholders, which may assist in improving water management in transboundary basins.

Acknowledgements

The work was financially supported by Academy of Finland funded project WASCO (grant no. 305471), Emil Aaltonen Foundation funded project 'eat-less-water', *Maa- ja vesitekniikan tuki ry*, and Academy of Finland SRC project 'Winland'. We highly appreciate the help and support of Prof Olli Varis and our other team members. We are grateful for the careful comments of editor Pieter van der Zaag, and reviewers Erik Mostert and Erik Ansink.

References

Al-Faraj, F. A. and Scholz, M.: Impact of upstream anthropogenic river regulation on downstream water availability in transboundary river watersheds, Int. J. Water Resour. Dev., 31, 28-49, 2015.

Allan, J. A.: The Middle East water question: Hydropolitics and the global economy, Ib Tauris, 2002.

Beck, L., Bernauer, T., Siegfried, T. and Böhmelt, T.: Implications of hydro-political dependency for international water cooperation and conflict: Insights from new data, Political Geography, 42, 23-33, 2014.

Bjornlund, H.: Farmer participation in markets for temporary and permanent water in southeastern Australia, Agric. Water Manage., 63, 57-76, 2003.

Brochmann, M. and Gleditsch, N.,P.: Shared rivers and conflict – A reconsideration, Political Geography, 31, 519-527, 2012.

Brochmann, M., Hensel, P. R. and Tir, J.: International river treaty effectiveness, in: International Studies Association Annual Meeting, San Diego, CA, 2012.

Brown, A. and Matlock, M. D.: A review of water scarcity indices and methodologies, White paper, 106, 19, 2011.

Degefu, D. M., He, W., Yuan, L. and Zhao, J. H.: Water allocation in transboundary river basins under water scarcity: a cooperative bargaining approach, Water Resour. Manage., 30, 4451-4466, 2016.

Delbourg, E. and Strobl, E.: Cooperation and conflict between upstream and downstream countries in African transboundary rivers thesis/masters, 2012.

Döll, P.: Impact of climate change and variability on irrigation requirements: A global perspective, Climatic Change, 54, 269-293, 2002.

Drieschova, A., Giordano, M. and Fischhendler, I.: Governance mechanisms to address flow variability in water treaties, Global Environ. Change, 18, 285-295, 2008.

Falkenmark, M., Berntell, A., Jägerskog, A., Lundqvist, J., Matz, M. and Tropp, H.: On the Verge of a New Water Scarcity: A Call for Good Governance and Human Ingenuity. SIWI Policy Brief., SIWI, Stockholm, 2007.

Garrick, D. E.: Water allocation in rivers under pressure: Water trading, transaction costs and transboundary governance in the Western US and Australia, Edward Elgar Publishing, 2015.

Gerten, D., Heinke, J., Hoff, H., Biemans, H., Fader, M. and Waha, K.: Global water availability and requirements for future food production, J. Hydrometeorol., 12, 885-899, 2011.

Giordano, M. A. and Wolf, T. A.: Sharing Waters: Post Rio International Water Management, Natural Resources Forum, 27, 163-171, 2003.

Gleick, P. H.: Water, Drought, Climate Change, and Conflict in Syria., Wea. Climate Soc., 6, 331-340, 2014.

Grafton, R. Q., Libecap, G., McGlennon, S., Landry, C. and O'Brien, B.: An integrated assessment of water markets: a cross-country comparison, Review of Environmental Economics and Policy, 5, 219-239, 2011.

Green, O., Cosens, B. and Garmestani, A.: Resilience in transboundary water governance: the Okavango River Basin, Ecology and Society, 18, 2013.

Hoekstra, A. Y. and Chapagain, A. K.: Globalization of water: Sharing the planet's freshwater resources, John Wiley & Sons, 2011.

Hoekstra, A. Y. and Mekonnen, M. M.: The water footprint of humanity, Proceedings of the National Academy of Sciences, 109, 3232-3237, 2012.

Jägerskog, A. and Zeitoun, M.: Getting Transboundary Water Right: Theory and Practice for Effective Cooperation., 25, SIWI, Stockholm, 2009.

Klein Goldewijk, K., Beusen, A. and Janssen, P.: Long-term dynamic modeling of global population and built-up area in a spatially explicit way: HYDE 3.1, The Holocene, 20, 565-573, 2010.

Kummu, M., Gerten, D., Heinke, J., Konzmann, M. and Varis, O.: Climate-driven interannual variability of water scarcity in food production potential: a global analysis, Hydrology and Earth System Sciences, 18, 447-461, 2014.

Kummu, M., Guillaume, J., De Moel, H., Eisner, S., Flörke, M., Porkka, M., Siebert, S., Veldkamp, T. and Ward, P. J.: The world's road to water scarcity: shortage and stress in the 20th century and pathways towards sustainability, Scientific reports, 6, 38495, 2016.

Kummu, M., Ward, P. J., de Moel, H. and Varis, O.: Is physical water scarcity a new phenomenon? Global assessment of water shortage over the last two millennia, Environmental Research Letters, 5, 034006, 2010.

Kwadijk, J. C., Haasnoot, M., Mulder, J. P., Hoogvliet, M., Jeuken, A., van der Krogt, Rob AA, van Oostrom, N. G., Schelfhout, H. A., van Velzen, E. H. and van Waveren, H.: Using adaptation tipping points to prepare for climate change and sea level rise: a case study in the Netherlands, Wiley interdisciplinary reviews: climate change, 1, 729-740, 2010.

Liu, J., Yang, H., Gosling, S. N., Kummu, M., Flörke, M., Pfister, S., Hanasaki, N., Wada, Y., Zhang, X. and Zheng, C.: Water scarcity assessments in the past, present, and future, Earth's Future, 5, 545-559, 2017.

Mehta, L.: The limits to scarcity: Contesting the politics of allocation, Routledge, 2013.

Mirumachi, N.: Transboundary water politics in the developing world, Routledge, 2015.

Mirumachi, N.: Securitising shared waters: an analysis of the hydropolitical context of the Tanakpur Barrage project between Nepal and India, The Geographical Journal, 179, 309-319, 2013.

Munia, H., Guillaume, J. H. A., Mirumachi, N., Wada, Y. and Kummu, M.: How downstream sub-basins depend on upstream inflows to avoid scarcity: typology and global analysis of transboundary rivers., Hydrol. Earth Syst. Sci. Discuss., 1-26, 2017.

Munia, H., Guillaume, J., Mirumachi, N., Porkka, M., Wada, Y. and Kummu, M.: Water stress in global transboundary river basins: significance of upstream water use on downstream stress, Environmental Research Letters, 11, 014002, 2016.

Natural Earth Admin 0 boundaries, access: July/7 2017.

Nepal, S., Flügel, W. A. and Shrestha, A. B.: Upstream-downstream linkages of hydrological processes in the Himalayan region, Ecological Processes, 3, 1-16, 2014.

O'Neill, B. C., Kriegler, E., Riahi, K., Ebi, K. L., Hallegatte, S., Carter, T. R., Mathur, R. and van Vuuren, D. P.: A new scenario framework for climate change research: the concept of shared socioeconomic pathways, Clim. Change, 122, 387-400, 2014.

Pastor, A. V., Ludwig, F., Biemans, H., Hoff, H. and Kabat, P.: Accounting for environmental flow requirements in global water assessments, Hydrol. Earth Syst. Sci., 18, 5041-5059, 2014.

Porkka, M., Kummu, M., Siebert, S. and Flörke, M.: The role of virtual water flows in physical water scarcity: the case of Central Asia, Int. J. Water Resour. Dev., 28, 453-474, 2012.

Scott, C. A., El-Naser, H., Hagan, R. E. and Hijazi, A.: Facing Water Scarcity in Jordan, Water Int., 28, 209-216, 2003.

Song, J. and Whittington, D.: Why have some countries on international rivers been successful negotiating treaties? A global perspective, Water Resour. Res., 40, 2004.

Thebo, A. L., Drechsel, P., Lambin, E. F. and Nelson, K. L.: A global, spatially-explicit assessment of irrigated croplands influenced by urban wastewater flows, Environmental Research Letters, 2017.

<u>UN</u> Watercourses Convention: <u>http://www.unwatercoursesconvention.org/the-convention/part-ii-general-principles/article-7-obligation-not-to-cause-significant-harm/7-1-2-significant-harm/, access: 13.3. 2018.</u>

Transboundary Waters: <u>http://www.unwater.org/publications/brochure-global-opening-1992-unece-water-</u> <u>convention/</u>, access: 9/4 2017.

Van Vuuren, D. P., Edmonds, J., Kainuma, M., Riahi, K., Thomson, A., Hibbard, K., Hurtt, G. C., Kram, T., Krey, V. and Lamarque, J.: The representative concentration pathways: an overview, Clim. Change, 109, 5, 2011.

Veldkamp, T. I. E., Wada, Y., Aerts, J C J H, Doll, P., Gosling, S. N., Liu, J., Masaki, Y., Oki, T., Ostberg, S., Pokhrel, Y., Satoh, Y., Kim, H. and Ward, P. J.: Water scarcity hotspots travel downstream due to human interventions in the 20th and 21st century, Nat. Commun., 8, 15697, 2017.

Wada, Y., van Beek, L P H and Bierkens, M. F. P.: Modelling global water stress of the recent past: on the relative importance of trends in water demand and climate variability, Hydrology and Earth System Sciences, 15, 3785-3808, 2011a.

Wada, Y., van Beek, L P H, Wanders, N. and Bierkens, M. F. P.: Human water consumption intensifies hydrological drought worldwide, Environmental Research Letters, 8, 1-14, 2013.

Wada, Y., Wisser, D. and Bierkens, M.: Global modeling of withdrawal, allocation and consumptive use of surface water and groundwater resources, Earth System Dynamics Discussions, 5, 15-40, 2014.

Wada, Y. and Bierkens, M. F.: Sustainability of global water use: past reconstruction and future projections, Environmental Research Letters, 9, 104003, 2014.

Wada, Y., Van Beek, L., Viviroli, D., Dürr, H. H., Weingartner, R. and Bierkens, M. F.: Global monthly water stress: 2. Water demand and severity of water stress, Water Resour. Res., 47, 2011b.

Walker, B., Holling, C. S., Carpenter, S. and Kinzig, A.: Resilience, adaptability and transformability in social-ecological systems, Ecology and society, 9, 2004.

Wolf, T.,A.: Conflict and cooperation along international waterways, Water Policy, 1, 251-265, 1998.

Wolf, A. T.: Shared waters: Conflict and cooperation. Annual Review of Environmental Resources, Annual Review of Environmental Resources, 32, 241-269, 2007.

Wolf, A. T., Yoffe, S. B. and Giordano, M.: International waters: identifying basins at risk, Water Policy, 5, 29-60, 2003.

Wolf, A. T.: Criteria for equitable allocations: the heart of international water conflict, in: Natural Resources Forum, 1999.