

Including Effects of Watershed Heterogeneity in the Curve Number Method Using Variable Initial Abstraction

Vijay P. Santikari, Lawrence C. Murdoch

5 Department of Environmental Engineering and Earth Sciences, Clemson University, Clemson, SC 29634, USA

Correspondence to: Vijay P. Santikari (vsantik@g.clemson.edu)

Abstract

The curve number (CN) method was developed more than half a century ago and is still used in many watershed/water quality models to estimate direct runoff from a rainfall event. Despite its popularity, the method is plagued by a conceptual problem where CN is assumed to be constant for a given set of watershed conditions, but many field observations show that CN decreases with event rainfall (P). Recent studies indicate that heterogeneity within the watershed is the cause of this behavior, but the governing mechanism remains poorly understood. This study shows that heterogeneity in initial abstraction, I_a , can be used to explain how CN varies with P . By conventional definition, I_a is equal to the cumulative rainfall before the onset of runoff, and is assumed to be constant for a given set of watershed conditions. Our analysis shows that the total storage in I_a (I_{aT}) is constant, but the effective I_a varies with P , and is equal to the filled portion of I_{aT} , which we call I_{aF} . CN calculated using I_{aF} varies with P similar to published field observations. This motivated modifications to the CN method, called Variable I_a Models (VIMs), which replace I_a with I_{aF} . VIMs were evaluated against Conventional Models CM0.2 ($\lambda = 0.2$) and CM λ (calibrated λ) in their ability to predict runoff data generated using a distributed parameter CN model. The performance of CM0.2 was the poorest whereas those of the VIMs were the best in predicting overall runoff and watershed heterogeneity. VIMs also predicted the runoff from smaller events better than the CMs, and eliminated the false prediction of zero-runoffs, which is a common shortcoming of the CMs. We conclude that including variable I_a accounts for heterogeneity and improves the performance of the CN method while retaining its simplicity.

1. Introduction

The estimation of runoff from a rainfall event is of primary importance in applied hydrology. It is necessary in the engineering design of small structures, post-event appraisals, environmental impact work, and other applications (Hawkins, 1993). One of the most popular techniques used for this purpose is the Curve Number method, which has been in use for more than half a century (D'Asaro and Grillone, 2012; Hawkins et al., 2008; Kent, 1968; Ponce and Hawkins, 1996; Rallison and Miller, 1982; Soil Conservation Service, 1956; Soil Conservation Service, 1972). The method uses a parameter called Curve Number (CN), which is assumed to depend mainly on land cover, soil types, and antecedent conditions within a watershed.

Curve Number varies spatially due to watershed heterogeneity, and temporally due to changes in soil moisture, land cover, temperature, and other processes (Hawkins et al., 2008; Ponce and Hawkins, 1996; Rallison and Miller, 1982). CN also varies with the magnitude (D'Asaro and Grillone, 2012; Hawkins, 1993; Hjelmfelt et al., 2001) and spatiotemporal distribution of rainfall (Hawkins et al., 2008; Van Mullem, 1997). When heterogeneity is known at sufficient detail, CN variation can be accounted by using a distributed parameter model, e.g. SWAT (Gassman et al., 2007). Otherwise this approach can introduce more parameters than can be reliably estimated from the available data (Soulis and Valiantzas, 2013), and can potentially cause large uncertainties in the predicted runoff. There are several ways to account for temporal variation of CN, each with its own advantages and shortcomings (Santikari, 2017). CN variation with the distribution of rainfall is usually ignored (Hawkins et al., 2008). CN method is most commonly applied as an event-scale lumped-parameter model, which is simple but also limited in its ability to account for the variations of CN. This diminishes the accuracy of its runoff predictions (e.g. Soulis and Valianzas, 2012).

The objective of this work is to improve the event-scale lumped-parameter application of the CN method by describing an approach for incorporating the spatiotemporal variations of CN. The investigation is described in two papers. In this paper, effects of spatial variation of CN (heterogeneity) at the watershed scale are analyzed. Insights gained from this analysis are used to create modified models that account for heterogeneity. The modified models are evaluated using the runoff generated by a distributed parameter model applied to a hypothetical heterogeneous watershed. In a companion paper (Santikari and Murdoch, 2018), the modified models are refined by including an approach that accounts for the temporal variation of CN using antecedent moisture. The refined models, which account for spatial and temporal variability, are then evaluated using data from real watersheds.

1.1. Background

The CN method assumes that a rainfall event produces runoff (Q) when the event rainfall (P) exceeds the initial abstraction (I_a). I_a includes interception storage (by tree canopy, roof tops and such), early infiltration, and surface depression storage. The effective rainfall, $P - I_a$, is partitioned between Q and further infiltration (F). This is given by mass balance as

$$P - I_a = F + Q \quad \forall \quad P \geq I_a \quad (1)$$

Both F and Q are zero when $P \leq I_a$, and both increase with P when $P > I_a$. It is assumed that F has an upper limit, which is referred to as the potential maximum retention (S). In other words, S is the total storage available for infiltration after the runoff begins.

The conceptual basis that defines the curve number method comes from the following assumption (Hawkins et al., 2008; NRCS, 2003; Ponce and Hawkins, 1996; Rallison and Miller, 1982; Woodward et al., 2002):

$$\frac{Q}{P - I_a} = \frac{F}{S} \quad (2)$$

i.e. the runoff coefficient (left hand side) is equal to the fraction of storage filled in S (right hand side). Equation (2) is developed using the reasoning that the equality holds at the end points ($P \leq I_a$ and $P \rightarrow \infty$) (Hawkins et al., 2008; Rallison and Miller, 1982; Woodward et al., 2002), and that the behavior of both ratios in the intermediate range is essentially the same (Figure 1).

5 When $P \leq I_a$, both Q and F are zero and therefore the ratios on either side of eq. (2) are zero. When $P > I_a$, both ratios increase with P , whereas their rate of increase diminishes. At the limit of $P \rightarrow \infty$, both ratios approach unity.




Figure 1. Presumed variation of the ratios in eq. (2) with event rainfall (P). Q is event runoff, I_a is initial abstraction, F is cumulative infiltration after runoff begins, and S is potential maximum retention (modified from Rallison and Miller (1982) Figure 2).

10

To eliminate the need for an independent estimation of I_a (Ponce and Hawkins, 1996; Rallison and Miller, 1982), it is assumed that

$$I_a = \lambda S \quad (3)$$

where λ is a dimensionless parameter called the initial abstraction ratio. Early field data suggested an optimum value of $\lambda = 0.2$ (Soil Conservation Service, 1956). However, more recent studies (Hawkins et al., 2008; Woodward et al., 2003) suggest that $\lambda = 0.05$ is more appropriate. Using eqs. (1), (2), and (3), I_a and F can be eliminated to give

15

$$Q = 0 \quad \forall \quad P \leq \lambda S \quad (4)$$

$$Q = \frac{[P - \lambda S]^2}{P + (1 - \lambda)S} \quad \forall \quad P > \lambda S$$

Since the value of λ is usually fixed (at 0.2 or 0.05), eq. (4) requires only one parameter, S , which varies within the range $0 \leq S \leq \infty$.

For convenience (Hawkins et al., 2008; Ponce and Hawkins, 1996), S (units in mm) is mapped on to a dimensionless parameter called the Curve Number (CN) as

$$5 \quad \text{CN} = \frac{25400}{254 + S} \quad (5)$$

so that CN is 100 when S is zero, but approaches zero as S approaches infinity. In practice, when $\lambda = 0.2$, CN ranges from around 30 (for vegetated surfaces with highly permeable soils) to close to 100 (for impermeable surfaces or soils) (USDA, 1986). Tabulated CN values for various land uses, soil types, and management scenarios are available in handbooks and manuals (NRCS, 2003; USDA, 1986). If a watershed has multiple land uses or soil types, typically, the CN is areally averaged.

10 CN can also be determined from field data by solving eq. (4) for S as

$$S = \frac{1}{2\lambda^2} \left[2\lambda P + (1 - \lambda)Q - \sqrt{(1 - \lambda)^2 Q^2 + 4\lambda P Q} \right] \quad (6)$$

and then using eq. (5). Conversely, when the CN of a watershed is known, Q can be estimated for a rainfall event using eqs. (4) and (5).

The curve number method is appealing because it is based on an intuitive concept [eq. (2)], relies on only one parameter, has a large body of literature (Hawkins et al., 2008), and a comprehensive database (NRCS, 2003; USDA, 1986). It has been included in many watershed/water quality models such as SWAT (Soil and Water Assessment Tool) (Neitsch S.L. et al., 2005), CREAMS (Chemicals, Runoff and Erosion from Agricultural Management Systems), GLEAMS (Groundwater Loading Effects of Agricultural Management Systems) (Knisel and Douglas-Mankin, 2012), AnnAGNPS (Annualized Agricultural Non-point Source Pollution Model) (Bingner et al., 2011), EPIC (Environmental Policy Integrated Climate), APEX (Agricultural Policy/Environmental Extender) (Wang et al., 2012), and HydroCAD (HydroCAD, 2015). A physically-based modeling framework, such as the diffusive-wave approximation for overland flow coupled with the Richard's equation for unsaturated subsurface flow, e.g. (Panday and Huyakorn, 2004), may improve accuracy and resolution of model predictions compared to the CN method, when the necessary input data, expertise, and computing resources are available. However, the CN method will likely remain popular for many applications in runoff modeling because of its ease of use, wide knowledge base, and less demand on computational resources than many physically-based models.

1.2. CN Variation with P

Curve Number is assumed to be a watershed property that depends on the current conditions, but it also varies with P [e.g. Figure 2(a) and 2(b)]. This behavior was also observed in several previous studies (D'Asaro and Grillone, 2012; Hawkins, 1993; Hjelmfelt et al., 2001; Soulis et al., 2009), and it appears to be a common phenomenon. Hawkins (1993) and D'Asaro and Grillone (2012) evaluated approximately 100 watersheds in a wide range of settings, and in 75% of the watersheds they observed, CN decreased with increasing P and asymptotically approached a constant value. Hawkins (1993) referred to this as *standard behavior*. In 20% of the watersheds, CN decreased with P but an asymptote was not attained within the range of the observed P . This was referred to as *complacent behavior*. In about 5% of the watersheds, the CN increased with P and asymptotically approached an apparent constant value. This behavior, referred to as *violent*, was often preceded by *complacent behavior* at smaller rainfalls. Hawkins (1993) hypothesized that the inverse relationship between CN and P may be due to some spurious correlation between them, or due to a bias that inherently results from the selective omission of data from small storm events that failed to produce runoff. The reasoning is that large rainfalls always produce runoff but small rainfalls produce runoff only under wet conditions, when the CN is large. Therefore, small CN values for small rainfalls go unrecorded.

In watersheds showing a *standard behavior*, CN was treated as an asymptotic function of P as

$$CN = CN_{\infty} + (100 - CN_{\infty}) e^{-kP} \quad (7)$$

where $CN = CN_{\infty}$ is the asymptote and k is a calibration parameter (Hawkins, 1993). CN_{∞} is the smallest possible value of CN for a watershed and is approached only at large values of P . To develop eq. (7), measured values of Q , ideally for a large range of values of P , are needed. The usual procedure involves “frequency matching” the data (Hawkins, 1993), i.e. sorting the values of P and Q separately, and pairing them according to their rank. CN for each pair is then calculated using eqs. (5) and (6). Frequency matching reduces the scatter of data points around the best fit curve in a CN vs. P plot.

A *standard behavior* of CN was also observed in two watersheds (BC5 and BC1) near Greenville, South Carolina, USA [Figure 2(a) and 2(b)]. In these watersheds, CN (calculated using $\lambda = 0.2$) decreased from 97 to 50 as P increased from 2 mm to 128 mm. The data was characterized by a modest scatter ($R^2 = 0.9$) about the best fit curve based on a quadratic function of P . Description of these watersheds is given by Santikari (2017) and Santikari and Murdoch (2018). The justification for using quadratic functions follows from the analysis of heterogeneity presented in Section-2.

The approach used in Figure 2(a) and 2(b) avoids the commonly used frequency matching, e.g. (Hawkins, 1993). Each CN value in the plot was calculated using the P - Q pair from the same storm event. Frequency matching would significantly reduce the scatter in the plot, but it would also downplay the importance of CN variation due to antecedent conditions. Reducing the scatter by accounting for antecedent conditions, e.g. using antecedent moisture (Mishra et al., 2006), is a better approach.

The hypotheses given by Hawkins (1993) are valid, but insufficient to explain the *standard* and *complacent behaviors*. It may be true that small rainfalls produce runoff only under wet (large CN) conditions and therefore only the large CN values are recorded. However, if one has a large enough sample of storms, some of the larger storms also must have occurred during wet conditions. For the larger storms, therefore, one would expect to see the whole spectrum of CN values ranging from the largest to the smallest. However, this is not the case. As P increases, the values of CN decrease consistently [Figure 2(a) and 2(b)].




Figure 2. Variation of CN ($\lambda = 0.2$) with P in watersheds (a) BC5, (b) BC1, near Greenville, SC. Variation of I_a with P in (c) BC5, (d) BC1 (see Santikari (2017) or Santikari and Murdoch (2018) for study area description). Best fit curves for I_a are quadratic functions of P with zero intercept. Corresponding best fit curves for CN were derived from those of I_a using eqs. (3) and (5).

1.3. Heterogeneity as a Cause of CN Variation with P

Soulis and Valiantzas (2012) hypothesized that the observed variation of CN with P in the *standard* and *complacent* cases is a consequence of watershed heterogeneity. They assumed a hypothetical heterogeneous watershed with two subareas characterized by different CNs. They then calculated the watershed runoff, for a range of values of P , as the area-weighted average of the runoffs from the subareas. Watershed CN calculated using this runoff varied with P akin to the *standard*

behavior. The shape of the synthetically generated CN vs. P curve could be matched with the observations by adjusting the areas of the subareas and their respective CNs. This idea can also be extended to multiple subareas so that the heterogeneity within a watershed can be represented more accurately. However, this could lead to problems of over-parameterization, non-uniqueness, and non-convergence as pointed out by Soulis and Valiantzas (2012).

- 5 In a later paper, Soulis and Valiantzas (2013) suggested using spatial information on land cover and soils to delineate the areal extent of subareas and constrain their respective CNs. This approach would reduce the number of calibrated parameters by half because it only requires the calibration of the CNs for the subareas. In essence, the multiple-subarea approach is similar to a distributed modeling approach that calculates the watershed runoff as the area-weighted average of the runoffs from the subareas, e.g. SWAT (Gassman et al., 2007). The approach used by Soulis and Valiantzas (2013) attempts to match the observed and simulated values of CN, whereas that used by SWAT attempts to match the observed and simulated values of Q . Since CN and Q are uniquely related for given values of P and λ , these approaches are equivalent. A major implication of the work of Soulis and Valiantzas (2013) is that a distributed modeling approach can account for the *standard* and *complacent behaviors* of CN.

- 15 Using a single value of CN independent of P in a heterogeneous watershed can cause a systematic error in Q , and lead to poor predictive ability of the method. This is because when CN is constant, Q may be underestimated for small P and overestimated for large P [e.g. Soulis and Valianzas (2012, 2013)]. This problem can be addressed either by treating CN as a function of P , e.g. asymptotic fitting (Hawkins, 1993), or by using a distributed modeling approach that accounts for heterogeneity in sufficient detail, e.g. SWAT (Gassman et al., 2007) or Soulis and Valianzas (2013). An understanding of the mechanism of how watershed heterogeneity leads to the variation of CN with P is also important. It could help in accounting for this variation without resorting to fine discretization or over-parameterization of the CN method. To accomplish this, an analysis of the effect of heterogeneity on I_a and S is performed, which can then be used to understand the effect on CN.

2. Reevaluation of Initial Abstraction

- 25 The quantities CN, I_a and S are considered to be the properties of a watershed that depend on current conditions. In usual practice, CN estimated for a certain set of conditions is applicable to any rainfall event occurring in those conditions irrespective of the magnitude of P . However, in every watershed evaluated by the previous studies (D'Asaro and Grillone, 2012; Hawkins, 1993) the CN varied with P . If so, since I_a and S are inversely related to CN [eqs. (3) and (5)], one can expect that they too vary with P but inversely to that of CN. The calculated values of I_a [using eqs. (3), (6), and $\lambda = 0.2$] for watersheds BC5 and BC1 near Greenville, SC, increase with P and appear to approach a constant at large values of P [Figure 2(c) and 2(d)]. A plot of S vs. P would be similar to the I_a vs. P plot, with the y -coordinate scaled by $1/\lambda$.

To evaluate the link between heterogeneity in I_a and its variation with P , we looked at how the effective I_a of a heterogeneous watershed is determined and whether it is affected by the magnitude of P . Our analysis shows that there is an inconsistency between the theoretical definition of I_a and its calculated value at the watershed scale. It also shows how heterogeneity can cause I_a to vary with P , and how this relates to variations of S and CN with P .

5 2.1. Problems with the Current Usage of I_a

By the theoretical definition of I_a , if runoff is detected in the hydrograph, it is assumed that I_a has been met for the watershed. Watersheds are heterogeneous combinations of various land use-soil-slope complexes. These are referred to as Hydrologic Response Units (HRUs) in SWAT (Gassman et al., 2007), and the same term is also used here. Each HRU is assumed to be homogeneous, and is characterized by representative values of CN (CN_i) and I_a (I_{ai}). During a rainfall event, the HRU with the smallest of the I_{ai} values will be the first to generate runoff. Assuming that this runoff reaches the watershed outlet, by definition, I_a of the watershed should be equal to the smallest of the I_{ai} values. This could even be zero if the watershed has surfaces such as open water bodies that cannot abstract the rainfall.

However, it is difficult to detect the exact moment of generation of runoff and determine the corresponding value of I_a , which is equal to the cumulative precipitation at that moment. There have been studies (Shi et al., 2009; Woodward et al., 2003) that tried to determine I_a from hydrographs. A problem with this approach is that there can be a time lag between runoff generation in headwaters and its detection at gauging station. Rainfall that occurs during this time lag is also included in I_a , leading to its overestimation. Another possible approach would be to collect observations from a large number of rainfall events and take I_a to be equal to the smallest P that produced runoff. This would eliminate the problem with the lag time, but Q needs to be insignificant to reduce the error in I_a . It should also be noted that I_a determined this way is only representative of the antecedent conditions of the smallest event that produced runoff.

It may be difficult to measure I_a directly, but it can be calculated for any event using eqs. (6) and (3). However, in medium to large rainfall events, even the HRUs with larger values of I_{ai} will contribute to Q . Therefore, the calculated value of I_a in these events will also be influenced by the larger values of I_{ai} . So, the calculated I_a tends to be greater than the smallest of the I_{ai} values. Moreover, it can be expected to increase with P as increasingly larger rainfalls generate runoff from HRUs with increasingly larger values of I_{ai} . Thus, there is an inconsistency between the definition of I_a and its calculated value at the watershed scale.

2.1.1. Spatial-scale effect on λ

Strictly adhering to the definition of I_a at the watershed scale may also cause a spatial-scale effect on λ . Let us refer to the CN of the watershed as CN_w , and I_a as I_{aw} . One of the common ways to determine CN_w is to calculate it as the area-weighted average of the CN_i values (NRCS, 2003) as

$$CN_w = \sum_{i=1}^n a_i CN_i \quad (8)$$

where a_i is the fractional area of the i^{th} HRU. Note that the fractional areas must add up to unity. By definition, I_{aW} is equal to the smallest of the I_{ai} values. Therefore, if $I_{a1} < I_{a2} < \dots < I_{an}$ then

$$I_{aW} = I_{a1} \quad (9)$$

5 From equations (3) and (5) it can be shown that CN and I_a are related as

$$CN = \frac{25400}{254 + \left(\frac{I_a}{\lambda}\right)} \quad (10)$$

If all the HRUs are assumed to have the same $\lambda = \lambda_i$, eqs. (8), (9) and (10) lead to

$$\begin{aligned} CN_1 &> CN_2 > \dots > CN_n \\ CN_w &< CN_1 \\ \frac{I_{aW}}{\lambda_w} &> \frac{I_{a1}}{\lambda_i} \\ \lambda_w &< \lambda_i \end{aligned} \quad (11)$$


10 where λ_w is the effective initial abstraction ratio of the watershed. Therefore, if λ is assumed to be the same among the component HRUs, it will have a smaller value at the watershed scale. This implies that λ decreases with increasing spatial-scale. Therefore setting λ constant, equal to 0.2 or 0.05, for all the spatial scales contradicts the definition of I_a . In any case, it is probably more accurate to calculate runoff at the HRU scale (Q_i) and take the area-weighted average of Q_i values, rather than take the area-weighted average of the CN_i values and calculate Q at the watershed scale. It is also more appropriate because Q is runoff per unit area whereas CN is a dimensionless index variable.

15 The inconsistencies in the usage of I_a are a direct result of heterogeneity in a watershed. Moreover, heterogeneity also appears to be responsible for the variation of I_{aW} with P [Figure 2(c) and 2(d)]. To verify this, a relationship between I_{aW} and the magnitude and areal distribution of I_{ai} values needs to be developed.

2.2. I_a in a Heterogeneous Watershed

20 Consider a watershed with four HRUs mainly characterized by their land use types viz. open waterbody (I_{a0}), urban area (I_{a1}), park (I_{a2}), and forest (I_{a3}) [Figure 3(a)], such that $I_{a0} = 0 < I_{a1} < I_{a2} < I_{a3}$. An open waterbody generates runoff during every

rainfall event. Other land use types generate runoff depending on the magnitude of the rainfall, with land uses of larger I_{ai} values requiring larger magnitudes. If each land use type is assumed to be directly connected to the drainage network, the number of land use types contributing to the runoff, in other words the runoff contributing area, increases with rainfall. This process can be conceptualized by representing the storage distribution of I_a as a series of bins where each bin corresponds to a HRU [Figure 3(b)]. The height and the width of a bin are given by I_{ai} and a_i , respectively, and all bins have unit thickness. In a rainfall event, only the bins with $I_{ai} \leq P$ are fully filled and contribute to runoff, whereas the others are partially filled and do not contribute to runoff. The total amount of filled storage in I_a [shaded area in Figure 3(b)] increases with P until it reaches a constant value when all the bins are fully filled and the whole watershed is contributing to the runoff.



10 **Figure 3.** Spatial distribution of I_a in a heterogeneous watershed (a) I_{ai} values of various HRUs mainly characterized by their land use types ($I_{a0} = 0 < I_{a1} < I_{a2} < I_{a3}$) (b) conceptual model in which each HRU is represented by a bin with height = I_{ai} , width = a_i , and unit thickness; shaded area indicates the filled portion during an event with rainfall = P .

Consider a general case of a heterogeneous watershed with $n + 1$ HRUs such that

$$I_{a0} = 0 < I_{a1} < I_{a2} < \dots < I_{an} \quad (12)$$

where I_{a0} represents open water bodies and other surfaces that cannot abstract rainfall. The areal average of the total initial abstraction (I_{aT}) is given by

$$I_{aT} = \sum_{i=0}^n a_i I_{ai} \quad (13)$$

In a rainfall event, all the HRUs with $I_{ai} \leq P$ have their initial abstractions completely filled while the others are partially filled. Just by analyzing the runoff for that event, it is impossible to quantify the magnitudes of I_{ai} in HRUs that are partially filled. Because these HRUs have not contributed to the runoff, all that can be said is that their I_{ai} values are greater than P , but their magnitudes remain unknown. However, the information on the magnitudes of I_{ai} in HRUs that are completely filled should be present in the runoff data. In other words, it takes larger rainfalls to fill larger values of I_{ai} and gather information about their magnitude.

Then what is the effective initial abstraction of the watershed for a given rainfall event? Consider an event where the rainfall falls within the range: $I_{am} \leq P < I_{a(m+1)}$. HRUs with $I_{ai} \leq I_{am}$ have their initial abstractions completely filled and produce runoff, whereas HRUs with $I_{ai} \geq I_{a(m+1)}$ have their initial abstractions partially filled up to the level of P and do not produce runoff. The areal average of the filled portion (includes completely filled as well as partially filled HRUs) of the initial abstraction is given by

$$I_{aF} = \sum_{i=0}^m a_i I_{ai} + \left(1 - \sum_{i=0}^m a_i\right) P \quad (14)$$

The first term on the right-hand side of eq. (14) represents completely filled HRUs. The second term represents partially filled HRUs, all of which are filled to the level of P . Note that I_{aT} is the areal average of total initial abstraction, whereas I_{aF} is the areal average of the filled portion. Therefore,

$$\begin{aligned} I_{aF} &< I_{aT} && \forall && P < I_{an} \\ I_{aF} &= I_{aT} && \forall && P \geq I_{an} \end{aligned} \quad (15)$$

The conceptual model presented in Figure 3, and in eqs. (14) and (15) is intuitively appealing, and also hints at the possibility that I_{aW} may be equal to I_{aF} . This is because I_{aF} increases with P and approaches a constant value (I_{aT}), similar to the

observations in Figure 2(c) and 2(d). Eq. (14) is also consistent with a distributed parameter model application of the CN method as described in Section-3.

2.3. Variation of I_{aF} with P

To investigate the variation of I_{aF} with P , eqs. (14) and (15) are applied to the scenario presented in Figure 3, where $n = 3$. A plot of I_{aF} vs. P (Figure 4) shows that I_{aF} increases with P and becomes constant ($I_{aF} = I_{aT}$) at large values of P ($P \geq I_{a3}$). The kink-points joining the line segments occur when the initial abstraction of one of the HRUs becomes completely filled. At these points, P is equal to one of the I_{ai} values. In between these points ($I_{am} < P < I_{a(m+1)}$), the relationship between I_{aF} and P is linear with a slope of $\left(1 - \sum_{i=0}^m a_i\right)$. The slope abruptly changes across the kink-points. It decreases with m , and becomes zero when $m = n$. The maximum value the slope can take is unity. This occurs with the line segment passing through the origin, when HRUs with zero initial abstraction are absent (i.e. $a_0 = 0$). When these HRUs are present, however, the origin itself is a kink-point where the slope abruptly jumps from unity to $1 - a_0$.




Figure 4. Variation of I_{aF} [eqs.(14) and (15)] with P for the scenario presented in Figure 3.

The analysis presented so far represents a discrete case where each HRU is homogeneous and has a finite area. The values of I_{ai} vary discontinuously across the HRUs. Their areal distribution can be represented by a plot of a_i vs. I_a [Figure 5(a)]. The smaller the area of HRUs, the more numerous they are, and the more accurate is the representation of the heterogeneity within the watershed. The most ideal representation would occur when the HRUs shrink to points. Then the values of I_{ai} within the watershed vary continuously and therefore can be represented by a probabilistic distribution of areal occurrence [Figure 5(b)]. It is impractical to characterize the watershed at such fine scale, but it is worth understanding the properties of the initial abstraction at the finest resolution first, and then making assumptions or simplifications later to suit the practical needs.




Figure 5. Representing areal distribution of I_a within a watershed (a) discrete case (b) continuous case.

For the case of a continuous distribution of I_a , eq. (14) takes the form

$$I_{aF} = \int_0^P I_a a(I_a) dI_a + \left(1 - \int_0^P a(I_a) dI_a \right) P \quad (16)$$

- 5 where $a(I_a)$ is the probability density function of areal occurrence of I_a . The fractional area with initial abstraction = I_a is given by $a(I_a) dI_a$. The upper limit of the integrals is set to P because the last initial abstraction to completely fill up would be equal to P . The areal average of total initial abstraction, I_{aT} , is given by

$$I_{aT} = \int_0^{I_{a,max}} I_a a(I_a) dI_a \quad (17)$$

where $I_{a,max}$ is the maximum value of I_a within the watershed. Thus, I_{aT} is equal to the mean of the distribution [Figure 5(b)].

- 10 Eq. (15) then becomes

$$\begin{aligned} I_{aF} < I_{aT} & \quad \forall \quad P < I_{a,max} \\ I_{aF} = I_{aT} & \quad \forall \quad P \geq I_{a,max} \end{aligned} \quad (18)$$




Figure 6. Variation of I_{aF} with P for a continuous distribution such as the one shown in Figure 5(b)

Unlike the discrete case, the slope of the I_{aF} curve for the continuous case decreases smoothly with increasing P (Figure 6). This is because the line segments in the discrete case (Figure 4) shrink to points in the continuous case. It follows from eq. (16) that

$$\left. \frac{dI_{aF}}{dP} \right|_{P=0} = 1$$

$$\left. \frac{dI_{aF}}{dP} \right|_{P \geq I_{a,max}} = 0$$
(19)

Thus, the I_{aF} curve is bounded by a line of slope = 1 passing through the origin, and a line of slope = 0 with the intercept equal to I_{aT} (Figure 6). The line of slope = 1 is referred to as the no-runoff line because along this line $I_{aF} = P$. When the whole watershed is represented by a single HRU, the I_{aF} curve coincides with the no-runoff line until $I_{aF} = I_{aT}$. A comparison of Figure 6 to Figure 2(c) and 2(d) strengthens the case that I_{aW} is equal to I_{aF} .

2.4. Variation of CN_W with P

Let us hypothesize that $I_{aW} = I_{aF}$, i.e. the effective I_a of a watershed is equal to the area-weighted average of the filled portion of the initial abstraction. Then, if eq. (10) is written for CN_W , I_a can be replaced by I_{aF} . Substituting eq. (16) in eq. (10) gives CN_W as a function of P . When plotted against P , CN_W starts at 100 when $P = 0$, and then decreases with increasing P (Figure 7).




Figure 7. CN_W as a function of P when I_{aW} is assumed to be equal to I_{aF} (shown in Figure 6).

Differentiating eq. (10) and using eq. (19) gives

5

$$\begin{aligned} \left. \frac{d(CN_W)}{dP} \right|_{P=0} &= -\frac{10}{\lambda} \\ \left. \frac{d(CN_W)}{dP} \right|_{P \geq I_{a,\max}} &= 0 \end{aligned} \quad (20)$$

where the constant 10 has units of 1/in. Thus the CN_W vs. P curve is at its steepest at $P = 0$ and flattens with increasing P , and becomes constant when $P \geq I_{a,\max}$. This constant, CN_T , is the smallest value CN_W can take and corresponds to the case $I_{aF} = I_{aT}$, when the initial abstractions of all the HRUs are fully filled. CN_W as a function of P is bounded by a curve corresponding to the condition $P = I_{aF}$, the no-runoff line, and a line of slope = 0 with the intercept equal to CN_T (Figure 7).

10

The shape of the CN_W vs. P curve (Figure 7) generated using eqs. (10) and (16) is quite similar to the best-fit curves from field observations [Figure 2(a) and 2(b)]. Nearly 95% of the watersheds evaluated in the previous studies (D'Asaro and Grillone, 2012; Hawkins, 1993) also had responses identical to Figure 7, supporting the hypothesis that $I_{aW} = I_{aF}$. Thus, as also concluded by Soulis and Valiantzas (2012, 2013), the observed *complacent* and *standard behaviors* are caused by the inevitable presence of heterogeneity in a watershed. Moreover, *complacent behavior* appears to be a special case of *standard behavior* (Soulis and Valiantzas, 2012), where observations from larger rainfalls are unavailable. Therefore, it is probably more appropriate to refer to any “CN decreasing with P ” trend as *standard behavior*. It also shows that assuming a partial source area whenever a *complacent behavior* is observed (D'Asaro and Grillone, 2012; D'Asaro and Grillone, 2015) can be misleading.

15





2.5. I_{aF} and CN_W Curves for Various Distributions of I_a

5 The functional form of $a(I_a)$ defines the areal distribution of I_a within a watershed. We considered idealized functional forms of $a(I_a)$ that correspond to uniform, normal, triangular, and bi-modal distributions (Table 1). In each $a(I_a)$, the maximum or other key value was constrained so that the total area under the distribution was unity. For example, the y-coordinate of the apex in the triangular distribution must be equal to $2 / I_{a,max}$ (Table 1). In the case of normal distribution, however, the area under the curve is unity only when the limits are infinite. Therefore, a standard deviation (σ) much less than $I_{a,max}$ was used so that the area under the curve within the range $0 \leq I_a \leq I_{a,max}$ is approximately equal to unity.

10 For each distribution, the corresponding functional form of I_{aF} was determined using eq. (16) and the results are presented in Table 1. For the general case of $a(I_a)$ as a polynomial, the corresponding I_{aF} is a polynomial two degrees higher than $a(I_a)$. For the normal distribution, I_{aF} is a combination of Gaussian and Error functions (Table 1).

For the purpose of comparison, symmetrical versions of the distributions were considered such that all of them have the same minimum, mean, and maximum values of I_a [Figure 8(a)]. The minimum value of I_a was set to zero and the maximum value was $I_{a,max}$. Therefore, the mean for all the distributions was $I_{a,max} / 2$.

Table 1. Functional forms of $a(I_a)$ and I_{af} for various synthetic distributions

Distribution	Graph	$a(I_a)$	I_{af}
Uniform		$\frac{1}{I_{a,\max}}$	$P - \frac{P^2}{2I_{a,\max}}$
Normal		$\frac{1}{\sigma\sqrt{2\pi}} e^{-(I_a - \mu)^2 / (2\sigma^2)}$	$P - \frac{\sigma}{\sqrt{2\pi}} \left[e^{-(P-\mu)^2 / (2\sigma^2)} - e^{-\mu^2 / (2\sigma^2)} \right] - \frac{(P-\mu)}{2} \left[\operatorname{erf}\left(\frac{P-\mu}{\sqrt{2}\sigma}\right) + \operatorname{erf}\left(\frac{\mu}{\sqrt{2}\sigma}\right) \right]$
Triangular		$\frac{2I_a}{aI_{a,\max}} \text{ if } I_a \leq a$ $\frac{2}{(I_{a,\max} - a)} \left(1 - \frac{I_a}{I_{a,\max}} \right) \text{ if } a < I_a$	$P - \frac{P^3}{3aI_{a,\max}} \text{ if } P \leq a$ $\frac{1}{(I_{a,\max} - a)} \left[-\frac{a^2}{3} + I_{a,\max}P - P^2 + \frac{P^3}{3I_{a,\max}} \right] \text{ if } a < P$
Bimodal		$u \text{ if } I_a \leq a$ $0 \text{ if } a < I_a < b$ $v \text{ if } b \leq I_a$	$P - \frac{uP^2}{2} \text{ if } P \leq a$ $\frac{ua^2}{2} + (1-ua)P \text{ if } a < P < b$ $\frac{(ua^2 - vb^2)}{2} + (1-ua + vb)P - \frac{vP^2}{2} \text{ if } b \leq P$




Figure 8. (a) Various symmetrical distributions of I_a with the same minimum (zero), mean ($I_{a,max}/2$), and maximum ($I_{a,max}$), (b) the corresponding I_{aF} curves calculated using eq. (16), (c) the corresponding CN_W curves calculated using eq. (10).

The kurtosis (peakedness) of $a(I_a)$ has a major influence on the shapes of I_{aF} and CN_W plotted as functions of P (Figure 8). The normal distribution has the greatest kurtosis whereas the bimodal distribution has the least. As the kurtosis decreases, the I_{aF} and CN_W curves deviate further from the bounding lines (Figure 8). When there is a gap in the distribution, as in the case of the bimodal distribution, the corresponding I_{aF} curve is linear for the range spanning the gap. This is consistent with the discrete case where I_{aF} was represented by line segments for the gaps in between the discrete values of I_{ai} (Figure 4).

Skewness of $a(I_a)$ also affects I_{aF} , and this is illustrated by an idealized case where an initially uniform distribution is positively skewed [Figure 9(a) and 9(b)]. The mean of $a(I_a)$, which is equal to I_{aT} [eq. (17)], decreases with increasing positive skewness. This is important because a land use change such as conversion of forest to urban land is expected to increase the positive skewness (i.e. more low values of I_a). During the conversion, $I_{a,max}$ remains unchanged while some forested land remains. When the entire forest is converted, $I_{a,max}$ drops to a lower value.

The analysis also shows that a watershed cannot be characterized or compared with other watersheds using a single value of CN [such as CN_{∞} used in asymptotic fitting, eq. (7)]. Depending on the distribution of heterogeneity, the relative runoff potential of a watershed can be P dependent. This is illustrated by considering two uniform distributions, uni1 and uni2, where uni2 has a narrower range and a smaller mean than uni1 [Figure 9(c)]. For smaller values of P , $I_{aF,uni1} < I_{aF,uni2}$ [Figure 9(d)], and therefore $CN_{W,uni1} > CN_{W,uni2}$. However, for larger values of P , the converse is true. Thus, the watershed with uni1 generates more runoff for smaller values of P , whereas the watershed with uni2 generates more runoff for larger values of P .




Figure 9. Effect of skewness, mean, and range of $a(l_a)$ on I_{aF} (a) uniform, uni (solid), and two positively skewed distributions, skew1 (dashed) and skew2 (dash dot dot) (b) I_{aF} as a function of P for the distributions shown in 9a (c) uniform distributions uni1 (solid) and uni2 (dashed) where uni2 has a narrower range of values of l_a and a smaller mean than uni1 (d) I_{aF} as a function of P for the distributions shown in 9c.

10

3. Effect of Heterogeneity on S

Similar to the case of I_a , the presence of heterogeneity also causes the effective S of a watershed (S_W) to vary with P . Functional form of S_W depends not only on the potential maximum retentions of the HRUs (values of S_i) but also on the values of I_{ai} . S_W can be estimated using eq. (2) if the quantities I_{aW} , Q_W , and F_W are known. A distributed modeling approach can be used to calculate these quantities for a heterogeneous watershed. Distributed CN models, e.g. SWAT (Gassman et al., 2007), commonly calculate Q_W as the area-weighted average of Q_i s, and this assumption can also be extended to F_W . Thus,

$$\begin{aligned} Q_W &= \sum_{i=0}^n a_i Q_i \\ F_W &= \sum_{i=0}^n a_i F_i \end{aligned} \quad (21)$$

Using eq. (21) and applying mass balance [eq. (1)] at watershed and HRU scales gives eq. (14) for I_{aW} . This shows that I_{aW} calculated using a distributed model is equal to I_{aF} .

10 Writing an expression for S_W in terms of I_{ai} and S_i values for a general case of a heterogeneous watershed is cumbersome. Therefore, it is only presented graphically for an example of a heterogeneous watershed. However, an expression for S_W can be presented in a compact form for a special case where all the values of I_{ai} are zero as

$$\text{if } I_{ai} = 0 \quad \forall \quad i \in \{0, 1, \dots, n\} \quad (22)$$

$$S_W = \frac{\sum_{i=0}^n \frac{a_i S_i}{P + S_i}}{\sum_{i=0}^n \frac{a_i}{P + S_i}}$$

Thus, S_W varies from the area-weighted harmonic mean $\left(\sum_{i=0}^n \frac{a_i}{S_i} \right)^{-1}$ when $P = 0$, to the area-weighted arithmetic mean

15 $\left(\sum_{i=0}^n a_i S_i \right)$ when $P \gg S$.

To illustrate the effect of heterogeneity on S_W , an example watershed with the storage distribution shown in (Table 2) was considered. The variation of S_W with P was analyzed for the cases of $\lambda_i = 0$ and $\lambda_i = 0.2$ (Figure 10). In both cases, S_W increases with P and approaches the area-weighted arithmetic mean, S_∞ , for large values of P . In the case of $\lambda_i = 0$, the slope of the curve

is maximum at the origin, and decreases monotonically with P . In case of $\lambda_i = 0.2$, however, the slope is zero at the origin and generally increases with P until $P \approx I_{an} = 40$ mm ($P \approx I_{a,\max}$ for the continuous case), where it reaches its maximum value. Thereafter the slope decreases monotonically with P , giving an S-shaped curve. In other words, the slope generally increases with P until the entire watershed area contributes to the runoff, and decreases thereafter.

5 **Table 2.** Storage distribution in a hypothetical heterogeneous watershed used to illustrate the variation of S_W with P .

HRU	a_i	S_i (mm)
0	0.05	0
1	0.20	50
2	0.35	100
3	0.25	150
4	0.15	200




Figure 10. Variation of S_W with P in a heterogeneous watershed with the storage distribution shown in Table 2.

The similarities between I_{aW} and S_W are that they both increase with P and have an upper limit equal to the area-weighted arithmetic mean of their respective components. The difference is that I_{aW} reaches its upper limit of I_{aT} for a finite value of P ($P = I_{an}$ or $P = I_{a,\max}$), whereas S_W requires large values of P ($P \gg S$) to reach its upper limit of S_∞ . Moreover, S_W vs. P is an S-

shaped curve when $\lambda_i > 0$. This shows that I_{aW} and S_W are not proportional, i.e. λ_W is not a constant even though λ_i values are assumed to be equal and constant.

4. Application

5 The analysis from previous sections shows that I_{aW} and S_W are functions of P , and gives their functional forms. Incorporating these functions in the lumped parameter application can potentially improve the performance of the CN method.

4.1. I_{aW} as a function of P

10 The distributed parameter modeling approach, eq. (21) with the application of mass balance [eq. (1)] at watershed and HRU scales, shows that $I_{aW} = I_{aF}$. I_{aF} is given by eq. (14) for the discrete case and eq. (16) for the continuous case. All the distributions in Table 1, except the normal distribution, gave a zero-intercept polynomial for I_{aF} . Therefore, using a quadratic function of the form

$$\begin{aligned} I_{aW} &= c_1 P - c_2 P^2 & \forall P \leq I_{a,\max} \\ I_{aW} = I_{aT} &= c_1 (I_{a,\max}) - c_2 (I_{a,\max})^2 & \forall P > I_{a,\max} \end{aligned} \quad (23)$$

is an efficient way to describe I_{aW} . In eq. (23), c_1 and c_2 are calibration parameters such that $0 \leq c_1 \leq 1$ and $c_2 \geq 0$. Since the slope of I_{aW} is zero at $P = I_{a,\max}$ [eq. (19)], it follows from eq. (23) that

$$\begin{aligned} I_{a,\max} &= \frac{c_1}{2c_2} \\ I_{aT} &= \frac{c_1^2}{4c_2} \end{aligned} \quad (24)$$

15 Similarly, the slope of I_{aW} is unity at $P = 0$ so c_1 should be unity. However, it was kept as a free parameter in eq. (23) to allow for the approximation of piecewise functions (e.g. I_{aF} for triangular and bimodal distributions in Table 1). Moreover, the analysis for the discrete case shows that when HRUs with zero initial abstraction are present, the origin is a kink-point where the slope abruptly jumps from unity to $1 - a_0$. To avoid over-parameterization of the model, a polynomial of degree > 2 for I_{aW} was not considered.

20 4.2. S_W as a function of P

The sigmoid shaped function of S_W , with the conditions that $S_W = 0$ when $P = 0$ and that the maximum slope occurs at $P = I_{a,\max}$, requires at least two parameters to describe it. However, this along with eq. (23) would also increase the number of calibrated parameters in the CN method, increasing its complexity and potentially causing non-uniqueness. A relatively simple approach

is to assume that S_W is constant similar to the conventional CN method. Another approach is to assume that S_W is proportional to I_{aW} , i.e. eq. (3) is applicable for a heterogeneous watershed.

5 Here the emphasis is placed on treating I_{aW} as a function of P while offering some flexibility on how S_W is treated. This is because the variation of I_{aW} with P had a significant impact on the model performance, whereas including the variation of S_W with P showed only marginal or no improvement. This may be because I_{aW} is a component of mass balance [eq. (1)] while S_W is not. F_W , which is the filled portion of S_W , is a component of mass balance and varies with P even if S_W is assumed to be a constant. Therefore, to maintain the simplicity of the CN method and avoid the problems of over-parameterization and non-uniqueness, modeling the sigmoid-shaped function of S_W is omitted.

4.3. Lumped Parameter Models

10 Lumped parameter application of the CN method was modified by treating I_{aW} as a function of P as described in the previous section. Modified lumped parameter CN models were evaluated by comparing their performance with that of the conventional lumped parameter CN models.

4.3.1. Conventional Models (CMs)

15 Conventional CN models are defined by eqs. (1) through (5), and by the assumption that I_{aW} and S_W are independent of P . In this study two types of conventional models, referred to as CM0.2 and CM λ , were used. In CM0.2, λ_W was fixed at 0.2, and in CM λ , λ_W was determined by calibration. Thus CM0.2 had one free parameter, S_W , whereas CM λ had two free parameters, λ_W and S_W .

4.3.2. Variable Initial Abstraction Models (VIMs)

20 VIMs are defined by eqs. (1), (2), (4), (5), and (23), and they have three free parameters. If S_W is assumed to be independent of P , then the model requires calibration of c_1 , c_2 , and S_W , and is referred to as VIMS. If eq. (3) is also included, then the model requires calibration of c_1 , c_2 , and λ_W , and is referred to as VIM λ .

5. Evaluation

25 Lumped parameter models described in the previous section were evaluated in their ability to predict runoff and account for watershed heterogeneity. Accounting for heterogeneity means that the model accurately predicts I_{aW} and S_W , and runoff from smaller events. This is because (i) I_{aW} and S_W as functions of P are directly related to heterogeneity, and (ii) inability to account for their variation with P causes under-estimation of runoff in smaller events.

Evaluation of lumped parameter models requires the data for I_{aW} , Q_W and S_W . This is generated using a distributed parameter model application of the CN method. The assumption is that a distributed parameter model accounts for heterogeneity, and therefore its estimates of I_{aW} , Q_W and S_W are accurate.

5.1. Distributed Parameter Model

5 In a distributed parameter model, eqs. (1) through (5) are applicable at the HRU scale, with the assumption that I_{ai} and S_i are independent of P . Once Q_i and F_i are calculated for each HRU, watershed scale quantities I_{aW} , Q_W , F_W and S_W are calculated using eqs. (14), (21), and (2).

The distributed parameter model was applied to an idealized synthetic watershed with the storage distribution shown in Table 2, for the cases of $\lambda_i = 0, 0.2, \text{ and } 0.5$. A range of values of P were synthetically generated such that they vary lognormally
10 from 0.1 mm to 200 mm with a median of 8 mm. For each rainfall event, I_{aW} , Q_W , F_W and S_W were calculated, and used in the evaluation of the lumped parameter models.

The reason for using a synthetic watershed here is that the heterogeneity can be precisely defined and used to evaluate the predictions of heterogeneity by the lumped parameter models. In real watersheds, the heterogeneity has to be determined by calibration, and there can be non-uniqueness when multiple HRUs are present. Application of these modified models to data
15 from real watersheds is discussed by Santikari (2017) and Santikari and Murdoch (2018).

5.2. Model Evaluation Criteria

Each lumped parameter model was calibrated by minimizing the sum of the squared residuals between its predicted runoff (Q_W) and the baseline from the distributed parameter model. All the models were evaluated using the Nash-Sutcliffe efficiency parameter (NSE), the standard error of estimate (SEE), and the percent bias (PB) (McCuen, 2003; Moriasi et al., 2007). NSE
20 can vary from $-\infty$ to 1. The calculations and observations are exactly equal when $NSE = 1$. The calculations are only as good as the average observation when $NSE = 0$. SEE is the root-mean-square residual adjusted to the degrees of freedom (Santikari, 2017). A smaller SEE indicates a better performance, and its ideal value is zero. PB indicates whether the model is over (PB < 0) or under-predicting (PB > 0) on average. The optimal value for PB is zero.

NSE values were calculated for the model predictions of runoff (NSE_Q), initial abstraction (NSE_{Ia}), potential maximum retention (NSE_S), and runoff from events with P less than the median value (NSE_{Q50}). Relative NSE, rNSE (Krause et al., 2005), was used instead of NSE when the latter was strongly influenced by larger events. PB values were calculated for runoff
25 from all the events (PB_Q) and runoff from events with P less than the median value (PB_{Q50}). SEE was calculated for runoff from all the events (SEE_Q).

5 NSE_{I_a} and NSE_S indicate how accurately a lumped parameter model predicts the watershed heterogeneity. NSE_Q , SEE_Q , and PB_Q reflect the overall accuracy in a model prediction of runoff from all the events, whereas NSE_{Q50} and PB_{Q50} reflect the accuracy in predicting runoff from smaller events ($P < 8$ mm). Conventional models tend to under-predict runoffs from smaller events because of the usage of constant I_a and S . They often falsely predict zero-runoffs because the runoff condition ($P > I_a$) cannot be overcome in smaller events. NSE_{Q50} and PB_{Q50} are used to expose this shortcoming.

6. Results and Discussion

10 The results show that using variable initial abstraction improved the accuracy of model predictions of runoff and heterogeneity (Table 3). Based on their overall performance, the models can be arranged from the best to the worst as $VIM\lambda > VIMS > CM\lambda > CM0.2$. Results for the case of $\lambda_i = 0$ are not presented in Table 3 because $VIM\lambda$, $VIMS$, and $CM\lambda$ performed equally well while $CM0.2$ was the worst (i.e. $VIM\lambda = VIMS = CM\lambda > CM0.2$).

15 Variable I_a models predicted runoff better than the conventional models. It was not possible to determine relative model performance using NSE_Q because it was 1.0 for all the models. This was because NSE_Q was strongly influenced by a few larger events, and a good fit in these events was sufficient to render $NSE_Q = 1.0$. Therefore $rNSE_Q$ (Krause et al., 2005) was calculated instead, and listed in Table 3. Larger events had greater influence on $rNSE_Q$ as well, but the values varied slightly between the models (Table 3). $rNSE_Q$ increased down the table whereas SEE_Q decreased, both indicating an improvement in model performance. PB_Q was positive for all the models, indicating that they all under-predicted runoff. The extent of under-prediction, however, was smaller in variable I_a models than the conventional models.

20 Variable I_a models gave a better estimate of watershed heterogeneity than the conventional models as indicated by the higher values of NSE_{I_a} and NSE_S (Table 3). NSE_{I_a} was zero or negative in the conventional models, whereas it varied from 0.2 to 0.7 in the variable I_a models. NSE_S was negative in all the models, indicating that their estimates of S were poor. In case of the conventional models this was due to using uniform I_a and S , and thereby homogenizing the watershed. In case of the variable I_a models, this was due to their inability to model the S-shaped function of S . Based on NSE_{I_a} and NSE_S , $VIM\lambda$ was the best model in estimating watershed heterogeneity.

25 Variable I_a models also predicted runoff better than the conventional models in smaller rainfall events ($P < 8$ mm) as indicated by NSE_{Q50} and PB_{Q50} . In both cases of $\lambda_i = 0.2$ and 0.5 , only HRU #0 (Table 2) produced runoff when $P < 8$ mm. This was similar to the case of a partial source area. As $CM0.2$ and $CM\lambda$ predicted an $I_a > 8$ mm in both cases (Table 3), they falsely predicted zero-runoffs in all the events with $P < 8$ mm because the runoff condition ($P > I_a$) could not be overcome. Therefore, their $PB_{Q50} = 100$ in both cases, indicating a 100% under-prediction in small events. Their NSE_{Q50} was also poor with the same value in both cases. $VIMS$ performed slightly better than the conventional models with 70-90% under-predictions, and with
30 NSE_{Q50} varying from -0.8 to -1.8 (Table 3). $VIM\lambda$ performed significantly better than all the other models with 30% or less

under-predictions, and with NSE_{Q50} varying from 0.6 to 0.9. Even though there were under-predictions, there was no false prediction of zero-runoff for any of the events in the variable I_a models.

Table 3. The performance of lumped parameter CN models that were calibrated to the runoff data generated using a distributed CN model for two cases of a synthetic watershed with the storage distribution shown in Table 2. SEE, I_a , and S are in mm. (SEE: Standard Error of Estimate, PB: Percent Bias, NSE: Nash-Sutcliffe Efficiency parameter, rNSE: relative NSE)

Lumped Model	Distributed Model: $\lambda_i = 0.2, I_{dT} = 22, I_{a,max} = 40, S_{\infty} = 112$										
	rNSE _Q	SEE _Q	PB _Q	NSE _{I_a}	NSE _S	NSE _{Q50}	PB _{Q50}	λ_W	I_a or I_{dT}	$I_{a,max}$	S or S_{∞}
CM0.2	0.93	0.91	12.6	-1.8	-13	-2.9	100	0.20	19	-	97
CM λ	0.94	0.37	5.4	0.0	-26	-2.9	100	0.07	9	-	132
VIMS	0.97	0.13	2.1	0.2	-22	-0.8	71	-	12	64	121
VIM λ	1.00	0.06	0.2	0.4	-3	0.9	16	0.09	11	43	124

Lumped Model	Distributed Model: $\lambda_i = 0.5, I_{dT} = 56, I_{a,max} = 100, S_{\infty} = 112$										
	rNSE _Q	SEE _Q	PB _Q	NSE _{I_a}	NSE _S	NSE _{Q50}	PB _{Q50}	λ_W	I_a or I_{dT}	$I_{a,max}$	S or S_{∞}
CM0.2	0.93	0.81	18.8	-1.4	-102	-2.9	100	0.20	31	-	155
CM λ	0.94	0.66	13.6	-0.3	-166	-2.9	100	0.11	21	-	197
VIMS	0.96	0.26	6.9	0.7	-83	-1.8	87	-	37	130	140
VIM λ	0.99	0.13	1.6	0.7	-9	0.6	33	0.21	33	96	153

In the models where λ_w was calibrated (CM λ and VIM λ), it was smaller than λ_i (Table 3). This shows that λ at the watershed scale tends to be smaller than that at the HRU scale in the lumped parameter models. All the models under-predicted I_a or I_{aT} with CM λ being the most severe. There was also a corresponding over-prediction of S or S_∞ by all the models except for the case of $\lambda_i = 0.2$ in CM0.2. Again, the most over-prediction of S occurred in CM λ . The under-prediction of I_a and the corresponding over-prediction of S is due to the transfer of storage from I_a to S , which generally improves the performance in the conventional models.

6.1. Storage Transfer from I_a to S

The storage in a watershed is distributed between I_a and S . I_a is the part of the storage that does not produce runoff while being filled, whereas S is the part that produces runoff while being filled. Using eqs. (2) and (1) it can be shown that

$$S = \frac{(P - I_a)(P - I_a - Q)}{Q} \quad (25)$$

For an observed storm event, P and Q are known and therefore are constants in eq. (25), so decreasing I_a will increase S . However, the magnitude of increase in S will be greater than the magnitude of decrease in I_a . This is illustrated by differentiating eq. (25) and using eq. (4) to give

$$\frac{dS}{dI_a} = - \left(1 + \frac{2S}{P - I_a} \right) \quad \forall \quad P > I_a \quad (26)$$

Thus, dS/dI_a is always negative and less than or equal to -1. If $(P - I_a) \gg S$ or $S \approx 0$, then $dS/dI_a \approx -1$, implying an equal transfer in storage between I_a and S . However, as P decreases, dS/dI_a becomes less than -1, implying that S changes more rapidly than I_a . In other words, the relative change of magnitude in S with respect to I_a is large for smaller P , decreases with increasing P , and approaches unity for large values of P .

Storage transfer is evident when the values of I_a and S for the models CM0.2 and CM λ are compared (Table 3). For the case of $\lambda_i = 0.2$, I_a decreased from 19 mm in CM0.2 to 9 mm in CM λ , whereas S increased from 97 mm to 132 mm, i.e. $dS/dI_a = -3.5$. Similarly, for the case of $\lambda_i = 0.5$, $dS/dI_a = -4.2$.

A transfer of storage from I_a to S improves the performance in the conventional models (i.e. CM $\lambda >$ CM0.2) because (i) a smaller I_a reduces the percentage of events with falsely predicted zero-runoffs, and (ii) it allows the model to mimic a variable I_a . Because of a larger I_a , CM0.2 falsely predicted zero-runoffs in 80% of the events for $\lambda_i = 0.2$, and in 85% of the events for $\lambda_i = 0.5$. In case of CM λ they dropped to 57% and 81% respectively because its I_a was smaller than CM0.2. Mimicking variable I_a can be explained by considering I_{aF} and F , which are the filled portions of I_a and S respectively. I_{aF} and F have similar

functional relationships with P (compare Figure 6 to Figure 1), i.e. they both increase with P and approach a constant for large values of P . In the conventional CN models, there is no provision to represent I_{aF} as a function of P . However, F is understood to be a function of P and is treated as such through eq. (2) and Figure 1. Therefore, by transferring the storage from I_a to S , CM λ uses F as a surrogate for I_{aF} , thereby partly mimicking the variable nature of I_{aF} .

5 Storage transfer from I_a to S also causes a decrease in λ_w (Table 3). Conversely, when λ_w decreases, storage is transferred from I_a to S . This is important because several studies (Baltas et al., 2007; D’Asaro and Grillone, 2012; Shi et al., 2009; Woodward et al., 2003) found that the optimal value of λ_w was much less than 0.2, and even close to zero in many watersheds. This shows that there is a positive correlation between a decrease in λ_w , storage transfer from I_a to S , and a general increase in model performance for the reasons mentioned above.

10 **6.2. Application to Real Watersheds**

The models were also evaluated using rainfall-runoff observations from 9 real watersheds located in different parts of the world (Santikari, 2017; Santikari and Murdoch, 2018). Models’ ability to predict the observed runoff was assessed using NSE_Q . Results show that in all the watersheds VIMs performed better than CMs but the difference in performance, ΔNSE_Q , varied across the watersheds. Between VIM λ and CM0.2, $\Delta NSE_Q < 0.05$ in one watershed, $0.05 \leq \Delta NSE_Q < 0.7$ in 6 watersheds, and $\Delta NSE_Q \geq 0.7$ in 2 watersheds. Between VIM λ and CM λ , $\Delta NSE_Q < 0.05$ in 3 watersheds, $0.05 \leq \Delta NSE_Q < 0.1$ in 4 watersheds, and $\Delta NSE_Q \geq 0.1$ in 2 watersheds. Based on their performance, the models can be arranged from the best to the worst as VIM λ > VIMS > CM λ > CM0.2, which is consistent with results from their application to the synthetic watershed.

15 **6.3. Effect of Degree of Heterogeneity**

The degree of heterogeneity, defined as the sharpness of change in CN, I_a , or S between the HRUs, may affect the relative performance of the models. To verify this, the degree of heterogeneity of the synthetic watershed (Table 2) was increased by doubling the values of S_i for HRUs 3 and 4 while the others were left unchanged, i.e. the modified distribution was $S_0 = 0$ mm, $S_1 = 50$ mm, $S_2 = 100$ mm, $S_3 = 300$ mm, and $S_4 = 400$ mm. The models were applied to this modified synthetic watershed, for the cases of $\lambda_i = 0.2$ and 0.5, and their performances were assessed using $rNSE_Q$ and SEE_Q .

Comparing the results (Tables 3 and 4) shows that the performance of VIMs remained nearly the same, whereas the performance of CM0.2 decreased and that of CM λ increased. The relative order of performance remained unchanged, i.e. VIM λ > VIMS > CM λ > CM0.2.

The results from real watersheds (Santikari, 2017; Santikari and Murdoch, 2018) also show that the performance of CM0.2 was poor, $NSE_Q < 0.25$, in watersheds with a sharp change in CN. Therefore, CM0.2 is unsuitable when the degree of heterogeneity is large. CM λ performed moderately well on synthetic and real watersheds with a large degree of heterogeneity, possibly by transferring the storage (Section 6.1). So, CM λ is suitable for predicting overall runoff, but unreliable for predicting

heterogeneity or runoff from small events. VIMs outperformed $CM\lambda$ in synthetic (Table 4) as well as real watersheds (Santikari, 2017; Santikari and Murdoch, 2018) with a large degree of heterogeneity, and therefore they are more reliable.

Table 4. Performance of the models for the cases of $\lambda_i = 0.2$ and 0.5 , when the degree of heterogeneity in the synthetic watershed (Table 2) was increased by doubling the values of S_i for HRUs 3 and 4.

Lumped Model	$\lambda_i = 0.2$		$\lambda_i = 0.5$	
	rNSE _Q	SEE _Q	rNSE _Q	SEE _Q
CM0.2	0.92	1.54	0.92	1.30
CM λ	0.95	0.19	0.94	0.38
VIMS	0.97	0.12	0.96	0.25
VIM λ	1.00	0.06	1.00	0.12

5

6.4. Model Suitability

One of the main objectives of this study was to improve the predictive ability of the CN method while maintaining its simplicity. Using the number of calibrated parameters as an indicator, the models can be arranged in the order of increasing complexity as: CM0.2 (one) < CM λ (two) < VIMS = VIM λ (three). CM0.2 was the simplest, but also had the poorest performance (Tables 3 and 4). Moreover, there is no justification in fixing λ_w at 0.2 or any other constant as its optimal value can vary from zero to one (Hawkins et al., 2008). Therefore, the usage of CM0.2 is not recommended.

CM λ predicted the overall runoff and the runoff from small events better than CM0.2. Often, the optimal λ_w is much smaller than 0.2 and this allows CM λ to partly mimic a variable I_{aF} by transferring storage from I_a to S . A smaller λ_w also reduces the false prediction of zero-runoffs, which are completely eliminated when $\lambda_w = 0$. Compared to the variable I_a models, CM λ is a poor predictor of runoff and watershed heterogeneity (Table 3). However, in watersheds with negligible I_{ai} values (or $\lambda_i \approx 0$) CM λ can perform as well as the variable I_a models, and therefore may be preferable because of its simplicity.

Variable I_a models show that significant improvement in the model prediction of overall runoff and heterogeneity can be achieved by using one extra parameter (Table 3). This is because the functional form of I_{aF} [eq. (23)] is consistent with the observations [Figure 2(c) and 2(d)] and the results from the theoretical analysis of heterogeneous watersheds [eq. (16), Figure 6, and Table 1]. Using variable I_a also improved the runoff predictions in small events and eliminated the false prediction of zero-runoffs. Therefore, their application is recommended in heterogeneous watersheds with non-zero initial abstractions.

20

When the watershed heterogeneity is known in great detail such that the number of calibrated parameters ≤ 3 , a distributed modeling approach [e.g. SWAT (Gassman et al., 2007) or Soulis and Valianzas (2013)] may be preferable over the variable I_a models. A distributed parameter model has advantages similar to the variable I_a models over the conventional models. It would inherently account for the variation of CN method's parameters spatially and with P . It would also avoid the false prediction of zero runoffs in small events because HRUs with larger CNs, which generate runoff even in small events, are explicitly considered. When the heterogeneity is unknown, however, the number of calibrated parameters (for values of CN_i and a_i) in a distributed model with n HRUs is $2n-1$. This number would increase further if values of λ_i are also calibrated. Therefore, when the number of calibrated parameters > 3 , application of a variable I_a model should be considered.

6.5. Model Limitation

A strength of the models proposed in this paper is that they provide a compact way to account for the spatial variation of CN, I_a , or S (watershed heterogeneity), but a limitation is that they do not account for the temporal variation. During dry periods I_a , and S increase whereas CN decreases. The behavior is opposite during the wet periods. Changes in land cover introduce additional temporal variations. Therefore, the calibrated model parameters in this paper can be considered as temporal averages. The models may underpredict runoff during wet periods and overpredict during dry periods. A procedure to account for temporal variations using antecedent moisture is described by Santikari (2017) and Santikari and Murdoch (2018).

Another limitation of VIMs is that the CN values calculated using eqs. (5) or (10) are incompatible with the standard CN values (NRCS, 2003; USDA, 1986) derived using CM0.2. However, this limitation is not unique to VIMs because any method, including $CM\lambda$, which involves an altered relationship between I_a and S (i.e. $\lambda \neq 0.2$) leads to CN values that are incompatible with those derived from CM0.2. Given that (i) CM0.2 is a poor predictor of runoff (Tables 3 and 4; Santikari, 2017; Santikari and Murdoch, 2018), and (ii) the evidence contradicts $\lambda = 0.2$ (Baltas et al., 2007; D'Asaro and Grillone, 2012; Shi et al., 2009; Woodward et al., 2003), the above-mentioned limitation is an acceptable compromise.

7. Conclusions

Watershed heterogeneity causes calculated values of I_a , S , and CN to vary with P . Therefore, using a single effective value of these quantities at the watershed scale can lead to systematic errors in the predictions of Q . This problem can be mitigated by treating I_a , S , or CN as functions of P . A theoretical analysis assuming spatial variation of I_a led to the following conclusions.

1. Effective I_a of a watershed is equal to the filled portion of the total storage in I_a

The total storage (called I_{aT}) is constant, whereas the filled portion (called I_{aF}) is a function of P [eq. (16)]. Variation of I_{aF} with P (Figure 6) is similar to the variation of calculated I_a (also called effective I_a or I_{aW}) with P [Figure 2(c) and 2(d)]. This shows that $I_{aW} = I_{aF}$, which is also supported by a distributed model using many HRUs [eq. (21)]. The form of I_{aF} as a function of P depends on the spatial distribution of I_a within a watershed (Table 1, Figures 8 and 9).

2. λ decreases with increasing spatial scale

Using CN_W , calculated as the area-weighted average of CN_i values (CNs of the HRUs), and the definition of I_a , it can be shown that $\lambda_W < \lambda_i$ [eqs. (8) through (11)]. Even when λ_W was calibrated using $CM\lambda$, the result was $\lambda_W < \lambda_i$ (Table 3). This shows that in conventional models, λ at the watershed scale tends to be smaller than that at the HRU scale, i.e. λ decreases with increasing spatial scale.

3. Replacing I_a with I_{aF} can account for heterogeneity

Heterogeneity causes the effective I_a of a watershed to vary with P , so to account for heterogeneity variable I_a models (VIMs) replace I_a with I_{aF} , which is a function of P (Figure 6). For practical purposes, I_{aF} can be treated as a quadratic function of P [eq. (23)] with two free parameters c_1 and c_2 that need to be calibrated. In addition, the model also requires the calibration of either S (VIMS) or λ (VIM λ).

4. Variable I_a models perform better than the conventional models

Variable I_a models predict runoff and heterogeneity better than the conventional models CM0.2 ($\lambda = 0.2$) and $CM\lambda$ (calibrated λ). They also eliminate the false prediction of zero-runoffs and improve runoff predictions in small events. Based on their overall performance, the models are arranged from the best to the worst as $VIM\lambda > VIMS > CM\lambda > CM0.2$.

5. Storage transfer can improve model performance

Storage transfer from I_a to S generally improves the model performance because the filled portions of I_a and S , I_{aF} and F respectively, have similar functional relationships with P (compare Figure 6 to Figure 1). This enables a CN model to partly mimic a variable I_{aF} by using F as its surrogate. Storage transfer also lowers the threshold P for runoff generation, thereby reducing the false prediction of zero-runoffs. Storage transfer decreases λ_W [eq. (3)], and this can explain why the optimal value of λ_W from published studies is much less than 0.2 or even zero in many watersheds.

Acknowledgments

Primary funding for this study was provided by the USDA Natural Resources Conservation Service (NRCS-69-4639-1-0010) through the Changing Land Use and Environment (CLUE) Project at Clemson University. Additional support was provided by the USDA Cooperative State Research, Education, and Extension Service under project number SC-1700278.

List of Symbols

a_i = fractional area of the i^{th} HRU

$a(I_a)$	=	probability density function of areal occurrence of I_a
CM0.2	=	conventional curve number model with $\lambda = 0.2$
CM λ	=	conventional curve number model with calibrated λ
CN	=	curve number, applicable to any spatial scale
CN $_i$	=	curve number of the i^{th} HRU
CN $_T$	=	curve number of a watershed when $I_{aF} = I_{aT}$
CN $_W$	=	curve number of a watershed
F	=	cumulative infiltration after runoff begins
HRU	=	hydrologic response unit
I_a	=	initial abstraction, applicable to any spatial scale
I_{aF}	=	areal average of the filled portion of I_{aT}
I_{ai}	=	initial abstraction of the i^{th} HRU
I_{aT}	=	areal average of the total initial abstraction
I_{aW}	=	effective initial abstraction of a watershed
$I_{a,\text{max}}$	=	maximum value of I_a within a watershed
λ	=	initial abstraction ratio, applicable to any spatial scale
λ_i	=	initial abstraction ratio at HRU scale
λ_W	=	initial abstraction ratio at watershed scale
m	=	no. of fully filled HRUs in which $I_{ai} \neq 0$
n	=	no. of HRUs in which $I_{ai} \neq 0$
NSE	=	Nash-Sutcliffe efficiency parameter
P	=	event rainfall

PB	=	percent bias
Q	=	event runoff
R^2	=	coefficient of determination
S	=	potential maximum retention, applicable to any spatial scale
S_i	=	potential maximum retention of i^{th} HRU
S_∞	=	maximum value of S_w , occurs when P is infinitely large
S_w	=	effective potential maximum retention of a watershed
SEE	=	standard error of estimate
VIM λ	=	variable initial abstraction model in which λ is calibrated
VIMS	=	variable initial abstraction model in which S is calibrated

References

- Baltas E.A., Dervos N.A. and Mimikou M.A. 2007. Technical note: Determination of the SCS initial abstraction ratio in an experimental watershed in Greece. *Hydrol. Earth Syst. Sci.* 11:1825-1829. doi: 10.5194/hess-11-1825-2007.
- Bingner R.L., Theurer F.D. and Yuan Y. 2011. AnnAGNPS technical processes documentation. 5.2.
- 5 D'Asaro F. and Grillone G. 2012. Empirical investigation of Curve Number Method parameters in the Mediterranean area. *J. Hydrol. Eng.* 17:1141-1152. doi: 10.1061/(ASCE)HE.1943-5584.0000570.
- D'Asaro F. and Grillone G. 2015. Discussion: "Curve Number derivation for watersheds draining two headwater streams in lower coastal plain South Carolina, USA" by Epps T.H., Hitchcock D.R., Jayakaran A.D., Loflin D.R., Williams T.H., and Amatya D.M. *J. Am. Water Resour. Assoc.* 51:573-578. doi: 10.1111/jawr.12264.
- 10 Gassman P.W., Reyes M.R., Green C.H. and Arnold J.G. 2007. The Soil and Water Assessment Tool—Historical development applications, and future research directions. *Trans. ASABE* 50:1211-1240.
- Hawkins R. 1993. Asymptotic determination of runoff Curve Numbers from data. *J. Irrig. Drain. Eng.* 119:334-345. doi: 10.1061/(ASCE)0733-9437(1993)119:2(334).

- Hawkins R., Ward T., Woodward D. and Van Mullem J. 2008. Curve Number hydrology: State of practice. American Society of Civil Engineers, Reston, VA.
- Hjelmfelt Jr. A. T., Woodward D. A., Conaway G., Plummer A., Quan Q. D., Van Mullen J., Hawkins R. H., and Rietz D. 2001. Curve numbers, recent developments, in: Proc. of the 29th Congress of the Int. As. for Hydraul. Res., Beijing, China. 5 17–21 September, 2001.
- HydroCAD. <<http://www.hydrocad.net>>.
- Kent, K. M. (1968). “A method for estimating volume and rate of runoff in small watersheds.” Technical Paper 149, USDA SCS, Washington, D.C.
- Knisel W.G. and Douglas-Mankin K.R. 2012. CREAMS/GLEAMS: Model use, calibration, and validation. Transactions of the ASABE 55:1291-1302. 10
- Krause P., Boyle D.P., and Base F. 2005. Comparison of different efficiency criteria for hydrological model assessment. Adv. Geosci. 5: 89-97.
- McCuen R.H. 2003. Modeling hydrologic change: Statistical methods. Lewis Publishers, Boca Raton, Fla.
- Mishra S.K., Sahu R.K., Eldho T.I. and Jain M.K. 2006. An improved I_a - S relation incorporating antecedent moisture in SCS-CN methodology. Water Resour. Manage. 20:643-660. doi: 10.1007/s11269-005-9000-4. 15
- Moriassi D.N., Arnold J.G., Van Liew M., Bingner R.L., Harmel R.D. and Veith T.L. 2007. Model evaluation guidelines for systematic quantification of accuracy in watershed simulations. Transactions of the ASABE 50:885-900.
- Neitsch S.L., Arnold J.G., Kiniry J.R. and Williams J.R. 2005. Soil and Water Assessment Tool theoretical documentation (version 2005). Agricultural Research Service, Temple, TX.
- NRCS. 2003. National engineering handbook: Part 630, Hydrology. USDA, Washington, DC. 20
- Panday S. and Huyakorn P.S. 2004. A fully coupled physically-based spatially-distributed model for evaluating surface/subsurface flow. Adv. Water Resour. 27:361-382. doi: 10.1016/j.advwatres.2004.02.016.
- Ponce V. and Hawkins R. 1996. Runoff Curve Number: Has it reached maturity? J. Hydrol. Eng. 1:11-19. doi: 10.1061/(ASCE)1084-0699(1996)1:1(11).

- Rallison R.E. and Miller N. 1982. Past, present, and future SCS runoff procedure. p. 353-364. *In* V.P. Singh (ed.) Proceedings of the international symposium on rainfall runoff modeling: Rainfall-runoff relationship, Mississippi State University, Mississippi. May 18-21, 1981 Water Resources Publications, Littleton, Colorado.
- 5 Santikari V. P. 2017. Accounting for Spatiotemporal Variations of Curve Number using Variable Initial Abstraction and Antecedent Moisture. Chapter 5. *In* Evaluating Effects of Construction-Related Land Use Change on Streamflow and Water Quality (Doctoral dissertation). https://tigerprints.clemson.edu/all_dissertations/1942
- Santikari V.P. and Murdoch L.C. 2018. Accounting for spatiotemporal variations of Curve Number using variable initial abstraction and antecedent moisture. Under Review.
- Shi Z., Chen L., Fang N., Qin D. and Cai C. 2009. Research on the SCS-CN initial abstraction ratio using rainfall-runoff event analysis in the Three Gorges Area, China. *Catena* 77:1-7. doi: <http://dx.doi.org/10.1016/j.catena.2008.11.006>.
- 10 Soil Conservation Service. 1956. National engineering handbook: Section 4, Hydrology. USDA SCS, Washington, D.C.
- Soil Conservation Service. 1972. National engineering handbook: Section 4, Hydrology. Chapter 10. USDA SCS, Washington, D.C.
- Soulis K.X., Valiantzas J.D., Dercas N. and Londra P.A. 2009. Investigation of the direct runoff generation mechanism for the analysis of the SCS-CN method applicability to a partial area experimental watershed. *Hydrol. Earth Syst. Sci.* 13:605-615. doi: 10.5194/hess-13-605-2009.
- 15 Soulis K.X. and Valiantzas J.D. 2012. SCS-CN parameter determination using rainfall-runoff data in heterogeneous watersheds - the two-CN system approach. *Hydrol. Earth Syst. Sci.* 16:1001-1015. doi: 10.5194/hess-16-1001-2012.
- Soulis K.X. and Valiantzas J.D. 2013. Identification of the SCS-CN parameter spatial distribution using rainfall-runoff data in heterogeneous watersheds. *Water Resour. Manage.* 27:1737-1749. doi: 10.1007/s11269-012-0082-5.
- 20 USDA. 1986. Urban hydrology for small watersheds. TR-55. USDA-NRCS, Washington, DC.
- Van Mullem, J. A. 1997. Precipitation variability and curve numbers. *In* Managing Water: Coping with Scarcity and Abundance. Proceedings of the 27th Congress of the International Association of Hydraulic Research, San Francisco, CA. August 1997. 518-523. Published by American Society of Civil Engineers, New York.
- 25 Wang X., Williams J.R., Gassman P.W., Baffaut C., Izaurre R.C., Jeong J. and Kiniry J.R. 2012. EPIC and APEX: Model use, calibration, and validation. *Trans. ASABE* 55:1447-1462.

Woodward D.E., Hawkins R.H. and Quan Q.D. 2002. Curve Number method: Origins, applications and limitations. *In* Hydrologic modeling for the 21st century: 2nd federal interagency hydrologic modeling conference, Las Vegas, Nevada. July 28 – August 1, 2002.

5 Woodward D., Hawkins R., Jiang R., Hjelmfelt Jr. A., Van Mullem J. and Quan Q. 2003. Runoff curve number method: Examination of the initial abstraction ratio. p. 1-10. *In* World water & environmental resources congress, Philadelphia, Pennsylvania, United States. June 23-26, 2003 American Society of Civil Engineers.