Comments to the Author:

I have received three reviews of the manuscript.

The first Referee provided no substantial comments on the paper. Both the second and the third Referees provided extensive comments and recommended re-considering the manuscript after major revisions.

A few comments were properly addressed by the authors in their responses. However, major criticism in the Referees' reports was answered by the authors in a rather formal manner. I fully agree with the major criticism.

First of all, I would recommend the authors to pay attention to the Referees' concern regarding the used SWAT model applicability to the impact study and to provide more convincing evidence of the model performance on the basis of the historical data. In fact, the calibration statistics are poor, inconsistent response in simulated river runoff to the increasing precipitations looks questionable, etc.

Second, major problem is the selection of meteorological forcing data used in the study. I share the all Referees concern about the lack of comparison between the observed and GCMs-based data, regarding the selection of the GCM models, etc.

Overall, I recommend the authors to consider the principle criticisms and re-submit the revised manuscript for the Editor's review and final decision on opportunity of publication in HESS.

Response to editor: We appreciate the editor's effort put into this manuscript and give our opportunity to revise this manuscript. The comments and suggestions provided by editor really helpful for us to improve the current manuscript. We have attempted to address every point raised by the editor which also the major criticism in the Referees' reports in our revised manuscript and hope we have the opportunity of publication in HESS.

The followings are summary for response to the key concerns, and details showed in the revsided manuscript:

1. <u>The application of SWAT.</u>

In this study, SWAT hydrological model were calibrated based on SWAT-CUP (SWAT Calibration and Uncertainty Programs) to improve the fit between simulated and observed discharge. However, the auto-calibration didn't result in satisfactory performance of the hydrological model in the SYR and the CBR. It is thought that this is because there are some model-observation divergences within the 1961–1990 calibration period that are simply too large to be resolved by an auto-calibration routine. Following the unsuccessful application of auto-calibration routines, a more extensive manual calibration was undertaken by manually varying the six most sensitive parameters in the SWAT. Following manual calibration of model parameters, a relative satisfactory fit between observed and simulated monthly river flow was obtained in the SYR and the CBR.

In general, the model simulation is considered acceptable when the E_{ns} values are greater than 0.5, R^2 should exceed 0.6, and the P_{bias} less than $\pm 20\%$. Model performance statistics over the calibration and validation periods were all found "satisfactory" for the four basins. The performance statistics E_{ns} and R^2 were both > 0.8 and considered highly acceptable for the two basins in southern China (i.e., the HHR and the FJR) for both the calibration and the validation periods. The same performance statistics were considered reasonably acceptable for the two basins in northern China (i.e., the SYR and the CBR) with efficiencies in the range 0.58~0.82. The percentage bias was generally less than 20% (excepted for the Baihe River for the calibration period) in the four rivers.

Furthermore, we evaluated the performance of discharge simulation of SWAT by comparing the graphical plots including monthly time series which reflects the month to-month sequencing (added as Figure S3), and flow duration curve which shows the frequency distributions of discharge (Fig.S4) in the revised manuscript. The two kind of graphical plots comparison well matching between the observed and simulated discharge during 1961-2001, details in Section 3.1 and Figure S3 and Figure S4 in the revised manuscript.

2. Inconsistent response in simulated river runoff to increasing precipitation.

We fully understand the argument about inconsistent response in simulated river runoff to increasing precipitation in the four river basins.

We added a section 5.1 Climate change impact on runoff to compare our result with previous studies (Chen et al. 2014; Liu et al., 2012; Ma et al., 2008). The four river basins in this study represent climate from dry to wet, and the response of runoff to precipitation change also coincided with the previous findings that more increase in precipitation need to maintain runoff in drier basins.

Considering evapotranspiration (ET) is the main output of surface water resources, we added the simulated change in ET (added Figure 4). The results showed that a general increase in simulated ET in all four basins accompanied with global warming, however, the magnitude of the simulated change of ET varies across the basins, i.e., it is larger in the two basins in north China than in the two basins in south China. For the two rivers located in northern China, the simulated change of ET in the SYR shows increase of 21% and 13%, while that of the CBR shows increase of 4% and 6% under 1.5 $\$ and 2.0 $\$ warming, respectively, which implies the increase in simulated ET contributes most to the decrease in simulated annual runoff in the SYR.

Reference:

- Ma, Z., Kang, S., Zhang, L., et al.: Analysis of impacts of climate variability and human activity on streamflow for a river basin in arid region of northwest China, J. Hydrol., 352, 239-249, https://doi.org/10.1016/j.jhydrol.2007.12.022, 2008.
- Liu, M., Tian, H., Lu, C., et al.: Effects of multiple environment stresses on evapotranspiration and runoff over eastern China, J. Hydrol., 426-427, 39-54, https://doi.org/10.1016/j.jhydrol.2012.01.009, 2012.
- Chen, J., Xia, J., Zhao, C., et al.: The mechanism and scenarios of how mean annual runoff varies with climate change in Asian monsoon areas, J. Hydrol., 517, 595-606, https://doi.org/10.1016/j.jhydrol.2014.05.075, 2014.

3. the selection of meteorological forcing data used in the study

- (1) We compared the WFD with climate observation based on meteorological station for annual mean and monthly mean temperature and precipitation (Table S1 and Figure S1). WFD showed slight difference in the two river basins in Southern China, with about 1.3% and 2.1% lower in mean annual precipitation and 0.1 °C and 0.9°C lower in mean annual temperature in the HHR and the FJR respectively. While in the two river basins in Northern China, there less 20% difference in mean annual precipitation (14.6% larger and 20% lower than observed meteorological observations), and 2.5°C and 4.1°C lower in mean annual temperature in the SYR and the CBR. The monthly distribution showed general coherence in the seasonal pattern in temperature and precipitation between WFD and meteorological observation.
- (2) Forcing hydrological model with WFD and observed climate data result in different parameterization, and has limited impact on performance of runoff simulation. Previous researchers found that Ens and R2 forced by WFD are slightly larger than those forced by observed climate in both the Huaihe River and in the Xijiang River, and Pbias is smaller in the Huaihe River while larger in the Xijiang River compared with forced by observed climate (Liu et al., 2012, Liu et al, 2018; Wang et al., 2018).
- (3) To reducing the uncertainties of hydrological model parameterization caused by inconsistent climate forcing, we calibrated and validate SWAT with WFD, because climate model output was corrected based on WFD in the frame of ISI-MIP, then was used to force the calibrated SWAT model in the hydrological scenarios modeling for the four rivers.

We have compared the WFD with meteorlogial observation inSection2.2, and clarified the reason using WFD force SWAT in Section 3.1 in the revised manuscript.

Reference:

Liu, L.; Jiang, T.;Xu, J.; Luo, Y.. Research on the hydrological processes using multi-GCMs and multi-scenarios. J. Hydral. Eng., 2012, 43 (12), 1413-1421.

Liu, L.; Jiang, T.; Xu, H.; Wang, Y. Potential threats from variations of hydrological parameters to the Yellow River and Pearl River Basins in China over the Next 30 Years. Water, 2018, 10(7), 883. https://doi.org/10.3390/w10070883.

Wang, S.; Xu, H;, Liu, L; Wang, Y.; Song, A. Projection of the Impacts of GlobalWarming of 1.5℃ and 2.0℃on Runoff in the Upper-Middle Reaches of Huaihe River Basin. J. Nat. Resour. 2018, 33(11): 1966-1978 (in Chinese).

4. the lack of comparison between the observed and GCMs-based data

- In this study, WFD data was used as the observation-based reference dataset for bias-correct for the output of GCMs. The trend-preserving bias correction method that were derived during the reference period are applied to the simulation data in the past, present and future (allocation period 1950-2099).
- (4) We added the comparison of WFD with the historical run of GCMs for 1961-2001 (Table S2. and Figure S2). The downscaling climate data from GCMs showed very good coherence with WFD for the historical period 1961-2001 in the four river basins in this study, with slight difference in temperature and larger precipitation.

We have clarified the comparison of WFD with **GCMs-based data** in Section 2.2 in the revised manuscript.

5. the selection of the GCM models.

- <u>GCM selection would introduce uncertainty and influence the range of climate change impact</u> assessment (Todd et al., 2011). The five GCMs used in this study, which captured 50 to 90% of the full range of future projections of 36 CMIP5 GCMs for temperature and 40 to 90% of the full range of future projections for precipitation in the four river basins (Fig.1 in McSweeney and Jones 2016).
- (2) Furthermore, Liu et al. (2017) compared the changes of precipitation and temperature by five GCMs used in this study with those of other 19 CMIP5 GCMs. The results showed that the five GCMs covered the range of GCMs from CIMP5 well for global mean precipitation and temperature during 2020-2050 for RCP2.6 and RCP4.5. (Fig.S1 in Liu et al., 2017)
- (3) The information indicates the importance for reducing uncertainty associated with the choice of an applied GCM. At the basin scale, prioritising or weighting GCMs may be considered on the basis of detailed analyses of the ability of an individual GCM to represent a specific characteristic of regional climate of interest (e.g., multi-annual or decadal variability).

Assessment of climate change impact and difference on the river runoff in four basins in China under 1.5 $^{\circ}$ C and 2.0 $^{\circ}$ C global warming

Hongmei Xu¹, Lüliu Liu¹, Yong Wang², Sheng Wang³, Ying Hao⁴, Jingjin Ma⁵, Tong Jiang^{6,1}

¹National Climate Center, China Meteorological Administration, Beijing, 100081, China
 ²Chongqing Climate Center, Chongqing, 401147, China
 ³Anhui Climate Center, Hefei, 230031, China
 ⁴Anhui Meteorological Observatory, Hefei, 230031, China
 ⁵Beijing Meteorological Disaster Prevention Center, Beijing, 100089, China

⁶Collaborative Innovation Center on Forecast and Evaluation of Meteorological Disasters, School of Geography and Remote Sensing, Nanjing University of Information Science & Technology, Nanjing, 210044, China

Correspondence to: Hongmei Xu (xuhm@cma.gov.cn)

Co-correspondence to: Tong Jiang (jiangtong@cma.gov.cn)

- 15 Abstract: To quantify climate change impact and difference on basin-scale river runoff under the limiting global warming thresholds of 1.5 °C and 2.0 °C, this study examined four river basins covering a wide hydroclimatic setting. We analyzed projected climate change in four basins, quantified climate change impact on annual and seasonal runoff based on the Soil Water Assessment Tool, and estimated the uncertainty constrained by the global circulation models (GCMs) structure and the Representative Concentration Pathways (RCPs). All statistics for the two river -basins (the Shiyang River (SYR) and the
- 20 <u>Chaobai River (CBR))</u> located in northern China indicated generally warmer and wetter conditions, whereas the two <u>river</u> basins (<u>The Huaihe River (HHR)</u> and the Fujiang River (FJR)) located in southern China projected less warming and were inconsistent regarding annual precipitation change. The simulated changes in annual runoff were complex; however, there was no shift in seasonal runoff pattern. The 0.5 °C global warming difference caused 0.7 °C and 0.6 °C warming in basins in northern and southern China, respectively. This led to projected precipitation increase by about 2% for the four basins, and to
- a decrease in simulated annual runoff of 8% and 1% in the <u>Shiyang-SYR</u> and <u>Huaihe riversthe HHR</u>, respectively, but to an increase of 4% in the <u>Chaobai-CBR</u> and the <u>Fujiang riversFJR</u>. The uncertainty in projected annual temperature was dominated by the GCMs or the RCPs; however, that of precipitation was constrained mainly by the GCM. The 0.5 °C difference decreased the uncertainty both in the annual precipitation projection and the annual and monthly runoff simulation. Keywords: 1.5 °C and 2.0 °C warming; runoff; Shiyang River; Chaobai River; Huaihe River; Fujiang River

1 Introduction

5

In addition to changes in other variables of the climate system, global temperature has shown warming of 0.85 °C during 1880–2012 and further increase of 2.0–4.0 °C is projected over the next 100 years (IPCC, 2013). The observed changes in elimate have affected both natural and human systems in recent decades. The level of elimate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of \geq 4.0 °C global warming is considered high to very high (IPCC, 2014). The target goal of 1.5 °C and 2.0 °C global warming relative to the preindustrial climate has been proposed as a threshold which to avoid the dangerous effects of anthropogenic climate change might be limited (UNFCCC, 2015). The observed changes in climate have affected both natural and human systems in recent decades. The level of climate change is the level of climate change is the level of climate have affected both natural and human systems in recent decades. The level of climate change is the level of climate change is the level of climate have affected both natural and human systems in recent decades. The level of climate change is climate have affected both natural and human systems in recent decades. The level of climate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of climate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of climate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of climate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of climate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of climate change risk at 1.0 °C or 2.0 °C global warming is thought considerable, while that associated with an increase of climate change risk at 1.0 °C or 2.0 °C global warming is though

- 10 ≥4.0 °C global warming is considered high to very high (IPCC, 2014). Significant progress has been achieved in comprehensive quantitative assessments of aggregate global climate impact (Schellnhuber et al., 2014). However, climate research is also challenged to provide more robust information on the impact of climate change under different scenarios of global warming (particularly at local and regional scales) to assist the development of sound scientific adaptation and mitigation measures (Huber et al., 2014). For example, a number of areas have been identified with severe projected impacts
- 15 of warming at 2.0 °C (Schleussner et al., 2016). Observed climate change has caused changes in global hydrological cycle, and this is expected to have considerable impact on multiple scale freshwater availability (Schmied et al., 2016). Most regional changes in precipitation can be attributed either to internal variability of the atmospheric circulation or to global warming. Climate change over the 21st century is projected to reduce renewable surface water significantly in most dry subtropical regions, while water resources are
- 20 projected to increase at high latitudes (IPCC, 2014). At the global scale, the extreme rainfall is projected to more frequency under both 1.5 ℃ and 2.0 ℃ warming until around 2070; however, the increase is expected to be higher under 2 ℃ warming after the late 2030s (Zhang and Villarini, 2017). Furthermore, global warming of 2.0 ℃ is anticipated to affect natural runoff in river basins around the world and to dominate runoff changes, even considering human impact (Haddeland et al., 2014). Global warming of 2.0 ℃ will enhance water scarcity in areas projected to experience severe water resources reduction,
- 25 although uncertainties exist in the projected changes in discharge and in the spatial heterogeneity depending on the contributions from global hydrological models and global climate models (Schewe et al., 2014). For the most region with simulated water resource declined, the uncertainties in simulated runoff usually constrained by global hydrological models, which suggests the necessity for improvement of regional- or local-scale hydrological projections (Su et al., 2017). Comparison of the performance of global and regional hydrological models indicates that regional hydrological models are
- 30 better able to represent the long-term average seasonal dynamics (Hattermann et al., 2017; Gosling et al., 2017). Within the context of the global temperature increase, China has experienced robust warming that is characterized by the greatest rate of annual mean temperature increase (i.e., more than 0.3 °C/10a during 1961–2012) in northern areas (Third National Assessment Report for Climate Change, 2015). River runoff has decreased consistently in the Yellow, Liao, and

Songhua rivers but increased in the Pearl River because of increased precipitation in southern China and decreased precipitation in northern China combined with human activities (Xu et al., $2010\underline{a}$). The runoff of rivers located in northern China, in areas with arid and semiarid climate, is more sensitive to precipitation than in southern China (Xie et al., 2018). The 2.0 $\$ warming threshold will be exceeded under two Representative Concentration Pathways (RCPs), averaged across

- 5 China, will be around 2033 ± 15a under RCP4.5 and 2029 ± 10a under RCP8.5 (Chen and Zhou, 2016). Simulations suggest that the Yiluo River in northern China will have reduced annual runoff but with a wetter flood season under both 1.5 ℃ and 2.0 ℃ warming, while the Beijiang River in southern China will have a slight increase in annual runoff with a drier flood season (Liu et al., 2017). The simulated runoff changes of the Yangtze River decrease under 1.5 ℃ warming; however, it shows opposite changes under 2.0 ℃ global warming (Chen et al., 2017).
- The objectives involved in this paper address the following: (1) to detect the level of warming and the change in precipitation in four river basins with differing hydroclimatic characteristics under limiting global warming thresholds of 1.5 °C and 2.0 °C, (2) to simulate the changes in river runoff under 1.5 °C and 2.0 °C warming among the four basins, (3) to estimate the uncertainty constrained by global circulation models (GCMs) and RCPs, and (4) to quantify the difference in projected climate changes and simulated changes of river runoff in relation to 0.5 °C global warming difference among the four basins.
- 15 To achieve these objectives, firstly, we analyze the projected changes in mean annual temperature and precipitation in the selected four basins at the annual scale-under 1.5 ℃ and 2.0 ℃ warming. Secondly, we investigate the changes in <u>simulated</u> annual and monthly river runoff in the four river basins based on validated Soil Water Assessment Tool (SWAT). Finally, we quantify the uncertainties in climate change impacts on river runoff based on five GCMs under four RCPs.

2 Study basins and available data

20 2.1 Basins

Four basins that span a wide hydroclimatic gradient from dry to wet were selected as case studies in this research. The locations as well as the physical and hydroclimatic characteristics of the selected basins are presented in Fig. 1 and Table Table 1.

- The Shiyang River <u>(SYR)</u> basin is one of three inland river basins in Northwest China. The basin is dominated by a continental temperate arid climate and variable topography. The Shiyang RiverSYR has eight tributaries that originate in the Qilian Mountains, the total drainage in mountain area of which $(1.1 \times 10^4 \text{ km}^2)$ was selected as the study area. River discharge is derived mainly from precipitation and snow melt water in summer and from groundwater in winter. Of the eight tributaries in the Shiyang River basin, five have decreasing trends in annual streamflow, mainly because of reduced precipitation (Ma et al., 2008). The basin has lost much of its natural vegetation and it has undergone gradual desertification
- 30 due to limited water resources, inappropriate human activities, and the arid climate, which together pose considerable threat to sustainable agricultural development (Zhu and Li, 2014).

The Chaobai River (CBR) basin is located on the North China Plain and it is a tributary of the Haihe River. The basin is dominated by a continental temperate monsoon climate. The <u>CBR</u>Chaobai River originates from the Yanshan Mountain via two tributaries: the Chaohe <u>River</u> and the Baihe <u>riverRvers</u>. The total area of the basin above the Xiahui and Zhangjiafen gauging stations (about 1.4×10^4 km²) was selected as the study area. This watershed is the source of more than half the water supplied to Beijing. Its runoff has declined considerably during 1956-2004 because of climate change, land use and

5 water supplied to Beijing. Its runoff has declined considerably during 1956-2004 because of climate change, land use and land cover change, and increased water consumption (Xu et al., 2014; Yang and Tian, 2009).
The Huaihe River (<u>HHR</u>) basin is an extensive flat plain located in a transition zone between the climates of North and South China. The basin is dominated by a warm temperate monsoon semihumid climate. The upper region of the <u>HHR</u>Huaihe

River basin above the Wujiadu gauging station, which has a drainage area of about 12.1×10^4 km², was selected as the study

- area. Climate change has led to severe storms, reduced and intense droughts in Huaihe River<u>HHR</u> Basin (Zhang et al., 2015). The Fujiang River<u>(FJR)</u> is the tributary of the Yangtze River and originates from Min Mountain located in Southwest China. The F<u>JRujiang River</u> basin is dominated by a humid subtropical climate. The area above the Xiaoheba gauging station, which has a drainage area of 2.9×10^4 km², was selected as the study area. Because of the high population density, intensive agricultural practices, and decreasing precipitation, the observed river discharge has a decreasing trend; however, high-
- 15 intensity and long-duration precipitation in this area frequently results in floods and associated landslides (Gao et al., 2017).

2.2 Available data

The consistent spatial dataset, such as the digital elevation model of China generated from topographic map with 1:250,000 scale, the harmonized world soil database with 30 arcsecond resolution (FAO/IIASA/ISRIC/ISS-CAS/JRC, 2008), and the digital land use map of China with 1:500, 000 were used for the parameterization of SWAT.

- 20 The observed discharge data were provided by the local authorities based on the Water Year Books. Monthly discharge records for selected gauging stations in the four basins (listed in Table 2) for the period of 1961–2001 were used for SWAT evaluation. The daily climate dataset (WATCH Forcing Data: WFD) (Weedon et al., 2010) with the resolution of 0.5 degree covered the period of 1958-2001 was obtained from the Water and Global Change Program. The WFD was used for driving SWAT hydrological model for the historical period, and also was used for the basis for GCMs output downscaling. Gridded
- 25 reanalysis climate datasets have been use for hydrological modeling widely, and the WFD is considered an acceptable dataset for forcing hydrological models in comparison with gridded observation database (Essou et al., 2016). Furthermore, WFD has been widely used in climate change impact assessment at regional or catchment scale in China (Hao et al., 2018; Liu et al., 2017; Chen et al, 2017; Su et al., 2017). The comparison of mean annual and monthly temperature and precipitation based on WFD and meteorological observations in the four river basins showed in Table S1 and Fig. S1. WFD
- 30 <u>showed slight difference in the two river basins in Southern China, with about 1.3% and 2.1% lower in mean annual precipitation and 0.1 °C and 0.9 °C lower in mean annual temperature in the HHR and the FJR respectively. While in the two river basins in Northern China, there were less 20% difference in mean annual precipitation (14.6% larger and 20% lower</u>

than observed meteorological observations), and 2.5° C and 4.1° C lower in mean annual temperature in the SYR and the CBR. The monthly distribution showed general coherence in the seasonal pattern in temperature and precipitation between WFD and meteorological observation. appears to be appropriate for application to hydrological modeling in this study, and the comparison of mean annual and monthly temperature and precipitation based on WFD and meteorological observations showed in Table S1 and Figure S1.

5

GCMs outputs were derived from the Inter-Sectoral Impact Model Intercomparison Project for five GCMs (HadGEM2-ES, IPSL-CM5A-LR, MIROC-ESM-CHEM, GFDL-ESM2M and NorESM1-M) under four RCPs (RCP2.6, RCP4.5, RCP6.0 and RCP8.5) (Warszawski et al., 2014). These models were selected to span GMT change and relative precipitation change as effectively as possible (Warszawski et al. 2014). The FRC index (Fractional range coverage) of the five GCMs in ISI-MIP

- 10
- project is 0.75 and 0.59, respectively, which is better than the five GCMs randomly selected from CMIP5, and can reasonably represent the changes of regional average temperature and precipitation (McSweeny and Jones, 2016). These climate model outputs are spatially interpolated into 0.5° resolution and corrected using trend-preserving bias correction approach based on WFD for the period 1950–2005 for historical simulation and 2006-2099 for future projection-under (Hempel et al., 2013). The downscaling climate data from GCMs showed very good coherence with WFD in-for the
- 15 historical period 1961-2001 in the four river basins in this study (Table Table S2 and Figure Fig. S2). There were slight differences in annual mean, maximum and minimum temperature in the four river basins, with less than 0.1 °C difference in the SYR, CBR and HHR, and 0.3°C larger in the FJR. All five GCMs' historical downscaling data showed insistent well agreement in temperature compared with WFD. For the annual precipitation, there was general wetter condition based on the five GCMs' historical downscaling data, with the magnitude less than 15%. The five GCMs' historical downscaling data
- 20 could reproduce the monthly distribution of temperature and precipitation well. These models were selected to span GMT change and relative precipitation change as effectively as possible (Warszawski et al. 2014). The FRC index (Fractional range coverage) of the five GCMs in ISI-MIP project is 0.75 and 0.59, respectively, which is better than the five GCMs randomly selected from CMIP5, and can reasonably represent the changes of regional average temperature and precipitation (MeSweeny and Jones, 2016). Such a subset can provide climate information that can improve the understanding of both the 25 total uncertainty of future climate impacts and the uncertainty constrained by the use of different GCMs and RCPs.
 - **3 Methodology**

3.1 Application of SWAT

The SWAT is a process-based semi-distributed hydrological model, which can simulate the river flow, water balance and nutrient transport at basin scale (Gassman et al., 2007). As an open and free tool, the SWAT is applied worldwide under various climatic conditions and hydrologic regime (Xu and Luo., 2015Arnold et al., 2012).

The simulations using the SWAT model were forced by WFD climate data <u>at a daily time step</u>, and they were spunwarm-up for the period 1958–1960. The SWAT models were then calibrated for the 1961–1990 and validated for 1991–2001 using monthly river runoff data from the gauging stations of the four basins. <u>Forcing SWAT by WFD mainly based on the consideration of reducing the uncertainties of hydrological model parameterization caused by inconsistent climate forcing.</u>

- 5 Because climate model output was corrected based on WFD in the frame of ISI-MIP, and was used to force the calibrated SWAT model in the hydrological scenarios modeling. Forcing hydrological model with gridded climate/reanalysis climate data, and observed climate data result in different parameterization (Xu et al., 2010b), and has limited impact on performance of runoff simulation (Liu et al., 2012a; Liu et al., 2018, Wang et al., 2018).
- Using sensitivity analysis procedures embed in SWAT resulted in the six most sensitive parameters (Table-Table_S3) in the hydrological model for each of the four rivers. There were two consistent sensitive parameters "CN2" and "GWQMN" among all four river basins which control the runoff process and soil water moving process respectively. However, there was consistent sensitive parameter for the two river basins located in northern China and southern China respectively, such as in the two river basins located in northern China, the common sensitive parameter was "ALPHA_BF" which reflect the

groundwater flow response to changes in recharge. There were specific sensitive parameters for each river basin, such as the

- 15 temperature related parameters for snow_"SMTMP" and "TIMP" in the Shiyang RiverSYR-basin. The definition of parameters showed in Table_Table_S4. The SWAT hydrological model were calibrated based on SWAT-CUP (SWAT Calibration and Uncertainty Programs) (Abbaspour., et al, 2007) to improve the fit betweebn simulated and observed discharge. For the Shiyang RiverSYR, the observed monthly streamflow at the Jiutiaoling gauging station for the Xiyinghe tributary was used for model calibration and validation, while the parameterization was used for the entire the Shiyang
- 20 <u>SYRRiver</u>. For the Chaobai River<u>BR</u>, the observed monthly streamflow at the Xiahui gauging station for the Chaobe <u>RChaobe Riveriver</u> and at the Zhangjiafen gauging station for the <u>Baibe RBaibe Riveriver</u> were available for hydrological model calibration and validation separately (Hao et al., 2018). For the HHR and the FJR, the observed monthly discharge in the main stream at guaing station Wujiangdu and Xiaobeba respectively was used for model calibration and validation. However, the auto-calibration didn't result in satisfactory performance of the hydrological model in the SYR and the CBR.
- 25 More extensive manual calibration was undertaken by manually varying the six most sensitive parameters in the SWAT which resulted in improvement in model performance, and a relative satisfactory fit between observed and simulated monthly river flow was obtained in the SYR and the CBR.

The coefficient of determination (R^2), Nash–Sutcliffe efficiency (E_{ns}) were used to measures the goodness-of-fit, and percentage of bias (P_{bias}) was used to assess systematic over- or under estimation and when the absolute value is applied it

30 shows the magnitude (Green and van Griensven, 2008). In general, the model simulation is considered acceptable when the E_{ns} values are greater than 0.5, \underline{R}^2 should exceed 0.6, and the P_{bias} less than $\pm 2520\%$ (Moriasi et al., 2007). Furthermore, the performance of discharge simulation of SWAT was also compared by the graphical plots including monthly time series which reflects the month to-month sequencing, and flow duration curve which shows the frequency distributions of discharge.

Model performance statistics over the calibration and validation periods were all found "satisfactory" for the four basins (Table Table. 2). The performance statistics E_{ns} and R^2 were both > 0.8 and considered highly acceptable for the two basins in southern China (i.e., the Huaihe-<u>HHR</u> and <u>the Fujiang riversFJR</u>) for both the calibration and the validation periods. The same performance statistics were considered reasonably acceptable for the two basins in northern China (i.e., the <u>Shiyang</u>)

- 5 <u>SYR and the Chaobai riversCBR</u>) with efficiencies in the range 0.58–<u>0.82</u>. <u>The percentage bias was generally less than 20%</u> (excepted for the Baihe River for the calibration period) in the four rivers. The monthly time series for discharge during the calibration and validation period (Fig. S3) showed apparently well month to-month sequencing in the four rivers with general underestimate in monthly discharge in dry season in the two rivers located in northern China, and underestimate for flooding season in occasion years in the CBR. This was also reflected in the flow duration curve (Fig.S4), with large
- 10 underestimate for the medium/lower and very high flow for the CBR. Oppositely, there was overestimate in medium/lower
 flow in both the two river located in the Southern China, however, underestimate in higher flow in FJR.
 Although, there was a few cases showed that SWAT could be used in snowmelt dominated streamflow (Wang and Melesse,
 2005; Tolston and Shoemaker, 2007; Grusson et al., 2015), a few previous researches have indicate that SWAT model did
 not adequately predict winter flows or snowmelt dominated runoff in several watershed (Peterson and Hamlett, 1998;
- 15 Srivastava et al., 2006; Chanasyk et al., 2003; Benaman et al., 2005), , which could be one reason that the low values of the Nash Sutcliffe efficiency for the Shiyang and Chaobai rivers in the northern China with cold winter. It can be summarized that appears to capture successfully the underlying hydrology of the four river basins evaluated by the three statistic metrics and compared by the monthly discharge series, and flow duration curve. The successful application of the SWAT in different climate regions is considered adequate verification of the suitability of the model for future climate change impact
- 20 on runoff in the four selected basins.

25

3.2 Climate change projection and runoff simulation

The future scenarios for limiting global warming thresholds of 1.5 $\$ and 2.0 $\$ were derived based on 30-year running mean of global mean temperature (GMT) followed the methodology of Liu et al. (2017) for each one of the 20 combinations under four RCPs and five GCMs of the climate projection subset. Table S5 showed the averaged middle year of the 30-year samples for all GCMs under each RCPs of 1.5 $\$ and 2.0 $\$ global warming. There were 18 scenarios under the threshold of -1.5 $\$ above preindustrial levels and 16 scenarios under the threshold of -2.0 $\$. These scenarios were used to quantify the difference in the changes of the projected annual temperature and precipitation in the four river basins by comparing with the baseline period (1976-2005).

To indicate the overall magnitude and difference of the climate change projection under limiting global warming thresholds

30 of 1.5 ℃ and 2.0 ℃, the projected changes in mean annual temperature and annual precipitation were quantified by the value of ensemble mean under all climate scenarios (Ave.), and the projected changes in maximum and minimum annual temperature and annual precipitation (Max. and Min.) among all climate scenarios. The uncertainty caused by RCPs was estimating using standard deviation of the mean of all GCMs under 1.5℃ and 2.0℃ global warming respectively, and the

uncertainty constrained by GCMs was estimated using standard deviations of all RCPs under the two threshold of global warming, whereas the all source of uncertainty of climate change scenarios was estimating using the standard deviation of all the 18 and 16 climate scenarios under 1.5° C and 2.0° C global warming.

The hydrological simulation adopted the climate projection subset for the downscaling climate data, and the future climate

- 5 scenarios from five GCM and validated SWAT models s in the four basins, and projected the impact of climate change on river discharges. Generally, the hydrological simulations based on downscaling climate data from five GCMs for baseline period compared well with those based on WFD, and were acceptable subsequent hydrological projection (Table-Tab. S6 and Figure-Fig. S3). The changes in averages of the annual and monthly runoff were compared based on the simulated runoff under all climate scenarios and with the simulated runoff based on the baseline period (1976-2005) from the five GCMs for baseline rather than the actual observed discharge data or simulated discharge forcing by WFD.
- The simulated changes in mean annual runoff were quantified by the value of ensemble mean annual runoff of all climate scenarios under 1.5°C and 2.0°C global warming, and mean annual runoff under RCP 2.6, RCP4.5, RCP6.0 and RCP8.5 respectively, and mean annual runoff under GCM GFDL-ESM2M, HaDGem2, IPSL_CM5A-LR, MIROC-ESM-CHEM, and NorESM1-M respectively. The simulated changes in monthly runoff were analysis by the proportion of monthly runoff in
- annual runoff using the mean of baseline period for 5 GCMs, and <u>ensemble</u> mean, maximum and minimum of simulated monthly runoff under all combined climate scenarios of GCMS and RCPs for 1.5 °C and 2.0 °C global warming, respectively.

4 Results

4.1 Projected climate change

The statistics of the projected climate change for the four basins from the <u>16-18</u> scenarios under 1.5 °C warming and the <u>18</u> <u>16</u> scenarios under 2.0 °C warming <u>are-were</u> shown in <u>Table Table.</u> 3. The results show substantial warming for all four basins under two thresholds global warming. The projected changes in ensemble mean annual temperature show 1.5 °C increase under 1.5 °C global warming and 2.2 °C increase under 2.0 °C warming for the <u>SYRhiyang</u> and the <u>Chaobai</u> rivers<u>CBR</u>. While, the projected changes in ensemble mean annual precipitation show 3% and 5% increase under 1.5 °C warming, and 5% and 8% increase under 2.0 °C warming for the <u>Shiyang-SYR</u> and the <u>Chaobai riversCBR</u>, respectively.
The projected changes in ensemble mean annual temperature show 1.1 °C and 1.2 °C increase under 1.5 °C warming, and 1.8 °C increase under 2.0 °C warming for the <u>Huaihe-HHR</u> and the <u>Fujiang riversFJR</u>. The projected changes in ensemble mean annual precipitation are minor for the <u>Huaihe-HHR</u> and Fujiang riversFJR (i.e., <±3%). All statistics for the two basins in northern China indicate generally warmer and wetter conditions in future compared with the 'present day.' The two basins in southern China are projected to have less warming and no consistent change in the projected ensemble mean annual precipitation.

The greatest range in projected changes in annual mean temperature occurs in the HHRHuaihe River, with the warming range of 0.3--1.6 °C under 1.5 °C warming and that of 0.7--2.3 °C under 2.0 °C warming among all projection scenarios. The projected range in annual temperature is also large for the Shivang SYRiver, with change in the range of warming 0.9– ~2.4 °C under 1.5 °C warming and that of 1.7-2.9 °C under 2.0 °C warming, respectively. There is no consistency in the

5 direction of range in projected annual precipitation change among the four river basins, with increases ranged 10% to 20% and decreases ranged -6% to -11%. For the two river basins in southern China, the range in projected change in annual precipitation is less than for the two basins in northern China.

The uncertainty is substantial in annual precipitation projection compared with that associated with annual temperature projection, with considerable dispersion among the scenarios. Comparing the uncertainty under limiting global warming under thresholds of 1.5 $^{\circ}$ C -and 2.0 $^{\circ}$ C, the former has larger uncertainties for the projected change in annual precipitation

- than that under the later; however, it is the opposite for the projected change in annual temperature. There is generally larger uncertainty constrained by the GCMs (i.e., about 1-3 times) than associated with the RCPs for the projected annual precipitation for all four river basins. However, the uncertainty in annual temperature projection associated
- with the RCPs is larger in the Shivang-SYR River (about 2 times) and in the Huaihe RiverHR (about 1.5-23.0 times) than 15 constrained with the GCMs. All these findings show the uncertainty in the projection of annual precipitation mainly constrained by GCM structure across the four river basins, whereas the dominance of the uncertainty associated with either the GCMs or the RCPs in the projection of annual mean temperature is dependent on the basin.

4.2 Simulated annual river runoff

Figure 2 shows the simulated ensemble mean annual river runoff based on all combined climate scenarios, and the average 20 simulated annual river runoff of the four RCPs and the average of the five GCMs. The simulated ensemble mean annual runoff decreases for the Shiyang RiverYR by about 25% and 33% under 1.5 °C and 2.0 °C warming, respectively, and the simulated change for the Fujiang RiverJR shows a decrease of about 4% under 1.5 °C warming. The simulated ensemble mean annual river runoff shows an increase with magnitude of about 8% and 12% for the Chaobai RiverBR and about 8% and 7% for the Huaihe RiverHR under 1.5 °C and 2.0 °C warming, respectively.

- 25 The decrease in the simulated annual river runoff for the Shiyang RiverYR occurs across all the combined scenarios, ranging ranged from 0% to -72% under 1.5 °C warming and from -11% to -63% under 2.0 °C warming. For the other three river basins, the change in simulated annual river runoff ranges from an increase of 57% to a decrease of 34%. The smallest range occurs in the Fujiang RiverJR, with a change in simulated annual river runoff in the ranged 10% to -17% and 11% to -11%under 1.5 °C and 2.0 °C warming, respectively. The largest range occurs in the Huaihe River<u>HR</u>, with a change in simulated annual river runoff in the ranged from 57% to -34% under 1.5 °C warming and from 38% to -32% under 2.0 °C warming. 30

The simulated change in annual river runoff for the mean of the four RCPs and the five GCMs shows consistent decrease in the range -61% to -14% under 1.5 °C warming and -56 to -18% under 2.0 °C warming for the Shiyang River<u>YR</u>, with the largest decrease occurring under RCP2.6. The simulated annual river runoff under the mean of the four RCPs for the Chaobai River-BR shows consistent increase in the range 3% to 13% under 1.5 °C warming and 6% to 19% under 2.0 °C

- 5 warming. For the Huaihe River<u>HR</u>, the simulated annual river runoff under RCP2.6 shows reduction of -33% and -25% under 1.5 °C and 2.0 °C warming, respectively, whereas it increases under the other scenarios by 6% to 20% and 10% to 17%, respectively. For the Fujiang River<u>FJR</u>, the simulated annual river runoff shows reduction for all RCPs under 1.5 °C warming, but an increase for RCP4.5 and RCP6.0 under 2.0 °C warming.
- The simulated annual river runoff for the Chaobai River<u>BR</u> under HaDGem2 for the mean of the four RCPs shows decrease of about -9% and -2% under 1.5 °C and 2.0 °C warming, respectively, while that of the Huaihe River<u>HR</u> under NorESM shows decrease of about -12%. However, for the Fujiang River<u>JR</u>, most GCMs show reduction for the simulated annual river runoff in the range<u>d of from</u> 0% to -14% under 1.5 °C warming and from 0% to -5% under 2.0 °C warming, while any increase is no larger than 3%.
- There is less uncertainty in the simulated annual river runoff among all the scenarios under 2.0 $^{\circ}$ than that of 1.5 $^{\circ}$ warming when quantified by standard derivation. The uncertainties associated with the RCPs are 1.3–2.6 times with those constrained by the GCMs for the Shiyang-SYR and the FJRujiang rivers, while for the Chaobai RiverBR, the uncertainties constrained by the GCMs are 2–23 times those associated with the RCPs. For the Huaihe RiverHR, the uncertainties associated with the RCPs are the largest under 1.5 $^{\circ}$ warming, whereas those constrained with the GCMs are the largest under 1.5 $^{\circ}$ warming.

20 4.3 Simulated seasonal river runoff

25

Figure 3 shows the change in the proportion (mean monthly percentage of annual runoff) of maximum, average, and minimum simulated river runoff based on all combined scenarios. For the Shiyang-SYR and Fujiang riversJR, the proportion shows no substantial change (i.e., <1.0%). For the Chaobai RiverBR, a decrease occurs during May–July with magnitude of about 1.0% to 2.0%, and an increase occurs mainly in September and October with magnitude of <2.0% under 1.5 $^{\circ}$ C warming. Similarly, a decrease occurs during May–August with magnitude of 0.4% to 2.3% and an increase occurs in September with magnitude of about 2.0% under 2.0 $^{\circ}$ C warming. While, a decrease occurs mainly during June–August for the Huaibe RiverHR, with magnitude of about 1.0% to 3.5% and 1.2% to 3.4%, while an increase occurs in May with magnitude of about 2.0% and in September with magnitude of <5% under 1.5 $^{\circ}$ C and 2.0 $^{\circ}$ C warming, respectively.

For all months, there are generally larger ranges for the mean monthly percentage of annual runoff for 1.5 °C warming. 30 These results indicate the uncertainties in simulated monthly runoff are larger under 1.5 °C warming than under 2.0 °C warming.

5 Discussion and conclusion

5.1 DiscussionClimate change impact on runoff

Chen et al. (2014) analyzed the effects of climate change on runoff in the Asian monsoon region. They indicated that different basins respond differently to the same climate change scenario. For example, they found that the change in runoff

- 5 of the Haihe River basin in northern China is highly sensitive to precipitation and temperature. It was established that a considerable increase in precipitation (about 4%) would be required to keep runoff unchanged in this semi-humid basin in Northeast China, while a smaller precipitation increase (about 2.8%) would be required to maintain runoff in wetter basins in South China. Precipitation is the main input of surface water resources and evapotranspiration (ET) is the main output. Previous studies have explored the climatic impacts of ET and runoff in China. For example, Liu et al. (2012) analyzed the
- 10 <u>environmental stress on ET and runoff over eastern China for 1961–2005. They found ET increased in most river basins,</u> while runoff increased in the Pearl River and the southeast river basins in southern China but it decreased in the basins of the Haihe and Huaihe rivers in northern China. It was determined that climate change was the dominant factor governing the long-term trend of ET and runoff in southern China. Ma et al. (2008) indicated that decreased precipitation and increased potential ET contribute most to the <u>observed</u> reduction of streamflow in <u>SYR in</u> northwest China.
- 15 The four river basins in this study represent climate from dry to wet, and the response of runoff to precipitation change also coincided with the previous findings (Chen et al., 2014) that more increase in precipitation need to maintain runoff in drier basins. In this study, a smaller precipitation change (±3%) would cause a change in runoff of about 7% and 8% in the HHR and of about 0% and −4% in the FJR under 1.5 ℃ and 2.0 ℃ warming in the wetter area; while, for the CBR in a semi-humid climate area, an increase in precipitation of about 5% and 7% would cause an increase in runoff of about 8% and 12%
- under 1.5 °C and 2.0 °C warming. Moreover, in SYR in the arid climate region, an increase in precipitation of about 5% and 7% companied with a decrease in runoff of about -33% and -25% in the SYR. Further analysis of ET simulation (Fig.4) indicated a general increase in simulated ET in all four basins. However, the magnitude of the simulated change of ET varies across the basins, i.e., it is larger in the two basins in north China than in the two basins in south China. For the two rivers located in northern China, the simulated change of ET in the SYR shows increase of 21% and 13%, while that of the CBR shows increase of 4% and 6% under 1.5 °C and 2.0 °C warming, respectively, which implies the increase in simulated ET contributes most to the decrease in simulated annual runoff in the SYR.
 - 5.2 Uncertainties in the quantitative assessment

30

Precipitation is the main input of surface water resources and evapotranspiration (ET) is the main output. Previous studies have explored the elimatic impacts of ET and runoff in China. For example, Liu et al. (2012) analyzed the environmental stress on ET and runoff over eastern China for 1961–2005. They found ET increased in most river basins, while runoff increased in the Pearl River and the southeast river basins in southern China but it decreased in the basins of the Haihe and Huaihe rivers in northern China. It was determined that elimate change was the dominant factor governing the long term

trend of ET and runoff in southern China. Ma et al. (2008) indicated that decreased precipitation and increased potential ET contribute most to the reduction of streamflow in northwest China. In this study, the simulated changes in annual river runoff showed opposing characteristics with decrease in the Shiyang River in northwest China and increase in the Chaobai River in north China, although the annual precipitation projection in the two river basins increased consistently. Figure 4 shows change in simulated ET in the four river basins based on the SWAT. The results indicate a general increase in simulated ET in all four basins. However, the magnitude of the simulated change of ET varies across the basins, i.e., it is larger in the two basins in north China than in the two basins in south China. The simulated change of ET in the Shiyang River shows increase of 21% and 13%, while that of the Chaobai River shows increase of 4% and 6% under 1.5 °C and 2.0 °C warming, respectively, which implies the increase in simulated ET contributes most to the decrease in simulated annual runoff in the China et al.

10 Shiyang River.

5

Chen et al. (2014) analyzed the effects of climate change on runoff in the Asian monsoon region. They indicated that different basins respond differently to the same climate change scenario. For example, they found that the change in runoff of the Haihe River basin is highly sensitive to precipitation and temperature. It was established that a considerable increase in precipitation (about 4%) would be required to keep runoff unchanged in this semihumid basin in Northeast China, while a

- 15 smaller precipitation increase (about 2.8%) would be required to maintain runoff in wetter basins in South China. As mentioned in Section 2.1, the four river basins in this study are located in different climatic zones and they have different hydrological processes. For the Chaobai River in a semihumid climate area, an increase in precipitation of about 5% and 7% would cause an increase in runoff of about 8% and 12% under 1.5 °C and 2.0 °C warming. However, a smaller precipitation increasing (±3%) would cause a change in runoff of about 7% and 8% in the Huaihe River and of about 0% and -4% in the
- 20 Fujiang River under 1.5 °C and 2.0 °C warming. While, an increase in precipitation of about 5% and 7% caused a decrease in runoff of about =33% and =25% in the Shiyang River. Li et al. (2016) indicated that frozen soil meltwater accounted for about 20% of river runoff during the flood season, while glacier meltwater contributed only about 3% in the Shiyang River. However, the glacier meltwater process was not considered in SWAT based simulations in this study, which would have also contributed to the decrease in simulated annual runoff in the Shiyang River.
- 25 This study followed the top-down methodology that common used in IPCC AR4 and AR5 WGII report. Within the IPCC AR 4 and AR5 water sector, most hydrological projection studies use the precipitation and temperature downscaled from GCMs to driven hydrological models. This study adopted climate projection information derived from Inter-Sectorial Impact Model Intercomparison Project (ISIMIP). Climate outputs are spatially interpolated into 0.5 °×0.5 ° resolution and corrected using trend-preserving bias correction approach based on reanalysis dataset WFD. The WFD was also the climate forcing to
- 30 calibrate and validate of SWAT hydrological model. There were multi sources of uncertainties in climate change impact assessment in this study. Considering the challenge to address uncertainties for all sources, which we only focus on the uncertainties constrained by GCMs and RCPs. Certain uncertainty source were not investigated, such as the climate forcing, hydrological model structure and parameterization, GCM structure.

<u>Climate forcing is one of major uncertainty in quantitative assessment of climate change impact (Müller Schmied et al.,</u> <u>2014). However, tThe he complex complex</u> terrain in different the four river basins makes it difficult for reanalysis data<u>WFD</u> to reach very satisfactory agreement with station based observation. <u>TOhe comparison of WFD with climate observation from</u> meteorological station showed reasonable agreement (Fig. S1 and Table S1), but, there wasur study show both underestimation and

- 5 overestimation in precipitation and temperature <u>based on WFD</u>.—<u>.</u><u>T</u>his could induce the uncertainty in the river runoff <u>hydrological simulation</u>, <u>such as difference in the ET simulation in SYR (Fig. S5</u>). <u>However, previous research indicates that the</u> <u>gridded climate dataset can be used in hydrological modeling, and the performance of hydrological model will improve by model</u> <u>calibration and validation (Xu et al., 2011)</u>. Furthermore, the <u>validated</u> SWAT <u>hydrological model calibrated and validated based</u> <u>on WFD, then</u>-driven by downscaling climate data from GCMs for baseline period and climate scenarios under 1.5 °C and 2.0 °C
- 10 global warming. Although, the method used for estimated the projected changes in runoff could avoid systematic errors that the SWAT model would introduce in comparing the projection period with the baseline period. However, <u>This_uncertainty in runoff</u> <u>simulation would spread to the runoff assessment could also induce the uncertainty in the river runoff simulation.</u> Meanwhile, the application SWAT in four river basins covered various climate and environmental condition may result in

uncertainty constrained by hydrological model structure and parameterization. Li et al. (2016) indicated that frozen soil meltwater

- 15 accounted for about 20% of river runoff during the flood season, while glacier meltwater contributed about 3% in the SYR. There was a few cases showed that SWAT could be used in snowmelt-dominated streamflow (Wang and Melesse, 2005; Tolston and Shoemaker, 2007; Grusson et al., 2015), a few previous researches have indicate that SWAT model did not adequately predict winter flows or snowmelt-dominated runoff in several watershed (Peterson and Hamlett, 1998; Srivastava et al., 2006; Chanasyk et al., 2003; Benaman et al., 2005), which could be one reason that the low values of E_{ns} for the SYR and the
- 20 <u>CBR in the northern China with cold and dry winter. This also could induce the uncertainty in the river runoff simulation.</u> <u>Furthermore, the glacier meltwater process was not considered in SWAT-based simulations in this study, which would enlarge the uncertainty in runoff assessment.</u>

Moreover, GCM selection would introduce uncertainty and influence the range of climate change impact assessment (Todd et al., 2011). The five GCMs used in this study, which captured 50 to 90% of the full range of future projections of 36

- 25 <u>CMIP5 GCMs for temperature and 40 to 90% of the full range of future projections for precipitation in the four river basins</u> (Fig. 1 in McSweeney and Jones 2016). Furthermore, Liu et al. (2017) compared the changes of precipitation and temperature by five GCMs used in this study with those of other 19 CMIP5 GCMs. The results showed that the five GCMs covered the range of GCMs from CIMP5 well for global mean precipitation and temperature during 2020-2050 for RCP2.6 and RCP4.5. The information indicates the importance for reducing uncertainty associated with the choice of an applied
- 30 <u>GCM. At the basin scale, prioritising or weighting GCMs may be considered on the basis of detailed analyses of the ability</u> of an individual GCM to represent a specific characteristic of regional climate of interest (e.g., multi-annual or decadal variability).

5.2 6 Conclusion

5

The 2.0 \C warming scenario caused more substantial warming than the 1.5 \C warming scenario in all four studied basins. For the two basins located in northern China, the 0.5 \C global warming difference caused warming of 0.7 \C in the local ensemble mean temperature; however, in southern China, this difference caused warming of 0.6 \C . The 0.5 \C global warming difference will cause consistently wetter conditions, with projected precipitation amounts about 2% greater for the four basins, although the projected changes in annual precipitation are minor in southern China compared with the increases in northern China.

The 2.0 °C warming caused a decrease of 8% and 1% in the simulated ensemble mean annual runoff in the Shiyang-SYR and the HHRHuaihe rivers compared with 1.5 °C warming, while it caused 4% increasing in the Chaobai–CBR and the FJRFujiang rivers. Climatic–hydrological interaction increases the complexity of changes in simulated annual runoff; however, the 0.5 °C global warming difference will cause a "wet-get-wetter" and "dry-get-drier" response in the two basins in northern China, and it will moderate the simulated annual runoff in the two basins in southern China. There is no shift in seasonal runoff pattern attributable to the effects of projected changes in climate under 1.5 °C and 2.0 °C warming; however, the monthly runoff percentage does change in the Chaobai–CBR and the HHRHuaihe rivers in some months.

- 15 the monthly runoff percentage does change in the Chaobai-CBR and the HHRHuaihe rivers in some months. The range of projected annual temperature is largest for the Huaihe River<u>HHR</u> and the Shiyang River<u>SYR</u>, with the uncertainties dominated mainly by the RCPs. Conversely, the ranges are smallest in the Chaobai River basin<u>CBR</u> and the Fujiang River basin<u>FJR</u>, with the uncertainties mainly constrained by the GCMs. Although, the range in the projected change in annual precipitation is smaller in the two basins in southern China than in the two basins in northern China, the GCMs
- 20 constitute the major source of the uncertainties in the projection of annual precipitation for the four river basins. Even under the limiting global warming thresholds of 1.5 °C and 2.0 °C, the uncertainties in the projected annual temperature at local or regional scale are dominated by either the GCMs or the RCPs; however, the uncertainties in local and regional projected annual precipitation are mainly constrained by GCM structure. The 0.5 °C global warming difference will generally reduce the uncertainties in the projected change in annual precipitation.
- 25 There is less uncertainty in the simulated change in runoff among all scenarios under 2.0 °C warming compared with 1.5 °C warming. This is consistent with the uncertainty in the projected annual precipitation. However, the uncertainties, dominated by the GCMs for the Chaobai River and constrained by the RCPs for the Shiyang-SYR and the FJRFujiang rivers, limit confidence in the projected annual runoff for the four studied river basins. Generally, there are less uncertainties in the simulated monthly runoff under the 2.0 °C warming.
- 30 Acknowledgments: We wish to thank the Inter-Sectoral Impact Model Intercomparison Project (ISIMIP), which make the data of the five GCMs available. This study was jointly supported by the National Key R&D Program of China

(2016YFE0102400), research project of the Meteorological Public Welfare Industry in China (GYHY201406021), and climatic change project of the China Meteorological Administration (CCSF201810).

References

5

<u>Arnold, J. G.; Moriasi, D. N.; Gassman, P. W.; Abbaspour, K. C.; White, M. J.; Srinivasan, R.; Santhi, C.; Harmel, R. D.;</u>
 <u>Van Griensven, A.; Van Liew, M. W.; Kannan, N.; and Jha, M. K. SWAT: model use, calibration and validation. Trans.</u>
 ASABE. 55:1491–1508,2012.

Benaman, J., C. A. Shoemaker, and D. A. Haith. Calibration and validation of Soil and Water Assessment Tool on an agricultural watershed in upstate New York. J. Hydrol. Eng.10(5): 363–374, 2005.

Chen, J., Gao, C., Zeng, X., et al.: Assessing changes of river discharge under global warming of 1.5 °C and 2 °C in the upper reaches of the Yangtze River Basin: Approach by using multiple- GCMs and hydrological models, Quat. Int., 453, 63-67, https://doi.org/10.1016/j.quaint.2017.01.017, 2017.

Asian monsoon areas, J. Hydrol., 517, 595-606, https://doi.org/10.1016/j.jhydrol.2014.05.075, 2014.
 Chen, X. and Zhou, T.: Uncertainty in crossing time of 2 °C warming threshold over China, Chin. Sci. Bull., 61, 451-1459, https://doi.org/10.1007/s11434-016-1166-z, 2016.

20 Essou, G., Sabarly, F., Lucas, P., et al.: Can precipitation and temperature from meteorological reanalyses be used for hydrological modeling?, J. Hydrometeoro., 17(7), 1929-1950, https://doi.org/10.1175/JHM-D-15-0138.1, 2016. FAO/IIASA/ISRIC/ISS-CAS/JRC.: Harmonized World Soil Database (version 1.0). FAO, Rome, Italy and IIASA, Laxenburg, Austria, 2008.

- 25 analysis in ungauged or poorly gauged tributaries of China's Yangtze River basin, J. Hydrol., 550, 478-496, https://doi.org/10.1016/j.jhydrol.2017.05.025, 2017.
 - Gassman, P.W., Reyes, M.R., Green, C.H., and Arnold, J.G.: The soil and water assessment tool: historical development, applications and future research directions, T. ASABE., 50, 1211–1250, 2007.
 - Gosling, S., et al.: A comparison of changes in river runoff from multiple global and catchment-scale hydrological models
- 30 under global warming scenarios of 1 ℃, 2 ℃ and 3 ℃, Clim. Change, 141(3), 577-595, https://doi.org/10.1007/s10584-016-1773-3, 2017.

Chanasyk, D. S., E. Mapfumo, and W. Willms. Quantification and simulation of surface runoff from fescue grassland watersheds. Agric. Water Mgmt. 59(2): 137–153, 2003.

Chen, J., Xia, J., Zhao, C., et al.: The mechanism and scenarios of how mean annual runoff varies with climate change in

Compiling Committee for "Third National Assessment Report for Climate Change": Third National Assessment Report for Climate Change, Science Press, Beijing, 2015.

Gao, Z., Long, D., Tang, G., et al.: Assessing the potential of satellite-based precipitation estimates for flood frequency

- Grunwald, S., and C. Qi. GIS-based water quality modelling in the Sandusky watershed, Ohio, USA. J. American Water Resour. Assoc. 42(4): 957–973, 2006.
- Haddeland, I., et al.: Global water resource affected by human interventions and climate change, Proc. Natl. Acad. Sci. USA., 111(9), 3251-3256, https://doi.org/10.1073/pnas.1222475110, 2014.
- 5 Y. Hao, J. Ma, J. Chen, D. Wang, Y. Wang*, H. Xu. Assessment of Changes in Water Balance Components under 1.5 °C and 2.0 °C Global Warming in Transitional Climate Basin by Multi-RCPs and Multi-GCMs Approach. Water, 10.1863, https://doi.org/10.3390/w10121863, 2018.
 - Hattermann, F., et al.: Cross-scale intercomparison of climate change impacts simulated by regional and global hydrological models in eleven large river basins, Clim. Change, 141(3), 561-576, https://doi.org/10.1007/s10584-016-1829-4, 2017.
- Hempel, S., Frieler, K., Warszawski, L., et al.: A trend-preserving bias correction-the ISIMIP approach, Earth. Syst. Dynam.,
 4, 219–236, https://doi.org/10.5194/esd-4-219-2013, 2013.
 - Huber, V., et al.: Climate impact research: beyond patchwork, Earth. Syst. Dynam., 5(1), 399-408, https://doi.org/10.5194/esd-5-399-2014, 2014.

IPCC.: Climate change 2013: the physical science basis. Contribution of working group I to the fifth assessment report of the

15 IPCC, Cambridge University Press, New York, 2013.

20

- IPCC.: Climate change 2014: impact, adaptation, and vulnerability. Part A: Global and sectoral aspects. Contribution of working group II to the fifth assessment report of the IPCC, Cambridge University Press, Cambridge, 2014.
- Li, Z., Qi, F., Wang, Q.J., et al.: Contribution from frozen soil meltwater to runoff in an in-land river basin under water scarcity by isotopic tracing in northwestern China, Glob. Planet. Change., 136, 41-51, http://dx.doi.org/10.1016/j.gloplacha.2015.12.002, 2016.
- Liu, L., Xu, H., Wang, Y., and Jiang, T.: Impacts of 1.5 and 2 °C global warming on water availability and extreme hydrological events in Yiluo and Beijiang River catchments in China, Clim. Change, 145(10), 1-14, https://doi.org/10.1007/s10584-017-2072-3, 2017.
- Liu, L., Jiang, T., Xu, J., Luo, Y. Research on the hydrological processes using multi-GCMs and multi-scenarios. J. Hydral.
- Eng., 43 (12), 1413-1421, 2012a.
 Liu, L., Jiang, T., Xu, H., Wang, Y. Potential threats from variations of hydrological parameters to the Yellow River and Pearl River Basins in China over the Next 30 Years. Water, 10(7), 883. https://doi.org/10.3390/w10070883, 2018.

Liu, M., Tian, H., Lu, C., et al.: Effects of multiple environment stresses on evapotranspiration and runoff over eastern China,
 J. Hydrol., 426-427, 39-54, https://doi.org/10.1016/j.jhydrol.2012.01.009, 2012b.

- 30 Ma, Z., Kang, S., Zhang, L., et al.: Analysis of impacts of climate variability and human activity on streamflow for a river basin in arid region of northwest China, J. Hydrol., 352, 239-249, https://doi.org/10.1016/j.jhydrol.2007.12.022, 2008.
 - McSweeney, C.F. and Jones, R.G.: How representative is the spread of climate projections from the 5 CMIP5 GCMs used in ISI-MIP?, Climate. Serv., 1, 24–29, https://doi.org/10.1016/j.cliser.2016.02.001, 2016.

Moriasi, D.N., et al.: Model evaluation guidelines for systematic quantification of accuracy in watershed simulations, Trans. Asabe., 50(3), 885–900, 2007.

- Müler Schmied, H., Eisner, S., Franz, D., Wattenbach, M., Portmann, F. T., Flörke, M., and Döll, P.: Sensitivity of simulated global-scale freshwater fluxes and storages to input data, hydrological model structure, human water use and
- calibration, Hydrol. Earth Syst. Sci., 18, 3511-3538, https://doi.org/10.5194/hess-18-3511-2014, 2014.
- Peterson, J. R., and J. M. Hamlet. Hydrologic calibration of the SWAT model in a watershed containing fragipan soils. J. American Water Resour. Assoc. 34(3): 531-544, 1998.
- Schellnhuber, H.J., Frieler, K., Kabat, P.: The elephant, the blind, and the intersectoral intercomparison of climate impacts, Proc. Natl. Acad. Sci. USA., 111(9), 3225-3227, https://doi.org/10.1073/pnas.1321791111, 2014.
- 10 Schewe, J., et al.: Multimodel assessment of water scarcity under climate change. Proc. Natl. Acad. Sci. USA., 111(9), 3245-3250, https://doi.org/10.1073/pnas.1222460110, 2014.
 - Schleussner, C.F., et al.: Differential climate impacts for policy-relevant limits to global warming: the case of 1.5 °C and 2 °C, Earth. Syst. Dynam., 6(2), 2447-2505, https://doi.org/10.5194/esd-7-327-2016, 2016.

Schmied, H. M., et al.: Variations of global and continental water balance components as impacted by climate forcing

- 15 uncertainty and human water use, Hydrol. Earth Syst .Sci., 20, 2877-2898, https://doi.org/10.5194/hess-20-2877-2016, 2016.
 - Srivastava, P., J. N. McNair, and T. E. Johnson. Comparison of process-based and artificial neural network approaches for streamflow modeling in an agricultural watershed. J. American Water Resour. Assoc. 42(2): 545–563, 2006.
- Su, B., Huang, J., Zeng, X., Gao, C., and Jiang, T.: Impacts of climate change on streamflow in the upper Yangtze River basin, Clim. Change, 141 (3), 533-546, https://doi.org/10.1007/s10584-016-1852-5, 2017.
 - Todd, M. C., Taylor, R. G., Osborn, T. J., Kingston, D. G., Arnell, N. W., and Gosling, S. N. Uncertainty in climate change impacts on basin-scale freshwater resources preface to the special issue: the QUEST-GSI methodology and synthesis of results, Hydrol. Earth Syst. Sci. 15:1035–1046, https://doi.org/10.5194/hess-15-1035-2011, 2011.
- Tolson, B. A., and C. A. Shoemaker. Cannonsville reservoir watershed SWAT2000 model development, calibration, and validation. J. Hydrol. 337(1-2): 68–86, 2007.

UNFCCC.: Decision 1/CP.21, The Paris Agreement, 2015.

Wang, S., Xu, H., Liu, L., Wang, Y., Song, A. Projection of the Impacts of GlobalWarming of 1.5°C and 2.0°Con Runoff in the Upper-Middle Reaches of Huaihe River Basin. J. Nat. Resour. 33(11): 1966-1978, 2018 (in Chinese).

Wang, X., and A. M. Melesse. Evaluation of the SWAT model's snowmelt hydrology in a northwestern Minnesota watershed. Trans. ASABE 48(4): 1359-1376, 2005.

30

Warszawski, L., Frieler, K., Huber, V., et al.: The Inter-Sectoral Impact Model Intercomparison project (ISI–MIP): project framework, Proc. Natl. Acad. Sci. USA., 111(9), 3228–3232, https://doi.org/10.1073/pnas.1312330110, 2014.

Weedon, G.P., Gomes, S., Viterbo, P., et al.: The WATCH forcing data 1958-2001: a meteorological forcing dataset for land surface- and hydrological, WATCH Technical Report No. 22 pp1-41, Available at http://www.eu-watch.org, 2010.
Xia, B., et al.: Evolution of the significance of abrunt changes in presinitation and pupelf process in China. J. Hydrol. 560.

Xie, P., et al.: Evaluation of the significance of abrupt changes in precipitation and runoff process in China, J. Hydrol., 560, 451-460, https://doi.org/10.1016/j.jhydrol.2018.02.036, 2018.

 Xu, H., Taylor, R., Kingston, D., Jiang, T., Thompson, J., and Todd, M.: Hydrological modeling of River Xiangxi using SWAT2005: a comparison of model parameterizations using station and gridded meteorological observations, Quatern. Int., 226, 54–59, doi:10.1016/j.quaint.2009.11.037, 2010b.

Xu, K., Milliman, J.D., Xu, H.: Temporal trend of precipitation and runoff in major Chinese Rivers since 1951, Glob. Planet.
 Change., 73 (3-4), 219–232, https://doi.org/10.1016/j.gloplacha.2010.07.002, 2010a.

Xu, X., Yang, D., Yang, H., et al.: Attribution analysis based on the Budyko hypothesis for detecting the dominant cause of runoff decline in Haihe basin, J. Hydrol., 510,530-540, https://doi.org/10.1016/j.jhydrol.2013.12.052, 2014.

Yang, Y. and Tian, F.: Abrupt change of runoff and its major driving factors in Haihe River Catchment, China, J. Hydrol.,

15 374 (3-4), 373-383, https://doi.org/10.1016/j.jhydrol.2009.06.040, 2009.

Zhang, W., Pan, S., Cao, L., et al.: Changes in extreme climate events in eastern China during 1960-2013: A case study of the Huaihe River Basin, Quat. Int., 380-381, 22-34, https://doi.org/10.1016/j.quaint.2014.12.038, 2015.

Zhang, W. and Villarini, G.: Heavy precipitation is highly sensitive to the magnitude of future warming, Clim. Change, 45(1-2), 249-257, https://doi.org/10.1007/s10584-017-2079-9, 2017.

20 Zhu, Q. and Li, Y.: Environmental Restoration in the Shiyang River Basin, China: Conservation, reallocation and more efficient use of water, Quati. Procedia., 24-34, https://doi.org/10.1016/j.aqpro.2014.07.005, 2014.

Xu, H. and Luo, Y.: Climate change and its impacts on river discharge in two climate regions in China, Hydrol. Earth Syst. Sci., 19, 4609-4618, https://doi.org/10.5194/hess-19-4609-2015, 2015.



15 Figure 1. Locations and average monthly precipitation/runoff of the four selected basins in China.



Figure 22. Changes in simulated annual river runoff: (a) SYRhiyang River, (b) CBRhaobai River, (c) HHRuaihe River, and (d) FJRujiang River under 1.5 °C and 2 °C global warming. (Baseline: 1976–2005; columns represent the simulated river runoff for all combined scenarios of GCMs and RCPs; hollow circles colored dark blue, red, green, blue, and purple
represent the GCMs: GFDL-ESM2M, HaDGem2, IPSL_CM5A-LR, MIROC-ESM-CHEM, and NorESM1-M, respectively; solid circles colored dark blue, red, green, and purple represent the RCPs: RCP2.6, RCP4.5, RCP6.0, and RCP8.5, respectively).



Figure <u>33</u>. Simulated proportion of monthly river runoff in annual runoff: (a) SY hiyang River, (b) Chaobai-CB River, (c) Huaihe-HH River, and (d) Fujiang FJ River under 1.5 and 2.0 °C global warming. (Baseline: 1976–2005; dotted line: mean of baseline for 5 GCMs, bars colored black and yellow show the maximum and minimum values of all simulated monthly runoff for all combined climate change scenarios of GCMs and RCPs; black diamonds and yellow crosses represent the mean values for monthly runoff for all combined climate change scenarios of GCMs and RCPs).



Figure 44. Same as in Figure 2 but for change in simulated annual ET.

Table 1. Hydroclimatic characteristics of the four selected basins.

Basin	Total Area	Study Area	A	Altitude(n	n)	1961-2000 A	verage(mm)
Dasiii	(Km ²)	(Km ²)	Max	Mean	Min	Precipitation	Runoff
Shiyang River<u>SYR</u>	41,600	11,000	5090	2448	1398	498	180
Chaobai River<u>CBR</u>	19,354	13,846	2266	930	38	469	53
Huaihe River <u>HHR</u>	144,900	121,330	2099	106	11	910	203
Fujiang River<u>FJR</u>	36,400	29,488	5541	1027	242	964	481

Table 2. Goodness of fit of SWAT simulations for monthly runoff of the <u>ShiyangSYR</u>, <u>ChaobaiCBR</u>, <u>HuaiheHHR</u>, and <u>Fujiang riversFJR</u>.

Basin		Calibrated area				51-1990)	Validation (1991-2001)		
	River	gauging	Area (km ²)	R^2	E_{ns}	P _{bias}	R^2	E_{ns}	P _{bias}
SYR	Xiying <mark>h</mark> e	Jiutiaoling	1,077	0.65	0.82	1%	0.71	0.58	7%
CBR	Chaohe	Xiahui	5,340	0.63	0.63	1%	0.68	0.65	8%
	Baihe	Zhangjiafeng	8,506	0.60	0.56	25%	0.77	0.61	-2%
HHR	Huaihe	Wujiadu	121,330	0.88	0.87	16%	0.86	0.81	8%
FJR	Fujiang	Xiaoheba	29,488	0.94	0.87	1%	0.93	0.87	5%

5 Table 3. Projected changes in annual mean temperature and annual precipitation for the four basins under 1.5 °C and 2.0 °C global warming.

	Global		Annual mean temperature					Annual precipitation					
Basin	warming	Changes (°C)		τ	Uncertainty		Changes (%)			Uncertainty			
		Ave.	Max.	Min.	All	GCMs	RCPs	Ave.	Max.	Min.	All	GCMs	RCPs
<u>SYR</u> Shiy	1.5°C	1.5	2.4	0.9	0.36	0.16	0.38	3	18	-11	7.0	6.6	5.0
ang	2.0°C	2.2	2.9	1.7	0.32	0.13	0.29	5	15	-6	6.0	4.7	2.1
River													
<u>CBR</u>	1.5°C	1.5	1.8	1.1	0.22	0.20	0.02	5	17	-11	7.3	6.0	2.2
Chaobai	2.0°C	2.2	2.8	1.7	0.33	0.15	0.06	7	20	-8	6.3	3.6	2.0
River													

HHR Hu	1.5°C	1.1	1.6	0.3	0.35	0.21	0.30	0	13	-9	6.3	4.4	4.3
aihe	2.0°C	1.8	2.3	0.7	0.38	0.12	0.35	3	13	-9	6.3	3.7	3.7
River													
<u>FJR</u> Fuji	1.5°C	1.2	1.7	0.8	0.23	0.24	0.06	-2	12	-10	5.6	5.0	3.8
ang	2.0°C	1.8	2.2	1.3	0.28	0.17	0.10				4.6	4.1	2.1
River								0	10	-6			

Supplement



5 Figure S1. The differences in monthly mean temperature and monthly precipitation based on WFD and meteorological observations in (a) SYR, (b) CBR, (c) HHR, and (d) FJR during 1961-2001.









Figure S<u>5</u>3. The agreements in simulated mean monthly runoff and mean monthly evapotranspiration based on WFD and downscaling climate data from 5 GCMs during 1961-2001 for the four river basins.

Table S1. The differences in annual mean temperature and precipitation based on WFD and meteorological observations during 1961-2001 for the four river basins.

Divor		Annual precipit	ation	Annual mean temperature			
River	OBS(mm)	WFD (mm)	Difference (%)	OBS(℃)	WFD(℃)	Difference (°C)	
<u>ShiyangSYR</u>	246.1	282.1	14.6	5.2	2.7	-2.5	
Chaobai <u>CBR</u>	570.7	476.5	-20.0	9.2	5.1	-4.1	
HuaiheHHR	917.6	898.7	-2.1	14.9	14.8	-0.1	
FujiangFJR	906.0	894.6	-1.3	16.5	15.6	-0.9	

Table S2. The agreements in annual mean, maximum and minimum temperature, and mean annual precipitation based on WFD and downscaling climate data from five GCMs for during 1961-2001 for the four river basins.

River	GFDL-	HadGEM2-	IPSL-	MIROC-	NorESM1-M
	ESM2M	ES	CM5A-	ESM-	
			LR	CHEM	
		Difference in	mean annual	temperature (°C	C)
<u>SYR</u>	-0.01	-0.03	0.02	-0.00	-0.03
Shiyang					
CBRChao	-0.01	-0.02	0.08	-0.03	-0.01
bai					
<u>HHR</u> Huai	-0.01	0.01	0.07	-0.03	-0.05
he					
<u>FJR</u> Fujian	0.31	0.31	0.36	0.33	0.29
g					
River	Diff	ference in mear	n annual maxi	mum temperatu	re (°C)
<u>SYR</u> Shiya	0.00	0.07	0.04	0.02	0.04
ng					
CBR Chao	0.02	0.10	-0.02	0.00	0.02
bai					
<u>HHR</u> Huai	0.07	0.13	0.03	0.01	0.06
he					
<u>FJR</u> Fujian	0.24	0.29	0.25	0.23	0.27
g					
	Dif	ference in mean	n annual mini	mum temperatu	re (°C)
<u>SYR</u> Shiya	-0.01	0.03	0.01	-0.01	0.01
ng					
CBR Chao	-0.03	0.08	-0.02	-0.01	0.00
bai					

<u>HHR</u> Huai	0.00	0.05	-0.05	-0.07	-0.04
he					
<u>FJR</u> Fujian	0.37	0.41	0.39	0.34	0.35
g					
River		Difference in	mean annual	precipitation (%	ó)
<u>SYR</u> Shiya	14.8	7.8	13.3	6.3	5.2
ng					
CBR Chao	9.7	8.2	9.1	8.0	6.3
bai					
<u>HHR</u> Huai	4.9	5.4	5.3	3.9	4.8
he					
<u>FJR</u> Fujian	11.0	5.6	8.7	10.4	7.2
g					

Table S3. Sensitivity results for pre-define parameters by SWAT for the four river basins

Rank	Shiyang	Chaobai	Huaihe	Fujiang
	RiverSYR	River <u>CBR</u>	River <u>HHR</u>	RiverFJR
1	ALPHA_BF	CN2	CN2	CN2
2	GWQMN	ALPHA_BF	GWQMN	ESCO
3	TIMP	GW_DELAY	RCHRG_DP	SOL_AWC
4	CN2	ESCO	ESCO	CANMX
5	SMTMP	GWQMN	SOL_AWC	GWQMN
6	SOL_AWC	CH_N	GW_REVAP	RCHRG_DP

Table S4. Definition of identified sensitive parameters in SWAT hydrological model for the four river basins

Parameters	Definition	Processes
ALPHA_BF	Baseflow recession constant (days)	Groundwater
CANMX	Maximum canopy storage (mm H ₂ O)	Runoff
CH_N	Manning coefficient value	Channel
CN2	SCS runoff curve number for moisture condition II	Runoff
ESCO	Soil evaporation compensation factor	Evaporation
GW_DELAY	Delay time for aquifer recharge (days)	Groundwater
GW_REVAP	Groundwater "Revap" coefficient (days)	Groundwater
GWQMN	Threshold water level in shallow aquifer for base	Soil
	flow (mm)	

RCHRG_DP	Deep aquifer percolation coefficient (fraction)	Groundwater
SMTMP	Threshold temperature for snow melt (°C)	Snow
SOL_AWC	Soil available water capacity (mm/mm soil)	Soil
TIMP	Snow temperature lag factor	Snow

Table S5.The mean of middle-year of the 30-year samples for all GCMs under RCPs and under 1.5° C or 2° C global warming scenarios.

threshold	RCP2.6	RCP4.5	RCP6.0	RCP8.5
1.5℃	2029	2030	2032	2025
2.0°C	×	2049	2053	2038

Table S6. The agreements in mean annual runoff and evapotranspiration based on WFD and downscaling climate simulation from 5 GCMs for during 1961-2001 for the four river basins.

River	GFDL-	HadGEM2-	IPSL-	MIROC-	NorESM1-M				
	ESM2M	ES	CM5A-	ESM-					
			LR	CHEM					
		Difference in mean annual runoff (%)							
<u>SYR</u> Shiya	16.2	25.3	16.6	14.4	12.7				
ng									
CBR Chao	-19.3	21.5	0.5	-9.1	-2.3				
bai									
<u>HHR</u> Huai	-7.2	23.7	9.3	6.3	3.8				
he									
<u>FJR</u> Fujian	-6.2	-16.7	6.3	0.0	-4.3				
g									
River	Γ	Difference in me	ean annual ev	apotranspiration	n (%)				
<u>SYR</u> Shiya	-3.3	-37.7	-4.7	-19.8	-17.6				
ng									
CBR Chao	12.4	-0.5	6.6	7.5	3.2				
bai									
<u>HHR</u> Huai	-1.8	-8.1	0.8	3.2	4.8				
he									
<u>FJR</u> Fujian	15.5	13.4	4.7	11.7	12.7				
g									