

1 A soil non-aqueous phase liquid (NAPL) flushing laboratory 2 experiment based on measuring the dielectric properties of soil- 3 organic mixtures via time domain reflectometry (TDR)

4 Alessandro Comegna^{a*}, Antonio Coppola^a, Giovanna Dragonetti^b, Angelo Sommella^c

5 ^aSchool of Agricultural Forestry Food and Environmental Sciences (SAFE), University of Basilicata, Potenza, Italy.

6 ^bMediterranean Agronomic Institute, Land and Water Division, IAMB, Bari, 70010, Italy.

7 ^cDepartment of Agriculture, University of Naples “Federico II”, Italy.

8 *Correspondence to:* Alessandro Comegna (alessandro.comegna@unibas.it)

9 **Abstract.** The term non-aqueous phase liquid (NAPL) refers to a group of organic compounds with scarce solubility in
10 water. They are the products of various human activities and may be accidentally introduced into the soil system. Given
11 their toxicity level and high mobility, NAPLs constitute a serious geo-environmental problem. Contaminant distribution
12 in the soil and groundwater entails fundamental information for the remediation of polluted soil sites. The present research
13 explored the possible employment of time domain reflectometry (TDR) to estimate pollutant removal in a silt-loam soil
14 that was primarily contaminated with a corn oil as a light NAPL and then flushed with different washing solutions. Known
15 mixtures of soil and NAPL were prepared in the laboratory to achieve soil specimens with varying pollution levels. The
16 prepared soil samples were repacked into plastic cylinders and then placed in testing cells. Washing solutions were then
17 injected upward into the contaminated sample, and both the quantity of remediated NAPL and the bulk dielectric
18 permittivity of the soil sample were determined. The above data were also used to calibrate and validate a dielectric model
19 (the α mixing model) which permits the volumetric NAPL content (θ_{NAPL} ; m^3/m^3) within the contaminated sample to be
20 determined and quantified during the different decontamination stages. Our results demonstrate that during a
21 decontamination process, the TDR device is NAPL-sensitive: the dielectric permittivity of the medium increases as the
22 NAPL volume decreases. Moreover, decontamination progression can be monitored using a simple (one-parameter)
23 mixing model.

24 1. Introduction

25 Soil and groundwater contamination with NAPL from point or nonpoint sources is a severe problem of considerable
26 complexity (Fitts, 2002; Fetter, 1993). The repercussions concern not only the deterioration of the soil's physical,
27 mechanical and chemical properties, but also account for a potentially severe hazard to the well-being of humans and
28 other living species (Freeze, 2000).

29 Soil flushing is the technical procedure used for treating polluted soils with water, surfactants and co-solvents (such as
30 methanol, ethanol and propanols). Surfactant-enhanced flushing was developed from the conventional pump-and-treat

31 method. The success of this approach is related to the capacity of such chemical compounds to greatly enhance the
32 aqueous solubility of oils (Pennell et al., 1994; Parnian and Ayatollahi, 2008).

33 There is high interfacial tension between NAPL and water molecules that makes water a non-efficient cleaning material
34 in removing NAPL from the soil. Instead, surfactants and co-solvent agents can promote the enhanced removal of NAPL
35 from the subsurface through mobilization and solubilization (Martel et al., 1998; Rinaldi and Francisca, 2006; Parnian
36 and Ayatollahi, 2008).

37 Primary remediation entails the removal of the NAPL free phase by pumping. This extraction mechanism returns
38 appreciable effects if there is a region of high NAPL saturation. After primary pumping, a considerable portion of NAPL
39 remains constrained within the soil as capillary forces overcome viscous and buoyancy forces. This discontinuous NAPL
40 phase is referred to as trapped residual NAPL (or NAPL residual saturation), and its remediation is referred to as secondary
41 remediation (Parnian and Ayatollahi, 2008). Residual NAPL is a long-term source of soil and groundwater pollution
42 (Mercer and Cohen, 1990; Troung Hong and Bettahar, 2000).

43 To develop powerful decontamination procedures, the characterization of polluted soils is required. Practices usually
44 employed to characterize polluted soil sites are coring, soil sampling and the installation of monitoring wells for the
45 collection of water samples from aquifers (Mercer and Cohen, 1990). Since the above procedures are costly, different
46 dielectric techniques can be used to detect organic contaminants in soils. The most widely accepted geophysical technique,
47 based on the principle of electromagnetic wave (EMW) propagation, is ground penetrating radar (GPR; Knight, 2001).
48 Redman et al. (1991) described some field experiments in the application of GPR to detect NAPL plumes.

49 Rinaldi and Francisca (2006) used a coaxial impedance dielectric reflectometry (CIDR) technique to measure the complex
50 dielectric permittivity in sands contaminated by a paraffin oil. Their research into the dielectric behavior of NAPL-
51 contaminated soils during a decontamination process mainly focused on the removal efficiency of different washing
52 solutions, and on the spectral response of the contaminated medium during the various tests conducted.

53 TDR is a further geophysical device based on electromagnetic wave (EMW) principles that can also be used for this
54 purpose (Endres and Redman et al., 1993; Redman and De Ryck, 1994; Mohamed and Said, 2005; Moroizumi and Sasaki,
55 2006; Francisca and Montoro, 2012). Few experiments have been conducted coupling the TDR technique and NAPL. In
56 these studies estimation of NAPLs using TDR measurements of dielectric properties relies greatly on various mixing
57 models relating the measured dielectric permittivity to the volume fractions of the pore fluids and various soil phases such
58 as solid, water, air and NAPLs (van Dam et al., 2005).

59 Some interesting results were achieved by Persson and Berndtsson (2002) whilst investigating the influence of different
60 LNAPLs on TDR measurements in a homogeneous silica sand under saturated and unsaturated soil conditions.
61 Measurements of both dielectric permittivity and electrical conductivity allowed a method to be developed (the two-step

62 method) which measured the dielectric properties of the system against the amount of NAPL in soils. Comegna et al.
63 (2016) developed a general TDR-based methodology for evaluating the correlations between the dielectric response and
64 the NAPL content in variable saturated soils with different textures and pedological characteristics.

65 The purpose of this study was as follows: i) to investigate a possible extension of TDR technology to assess the effects
66 of NAPL removal in soils, and ii) revisit, on the basis of the acquired data and the experimental results, a dielectric model
67 to predict “*in real time*” the volumetric amounts of NAPL (θ_{NAPL}) within the contaminated soil during the
68 decontamination process.

69 **2. Theoretical concepts of TDR**

70 TDR is a geophysical technique employed to determine the dielectric permittivity of liquids and solids (Ferrè and Topp,
71 2002, described this method in detail). In general, the bulk dielectric permittivity is a complex term (ε_r^*), which may be
72 expressed as follows (Robinson et al., 2003):

$$\varepsilon_r^* = \varepsilon'_r - j \left[\varepsilon''_r + \frac{\sigma}{\omega \varepsilon_0} \right] \quad (1)$$

73 where ε'_r is the real part of dielectric permittivity, which gives the energy stored in the dielectrics at a certain frequency
74 and temperature, and ε''_r is the imaginary part due to relaxations. The zero frequency conductivity σ , the angle frequency
75 ω , the imaginary number $j = \sqrt{-1}$ and the permittivity ε_0 in free space contribute to define ε_r^* .

76 When the frequency of a TDR cable tester ranges between 200 MHz to 1.5 GHz, dielectric losses can be considered
77 minimal (Heimovaara, 1994) and the bulk dielectric permittivity ε_b (\cong the real part of permittivity) of a probe of length
78 L is determined from the propagation velocity $v(=2L/t)$ of an electromagnetic wave along the wave guide across the
79 investigated medium by the following expression:

$$\varepsilon_b = \left(\frac{c}{v} \right)^2 \quad (2)$$

80 where c ($=3 \times 10^8 \text{ m s}^{-1}$) is the velocity of an electromagnetic wave in vacuum (Topp et al., 1980) and t is travel time, i.e.
81 the time required by the generated signal to go back and forth through the TDR probe of length L (m). This can be
82 calculated as follows:

$$t = \frac{2L}{c} \sqrt{\varepsilon_b} \quad (3)$$

83 The direct dependence of the signal's travel time t upon soil dielectric permittivity is expressed by equation 3.

84 **3. Estimating volumetric NAPL content during a decontamination process in soils**

85 Dielectric mixing models, in their classical application, have been proposed to estimate the bulk dielectric permittivity of
86 a multi-phase medium, that is, a combination of three or four dielectric phases, and to couple the dielectric permittivity
87 of the medium to the dielectric permittivity of each single phase (Hilhorst, 1998). Recently, after analyzing the effects of
88 organic contaminants on soil dielectric properties, the above models were further developed to estimate the dielectric

89 properties of NAPL-polluted soils (Redman et al., 1991; Persson and Berndtsson, 2002; Francisca and Montoro, 2012,
 90 Comegna et al., 2013a; Comegna et al., 2016; Comegna et al., 2017).

91 Based on such models, in the present study, we analyze the possibility of predicting the correlations between the
 92 volumetric contents of NAPL (θ_{NAPL}) and the dielectric response (ϵ_b) of contaminated soil during the progression of a
 93 steady-state remediation process.

94 In the present research, we chose the so-called α model (Birchack et al., 1974; Knight and Endress, 1990; Roth et al.,
 95 1990):

$$\epsilon_b = \left[\sum_{i=1}^n V_i \epsilon_i^\alpha \right]^{1/\alpha} \quad (4)$$

96 where V_i is the volume and ϵ_i is the permittivity of each component of the complex medium; the exponent α is a fitting
 97 parameter (α varies between -1 and 1), which may be related to the internal structure of the investigated medium (Hilhorst,
 98 1998; Coppola et al., 2013; Coppola et al., 2015). Under the following hypothesis: i) the soil is homogeneous from a
 99 textural point of view, and ii) the soil porosity (ϕ) is constant, equation 4 was reformulated for our purposes.

100 For mixtures of soil (s) saturated with a certain amount of washing solution (ws), in rearranging the model formulation of
 101 Rinaldi and Francisca (2006), the α model yields the following:

$$\epsilon_{s-ws}^\alpha = [(1 - \phi)\epsilon_s^\alpha + \phi\epsilon_{ws}^\alpha] \quad (5)$$

102 where ϵ_{s-ws} is the soil-washing solution permittivity, and ϵ_s and ϵ_{ws} are the permittivities of soil particles and washing
 103 solutions, respectively. By the same token, for soil organic (s -NAPL) compounds at saturation, the α model can be
 104 expressed as follows:

$$\epsilon_{s-NAPL}^\alpha = [(1 - \phi)\epsilon_s^\alpha + \phi\epsilon_{NAPL}^\alpha] \quad (6)$$

105 where ϵ_{s-NAPL} is the permittivity of the soil-NAPL mixture, and ϵ_{NAPL} is the oil permittivity.

106 A medium consisting of soil particles, washing solution and NAPL (s - ws -NAPL) can be viewed as a mix of soil-washing
 107 solution (equation 5) and soil-NAPL (equation 6):

$$\epsilon_{s-ws-NAPL}^\alpha = [\beta\epsilon_{s-NAPL}^\alpha + (1 - \beta)\epsilon_{s-ws}^\alpha] \quad (7)$$

108 where β is the relative volume of NAPL contained in the whole fluid phase:

$$\beta = \frac{\theta_{NAPL}}{(\theta_{ws} + \theta_{NAPL})} = \frac{\theta_{NAPL}}{\theta_f} \quad (8)$$

109 where θ_f is the volumetric fluid content (m^3/m^3), sum of the volumetric washing solution content (θ_{ws}) and volumetric
 110 NAPL content (θ_{NAPL}); β varies between 0 (i.e. a soil-washing solution mixture) and 1 (i.e. a soil-NAPL mixture).

111 To estimate θ_{NAPL} , equation 7 is first reformulated in terms of β :

$$\beta = \frac{\varepsilon_{s-ws}^{\alpha} - \varepsilon_{s-ws-NAPL}^{\alpha}}{\varepsilon_{s-ws}^{\alpha} - \varepsilon_{s-NAPL}^{\alpha}} = \frac{(1 - \phi)\varepsilon_s^{\alpha} + \phi\varepsilon_{ws}^{\alpha} - \varepsilon_{s-ws-NAPL}^{\alpha}}{((1 - \phi)\varepsilon_s^{\alpha} + \phi\varepsilon_{ws}^{\alpha}) - ((1 - \phi)\varepsilon_s^{\alpha} + \phi\varepsilon_{NAPL}^{\alpha})} \quad (9)$$

112 Substituting equation 8 into equation 9, and considering that for a saturated medium, the volumetric fluid content is equal
 113 to soil porosity (i.e. $\theta_f = \phi$), θ_{NAPL} can be calculated as follows:

$$\theta_{NAPL} = \frac{(1 - \phi)\varepsilon_s^{\alpha} + \phi\varepsilon_{ws}^{\alpha} - \varepsilon_{s-ws-NAPL}^{\alpha}}{\varepsilon_{ws}^{\alpha} - \varepsilon_{NAPL}^{\alpha}} \quad (10)$$

114 Equation 10 correlates the dependence of volumetric NAPL content with soil porosity; θ_{NAPL} can be estimated (within
 115 the contaminated soil) during the progression of a remediation process once the dielectric permittivity of the soil-
 116 contaminated mixture ($\varepsilon_{s-ws-NAPL}$) is known.

117 4 Materials and Methods

118 4.1 Soil and fluid properties

119 A silt-loam Anthrosol (IUSS Working Group WRB, 2006) from the region of Puglia (Italy) was used for this study. The
 120 soil texture was measured by means of the hydrometer method (Day, 1965), while the Walkley–Black procedure (Allison,
 121 1965) was used to determine soil organic *C* content. The method developed by Miller and Curtis (2006) was used to
 122 measure soil electrical conductivity (EC_w), while soil *pH* was determined on the basis of a 1:1 soil/water ratio (Eckert,
 123 1988). In textural terms, the soil comprised 15.7% sand, 11.6% clay and 72.4% silt. Soil porosity was 0.57%, organic
 124 content 1.84%, EC_w 0.17 dS/m and soil *pH* 8.40.

125 The NAPL employed for the laboratory tests was corn oil ($\varepsilon_{NAPL}=3.2$; $EC_{NAPL}=0.055$ dS/m at 25°C) with a density of 0.905
 126 g/cm³ (at 25°C). Three different removal solutions were employed for soil cleaning: a) a first solution (referred to below
 127 as wd) composed of 99% distilled water and 1% commercial detergent ($\varepsilon_d=9.22$, at 25°C), b) a second solution (wda#1)
 128 composed of 90% distilled water, 1% commercial detergent and 9% methanol as co-solvent ($\varepsilon_{alcohol}=26.13$, at 25°C) and
 129 c) a third solution (wda#2) composed of distilled water (85%) with commercial detergent (1%) and methanol (14%). The
 130 dielectric permittivity of the washing solutions, measured at 25°C, was $\varepsilon_{wd}=75.04$, $\varepsilon_{wda\#1}=68.98$ and $\varepsilon_{wda\#2}=65.92$, whereas
 131 the dielectric permittivity of the tested soil saturated with each of the three cleaning solutions was $\varepsilon_{soil+wd}=34.59$,
 132 $\varepsilon_{soil+wda\#1}=31.04$ and $\varepsilon_{soil+wda\#2}=30.10$.

133 4.2 Measurement of dielectric permittivity of soil-NAPL contaminated samples during soil remediation

134 4.2.1 Experimental setup

135 As illustrated in Fig. 1, the experimental layout consisted of the following: i) a Techtronix (model 1502C) cable tester; ii)
 136 a three-rod probe 14.5 cm long with a wire diameter of 0.003 m and a wire spacing of 0.02 m, introduced vertically into
 137 the soil samples; iii) a testing cell 0.15 m high and 0.08 m in diameter; iv) a peristaltic pump used for upward movement
 138 of the washing solution.

139 4.2.2 Sample preparation and testing procedures

140 Soil was oven dried at 105°C and passed through a 2-mm sieve. Known amounts of soil and oil were mixed together,
141 shaken and then kept for 24 hours in sealed plastic bags to avoid any evaporation and ensure a uniform distribution of oil
142 within the sample and good oil adsorption by the soil matrix. The samples were then allocated to cylindrical boxes. With
143 a view to achieving different degrees of (initial) soil contamination, volumetric NAPL content (θ_{NAPL}) was varied from
144 0.05 to 0.40 (in steps of 0.05). In all, each washing solution comprised eight oil-contaminated soil samples.

145 For all experiments, the soil samples were placed in the vessels in various steps at a bulk density of 1.13 g/cm³. During
146 TDR measurements, the soil samples were conserved at a temperature of 25°C by using a thermostat box. Remediation
147 was performed using an upward flux of diverse pore volumes T of three washing solutions (wd, wda#1 and wda#2)
148 supplied at the rate of 90 cm³/h, corresponding to a Darcian velocity of 1.8 cm/h. After collection of the outflow from the
149 soil columns, the supernatant NAPL was separated from the washing solution and the quantity of NAPL remediated from
150 the soil was determined.

151 The obtained data series were employed to calibrate the proposed dielectric model of equation 10. An independent data
152 set, obtained in the same manner as the calibration data set, was used for model validation.

153 4.3. Numerical indices for model performance evaluation

154 The goodness of equation 10 was evaluated using two different criteria: i) the mean bias error (MBE), and ii) the model
155 efficiency (EF), computed according to the following relations (Legates and McCabe Jr, 1999):

$$156 \quad MBE = \frac{\sum_{i=1}^N (E_i - O_i)}{N} \quad (11)$$

$$EF = 1 - \frac{\sum_{i=1}^N (E_i - O_i)^2}{\sum_{i=1}^N (O_i - \bar{O})^2} \quad (12)$$

157 where E_i and O_i are respectively the expected and the observed value, \bar{O} is the mean of the observed data, and N is the
158 number of observations.

159 MBE measures the differences between model-simulated data and measured values (positive MBE values are used to
160 indicate average overprediction, while negative values indicate underprediction). The model's ability to forecast θ_{NAPL} is
161 described by parameter EF , according to which $EF=1$ indicates perfect accord between predicted and measured data.

162 5. Results and Discussion

163 5.1 Influence of washing solution on NAPL removal

164 Figures 2a, b, c, d, e and f, with reference to the most representative experimental results, reveal the influence of pore
165 volumes T on evaluated bulk dielectric permittivity ($\epsilon_{s-ws-NAPL}$) for the soil specimens initially polluted with oil. As the
166 washing solution started to remove oil, the dielectric permittivity rose due to the larger dielectric permittivity of the
167 flushing mixture. As the remediation solution continued to move upward, the rising rate of the dielectric permittivity

168 decreased and asymptotically approached a constant value. This steady value was smaller than that observed when the
169 soil specimens were completely saturated by only the flushing solution (i.e. wd, wda#1 or wda#2), which in our tests
170 corresponds to the condition of a completely decontaminated soil. This difference in values is undoubtedly due to oil
171 confined in soil pores (i.e. NAPL residual saturation). For the same reason, residual saturation may explain why
172 insignificant oil remediation was observed for θ_{NAPL} values less than 0.15. This aspect may be explained by the fact that
173 for low volumetric NAPL contents, the non-wetting fluid (oil) is disconnectedly distributed (i.e. immobile) in the soil
174 samples, which means that θ_{NAPL} is close to the limiting *residual value*, and thus NAPL loses its ability to move in the
175 soil in response to a hydraulic gradient [i.e. capillary retention forces are greater than gravitational forces, which tend to
176 immobilize the NAPL (Brost and DeVauil, 2000)].

177 The NAPL volumes removed for different washing solutions and the initial volumetric content of NAPL are compared in
178 Fig. 3. For all the three cleaning solutions adopted, the experiments ultimately demonstrate (for a fixed θ_{NAPL}) the same
179 results in terms of soil decontamination, and they show that NAPL removal increases with increasing θ_{NAPL} . In some cases
180 (i.e. $\theta_{NAPL}=0.15, 0.20$ and 0.30), contaminated samples flushed with the wda#1 solution yield slightly higher removal
181 efficiency values compared to the samples flushed with wd and wda#2. Martel et al. (1998) suggest the need to investigate
182 the best water-surfactant-alcohol combination in order to enhance NAPL solubilization in soil.

183 **5.2 Model calibration and validation**

184 For the model (equation 10) calibration methodology, with reference to the three washing solutions (wd, wda#1 and
185 wda#2), we analyze the effect of the measured dielectric permittivity on volumetric NAPL content (θ_{NAPL}) in order to
186 estimate the α parameter of the model. The complete calibration data set of estimated α parameters is reported in Table
187 1. The α parameter of the mixing model was determined, for a fixed θ_{NAPL} value and washing solution, by an optimization
188 procedure based on the least squares technique, and was kept constant for each of the remediation tests developed.

189 A permittivity value of 3.70 was adopted for the solid phase. This value was determined using the “*immersion method*”
190 which is commonly employed for estimating the ϵ_s of soils (Robinson and Friedman, 2003; Kameyama and Miyamoto,
191 2008; Comegna et al., 2013b).

192 For the sake of brevity, a selection of the experimental $\epsilon_{s-ws-NAPL}-\theta_{NAPL}$ relationships (validation dataset) is reported in Fig.
193 4a, b, c, d, e and f. The data in Fig. 4 (except for Fig. 4e, f) show that some of the model-simulated values tend to
194 overestimate the measured data. This behavior is mostly restricted to the beginning of the remediation process, when a
195 rapid change in dielectric permittivity may be observed. This behavior was also verified in other tests (not shown here)
196 and may be explained by invoking both NAPL properties such as liquid density, surface tension and viscosity, and soil
197 properties including moisture content, relative permeability and soil porosity (Brost and DeVauil, 2000; Wang et al.,
198 2013).

199 Mercer and Cohen (1990) referred to the existence, in NAPL-contaminated soils, of a “*double fluid domain*,” defined as
200 the composition of the following: i) mobile pools, which are NAPL-connected phases that move in the soil and ii)
201 immobile residuals (i.e. low permeability regions), which depend on small disconnected blobs or ganglia within the
202 contaminated soil (see also section 5.1 above). As long as the flushing continues, mobile pools are reduced and the oil
203 tends increasingly to be trapped in the immobile areas. This means that, during soil cleaning, the capacity of non-wetting
204 fluids to respond to gravitational forces gradually diminishes (Luckner et al., 1989). From a dielectric point of view, this
205 mechanism may appear as a rapid dielectric permittivity increase (identified in Fig. 4 as *fast oil mobility region*) within a
206 few pore volumes. When this fast mobility mechanism is dominant, the predictions of equation 10 fail.

207 Another possible explanation for this discrepancy between the observed and the predicted permittivity values may be
208 linked to the propensity of NAPL-water mixtures to form macroinclusions in the soil (Persson and Berndtsson, 2002),
209 which affected the initial pore-scale distribution of NAPL, and thus the global dielectric response of the medium (Ferré
210 et al, 1996), during the first remediation stages.

211 However, since the phenomenon is mostly limited to the initial part of the washing process, overall model effectiveness
212 is not compromised, as also shown in Table 2, which summarizes the goodness-of-fit statistical indices, and in Fig. 5a, b,
213 c, d, e, f, where the estimated θ_{NAPL} from equation (10) and the known θ_{NAPL} are illustrated in a series of 1:1 scatter plots.
214 Overall, both graphical and quantitative evaluations in terms of *MBE* and *EF* reveal the suitability of the dielectric model
215 adopted to estimate the volumetric NAPL content in the θ_{NAPL} range 0.15-0.40.

216 **6. Conclusions**

217 This paper presented an extensive dataset of remediation experiments that were conducted at a laboratory scale using corn
218 oil as a soil contaminant, and three different solutions for soil cleaning. The results of these tests were employed to
219 investigate the potential of the TDR technique in monitoring the development of a steady-state decontamination process.
220 Dielectric data analysis showed that, during soil flushing, dielectric permittivity behavior is highly dependent on the initial
221 volumetric content and intrinsic permittivity of the specific NAPL: *removal of NAPL produces an increase in bulk*
222 *dielectric permittivity*, due to the low value of oil permittivity. The experiments conducted also allowed us to calibrate
223 and validate a dielectric mixing model (equation 10). The model outcomes are encouraging; the calculated statistical
224 indices confirmed a high accuracy in NAPL predictions of the α -model at different stages during soil cleaning, with the
225 only exception of the very initial cleaning stage (confined to the low values of *T*) where the eventual presence of a *fast*
226 *flow region* may limit its applicability.

227 The approach requires additional experiments and data sets for model calibration and validation in different pedological
228 contexts, mainly to confirm the potential of the methodology developed. Furthermore, an effort should be made,
229 introducing the water phase, *ab initio* in the experimental setup, to simulate a possible natural contamination-

230 decontamination scenario more accurately. Finally, full field-scale tests should also be conducted to evaluate the
231 performance of equation 10 in real field conditions.

232 *Data availability.* The dataset used in this paper is available on request to alessandro.comegna@unibas.it.

233 *Competing interests:* The authors declare that they have no conflict of interest.

234 **References**

235 Allison, L.E.: Organic carbon. In A. Klute (ed.). *Methods of Soil Analysis, Part 1*, Madison, Agron. Monograph, vol 9,
236 ASA and SSSA, pp. 1367–1378, 1965.

237 Birchack, J.R., Gardner, C.Z.G., Hipp, J.E., and Victor, J.M.: High dielectric constant microwave probes for sensing soil
238 moisture. *Proc. IEEE*, 62, 1, 93–98, 1974.

239 Brost, E.J., and DeVaul, G.E.: Non-Aqueous phase liquid (NAPL) mobility limits in soils. *Soil and Groundwater*
240 *Research Bulletin*, 9, 1–9, 2000.

241 Comegna, A., Coppola, A., Dragonetti, G., and Sommella, A.: Interpreting TDR signal propagation through soils with
242 distinct layers of nonaqueous-phase liquid and water content. *Vadose Zone J.*, 16, doi:10.2136/vzj2017.07.0141, 2017.

243 Comegna, A., Coppola, A., Dragonetti, G., and Sommella, A.: Estimating non-aqueous phase liquid (NAPL) content in
244 variable saturated soils using time domain reflectometry (TDR). *Vadose Zone J.*, 15, doi:10.2136/vzj2015.11.0145, 2016.

245 Comegna, A., Coppola, A., Dragonetti, G., and Sommella, A.: Dielectric response of a variable saturated soil
246 contaminated by Non-Aqueous Phase Liquids (NAPLs). *Procedia Environmental Sciences*, 19, 701–710, 2013a.

247 Comegna A., Coppola A., Dragonetti G., Severino G., Sommella A., Basile A.: Dielectric properties of a tilled sandy
248 volcanic-vesuvian soil with moderate andic features. *Soil Till. Res.*, 133,93-100, 2013b.

249 Comegna, A., Coppola, A., Dragonetti, G., Chaali N., and Sommella A.: Time domain reflectometry-measuring dielectric
250 permittivity to detect soil non-aqueous phase liquids contamination-decontamination processes. *Journal of Agricultural*
251 *Engineering*, XLIV(s1), e167, 2013c.

252 Coppola, A., Comegna, A., Dragonetti, G., Gerke, H.H., and Basile, A.: Simulated water flow and solute transport in
253 shrinking soils. *Vadose Zone J.*, 14, 2015.

254 Coppola, A., Dragonetti, G., Comegna, A., Lamaddalena, N., Caushi, B., Haikal, M.A., and Basile, A.: Measuring and
255 modeling water content in stony soils. *Soil Till. Res.*, 128, 9–22, 2013.

256 Day, P.R.: Particle fractionation and particle-size analysis. In C.A. Black (ed.). *Methods of Soil Analysis, Part 1*, Madison,
257 American Society of Agronomy, pp. 545–567, 1965.

258 Eckert, D.J.: Soil pH. In W.C. Dahnke (ed.). *Recommended chemical soil test procedures for the North Central Region.*

259 Fargo: North Dakota Agricultural Experiment Station Bulletin No. 221 (revised), pp. 6–8, 1988.

260 Endres, A., and Redman, J.D.: Modeling the electrical properties of porous rocks and soils containing immiscible
261 contaminants. In: Bell, R.S., Lepper, C.M. (Eds). Proceedings of the Symposium on the application of geophysics to
262 Engineering and Environmental Problems, San Diego, pp. 21-38, 1993.

263 Ferré, P.A., and Topp G.C.: Time domain reflectometry. In *Methods of Soil Analysis: Part 4, Physical Methods*, ed. J.H.
264 Dane and G.C. Topp, SSSA, Madison, WI. 434-446, 2002.

265 Ferré, P.A., Rudolph, D.L., and Kachanoski R.G.: Spatial averaging of water content by time domain reflectometry:
266 Implications for twin rod probes with and without dielectric coatings. *Water Resour. Res.*, 32, 271-279, 1996.

267 Fetter, C.W.: *Contaminant hydrogeology*. 2nd ed., Practice. Hall Englewood Cliffs, N.J., 500, 1993.

268 Fitts, C.R.: Contamination sources. In *Groundwater Science*, Academic Press, London, pp. 339–343, 2002.

269 Francisca, M., and Montoro, M.A.: Measuring the dielectric properties of soil-organic mixtures using coaxial impedance
270 dielectric reflectometry. *J. Appl. Geophys.*, 80, 101–109, 2012.

271 Freeze, R.A.: The unpleasant truths about waste management. In *The Environmental Pendulum*. Univ. of Calif., Press
272 Berkeley, pp. 147–196, 2000.

273 Heimovaara, T.J.: Frequency domain analysis of time domain reflectometry waveforms, 2, A four-component complex
274 dielectric mixing model for soil, *Water Resour. Res.* 30, 201-209, 1994.

275 Hilhorst, M.A.: Dielectric characterisation of soil. PhD dissertation, Wageningen Agricultural University, 1998.

276 IUSS Working Group WRB. World reference base for soil resources 2006: A framework for international classification,
277 correlation and communication. 2nd ed. *World Soil Resour. Rep.*, 103, FAO, Rome, 2006.

278 Kameyama, K., and Miyamoto, T.: Measurement of solid phase permittivity for soils by time domain reflectometry. *Eur.*
279 *J. Soil Sci.*, 59, 1253–1259, 2008.

280 Knight, R.: Ground penetrating radar for environmental applications. *Annu. Rev. Earth Planet. Sci.* 29:229-255, 2001.

281 Knight, R., and Endres A.: A new concept in modeling the dielectric response of sandstones: Defining a wetted rock and
282 bulk water systems. *Geophysics*, 55, 586-594, 1990.

283 Legates, D.R., and McCabe Jr, G.J.: Evaluating the use of "goodness-of-fit" measures in hydrologic and hydroclimatic
284 model validation. *Water Resour. Res.*, 35, 233–241, 1999.

285 Luckner, L., van Genuchten, M.Th., and Nielsen, D.R.: A consistent set of parametric models for the two-phase flow of
286 immiscible fluids in the subsurface. *Water Resour. Res.*, 25, 2187–2193, 1989.

287 Martel, R., Gelinas, P.J., and Saumure, L.: Aquifer washing by micellar solutions: 3 Field test at the Thounin Sand Pit
288 (L'Assomption Quebec, Canada). *J. Contam. Hydrol.*, 30, 33–48, 1998.

289 Mercer, J.W., and Cohen, R.M.: A review of immiscible fluids in the subsurface: Properties, models, characterization,
290 and remediation. *J. Contam. Hydrol.*, 6, 107–163, 1990.

291 Miller, J.J., and Curtis, D.: Electrical conductivity and soluble ions. In M.R. Carter and E.G. Gregorich (eds.). Soil
292 Sampling and Methods of Analysis. Canadian Society of Soil Science, 2006.

293 Mohamed, A.M.O., and Said R.A.: Detection of organic pollutants in sandy soils via TDR and eigendecomposition. *J.*
294 *Contain. Hydrol.*, 76, 235–249, 2005.

295 Moroizumi, T., and Sasaki, Y.: Estimating the nonaqueous-phase liquid content in saturated sandy soil using amplitude
296 domain reflectometry. *Soil Sci. Soc. Am. J.*, 72, 1520–1526, 2006.

297 Parnian, M.M., and Ayatollahi, Sh.: Surfactant remediation of LNAPL contaminated soil; effects of adding alkaline and
298 foam producing substances. *Iranian J. of Chemical Engineering*, 2, 34–44, 2008.

299 Pennell, K.D., Jin, M., Abriola, L.M., and Pope, G.A.: Surfactant enhanced remediation of soil columns contaminated by
300 residual tetrachloroethylene. *J. Contam. Hydrol.*, 16, 35–53, 1994.

301 Persson, M., and Berndtsson, R.: Measuring nonaqueous phase liquid saturation in soil using time domain reflectometry,
302 *Water Resour. Res.*, 38, doi: 10.1029/2001WR000523, 2002.

303 Redman, J.D., Kueper, B.H., and Annan, A.P.: Dielectric stratigraphy of a DNAPL spill and implications for detection
304 with ground penetrating radar: Aquifer restoration, ground water monitoring and geophysical methods, 5th national
305 outdoor action conf, 1017-1030, 1991.

306 Redman, J.D., and DeRyck, S.M.: Monitoring Non-Aqueous Phase Liquids in the Subsurface with Multilevel Time
307 Domain Reflectometry Probes, Proceedings of the Symposium on Time Domain Reflectometry in Environmental,
308 Infrastructure, and Mining Applications, Evanston, Illinois, Sept 7-9, U.S. Bureau of Mines, Special Publication SP 19-
309 94, NTIS PB95-105789, 207-215, 1994.

310 Rinaldi, V.A., and Francisca, F.M.: Removal of immiscible contaminants from sandy soils monitored by means of
311 dielectric measurements. *J. Environ. Eng.*, 132, 931–939, 2006.

312 Robinson, D.A., Jones, S.B., Wraith, J.M., and Or, D.: A review of advances in dielectric and electric conductivity
313 measurements using time domain reflectometry. *Vadose Zone J.*, 2, 444–475, 2003.

314 Robinson, D.A., Friedman, S.P.: The effective permittivity of dense packing of glass beads, quartz sand and their mixtures
315 immersed in different dielectric backgrounds. *Journal of Non-Crystalline Solids* 305, 261-267, 2003.

316 Roth, K., Schulin, R., Fluhler, H., and Attinger, W.: Calibration of time domain reflectometry for water content
317 measurements using a composite dielectric approach. *Water Resour. Res.*, 26, 2267–2273, 1990.


318 Topp, C.G., Davis, J.L., and Annan, A.P.: Electromagnetic determination of soil water content: Measurements in coaxial
319 transmission lines. *Water Resour. Res.*, 16, 574–582, 1980.

320 Truong Hong, T., and Bettahar, M.: Effect of the water-oil ratio on brine/surfactant/alcohol/oil systems optimized for soil
321 remediation. *J. Mater Cycles Waste Management*, 2, 109–117, 2000.

322 van Dam R.L., Borchers B., and Hendrickx J.M.H.: Methods for prediction of soil dielectric properties: a review.
323 Proceedings of SPIE-the International Society for Optical Engineering, 2005.

324 Wang, X.P., Quan, G.J., Pan, Y.X., Hu, R., Zhang, Y.F, Tedeschi, A., Basile, A., Comegna, A., Coppola, A., and de
325 Mascellis, R.: Comparison of hydraulic behaviour of unvegetated and vegetation-stabilized sand dunes in arid desert
326 ecosystems. *Ecohydrology*, 62, 264–274, 2013.

327




329

330 **Figure 1.** Experimental setup used in the NAPL removal experiments (from Comegna et al., 2013c).


331

a) $\theta_{NAPL}=0.15$




332

b) $\theta_{NAPL}=0.20$




333

c) $\theta_{NAPL}=0.25$




334

d) $\theta_{NAPL}=0.30$




335
336

e) $\theta_{NAPL}=0.35$




337
338

f) $\theta_{NAPL}=0.40$



339
340
341
342
343


Figure 2. Selection of experimental relationships between the measured dielectric permittivity ($\epsilon_{s-ws-NAPL}$) and number of pore volumes T under the effect of different washing solutions: i) water-detergent (wd) and ii) water-detergent-alcohol (wda#1 and wda#2).




344

345 **Figure 3. Volume of NAPL recovered ($V_{NAPL-Rem}$) with respect to the initial volume of NAPL present in the soil sample (V_0) of**
 346 **different washing solutions (wd, wda#1 and wda#2) for different experiments ($\theta_{NAPL}=0.15, 0.20, 0.25, 0.30, 0.35, 0.40$).**

347




348




349


350




351



352



353



354

355 Figure 4 a, b, c, d, e, f. Selection of observed (symbols) and modeled (dashed lines) volumetric NAPL content (θ_{NAPL}) versus
 356 dielectric permittivity ($\epsilon_{s-ws-NAPL}$), with reference to the three washing solutions (wd, wda#1 and wda#2) used during the
 357 remediation tests.

358




Figure 5 a, b, c, d, e, f. Measured (equation 10) vs. known volumetric NAPL content (θ_{NAPL}) of contaminated soils, with reference to the different remediation tests in figure 4.

Tables

Table 1. Estimated α parameter of equation 10 for all three washing solutions (wd, wda#1 and wda#2) and volumetric NAPL content (θ_{NAPL}) tested.

parameter	washing solution	θ_{NAPL}					
α		0.15	0.20	0.25	0.30	0.35	0.40
	wd	0.45	0.30	0.49	0.65	0.67	0.55
	wda#1	0.25	0.45	0.45	0.42	0.50	0.55
	wda#2	0.20	0.45	0.30	0.45	0.55	0.52

Table 2. Model efficiency (*EF*) and mean bias error (*MBE*) statistical indices, referring to measured and predicted (equation 10) volumetric NAPL content (θ_{NAPL}).

Washing solution	$\theta_{\text{NAPL}}=0.15$		$\theta_{\text{NAPL}}=0.20$		$\theta_{\text{NAPL}}=0.25$	
	EF	MBE	EF	MBE	EF	MBE
wd	0.98	1.548	0.93	-0.422	0.96	0.570
wda#1	0.86	0.405	0.99	0.516	0.97	-0.048
wda#2	0.84	0.148	0.94	0.420	0.66	0.001
Washing solution	$\theta_{\text{NAPL}}=0.30$		$\theta_{\text{NAPL}}=0.35$		$\theta_{\text{NAPL}}=0.40$	
	EF	MBE	EF	MBE	EF	MBE
wd	0.98	-0.023	0.99	-0.153	0.99	-0.179
wda#1	0.95	-0.074	0.99	-0.066	0.99	0.303
wda#2	0.91	0.014	0.97	0.326	0.99	0.019

*Range of model applicability: $0.15 \leq \theta_{\text{NAPL}} \leq 0.40$.