

# Beyond binary baseflow separation: a delayed flow index for multiple streamflow contributions

Michael Stoelzle<sup>1</sup>, Tobias Schuetz<sup>2</sup>, Markus Weiler<sup>1</sup>, Kerstin Stahl<sup>1</sup>, and Lena M. Tallaksen<sup>3</sup>

<sup>1</sup>Faculty of Environment and Natural Resources, University Freiburg, Germany

5 <sup>2</sup>Department of Hydrology, Faculty VI Regional and Environmental Sciences, University of Trier, Germany

<sup>3</sup>Department of Geosciences, University of Oslo, Norway

*Correspondence to:* Michael Stoelzle ([michael.stoelzle@hydro.uni-freiburg.de](mailto:michael.stoelzle@hydro.uni-freiburg.de))

**Abstract.** Understanding components of the total streamflow is important to assess the ecological functioning of rivers. Binary or two-component separation of streamflow into a quick- and a slow (often referred to as baseflow) component are often based on arbitrary choices of separation parameters and also merge different delayed components in one baseflow component and one baseflow index (BFI). As streamflow generation during dry weather often results from drainage of multiple sources, we propose to extend the BFI by a delayed flow index (DFI) considering the dynamics of multiple delayed contributions to streamflow. The DFI is based on characteristic delay curves where the identification of breakpoint estimates helps to avoid rather subjective separation parameters and allows distinguishing four types of delayed streamflow contributions. The methodology is demonstrated using streamflow records from a set of 60 mesoscale catchments in Germany and Switzerland covering a pronounced elevation gradient of roughly 3000 m. We found that the quickflow signal often diminishes earlier than assumed by two-component BFI-analyses, and distinguished a variety of additional flow contributions with delays shorter than 60 days. For streamflow contributions with delays longer than 60 days, we show that the method can be used to assess catchments' water sustainability during dry spells. Colwells's Predictability, a measure of streamflow periodicity and sustainability, was applied to attribute the identified delay patterns to dynamic catchment storage. The smallest dynamic storages were consistently found for catchments between approx. 800 and 1800 m a.s.l. Above an elevation of 1800 m the DFI suggests that seasonal snowpack provides the primary contribution, whereas below 800 m groundwater resources are most likely the major streamflow contributions. Our analysis also indicates that dynamic storage in high alpine catchments might be large and is overall not smaller than in lowland catchments. We conclude that the DFI can be used to assess the range of sources forming catchments' storages and to judge long-term sustainability of streamflow.

## 1 Introduction

During dry weather sustained streamflow modulates aquatic ecosystem functioning and is important for groundwater-surface-water-interactions (Sophocleous, 2002), the variability of water temperature (Constantz, 1998) or the dilution of contaminants (Schuetz et al., 2016). Estimates of the amount or timing of baseflow or of the baseflow index (BFI) quantify catchments' freshwater availability during dry weather. The BFI is the proportion of baseflow to total streamflow, i.e. higher BFI values

are interpreted as an indicator of more water being provided from stored sources (Tallaksen and van Lanen, 2004). Total streamflow is composed of quick- and baseflow. Quickflow is the portion of total streamflow originating directly from precipitation input (also termed direct runoff or stormflow). In contrast, baseflow has commonly been considered “as the portion of flow that comes from groundwater storage or other delayed sources” (Hall, 1968), i.e. water that has previously infiltrated into the soil and recharged to aquifers, but can also origin from other sources of delayed flow (e.g. snowmelt). Dingman (2015) understands baseflow as water maintaining streamflow between water-input events. Different sources such as groundwater, melt water from snow, glacier or ice, water from lakes, riverbanks, floodplains, wetlands, spring or return flow from irrigation can contribute to the “baseflow” component of streamflow (Smakhtin, 2001). Considering these different potential sources requires consideration of the different delayed contributions that may maintain streamflow during prolonged dry weather and are thus important to assess the vulnerability of aquatic ecosystems, e.g. due to climatic change (e.g. Olden et al., 2011). Therefore, the various contributions from different sources to the “baseflow” component need to be better distinguished, in particular across different climates and streamflow regimes.

The question is, how we can identify and quantify different delayed contributions to streamflow? Traditionally, conceptual methods use reservoir algorithms to represent multiple contributions to streamflow (Schwarze et al., 1989; Wittenberg, 2003). Stoelzle et al. (2015) have shown that baseflow modelling can be improved by using information on geology to select appropriate groundwater model structures. However, instead of using parameterized box models with assumptions about their drainage behavior, the observed hydrograph can also be consulted directly. Hydrometric- or tracer-based hydrograph separation allow decomposing different streamflow contributions to gain a quick- and baseflow component (Smakhtin, 2001). Hydrograph-based separation has a long history, but has been also criticized for ambiguous results compared to newer approaches based on chemical- or isotopic-tracers (Klaus and McDonnell, 2013). A general assumption is that the latter approaches are physically more meaningful and allow assessing the water age, the mixing of the water (e.g. pre-event and event water) and the sources of different water contributions. However, isotope or chemical data sets are often not available or have limitations regarding spatial extent, resolution or the period of record. Furthermore, Freyberg et al. (2018) recommend developing hydrograph separation beyond the traditional separation of event and pre-event water (i.e. quick- and baseflow) to eventually identify many different sources of streamflow.

In the past, two-component hydrograph separation such as recursive digital filtering (Lyne and Hollick, 1979; Nathan and McMahon, 1992) or separation based on progressively identified streamflow minima in the IH-UK (Institute of Hydrology, United Kingdom) baseflow separation method (Gustard et al., 1992; Natural Environment Research Council, 1980) have proven a simple and practical way of indexing catchment response. Both methods were developed in regional studies (e.g. Australia, United Kingdom) and need reasonable, but subjective, decisions on the separation of quick- and baseflow from total streamflow. The proposed parameter ranges reflect region-specific streamflow response characteristics (e.g. for BFI, the choice of 5-days windows for separation in the UK is adapted to the typical rainfall regime in the UK) and would have to be recalibrated for other climates as demonstrated e.g. for seasonal snow regimes by (Tallaksen, 1987) or for intermittent streams by (Aksoy et al., 2008). Accordingly, other studies have discussed the limitations of the BFI and two-component baseflow

65 separation due to e.g. arbitrary separation parameters or the mixture of different delayed sources into one baseflow component (Hellwig and Stahl, 2018; Kronholm and Capel, 2015; Parry et al., 2016a; Partington et al., 2012). Meyer et al. (2011) applied different baseflow separation methods (IH-UK procedure, Wittenberg procedure (Wittenberg and Sivapalan, 1999) and the Demuth procedure (Demuth, 1993; Demuth and Kulls, 1997)) demonstrating that different procedures of quick- and baseflow separation lead to different BFI values with a consistent ranking across the procedures (i.e. Demuth < IH-UK < Wittenberg).  
70 The authors found for rainfall-dominated catchments in Switzerland reliable relationships between BFI and catchment characteristics such as groundwater availability or soil properties. In general, BFI and mean catchment elevation were negatively correlated (below 1500 m a.s.l.), but between 1500-3000 m a.s.l. (i.e. snowmelt-dominated catchments) their results indicated generally higher BFI values, an indication of additional delayed contributions, and a much weaker correlation between BFI and elevation, an indication of importance of specific catchment characteristics.  
75 To improve our understanding of different streamflow components we propose to extend common binary baseflow separation (resulting in BFI) into a hydrograph separation considering multiple delayed contributions to streamflow. The objectives of our study are:

- 1) to develop a delayed flow separation procedure with the ability to quantify multiple delayed streamflow contributions (i.e. the delayed flow index, DFI) and
- 80 2) to evaluate the reliability and applicability of this procedure by linking delayed flow contributions to catchment characteristics and dynamic catchment storage.

For this purpose, the DFI is tested for a set of catchments covering a pronounced elevation gradient acting as a proxy for different streamflow regimes, catchment characteristics and climate characteristics (e.g. rainfall- or snowmelt-dominated catchments). Accordingly, we hypothesize that multiple delayed streamflow contributions with specific signals (e.g. stormflow, snowmelt or groundwater contributions) are distinguishable. As catchment storage is both seasonally stored surface water (e.g. snow) as well as sub-surface water stored with less pronounced seasonality (e.g. shallow or deep groundwater aquifers), we used Colwell's Predictability (Colwell, 1974) as a metric to assess streamflow predictability considering both facets of water storage in catchments.  
85

## 2 Methods

### 90 2.1 Delayed flow separation

The proposed procedure is built on the widely used IH-UK baseflow separation method (Gustard et al., 1992), also referred to as the smoothed minima method. The IH-UK method was developed for humid, rainfall-dominated catchments in the United Kingdom (UK) and separates the total flow into two components (quick- and baseflow), i.e. above and below a baseflow hydrograph derived from a daily streamflow series of perennial streams. For a thorough description of the original method see  
95 e.g. Hisdal et al. (2004) and the Manual on Low-flow Estimation and Prediction of WMO (2009). The IH-UK method identifies local minima in daily streamflow series. A continuous baseflow hydrograph is then obtained by linear interpolation between


the identified local streamflow minima. The separation method is based on identifying streamflow minima in consecutive periods of  $N=5$  days (block size) and a multiplying factor  $f$  (also referred to as a turning point parameter) that determines whether the minimum is identified as a local minimum or not ( $f$  equal 0.9 in the original method). The estimated baseflow hydrograph is more sensitive to changes in parameter  $N$  than to changes in the turning point parameter  $f$  (Aksoy et al., 2008; Tallaksen, 1987). Hence, we focus in this study only on the variation of block size  $N$ , which can be seen as an estimate of an average streamflow delay and catchments response (i.e. unit of  $N$  is ‘days’).

It has further been suggested to calculate the BFI separately for different seasons using different  $N$  values to avoid identifying minima during seasons with a deviating runoff response (to that of rainfall), such as spring flood due to snowmelt (Tallaksen, 1987). Aksoy et al. (2008; 2009) adapted the IH-UK method for perennial and intermittent streams accounting for the sensitivity of BFI to different block sizes  $N$ . They also compared the IH-UK method to other filter separation methods such as the recursive digital filter method (Lyne and Hollick, 1979), and were amongst others aware of the sensitivity of BFI to different block sizes  $N$  (Miller et al., 2015; Piggott et al., 2005). However, to our knowledge, a comprehensive analysis of the sensitivity in BFI to different block sizes  $N$  is still missing. Aksoy et. al (2008) suggested to determine catchment-specific values for  $N$  as a function of catchment area  $A$  [km<sup>2</sup>] with  $N = 1.6A^{0.2}$ , however, if applied as “a rule of thumb” (Linsley et al., 1958),  $N$  will only vary between roughly 2 and 10 days for catchment areas between 10 and 10.000 km<sup>2</sup>. Thus, there is a need for a more systematic approach. In this study, we expand on the IH-UK method (i.e. smoothed minima method) to derive a delayed flow index (DFI<sub>N</sub>) for integer values of  $N$  ranging between 1 and 90 days, as follows:

1. Similar to the BFI procedure (WMO, 2009) the time series is divided into non-overlapping consecutive blocks of  $N$  days.
2. The minimum value of each block is compared to the minimum of the two adjacent blocks. If a factor  $f=0.9$  times of the minimum value, is less than or equal to the two adjacent minima, a turning point (TP) is defined. TPs will be separated by a varying number of days due to the algorithm.
3. The TPs are connected by straight lines to become the delayed flow hydrograph. Between TPs the delayed flow values are derived by linear interpolation. If the estimated delayed flow exceeds the original streamflow value, the delayed flow is replaced by the original streamflow value.
4. The delayed flow index for a given  $N$  (DFI<sub>N</sub>) is then calculated as the ratio of the sum of delayed flow to the sum of total streamflow.

$N = 0$  represent the case of no separation and the delayed flow series is set equal to the streamflow series (DFI<sub>0</sub> = 1). For  $N = 1$  the DFI value will be slightly less than 1 as some peaks in the hydrograph will be cut by the  $f=0.9$  criterion. The BFI value of the original method is equal to DFI<sub>5</sub>, i.e.  $N = 5$  days. Theoretically, DFI<sub>N</sub> (as well as the original BFI value) range between 0 and 1. With increasing  $N$  the length of each consecutive period increases and DFI decreases because TPs are set wider apart and more and more streamflow peaks (i.e. contributions with shorter delays) are excluded from the separation as illustrated in Figure 1. Here the methodology is demonstrated for three catchments with different streamflow regimes (Fig. 1a and 1b), showing the full range of delayed contributions as a continuous change from  $N = 1$  (only the sharpest peaks are

identified) to  $N = 60$  (all peaks are separated). With increasing  $N$ , the  $DFI_N$  shows a monotonic decrease and converges to a catchment-specific limiting value for large values of  $N$  (Fig. 1c).  $DFI_N$  would only approach 0, if streamflow series has regularly zero flow periods (intermittent streams): Zero flow must then occur approximately every  $N$  days, which was not the case for any of our study catchments.



135

140


**Figure 1:** a) Delayed flow separation for three catchments from Switzerland, namely Langeten (LAN), Poschiavino (POS) and Lümpenbach (LUE), with different streamflow regimes, b) Flow duration curves for delayed flow hydrographs (for 1 day, at breakpoint 1, at breakpoint 2 and, for 60 days) and c)  $DFI_N$ -values for different block size  $N$  shown in combination with breakpoints (circles). Colours refer to the four different delay classes identified. The methodology to derive the breakpoints and delay classes is explained in section 2.3. The catchment classification is explained in Table 1 in section 3. Note the logarithmic y-axis in a) and b).

As the appropriate maximum block size ( $N_{max}$ ) is unknown a priori, we originally calculated the  $DFI_N$  index for block sizes from 1 to 180 days (cf. Sect. 2.2) to receive characteristic delay curves (CDC) characterizing the relationship between block size  $N$  and  $DFI_N$ .  $DFI_N$  values and resulting CDCs are calculated for the whole year and separately for the summer season (May to October) and the winter season (November to April) to allow the seasonal variability of different contributing sources to be assessed. The final CDC was smoothed by choosing the minimum of two consecutive  $DFI$  values for all pairs of  $DFI_i$  and  $DFI_{i+1}$ .

## 2.2 Maximum block size $N_{max}$

Some studies (Wahl and Wahl, 1995) have shown that CDCs converge to a catchment-specific asymptotic value for large  $N$ . Accordingly, we hypothesize that for a given  $N_{max}$  the proportion of delayed streamflow stays nearly constant even if  $N$  is further increased ( $N > N_{max}$ ). This value, which is considered a typical maximum delay of all contributing sources, is then captured by this maximum block size  $N_{max}$ . During low flows, streamflow typically originates from one or only a few delayed sources (e.g. slowly draining groundwater aquifers). We thus attributed the mean annual minimum streamflow (MAM) to the slowest contributing sources and identified  $N_{max}$  by comparing the fraction of MAM to mean streamflow (MQ) as an indicator of low flow sensitivity (MAM/MQ). This indicator is comparable to  $Q_{95}/Q_{50}$ , but integrates one minimum flow per year. Higher MAM/MQ means higher low flow stability. MAM and MQ are calculated for each catchment based on daily streamflow values (see Sect. 3). With that  $N$  in the delayed flow separation is increased until a clear relationship between MAM/MQ values and  $DFI_N$  values for all catchments is established.

The relationships between MAM/MQ and  $DFI_N$  is shown in Figure 2 for different  $N$ . As the block size  $N$  is increasing, the maximum block size  $N_{max}$  is identified as the point when the explanatory power of the regression between MAM/MQ and  $DFI_N$ , the coefficient of determination (Fig. 2, insets), ceases to increase. Based on this initial analysis,  $N_{max}$  is set to 60 days as  $N = 60$  is sufficient to capture all annual minimum flows across the catchments and larger values of  $N$  provide no additional information on streamflow variability (i.e. CDCs flatten out for  $N > 60$ , cf. Sect. 2.3).



165 **Figure 2: The Coefficient of determination,  $R^2$ , between  $DFI_N$  and the ratio of Mean Annual Minimum flow to Mean Flow (MAM/MQ) for varying block size  $N$  ranging between 2 and 180 days. Insets show the degree of agreement (as compared to a 1:1 line) for  $N = 16, 38$  and  $60$  days.**

### 2.3 Breakpoints and delay classes

170 Generally, DFI values decrease with increasing  $N$ , but the rate of decrease varies among the catchments (Fig. 3). We assume that a decrease in the slope of the CDC indicates a transition from faster to slower contributing sources (stores) in the catchment. Such specific values of  $N$  can be defined as breakpoints (BP) splitting the CDCs into piecewise linear segments with different slopes (Miller et al., 2015; Wahl and Wahl, 1995). We calculated two breakpoints between 0 and 60 days for each CDC by minimizing the residual sums of the resulting three linear regressions (Muggeo, 2008). Accordingly, the linear regressions represent the piecewise linear shape of the CDCs for the four segments as shown in Figure 3 for four random catchments from the data set (catchment A, B, C and D). The position of each breakpoint pair ( $DFI_{BP1}$  and  $DFI_{BP2}$ ; given as integer values) together with the associated  $DFI_{60}$  value, hence characterize the shape (e.g. curvature, changes in slope, minimum level) of


each single CDC. The delayed contributions to streamflow are then classified into four delay classes, and quantified as the ratio of each component to the total annual streamflow (ranging between zero and one) for each class (Fig. 3):

180

- short delay ( $D_s$ ): between  $N = 0$  (equal to original streamflow series) and  $BP_1$
- intermediate delay ( $D_i$ ): between the two breakpoints ( $BP_1$  and  $BP_2$ )
- long delay ( $D_L$ ): between the  $BP_2$  and  $N = 60$
- baseline ( $D_B$ ) delay: equals the  $DFI_{60}$  value ( $N = 60$ ).

185

The resulting four delay classes can be interpreted according to their relative contributions to streamflow, but also in terms of their absolute values (e.g. mean annual water volume contributing to streamflow in each delay class). Absolute streamflow contributions in each delay class are then calculated based on the catchment-specific average annual streamflow. Relative contributions are calculated based on the differences of the DFI values, i.e. relative contribution in the delay class  $D_s = DFI_0 - DFI_{BP_1}$ ,  $D_i = DFI_{BP_1} - DFI_{BP_2}$ ,  $D_L = DFI_{BP_2} - DFI_{60}$ , and  $D_B = DFI_{60}$ .



190

**Figure 3: Various CDC curves for four example catchments A-D and their variation in  $DFI_0$ ,  $DFI_{60}$  and breakpoints 1 and 2. The example catchments are extracted from the study data set to highlight the variety of CDCs and ratios of delayed streamflow contributions.**

## 2.5 Colwell's Predictability

195

Testing the physical interpretability of the identified delay classes regarding catchment storages and processes, we utilize Colwell's Predictability (Colwell, 1974) to interpret different delay classes of streamflow based on the predictability, constancy, and seasonality of streamflow regimes. Colwell's Predictability is an approach to compare regime constancy or stability in multi-catchment studies with pronounced elevation gradients and different streamflow regimes (Viviroli and Weingartner, 2004). Colwell developed a metric to assess the uncertainty of periodically changing environmental variables with respect to state and time. The detailed mathematical derivation of Colwell's Predictability can be found in Colwell (1974).

200

Exemplary applications of Colwell's Predictability are the periodicity of fruiting and flowering (Colwell, 1974) or the analyses



of streamflow (Poff, 1996) and precipitation (Gan et al., 1991) patterns. Based on information theory, the uncertainty of a variable with respect to its state and timing has been defined as an estimate of reciprocal predictability. This means, if the state and/or timing of a variable is highly uncertain, it is also poorly predictable. This, in turn, leads to a highly predictable flow regime when flow is nearly invariant throughout the year (state is known) or when streamflow has a clear interannual seasonal pattern (timing is known). Combining variation in state and timing the total Colwell's Predictability  $P_T$  [-] is calculated as


$$P_T = P_C + P_S$$

with a component for constancy  $P_C$  [-] and a component for contingency or seasonality  $P_S$  [-]. All three values can vary between 0 and 1 under the condition  $P_C + P_S \leq 1$ . The variables  $P_C$  and  $P_S$  are calculated with the *R* package *hydrostats* with standard configuration (Bond, 2016). A value of  $P_T = 1$  indicates that the mean monthly streamflow values show the same temporal pattern (here streamflow regime) for each temporal cycle (here the hydrological year) (Gan et al., 1991). If so, Constancy  $P_C$  is 1 (e.g. constant flow without any seasonality) or Seasonality  $P_S$  is 1 (e.g. pronounced seasonality with identical monthly flows from between the years) or  $P_C$  and  $P_S$  add theoretically up to 1. In reality, smaller values for  $P_T$  are found due to the variability of climate and the influences of catchment characteristics and water uses (i.e. stronger interannual variability).

### 3 Data and regime classification

We use daily streamflow data (1976–2012) with flow rates per unit area ( $\text{mm d}^{-1}$ ) for a set of 60 catchments with areas between 0.54 and 955  $\text{km}^2$ , all located in southwestern Germany and Switzerland (Fig. 4). Mean catchment elevations range from 227 to 2377 m a.s.l., whereas maximum catchment elevation ranges from 338 up to 3231 m a.s.l. Some of the high-elevation catchments include small proportions of glaciers (2–7%). Although most of the catchments are not pristine, human influences (e.g. urbanization) in these catchments are often small. However, a few streamflow records are influenced by hydropower (i.e. hydropeaking, dams) or sewage discharge.

Mountain regions are heterogeneous in many aspects (morphology, geology, climate, etc.). Since their catchment characteristics offer many plausible catchment classifications, we classify catchments with a rather simple, but straightforward scheme based on the mean and maximum catchment elevation, reflecting hydrological regime types: rainfall-dominated (mean catchment elevation below 1000 m a.s.l.), snowmelt-dominated (mean catchment elevation above 1600 m a.s.l.) and “hybrid”-regime catchments (i.e. mixture of rainfall and snowmelt) between these elevation bounds (Table 1, Fig. 4). From lowland to montane to alpine catchments catchment characteristics generally show gradual changes. Overall, lowland catchments are thought to have thicker soils, larger groundwater storages and longer growing season. Montane catchments comprise pronounced slopes, large elevation ranges and higher freeze-thaw-dynamics due to high variations in catchment snowpack. Alpine catchments are often snowmelt- or (occasionally) glaciermelt-dominated, they have thinner soils and are characterized by bedrock, gravel and taluses, and are near or above the treeline.



235 **Figure 4: Location and area (size of circle) of study catchments. Catchment classification (colors) is explained in Table 1. The right panel shows Pardé coefficients, i.e. the ratio of the long-term mean monthly streamflow to the long-term mean annual streamflow for all catchments grouped by regime type.**

240 The classification follows the definitions of mountains and lowlands for the Alps by Viviroli and Weingartner (2004), which are Pardé coefficients to characterize the seasonality of streamflow (e.g. different typical low flow periods, Table 1). Rainfall-dominated catchments were further divided into “lower” and “upper” catchments with maximum elevations below and above 1000 m a.s.l. to consider possible differences in seasonal snowmelt and evaporative processes between the two groups. The number of classes and lower and upper elevation bounds are comparable to other catchment classifications in the same region (Jenicek et al., 2015; Staudinger et al., 2017; 2015; Viviroli and Weingartner, 2004).

245 **Table 1: Classification scheme separating the catchments into four different groups (abbreviation and color coded) according to elevation and hydrological regime types. Typical low flow periods are derived from streamflow data. Information on snow onset and snowmelt periods are derived from literature (Klein et al., 2016) and generalized for the groups HYBR and SNOW.**

Regime type	Classification scheme				Typical low flow period	Snow season	
	Catchment group	Color code	Mean Elevation (m a.s.l.)	Maximum Elevation (m a.s.l.)		Typical snow onset	Typical begin of snowmelt
<b>rainfall-dominated</b> (lower elevation)	RLWR	green	< 1000	< 1000	Aug – Sep	variable	variable
<b>rainfall-dominated</b> (upper elevation)	RUPR	orange	< 1000	> 1000	Aug – Sep	variable	variable
<b>rainfall- and snowmelt</b>	HYBR	magenta	1000 - 1600	-	Jan – Feb	Nov – Dec	Mar – Apr
<b>snowmelt-dominated</b>	SNOW	blue	> 1600	-	Jan – Mar	Oct – Nov	Apr – May

Our study catchments are uniformly distributed over the four classes allowing for a balanced statistical analysis across the four regime types (Table 2). However, the snowmelt-dominated catchments (SNOW) have notably smaller catchment areas compared to the other groups (around 40%) but their streamflow flashiness is not higher than for catchments in the other groups (Fig. A1). The catchment characteristics and hydrometeorological metrics show in general a increase in precipitation  $P$ , streamflow  $Q$  and the runoff ratio  $Q/P$  with elevation. The HYBR catchment group has the smallest low flow stability index ( $Q_{95}/Q_{50}$ ) and almost no low flow seasonality ( $R_S \approx 1$ ), whereas RLWR and RUPR catchments have summer low flows ( $R_S < 1$ ) and SNOW catchments have winter low flows ( $R_S > 1$ ) (Brunner and Tallaksen, 2019; Laaha and Blöschl, 2006).


260 **Table 2: Catchment characteristics and hydrometeorological metrics (based on period 1992–2013) of the four catchment groups. Numbers given are the average values with the standard deviation of catchments within each group. The seasonality ratio  $R_S$  is the ratio of standardised summer low flows ( $Q_{95s}$  during May – Oct) and winter low flows ( $Q_{95w}$  during Nov – Apr). More details on catchment, climate and streamflow characteristics are given in Fig. A1.**

Catchment group	Number of catchments (-)	Catchment Area $A$ (km <sup>2</sup> )	Mean Elevation (m a.s.l.)	Precipitation $P$ (mm a <sup>-1</sup> )	Streamflow $Q$ (mm a <sup>-1</sup> )	$Q/P$ (-)	$Q_{95}/Q_{50}$ (-)	$R_S = Q_{95s}/Q_{95w}$ (-)
RLWR	18 (30%)	152 ± 102	512 ± 181	1038 ± 191	387 ± 141	0.36 ± 0.07	0.43 ± 0.10	0.78 ± 0.14
RUPR	16 (27%)	178 ± 245	755 ± 158	1433 ± 234	732 ± 236	0.50 ± 0.09	0.30 ± 0.06	0.63 ± 0.16
HYBR	15 (25%)	152 ± 257	1213 ± 166	1803 ± 200	1240 ± 397	0.67 ± 0.17	0.26 ± 0.09	0.98 ± 0.18
SNOW	11 (18%)	62 ± 97	2101 ± 302	1635 ± 187	1529 ± 358	0.92 ± 0.13	0.31 ± 0.09	2.39 ± 0.78

## 4. Results

### 4.1 Characteristic Delay Curves

The Characteristic Delay Curves (CDCs) demonstrate a high variability among catchments and within catchments groups. In Figure 5a CDCs for all catchments are grouped by regime type and season (summer and winter), whereas the average curve for each regime type is shown in Figure 5b. In general, the shape of the CDCs for rainfall-dominated catchments decreases more slowly for increasing  $N$  than for more snowmelt-dominated catchments. The shapes of the curves and also the values of  $DFI_{60}$ , (indicated by the boxplots in Fig. 5a), vary markedly among all catchment groups. Steeper curves imply higher streamflow dynamics, whereas a gentle decrease indicates a higher ratio of longer delayed contributions (compare Fig. 1). Seasonal differences suggest different streamflow generation processes (Fig. 5b), e.g. in snowmelt-dominated catchments rather stable winter flows and higher flashiness during summer.



**Figure 5: Characteristic delay curves (CDCs) for a) all catchments and b) as average for each catchment groups. CDCs are shown for the whole year, and summer (May–Oct) and winter (Nov–Apr) separately. Black dots are estimated breakpoints. Boxplots show the distribution of  $DFI_{60}$  values. The grey lines (delay > 60 days) have very small or zero slopes.**

275 We found a higher variation in the CDCs in the lowest and the highest catchment group (RLWR and SNOW) with an  
interquartile range (IQR) of  $DFI_{60}$  between 0.12 and 0.20 for all seasons. In the other catchment groups (RUPR and HYBR)  
IQR of  $DFI_{60}$  is between 0.06 and 0.12 for all seasons. There the CDCs have a smaller range and show a faster decrease  
compared to RLWR and SNOW catchments. Overall, the curves have small or near zero slopes for delays  $N > 60$  (Fig. 5a),  
however, a few curves continue to decrease, although slowly, for  $N > 60$ . The relative changes in DFI between  $N = 60$  and  
280  $N = 90$  are in all cases relatively small compared to the changes when  $N < 60$ . The proportion of  $DFI_{60} - DFI_{90}$  to  $DFI_0 - DFI_{60}$   
is overall small, varying between 6% (RLWR) and 1.5% (HYBR) with an average of 3% for all catchments.


From a hydrological perspective, the  $DFI_{60}$  (baseline delay  $D_B$ ; Section 2.4) value is important as it quantifies the streamflow  
contribution of slowly varying sources with delays of 60 days and longer. Considering the whole year, RLWR catchments  
have on average the largest proportion of slowly varying sources (0.39), whereas SNOW (0.22), RUPR (0.21) and HYBR  
285 catchments (0.14) have notable lower  $DFI_{60}$  contributions (Fig. 5). Compared to the annual analysis, the summer season (May–  
Oct)  $DFI_{60}$  is higher for RLWR and RUPR catchments (+10% and +5%) and lower for HYBR and SNOW catchments (-1%  
and -6%). For the winter season average  $DFI_{60}$  are lower compared to the whole year for RLWR and RUPR catchments (-6%  
and -3%) and higher for SNOW catchments (+26%) and almost equal for HYBR catchments (+1%). This result reveals that  
low-elevation catchments have comparably fewer streamflow contributions with longer delays during winter (e.g. due to the  
290 snow season and melt events), whereas SNOW catchments show higher streamflow contributions with longer delays during  
winter low flows (Fig. 5b). The HYBR catchments have the smallest  $DFI_{60}$  values for both seasons and the corresponding  
CDCs are characterized by a rapid decrease as  $N$  increases until a value of approximately  $N = 20-30$  days where the curve  
flattens in both summer and winter. In case of HYBR catchments (Fig. 5a), we found that on average 65% of the streamflow  
contributions have delays of 5 days or less ( $DFI_5 = 0.35$ ), 78% have 20 days or less ( $DFI_{20} = 0.22$ ) and 84% have 40 days or  
295 less ( $DFI_{40} = 0.16$ ).

#### 4.2 Breakpoint estimates and streamflow contributions in delay classes

The locations of the first and second breakpoints ( $BP_1$  and  $BP_2$ ) show some distinct features for the four catchment groups.  
The breakpoint estimates for RLWR and SNOW catchments are generally further apart than for RUPR and HYBR catchments.  
Short delayed contributions corresponding to  $BP_1$  are between 2 and 4 days for 95% of the catchments. Three catchments have  
300  $BP_1$  of 5, 6 or 10 days, respectively.  $BP_2$  are around 15 days for RUPR and HYBR catchments and around 25 days for RLWR  
and SNOW catchments, indicating that the RLWR and SNOW catchments have overall larger streamflow contributions with  
intermediate delays.

Transforming the resulting CDC fractions into delay classes many catchments show overall larger streamflow contributions  
from the short delay class ( $D_S$ ), second largest contributions in the intermediate delay ( $D_I$ ) or the baseline delay ( $D_B$ ) and the  
305 smallest streamflow contributions in the long delay class ( $D_L$ ). This suggests that  $D_S$  contributions are often important for  
streamflow generation. However, the DFI analysis unveils also exceptions from this pattern with dominant streamflow  
contributions in  $D_B$  for RLWR catchments and in  $D_I$  for SNOW catchments (Fig. 6a, lower panel). These dominant


310 contributions account for around 40% of the total streamflow in both catchment groups (Fig 6b, lower panel) and are clearly larger than the  $D_L$  contributions in these groups. In contrast, HYBR catchments have an average  $D_S$  contribution of 50% and an average  $D_S$  plus  $D_I$  contribution of 75%. For all HYBR catchments, the first breakpoint is consistently assigned at a delay of  $N=2$  (Fig. 5a), highlighting the importance of fast streamflow generation processes and comparable fast streamflow recessions. Beside  $D_S$  also  $D_I$  contributions stand out and show a clear increase in absolute streamflow contributions with increasing elevation (see also Sect. 4.3, Fig. 7).



315 **Figure 6: Delayed contributions (in absolute and relative terms) to streamflow according to a) delay classes and b) catchment groups. In panel a) each coloured line intentionally represents one catchment to highlight the catchment-specific composition of different contributions.**

### 4.3 Elevation patterns of delayed flows


To explore the elevation dependency pattern of delayed contributions in more detail and to investigate whether these results are sensitive to the catchment classification scheme (Table 1), we sorted the catchments by the mean catchment elevation and binned ten catchments together to calculate smoothed relative streamflow contributions for the four delay classes as shown in Figure 7. This analysis reveals distinct patterns of varying streamflow contributions. Below approximately 800 m a.s.l. the contributions for all delay classes show a high variability and the delay classes are less distinguishable. Above this elevation, the different delay classes show a clear pattern.  $D_S$  contributions dominate in an elevation range between approx. 800 and 1800 m a.s.l. Below 800 m a.s.l.  $D_L$  contributions dominates whereas above 1800 m a.s.l.  $D_I$  contributions are more prominent. The peak of the  $D_S$  contribution is around 1300 m a.s.l. corresponding to the smallest  $D_B$  contribution.  $D_L$  contributions decrease with increasing elevation levelling off at around 10% streamflow contribution slightly above 1500 m a.s.l.  $D_B$  contributions are large for a few low-elevation catchments and show an opposed pattern to  $D_S$  contributions. The decreasing  $D_S$  contributions for elevations higher than 1300 m a.s.l. are compensated not only by  $D_I$ , but also by  $D_B$  contributions. Catchments above 2000 m a.s.l. have larger  $D_I$  than  $D_S$  contributions and  $D_B$  contributions are almost as large as  $D_S$  indicating that at these elevations intermediate and baseline delayed contributions control around 60% of the streamflow dynamics.



335 **Figure 7: Relationship between elevation and contributions to streamflow in different delay classes. Catchments are sorted according to mean elevation and grouped into sets of 10 catchments to estimate average mean elevation for each group.**

#### 4.4 Colwell's Predictability for attribution of delayed contributions

Following Colwell's Predictability ( $P_T$ ) measure, streamflow predictability is composed of constancy ( $P_C$ ) and seasonality ( $P_S$ ). Adding up  $P_C$  and  $P_S$  reveals a distinct *U-shape* pattern for  $P_T$  (Fig. 8a). Overall,  $P_T$  of RLWR and SNOW catchments is higher than for RUPR and HYBR catchments. The lower  $P_T$  provide insights into the catchment characteristics of HYBR, and partly RUPR catchments, as smaller contributions in  $D_L$  and  $D_B$  point to smaller dynamic storage capacity. As HYBR catchments are mainly controlled by  $D_S$  contributions we attribute a smaller dynamic storage capacity and less water retention potential to those catchments. A higher  $P_T$  is mainly attributable to higher  $P_C$  in RLWR and higher  $P_S$  in SNOW catchments. Including a correlation analysis (Fig 8c) we found strong relationships between  $D_B$  contributions and  $P_C$  ( $r = 0.61$ ) and between  $D_L$  contributions and  $P_S$  ( $r = 0.82$ ). Interestingly,  $P_C$  for SNOW catchments is not markedly lower compared to the other three catchment groups. Higher  $P_C$  indicates higher streamflow sustainability throughout the year and this sustainability is related to  $D_B$  contributions. Correlation analysis (Fig. 8c) also reveals that  $D_S$  contributions is negatively correlated to  $P_T$  ( $r = -0.47$ ) and  $P_C$  ( $r = -0.45$ ).



350 **Figure 8: Overview of Colwell's Predictability ( $P_T$ ) = Constancy ( $P_C$ ) + Seasonality ( $P_S$ ) for (a) all catchments and (b) the four catchment groups (higher saturation of violin plots delimits the data range). (c) Relationship (i.e. Pearson's correlation coefficient) between relative streamflow contributions in the four delay classes and the components of Colwell's Predictability ( $P_T = P_C + P_S$ ). Coloured coefficients are statistically significant ( $p$ -value < 0.001).**



## 5. Discussion

### 355 5.1 Technical aspects of delayed flow separation

Any discussion of the applicability of the UK-IH baseflow separation method has to account for the fact that the methodology was developed for humid- and rainfall-dominated catchments (Gustard et al., 1992) and the conventional block size  $N = 5$  is not necessarily valid for catchments with a different climate and hydrological regime, such as lake- or snow-dominated catchments (WMO, 2009). It provides a first-order estimate of catchment responsiveness, separating the streamflow into a fast  
360 and a slow component, and has proved useful in many studies around the world.

In this study, we introduce the new Delayed Flow Index (DFI), which allows to assess a range of different delayed sources providing an alternative to the BFI for more complex systems. From a practical perspective the proposed method is data parsimonious and has a high potential for hydrological application worldwide (due to readily available streamflow data) and can be also adapted for other regimes e.g. for intermitted streams with zero flows in semiarid regions as suggested by Aksoy  
365 et al. (2008) or other variables (e.g. precipitation, groundwater). Comparing DFI and BFI we found a relatively consistent ranking between BFI and  $DFI_{60}$  values with a Spearman's rank coefficient  $\rho = 0.83$ . However, the  $DFI_{60}$  values varied between 20 and 80% of the corresponding BFI values among the catchments included in our study. Accordingly, we argue that  $DFI_{60}$  may provide a more precise quantification of the catchment's ability to maintain flows during dry periods. This is important for assessing the resilience of aquatic ecosystems, improve water resources management (e.g. for quantification of  
370 environmental flow) or test low flow sensitivity to climate change (e.g. change of  $DFI_{60}$  over time).

The decision to use the smoothed minima method instead of the also well-established recursive filter procedures (Eckhardt, 2008; Nathan and McMahon, 1990; Smakhtin, 2001) had the advantage that the choice of block size  $N$  (in days) can be directly related to catchment response and thus, usable for interpretation of main sources of streamflow and as such generally more accessible compared to parameterization of recursive filters (e.g. recession parameters) and their forward- and backward-  
375 filtering procedures. However, a preliminary analysis showed that using a common recursive filter procedure (Nathan and McMahon, 1990) lead to the same ranking of BFI ( $DFI_5$ ) values as the original IH-UK method (results not shown). Similarly, it would be possible to systematically vary parameters in recursive filter procedures to derive different DFI values for different recession parameters.


The wide variety in the shape of CDCs can be seen as reflecting the wide range of catchments spanning from irregular (more  
380 flashy) to persistent (more stable) streamflow regimes (Botter, 2014). Accordingly, we identified catchments with large fractions of shorter and intermediate delayed contributions, and catchments with large fractions of longer delayed contributions to streamflow. The fraction of flow contributions within each delay class is, however, depending on the number of delay classes, i.e. the number of breakpoints and  $N_{max}$ . Both fewer or more breakpoints are feasible to imbed as long as the breakpoints represent the stepwise decrease of the slope and the shape of the CDC (Miller et al., 2015). Also, an adjusted value of  $N_{max}$   
385 might be needed for other climates or streamflow regimes.

In this respect, another potential future application of DFI may be the separation of snowmelt and glaciermelt contributions to streamflow with an additional breakpoint. Some of our study catchments are partly glacierized (<7%) and glacier melt in headwaters during warm and dry summers will eventually make a significant streamflow contribution. However, due to the small proportion of glacierized catchments in our data set, the detected delay classes did not separate clearly between snow- and glaciermelt in catchments represented both by the intermediate delayed component. One useful future approach might be to investigate CDCs of years with more/less snowmelt and more/less glaciermelt (i.e., in total four combinations) to identify the specific delays of those contributions or alternatively, to perform a seasonal analyse of DFI values, e.g. during specific “melt months” (i.e. May versus August in Switzerland). Then the variation in the CDC slope and the piecewise linearity of CDCs can be compared across catchments and seasons building a meaningful tool for hydrological analysis as breakpoints identify specific points in time during receding streamflow when a faster source stops to contribute. Nevertheless, a definite attribution of delayed streamflow contributions to specific sources within a catchment is technically only feasible if a catchment’s fingerprint (e.g. chemical or isotopic) of contributing sources is known and underlying processes are understood. Hence, the DFI is separating different components of the streamflow hydrograph based on their delay patterns and not based on their source identification.

We analysed if the elevation-based classification is a valuable proxy to link patterns of delayed contribution to potential sources. We evaluate the catchment grouping with a cluster analysis to examine the relationship between different delayed contributions and catchments’ assignment to one catchment group based on elevation. K-Means clustering is performed based on the relative proportion of contributions across the four delay classes. Each cluster should then ideally represent a homogenous group of catchments, i.e. RLWR, RUP, HYBR, and SNOW catchments. The applied cluster analysis (Fig. 9) leads to three conclusions: Firstly, clustering based on four clusters explained 76.8% of the total variance in the data set and more additional clusters ( $k > 4$ ) will only slightly increase the explained variance (see inset in Fig. 9). Secondly, three of four clusters (assigned to RLWR, HYBR, and SNOW) are mainly homogenous and distinguishable comparing short and baseline and intermediate and baseline delayed contributions. The fourth cluster is rather heterogeneous but encloses most of the RUPR catchments. Consequently, maximum catchment elevation compared to mean catchment elevation seems to be a rather weak classification criteria as the patterns of delayed contributions in the groups RLWR and RUPR are less distinguishable. A clear classification of delayed streamflow contributions seems to be more challenging if streamflow is not consistently controlled by either rain or snow. Thirdly, for long-delayed contributions (right panel in Fig. 9) the clusters except for the RLWR cluster mostly overlap indicating that specific catchment characteristics (e.g. hydrogeology) or different climate can superimpose the general partitioning of delayed contributions along the proposed elevation gradient. The scattered clustering for long delayed contributions suggests that contributions in this class can also assigned to intermediate or baseline delayed contributions which will reduce one breakpoint (i.e. BP<sub>2</sub>) during DFI separation (Fig. 1 and 3). If so, one should note that also BP<sub>1</sub> will most likely

shift to longer delays, because  $BP_1$  and  $BP_2$  estimates are not independent during the minimization of residuals of the piecewise linear segmentation through the breakpoints.

From a more hydrological perspective, some catchments in the southern Alps have a second regime peak in fall (see Pardé coefficients in g. 4) and are deviating from the nival alpine regimes in the northern Alps. Here, an additional catchment group with nivo-pluvial méridional regimes (Weingartner and Aschwanden, 1992) might be feasible demonstrating in general that future DFI applications in other regions or climates needs potentially an adjusted catchment grouping. We are also aware of some catchments with human influences (like dams and hydropeaking for the Maggia river in the Southern Alps) and recommend to handle such catchments with care. Regardless, for our study neither different climates in the same catchment group (i.e. Northern and Southern Alps) nor human influences lead to extreme behaviour with respect to the breakpoint estimates or the delayed contributions within one of the four catchment groups. Human influences will most likely effect specific delayed contributions, e.g. hydropeaking will alter short delayed contributions whereas damped flow or elevated low flows will alter baseline delayed contributions, e.g. due to zero flow periods or flow stabilization.



**Figure 9: Relationship between short (left panel), intermediate (middle panel) and long delayed (right panel) contributions and baseline delayed contributions (each time on the y-axis). Each point represents one catchment and is colored by its catchment group (RLWR, RUPR, HYBR, SNOW). Each grey polygon is the envelope of one cluster and the lines within the polygon are pointing to the cluster center. The inset in the left panel shows the ratio of between-cluster sum of squares (between\_SS) and total sum of squares (total\_SS), i.e. the ratio of explained variance.**

## 5.2 Paradigm shift from quick- and baseflow to delayed flow

Splitting contributions into two main categories, i.e. fast and slow, has been proven to be useful as a simple measure of catchment responsiveness. Several studies using hydrograph separation with empirical parameter values, e.g. fixed block size  $N$  or fixed recursive filter parameter like suggested by Nathan and McMahon (1990), ignore that different environments have a different type and number of storages and hence, various delayed contributions to streamflow, which also may be highly

depending on season. Even if, for example, a snowmelt pulse is considered as a baseflow contribution to streamflow, the higher BFI value should not be attributed to (large) groundwater storages, but instead to the snowpack and snowmelt processes and their seasonality. Furthermore, especially in large sample hydrology single specific catchment features like the proportion of lakes, wetlands or reservoirs are not considered appropriately in two-component hydrograph separation, as often climate variability is used to explain streamflow variability. With DFI analysis two catchments with the same climate will have different CDCs if e.g. one has streamflow contributions from a lake or reservoir and the other has not. In this respect, delayed flow contributions can be seen as “response patterns” which go along with recent efforts to focus more on effect tracking instead of particle tracking to understand streamflow components and streamflow generation processes (Weiler et al., 2017). Breakpoint estimates are particularly helpful to support this effort as their positions on the CDCs can be interpreted as the maximum delay of a faster source ( $N = BP$ ). Beyond the breakpoint, the streamflow contribution of the faster source diminishes continuously and streamflow variability is more and more controlled by the slower source ( $N > BP$ ). According to the breakpoint analysis, quickflow can be considered as the short delayed component ( $D_s$ ) that ceases to contribute after 2, 3 and 4 days in 55%, 70% and 95% of all our study catchments, respectively. Comparing  $D_s$  contributions (DFI) with quickflow contributions (BFI;  $N = 5$ ) we found on average 11.5, 7.0 and 2.9 % less short delayed contributions to streamflow for catchments with their first breakpoint  $BP_1$  at 2, 3 or 4 days, respectively. Differences between quickflow (in BFI analysis) and  $D_s$  contributions are higher for HYBR and RLWR catchments and less pronounced for SNOW and RLWR catchments.

Based on the breakpoint and DFI analysis, we encourage the recommendation of Hellwig and Stahl (2018) to integrate catchment-specific response times in low flow analysis and hydrological modelling. The authors show that it is impossible to distinguish the contributions from groundwater and snowmelt in snowmelt-dominated catchments with a two-component hydrograph baseflow separation. The governing time scales of streamflow dynamics are also subject of other studies. Brutsaert (2008) reviewed storage coefficients in comparison with recession analysis and identified characteristic drainage processes on timescales of  $45 \pm 15$  days. Staudinger and Seibert (2014) estimated streamflow persistence in various pre-alpine and alpine catchments and found even in quickly responding catchments with assumingly small storages, the slowest delayed signal to be around 50 days. We found from CDC analysis that the slowest dynamic contributions have response times with mean values between 28 and 45 days in the long delay class ( $D_L$ ). In a pan-European modelling study, Longobardi and Van Loon (2018) separated response patterns of catchments into poorly drained ( $BFI < 0.5$ ) and well drained ( $BFI > 0.5$ ) catchments and assigned estimated delay times of the slowest storage in the model to be  $48 \pm 14$  days and  $126 \pm 47$ , respectively. This provides some evidence that for mostly groundwater-dominated catchments,  $N_{max}$  may be set to a larger value (here 60 days) to better capture small variations in interannual low flow magnitude. However, also smaller delays around 60 days for groundwater-dominated systems were found (Huang et al., 2012). A 60 days 'seasonal' period has also been reported as an appropriate window size to characterize the variability of streamflow regimes in respect to environmental flow and ecohydrology (Lytle and Poff, 2004; Poff, 1996). Schmieder et al. (2019) reported for a glacierized high-elevation catchment that “streamflow is dominated by the release of water younger than 56 days”. Accordingly, we found 60 days a suitable block size to capture virtually all the variability in the annual minimum flows (Fig. 2 and 5). Our findings are also consistent with studies based on isotopic tracers

475 revealing that a high proportion of streamflow is less than three months old (Jasechko et al., 2016). However, we recommend further evaluation of the DFI approach, in particular the delayed flow separation based on breakpoints in catchments where contributing sources to streamflow are well understood and timescales of contribution are already estimated by isotopic or solute measurements with, for example, end-member mixing analysis (Miller et al., 2016).

### 5.3 Attribution of delayed flows to catchments' dynamic storages

480 Recharge is crucial to replenish the dynamic storage that supplies groundwater contribution to streamflow. Estimating future groundwater recharge is difficult due to the combined effects of anticipated changes in precipitation, evapotranspiration, land use and land cover as well as in human water demand. Knowledge about different delayed contributions could help to better understand recharge, drainage mechanisms, and dynamic storage in different catchments or regimes. We investigate the relationship between delayed flows and dynamic storage that can be estimated by streamflow analysis (Staudinger et al., 2017).  
485 Higher short delayed contributions indicate lower dynamic storage capacities (i.e. flashier hydrograph) and higher baseline delayed contributions indicate higher potential of a catchment to temporally store water (i.e. smoother hydrograph). The analysis of delayed contributions (Fig. 7) reveals that for our study region, certain mean catchment elevations influence the contributions with different delays for streamflow generation. For example,  $D_S$  contributions are highest at around 1300 m a.s.l., but then decrease for higher elevations. Above this elevation water stored in snow has increasing influence on streamflow  
490 contributions (higher  $D_I$  contributions), but also  $D_B$  contributions (e.g. groundwater) increase and play an important role in maintaining streamflow. Furthermore, our findings of a shift in the catchment response from rainfall- to snow-dominated (at around 1800 m a.s.l. in Fig. 7) support the results of a soil moisture analysis in Switzerland which identified a change from precipitation/evaporation to more frost-affected regime controls at around 2000 m a.s.l. (Pellet and Hauck, 2017). For the HYBR catchments, the results suggest that a smaller storage capacity causes more short delayed contributions (i.e. flashier  
495 hydrographs) indicating that these catchments are likely to be more exposed to future streamflow droughts. The streamflow variability in these catchments is highly sensitive to rainfall, evapotranspiration and fast runoff processes as the observed low predictability of streamflow (i.e. Colwell's Predictability  $P_T$ ) is caused by a high amount (up to 60%) of short delayed contributions (Fig. 8).

Parry et al. (2016b) have shown that elevation outperforms BFI as a measure to characterize the spatial variability of  
500 catchments' responsiveness in the UK. Hence, BFI might not be sufficient to capture the dominant delayed contributions to streamflow across different streamflow regimes. Whereas for some regions, such as the UK, a linear relationship between elevation and responsiveness will be sufficient, the U-shape of Colwell's Predictability (Fig. 8a) suggests that higher streamflow predictability in our study region can be caused by different delayed contributions (i.e.  $D_I$  and  $D_B$  contributions). This justifies using multiple delayed components during response analysis. Minimum annual flow is sustained by a rather  
505 constant delayed contribution with slower and deeper pathways with minimal variations from year to year. The baseline contribution ( $D_B$ ) has a smooth seasonal variability and accounts for up to 60% of mean streamflow in our study catchments (mean 25%) and is an estimate of the dynamic storage controlling the streamflow variability. Analysing the baseline

contributions of our study catchments the corresponding storages drain between 70 and 350 mm a<sup>-1</sup> (using the range between 5<sup>th</sup> and 95<sup>th</sup> percentile of all baseline contributions). This storage drainage is equivalent to 6–24% of annual rainfall and 11–53% of annual streamflow. Interestingly, this proportion is not much smaller in alpine catchments (catchment group SNOW), where D<sub>B</sub> accounts for 12–24% of annual precipitation, and 15–39% of annual discharge. Hood and Hayashi (2015) estimated peak groundwater storage amount (60–100 mm a<sup>-1</sup>) in a small headwater located above 2000 m to be roughly 5–8% of mean annual precipitation and 9–20% of pre-melt snow water equivalent. Floriancic et al. (2018) estimated 50 – 200 mm storage depletion for an alpine headwater catchment in the Alps during a four-month monitoring period in winter. We found that SNOW catchments (22%) have higher baseline delayed contributions compared to RUPR (21%) and HYBR (14%) catchments. The average absolute D<sub>B</sub> contributions for SNOW catchments of 250 mm/a are around 100 mm/a larger than the average absolute D<sub>B</sub> contribution in each of the other three catchment groups (Fig 5b, Fig. 6).

Consequently, we recommend to reconsider the hydrological role of dynamic storages beyond snow storage in alpine environments (Staudinger et al., 2017). According to our CDC analysis the recession behavior during winter in high-elevation catchments is in many SNOW catchments likely the results of slowly draining and/or large dynamic storage. This is underpinned by the “frozen state” of the SNOW catchments during winter; precipitation is stored in the snowpack, snowmelt is not occurring and recharge pulses are infrequent. Thus, subsurface storages (e.g. groundwater) are responsible for sustaining flow during winter (Schmieder et al., 2019) and debris cover and weathered rock might be important groundwater storages (Floriancic et al., 2018).

Our analysis suggests amongst other studies that beside transient snowpack storage also diverse groundwater storage units in alpine catchments (e.g. glacier forefields, taluses, gravel banks, and other colluvial features) are important subsurface storages sustaining streamflow and downstream water availability (Clow et al., 2003; Hood and Hayashi, 2015; Miller et al., 2014; Roy and Hayashi, 2009; Staudinger and Seibert, 2014). Weekes et al. (2014) argued that depositional, often paraglacial landforms with colluvial channel, talus and rock glacier features are good indicators of higher recession constants and thus high water storages indicating slower draining and more sustained baseflow. Talus fields, for example, can contribute more than 40% to streamflow and sustained baseflow after the snowmelt period (Liu et al., 2004). Estimates of total storage volume and a comprehensive understanding of the recharge cycle of those storage units are missing so far, but Paznekas and Hayashi (2015) assumed, for multiple alpine catchments in the Canadian Rockies, that groundwater storage is completely filled up every year and described alpine groundwater as an important streamflow contribution. Also in semiarid mountainous regions, groundwater is supposed to be a major streamflow contribution, sustaining water availability downstream (Jódar et al., 2017).

Regarding dynamic storage in high-elevation catchments the results of our data-driven analysis agree well with methodological more advanced studies in the same (Staudinger et al., 2017) or similar regions (Hood and Hayashi, 2015).

## 6. Conclusions

We extended a commonly used binary quickflow-baseflow hydrograph separation method and introduced a novel concept of  
540 delayed flow index (DFI) based on short, intermediate, long and baseline delayed streamflow contributions. Testing the DFI  
for a set of 60 mesoscale catchments revealed that catchments along a pronounced elevation gradient have characteristic  
delay curves with sets of unique breakpoints. The breakpoints in these curves identify different streamflow contributions  
with different controls on streamflow regime. Our analysis shows that for headwater catchments in Switzerland and south-  
west Germany covering a pronounced elevation gradient, short delayed contributions (i.e. quickflow) cease 2–4 days after  
545 hydrograph peaking and baseline delayed contributions (delays with > 60 days) control the magnitude of streamflow  
sustainability. The continuous analysis for delays between 1 and 60 days is one of the major differences compared to two-  
component BFI analysis (delay smaller or larger than 5 days). The response-oriented perspective on streamflow  
contributions supports a more comprehensive analysis of different catchment storages revealing that groundwater and  
snowmelt are often mixed in one baseflow component in binary baseflow separation given that the whole year is considered.  
550 In addition, intermediate delayed contributions can have a strong influence on the streamflow regime. Hence, the proposed  
DFI allows a more physically meaningful insight into governing processes than the binary, two-component separation  
procedures, and thus represent a step towards an attribution of delayed contribution to potential sources (storages).  
The notably high baseline delayed contributions even in alpine catchments further support the need to reconsider the role of  
dynamic alpine groundwater storages, which may indeed be larger than previously thought (Staudinger et al., 2017).  
555 Baseline delayed contributions in high elevation catchments can account for around 25% of annual precipitation and 40% of  
annual streamflow. Study catchments in between approx. 800–1800 m a.s.l. show the highest low flow sensitivity to climate  
variability due to high amount of short delayed contributions to streamflow which can be explained by smaller dynamic  
catchment storage. The distribution of different delays across catchments improves our understanding of catchment storage  
and release across streamflow regimes, drivers of low flow variability in different seasons, and allows quantifying  
560 streamflow sustainability.


### Code availability

The R Code to calculate the Delayed Flow Index is available in the R package *lfstat* (Koffler et al., 2016). Within the package,  
the function *baseflow* allows calculating delayed flow time series based on the parameter *block.len* ( $N$ ). Breakpoints of CDCs  
can be calculated with R package *segmented* (Muggeo, 2008).

## 565 Data availability

Data is not freely available, but streamflow data can be accessed through the agencies.

## Appendix



570 **Figure A1: Distribution of catchment, climate and streamflow characteristics across the four catchment groups. Data points outside the boxplot range are marked with vertical lines. Catchment characteristics (a, b) are derived from (FOEN, 2013), catchment precipitation (c) is estimated on basis of gridded daily precipitation P (MeteoSwiss RHiresD, 2km interpolated observations data set). For streamflow related metrics (d-g) the same streamflow data is used as described in section 3. Streamflow metrics show the distribution of average daily flow (e), ratio of mean annual minimum flow to average flow as metric for low flow stability (f) and the R-B Index (Baker et al., 2004), where higher values indicating higher hydrograph flashiness (g).**

## 575 Author contribution

MS, TS, MW and LMT had the research idea and designed the study. MS performed the analyses and developed the delayed flow index framework together with TS and MW. All co-authors edited the manuscript.

## Competing interests

The authors declare that they have no conflict of interest.



## 580 **Acknowledgments**

Streamflow and catchment metadata were provided by the Environment Agency of the German state of Baden-Württemberg (LUBW) and the Federal Office for the Environment (FOEN), section of hydrology in Switzerland (BAFU). The authors thank Maria Staudinger and Benedikt Heudorfer for their comments during manuscript drafting. The study is also a contribution to UNESCO IHP-VII and the Euro-FRIEND project.

## 585 **References**

- Aksoy, H., Kurt, I. and Eris, E.: Journal of Hydrology, J. Hydrol., 372(1-4), 94–101, doi:10.1016/j.jhydrol.2009.03.037, 2009.
- Aksoy, H., Unal, N. E. and Pektas, A. O.: Smoothed minima baseflow separation tool for perennial and intermittent streams, Hydrological Processes, 22(22), 4467–4476, doi:10.1002/hyp.7077, 2008.
- 590 Baker, D. B., Richards, R. P., Loftus, T. T. and Kramer, J. W.: A New Flashiness Index: Characteristics And Applications To Midwestern Rivers And Streams, Journal of the American Water Resources Association, 40(2), 503–522, doi:10.1111/j.1752-1688.2004.tb01046.x, 2004.
- Bond, N.: Hydrological Indices for Daily Time Series Data, [online] Available from: <https://CRAN.R-project.org/package=hydrostats>, 2016.
- 595 Botter, G.: Flow regime shifts in the Little Piney creek (US), Adv. Water. Resour., 71, 44–54, doi:10.1016/j.advwatres.2014.05.010, 2014.
- Brunner, M. I. and Tallaksen, L. M.: Proneness of European catchments to multi-year streamflow droughts, Water Resources Research, 2019WR025903–35, doi:10.1029/2019WR025903, 2019.
- Brutsaert, W.: Long-term groundwater storage trends estimated from streamflow records: Climatic perspective, Water  
600 Resources Research, 44(2), W02409, doi:10.1029/2007WR006518, 2008.
- Clow, D. W., Schrott, L., Webb, R., Campbell, D. H., Torizzo, A. and Dornblaser, M.: Ground Water Occurrence and Contributions to Streamflow in an Alpine Catchment, Colorado Front Range, Ground Water, 41(7), 937–950, doi:10.1111/j.1745-6584.2003.tb02436.x, 2003.
- Colwell, R. K.: Predictability, constancy, and contingency of periodic phenomena, Ecology, 55(5), 1148–1153, 1974.
- 605 Constantz, J.: Interaction between stream temperature, streamflow, and groundwater exchanges in alpine streams, Water Resources Research, 1998.
- Demuth, S.: Untersuchungen zum Niedrigwasser in West-Europa [Low flow studies in West Europe], Freiburger Schriften zur Hydrologie, Institute of Hydrology, 1, 1993.
- Demuth, S. and Kulls, C.: Probability analysis and regional aspects of droughts in southern Germany, IAHS-AISH  
610 publication, 240, 97–104, 1997.
- Dingman, S. L.: Physical hydrology, 3rd ed., Waveland Press. 2015.

- Eckhardt, K.: A comparison of baseflow indices, which were calculated with seven different baseflow separation methods, *J. Hydrol.*, 352(1-2), 168–173, doi:10.1016/j.jhydrol.2008.01.005, 2008.
- 615 Floriancic, M. G., Meerveld, I., Smoorenburg, M., Margreth, M., Naef, F., Kirchner, J. W. and Molnar, P.: Spatio-temporal variability in contributions to low flows in the high Alpine Poschiavino catchment, *Hydrological Processes*, 32(26), 3938–3953, doi:10.1002/hyp.13302, 2018.
- FOEN: Federal Office for the Environment, section of hydrology, [online] Available from: <http://www.hydrodaten.admin.ch/en/>, 2013.
- 620 Freyberg, von, J., Studer, B., Rinderer, M. and Kirchner, J. W.: Studying catchment storm response using event and pre-event water volumes as fractions of precipitation rather than discharge, *Hydrol. Earth Syst. Sci. Discuss.*, 1–34, doi:10.5194/hess-2018-401, 2018.
- Gan, K. C., McMahon, T. A. and Finlayson, B. L.: Analysis of periodicity in streamflow and rainfall data by Colwell's indices, *J. Hydrol.*, 123(1), 105–118, 1991.
- 625 Gustard, A., Bullock, A. and Dixon, J. M.: Low flow estimation in the United Kingdom, *Institute of Hydrology (UK)*, 108, 88, 1992.
- Hall, F. R.: Base-flow recessions—a review, *Water Resources Research*, 4(5), 973–983, 1968.
- Hellwig, J. and Stahl, K.: An assessment of trends and potential future changes in groundwater-baseflow drought based on catchment response times, *Hydrol. Earth Syst. Sci.*, 22(12), 6209–6224, doi:10.5194/hess-22-6209-2018, 2018.
- 630 Hisdal, H., Tallaksen, L., Clausen, B., Peters, E. and Gustard, A.: Hydrological Drought Characteristics, in *Hydrological Drought Processes and Estimation Methods for Streamflow and Groundwater*, vol. 48, edited by L. M. Tallaksen and H. A. J. van Lanen, pp. 139–198, Elsevier B.V., the Netherlands. 2004.
- Hood, J. L. and Hayashi, M.: *Journal of Hydrology*, *J. Hydrol.*, 521(C), 482–497, doi:10.1016/j.jhydrol.2014.12.041, 2015.
- Huang, J., Halpenny, J., van der Wal, W., Klatt, C., James, T. S. and Rivera, A.: Detectability of groundwater storage change within the Great Lakes Water Basin using GRACE, *J. Geophys. Res.*, 117(B8), B08401, doi:10.1029/2011JB008876, 2012.
- 635 Jasechko, S., Kirchner, J. W., Welker, J. M. and McDonnell, J. J.: Substantial proportion of global streamflow less than three months old, *Nature Geoscience*, 9(2), 126–129, doi:10.1038/ngeo2636, 2016.
- Jenicek, M., Seibert, J., Zappa, M., Staudinger, M. and Jonas, T.: Importance of maximum snow accumulation for summer low flows in humid catchments, *Hydrol. Earth Syst. Sci. Discuss.*, 12(7), 7023–7056, doi:10.5194/hessd-12-7023-2015, 2015.
- 640 Jódar, J., Cabrera, J. A., Martos-Rosillo, S., Ruiz-Constán, A., González-Ramón, A., Lambán, L. J., Herrera, C. and Custodio, E.: Groundwater discharge in high-mountain watersheds: A valuable resource for downstream semi-arid zones. The case of the Bérchules River in Sierra Nevada (Southern Spain), *Science of The Total Environment*, 593-594(C), 760–772, doi:10.1016/j.scitotenv.2017.03.190, 2017.
- Klaus, J. and McDonnell, J. J.: *Journal of Hydrology*, *J. Hydrol.*, 505(C), 47–64, doi:10.1016/j.jhydrol.2013.09.006, 2013.
- 645 Klein, G., Vitasse, Y., Rixen, C., Marty, C. and Rebetez, M.: 2016-09-28\_art%3A10.1007%2Fs10584-016-1806-y, *Climatic Change*, 1–13, doi:10.1007/s10584-016-1806-y, 2016.

- Koffler, D., Gauster, T. and Laaha, G.: *lfstat*: Calculation of Low Flow Statistics for Daily Stream Flow Data. <https://CRAN.R-project.org/package=lfstat> [online] Available from: <https://CRAN.R-project.org/package=lfstat> (Accessed 2016), 2016.
- 650 Kronholm, S. C. and Capel, P. D.: A comparison of high-resolution specific conductance-based end-member mixing analysis and a graphical method for baseflow separation of four streams in hydrologically challenging agricultural watersheds, *Hydrological Processes*, 29(11), 2521–2533, doi:10.1002/hyp.10378, 2015.
- Laaha, G. and Blöschl, G.: Seasonality indices for regionalizing low flows, *Hydrological Processes*, 20(18), 3851–3878, doi:10.1002/hyp.6161, 2006.
- 655 Linsley, R., Kohler, M. and Paulhus, J.: *Hydrology for Engineers*, McGraw-Hill, New York. 1958.
- Liu, F., Williams, M. W. and Caine, N.: Source waters and flow paths in an alpine catchment, Colorado Front Range, United States, *Water Resources Research*, doi:10.1029/2004WR003076, 2004.
- Longobardi, A. and Van Loon, A. F.: Assessing baseflow index vulnerability to variation in dry spell length for a range of catchment and climate properties, *Hydrological Processes*, 32(16), 2496–2509, doi:10.1002/hyp.13147, 2018.
- 660 Lyne, V. and Hollick, M.: *Stochastic time-variable rainfall-runoff modelling*. 1979.
- Lytle, D. A. and Poff, N. L.: Adaptation to natural flow regimes, *Trends in Ecology & Evolution*, 19(2), 94–100, doi:10.1016/j.tree.2003.10.002, 2004.
- Meyer, R., Schadler, B. and Weingartner, D. V. U. R.: Die Rolle des Basisabflusses bei der Modellierung von Niedrigwasserprozessen in Klimaimpaktstudien, *Hydrologie und Wasserbewirtschaftung*, 55(5), 244–257, 2011.
- 665 Miller, M. P., Buto, S. G., Susong, D. D. and Rumsey, C. A.: The importance of base flow in sustaining surface water flow in the Upper Colorado River Basin, *Water Resources Research*, 52(5), 3547–3562, doi:10.1002/2015WR017963, 2016.
- Miller, M. P., Johnson, H. M., Susong, D. D. and Wolock, D. M.: A new approach for continuous estimation of baseflow using discrete water quality data: Method description and comparison with baseflow estimates from two existing ..., *J. Hydrol.*, doi:10.1016/j.jhydrol.2014.12.039, 2015.
- 670 Miller, M. P., Susong, D. D., Shope, C. L., Heilweil, V. M. and Stolp, B. J.: Continuous estimation of baseflow in snowmelt-dominated streams and rivers in the Upper Colorado River Basin: A chemical hydrograph separation approach, *Water Resources Research*, n/a–n/a, doi:10.1002/2013WR014939, 2014.
- Muggeo, V. M.: *Segmented*: an R package to fit regression models with broken-line relationships, *R news*, 8(1), 20–25, 2008.
- 675 Nathan, R. and McMahon, T.: Evaluation of automated techniques for base flow and recession analyses, *Water Resources Research*, 26(7), 1465–1473, 1990.
- Nathan, R. J. and McMahon, T. A.: Estimating low flow characteristics in ungauged catchments, *Water Resour Manage*, 6(2), 85–100, doi:10.1007/BF00872205, 1992.
- Natural Environment Research Council: *Low Flow Studies*, Institute of Hydrology, 1–50, 1980.

- 680 Olden, J. D., Kennard, M. J. and Pusey, B. J.: A framework for hydrologic classification with a review of methodologies and applications in ecohydrology, *Ecohydrology*, 5(4), 503–518, doi:10.1002/eco.251, 2011.
- Parry, S., Wilby, R. L., Prudhomme, C. and Wood, P. J.: A systematic assessment of drought termination in the United Kingdom, *Hydrol. Earth Syst. Sci.*, 20(10), 4265–4281, doi:10.5194/hess-20-4265-2016, 2016a.
- 685 Parry, S., Wilby, R. L., Prudhomme, C. and Wood, P. J.: A systematic assessment of drought termination in the United Kingdom, *Hydrol. Earth Syst. Sci.*, 20(10), 4265–4281, doi:10.5194/hess-20-4265-2016, 2016b.
- Partington, D., Brunner, P., Simmons, C. T., Werner, A. D., Therrien, R., Maier, H. R. and Dandy, G. C.: Evaluation of outputs from automated baseflow separation methods against simulated baseflow from a physically based, surface water-groundwater flow model, *J. Hydrol.*, 458, 28–39, doi:10.1016/j.jhydrol.2012.06.029, 2012.
- 690 Paznekas, A. and Hayashi, M.: Groundwater contribution to winter streamflow in the Canadian Rockies, *Canadian Water Resources Journal / Revue canadienne des ressources hydriques*, 41(4), 484–499, doi:10.1080/07011784.2015.1060870, 2015.
- Pellet, C. and Hauck, C.: Monitoring soil moisture from middle to high elevation in Switzerland: set-up and first results from the SOMOMOUNT network, *Hydrol. Earth Syst. Sci.*, 21(6), 3199–3220, doi:10.5194/hess-21-3199-2017, 2017.
- 695 Piggott, A. R., Moin, S. and Southam, C.: A revised approach to the UKIH method for the calculation of baseflow, *Hydrol. Sci. J.*, 50(5), 911–920, 2005.
- Poff, N. L.: A hydrogeography of unregulated streams in the United States and an examination of scale-dependence in some hydrological descriptors, *Freshwater Biology*, 36(1), 71–91, 1996.
- Roy, J. W. and Hayashi, M.: Multiple, distinct groundwater flow systems of a single moraine-talus feature in an alpine watershed, *J. Hydrol.*, 373(1-2), 139–150, doi:10.1016/j.jhydrol.2009.04.018, 2009.
- 700 Schmieder, J., Seeger, S., Weiler, M. and Strasser, U.: “Teflon Basin” or Not? A High-Elevation Catchment Transit Time Modeling Approach, *Hydrology*, 92(6), doi:10.3390/hydrology6040092, 2019.
- Schuetz, T., Gascuel-Oudou, C., Durand, P. and Weiler, M.: Nitrate sinks and sources as controls of spatio-temporal water quality dynamics in an agricultural headwater catchment, *Hydrol. Earth Syst. Sci.*, 20(2), 843–857, doi:10.5194/hess-20-843-2016, 2016.
- 705 Schwarze, R., Grünewald, U., Becker, A. and Fröhlich, W.: Computer-aided analyses of flow recessions and coupled basin water balance investigations, *FRIENDS in Hydrology*, 75–83, 1989.
- Smakhtin, V.: Low flow hydrology: a review, *J. Hydrol.*, 240(3), 147–186, doi:10.1016/S0022-1694(00)00340-1, 2001.
- Sophocleous, M.: Interactions between groundwater and surface water: the state of the science, *Hydrogeol. J.*, 10(1), 52–67, doi:10.1007/s10040-001-0170-8, 2002.
- 710 Staudinger, M. and Seibert, J.: Predictability of low flow - An assessment with simulation experiments, *J. Hydrol.*, 519, 1383–1393, doi:10.1016/j.jhydrol.2014.08.061, 2014.
- Staudinger, M., Stoelzle, M., Seeger, S., Seibert, J., Weiler, M. and Stahl, K.: Catchment water storage variation with elevation, *Hydrological Processes*, 47(4), 1–16, doi:10.1002/hyp.11158, 2017.

- 715 Staudinger, M., Weiler, M. and Seibert, J.: Quantifying sensitivity to droughts - an experimental modeling approach, *Hydrol. Earth Syst. Sci.*, 19(3), 1371–1384, doi:10.5194/hess-19-1371-2015, 2015.
- Stoelzle, M., Weiler, M., Stahl, K. and Morhard, A.: Is there a superior conceptual groundwater model structure for baseflow simulation? *Hydrological Processes*, 29, doi:10.1002/hyp.10251, 2015.
- Tallaksen, L.: An evaluation of the base flow index (BFI), *Rapportserie: HYDROLOGI*, 16, 1–27, 1987.
- 720 Tallaksen, L. M. and van Lanen, H.: *Hydrological Drought: Processes and Estimation Methods for Streamflow and Groundwater*, edited by L. M. Tallaksen and H. van Lanen, Elsevier Publ. The Netherlands, Amsterdam. 2004.
- Viviroli, D. and Weingartner, R.: The hydrological significance of mountains: from regional to global scale, *Hydrol. Earth Syst. Sci.*, 8(6), 1016–1029, 2004.
- Wahl, K. L. and Wahl, T. L.: Determining the flow of comal springs at New Braunfels, Texas, *Proceedings of Texas Water*, 95, 16–17, 1995.
- 725 Weekes, A. A., Torgersen, C. E., Montgomery, D. R., Woodward, A. and Bolton, S. M.: Hydrologic response to valley-scale structure in alpine headwaters, *Hydrological Processes*, 29(3), 356–372, doi:10.1002/hyp.10141, 2014.
- Weiler, M., Seibert, J. and Stahl, K.: Magic components - why quantifying rain, snow- and icemelt in river discharge isn't easy, *Hydrological Processes*, 1–10, doi:10.1002/hyp.11361, 2017.
- 730 Weingartner, R. and Aschwanden, H.: *Abflussregimes als Grundlage zur Abschätzung von Mittelwerten des Abflusses*, *Hydrologischer Atlas der Schweiz*, Tafel, 5, 1992.
- Wittenberg, H.: Effects of season and man-made changes on baseflow and flow recession: case studies, *Hydrological Processes*, 17(11), 2113–2123, doi:10.1002/hyp.1324, 2003.
- Wittenberg, H. and Sivapalan, M.: Watershed groundwater balance estimation using streamflow recession analysis and baseflow separation, *J. Hydrol.*, 219(1), 20–33, doi:10.1016/S0022-1694(99)00040-2, 1999.
- 735 WMO: *Manual on Low-flow Estimation and Prediction – Operational Hydrology Report No. 50*, edited by A. Gustard and S. Demuth, World Meteorological Organization, 1029, 136, 2009.