

Authors' response to reviews

Antoine PELLETIER, on behalf of co-authors

24th January 2020

1 Response to reviews

We would like to thank Pr. Romanowicz and Pr. Cartwright for reading our manuscript and for their careful and useful reviews. We also thank Pr. Beven and Dr. Ding for their short comments which contributed to the rich interactive discussion. Here are our response to the points raised by the debate.

Optimisation criterion

As it is highlighted in Pr. Romanowicz's comment, the optimisation criterion that we use to calibrate the parameters of the hydrograph separation algorithm – Pearson correlation between baseflow and cumulated effective rainfall – is not univocal enough to be a satisfying correlation criterion. Indeed, it is subject to pseudo-periodical oscillations caused by the annual hydroclimatic cycle; it is visible on figure 3, page 14. We chose to use Pearson correlation since it is quick to compute and easy to interpret; however, a more complex optimization criterion could be developed indeed to get more univocal results.

Recharge as linear fraction of streamflow

This issue was underlined by both referees, Pr. Romanowicz and Pr. Cartwright: the fact that the water inflow of the quadratic reservoir is a linear fraction of daily measured streamflow is a major hypothesis of the algorithm. This is a very crude estimate of aquifer/subsurface recharge, which is a far more complex process including water flow through banks of the river, soil water balance, vegetation, seasonality, etc. Solving the groundwater transmissivity equation in a theoretical framework of a shallow aquifer connected to a river shows that recharge is anything but a linear fraction of streamflow; and real configurations of river-aquifer interactions are even more intricate.

However, as highlighted by the exchange with Pr. Beven, we do not claim to present a physically-based hydrograph separation method. For such a purpose, we would need an explicit recharge model, that would add more hypotheses and parameters: an elaborate production function in such an imperfect, but objective, algorithm would be a disproportionate weapon. Therefore, the inflow function composed of a fixed linear fraction of daily streamflow can be regarded as a basic estimate of the quantity of water that bears the catchment memory.

In the revised version of the article, we added a clearer explanation about the inflow function of the reservoir.

Notations in equations

We use a different notation for the continuous and the discrete versions of a variable: $X(t)$ for the continuous one and X_t for the discrete one. Integration of the continuous differential equations is

made through a Eulerian explicit scheme and equation on page 7, line 15 is intended to explain how continuous variables are made from discrete measurements; in the revised version of the manuscript, we replaced it by a clearer plain-text explanation that will avoid confusion with other variables in the algorithm. As suggested by Pr. Cartwright, we added a table of variables to help the readability.

Correlation between parameters

Two parameters need to be calibrated in the algorithm presented in article. We tried to find a simple relationship between catchments' characteristics and parameters, in order to remove one degree of freedom in the optimization process; but we did not manage to find one. Since it is an unsuccessful point, it is not detailed in the manuscript; it is only mentioned at the end of page 17. In the revised version of the manuscript, we gave more details about it and the hydrological interpretation of such a result.

Hydrograph separation and hydrological processes

The separation of streamflow in two components – the slow and the quick one, or more precisely the delayed and the non-delayed one – is artificial: there is generally a wider range of hydrological processes at stake that have different response times to hydroclimatic events. Having said that, it is still possible to set up an arbitrary barrier between the *not too delayed* components of streamflow and the *delayed enough* components.

But attributing the flow component to an explicit physical process seems to be risky with a conceptual separation method like the one we present in the manuscript. Pr. Cartwright highlights that we define baseflow as the groundwater component of streamflow and quick flow as the surface runoff component. This distinction is improper and partial, we agree that it is an oversimplification of the system. Ideally, we should take into account various intermediate stores of water, for which we do not want to make hypotheses about their water residence time.

Anyhow, process interpretation of a conceptual separation method is hazardous practice – this was highlighted too by the interactive discussion with Pr. Beven. In the revised version of the article, after explaining the various types of water sources and their response behaviour, we defined baseflow as the sum of delayed streamflow components, whatever source they are from. The interest of this component is that it bears inter-annual memory of a catchment. We added this discussion to the introduction section.

Abstract

We believe in short and catchy abstracts that are likely to be read entirely. However, we agree that some crucial elements are missing in the proposed version. We propose a new abstract, which is a little longer.

Introduction and review section

In the revised version of the article, we merged the two sections. As underlined by Pr. Cartwright, some recent references are missing in the literature review; we rectified the review by adding new citations.

Yearly reservoir update

In the presented algorithm, there are two ways the level of the reservoir can be updated: downward, when the computed baseflow is greater than measured streamflow; upward, once a year, at the yearly minimum point of measured streamflow. The first one is understandable – baseflow cannot be greater than total streamflow – and the second one is just practical: as highlighted by Pr. Cartwright, in humid temperate French climate, the hypothesis that streamflow is only composed of baseflow at its yearly minimum is questionable, even though most recent French summers were dry enough to support this assumption. However, we need an upward update mechanism to compensate the downward one, since it allows the algorithm to be constrained to a water balance condition – that can be summed up by $\beta = BFI$. Removing the yearly upward update adds a degree of freedom for the model calibration and it causes significant difficulty to optimize the values of parameters. We added this discussion in the revised version of the paper.

Role of τ parameter

The idea of the optimization criterion used to calibrate the parameters is the following: we try to correlate two estimates of the quantity of water available to bear the catchment memory. First, computed baseflow; second, medium-term or long-term cumulative effective rainfall – which we estimated through the Turc-Mezentsev formula. Parameter τ is the length of the cumulating period for effective rainfall, it is an estimate of the response time of the catchment. Unfortunately, it gave less consistent results than the computed values of baseflow index, due to more calibration difficulty.

Validation using hydrochemical data

We agree with Pr. Cartwright that using geochemical data would be a less questionable way to calibrate our hydrograph separation process than the hydroclimatic criterion that we use. Unfortunately, we do not have available enough geochemical data in the French catchments of the sample to carry out a reliable study. We mentioned this idea as a perspective.

Limitations of the method

The technique presented in the manuscript is designed to be used on non-anthropised catchments and perennial streams. As highlighted by Pr. Cartwright, these limitations need to be more explicitly exposed in the conclusion. When the value of streamflow is affected by human activity – pumping, regulation by dams, canals, etc. – the algorithm can be applied only if the anthropised fraction of streamflow is small enough. This is a classical check in rainfall-runoff modelling. The case of groundwater abstraction resulting in disconnection is different: it is still caused by human activity but it indirectly affects streamflow. In such a case, if the aquifer contribution to the river is zero; but in the algorithm, reaching an empty filtering reservoir could result in some artefacts. This is a clear practical limitation of the method. In the revised version of the manuscript, we mentioned these limits of the study.

2 List of changes in manuscript

Page	Lines	Description
1	1-8	Longer abstract
1	17-18	Definition of baseflow
2	9	Merging introduction and review section
2	10-26	New section defining hydrograph separation
2	27-30	Re-writing some sentences of the introduction to review
3	1-3	Re-writing some sentences of the introduction to review
3	5	Re-writing without process interpretation
3	12-13	Adding new reference
3	24-25	Discussion about tracer-based methods
3	25	Adding new references
4	15	Adding new references
4	24	Adding new references
4	29	Re-writing without process interpretation
5	21-22	Adding new references
6	9-10	Minor rephrasing
6	19	Re-writing without process interpretation
6	24	Re-writing without process interpretation
7	6-9	Discussion about the reservoir inflow function
7	19	Mentioning the table of variables
8	13-15	Clearer description of the integration scheme
8	21	Clearer description of the integration scheme
9	4	Minor rephrasing
9	13	Minor rephrasing
10	12-14	Discussion about the yearly minimum update
11	16	Minor rephrasing
11	7	Addong missing β in the algorithm
12	17-18	Clearer definition of the parameter τ
14	1	Minor caption rephrasing
18	8	Correcting a typing error
18	22-25	Clearer explanation about the correlation between BFI and τ
23	1	Adding figure reference
23	3-5	Adding conclusive remarks about the optimization criterion
23	11-12	Perspective of evaluating the method using hydrochemical data
23	13-14	Discussion about catchments affected by human activity
23	18	Adding the package reference with a DOI
28	All	Table of variables

Table 1: List of changes made by authors in the manuscript. Page and line numbers refer to the latexdiff version of the manuscript, available below.

3 latexdiff version of the manuscript

This version of the manuscript is available below. Added content is typeset in blue and removed one is in red footnotes.

Hydrograph separation: an impartial parametrization for an imperfect method

Antoine PELLETIER^{1,2} and Vazken ANDRÉASSIAN²

¹École des Ponts ParisTech, Champs-sur-Marne, France

²Université Paris-Saclay, INRAE, UR HYCAR, Antony, France

Correspondence: Antoine Pelletier (antoine.pelletier@irstea.fr)

Abstract. This paper presents a new method for hydrograph separation. It is well-known that all hydrological methods aiming at separating streamflow into baseflow [¹] – its slow or delayed component – and quickflow – its non-delayed component – present large imperfections, and we do not claim to provide here a perfect solution. However, the method described here is at least (i) impartial in the determination of its two parameters (a quadratic reservoir capacity and a response time), (ii) coherent in time (as assessed by a split-sample test) and (iii) geologically coherent (an exhaustive validation on 1,664 French catchments shows a good match with what we know of France’s hydrogeology). With these characteristics, the method can be used to perform a general assessment of hydroclimatic memory of catchments. Last, an R package is provided to ensure reproducibility of the results presented.

1 Introduction

Hydrograph separation and the identification of the baseflow contribution to streamflow is definitely not a new subject in hydrology. This age-old topic (Boussinesq (1904); Horton (1933); Maillet (1905)) is almost as universally decried as it is universally used. Indeed, two adjectives appear repeatedly in hydrology textbooks: *artificial* and *arbitrary* (see. e.g., Linsley et al. (1975); Réménieras (1965); Roche (1963); Chow (1964)). Hewlett and Hibbert (1967) – the famous forest hydrology precursors – even added *desperate*, where Klemeš (1986) compared the hydrograph separation procedures with the astronomical epicycles (i.e., the absurd trajectories that had been invented to maintain the geocentric theory before the time of Copernicus and Galilei).

To assess baseflow, direct measurement is generally impossible, [²] since it is a conceptual quantity, not a physical one. Proxy approaches involving chemical tracer-based procedures are efficient but need chemical data and involve their load of assumptions. Most approaches rely on solving an *inverse problem*, i.e, reckoning the quantitative causes (here baseflow and quickflow) of an observed physical phenomenon – total runoff. This procedure is very common in hydrology and it is reasonably feasible when the variable can be measured and a calibration procedure can be implemented; but here again, the non-measurable character of baseflow renders the question difficult.

¹removed: and quickflow

²removed: because aquifer–river exchanges are usually continuous processes that take place all along the stream network

It is perhaps impossible to propose a physically based baseflow separation procedure (just because of the multiplicity of flow paths that make the procedure fundamentally equifinal), and we will not argue on this point. But we believe that even the imperfect conceptual–mathematical–empirical methods in use could receive an unarbitrary, impartial, repeatable parameterization that could be used as a general-purpose study tool over large catchment sets.

5 This paper focuses on a hydrograph separation method that is based only on quantitative streamflow data and climate descriptors and does not require *a priori* physical parametrization, presented in section 3. The originality of this method lies in its parametrization strategy, which we discuss in detail in section 3.2. The application of this procedure to a set of 1,664 catchments, its geological coherence and its stability in time are presented in section 4.

2 [..³]

10 1.1 The principle of hydrograph separation

Hydrograph separation is founded on the following assumption: streamflow can be divided into two components, *baseflow* and *quickflow* whose response to hydroclimatic events is different. Baseflow is the slow component of streamflow, while quickflow is the remaining part, i.e. the quick part of streamflow. This separation in two components is obviously artificial: there is generally a wider range of hydrological processes at stake that respond diversely to hydroclimatic events. Having
15 said that, it is still possible and interesting to set up an arbitrary barrier between the *not too delayed* components of streamflow – quickflow – and the *delayed enough* – baseflow – ones.

A commonly found definition of hydrograph separation is splitting streamflow between surface runoff and groundwater contribution. This may be an acceptable interpretation of chemicophysical methods that are based on the difference – of composition or temperature, for instance – between different sources of water. But in general, process interpretation of
20 hydrograph separation is hazardous practice (Beven (1991)). If surface runoff is definitely one of the quicker hydrological processes, a quick response to a rainfall event is not necessarily composed of recent water; it can be even be made of mostly old water (Kirchner (2003)). At the scale of a single event, defining baseflow as groundwater contribution results from a confusion between celerity and velocity of the hydrograph response (McDonnell and Beven (2014)): baseflow is composed of perturbations propagated with a low celerity and much dispersion, which can be composed of old and recent
25 water, coming from various stores of water, such as subsurface flow, aquifers or bank storage. Therefore, baseflow is the component of the hydrograph bearing the catchment's memory.

Existing procedures for hydrograph separation and baseflow assessment can be divided into three categories (Gonzales et al. (2009)), according to their level of *physicalness*: (i) physical/chemical methods are based on [..⁴] **chemicophysical differences between quick water and slow water, assuming that they come from different sources**; (ii) numerical/empirical methods
30 do not attempt any kind of hydrological representation or modelling and use signal processing tools to alter streamflow hydro-

³removed: Hydrograph separation: a short review

⁴removed: the differences – of composition or temperature, for instance – between groundwater and surface water

graphs; (iii) conceptual methods conceive ^[..⁵]baseflow as the outflow of a reservoir that ^[..⁶]represents the catchment's memory. The following ^[..⁷]sections paint a quick picture of these three categories, before concluding about their shortages and drawbacks that led to the development of a new method.

1.2 Chemicophysical methods

- 5 Chemicophysical methods are based on the fact that total flow is a *mix* of ^[..⁸]various sources of water, with different characteristics (Pinder and Jones (1969)). By knowing the latter, it is possible to revert mixing equations to get the relative contribution of each flow source, using a simple mass-balance approach. Chemicophysical methods are powerful and they provide a lot of information where ^[..⁹]water quality data are available and where the hydrochemical configuration allows for rather strong hypotheses: consistency in space and time of water characteristics and the assumption that the hydrological system is conservative – to avoid any unknown water inflow.

The most common methods of this family are tracer-based baseflow separations. A passive tracer whose concentration is different in groundwater^[..¹⁰], subsurface, bank and surface runoff water – for instance, isotopes (Cartwright and Morgenstern (2018)) such as deuterium, tritium or ¹⁸O, ions (carbonates, calcium, magnesium, sulphates) from dissolved minerals or silica – is used as a proxy for mass balance assessment^[..¹¹]; at each time step of available data, ^[..¹²]it allows for a dynamic real-time baseflow decomposition. Other methods rely on conductivity, pH, or temperature, which can be easier to measure in situ.

There are ^[..¹³]three main drawbacks in chemicophysical methods. First, the uncertainties that are inherent to them – there are measurement errors, concentrations can have spatial and temporal heterogeneity, even within the same rainstorm, and the passiveness of tracers may not be a valid hypothesis even in short events; Kirchner (2019) proposed a statistical tracer-based separation to replace this mass balance hypothesis, using a regression between baseflow and tracer concentrations in streamflow and rainfall. Second, the implementation of these methods on catchments is limited by the large number of data needed. Continuous groundwater and surface water quality data are seldom available except for specially instrumented catchments (Gonzales et al. (2009)). Finally, they imply a process-based definition of baseflow and quickflow, which is difficult to build without knowing the particular context of each catchment; that-is-why tracer-based methods generally give different results respect to conceptual and numerical methods (Cartwright et al. (2014); Costelloe et al. (2015)). Even though tracer-based methods can provide useful and valuable information on dominant processes occurring inside a catchment, their application for routine analysis is not conceivable on a large number of gauging stations.

⁵removed: the aquifer as

⁶removed: empties itself during recessions

⁷removed: section paints

⁸removed: baseflow waterand surface flow water

⁹removed: surface water and groundwater

¹⁰removed: and surface

¹¹removed: ,

¹²removed: which

¹³removed: two main drawbacks of

1.3 Empirical and numerical methods

Several classic baseflow-separation methods are not based on hydrological considerations, but rely on processing the hydrograph as a signal. Most of these methods are based on the hypothesis that the transfer time of surface runoff is much shorter than that of groundwater and that this time is relatively constant between rainfall events. The first methods of this type were graphical. After identifying peaks along the hydrograph and estimating the surface runoff time constant – let us say N days – peaks are cut by drawing a straight line between the beginning of each peak and the point N days after (Linsley et al. (1975); Gonzales et al. (2009)). This simple approach has been honed to take into account consecutive precipitation events or aquifer recharge during rainfall, but it remains quite subjective, as the graphical processing is supposed to be done by hand and is difficult to automatize. Streamflow under the constructed dividing line is assumed to be baseflow, while the remaining peaks are surface flow.

Within the same set of hypotheses, low-pass numerical filtering of the hydrograph has been used as a baseflow separation method. As in electronic signal filtering, the highest frequencies of the signal are dropped and the low ones are kept. Fourier transform-based filters implement this framework, but they are intended for data with stationary periodic processes, whereas hydrological signals operate on a very large range of time scales. Even *quick* components of streamflow have low-frequency Fourier terms ([..¹⁴]Duvert et al. (2015); Labat (2005); Su et al. (2016)). Classical electronic low-pass filters are therefore not adapted to hydrograph separation. In line with graphical methods, a local minimum filter on a sliding window – whose length is basically the time scale of baseflow – has been developed, as well as recursive digital filters with low-pass properties. Transformations can be applied on the streamflow time series before numerical filtering, in order to improve the filter's efficiency (Romanowicz (2010)). Finally, artificial neural networks have been employed as data-driven models for hydrograph separation (Taormina et al. (2015); Jain et al. (2004)).

Numerical methods all need one or several parameters, with or without hydrological meaning, which have to be valued before processing: time interval width, coefficients of a linear filter, formula of the transformation function, etc. Even though authors generally give advice about the possible values of these parameters, determining them involves adding new hypotheses for each catchment examined ([..¹⁵]Eckhardt (2008, 2005); Mei and Anagnostou (2015)). In particular, quantitative results of the filtering change with the value of the parameters. Although the shape of the hydrograph separation can be eye-pleasing, it is basically impossible to draw any conclusion from it.

1.4 Conceptual methods

In addition to chemico-physical and numerical methods, another way of separating hydrographs has been developed, starting from the idea that [..¹⁶]the slow parts of catchments can be represented as conceptual reservoirs, whose outflow is baseflow. Such an approach comes from the analysis of long recession curves and the inference of depletion laws, which rule streamflow during long, dry periods of low flows. By knowing the outflow law of the conceptual reservoir, assuming that its input is zero,

¹⁴removed: Duvert et al. (2015); Labat (2005)

¹⁵removed: Eckhardt (2008, 2005)

¹⁶removed: aquifers

it is possible to get the full recession curve until the next significant rainfall event (Coutagne (1948); Wittenberg (1994)). In practice, various types of reservoirs are implemented in this type of model: linear, quadratic and exponential are the most common (Bentura and Michel (1997); Michel et al. (2003)).

It is possible to calibrate such a model by fitting it on *long recession curves*, but the latter have to be defined, for instance, through a threshold on streamflow – considering that only low flows correspond to recessions – or on its derivative, possibly with a smoothing filter – such as moving average or sliding window minimum – in order to eliminate noise in the signal. Such a sampling of the hydrograph can be difficult to make without arbitrariness, either in the value of thresholds or in smoothing filters. Existing studies generally focus on a particular recession, for instance, along a drought in which streamflow is known to have been measured well (Wittenberg and Sivapalan (1999); Wittenberg (1994); Coutagne (1948)). It may be impossible to find such a drought to respect the zero-input hypothesis – in Western Europe, for instance, rainstorms at the end of summer often disrupt the low-flow signal.

To filter the whole hydrograph with this conceptual idea of baseflow, a backward filter was developed by Wittenberg (1999). The hydrograph is traced back with reservoir recession curves; the level of the reservoir increases as depletion is followed backward and reinitialized when the peak is reached. Some arbitrariness remains in the value of the reservoir parameter; moreover, whereas this method yields good-looking hydrograph separations with wide time steps, baseflow may not be smooth enough under flood peaks: a further smoothing is thus needed and constitutes, here again, a source of partiality.

1.5 Elements of comparison and coupling between methods

Although it is impossible to perform an absolute evaluation of a hydrograph separation method – since baseflow cannot be measured and compared with a simulated value – several comparative studies have challenged results from various methods. Chemicophysical and non-calibrated graphical/empirical algorithms – i.e., without parameters or whose parameters are determined *a priori* and do not vary between catchments – have given very different results ([..¹⁷]Kronholm and Capel (2015); Miller et al. (2015); Lott and Stewart (2016); Cartwright et al. (2014)). It is therefore difficult to use non-calibrated empirical or graphical hydrograph separation methods as general-purpose analysis tools.

To remedy this, several studies use parametric graphical/empirical methods and calibrate them with chemicophysical data (Saraiva Okello et al. (2018); Miller et al. (2015); Chapman (1999)). It allows one to extend the hydrograph separation on time periods where chemicophysical data are not available, or to perform temporal downscaling – when daily streamflow data or monthly tracer concentrations are available, for instance. Such calibrated parametric algorithms have given satisfying results. Chapman (1999) highlighted that adding parameters to a hydrograph separation algorithm does not necessarily improve performance, since the algorithm becomes harder to calibrate.

When performing a large-scale baseflow analysis over a territory, it is possible to extend calibrated parameters at gauged catchments to ungauged ones, through regionalization models. Singh et al. (2019) performed such a study over the entire territory of New Zealand. We decided to limit ourselves to gauged catchments for this work.

¹⁷removed: Kronholm and Capel (2015); Miller et al. (2015); Lott and Stewart (2016)

1.6 Synthesis and guidance for this work

[..¹⁸]

Most of the methods above rely on one or several parameters whose value has a strong influence on hydrograph separation; as it is impossible to calibrate this (or these) parameter(s) on the basis of a measurement, some physical hypotheses must be made on the desirable properties of baseflow, in relation to the memory of the catchment. Non-calibrated algorithms are not usable as general-purpose analysis tools and existing calibration procedures rely on the availability of chemico-physical data. In this work, we propose a calibration procedure of a conceptual hydrograph separation method that relies only on hydroclimatic data: streamflow, rainfall and temperature.

Frugality and objectivity do not only result in a small number of parameters. The choice of modelling options [..¹⁹] can also be a source of arbitrariness and useless complication. A modelling alternative can, moreover, be solved only through a personal choice of the modeller; one way to build a trustworthy framework is to make it of well-known and well-validated elements that have proven themselves relevant in lumped conceptual hydrology. Beyond the complexity of elements, there is the complexity of the modelling chain itself. The simpler the model is, the more readable and thus the less questionable it is; in this work, it was considered that a baseflow separation process should be much simpler than, for instance, a lumped conceptual model designed for flow simulation.

2 Proposed methodological framework

2.1 Digital filtering based on conceptual storage

In this paper, we postulate that the memory and smoothing effect of a catchment – which underpins the concept of baseflow – can be represented by a conceptual reservoir, whose outflow will represent the [..²⁰] delayed contribution to streamflow, which we will assimilate into baseflow. To be applied in practice, this postulate must be complemented by an answer to the two following questions: what should the input to the reservoir be? What should the relationship between the level of the reservoir and its outflow be?

2.1.1 Discharge as a proxy of recharge

The first question is: "What should refill the conceptual reservoir?"; i.e., "What recharges the [..²¹] catchment with water that will be baseflow afterwards?". The part of rainfall that does not contribute to surface runoff or to evaporation is generally named

¹⁸removed: Hydrograph separation into baseflow and quickflow relies on a set of hypotheses about the general behaviour of a river basin. Streamflow in a river is seen as having two origins, groundwater – the sum of contributions of various aquifers – and surface water, made of surface runoff and subsurface interflow, i.e., water that does not stay too long underground. Surface water response to climatic events is much quicker than that of groundwater and this speed difference is time-coherent all along the hydrograph. All this eliminates strongly karstic catchments, as the response of karst systems can be almost as quick as surface runoff.

¹⁹removed: is also

²⁰removed: groundwater

²¹removed: aquifer

recharge, as it is thought to feed groundwater storage. It is common to estimate the recharge function through a surface water budget model, which computes it from climatic information (rainfall, evapotranspiration, temperature, etc.) as it is done more or less complexly in common rainfall–runoff models or in soil–vegetation–atmosphere schemes. ^[..²²] A physical separation between hydrological processes would need such production modules^[..²³], but it is not the scope of our conceptual method; we do not try to estimate the groundwater recharge, but the fraction of water that will contribute to the delayed component of streamflow.

^[..²⁴] The general contribution of this *conceptual memory recharge* is supposed to be an increasing function of stream-flow: a flood event will lead to a more humid behaviour of the catchment months after, while a drought will decrease baseflow for several years. That is why we make the hypothesis that the best candidate for a proxy of this conceptual recharge is a linear fraction of total flow itself. It is ^[..²⁵] available without a further model or hypothesis. But using a linear fraction of total flow raises an issue: if x % of total flow is poured into the reservoir and baseflow – which represents on average y % of total flow – is taken out of the reservoir, then the water budget of the filtering process will only be balanced if $x = y$. The parametrization strategy takes this problem into account; it is presented in section 2.2.

2.1.2 Reservoir filtering

The filtering part of the method is a conceptual reservoir, whose inflow is a fraction of the total observed flow at the gauging station and the outflow is regarded as baseflow. The content of this reservoir is managed by an outflow function and a continuous differential equation: since data are obviously available as discrete time series with a time step Δt , it is necessary to discretize this equation to set the numerical filtering algorithm.

The ^[..²⁶] notations listed in table 1 will be used henceforth. All variables are expressed as intensive values – i.e., as depths in millimetres for precipitation, flows, reservoir storage – in order to avoid conversions with the basin area.

According to the definition of a reservoir, $V(t)$ is governed by the following system of equations:

$$\frac{dV}{dt} = \beta Q(t) - R(t) \quad (1)$$

$$R(t) = f(V(t), S) \quad (2)$$

f is the outflow function of the reservoir, with a parameter S – whose dimension depends on the formula of f . Many functions can be imagined, but the most common ones are the following (Brodie and Hosteletler (2005)):

²²removed: But using

²³removed: would introduce additional hypotheses and parameters inside the baseflow separation method. Instead, we looked for a proxy of recharge, which would represent at least a general yearly behaviour on a rainfall-dominated basin. During high-flow periods, recharge is high, whereas during low-flow periods, most or all the available water goes to evaporation, and thus recharge is low

²⁴removed: In this paper,

²⁵removed: quite well-correlated with the behaviour of recharge given above. In addition, it is

²⁶removed: following notations

- linear reservoir: $f(V(t), S) = \frac{V(t)}{S\Delta t}$;
- quadratic reservoir: $f(V(t), S) = \frac{V(t)^2}{S\Delta t}$;
- exponential reservoir: $f(V(t), S) = R_0 \exp\left(\frac{V(t)}{S}\right)$.

Linear reservoir has been widely used because of computation ease and direct analogy with linear filtering systems: the reservoir can be, for instance, assimilated into a low-pass electronic filter – the comparison with a capacitor and a resistor is quite straightforward. On the contrary, computations with the two other functions involve solving a non-linear differential equation, which removes the analogy with classical linear filters. Notwithstanding these practical considerations, groundwater discharge is fundamentally a non-linear phenomenon. Several authors (Coutagne (1948); Wittenberg (1994, 1999); Bentura and Michel (1997)) have argued that from a general-purpose point of view, a quadratic reservoir is the most adapted function. It has been derived from statistical studies of various catchments, together with theoretical studies of springs and unconfined aquifers. Therefore, a quadratic reservoir is chosen for this work.

In order to discretize the filter, we define discrete versions of continuous variables cited above. If $X(t)$ is continuous, for a discrete time step t , we define $X_t = X(t)$. To integrate equation 1, ^[.37] a direct integration scheme is performed: ^[.38] at each time step t , βQ_t is ^[.39] added to the reservoir at the beginning of the time interval $[t ; t + \Delta t]$ ^[.40] ^[.41] , and the differential equation is solved on this time interval.

Although it is used in most conceptual hydrological models, this way of integrating differential equations for a discrete hydrological model could be criticized (Fenicia et al. (2011); Ficchi (2017)) because the explicit Euler integration scheme is not stable for solving many ordinary differential equations. For instance, it can lead to diverging numerical solutions while analytical ones are supposed to be bounded. We find it acceptable to use this explicit integration scheme for the sake of simplicity, given that divergence of the result is controlled by the reservoir update detailed in section 2.1.3.

Thus, just before t $V(t^-) = V_t$ and just after t $V(t^+) = V_t + \beta Q_t \Delta t$. With a quadratic reservoir function, equation 1 can now be written on the time interval $[t^+ ; (t + \Delta t)^-]$:

$$-\frac{dV}{V^2} = \frac{dt}{S\Delta t} \quad (3)$$

After integration, the discrete recursive equation is:

$$V_{t+\Delta t} = \frac{V_t + \beta Q_t \Delta t}{1 + \frac{V_t + \beta Q_t \Delta t}{S}} \quad (4)$$

³⁷removed: the reverse process

³⁸removed: $Q(\tau)$ is simply built from measured Q_t through a sum of Dirac distributions. It simply means that

³⁹removed: poured into

⁴⁰removed: :

⁴¹removed: $Q(\tau) \simeq \sum_t Q_t \delta_t(\tau)$

R_t is the total outflow during the time interval $[t ; t + \Delta t]$. From another integration of equation 1, a balance equation is obtained: $V_{t+\Delta t} = V_t + \beta Q_t \Delta t - R_t \Delta t$. Therefore, using equation 4, the following formula for R_t is obtained:

$$R_t = \frac{1}{\Delta t} \frac{(V_t + \beta Q_t \Delta t)^2}{S + V_t + \beta Q_t \Delta t} \quad (5)$$

Note that these equations have a [\[..⁴²\]](#) conceptually coherent behaviour: V_t and R_t are always positive; without inflow, equation 4 becomes a depletion equation, which converges to zero; the reservoir empties itself all the faster as its level is high ; S acts as a capacity, i.e., at the end of a time step, the level of the reservoir is always lower than S .

2.1.3 Reservoir update

The filtering process detailed above raises an issue: baseflow is by definition a fraction of total flow; yet, equation 5 does not guarantee that R_t is lower than Q_t . Conceptual rainfall–runoff models classically rely on evaporation or on a leakage function to empty their reservoirs. Here, for the sake of simplicity, it was decided to perform a simple update of the reservoir level, when the outflow is greater than the measured flow. Although it may seem quite brutal, it must be seen as a readjustment of the model after a flood peak, in order to fit the observed flood recession. Since part of streamflow is only used as a proxy of recharge – and is therefore not the recharge itself – it [\[..⁴³\]](#) can only be an imperfect input data for the model and thus a correction process within the latter is not a surprise.

If R_t is computed as greater than Q_t , the level of the reservoir V_t needs to be updated so that $R_t = Q_t$, which leads through a simple balance of the reservoir to $V_t = V_{t+\Delta t}$. Equation 6 then gives the update function, by solving a quadratic polynomial equation:

$$V_t = \frac{1}{2} Q_t \Delta t \left(\sqrt{1 + \frac{4S}{Q_t \Delta t}} - 2\beta + 1 \right) \quad (6)$$

Here again, V_t is always non-negative and strictly lower than S . The formula above artificially creates a numerical exception when $Q_t = 0$, which must be taken into account in the implementation of the algorithm, with $V_t = 0$.

This update process takes water out of the reservoir when computed baseflow is too high; but do we not need to correct baseflow when it is too low? Indeed, quickflow is supposed to be zero during long rainless, dry periods. For the sake of simplicity, a straightforward hypothesis is added: baseflow must be equal to total flow at least once in a hydrological year, when measured streamflow reaches its yearly minimum. The value of the latter can be affected by measurement errors, but it is hard to take it into account in a general-purpose analysis tool: the structure of the error is determined by the idiosyncrasies of each catchment. Moreover, the two ways of updating the reservoir helps the model to forget about previous errors; therefore, for the sake of simplicity, we prefer not to add another hypothesis about the low-flow measurement uncertainty.

⁴²removed: physically

⁴³removed: is an imperfect and conceptually questionable

A test study is performed on a set of catchments in continental France: thus, the low-flow hydrological year is taken from the 1st of April to the 31st of March, as streamflow minima do not generally occur during spring. The Q_t time series is then sliced into hydrological years, and for each of them, a minimum value and its index are computed. If the series is n hydrological years long, it creates a set of n points where reservoir level is updated through equation 6, so that $R_t = Q_t$.

- 5 This second update process adds water to the reservoir; it is thus possible to balance the updates of the reservoir and, thereby, to balance the total water budget of the filtering process. If \bar{Q} and \bar{R} are the means of time variables Q_t and R_t , water budget is given by equation 7.

$$\beta \bar{Q} = \bar{R} = BFI \times \bar{Q} \quad (7)$$

BFI is *baseflow index*, namely, the long-term ratio of the computed baseflow to total measured streamflow – i.e., $BFI = \frac{\bar{R}}{\bar{Q}}$.

- 10 Equation 7 gives a simple parametrization constraint to ensure a balanced water budget: $\beta = BFI$.

2.1.4 [..⁴⁴]

The yearly minimum update may look brutal and arbitrary, but tests have shown that it is necessary to avoid issues in the parametrization strategy: removing it adds a third degree of freedom in calibrating the model – the value of β , which is not constrained to be equal to BFI – which leads to optimisation problems while calibrating the algorithm.

15 2.1.4 Initialisation

Our algorithm does not need a long warm-up period, as [..⁴⁵] required by rainfall–runoff models. Since the algorithm presented above contains only one state and involves a regular update with observed data, this update erases the memory of the past states of the model. Therefore, a simple initialization approach is possible. Several methods were tested and the best compromise between simplicity and robustness was adopted. The reservoir level is initialized through equation 6, using mean flow over a small time period – five time steps – at the beginning of the flow time series. To avoid any overestimation of baseflow at the beginning of the hydrograph, computations were started far from any flood events: the 1st of August is a convenient date for continental mainland France since no French river has major high-flow episodes in mid-summer.

2.1.5 Synthesis of the algorithm


- Finally, the filtering algorithm can be summarised with the pseudo-code detailed in algorithm 1. $f_{up}(Q_t)$ is the update function of equation 6, $f_{rec}(V_t, Q_t)$ is the recursion function of equation 4, n is the number of time steps and YM is the set of indexes of yearly minima. Figure 1 synthesises the principle of the algorithm.

⁴⁴removed: Initialization

⁴⁵removed: it exists for

Algorithm 1 Reservoir filtering algorithm

Initialization $V_1 \leftarrow f_{up}(\text{MEAN}(Q_i, i \in [1; 5]))$ **Recursion loop****for** $i = 0$ to n **do** $V_{i+1} \leftarrow f_{rec}(V_i, Q_i)$ $[..^{46}] R_i \leftarrow \beta Q_i + \Delta t(V_i - V_{i+1})$ **if** $R_i > Q_i$ or $i \in YM$ **then** $R_i \leftarrow Q_i$ $V_i \leftarrow f_{up}(Q_i)$ $V_{i+1} \leftarrow V_i$ **end if****end for**

**Figure 1.** Synthesis of the filtering algorithm

2.2 Parametrization strategy

As stated above, the difficulty of parametrization comes from the fact that baseflow cannot be measured. In the absence of measurement, we need to make an hypothesis concerning a desirable property of the computed baseflow, in order to be able to look for the parameter set that will best respect this property. Since baseflow accounts for the slow component of total flow,

coming out from the storage parts of a river basin, we make the following hypothesis: baseflow should be correlated with past climatic events that have filled or emptied this storage ; and since it is supposed to be slow, it should be correlated with events that happened quite a long time ago. The calibration criterion has to be a simple quantification of this idea, which corresponds to the concept of *recharge* stated earlier: a proxy of past recharge must be found.

- 5 The filtering algorithm detailed above depends on two parameters: capacity S of the reservoir and scaling factor β . Yet, with the water balance condition given by equation 7, it is possible to remove one degree of freedom: for a given value of S , function $\beta \mapsto BFI(S, \beta) - \beta$ is injective; therefore, there is a unique value of β that satisfies $BFI(S, \beta) = \beta$ and the $\beta(S)$ function can be identified.

- 10 After eliminating one degree of freedom, the correlation hypothesis stated above can be converted into a criterion: it computes Pearson's correlation between the computed baseflow time series – which depends on the reservoir's parameter, S – and cumulated effective rainfall on the τ days before each time step. The first $\tau - 1$ values of the baseflow time series thus do not influence the criterion, since the first $\tau - 1$ values of the cumulated effective rainfall time series are missing values and, therefore, they are eliminated when computing Pearson's correlation; this limits the effect of model initialization. If $P_{eff,t}$ is the daily effective rainfall value on day t , the criterion is written:

$$15 \quad C(S, \tau) = \text{Corr} \left(R_t(S), \sum_{u=t-\tau+1}^t P_{eff,u} \right) \quad (8)$$

This correlation must be maximized to yield two pieces of information: the optimal value S_{opt} of the capacity of the [\[..⁴⁷\]](#)reservoir, which gives a hydrograph separation; a [\[..⁴⁸\]](#)conceptual response time τ_{opt} of the [\[..⁴⁹\]](#)catchment to hydroclimatic events, which can be compared with other pieces of knowledge about its behaviour, in order to assess the separation method's relevance.

- 20 As far as the optimization process is concerned, it is necessary to define search intervals for S and τ . For S , values lower than 1 mm were not observed during tests and led to computation issues, thus the lower bound can be set at 1 mm; on the other side of the search interval, values around 10^6 mm – 1 km – were found during tests, without leading to incongruities in baseflow separation; therefore, it is suggested to set the upper bound to $2 \cdot 10^6$ mm. For τ , typical values are between 3 months and 1 year: the search range is then set to $[5; 1825]$ days. Note that during tests, τ optimal values were easier to find than S values.

Effective rainfall was computed with the Turc–Mezentsev formula (Turc (1953); Mezentsev (1955)), with a quadratic harmonic mean between potential evaporation (PET) and rainfall, i.e.:

$$P_{eff} = P_{tot} \left(1 - \frac{1}{\sqrt{1 + \left(\frac{P_{tot}}{PET} \right)^2}} \right)$$

⁴⁷removed: conceptual

⁴⁸removed: time response

⁴⁹removed: river basin

P_{tot} is daily total rainfall and PET is daily potential evapotranspiration, computed with Oudin’s formula (Oudin (2004); Oudin et al. (2005)): effective rainfall is thus computed at a daily time step and aggregated to get the criterion defined by equation 8. By way of comparison, alternative ways of computation were tried: Penman–Monteith formula for PET (Monteith (1965)) and simple screening of rain by PET for effective rainfall – i.e., $P_{eff} = \text{Max}(P_{tot} - PET, 0)$. No major difference was found in the results.

Therefore, we found an effective parametrization strategy for choosing the three used parameters β , S and τ . β is first linked to S through the budget condition given by equation 7, which removes one degree of freedom; then, the two remaining parameters S and τ are chosen by optimizing the correlation criterion given by equation 8.

2.3 Catchment dataset

Several hydrographic regions of mainland France are influenced by large aquifers, which bear memory of past climatic events and have a significant contribution to river flow. In the Paris basin, the Chalk aquifer – composed of Late Cretaceous formations – has a significant connection with many rivers in the Seine and the Somme basins, which notably led to major groundwater-induced floods after the extremely wet years of 1999 and 2000 (Pinault et al. (2005); Habets et al. (2010)). The Loire basin is linked to the Beauce aquifer – mostly made of tertiary layers – whose situation under a large agricultural plain induces water management issues that affect Loire low-flows. The international Rhineland aquifer, part of which extends to the Alsace, also plays a major role in the hydrology of the Rhine.

Tests were performed on a set of 1,664 catchments that were selected on the basis of diversity of area, climate, hydrological regime and completeness of the time series in the period 1967–2018. Streamflow data are from the national database Banque Hydro (SCHAPI (2015); Leleu et al. (2014)), where measurements regarded as unreliable were converted into missing values. Climatic data are from Safran reanalysis (Vidal et al. (2010)), developed by Météo France and aggregated for each catchment, to get a lumped climatic series of rainfall and PET. The combination of the Safran and Banque Hydro data is stored in the HydroSafran database, maintained and hosted by Irstea (Delaigue et al. (2019)).

Gaps in the streamflow time series were filled using simulated flows from the daily lumped rainfall–runoff model GR4J (Perrin (2002); Perrin et al. (2003)), calibrated on the whole period 1968–2018 – we make the hypothesis that hydrological characteristics of catchments are stationary all along this period. The chosen catchments have more than 20 complete years – a hydrological year is regarded as complete when there is no gap longer than a week and the total proportion of missing values is lower than 5 % – and the filling simulation model GR4J has a good performance, with a Nash–Sutcliffe criterion higher than 0.7. All computations were performed with R and airGR package for specific hydrological processing (Coron et al. (2017, 2019)).

Tables 2 and 3 show some characteristics of the catchment dataset: it is representative of the climatic and landscape diversity in mainland France. We chose basins with a large range in size, from very small (less than 2 km²) to very large (117,000 km²). A quick geological analysis of the 1,664 catchments was also performed based on the national hydrogeological map by Margat (1980); it highlighted that 1,310 catchments are not very likely to be influenced by aquifers, since they are on impermeable formations, such as igneous or metamorphic rocks or clay; 122 catchments have more than 90 % of their surface




Figure 2. Map of the catchments in the dataset. Dots represent the outlet of each [\[52\]](#) catchment, with different colours according to the type of aquifer influence used in figure 8.

on sedimentary formations that are likely to carry large aquifers; and 232 catchments have a mixed configuration. Figure 2 shows the geographic repartition of the catchment set.

For each catchment of the dataset, a two-variables grid search was performed to find the optimum of the criterion. Hydrograph separation was then computed with the parameters obtained.

3.1 Criterion surface plots

5




Figure 3. Surface plot of optimization criterion for the Vair river in Soumousse-sous-Saint-Élophé. Red cross indicates the numerical optimum.

10




Figure 4. Surface plot of optimization criterion for the Petit Thérain river in Saint-Omer-en-Chaussée. Red cross indicates the numerical optimum.

with other local maxima. In agreement with geologic and climatic configurations, the optimized BFI (0.11) and τ (170 days) are low; the optimal value of S is 4.42 m. The Petit Thérain river in Saint-Omer-en-Chaussée is heavily influenced by the large chalk aquifer in the Paris basin: its BFI and response time should be high. The criterion optimization is more equivocal here: there is a large plateau in the middle of the criterion map – around a correlation of 0.8 – which gives significantly different values of BFI – from 0.78 to 0.86 – and τ – from 700 to 1,400 days. However, a hill in the middle of the shelf indicates the optimal point, where the correlation is 0.86, is at BFI = 0.783 and τ = 1,015 days. Pseudo-periodical oscillations can be seen in parallel to the τ axis; they are consequences of the annual hydroclimatic cycle.

3.2 Hydrograph separations obtained

Figures 5, 6 and 7 show three examples of hydrograph separations obtained among the test set of catchments, with the respective BFI values of 0.11, 0.30 and 0.78. Figure 5 shows the example for the Vair river in Soulosse-sous-Saint-Élophé, a small catchment in the Meuse basin, with a small BFI. It lies on poorly permeable sandstone, marl and clay, with no connection to a

large aquifer. During dry periods, baseflow is almost determined by a local minimum on a sliding window with a length of 1 year, whereas it rises a little during wet periods, as seen during the 2000–2001 winter period.




Figure 5. Hydrograph separation of the Vair river in Soulosse-sous-Saint-Élophé – 1995–2005.




Figure 6. Hydrograph separation of the Virène river in Vire-Normandie – 1995–2005.




Figure 7. Hydrograph separation of the Petit Thérain river in Saint-Omer-en-Chaussée – 1995–2005.

Figure 6 displays a medium BFI case: the Virène river in Vire-Normandie is a granodioritic catchment located in the north-eastern part of the Armorican Massif, with a moderate aquifer influence. Baseflow fits the total flow during low-flow periods and rises during high flows, with a jagged shape made of asymmetric peaks: decreasing slopes fit the total flow – thanks to the

update procedure – whereas increasing slopes are gentler, driven by the smoothing effect of the reservoir. This creates a delay of baseflow with respect to total flow that resembles an aquifer's behaviour, with an outflow much higher just after a flood event than before. This baseflow recession resembles what would be obtained with a graphical separation method.

Figure 7 corresponds to a high BFI case: the majority of flow is identified as baseflow by the model. The Petit Thérain river in Saint-Omer-en-Chaussée is a small catchment fed by the well-known chalk aquifer of the Paris basin. Therefore, it is not surprising to find a BFI close to 1. An ensemble view to the hydrograph shows that long oscillations seem to influence total flow, with a period greater than one decade; it is well taken into account by baseflow separation.

Among the dataset of 1,664 catchments, optimisation of parameter S failed for three catchments [..⁵³]only; there, the correlation criterion kept increasing with the value of S , without the possibility of reaching an optimal value. The failing catchments are small basins where most of the water comes from glaciers in the Alps: effective rainfall – as computed by the Turc–Mezentsev formula – is thus not really correlated with baseflow and the quadratic reservoir fails to reproduce the particular memory effect of a glacier.

3.3 Synthesis and geological interpretation

Table 4 presents a summary of the parameters identified by calibrating the separation algorithm on the 1,664 catchments. First, the criterion values obtained are quite high for Pearson correlations, with all values greater than 0.66 and half of the catchments above 0.80; baseflow is quite well-correlated with cumulated effective rainfall. Values of the reservoir parameter S are huge, if we compare them with annual rainfall or with usual reservoir capacities for commonly used hydrological models; it is thus difficult to give them a physical meaning. The range of BFI obtained is large, between 0.01 and 0.90, with a median of 0.16. The chosen catchments represent a wide variety of situations that can be taken into account by the separation algorithm. Finally, τ also covers a wide range of values, between 5 and 1,790 days with half of the catchments between 165 and 200 days.

Concerning correlations between these results, we found that no clear relationship can be highlighted between themselves and with hydroclimatic values given in table 3[..⁵⁴]. We found no solution to reduce the number of parameters by inferring one from the other. However, a positive Pearson correlation of 0.42 between BFI and τ was found: catchments with higher baseflow have a larger response time, which is consistent with the conceptual definition of baseflow; the more important is the slow component of streamflow, the slower is the average response of the system.

Figure 8 shows the distribution of BFI and τ values for each hydrogeological class of basin. The mean BFI is significantly larger for *aquifer-driven* basins than for other classes, but the ranges of BFI are not significantly separated: even *aquifer-driven* catchments can have low BFIs. However, those that are *not aquifer-driven* are limited to BFI values under 0.4. All this agrees with the fact that baseflow is highly connected to the outflow of aquifers, whose contribution to total flow is much higher in catchments connected to large underground reservoirs. There are also catchments whose geological configuration suggests an *aquifer-driven* regime, whereas the BFI found is low; most of them are located above the Vosges sandstone aquifer which, although a crucial resource for water supply in this region, is not directly connected to piedmont rivers. As far as τ is concerned,

⁵³removed: onl; ;

⁵⁴removed: , except for a positive Pearson correlation between BFI and τ of 0.42: we




Figure 8. Boxplots of BFI values and τ according to the hydrogeological class of basins, i.e., whether they are likely to be under the influence of a significant aquifer. Central box accounts for the interval between first and third quartile; the segment in the middle is the median; whiskers represent 95 % confidence interval.

most catchments are around 200 days, with a larger mean value for aquifer-driven catchments. It is notable that *mixed* or *not aquifer-driven* basins are limited to values of τ less than 300 days, whereas the range of *aquifer-driven* catchments' values extends to more than 1,000 days: this confirms the hypothesis that long memory is caused by the influence of an aquifer – even if the presence of the latter does not guarantee a long-memory behaviour.

- 5 Figure 9 shows geographic variations of the values of τ and BFI obtained. BFI values are coherent with the geological context: granitic regions like the Armorican massif or Massif Central have low values of BFI; high values are observed in the Alsace plain, in the sandy Landes of Gascony and particularly in the chalky zones of the Paris basin and the Somme basin. The rivers of these regions are known to be particularly under the influence of major aquifers that bear the memory of climatic events. The south-east area of France has medium BFI values, which is surprising since most of this region is composed of
- 10 mountainous areas without any large aquifer; however, particularly smooths hydrographs can be explained by the presence of many hydroelectric dams and natural lakes – the first of which is the Lemman lake on the Rhone river – in this region, which have a significant influence on streamflow. Values of τ are more difficult to interpret: even though the chalk aquifer is clearly visible around the Paris region, high values of τ can be observed in the Alps, too, and medium values in the Massif Central. Here again, it can be explained by the presence of natural and artificial lakes that bear memory of past hydroclimatic events.




Figure 9. Maps of resulting values of parameters on the catchment dataset. Left: BFI; right: τ .

3.4 Split-sample test as a stability assessment

In order to evaluate the stability of the proposed algorithm and of its calibration procedure, a split-sample test was performed. The time extent of the time series of the dataset – 1958-08-01 to 2018-07-31 – was divided into two equal parts P_1 (1958-08-01 to 1988-07-31) and P_2 (1988-08-01 to 2018-07-31). The algorithm was then calibrated separately for each basin on these two periods and the values obtained for BFI and τ were then compared.

Figure 10 shows the graphical comparison of BFI and τ values obtained; table 5 displays two ways of statistical assessment that were performed after the split sample-test: correlation between values of BFI and τ and non-parametric Kolmogorov–Smirnov test (Smirnov (1939)), in order to check the equality of distributions, i.e., the bias between series of values. The BFI shows a good graphical consistency, with high Pearson correlation values – higher than 0.91 – but the p-values of the Kolmogorov–Smirnov test are under 0.05 for P_1 ; there is a constant bias between the BFI values computed for P_1 and those computed for the whole period. The scatterplot shows a good correlation between the BFI values computed for P_1 and P_2 . As for τ , it is less consistent than the BFI: the scatterplot shows some outliers that are far from the diagonal, which explains the lower Pearson correlation values, between 0.53 and 0.84. Here again, values computed for P_1 are further away from those computed for the whole period than those computed for P_2 . Despite these imperfections, this split-sample test can be regarded as successful, especially for a general-purpose analysis tool on a large set of catchments.




Figure 10. Results of split-sample test for BFI – on the left – and τ – on the right. Values obtained for P_1 and P_2 are compared.

3.5 Comparison with a reference method

The BFI obtained was compared with the one resulting from a simple graphical method, based on local minima on a sliding interval of 5 days. It is detailed in Gustard and Demuth (2008). Figure 11 shows the scatterplot of the two computed BFIs. Gustard’s method gives higher indexes than the conceptual filtering algorithm, but the trend remains, which is confirmed by the high Spearman correlation – 0.819. A high-BFI catchment according to Gustard’s method will also get a high BFI from the conceptual filtering and so it is for low values too. The difference between the results of the two methods can be explained by the time scales: the width of the sliding minimum window in Gustard’s method is 5 days, whereas we get much larger values of τ . Graphical quickflow is much quicker than the one resulting from the conceptual algorithm.

4 Conclusion

4.1 Synthesis

The hydrograph separation algorithm and its calibration procedure presented in this work gave credible results for a large set of test catchments. The algorithm has suitable characteristics for such a model: (i) frugality – only two parameters to calibrate; (ii) objectivity – the procedure is not supposed to require any intervention or interpretation from the user; (iii) generalization ability – the procedure succeeded on the whole dataset, with a unique value found for the reservoir parameter; (iv) repeatability




Figure 11. Comparison between BFI obtained with the conceptual algorithm and a reference graphical method.

– as assessed by the split-sample test performed on the test dataset. The analysis of the results in the light of the geological characteristics of catchments shows that the model is able to acknowledge the importance of groundwater flow in total flow generation without prior knowledge about the studied catchment, which is a significant step forward with respect to other non-tracer-based baseflow separation methods.

- 5 A conceptual and empirical baseflow separation method is not intended to replace precise estimation of the elements of water balance at the scale of a given catchment, especially when infield physical data are available; neither can it precisely highlight particular hydrological processes occurring at the catchment or under-catchment scale, such as karstic non-linear transfers or human regulation of rivers. Yet, in the absence of infield data, i.e., outside of specially instrumented catchments, conceptual baseflow separation is a useful tool for obtaining meaningful insights about the role of groundwater and aquifers inside a
- 10 catchment. Even if the present method has limitations – which we summarize below – it could be applied as an objective, general-purpose, automated analysis tool for information on a large set of flow series. Beyond the inherent characteristics of the presented method, the results show that the hydrogeological processes of a catchment are deeply engraved in streamflow.

4.2 Limitations

- We used an optimization procedure set, which searches for values of τ less than 5 years. It showed great convergence ability,
- 15 i.e., an optimal point was found for every catchment of the test dataset. Yet, a mere glance at the Petit Thérain river hydrograph

(figure 7) shows that its response time may be greater than 5 years, with long dynamics at the scale of climatic cycles. All this highlights the fact that the simplistic distinction between *baseflow* and *quickflow* hides the diversity of time scales and travel times among processes that influence the total flow of a river. Anyhow, the optimization criterion is not indisputably univocal for a significant number of catchments; more work is needed to conceive a better optimization criterion for the parametrization strategy of the algorithm.

The split-sample test is a way to check temporal consistency of the baseflow separation method; the one performed on the test dataset can be considered as successful, at least concerning BFI results. Nevertheless, the spatial coherence of the method was not checked; it could be tested, for instance, with propagation of baseflow from sub-basins of a larger catchment, in order to test whether the sum of tributary baseflows makes up total baseflow. Our optimization procedure does not take into account regional aspects while calibrating the model, although it could be a way of introducing objective prior knowledge in the method. On a sample of catchments where chemico-physical data is available, a comparison with tracer-based separation procedures would be a reliable way to validate the presented method.

Our algorithm is only intended for catchments that are not affected by human activity – pumping, regulation by dams, canals – which excludes most large rivers in Europe. Finally, the generalization capacity of the method has only been demonstrated in mainland France hydroclimatic conditions: even if the spatial extent of the present work has a substantial diversity of climates, further study with a wider range of climates and geologies is needed to validate the method.

4.3 Implementation

An R package named *baseflow* (Pelletier et al. (2020)) is provided to ensure the reproducibility of our results. It implements the algorithm presented in this paper with a high-performance computing core written in Rust. The example data taken from airGR are linked in the examples. The package is being released on CRAN (Comprehensive R Archive Network) and its documentation is available as supplementary material.

Competing interests. The authors declare that there are no competing interests.

Acknowledgements. Data for this work were provided by Météo France (climatic data) and the hydrometric services of the French government (flow data). We would like to thank Pierre NICOLLE and Benoît GENOT for the database creation and maintenance and José TUNQUI NEIRA for his help in the literature review. We would also like to extend our warmest thanks to Charles PERRIN and Lionel BERTHET for their remarks and suggestions during the writing process. Last but not least, computing codes could not not have been developed without the precious expertise and availability of Olivier DELAIGUE (Irstea Antony) and Denis MERIGOUX (INRIA Paris).

References

- Bentura, P. L. F. and Michel, C.: Flood routing in a wide channel with a quadratic lag-and-route method, *Hydrological Sciences Journal*, 42, 169–189, <https://doi.org/10.1080/02626669709492018>, 1997.
- Beven, K.: Hydrograph separation?, in: *Proc.BHS Third National Hydrology Symposium*, pp. 3.2–3.8, Institute of hydrology, 1991.
- 5 Boussinesq, J.: Recherches théoriques sur l’écoulement des nappes d’eau infiltrées dans le sol et sur le débit des sources, *Journal de Mathématiques Pures et Appliquées*, 10, 5–78, <https://eudml.org/doc/235283>, 1904.
- Brodie, R. and Hosteletter, S.: A review of techniques for analysing baseflow from stream hydrographs, <https://pdfs.semanticscholar.org/53e7/0d6591eb10f468d9c27929fb9945f3f29f00.pdf>, 2005.
- Cartwright, I. and Morgenstern, U.: Using tritium and other geochemical tracers to address the “old water paradox” in headwater catchments, *Journal of Hydrology*, 563, 13–21, <https://doi.org/10.1016/j.jhydrol.2018.05.060>, 2018.
- 10 Cartwright, I., Gilfedder, B., and Hofmann, H.: Contrasts between estimates of baseflow help discern multiple sources of water contributing to rivers, *Hydrology and Earth System Sciences*, 18, 15–30, <https://doi.org/10.5194/hess-18-15-2014>, 2014.
- Chapman, T.: A comparison of algorithms for stream flow recession and baseflow separation, *Hydrological Processes*, 13, 701–714, [https://doi.org/10.1002/\(SICI\)1099-1085\(19990415\)13:5<701::AID-HYP774>3.0.CO;2-2](https://doi.org/10.1002/(SICI)1099-1085(19990415)13:5<701::AID-HYP774>3.0.CO;2-2), 1999.
- 15 Chow, V. T.: *Runoff*, in: *Handbook of applied hydrology*, pp. 1–54, McGraw-Hill, 1964.
- Coron, L., Thirel, G., Delaigue, O., Perrin, C., and Andréassian, V.: The suite of lumped GR hydrological models in an R package, *Environmental Modelling and Software*, 94, 166–171, <https://doi.org/10.1016/j.envsoft.2017.05.002>, 2017.
- Coron, L., Delaigue, O., Thirel, G., Perrin, C., and Michel, C.: airGR: Suite of GR Hydrological Models for Precipitation-Runoff Modelling, <https://CRAN.R-project.org/package=airGR>, r package version 1.3.2.23, 2019.
- 20 Costelloe, J. F., Peterson, T. J., Halbert, K., Western, A. W., and McDonnell, J. J.: Groundwater surface mapping informs sources of catchment baseflow, *Hydrology and Earth System Sciences*, 19, 1599–1613, <https://doi.org/10.5194/hess-19-1599-2015>, 2015.
- Coutagne, A.: Les variations de débit en période non influencée par les précipitations - Le débit d’infiltration (corrélations fluviales internes) - 2e partie, *La Houille Blanche*, pp. 416–436, <https://doi.org/10.1051/lhb/1948053>, 1948.
- Delaigue, O., Génot, B., Bourgin, P.-Y., Brigode, P., and Lebecherel, L.: Base de données hydroclimatique à l’échelle de la France, Tech. rep., Irstea, UR HYCAR, Equipe Hydrologie des bassins versants, Antony, <https://webgr.irstea.fr/activites/base-de-donnees/>, 2019.
- 25 Duvert, C., Jourde, H., Raiber, M., and Cox, M. E.: Correlation and spectral analyses to assess the response of a shallow aquifer to low and high frequency rainfall fluctuations, *Journal of Hydrology*, 527, 894–907, <https://doi.org/10.1016/j.jhydrol.2015.05.054>, 2015.
- Eckhardt, K.: How to construct recursive digital filters for baseflow separation, *Hydrological Processes*, 19, 507–515, <https://doi.org/10.1002/hyp.5675>, 2005.
- 30 Eckhardt, K.: A comparison of baseflow indices, which were calculated with seven different baseflow separation methods, *Journal of Hydrology*, 352, 168–173, <https://doi.org/10.1016/j.jhydrol.2008.01.005>, 2008.
- Fenicia, F., Kavetski, D., and Savenije, H. H. G.: Elements of a flexible approach for conceptual hydrological modeling: 1. Motivation and theoretical development, *Water Resources Research*, 47, <https://doi.org/10.1029/2010WR010174>, 2011.
- Ficchi, A.: An adaptative hydrological model for multiple time-steps: diagnostics and improvements based of luxes consistency, Ph.D. thesis, Université Pierre et Marie Curie, 2017.
- 35 Gonzales, A. L., Nonner, J., Heijkers, J., and Uhlenbrook, S.: Comparison of different base flow separation methods in a lowland catchment, *Hydrology and Earth System Sciences*, 13, 2055–2068, <https://doi.org/10.5194/hess-13-2055-2009>, 2009.

- Gustard, A. and Demuth, S.: Manual on Low-Flow Estimation and Prediction, Tech. Rep. 50, World Meteorological Organization, 2008.
- Habets, F., Gascoin, S., Korkmaz, S., Thiéry, D., Zribi, M., Amraoui, N., Carli, M., Ducharne, A., Leblois, E., Ledoux, E., Martin, E., Noilhan, J., Ottlé, C., and Viennot, P.: Multi-model comparison of a major flood in the groundwater-fed basin of the Somme River (France), *Hydrology and Earth System Sciences*, 14, 99–117, <https://doi.org/10.5194/hess-14-99-2010>, 2010.
- 5 Hewlett, J. D. and Hibbert, A. R.: Factors affecting the response of small watersheds to precipitation in humid areas, *Forest hydrology*, 1, 275–290, 1967.
- Horton, R. E.: The Rôle of infiltration in the hydrologic cycle, *Eos, Transactions American Geophysical Union*, 14, 446–460, <https://doi.org/10.1029/TR014i001p00446>, 1933.
- Jain, A., Sudheer, K. P., and Srinivasulu, S.: Identification of physical processes inherent in artificial neural network rainfall runoff models, *Hydrological Processes*, 18, 571–581, <https://doi.org/10.1002/hyp.5502>, 2004.
- 10 Kirchner, J. W.: A double paradox in catchment hydrology and geochemistry, *Hydrological Processes*, 17, 871–874, <https://doi.org/10.1002/hyp.5108>, 2003.
- Kirchner, J. W.: Quantifying new water fractions and transit time distributions using ensemble hydrograph separation: theory and benchmark tests, *Hydrology and Earth System Sciences*, 23, 303–349, <https://doi.org/10.5194/hess-23-303-2019>, 2019.
- 15 Klemeš, V.: Dilettantism in hydrology: Transition or destiny?, *Water Resources Research*, 22, 177S–188S, <https://doi.org/10.1029/WR022i09Sp0177S>, 1986.
- Kronholm, S. C. and Capel, P. D.: A comparison of high-resolution specific conductance-based end-member mixing analysis and a graphical method for baseflow separation of four streams in hydrologically challenging agricultural watersheds, *Hydrological Processes*, 29, 2521–2533, <https://doi.org/10.1002/hyp.10378>, 2015.
- 20 Labat, D.: Recent advances in wavelet analyses: Part 1. A review of concepts, *Journal of Hydrology*, 314, 275–288, <https://doi.org/10.1016/j.jhydrol.2005.04.003>, 2005.
- Leleu, I., Tonnelier, I., Puechberty, R., Gouin, P., Viquendi, I., Cobos, L., Foray, A., Baillon, M., and Ndimi, P.-O.: La refonte du système d'information national pour la gestion et la mise à disposition des données hydrométriques, *La Houille Blanche*, pp. 25–32, <https://doi.org/10.1051/lhb/2014004>, 2014.
- 25 Linsley, R. K., Kohler, M. A., and Paulhus, J. L. H.: *Hydrology for engineers*, McGraw-Hill, New York, 2nd ed edn., <https://trove.nla.gov.au/work/13510461>, 1975.
- Lott, D. A. and Stewart, M. T.: Base flow separation: A comparison of analytical and mass balance methods, *Journal of Hydrology*, 535, 525–533, <https://doi.org/10.1016/j.jhydrol.2016.01.063>, 2016.
- Maillet: *Essais d'hydraulique souterraine & fluviale*, A. Hermann, <http://archive.org/details/essaisdhydrauli00mailgoog>, 1905.
- 30 Margat, J.: *Carte hydrogéologique de la France : systèmes aquifères*, en coul. 88 x 100 cm, pliée sous couv. 26 x 17 cm. notice (26 p. ; 24 cm)., 1980.
- McDonnell, J. J. and Beven, K.: Debates—The future of hydrological sciences: A (common) path forward? A call to action aimed at understanding velocities, celerities and residence time distributions of the headwater hydrograph, *Water Resources Research*, 50, 5342–5350, <https://doi.org/10.1002/2013WR015141>, 2014.
- 35 Mei, Y. and Anagnostou, E. N.: A hydrograph separation method based on information from rainfall and runoff records, *Journal of Hydrology*, 523, 636 – 649, <https://doi.org/10.1016/j.jhydrol.2015.01.083>, 2015.
- Mezentsev, V.: Back to the computation of total evaporation (Ещё раз о расчете среднего суммарного испарения), *Meteorologia i Gidrologia - Метеорология и Гидрология*, 5, 24–26, 1955.

- Michel, C., Perrin, C., and Andréassian, V.: The exponential store: a correct formulation for rainfall—runoff modelling, *Hydrological Sciences Journal*, 48, 109–124, <https://doi.org/10.1623/hysj.48.1.109.43484>, <http://www.tandfonline.com/doi/abs/10.1623/hysj.48.1.109.43484>, 2003.
- Miller, M. P., Johnson, H. M., Susong, D. D., and Wolock, D. M.: A new approach for continuous estimation of baseflow using discrete water quality data: Method description and comparison with baseflow estimates from two existing approaches, *Journal of Hydrology*, 522, 203–210, <https://doi.org/10.1016/j.jhydrol.2014.12.039>, 2015.
- Monteith, J. L.: Evaporation and environment., *Symposia of the Society for Experimental Biology*, 19, 205–34, 1965.
- Oudin, L.: Recherche d'un modèle d'évapotranspiration potentielle pertinent comme entrée d'un modèle pluie-débit global, PhD thesis, ENGREF (AgroParisTech), <https://pastel.archives-ouvertes.fr/pastel-00000931/document>, 2004.
- 10 Oudin, L., Hervieu, F., Michel, C., Perrin, C., Andréassian, V., Anctil, F., and Loumagne, C.: Which potential evapotranspiration input for a lumped rainfall–runoff model?: Part 2—Towards a simple and efficient potential evapotranspiration model for rainfall–runoff modelling, *Journal of Hydrology*, 303, 290–306, <https://doi.org/10.1016/j.jhydrol.2004.08.026>, 2005.
- Pelletier, A., Andréassian, V., and Delaigue, O.: baseflow: Computes Hydrograph Separation, <https://doi.org/10.15454/Z9IK5N>, <https://cran.r-project.org/package=baseflow>, r package version 0.11.4, 2020.
- 15 Perrin, C.: Vers une amélioration d'un modèle global pluie-débit au travers d'une approche comparative, *La Houille Blanche*, pp. 84–91, <https://doi.org/10.1051/lhb/2002089>, 2002.
- Perrin, C., Michel, C., and Andréassian, V.: Improvement of a parsimonious model for streamflow simulation, *Journal of Hydrology*, 279, 275–289, [https://doi.org/10.1016/S0022-1694\(03\)00225-7](https://doi.org/10.1016/S0022-1694(03)00225-7), 2003.
- Pinault, J.-L., Amraoui, N., and Golaz, C.: Groundwater-induced flooding in macropore-dominated hydrological system in the context of climate changes, *Water Resources Research*, 41, <https://doi.org/10.1029/2004WR003169>, 2005.
- 20 Pinder, G. F. and Jones, J. F.: Determination of the ground-water component of peak discharge from the chemistry of total runoff, *Water Resources Research*, 5, 438–445, <https://doi.org/10.1029/WR005i002p00438>, 1969.
- Réménieras, G.: *L'Hydrologie de l'ingénieur*, Eyrolles, 1965.
- Roche, M.: *Hydrologie de surface*, Office de la recherche scientifique et technique outre-mer, 1963.
- 25 Romanowicz, R.: An application of a log-transformed low-flow (LTLF) model to baseflow separation, *Hydrological Sciences Journal*, 55, 952–964, <https://doi.org/10.1080/02626667.2010.505172>, 2010.
- Saraiva Okello, A. M. L., Uhlenbrook, S., Jewitt, G. P., Masih, I., Riddell, E. S., and Van der Zaag, P.: Hydrograph separation using tracers and digital filters to quantify runoff components in a semi-arid mesoscale catchment, *Hydrological Processes*, 32, 1334–1350, <https://doi.org/10.1002/hyp.11491>, 2018.
- 30 SCHAPI: Banque Hydro, <http://hydro.eaufrance.fr/>, 2015.
- Singh, S. K., Pahlow, M., Booker, D. J., Shankar, U., and Chamorro, A.: Towards baseflow index characterisation at national scale in New Zealand, *Journal of Hydrology*, 568, 646–657, <https://doi.org/10.1016/j.jhydrol.2018.11.025>, 2019.
- Smirnov, N.: Estimate of deviation between empirical distribution functions in two independent samples (Оценка расхождения между эмпирическими кривыми распределения в двух независимых выборках), *Bull. Moscow Univ. (Бюлл. Московского ун-та, серия А)*, pp. 3–14, 1939.
- 35 Su, C.-H., Costelloe, J. F., Peterson, T. J., and Western, A. W.: On the structural limitations of recursive digital filters for base flow estimation, *Water Resources Research*, 52, 4745–4764, <https://doi.org/10.1002/2015WR018067>, 2016.

- Taormina, R., Chau, K.-W., and Sivakumar, B.: Neural network river forecasting through baseflow separation and binary-coded swarm optimization, *Journal of Hydrology*, 529, 1788–1797, <https://doi.org/10.1016/j.jhydrol.2015.08.008>, 2015.
- Turc, L.: Le Bilan d'eau des sols: relations entre les précipitations, l'évaporation et l'écoulement, PhD thesis, Institut national de la recherche agronomique, Paris, 1953.
- 5 Vidal, J.-P., Martin, E., Franchistéguy, L., Baillon, M., and Soubeyroux, J.-M.: A 50-year high-resolution atmospheric reanalysis over France with the Safran system, *International Journal of Climatology*, 30, 1627–1644, <https://doi.org/10.1002/joc.2003>, 2010.
- Wittenberg, H.: Nonlinear analysis of flow recession curves, in: FRIEND: flow regimes from international experimental and network data, vol. 221, pp. 61–67, IAHS Publications, Brunswick, 1994.
- Wittenberg, H.: Baseflow recession and recharge as nonlinear storage processes, *Hydrological Processes*, 13, 715–726, [https://doi.org/10.1002/\(SICI\)1099-1085\(19990415\)13:5<715::AID-HYP775>3.0.CO;2-N](https://doi.org/10.1002/(SICI)1099-1085(19990415)13:5<715::AID-HYP775>3.0.CO;2-N), 1999.
- 10 Wittenberg, H. and Sivapalan, M.: Watershed groundwater balance estimation using streamflow recession analysis and baseflow separation, *Journal of Hydrology*, 219, 20–33, [https://doi.org/10.1016/S0022-1694\(99\)00040-2](https://doi.org/10.1016/S0022-1694(99)00040-2), 1999.

Notation	Description	Unit
$Q(t)$ [.. ²⁷]	Continuous total measured flow [.. ²⁸]	mm per Δt [.. ²⁹]
Q_t	Discrete total measured flow	mm per Δt
$R(t)$ [.. ³⁰]	Continuous baseflow	mm per Δt [.. ³¹]
R_t	Discrete baseflow	mm per Δt
$P(t)$ [.. ³²]	Continuous rainfall	mm per Δt [.. ³³]
P_t	Discrete rainfall	mm per Δt
$V(t)$ [.. ³⁴]	Continuous reservoir storage	mm
V_t	Discrete reservoir storage	mm
β [.. ³⁵]	Fraction of total flow that enters the conceptual reservoir [.. ³⁶]	Dimensionless
BFI	Baseflow index	Dimensionless
t	Time	Δt
f	Reservoir function	mm per Δt
S	Reservoir parameter	Depends on f
\bar{Q}	Average streamflow	mm per Δt
\bar{R}	Average baseflow	mm per Δt
f_{up}	Reservoir update function	mm
f_{rec}	Reservoir recursion function	mm
τ	Response time parameter	Δt
P_{eff}	Effective rainfall	mm per Δt

Table 1. List of variables

Table 2. Geographic characteristics of catchment dataset

	Outlet altitude (m)	Average altitude (m)	Average hydraulic slope	Area (km ²)
<i>Minimum</i>	0.50	22.3	0.01	[.. ⁵⁰]1.9
<i>First quartile</i>	72.0	181	0.05	[.. ⁵¹]95
<i>Median</i>	169	341	0.08	229
<i>Mean</i>	237	472	0.12	1,828
<i>Third quartile</i>	304	664	0.15	716
<i>Maximum</i>	2,154	2,871	0.67	117,183

Table 3. Hydrological characteristics of catchment dataset. Aridity index is defined as the quotient of average rainfall by average PET. NB: Precipitation yield greater than 100% was encountered in a small karstic catchment where supplementary water is brought by a major resurgence.

	Annual streamflow (mm)	Annual precipitation (mm)	Precipitation yield (%)	Aridity index
<i>Minimum</i>	59	617	5	0.75
<i>First quartile</i>	248	849	29	1.20
<i>Median</i>	355	960	37	1.43
<i>Mean</i>	446	1,035	40	1.59
<i>Third quartile</i>	543	1,137	48	1.75
<i>Maximum</i>	2,300	2,219	164	6.05

Table 4. Summary of the results from the set of 1,664 catchments

	BFI	τ (days)	Criterion value	S (m)
<i>Minimum</i>	0.005	5	0.67	0.001
<i>First quartile</i>	0.103	165	0.74	1.98
<i>Median</i>	0.164	180	0.80	4.16
<i>Mean</i>	0.199	209	0.82	12.45
<i>Third quartile</i>	0.250	200	0.92	81.0
<i>Maximum</i>	0.896	1790	0.95	1,000

Table 5. Statistical assessment of split-sample test through Pearson correlation and Kolmogorov–Smirnov (KS) non-parametric test.

BFI							τ					
Pearson correlation				KS test p-value			Pearson correlation			KS test p-value		
	P_1	P_2	P_{tot}	P_1	P_2	P_{tot}	P_1	P_2	P_{tot}	P_1	P_2	P_{tot}
P_1	1	0.91	0.94	1	<0.01	<0.01	1	0.53	0.61	1	<0.01	<0.01
P_2	0.91	1	0.98	<0.01	1	0.42	0.53	1	0.84	<0.01	1	0.28
P_{tot}	0.94	0.98	1	<0.01	0.42	1	0.61	0.84	1	<0.01	0.28	1