Revision Notes (HESS2019656)

July 17, 2020

Dear Professor Alberto Guadagnini,

Thank you for allowing us to resubmit the minor changed manuscript Hess-2019-656 entitled "A FIELD VALIDATED SURROGATE CROP MODEL FOR PREDICTING ROOTZONE MOISTURE AND SALT CONTENT IN REGIONS WITH SHALLOW GROUNDWATER". Your latest evaluation of the manuscript was as follows:

"While I do think the manuscript can be accepted at this stage, there are a few technical elements, related to the use of English, which should be carefully considered. For example, statements such as "Also, future refinement of the model would be served by measuring the salinity of irrigation source water. This would be more important if this model was implemented for irrigation that depends on groundwater sources, especially hydrologically closed basins" are somehow awkward in terms of wording. I am confident these issues will be resolved in this final segment of the process."

We have reviewed the full text and made some revisions. In our response and in the revised manuscript we show in blue the changed text. We are grateful to you and the reviewers for the comments and your time. We are looking forward to hearing from you whether additional changes are needed.

With high regard

Zalin Huo, Tammo Steenhuis and Zhongyi Liu

List of all relevant changes made in the manuscript:

NO.1. Before (Page 4, L62-63): " The leaching of salts with irrigation water is necessary and useful for irrigated agriculture (Letey et al., 2011)."

After revision (Page 4, L62-63): "The leaching of salt with irrigation water is necessary and useful for irrigated agriculture (Letey et al., 2011)."

NO.2. Before (Page 5, L83-85): "Models focused on water and solute movement in the vadose zone using some form of Richards' equation are HYDRUS (Šimůnek et al., 1998) and SWAP (Dam et al., 1997)."

After revision (Page 5, L83-85): "Models that focus on water and solute movement in the vadose zone using some form of Richards' equation are HYDRUS (Šimůnek et al., 1998) and SWAP (Dam et al., 1997). "

NO.3. Before (Page 8, L154-156): "The model, called the Shallow Vadose Groundwater model, applies directly to surface irrigated districts where the groundwater is within 3.3 m from the soil surface (Liu et al. 2019)."

After revision (Page 8, L154-156): "The model, called the Shallow Vadose Groundwater model, is applied directly to surface irrigated districts where the groundwater is within 3.3 m from the soil surface (Liu et al. 2019)."

NO.4. Before (Page 12, L212-215): "Since the equations for the downward movement on days of rainfall and/or irrigation are different than for upward movement from the groundwater on the remaining days, we present upward and downward movement in separate sections."

After revision (Page 12, L212-215): "Since the equations for the downward movement on days of rainfall and/or irrigation are different than for upward movement from the groundwater on the remaining days, we present the upward and downward movement in separate sections."

NO.5. Before (Page 17, L303): " φ_m is matric potential (cm)."

After revision (Page 16, L303): " φ_m is the matric potential (cm)."

NO.6. Before (Page 41, L720-721): "For calibration, the data collected in 2017 were used for sunflower fields B and C and maize field A. "

After revision (Page 41, L720-721): "The data of sunflower fields B and C and maize field A were collected and used for calibration."

NO.7. Before (Page 49, L862-865): "Also, future refinement of the model would be served by measuring the salinity of irrigation source water. This would be more important if this model was implemented for irrigation that depends on groundwater sources, especially hydrologically closed basins."

After revision (Page 49, L861-863): "The salinity of irrigation source water also needs to be measured, especially for the areas irrigated by groundwater or the hydrologically closed basins."

NO.8. Before (Page 51, L912-914): "Financial support: This study has been supported by National Key Research and Development Program of China (2017YFC0403301) and the National Natural Science Foundation of China (No. 51639009, 51679236). "

After revision (Page 51, L910-912): "Financial support: This study has been supported by National Key Research and Development Program of China (2017YFC0403301, 2016YFC0400107) and the National Natural Science Foundation of China (No. 51639009, 51679236)."

1	A FIELD VALIDATED SURROGATE CROP MODEL FOR					
2	PREDICTING ROOTZONE MOISTURE AND SALT CONTENT IN					
3	REGIONS WITH SHALLOW GROUNDWATER					
4	Zhongyi Liu ¹ , Zailin Huo ¹ *, Chaozi Wang ¹ , Limin Zhang ² , Xianghao Wang ¹ ,					
5	Guanhua Huang ¹ , Xu Xu ¹ , Tammo S. Steenhuis ^{3*}					
6						
7	1. Center for Agricultural Water Research in China, China Agricultural University, Beijing,					
8	100083, PR China					
9	2. School of Water Resources and Environment, China University of Geosciences, Beijing,					
10	100083, PR, China					
11	3. Department of Biological and Environmental Engineering, Cornell University, Ithaca, NY,					
12	USA.					
13						
14	Correspondence to:	Zailin Huo (huozl@cau.edu.cn)				
15		Tammo S. Steenhuis (tss1@cornell.edu)				
16						
17						
18						
19						
20						
21						

22 Abstract

Optimum management of irrigated crops in regions with shallow saline groundwater 23 requires a careful balance between application of irrigation water and upward 24 movement of salinity from the groundwater. Few field validated surrogate models are 25 available to aid in the management of irrigation water under shallow groundwater 26 conditions. The objective of this research is to develop a model that can aid in the 27 management using a minimum of input data that is field validated. In this paper a 28 2-year field experiment was carried out in the Hetao irrigation district in Inner 29 30 Mongolia, China and a physically based integrated surrogate model for arid irrigated areas with shallow groundwater was developed and validated with the collected field 31 data. The integrated model that links crop growth with available water and salinity in 32 33 the vadose zone is called Evaluation of the Performance of Irrigated Crops and Soils (EPICS). EPICS recognizes that field capacity is reached when the matric potential is 34 equal to the height above the groundwater table and thus not by a limiting hydraulic 35 conductivity. In the field experiment, soil moisture contents and soil salt conductivity 36 at 5 depths in the top 100 cm, groundwater depth, crop height, and leaf area index 37 were measured in 2017 and 2018. The field results were used for calibration and 38 validation of EPICS. Simulated and observed data fitted generally well during both 39 calibration and validation. The EPICS model that can predict crop growth, soil water, 40 groundwater depth and soil salinity can aid in optimizing water management in 41 irrigation districts with shallow aquifers. 42

43 Key words: Surrogate hydrological model, irrigated crops, shallow aquifer

Nomer	nclature					
ст.	Deference evenetropenization (mm)	р	Fraction of readily available soil water			
ET₀	Reference evapotranspiration (mm)	relative to the total available soil water				
EΤ _Ρ	Potential evapotranspiration (mm)	S	Salt stress coefficient ()			
Ep	Potential evaporation (mm)	В	Crop specific parameter (%)			
Tp	Potential transpiration (mm)	ky	Factor that affects crop yield			
-	Actual even eration (mm)	E _{Ce}	Electrical conductivity of the soil			
Ea	Actual evaporation (mm)	saturation extract (mS cm ⁻¹)				
		$EC_{ethreshold}$ Threshold of the electrical conductivity of				
Ta	Actual transpiration (mm)	the soil saturation extract when the crop yield becomes				
		affected by salt (mS cm ⁻¹)				
	Crop coefficient ()	EC _{1:5}	Electrical conductivity of the soil extract			
Kc		that soil samples mixed with distilled water in a				
		proportion of 1:5 (mS cm ⁻¹)				
-	Development stage of the leaf canopy ()	θs	Soil moisture content at saturation (cm ⁻³			
т	Development stage of the leaf carlopy ()	cm ⁻³)				
r⊤	Root function for transpiration ()	ϕ_{b}	Bubbling pressure (cm)			
rε	Root function for transpiration ()	φm	Matric potential (cm)			
j	Number of soil layer ()	λ	Pore size distribution index			
LAI	Leaf area index ()	h	Groundwater depth (cm)			
т	Mean daily temperature (°C)	Z	Depth of the point below the soil surface			
T _{mean}		(cm)				
T _{mx}	Maximum daily temperature (°C)	W _{fc} (h)	Total water content at field capacity of the			
I mx	Maximum dany temperature (C)	soil profile over a prescribed depth (cm)				
T_{mn}	Minimum daily temperature (°C)	L(j)	Height of layer j (cm)			
LAI _{mx}	Maximum leaf area index	μ	Drainable porosity			
RD _{mx}	Maximum root depth (cm)	Р	Precipitation (mm)			
Kb	Dimensionless canopy extinction coefficient	I	Irrigation (mm)			
PHU	PHU Total potential heat units required for crop		Number of soil layers			
matura	ation (°C)	n	Number of 301 layers			
Z _{1j}	Depth of the upper boundaries of soil layer j	R _{gw}	Percolation to groundwater (mm)			
(cm)		TXgw				
Z_{2j}	Depth of the lower boundaries of the soil layer	R _w (j-1,t)	Percolation rate to layer j from layer j-1 at			
for r _E (j	,t); root depth or the lower boundaries of the soil	day t (mm)	r ercolation rate to layer j nom layer j-r at			
layer fo	or r⊤(j,t) (cm)	day t (mm)				
δ	Water use distribution parameter	C(j,t)	Salt concentration of layer j at day t (g L ⁻¹)			
kε	Water stress coefficient for evaporation	Cı	Salt concentration of irrigation water (g L-1)			
k⊤	Water stress coefficient for transpiration	Cgw	Salt concentration of groundwater (g L ⁻¹)			
θ	Soil moisture content (cm ⁻³ cm ⁻³)	U _{gw}	Actual upward flux of groundwater (mm)			
θ_{fc}	Soil moisture content at field capacity (cm ⁻³	U _{gw,max}	Maximum upward flux of groundwater			
cm ⁻³)		(mm)				
θr	Soil moisture content at wilting point (cm ⁻³ cm ⁻³)	а	Constant used for calculation of $U_{gw,max}$ ()			
f shape	Shape factor of k_T curve ()	b	Constant used for calculation of $U_{gw,max}()$			

45 **1. Introduction**

⁴⁶ Irrigation water is a scarce resource, especially in arid and semi-arid areas of the ⁴⁷ world. Irrigation improves quality and quantity of food production; however, excess ⁴⁸ irrigation and salinization remain one of the key challenges. Almost 20% of the ⁴⁹ irrigated land in the world is affected by salinization and this percentage is still on the ⁵⁰ rise (Li et al., 2014). Soil salinization and water shortages, especially associated with ⁵¹ surface irrigated agriculture in arid to semi-arid areas, is a threat to the well-being of ⁵² local communities in these areas (Dehaan and Taylor, 2002; Rengasamy, 2006).

In arid and semi-arid areas where people divert surface water for flood irrigation 53 and have poor drainage infrastructures, the groundwater table is close to the surface 54 because more water has been applied than crop evapotranspiration. Capillary rise of 55 the shallow groundwater can be used to supplement irrigation and thereby, in closed 56 basins, can possibly save water for irrigating additional areas downstream (Gao et al., 57 2015; Yeh and Famiglietti, 2009; Luo and Sophocleous, 2010.). However, at the same 58 time, capillary upward moving water carries salt from the groundwater increasing the 59 salt in the upper layers of the soil leading to soil degradation and possibly decreasing 60 yields and change of crop patterns to more salt tolerant crops (Guo et al., 2018; 61 Huang et al., 2018). The leaching of salt with irrigation water is necessary and useful 62 for irrigated agriculture (Letey et al., 2011). In north China, the fields are commonly 63 irrigated in the autumn before soil freezing to leach salts and provide water for first 64 growth after seeding in the following year (Feng et al., 2005). 65

66

Tradeoffs between irrigation practices and soil salinity were studied by a lot of

researchers (Hanson et al., 2008; Pereira et al., 2002, 2009; Minhas et al., 2020).
Minhas et al. (2020) give a brief review of crop evapotranspiration and water
management issues when coping with salinity in irrigated agriculture. Phogat et al.
(2020) assessed the effects of long-term irrigation on salt build-up in the soil under
unheated greenhouse conditions by the UNSA-TCHEM and HYDRUS-1D (Phogat et
al., 2020).

Therefore, understanding the interaction of improved crop yield, soil salinization and decreased surface irrigation is important to the sustainability of the surface irrigation water systems in arid and semi-arid areas. This will require experimentation under realistic farmers' field conditions, as well as modeling to extend the findings beyond the plot scale.

Field scale models for water, solute transport and crop growth are widely 78 available. Crop growth models use either empirical functions or model the underlying 79 physiological processes (Liu, 2009). Models widely used for simulating crop growth 80 are EPIC (Williams et al., 1989), DSSAT (Uehara, 1989), WOFOST (Diepen et al., 81 1989) and AquaCrop (Hsiao et al., 2009; Raes et al., 2009; Steduto et al., 2009). 82 Models that focus on water and solute movement in the vadose zone using some 83 form of Richards' equation are HYDRUS (Šimunek et al., 1998) and SWAP (Dam et 84 al., 1997). Models that integrate crop growth and water-solute movement processes 85 are SWAP-WOFOST (Hu et al., 2019), SWAP-EPIC (Xu et al., 2015; Xu et al., 2016), 86 HYDRUS-EPIC ((Wang et al., 2015), and HYDRUS-DSSAT (Shelia et al., 2018). 87 These integrated models require input data that are usually not available when 88

applied over extended areas (Liu et al., 2009; Xu et al., 2016; Hu et al., 2019). The
EPIC crop growth model is often preferred in integrated crop growth hydrology
models because it requires relatively few input data and is accurate (Wang et al.,
2014; Xu et al., 2013; Chen et al., 2019).

There is a tendency with the advancement of computer technology to include 93 more physical processes in these models (Asher et al., 2015; Doherty and Simmons, 94 2013; Leube et al., 2012). Detailed spatial input of soil hydrological properties and 95 crop growth are required to take advantage of the model complexity (Flint et al., 2002; 96 97 Rosa et al., 2012). This greater model complexity, both in space and time, requires longer model run times, especially for the time-dependent models (Leube et al., 2012). 98 These models are useful for research purposes but for actual field applications, the 99 100 required input data are not available and expensive to obtain. In such cases, simpler surrogate models are a good alternative (Blanning, 1975; Willcox and Peraire, 2002; 101 Regis and Shoemaker, 2005). Surrogate models run faster and are as accurate as 102 the complex models for a specific problem (shallow groundwater here) but not as 103 versatile as the more complex models that can be applied over a wide range of 104 conditions (Asher et al., 2015). 105

Simple surrogate models are abundant in China for areas where the groundwater
is deeper than approximately 10 m (Kendy et al., 2003; Chen et al., 2010; Ma et al.,
2013; Li et al., 2017; Wu et al., 2016), but are limited and relatively scarce for areas
where the groundwater is near the surface in the arid to semi-arid areas (Xue et al.,
2018; Gao et al., 2017; Liu et al., 2019). In these areas with shallow aquifer, the

upward groundwater flux from groundwater is an important factor in meeting the evapotranspiration demand of the crop (Babajimopoulos et al., 2007; Yeh and Famiglietti, 2009). The advantage of applying surrogate models in areas with shallow aquifer is that they can simulate the hydrological process with fewer parameters using with simpler and computationally less demanding mathematical relationships than the traditional finite element or difference models (Wu et al., 2016; Razavi et al., 2012).

The change in matric potential is often ignored in these surrogate models for 117 soils with a deep groundwater table. However, for areas with shallow aquifers (i.e., 118 less than approximately 3 m), the matric potential cannot be ignored. The flow of 119 water is upward when the absolute value of matric potential is greater than the 120 groundwater depth or downward when it is less than the groundwater depth (Gardner, 121 122 1958; Gardner et al., 1970a; b; Steenhuis et al., 1988). The field capacity in these soils is reached when the hydraulic gradient is constant (i.e., the constant value of 123 sum of matric potential and gravity potential). In this case, the soil water is in 124 equilibrium and no flow occurs. 125

Xue et al. (2018) and Gao et al. (2017), developed models for the shallow groundwater, but used field capacities and drainable porosities that were calibrated and independent of the depth of the groundwater. This is inexact when the groundwater is close to the surface. Liu et al. (2019), used for simulating shallow groundwater the same type of model as described in this paper but calibrated crop evaporation and did not simulate the salt concentrations in the soil. This made their model less useful for practical application.

Because of the shortcomings in the above complex models, we avoided the use 133 of a constant drainable porosity and considered the crop growth and thus improved 134 the surrogate model in our last study (Liu et al., 2019). The objective of this research 135 was to develop a field validated surrogate model that could be used to simulate the 136 water and salt movement and crop growth in irrigated areas with shallow groundwater 137 and salinized soil with a minimum of input parameters. To validate the surrogate 138 model, we performed a 2-year field experiment in the Hetao irrigation district that 139 investigated the change in soil salinity, moisture content, groundwater depth and 140 141 maize and sunflower growth during the growing season.

In the following section we present first the theoretical background of the surrogate model. The model consists of crop growth module and a vadose zone module. This is followed by detailed description of the two-year field experiments started in 2017 in the Hetao irrigation district where maize and sunflower were irrigated by flooding the field. The experimental results consisting of climate data, irrigation application, crop growth parameters, moisture and salt content and groundwater depth are used to calibrate and validate the model.

149 **2. Model description**

150 2.1 Introduction of the model


In a recent study, we presented a surrogate model for the vadose zone with shallow groundwater using the novel concept that the moisture content at field capacity is a unique function of the groundwater depth after irrigation or precipitation that wets up the entire soil profile. The model, called the Shallow Vadose Groundwater model, is

applied directly to surface irrigated districts where the groundwater is within 3.3 m from the soil surface (Liu et al. 2019). The model was a proof of concept with calibrated values for evapotranspiration and soil salinity which was not simulated.


To make the Shallow Vadose Groundwater model more physically realistic, we added a crop growth model and included the effect of salinity and moisture content on evaporation and transpiration directly in this study. The new model that combines parts of the EPIC (Erosion Productivity Impact Calculator, Williams et al., 1989) with Shallow Vadose Groundwater model is called the *Evaluation of the Performance of Irrigated Crops and Soils* (EPICS).

164 2.2 Structure of the EPICS model

In the EPICS model, the soil profile is divided into five layers of 20 cm (from the soil surface down) and a sixth layer that stretches from the 100 cm depth to the water table below (Fig. 1).



168



The moisture content and salt content are calculated for each day (Fig.1). All flow 170 takes place within the day and the water and salt content are in "equilibrium" (i.e., 171 fluxes are zero) at the end of the day for which the calculations are made. Daily fluxes 172 considered in the vadose model are the following: at the surface, the fluxes are 173 irrigation, both irrigation water, I(t), and salt, $S_0(t)$, and precipitation, P(t), and for each 174 175 layer, j, on days with irrigation and rainfall, the downward flux of water, $R_w(j,t)$, and salt, S(j,t), between the layers. On days without water input at the soil surface, an upward 176 groundwater flux U(j,h,t), and salt, S(j,t) are considered. The flux to the surface 177 depends on the groundwater depth. Finally, transpiration, T(j,t), removes water from 178 the layers with roots of the crops and evaporation, E(j,t), from all layers. 179

The EPICS model consists of two modules: the VADOSE module and the CROP module. The two modules are linked through the evapotranspiration flux in the soil (Fig. 2).






Figure 2. Schematic diagram of the linked novel Shallow Aquifer-Vadose zone surrogate module and EPIC module. Note: ET_0 is the reference evapotranspiration, E_p and T_p are the potential evaporation and potential transpiration, E_a and T_a are the actual evaporation and actual transpiration, K_c is the crop coefficient, τ is the development stage of the leaf canopy, and r_j is the root function of soil layer *j*.

189

The CROP module employs functions of the EPIC model (Williams et al., 1989) and root growth distribution (Novak, 1987; Kendy et al., 2003; Chen et al. 2019). The CROP module calculates daily values of crop height, root depth and leaf area index (LAI) based on climatic data (Fig. 2).

The VADOSE module calculates the moisture and salt content in the root zone and the upward movement of the groundwater (Fig.2). Field capacity varies with depth and is a function of the (shallow) groundwater depth and the soil characteristic curve (Liu et al., 2019). Moisture contents become less than field capacity when the upward flux is less than the actual evapotranspiration.

Finally, the link between the VADOSE and the CROP modules is achieved by calculating the actual evapotranspiration with parameters of both modules consisting of the moisture content and the salt content simulated in the VADOSE module and root distribution and potential evapotranspiration in the CROP module (Fig. 2).

203 2.3 Theoretical background of the EPICS model

In the next section, the equations of the CROP in the VADOSE modules are 204 presented. The calculations are carried out sequentially on a daily time step. This 205 model predicts field daily soil water, salt content and crop growth, which are critical 206 parameters for irrigation water management. For field and regional water 207 management and irrigation policy development, resolution of daily time step is 208 209 sufficient. Finer resolution is not needed for managing water and salt content for irrigation. In the first step, the actual evaporation and transpiration are calculated for 210 each layer in the model. Next, the moisture content and salt content are adjusted for 211 the various fluxes. Since the equations for the downward movement on days of 212 rainfall and/or irrigation are different than for upward movement from the groundwater 213 on the remaining days, we present the upward and downward movement in separate 214 sections. The code was written in Matlab 2014Ra and Microsoft Excel was used for 215 data input and output. 216

217 2.3.1 CROP module

The crop module uses functions of EPIC (Erosion Productivity Impact Calculator, Williams et al., 1989) to calculate leaf area index, LAI, crop height and the root depth

(green boxes in Fig. 2), and the potential transpiration, *T*, and evaporation, *E* (orange boxes in Fig, 2). Input data for the CROP module included: mean daily temperature (T_{mean}) , maximum daily temperature (T_{mx}) , minimum daily temperature (T_{mn}) , maximum crop height (H_{mx}) , maximum LAI (LAI_{mx}) , maximum root depth (RD_{mx}) , dimensionless canopy extinction coefficient (K_b) , and total potential heat units required for crop maturation (PHU).

The potential rates of evaporation, $E_P(j,t)$, and transpiration, $T_P(j,t)$, of different layers are derived from the total rates and a root function that determines the distribution of roots in the vadose zone

229
$$T_P(j,t) = r_T(j,t)T_p(t)$$
(1a)

$$E_p(j,t) = r_E(j,t)E_p(t)$$
(1b)

where *j* is the number of soil layers and *t* is the day number, $T_P(t)$ is the total potential transpiration and $E_P(t)$ is the total potential transpiration at time, *t*. Both are calculated with the CROP module (S1 in the supplementary material). Root functions (Sau et al., 2004; Delonge et al., 2012) were used to calculate transpiration and evaporation of different soil layer. $r_T(j,t)$ is the root function for the transpiration and $r_E(j,t)$ is the root function for the evaporation. Both have the same general equation but with a different value for the constant δ .

238
$$r_T(j,t) = \left[\frac{1}{1 - exp(-\delta)}\right] \left\{ exp\left[-\delta\left(\frac{Z_{1j}}{Z_{2j}}\right)\right] \left[1 - exp\left(-\delta\frac{Z_{2j} - Z_{1j}}{Z_r}\right)\right] \right\}$$
(2a)

239
$$r_E(j,t) = \left[\frac{1}{1 - exp(-\delta)}\right] \left\{ exp\left[-\delta\left(\frac{Z_{1j}}{Z_{2j}}\right)\right] \left[1 - exp\left(-\delta\frac{Z_{2j} - Z_{1j}}{Z_r}\right)\right] \right\}$$
(2b)

240 Where z_{1j} is the depth of the upper boundaries of the soil layer *j*. For $r_T(j,t)$ if the

root depth is smaller than the lower boundaries of the soil layer j, Z_{2j} is equal to the 241 root depth and if the root depth is greater than the lower boundaries of the soil layer *j*, 242 Z_{2j} is the depth of the lower boundaries of the soil layer j. For $r_E(j, t)$, Z_{2j} is depth of 243 the lower boundaries of the soil layer j. Z_r is the root zone depth and δ is the water 244 use distribution parameter. Note that the sum of $r_T(j,t)$ of all soil layers is equal to 1. 245 In the study of Novark (1987), the value of δ for corn is 3.64 and we used this value. 246 To obtain $r_E(j,t)$, δ was set to 10 (Chen et al., 2019; Kendy et al., 2003). Sunflower 247 root function simulation employed the same δ values as for maize. 248

The actual evaporation rates, $E_a(j, t)$, and transpiration, $T_a(j, t)$, for each soil layer, *j*, at time, *t*, are calculated as a proportion of the potential values as:

$$E_a(j,t) = k_E(j,t)E_p(j,t)$$
(3a)

252
$$T_a(j,t) = k_T(j,t)S(j,t)T_p(j,t)$$
 (3b)

where $k_E(j)$ and $k_T(j)$ are water stress coefficients and S(j) is a salt stress coefficient. According to Raes et al. (2009), the water stress coefficients are

255
$$k_E(j,t) = \exp\left(-2.5\frac{\theta_{fc}(j) - \theta(j,t)}{\theta_{fc}(j) - \theta_r(j)}\right) \qquad \theta \le \theta_{fc} \qquad (4a)$$

$$k_E(j,t) = 1 \qquad \qquad \theta > \theta_{fc} \qquad (4b)$$

where $\theta_{fc}(j)$ is the moisture content at field capacity for layer *j*, or when the conductivity becomes limiting and $\theta_r(j)$ is the moisture content at wilting point, $\theta(j,t)$ is the soil moisture content for layer *j* at time *t*.

260 Then water stress coefficient in Eq. 3b is:

261
$$k_T(j,t) = 1 - \frac{\exp\left[\left(1 - \frac{\theta(j,t) - \theta_r(j)}{(1-p)\left[\theta_{fc}(j) - \theta_r(j)\right]}\right) f_{shape}\right] - 1}{\exp(f_{shape}) - 1} \quad \theta \le \theta_{fc} \quad (5a)$$

262
$$k_T(j,t) = 1 \qquad \qquad \theta > \theta_{fc} \quad (5b)$$

where f_{shape} is the shape factor of $k_T(j,t)$ curve, p is the fraction of readily available soil water relative to the total available soil water. Finally, the salt stress coefficient S(j,t) for each layer in Eq 3b can be calculated as (Allen et al., 1998; Xue et al., 2018):

$$S(j,t) = 1 - \frac{B}{100 k_{\nu}} (EC_e(j,t) - EC_{ethreshold})$$
(6)

where k_y is the factor that affects the yield, EC_e is the electrical conductivity of the soil saturation extract (mS cm⁻¹), $EC_{ethreshold}$ is the calibrated threshold of the electrical conductivity of the soil saturation extract when the crop yield becomes affected by salt (mS cm⁻¹), and *B* is the calibrated crop specific parameter that describes the decrease rate of crop yield when EC_e increases per unit below the threshold. The electrical conductivity of the soil saturation extract can be calculated as (Rhoades et al., 1989):

275

$$EC_e = 1.33 + 5.88 \times EC_{1:5} \tag{7}$$

where $EC_{1:5}$ is the electrical conductivity of the soil extract that soil samples mixed with distilled water in a proportion of 1:5.

278 2.3.2 VADOSE Module

For modeling the daily soil moisture content and groundwater depth, first we need to calculate the soil moisture content at field capacity and the drainable porosity based on the soil moisture characteristic curve. Besides, we assume that the water and salt moves downward on rainy and/or irrigation days, while the water and salt moves upward on days without rain and/or irrigation. 284 2.3.2.1 Parameters based on soil moisture characteristic curve for modeling

285 Moisture content at field capacity

Field capacity with a shallow groundwater is different than in soils with deep 286 groundwater where water stops moving when the hydraulic conductivity becomes 287 limiting at -33 kPa. When the groundwater is shallow, the hydraulic conductivity is not 288 limiting and the water stops moving when the hydraulic potential is constant and thus 289 the matric potential is equal to the height above the water table (Gardner 1958; 290 Gardner et al., 1970a, b; Steenhuis et al., 1988; Liu et al., 2019). Assuming a unique 291 relationship between moisture content at field capacity and matric potential (i.e. soil 292 characteristic curve), the moisture content at field capacity at any point above the 293 water table is a unique function of the water table depth. Thus, any water added 294 295 above field capacity will drain downward. When the groundwater is recharged, the water table will rise and increase the moisture contents at field capacity throughout 296 the profile. 297

The moisture contents at field capacity were found by Liu et al. (2019) using the simplified Brooks and Corey soil characteristic curve (Brooks and Corey, 1964)

300
$$\theta = \theta_s \left[\frac{\varphi_m}{\varphi_b}\right]^{-\lambda} \quad for \ |\varphi_m| > |\varphi_b| \tag{8a}$$

301

$$\theta = \theta_s \qquad for \ |\varphi_m| \le |\varphi_b| \qquad (8b)$$

in which θ is the soil moisture content (cm³ cm⁻³), θ_s is the saturated moisture content (cm³ cm⁻³), φ_b is the bubbling pressure (cm), φ_m is the matric potential (cm), and λ is the pore size distribution index. The moisture content at field capacity, $\theta_{fc}(z, h)$, for any point, *z*, from the surface water for a groundwater at depth, h, can be 306 expressed as (Liu et al. 2019)

307

$$\theta_{fc}(z,h) = \theta_s(z) \left[\frac{h-z}{\varphi_b}\right]^{-\lambda} \quad for \ |h-z| > |\varphi_b(z)| \quad (9a)$$

308
$$\theta_{fc}(z,h) = \theta_s(z)$$
 for $|h-z| \le |\varphi_b(z)|$ (9b)

where *h* (cm) is the depth of the groundwater and *z* (cm) is the depth of the point below the soil surface. Thus (*h-z*) is the height above the groundwater and this is equal to the matric potential for soil moisture content at field capacity.

For shallow groundwater, the matric potential at the surface is -33kPa when the groundwater is 3.3 m depth. For this matric potential, as mentioned above, the conductivity becomes limiting. This depth of the groundwater is therefore the lower limit over which the VADOSE module is valid.

Evapotranspiration can lower the soil moisture content below field capacity. Thus, the maximum moisture content in the VADOSE module is determined by the soil characteristic curve and the height of the groundwater table, and the minimum is the wilting point that can be obtained by evapotranspiration by the crop. Note that the saturated hydraulic conductivity does not play a role in determining the moisture content because inherently it is assumed that it is not limiting in the distribution of the water.

323 Drainable porosity

The drainable porosity is a crucial parameter in modelling the groundwater depth and soil moisture content. According to the soil water characteristic curve at field capacity, the drainable porosity can be expressed as a function of the depth. The drainable

porosity is obtained by calculating the field capacity, $W_{fc}(h)$ (cm) for each layer at all groundwater depths. The total water content at field capacity of the soil profile over a prescribed depth with a water table at depth *h* can be expressed as:

330
$$W_{fc}(h) = \sum_{j=1}^{n} [L(j) \,\theta_{fc}(j,h)]$$
(10)

where $\theta_{fc}(j,h)$ is the average moisture content at field capacity of layer j that can be found by integrating Eq. 8 from the upper to the lower boundary of the layer and dividing by the length L(j) which is the height of layer *j*. The matric potential at the boundary is equal to the height above the water table. The drainable porosity, $\mu(h)$, which is a function of the groundwater depth *h*, can simply be found as the difference in water content when the water table is lowered over a distance of $2\Delta h$.

337
$$\mu(h) = \frac{W_{fc}(h + \Delta h) - W_{fc}(h - \Delta h)}{2\Delta h}$$
(11)

338 where $\Delta h = 0.5L(j)$ (cm).

2.3.2.2 Downward flux (at times of irrigation and/or precipitation) and model output
During the downward flux period, the upward water flux from groundwater is zero.
Under this condition, the model can output the daily soil moisture content of different
soil layers, the percolation from each soil layer to the soil layer beneath, the discharge
from soil water to groundwater, the salt concentration of groundwater and of soil water
in each soil layer, and the groundwater depth.

345 Water

A downward flux occurs when either the precipitation or irrigation is greater than the actual evapotranspiration. In this case, upward flux will not occur because the actual evapotranspiration is subtracted from the input at the surface. We consider two cases

³⁴⁹ when the groundwater is being recharged and when it is not.

When the net flux at the surface (irrigation plus rainfall minus actual 350 evapotranspiration) is greater than that needed to bring the soil up to equilibrium 351 moisture content, the groundwater will be recharged and the distance of the 352 groundwater to soil surface decreases and the moisture content will be equal to the 353 moisture at field capacity. The fluxes from one layer to the next can be calculated 354 simply by summing the amount of water needed to fill up each layer below to the new 355 moisture content at field capacity. Hence, the percolation to groundwater, $R_{gw}(t)$, can 356 be expressed as: 357

358
$$R_{gw}(t) = P(t) + I(t) - E_a(t) - T_a(t) - \sum_{j=1}^n \frac{\left[\theta_{fc}(j,h) - \theta(j,t-\Delta t)\right]L(j)}{\Delta t}$$
(12)

where *n* is the total number of layers, $\theta(j,t)$ is the average soil moisture content in day *t* of layer *j* (cm³ cm⁻³), $E_a(t)$ is the actual evaporation (mm), $T_a(t)$ is the actual transpiration (mm), P(t) is the precipitation (mm), and I(t) is the irrigation (mm).

When the groundwater is not recharged, the rainfall and the irrigation are added to uppermost soil layer and when the soil moisture content will be brought up to the field capacity and the excess water will infiltrate to next soil layer bringing it up to field capacity. This process continues until all the rainwater is distributed. Formally the soil moisture can be expressed as

367
$$\theta(j,t) = \min\left[\theta_{fc}(j,h), \left[\theta(j,t-\Delta t) + \frac{R_w(j-1,t)\,\Delta t}{L(j)}\right]\right]$$
(13)

where $\theta(j,t)$ is the average soil moisture content in day *t* of layer *j* (cm³ cm⁻³), $R_w(j-1,t)$ is the percolation rate to layer *j* (mm) and can be found with Eq 12 by

replacing *j*-1 for n in the summation sign. 370

371
$$R_w(j-1,t) = P(t) + I(t) - E_a(t) - T_a(t) - \sum_{1}^{j-1} \frac{\left[\theta_{fc}(j,h) - \theta(j,t-\Delta t)\right]L(j)}{\Delta t}$$
(14)

For the uppermost soil layer, the water percolation can be expressed as 372

373
$$R_w(0,t) = I(t) + P(t) - E_a(t) - T_a(t)$$
(15)

Salinity 374

378

The salt concentration for layer j can be expressed by a simple mass balance as: 375

376
$$C(j,t) = \frac{\theta(j,t-\Delta t) C(j,t-\Delta t)L(j) + [R_w(j-1,t) C(j-1,t) - R_w(j,t) C(j,t)] \Delta t}{\theta(j,t)L(j)}$$
(16)

where C(j,t) is the salt concentration of layer j at time t (g L⁻¹). The equation can be 377 rewritten as an explicit function of C(j, t)

379
$$C(j,t) = \left[\frac{\theta(j,t)L(j)}{1+R_w(j,t)\ \Delta t}\right] \left[\frac{\theta(j,t-\Delta t)\ C(j,t-\Delta t)L(j)+R_w(j-1,t)\ C(j-1,t)\ \Delta t}{\theta(j,t)L(j)}\right] (17)$$

For the surface layer j=1, we obtain 380

381
$$C(1,t) = \left[\frac{\theta(1,t)L(1)}{1+R_w(1,t)\Delta t}\right] \left[\frac{\theta(1,t)L(1)}{1+R_w(1,t)\Delta t} \frac{\theta(j,t-\Delta t)C(j,t-\Delta t)L(j)+I(t)C_I\Delta t}{\theta(j,t)L(j)}\right] (18)$$

where C_I is the salt concentration in the irrigation water (g L⁻¹). 382

The salt concentration of the groundwater $C_{gw}(t)$ can be estimated as: 383

384
$$C_{gw}(t) = \frac{\left[G(t-1) \times C_{gw}(t-1) + C(5,t) \times R_{w}(t)\right]}{G(t-1) + R_{w}(t)}$$
(19)

Where C(5,t) is the soil salinity concentration of the soil layer 5 on day t (g L⁻¹), 385 G(t-1) is the difference of the groundwater depth and the depth that the largest 386 groundwater table fluctuations depth of groundwater table on day (t-1) (m) (Xue et al., 387 2018), $C_{gw}(t)$ is the soluble salt concentration of groundwater at day t (g L⁻¹). 388

2.3.2.3 Upward flux and model output 389

For the upward flux period, the downward water flux to groundwater is zero. The 390

evapotranspiration leads to the decrease of soil moisture content in the vadose zone and lowers the groundwater table due to the upward movement of groundwater to crop root zone and soil surface. The soil moisture content is calculated by taking the difference of equilibrium moisture content associated with the change of groundwater depth. Under this condition, the model can output the daily soil moisture content of different soil layers, the upward groundwater flux, the groundwater depth, and the salt concentration of groundwater and of soil water in each soil layer.

398 Water

The groundwater upward flux, $U_{gw}(h, t)$, is limited by either the maximum upward flux of groundwater, $U_{gw,max}(h)$, or the actual evapotranspiration, formally stated as:

401
$$U_{gw}(h,t) = min\left[[E_a(t) + T_a(t)], U_{gw,max}(h)\right]$$
(20)

402
$$E_a(t) = \sum_{j=1}^{n} E_a(j,t)$$
(21)

403
$$T_a(t) = \sum_{j=1}^{n} T_a(j, t)$$
(22)

where $U_{gw,max}(h)$ is the actual upward flux from groundwater (mm), $E_a(t)$ is the actual evaporation at day t (mm), $T_a(t)$ is the actual transpiration at day t (mm), $E_a(j,t)$ is the actual evaporation at day t of layer j (mm) and $T_a(j,t)$ is the actual transpiration at day t of layer j (mm).

The maximum upward flux can be expressed as (Liu et al., 2019; Gardner et al., 1958)

410
$$U_{gw,max}(h) = \frac{a}{e^{bh} - 1}$$
 (23)

where *a* and *b* are constants that need to be calibrated, *h* is the groundwater depth

412 (cm).

Two cases are considered for determining the moisture contents of the layers depending on whether the actual evapotranspiration is greater or less than the maximum upward flux.

416 Case I:
$$U_{gw,max}(h) > E_a(t) + T_a(t)$$

In this case, where the maximum upward flux is greater than the evaporative demand,
the groundwater depth is updated

419
$$h(t) = h(t - \Delta t) + \frac{E_a(t) + T_a(t)}{\mu(\bar{h})}$$
(24)

420 where $\mu(\bar{h})$ is the average drainable porosity over the change in groundwater depth 421 *h*. The moisture content after the change in groundwater depth becomes

422
$$\theta(j,t) = \theta(j,t-\Delta t) + \theta_{fc}(j,h(t)) - \theta_{fc}(j,h(t-\Delta t))$$
(25)

423 Note that when the layer is at field capacity and the upward flux is equal to the 424 evaporative flux, the layer remains at field capacity for the updated groundwater 425 depth at time t.

- 426 Case II: $U_{gw,max}(h) \le E_a(t) + T_a(t)$
- 427 In this case, the groundwater depth is updated

428
$$h(t) = h(t - \Delta t) + \frac{U_{gw,max}(h)}{\mu(\bar{h})}$$
 (26)

When the upward flux is less than the sum of the actual evaporation and transpiration, the moisture content is updated with the difference between the two fluxes, $U_{gw,max}(h)$ and $[E_a(t) + T_a(t)]$, according to a predetermined distribution extraction of water out of the root zone

433
$$\theta(j,t) = \theta(j,t-\Delta t) + \theta_{fc}(j,h(t)) - \theta_{fc}(j,h(t-\Delta t)) - \frac{r(j)[E_a(t) + T_a(t) - U_{gw,max}(h)]}{L(j)}$$
(27)

The upward flux of water can be found by summing the differences in moisture content above the layer *j* similar to Eq 14, but starting the summation at the groundwater.

437 Salinity

The salt from groundwater is added to the soil layers according to the root function.

The soil salinity concentration in layer *j* at day *t* can be expressed as

440
$$C(j,t) = \frac{\theta(j,t-\Delta t) C(j,t-\Delta t) L(j) + r(j,t) U_g(h,t) C_{gw}(t)}{\theta(j,t-\Delta t) L(j) + (\theta_{fc}(j,h(t)) - \theta_{fc}(j,h(t-\Delta t)) L(j) - r(j,t) (E_a(t) + T_a(t) - U_{gw,max}(h))}$$
(28)

Since water is extracted from the reservoir that has the same concentration as in the
reservoir, the concentration will not change, hence the equation used to estimate the
groundwater salt concentration can be expressed as


444

$$C_{gw}(t) = C_{gw}(t - \Delta t) \tag{29}$$

445 **3. Data collection**

446 3.1 Study area

Field experiments were conducted in 2017 and 2018 in Shahaoqu experimental station in Jiefangzha sub-district, Heato irrigation district in Inner Mongolia, China (Fig. 3). Irrigation water originates from the Yellow River. The change of the irrigation water salinity is small and can be ignored during the crop growth period. The area has an arid continental climate. Mean annual precipitation is 155 mm a⁻¹ of which 70% falls from June to September. Pan evaporation is 2000 mm a⁻¹ (Xu et al., 2010). The mean annual temperature is 7°C. The soils begin to freeze in the middle of November and to thaw in end of April or beginning of May. Maize, wheat and sunflower are the main crops in Jiefangzha sub-district and are grown with flood irrigation. The groundwater depth is between 0.5-3 m. Regional exchange of groundwater is minimal due to low gradient of 0.01-0.025 (Xu et al., 2010). Thus, the groundwater flows mainly vertically with minimum lateral flow in the regional scale. Over 50% of the total irrigated cropland, 5250 km² in the Hetao irrigation district in the Yellow River basin, is affected by salinity (Feng et al., 2005).



461

Figure 3. Location of the Shahaoqu experimental field (Note: The figure was
 downloaded from Google earth. The imagery is taken on April 8, 2019)

464 3.2 Field observations and data

The layout of the experimental fields is shown in Figure 3. The areas of fields A, B, C and D are 920, 2213, 1167, 1906 m², respectively. Field A and D were planted with maize on May 10 and harvested on September 30, 2017. In 2018, fields A and D were planted with gourds and were therefore not monitored in 2018. Fields B and C were seeded with sunflower in both 2017 and 2018. The sunflower was planted on June 1, 2017 and June 5, 2018. Harvest was on September 15 in both years. The fields were
irrigated by flooding the field ranging from two to five times during the growing season
(Table 1). The salinity of the irrigation source water was measured three times during
crop growth period and the mean value was used in the mass balance. The salinity of
the irrigation source water is assumed unchanged. A well was installed in each
experimental field to monitor the groundwater depth.

Field	Year	Irrigation events	Date	Irrigation depth (mm)	
A (maize)	2017	1	5/30	100	
		2	6/25	162	
		3	7/14	275	
		4	8/6	199	
	2017	1	6/26	140	
_		2	7/23	121	
В	2018	1	6/20	134	
ם (sunflower)		2	6/24	60	
(Sumower)		3	7/15	114	
		4	7/22	40	
		5	8/31	130	
	2017	1	6/19	80	
С	2017	2	6/30	80	
(sunflower)	2018	1	6/20	140	
		2	7/14	100	
	2017	1	6/13	150	
		2	6/26	94	
D (maizo)		3	7/6	50	
(maize)		4	7/14	174	
		5	8/6	120	

Table 1 Irrigation scheduling for the Shahaoqu experimental fields in 2017 and 2018

477

Daily meteorological data, including air temperature, precipitation, relative humidity, wind speed, and sunshine duration, originated from the weather station at the Shahaoqu experimental station. The soil moisture content for the four

experimental fields in 2017 and for field C in 2018 during the crop growing season 481 was measured every 7-10 days at the depths of 0-20, 20-40, 40-60, 60-80, 80-100 cm 482 by taking soil samples and oven drying. In 2018, in addition, the soil moisture content 483 at same depths was monitored daily using Hydra Probe Soil Sensors (Stevens Water 484 Monitoring System Inc., Portland, OR, USA) in field B except the oven drying method. 485 The Hydra Probe was calibrated using the intermittent manual measurements. In 486 2017, the groundwater depths were manually measured in all four experimental fields 487 about every 7-10 days. In 2018, the groundwater depth in fields B and C was 488 recorded at 30 min intervals using an HOBO Water Level Logger-U20 (Onset, Cape 489 Cod, MA, USA). The sensors of the soil moisture content and groundwater depth 490 were connected to data loggers and downloaded via wireless transmission. The crop 491 492 leaf area and crop height were manually measured every 7-12 days.

Undisturbed soil samples were collected in 5 cm high rings with a diameter of 5.5 493 cm from the five soil layers where the soil moisture were taken and used for textual 494 analysis, saturated soil moisture content, field capacity and soil bulk density. The soil 495 texture was analyzed with a laser particle size analyzer (Mastersizer 2000, Malvern 496 Instruments Ltd., United Kingdom). The American soil texture classification method 497 was used in this study. Finally, the soil samples were collected 7-10 days apart to 498 monitor the change of electrical conductivity (EC). The soil samples were mixed with 499 distilled water in a proportion of 1:5 to measure the electrical conductivity of the soil 500 water by a portable conductivity meter. It is assumed that 1 Ms cm⁻¹ corresponds to 501 640 mg L⁻¹ of total dissolved salts (Wallender and Tanji, 2011; Xue et al., 2018). 502

503 3.3 Model calibration and validation

The observed soil moisture contents, groundwater depths, crop heights, LAIs and 504 salinity concentrations for field A with maize and sunflower fields B and C in 2017 505 were used for calibration and the sunflower data of fields B and C in 2018 and the 506 maize data in field D in 2017 were used for validation. The initial θ_{fc} was based on the 507 measured data (Table 2). The initial values of θ_s and θ_r were derived from the soil 508 texture with the method of Ren et al. (2016) (Table2). The default values of EPIC for 509 sunflower and maize were used as initial values for simulating crop growth (K_{cmax} and 510 LAI_{mx} in Eq. S3, K_b in Eq. S4, H_{mx} in Eq. S7, PHU in Eq. S9, T_b in Eq. S10, ad in Eq. 511 S12, T_0 and T_b in Eq. 16, RD_{mx} in Eq. S18). The initial value maximum crop coefficient 512 (K_{cmax}) in Eq. S3 in Supplementary S1 for evapotranspiration calculation was taken 513 514 from Sau et al., (2004). The initial values of two groundwater parameters (a and b in Eq. 23) were based on Liu et al., (2019). The Brooks and Corey soil moisture 515 characteristic parameters (φ_b , λ in Eq. 8) were obtained by fitting the outer envelope 516 517 of the measure moisture content and water table data.

518 Statistical indicators were used to evaluate goodness of fit of the hydrological 519 model for both calibration and validation (Ritter and Muñoz-Carpena, 2013). The 520 statistical indicators included the root mean square error (RMSE) (Abrahart and See, 521 2000),

522
$$RMSE = \sqrt{\frac{1}{N} \sum_{i=1}^{N} (P_i - O_i)^2}$$
(30)

the mean relative error (MRE) (Dawson et al., 2006; Nash and Suscliff, 1970),

524
$$MRE = \frac{1}{N} \sum_{i=1}^{N} \frac{(P_i - O_i)}{O_i} \times 100\%$$
(31)

the Nash-Sutcliffe efficiency coefficient (NSE) (Nash and Suscliff, 1970),

526
$$NSE = 1 - \frac{\sum_{i=1}^{N} (P_i - O_i)^2}{\sum_{i=1}^{N} (O_i - \overline{O})^2}$$
(32)

and the determination coefficient (R²) and regression coefficient (b) (Xu et al., 2015)

528
$$R^{2} = \left[\frac{\sum_{i=1}^{N} (O_{i} - \bar{O})(P_{i} - \bar{P})}{[\sum_{i=1}^{N} (O_{i} - \bar{O})]^{0.5} [\sum_{i=1}^{N} (P_{i} - \bar{P})]^{0.5}}\right]^{2}$$
(33)

where N is the total number of observations; P_i and O_i are the *i*th model predicted and 530 observed values (*i*=1,2,3...N), respectively; \overline{O} and \overline{P} are the mean observed values 531 and predicted values, respectively. The RMSE is used to evaluate the bias of the 532 measured data and predicted data. The MRE can evaluate the credibility of the 533 measured data. The NSE is usually used to evaluate the quality of the hydrological 534 models. The R² is used to measure the fraction of the dependent variable total 535 variation that can be explained by the independent variable. And the regression 536 coefficient represents the influence of the independent variable on the dependent 537 variable in the regression equation. The value of RMSE and MRE close to 0 indicates 538 good model performance. The value of NSE ranges from -∞ to 1. NSE=1 means a 539 perfect fit while the negative NSE value indicates the mean observed value is a better 540 predictor than the simulated value (Moriasi et al., 2007). For b and R², the value 541 closest to 1 indicates good model predictions. 542

543 3.4 Parameters sensitivity analysis

A sensitivity analysis was performed to determine how the input parameters affected output of the models (Cloke et al., 2008; Cuo et al., 2011). Each parameter was varied over a range of -30% to 30% to derive the corresponding impact on the model output of soil moisture, groundwater depth, soil salinity, leaf area index and actual evapotranspiration. The change in output values was plotted against the change in input values.

550 **4. Results**


The 2017 and 2018 experimental data of the Shahaoqu farmers' fields in the Hetao irrigation district (Fig.3) are presented first, followed by the calibration and validation results of the CROP and VADOSE modules of EPICS model.

4.1 Results of the field experiment

555 4.1.1 Water input

The precipitation was 63 mm in 2017 (May 10 to September 30) and 108 mm in 556 2018 (June 1 to September 15). The precipitation from the greatest rainstorm was 26 557 mm on September 1, 2018 (Fig. 4). Irrigation provided most of the water for the crops. 558 Field A (maize) was irrigated four times with a total of 736 mm and field D (maize) was 559 irrigated five times for a total of 588 mm in 2017. Sunflower fields B and C were both 560 irrigated twice with a total water amount of 261mm and 160mm, respectively, in 2017. 561 In 2018, fields B and C were irrigated five and two times, respectively, with a total 562 water amount of 478mm and 240mm, respectively. The reference evapotranspiration 563 ranged from 1 mm d⁻¹ to a maximum of 6.4 mm d⁻¹ during crop growing period (Fig. 4). 564 The total reference evapotranspiration from May 10 to September 30, 2017 was 595 565

mm and 368 mm from June 1 to September 15, 2018. The reason was that there were more rainfall days in June, July and September in 2018 than in 2017, which increased the amount of water available for the evapotranspiration by the crop in 2018. In addition, the wind speed was high in May that increase the evapotranspiration was elevated. In the study of Ren et al. (2017) and Miao (et al. 2016), the mean ET_0 was over 6 mm per day on May. Hence, the ET_0 during the study period in 2017 was greater than in 2018.



574 Figure 4. Reference evapotranspiration (ET₀) and precipitation during crop growth 575 period in 2017 and 2018.

576

573

577 4.1.2 Soil physical properties

Based on the soil textural analysis in Table 2, the soils were classified as silt, silt loam
and loamy sand. Bulk densities varied from 1.24 to 1.47 Mg m⁻³ with the greatest bulk
densities in the 0-20 cm soil layer. There was generally more sand in the top 40 cm
than below. The subsoil was heavier and had the greatest percentage of silt (Table 2).
The moisture content at -33 kPa (0.33 bar) varied from 0.25 to 0.35 cm³cm⁻³ and at
1.5 Mpa (wilting point at15 bar) ranged from 0.08 to 0.15 cm³cm⁻³ (Table 2).
Table 2 Soil texture and bulk density of the experimental fields in Shahaogu

Field	Soil depth (cm)	Sand(%)	Silt(%)	Clay(%)	Soil type	ρ(Mg m⁻³)	θ _{fc} (m³m ⁻³)	θ _r (m³m⁻³)
	0-20cm	26	62	13	Silt loam	1.44	0.31	0.1
•	20-40cm	76	22	2	Loamy sand	1.24	0.32	0.07
A	40-60cm	10	79	10	Silt loam	1.33	0.33	0.12
	60-100cm	6	79	15	Silt loam	1.35	0.34 0.35	0.14 0.14
	0-20cm	22	64	13	Silt loam	1.44	0.29	0.15
	20-40cm	16	73	11	Silt loam	1.24	0.26	0.13
В	40-60cm	18	73	9	Silt loam	1.33	0.32	0.11
	60-80cm	8	77	16	Silt	1.35	0.34	0.14
	80-100cm	13	79	8	Silt loam		0.35	0.12
	0-20cm	29	63	8	Silt loam	1.47	0.26	0.08
	20-40cm	37	56	6	Silt loam	1.33	0.25	0.08
С	40-60cm	35	59	7	Silt loam	1.32	0.26	0.08
	60-80cm	14	74	12	Silt loam	1.38	0.31	0.12
	80-100cm	10	82	8	Silt	1.38	0.34	0.11
	0-20cm	27	62	11	Silt loam	1.47	0.3	0.15
	20-40cm	5	80	15	Silt loam	1.33	0.27	0.14
D	40-60cm	7	75	18	Silt loam	1.32	0.33	0.15
	60-100cm	10	81	9	Silt	1.38	0.34 0.31	0.12 0.14

585

586 4.1.3 Soil moisture content

Moisture content, rainfall and irrigation amounts are depicted for the five layers 587 and the four fields in 2017 and two fields in 2018 in Fig. 5. Blue closed spheres 588 indicate that the moisture content was determined on cored soil samples (Figs. 5a, b, 589 c, e, f) and close-spaced spheres when the hydra probe was used (Fig. 5d). The 590 moisture contents were near saturation when irrigation water was added and 591 subsequently decreased due to crop transpiration and soil evaporation (Fig. 5). In all 592 cases, the moisture contents during the main growing period remained above the 593 moisture content at -33 kPa that ranged from 0.25 cm³ cm⁻³ to 0.34 cm³ cm⁻³ for the 594

595 60-80 cm depth (Table 2, Fig.5). Only after the last irrigation and during harvest of the 596 crop did the moisture content in the top 0-40 cm for maize and 0-60 cm for sunflower 597 decrease below the moisture content at -33 kPa. During the growing season, the 598 variation of moisture content was greater in the top 60 cm with the majority of the 599 roots than in the lower depths where, after the first irrigation, it remained nearly 600 constant close to saturation.





Figure 5. Observed (blue dots) and simulated soil moisture content of the Shahaoqu
 experimental fields during model calibration (a,b,c) and validation (d,e,f)



604

Figure 6. Observed (blue dots) and simulated soil salinity concentration of the experimental fields in Shahaoqu during model calibration (a,b,c) and validation (d,e,f).

607 4.1.4 Salinity

Overall the salt concentration is greatest at the surface and increases at all depths during the growing season. Sunflower is more salt tolerant than maize and the overall salt concentration was greater in the sunflower fields (Fig. 6) at comparable times of the crop development for field B but not for field C. Comparing the salt concentration and soil moisture patterns (Fig.5), we note that they behave similarly but opposite to each other (Fig. 6). The soil salinity concentration was decreasing during an irrigation event due to dilution and then gradually increasing partly due to evaporation of the water. Some of the soil salt was transported to the layers below during irrigation and some salt was moving upward with the evaporation from the surface. As expected, after the harvest, the autumn irrigation decreased the salt concentration from fall 2017 to spring 2018.

4.1.5 Groundwater observations

The variation in groundwater depth during the growing season was very similar 620 for both years and in all fields. The groundwater depth for all fields was between 50 621 622 and 100 cm from the surface after an irrigation event and then decreased to around 150 cm before the next irrigation or rainfall (Fig.7). Only after the last irrigation in 623 August 2017 did the water table decrease to below 250 cm and to around 200 cm in 624 625 2018. Field D followed the same pattern but the groundwater was more down from the surface. In several instances, the groundwater table increased without an 626 irrigation or rainfall event in sunflower field C (Fig. 7c and 7e). This was likely related 627 to an irrigation event either from an irrigation in nearby field that affected the overall 628 water table or an accidental irrigation that was not properly documented. We 629 estimated the amount of irrigation water based on the change in moisture content in 630 the soil profile (orange bars in Fig. 7c and 7e). Finally, there was a notable rise in the 631 water table of an mean 375mm "autumn irrigation" after harvest between the end of 632 2017 (Figs. 7 a, b, c) and the beginning of 2018 (Figs. 7 d, e, f), which is a common 633 practice in the Jiefangzha irrigation district to leach the salt that has accumulated in 634 the profile during the growing periods. 635

Note that in Fig. 7, after an irrigation event, the groundwater depth was between 50-80 cm while the whole profile was saturated (Fig. 5). This is directly related to the bubbling pressure of the water. After the irrigation event stopped, the water table was likely at the surface but then immediately decreased because a small amount of evaporated water will bring the water table down to a depth of approximately equal to the bubbling pressure, φ_b , in Eq. 5. The bubbling pressures are listed in Table 3.

642 4.1.6 LAI and plant height

Plant height and LAI followed the typical growth curve that started slowly to rise
in the beginning, accelerated during the vegetative stage and then became constant
during the seed setting and ripening stages (Fig. 8). In the maturing stage, the leaf
area index decreased.






Figure 7. Observed (blue dots) and simulated groundwater depth of the experimental
 fields in Shahaoqu during model calibration (a, b, c) and validation (d, e, f)






Figure 8. Observed crop height (a) and leaf area index (b) of the experimental field inShahaoqu in 2017 and 2018.

653

4.2 Soil Characteristic curve and drainable porosity

To simulate the soil moisture content and to derive drainable porosity as a function of 655 water table depth, the soil moisture characteristic curves were derived by plotting the 656 observed soil moisture content in 2017 and 2018 versus the height above the water 657 table to the soil surface for the five soil layers in Fig. 9. The Brooks-Corey equation 658 (Brooks and Corey, 1964) was fitted through outer envelope of the points. The 659 parameters of the Brooks-Corey equation were adjusted through a trial and error to 660 obtain the best fit (Table 3a). In Fig. 9, points on the left side of the soil moisture 661 characteristic curve (moisture content smaller than the field capacity) were due to 662 water removal at times when evaporative demand was greater than the upward water 663 flux. Under these conditions the conductivity is limiting in the soil and there is no 664 relationship between groundwater depth and matric potential. Since we take the 665 water table depth as proxy for matric potential, these points are omitted when drawing 666 the soil characteristic curve. The few points at the right of the soil moisture 667 characteristic curve indicate the soil moisture was greater than field capacity and 668

669 matric potential and groundwater were not yet at equilibrium after an irrigation event.

The fitted parameter values are consistent. Field A had a greater bubbling pressure and moisture content at -33 kPa than the other fields indicating that this field had more clay. This was confirmed by the data in Table 2. For fields B, C and D, the bubbling pressure was greater at the 60-80 cm depth or the 80 -100 cm depth, which was also in accordance with the data in Table 2.

Table 3a Calibrated soil hydraulic parameters in the Brooks and Corey soil moisture


Field	Parameter	0-20cm	20-40cm	40-60cm	60-80cm	80-100cm
A	θs	0.4	0.36	0.43	0.45	0.47
	$oldsymbol{arphi}_{b}$	80	100	90	70	50
	λ	0.18	0.21	0.22	0.18	0.15
В	θs	0.35	0.37	0.41	0.4	0.4
	$oldsymbol{arphi}_{b}$	50	55	33	60	55
	λ	0.14	0.11	0.16	0.2	0.2
С	θs	0.38	0.37	0.39	0.71	0.43
	$oldsymbol{arphi}_{b}$	55	50	40	60	40
	λ	0.26	0.24	0.2	0.18	0.13
D	θs	0.4	0.36	0.45	0.45	0.44
	$oldsymbol{arphi}_b$	50	40	55	50	50
	λ	0.21	0.2	0.3	0.17	0.15

676 characteristic curve.

Note: θ_s is the soil moisture at saturation (cm³cm⁻³), φ_b is bubbling pressure (cm), λ is the pore size distribution index.

Table 3b Calibrated groundwater parameters

Field\parameters	А	В	С	D	
а	70	75	110	70	
b	0.02	0.025	0.022	0.015	



681

Figure. 9 Soil moisture characteristic curves of five soil layers in the experimentalfields. The pink line is the fit with the Brooks-Corey equation.


684

685 4.3 Parameters sensitivity analysis

The results of sensitivity analysis of the 15 input parameters on 5 output parameters are shown in Fig. 10. The evaluated output parameters are soil moisture content, groundwater depth, soil salinity concentration, field evapotranspiration, and crop leaf area index (LAI). Steeper lines indicate a greater sensitivity of the parameter.

The results of the sensitivity analysis show that moisture content predictions (Fig. 690 10a) are the most sensitive to the input value of the saturated moisture content (θ_s). 691 None of the other parameters are very sensitive. This includes the shape parameters 692 for the soil characteristic curve, bubbling pressure φ_b , and the exponent λ . The input 693 parameter with the most sensitivity for groundwater depth (Fig. 10b), is the saturated 694 moisture content as well. Other less sensitive parameters are the exponent b and 695 constant a in Eq. 23 in predicting the upward flux and the bubbling pressure, φ_b , of the 696 soil moisture characteristic curve (Eq. 8a). Likewise, in case of the salinity predictions 697 (Fig. 10c), the saturated moisture content gives the greatest relative change in salt 698 content. Less sensitive, but still important, are the field capacity, θ_{fc} , the bubbling 699 pressure, φ_{b} , and the exponent λ of the soil characteristic curve (Eq. 8a) and b in Eq. 700 23. The sensitive parameters for the leaf area index (LAI) (Fig 10d) are the maximum 701 potential leaf area index, LAImx, and fraction of growing season when leaf area 702 declines (DLAI) followed by total potential heat units required for crop maturation 703 (PHU). Finally, for the evapotranspiration (Fig 10e), the saturated soil moisture 704 content is the most sensitive parameter, and other less sensitive parameters are the 705 exponent *b* and field capacity. 706

Thus, the model output is most sensitive to the input parameters that define the soil hydraulic properties, groundwater flux and crop growth. As expected, since the soil remains near field capacity, the parameters that relate to the reduction of evaporation when the soil dries out are insensitive. When used in the simulation



practices, the model needs to be calibrated and verified to avoid high error from

712 parameters uncertainty.

711

713

Figure. 10 Parameters sensitivity analysis for (a) soil moisture content, (b) groundwater depth, (c) salt salinity concentration, (d) LAI, (e) ET

717 4.4 Model calibration and validation with field data

The model parameters were calibrated and validated using the observed moisture content, groundwater depth, plant height, leaf area index and the calculated

evapotranspiration. The data of sunflower fields B and C and maize field A were collected and used for calibration. Since farmers did not grow maize in 2018, the 2017 data of maize field D, together with sunflower fields B and C in 2018 were used for validation. The optimal parameter set was determined using graphical similarity between observed and predicted results together with near optimum performance of the statistical indicators while keeping all values within physical acceptable ranges.

As a way of reducing the number of parameters that needed to be calibrated, we initially selected one to three most sensitive parameters for each of the observed time series, starting with evapotranspiration (including *LAI* and crop height) followed by moisture content, groundwater depth, and salt content in the soil. This cycle was repeated several times until changes became small. The last stage of the calibration consisted of fine-tuning the remaining least sensitive parameters.

the CROP То calibrate the parameters in module, calculated we 732 evapotranspiration during the crop growth period with the observed soil moisture 733 content and groundwater depth by the soil water balance method. In addition, we 734 used the observed LAI measurements in 2017 and plant height in both 2017 and 735 2018. LAI was not measured in 2018. The DLAI, LAI_{mx} and H_{mx} in the crop module 736 were adjusted to fit the observed LAI and crop height values. In addition, we fitted the 737 θ_{fc} moisture content to obtain a good fit of the evapotranspiration. The saturated 738 moisture content values were not adjusted since they were already determined for 739 fitting the soil characteristic curve. The exponent b and constant a in Eq. 23 were 740 adjusted to fit the observed soil moisture content and groundwater depth. 741

4.4.1 Evapotranspiration, crop height and leaf area index

The predicted evapotranspiration and that calculated from the mass balance 743 show a good agreement with Nash Sutcliff values ranging from 0.96-0.89 during 744 calibration and validation (Fig. 11 and Table 4). The calibrated predictions of plant 745 height fitted the observed values well during calibration and validation with Nash 746 Sutcliff values ranging from 0.77-0.96 for the individual fields (Table 4) and over 90% 747 when the data was pooled for the fields during calibration and validation (Fig.12). LAI 748 was not measured in 2018. During calibration, Nash Sutcliff predicted LAI values 749 were good for sunflower but not as good for maize but the coefficient of determination 750 and slope in the regression were acceptable (Table 4, Fig. 13). In addition, the overall 751 trend was predicted reasonably well (Fig. 13b). 752




Figure 11. Comparison of predicted and observed actual evapotranspiration: a) Calibration and b) Validation




Figure 12. Comparison of predicted and observed crop height: a) Calibration and b)Validation




Figure 13. Comparison of predicted and observed LAI: a) Calibration and b) validation

Table 4 Model error statistics for calibration and validation of model in 2017 and 2018

(Mean relative error, MRE; root mean square error, RMSE; Regression slope;

⁷⁷⁰ Coefficient of determination, R²; Regression coefficient, slope).

Process	Field	Variable	MRE (%)	RMSE (cm ³ cm ⁻³ cm or gL ⁻¹ or mm)	NSE	R²	Regre ssion coeffici entslo pe
	2017 Field A (maize)	SWC (0-1m)	2.9	0.04	0.8	0.56	1.01
		GWD	4.5	33.8	0.64	0.64	0.97
		LAI	-17.4	0.78	0.11	0.92	0.89
		hcrop	0.04	16.2	0.95	0.99	0.97
		C (0-1m)	13.9	0.5	*	0.49	1.07
	2017 Field B	SWC (0-1m)	-1.2	0.04	0.71	0.74	0.97
		GWD	6.0	22.9	0.86	0.98	0.96
Calibration		LAI	4.7	0.58	0.9	0.92	0.91
	(sunflower)	hcrop	6.8	33.5	0.83	0.96	1.1
		C (0-1m)	11.0	0.55	*	0.7	1.1
	2017 Field C (sunflower)	SWC (0-1m)	8.5	0.04	0.88	0.9	1.05
		GWD	-7.3	19.1	0.91	0.94	0.94
		LAI	48.6	1.0	0.59	0.93	1.29
		hcrop	5.42	27.4	0.88	0.98	1.07
		C (0-1m)	-1.6	0.52	*	0.08	0.94
		ETa	12.2	40.5	0.92	0.96	1.11
	2018 Field B (sunflower)	SWC (0-1m)	-2.3	0.03	0.43	0.68	0.98
		GWD	4.86	16.1	0.83	0.84	1.01
		hcrop	12.5	26.9	0.86	0.99	0.95
		C (0-1m)	4.0	0.35	*	0.72	1.06
	2018 Field C (sunflower)	SWC (0-1m)	17.3	0.06	0.64	0.72	1.04
		GWD	2.1	13.8	0.86	0.87	1.01
Validation		hcrop	-10.3	36.4	0.77	0.97	0.84
		C (0-1m)	0.51	0.33	*	0.73	1.02
	2017 Field D (maize)	SWC (0-1m)	6.1	0.04	0.68	0.77	1.05
		GWD	0.64	39.1	0.52	0.71	1.01
		LAI	-10.7	0.79	-0.02	0.58	0.93
		hcrop	-1.7	13.6	0.96	0.98	1
		C (0-1m)	9.8	0.51	*	0.54	1.11
		ETa	8.0	42.4	0.89	0.89	0.95

Note: * Relative bias was over 5% invalidating the calculation of NSE. SWC is the soil

moisture content, GWD is the groundwater depth, LAI is the leaf area index, hcrop is

the height of the crop, C is the soil salinity concentration, ETa is the actual

evapotranspiration.

4.4.2 Soil moisture and groundwater depth

Next, the moisture contents and groundwater table were fitted with the parameters in 776 the Vadose model without changing the parameters in the CROP module. Saturated 777 moisture content was the most sensitive parameter for calibrating the moisture 778 779 content (Fig.10a). Since this value was already determined a priori from the soil characteristic curve (Table 3a), we could not use other parameters to obtain a better 780 fit since none were sensitive (Fig.10a). Therefore, we calibrated the groundwater 781 parameters (i.e., a and b parameters (Eq. 23)) together with the moisture content to 782 783 obtain the best fit for both. The fitted a and b values are listed in Table 3b. The fitted parameters between the four experimental fields were similar but not the same. This 784 can be expected in river plains where soils can vary over short distances. 785

786 Overall, the moisture contents were predicted well during calibration and validation (Figs. 5, 14 and Table 4) with the exception of field B during validation 787 (Table 4) with a NSE of 0.43. The moisture contents were predicted most accurately 788 in the layers from 40-100cm where the soil moistures were at field capacity during 789 most of the growing season (Fig. 14). In the top 40 cm, the predicted soil moisture 790 content deviated from observed moisture contents, especially at the dryer end (Fig. 5 791 and 14). Unlike at deeper depths, evapotranspiration determined the moisture 792 contents at shallow depths. Prediction of evapotranspiration introduced additional 793 uncertainties such as the distribution of the root system. This uncertainty is also likely 794 795 the reason why the 2018 moisture contents during the validation are acceptable but not predicted as well as in 2017. 796




Figure 14. Comparison of predicted and observed soil moisture content: a) calibrationand b) validation

800

797

The predicted and observed groundwater depths are in good agreement during both calibration and validation (Figs 7, 15). The MRE values were within $\pm 10\%$ and the NSE values ranged from 0.52 for field D during validation to 0.91 in field C during calibration where some of the recharge events were estimated (Table 4).






Figure 15. Comparison of predicted and observed groundwater depth a) calibration and b) validation.



The only parameter that could be adjusted each year for calibration of the salt 809 concentrations was the initial salt concentration. The predicted salt concentrations in 810 the top layers decreased after an irrigation event similar to the limited observed values 811 (Figs. 6). Despite that the salt concentration fitted visually reasonably well as shown in 812 Figures 6 and 16, there was a bias of 8% in the data and consequently the Nash 813 Sutcliff efficiency could not be applied (Table 4) (Ritter and Muñoz-Carpena, 2013). 814 Similarly to the moisture contents, the salt concentrations in the layers below 40 cm 815 were predicted more accurately than the layers above the 40 cm. More data should be 816 collected during the whole year on the salt concentrations in the soil in order to 817 accurately predict the salt concentrations. 818



819

Figure 16. Comparison of predicted and observed salt concentration during calibration (a) and validation (b)

822 **5. Discussion**

The EPICS model is a surrogate model that can be applied in areas with shallow groundwater. It can simulate the soil moisture content and salt concentration for layers in the soil, the groundwater depth, upward movement of water from groundwater, evapotranspiration, and plant growth.

The model is different from traditional models that are based on Richards 827 equation; instead of calculating the fluxes first, in the EPICS model, the groundwater 828 depth is calculated first based either on the amount of water removed by 829 evapotranspiration on days without rain or irrigation or recharge to groundwater on 830 the other days. Subsequently, when the groundwater is sufficiently shallow and the 831 potential upward flux from the groundwater is greater than the evaporative demand, 832 the moisture contents are adjusted so that soil moisture and groundwater depth are in 833 equilibrium (i.e., field capacity). In this case, the matric potential is equal to the height 834 above the water table and the moisture contents can be found with the soil 835 characteristic curve. When the upward flux is less than the evaporative demand of the 836 atmosphere and crop, the difference between the upward moisture content is 837 determined by first decreasing the moisture content below the field capacity. The flux 838 of water in the soil is then calculated based on the changes in water content. The 839 advantage is fewer input parameters needed when compared with other numerical 840 models (Šimůnek et al., 1996; Dam et al., 1997). For example, the hydraulic 841 conductivity is not used in EPICS. 842

Although the uncertainties of field experimental observations and input data of the model affected the accuracy of simulation results, EPICS compares well with other models. Xu et al. (2015) tested the SWAP-EPIC for two lysimeters grown with maize on the same experimental farm in the Hetao irrigation district where our experiment was carried out. The SWAP model solves the Richards' Equation

numerically with an implicit backward scheme and is combined by Xu et al. (2015) 848 with the EPIC model. The accuracy of our simulation results, despite the difference in 849 complexity, are very similar. The moisture contents were simulated slightly better with 850 EPICS, the groundwater depth was nearly the same, and the LAI values were 851 predicted more accurately in the SWAP-EPIC model. Xue et al. (2015) did not 852 simulate the salt content of the soil. Compared to less data and computational 853 intensive models that are applied in the Yellow River, the soil moisture content were 854 simulated more accurately by EPICS than in the North China Plain with 30 m deep 855 groundwater by surrogate models of Kendy et al. (2003) and Yang et al. (2015 a,b) 856 and in the Hetao irrigation district by Gao et al. (2017b) and Xue et al. (2018) during 857 the crop growth period. 858

To obtain more accurate results in the future, the upward capillary flux from groundwater needs to be improved. The salinity of irrigation source water also needs to be measured, especially for the areas irrigated by groundwater or the hydrologically closed basins. In addition, the evapotranspiration measured independently, using Eddy covariance (Zhang et al., 2012; Armstrong et al., 2008) and Bowen ratio-energy balance method (Zhang et al., 2007) should be further used to test performance of the model in the future study.

The limitation of the EPICS model is it can only be applied in areas where groundwater is generally less than 3.3 m deep. When the groundwater is deeper than 3.3 m, the field capacity of the surface soil is determined by the moisture content when the hydraulic conductivity becomes limiting and not by the depth of the

870 groundwater.

Overall, the present model has the advantage that it greatly simplifies the calculation of the moisture content, groundwater depth and salt content and despite that, gives results similar to or better than other models applied in the Yellow river basin.

875 6. Conclusions

A novel surrogate field hydrological model called Evaluation of the Performance 876 of Irrigated Crops and Soils (EPICS) was developed for irrigated areas with shallow 877 groundwater. The model was tested with two years experimental data collected by us 878 for sunflower and one year of maize on replicated fields in the Hetao irrigation district, 879 a typical arid to semi-arid irrigation district with a shallow aquifer. The EPICS model 880 uses the soil moisture characteristic curve, upward capillary flux, and groundwater 881 depth to derive the drainable porosity and predict the soil moisture contents and 882 salinity. The evaporative flux is calculated with equations in EPIC (Environmental 883 Policy Integrated Climate) and root distribution equation. 884

The simulation results show that the EPICS model can predict the soil moisture content and salt concentration in different soil layers, groundwater depth, and crop growth on a daily time step with acceptable accuracy during calibration and validation. The saturated soil moisture content is the most sensitive parameter for soil moisture content, salt concentration, and ET in our model.

890 In the future, the model should be tested in other areas with shallow groundwater 891 that can be found in surface irrigated sites and in humid climates in river plains. Once

fully tested, the EPICS model can be used for optimizing water use at the local scale
but, more importantly, on a watershed scale in closed basins where every drop of
water counts.

895

Data availability: The observed data used in this study are not publicly accessible.
These data have been collected by personnel of the College of Water Resources and
Civil Engineering, China Agricultural University, with funds from various cooperative
sources. Anyone who would like to use these data, should contact Zhongyi Liu,
Xianghao Wang and Zailin Huo to obtain permission.

Author contributions: LZ and XW collected the data. ZL, ZH, CW, GH, XX and TS
contributed to the development of the model. The simulations with the model were
done by ZL, ZH and TS. Preparation and revision of the paper were done by ZL under
the supervision of TS and ZH.

Competing interests: The authors declare that they have no conflicts of interest.

Acknowledgements: Peggy Stevens helped greatly with polishing the English. We
 thank Xianghao Wang and Limin Zhang and the technicians in the Shahaoqu
 experimental station who helped in collecting data.

Financial support: This study has been supported by National Key Research and
Development Program of China (2017YFC0403301, 2016YFC0400107) and the
National Natural Science Foundation of China (No. 51639009, 51679236).

912

913

References

Abrahart, R.J and See, L.: Comparing neural network and autoregressive moving 915 average techniques for the provision of continuous river flow forecasts in two 916 contrasting catchments. Hydro. Processes, 14: 2157-2172. http: // 917 doi.org/10.1002/1099-1085(20000815/30)14:11/12<2157::AID-HYP57>3.0.CO;2 918 -S. 2000. 919

- Allen, R.G., Pereira, L.S., Raes, D., and Smith, M.: Crop evapotranspiration.
 Guidelines for computing crop water requirements-FAO Irrigation and Drainage
 Paper 56, FAO, Rome. 1998
- Armstrong, R.N., Pomeroy, J. W., Martz, L.W.: Evaluation of three evaporation
 estimation methods in a Canadian prairie landscape. Hydrol. Process, 22(5):
 2801-2815. https:// doi.org/ 10.1002/hyp.7054. 2008.
- Asher, M.J., Croke, B.F.W., Jakeman, A.J. and Peeters, L.J.M.: A review of surrogate
 models and their application to groundwater modeling. Water Resour Res,
 51:5957-5973. http://doi.wiley.com/10.1002/2015 WR016967. 2015.Blanning, R.
 W., The construction and implementation of metamodels, Simulation, 24(6):
 177-184. https:// doi.org/10.1177/003754977502400606.1975.
- Babajimopoulos, C., Panoras, A., Georgoussis, H., Arampatzis, G., Hatzigiannakis, E.,
 Papamichail, D.: Contribution to irrigation from shallow water table under field
 conditions. Agr. Water Manage. 92:2015-210. https://doi.org/
 10.1016/j.agwat.2007.05.009
- 935
- Brooks, R.H., and Corey, A.T.: Hydraulic properties of porous media, Hydrology
 Paper 3. Colorado State University. Fort Collins, Colorado, 37pp, 1964.
- Blanning, R.W.: Construction and Implementation of Metamodels. Simulation,
 24(6):177-184. https:// doi.org/ 10.1177/003754977502400606. 1975.
- Chen, C., Wang, E., and Yu, Q.: Modelling the effects of climate variability and water
 management on crop water productivity and water balance in the North China
 Plain. Agr. Water Manage., 97:1175-1184. https://
 doi.org/10.1016/j.agwat.2008.11.012. 2010.
- Chen, S., Huo, Z., Xu, X., Huang, G.: A conceptual agricultural water productivity
 model considering under field capacity soil water redistribution applicable for arid
 and semi-arid areas with deep groundwater, Agr Water Manage, 213, 309-323.
 https:// doi.org/10.1016/j.agwat.2018.10.024. 2019.

- Cloke, H., Pappenberger, F., Renaud, J.: Multi-Method Global Sensitivity Analysis
 (MMGSA) for modelling floodplain hydrological processes. Hydrol Process, 22(1):
 1660-1674. https:// doi.org/ 10.1002/hyp.6734. 2008.
- Cuo, L., Giambelluca, T., Ziegler, A.: Lumped parameter sensitivity analysis of a
 distributed hydrological model within tropical and temperate catchments. Hydrol
 Process, 25(15): 2405-2421. http://doi.org/ 10.1002/hyp.8017. 2011.
- Dam, JC. Van., Huygen, J, Wesseling, JG, Feddes, RA., Kabat, P., Walsum, PEV. 954 Van., Groenendijk, P., Diepen.: Theory of SWAP version 2.0. Simulation of water 955 flow, solute transport and plant growth in the soil-water-atmosphere-plant 956 environment. Report 71, Department Water Resources, Wageningen Agricultural 957 Technical document 45, Winand 958 University. DLO Staring Centre. Wageningen, 152pp, 1997. 959
- Dawson, C.W., Abrahart, R.J., Shamseldin, A.Y., Wilby, R.L.: Flood estimation at
 ungauged sites using artificial neural networks. J Hydrol.319: 391-409.
 http://doi.org/10.1016/.jhydrol.2005.07.032. 2006.
- Dehaan, R., and Taylor, G.: Field-derived spectra of salinized soils and vegetation as
 indicators of irrigation-induced soil salinization, Remote Sens Environ, 80(3),
 406-417. https:// doi.org/10.1016/S0034-4257(01)00321-2. 2002.
- Delonge, K. C., Ascough, J. C., Andales, A. A., Hansen, N. C., Garcia, L. A., Arabi, M.:
 Improving evapotranspiration simulations in the CERES-Maize model under
 limited irrigation. Agr Water Manage, 115: 92-103. http://doi.org/
 10.1016/j.agwat.2012.08.013. 2012.
- Doherty, J. and Simmons C.: Groundwater modelling in decision support: reflections
 on a unified conceptual framework, Hydrogeol. J, 21(7), 1531-1537. https://
 doi.org/10.1007/s10040-013-1027-7. 2013.
- Feng, Z., Wang, X., Feng, Z.: Soil N and salinity leaching after the autumn irrigation
 and its impact on groundwater in Hetao Irrigation District, China. Agr Water
 Manage, 71(2): 131-143. https:// doi.org/10.1016/j.agwat.2004.07.001. 2005.
- Flint, A.L., Flint, L.E., Kwicklis, E.M., Fabryka-Martin, J.T., and Bodvarsson, G.S.:
 Estimating recharge at Yucca Mountain, Nevada, USA: comparison of methods.
 Hydrogeol. J., 10:180-204. https:// doi.org/ 10.1007/s10040-001-0169-1. 2002.

- Gao, X., Huo, Z., Bai, Y., Feng, S., Huang, G., Shi, H., and Qu, Z.: Soil salt and
 groundwater change in flood irrigation field and uncultivated land: a case study
 based on 4-year field observations. Environ. Earth Sci., 73:2127-2139. https://
 doi.org/10.1007/s12665-014-3563-4. 2015.
- Gao, X., Huo, Z., Qu, Z., Xu, X., Huang, G., and Steenhuis, T.S.: Modeling
 contribution of shallow groundwater to evapotranspiration and yield of maize in
 an arid area. Sci. Rep-UK 7. https:// doi.org/10.1038/srep43122. 2017.
- Gardner, W.: Some study-state solutions of the unsaturated moisture flow equation
 with application to evaporation from a water table. Soil Sci., 85:228-232. 1958.
- Gardner, W., Hillel, D., and Benyamini, Y.: Post-Irrigation Movement Soil Water 1.
 Redistribution. Water Resour Res., 6:851-860. https:// doi.org/
 10.1029/WR006i003p00851. 1970a.
- Gardner, W., Hillel, D., and Benyamini, Y.: Post-Irrigation Movement of Soil Water 2.
 Simultaneous Redistribution and Evaporation. Water Resour Res., 6:1148-1153.
 https:// doi.org/ 10.1029/WR006i004p01148. 1970b.
- Guo, S., Ruan, B., Chen, H., Guan, X., Wang, S., Xu, N. and Li, Y.: Characterizing the
 spatiotemporal evolution of soil salinization in Hetao Irrigation District (China)
 using a remote sensing approach. Int J Remote Sens 39: 6805-6825. https://
 doi.org/10.1080/01431161.2018.1466076. 2018.
- Hanson, B., Hopmans, J., Šimůnek, J.: Leaching with Subsurface Drip Irrigation
 under Saline, Shallow Groundwater Conditions. Vadose Zone J. 7, 810-818.
 http://doi.org/10.2136/vzj2007.00532008. 2008.
- Hsiao, T., Heng, L., Steduto, P., Rojas-Lara, B., Raes, D., Fereres, E.: AquaCrop-The
 FAO Crop Model to Simulate Yield Response to Water: III. Parameterization and
 Testing for Maize. Agron. J, 101(3):448-459. https:// doi.org/
 10.2134/agronj2008.0218s. 2009.
- Hu, S., Shi, L., Huang, K., Zha, Y., Hu, X., Ye, H., Yang, Q.: Improvement of
 sugarcane crop simulation by SWAP-WOFOST model via data assimilation.
 Field Crop Res., 232: 49-61. https:// doi.org/10.1016/j.fcr.2018.12.009. 2019.
- Huang, Q., Xu, X., Lu, L., Ren, D., Ke, J., Xiong,Y., Huo, Z. and Huang, G.: Soil salinity distribution based on remote sensing and its effect on crop growth in

Hetao Irrigation District. Transactions of the Chinese Society of AgriculturalEngineering, 34:102-109. 2018.

Kendy, E., Gérard-Marchant, P., Walter, M. T., Zhang, Y., Liu, C., and Steenhuis, T.S.:
 A soil-water-balance approach to quantify groundwater recharge from irrigated
 cropland in the North China Plain. Hydrol. Process., 17:2011-2031. https://
 doi.org/10.1002/hyp.1240. 2003.

- Leube, P. C., : Temporal moments revisited: Why there is no better way for physically
 based model reduction in time, Water Resour Res, 48(11): W11527. https://
 doi.org/10.1029/2012WR011973 2012.
- Li, J., Pu, L., Han, M., Zhu, M., Zhang, R., Xiang, Y.: Soil salinization research in
 China: Advances and prospects, J Geogr Sci, 24(5), 943-960. https:// doi.org/
 10.1007/s11442-014-1130-2 .2014
- Letey, J., Hoffman, G.J., Hopmans, J.W., Grattan, S.R., Suarez, D., Corwin, D.L.,
 Oster, J.D., Wu, L., Amrhein, C.: Evaluation of soil salinity leaching requirement
 guidelines. Agric. Water Manag. 98, 502–506.
 https://doi.org/10.1016/j.agwat.2010.08.009. 2011.
- Li, X., Zhao, Y., Xiao, W., Yang, M., Shen, Y., Min, L.: Soil moisture dynamics and implications for irrigation of farmland with a deep groundwater table. Agr. Water Manage.,192:138-148. https:// doi.org/ 10.1016/j.agwat.2017.07.003.2017.
- Liu, J.: A GIS-based tool for modelling large-scale crop-water relations. Environ
 Modell Softw. 24(3): 411-422. https:// doi.org/ 10.1016/j.envsoft.2008.08.004.
 2009.
- Liu, Z., Wang, X., Huo, Z, Steenhuis, T.S.: A unique vadose zone model for shallow aquifers: the Hetao irrigation district, China. Hydrol Earth Syst Sc. 23(7):3097-3115. https:// doi.org/ 10.5194/hess-23-3097-2019. 2019.
- Luo, Y., and Sophocleous, M.: Seasonal groundwater contribution to crop-water use assessed with lysimeter observations and model simulations. J. Hydrol, 389:325-335. https:// doi.org/10.1016/j.jhydrol.2010.06.011. 2010.
- Ma, Y., Feng, S., and Song, X.: A root zone model for estimating soil water balance
 and crop yield responsesto deficit irrigation in the North China Plain. Agr. Water
 Manage., 127:13-24. https:// doi.org/10.1016/j.agwat.2013.05.011. 2013.

- Miao, Q., Rosa, R., Shi, H., Paredes, P., Zhu, L., Dai, J., Goncalves, J., Pereira, L.:
 Modeling water use, transpiration and soil evaporation of spring wheat-maize
 and spring wheat-sunflower relay intercropping using the dual crop coefficient
 approach. Agr Water Manage, 165:211-229.
- 1045 https://doi.org/10.1016/j.agwat.2015.10.024.2016.
- Minhas, P., Ramos, T., Ben-Gal., A., Pereira, L.: Coping with salinity in irrigated
 agriculture: Crop evapotranspiration and water management issues. Agr Water
 Manage, 227, 105832. https://doi.org/ 10.1016/j.agwat.2019.105832. 2020.
- Moriasi, D. N., Arnold, J. G., Van Liew, M. W., Bingner, R. L., Harmel, R. D., Veith, T.
 L.: Model evaluation guidelines for systematic quantification of accuracy in
 watershed simulations. T ASABE, 50(3): 885-900. 2007.
- Nash, J.E., and Sutcliffe, J.V.: River flow forecasting through conceptual models part I
 a discussion of principles. J Hydrol. 10:282-290. 1970.
- 1054 Novark, V.: Estimation of Soil-water Extraction Patterns by Roots, Agr Water Manage,
 1055 12(4), 271-278. https:// doi.org/10.1016/0378-3774(87)90002-3. 1987
- Phogat, V., Mallants, D., Cox, J., Šimůnek, J., Oliver, D., Awad, J.: Management of
 soil salinity associated with irrigation of protected crops. Agr. Water Mange.,
 227:105845. https://doi.org/10.1016/j.agwat.2019.105845.2020.
- Raes, D., Steduto, P., Hsiao, T., Fereres.: AquaCrop-The FAO Crop Model to
 Simulate Yield Response to Water: II. Main Algorithms and Software Description,
 Agron. J, 101(3), 438. https:// doi.org/10.2134/agronj2008.0140s.2009.
- Regis, R., and Shoemaker, C.: Constrained Global Optimization of Expensive Black
 Box Functions Using Radial Basis Functions, J Global Optim, 31(1), 153-171.
 https:// doi.org/10.1007/s10898-004-0570-0. 2005.
- Ren, D., Xu, X., Hao, Y., and Huang, G.: Modeling and assessing field irrigation water
 use in a canal system of Hetao, upper Yellow River basin: Application to maize,
 sunflower and watermelon. J. Hydrol, 532:122-139. https://
 doi.org/10.1016/j.jhydrol.2015.11.040. 2016.
- Ren, D., Xu, X., Romos, T., Huang, Q., Huo, Z., Huang, G.: Modeling and assessing
 the function and sustainability of natural patches in salt-affected
 agro-ecosystems: Application to tamarisk (Tamarix chinensis Lour.) in Hetao,
 upper Yellow River basin. J. Hydrology.

- 1073 532:490-504.https://doi.org/10.1016/j.jhydrol.2017.04.054.2017.
- 1074 Rengasamy, P.: World salinization with emphasis on Australia, J Exp. Bot., 57(5),
 1017-1023. https:// doi.org/10.1093/jxb/erj108 .2006
- 1076 Rhoades, J., Manteghi, N., Shouse, P., Alves, W.: Soil Electrical Conductivity and
 1077 Soil Salinity: New Formulations and Calibrations, Soil Sci. Soc. Am. J., 53(2):
 1078 433-439. https:// doi.org/ 10.2136/sssaj1989.03615995005300020020x. 1989.
- Ritter, A., and Muñoz-Carpena, R.: Performance evaluation of hydrological models:
 Statistical significance for reducing subjectivity in goodness-of-fit assessments. J
 Hydrol., 480:33-45. 2013.htt p:// doi.org/ 10.1016/j.jhydrol.2012.12. 004. 2013.
- Rosa, R.D., Paredes, P., Rodrigues, G.C., Alves, I, Fernando, R.M., Pereira, L.S.,
 Allen, R.G.: Implementing the dual crop coefficient approach in interactive
 software. 1. Background and computational strategy. Agr. Water Manage., 103:
 8-24. https:// doi.org/10.1016/j.agwat.2011.10.013. 2012.
- Sau, F., Boote, K., Bostick, W., Jones, J., Minguez, M.,: Testing and improving
 evapotranspiration and soil water balance of the DSSAT crop models. Agron. J.,
 96: 1243-1257. https:// doi.org/ 10.2134/agronj2004.1243. 2004.
- Shelia, V., Simunek, J., Boote, K., Hoogenbooom, G.: Coupling DSSAT and
 HYDRUS-1D for simulations of soil water dynamics in the soil-plant-atmosphere
 system. J Hydrol Hydromech., 66(2): 232-245. https://
 doi.org/10.1515/johh-2017-0055. 2018.
- Šimůnek, J., Šejna, M. and van Genuchten, M.T.: The HYDRUS-1D software
 package for simulating the one-dimensional movement of water, heat, and
 multiple solutes in variably-saturated media. Version 2.0. IGWMC-TPS-70. Int.
 Groundwater Modeling Ctr., Colorado Schoolof Mines, Golden. 1998.
- Steduto, P., Hsiao, T., Raes, D., Fereres, E.: AquaCrop-The FAO Crop Model to
 Simulate Yield Response to Water: I. Concepts and Underlying Principles. Agron
 J., 101(3):426-437. https:// doi.org/10.2134/agronj2008.0139s. 2009.
- Steenhuis, T., Richard, T., Parlange, M., Aburime, S., Geohring, L., PArlange, J.:
 Preferential Flow Influences on Drainage of Shallow Sloping Soils. Agr Water
 Manage., 14(1-4):137-151. https:// doi.org/ 10.1016/0378-3774(88)90069-8.
 1988.

- Uehara, G.: Technology-transfer in the tropics. Outlook Agr., 18(1): 38-42. https://
 doi.org/ 10.1177/003072708901800107. 1989.
- Van Diepen, C., Wolf, J., van Keulen, H., Rappoldt, C.: WOFOST A STIMULATION
 MODEL OF CROP PRODUCTION. Soil Use and Management, 5(1): 16-24.
 1989.
- Wallender, W. , Tanji, K. : Agricultural salinity assessment and management.
 Agricultural salinity assessment and management. Ed.2. American Society of
 Civil Engineers (ASCE), Reston, USA. University of California-Davis, USA.:
 xxx+1094pp. 2011.
- Wang, X., Huang, G., Yang, J., Huang, Q., Liu, H., Yu, L.: An assessment of irrigation
 practices: Sprinkler irrigation of winter wheat in the North China Plain. Agr Water
 Manage., 159: 197-208. https:// doi.org/ 10.1016/j.agwat.2015.06.011. 2015.
- Wang, J., Huang, G., Zhan, H., Mohanty, B., Zheng, J., Huang, Q., Xu, X.: Evaluation
 of soil water dynamics and crop yield under furrow irrigation witha
 two-dimensional flow and crop growth coupled model. Agr Water Manage., 141:
 10-22. https:// doi.org /10.1016/j.agwat.2014.04.007. 2014.
- Wu, X., Zheng, Y., Wu, B., Tian, Y., Han, F., Zheng, C.: Optimizing conjunctive use of
 surface water and groundwater for irrigation to address human-nature water
 conflicts: A surrogate modeling approach. Agr Water Manage, 163(1): 380-392.
 https:// doi.org/10.1016/j.agwat.2015.08.022. 2016.
- Williams, J., Jones, C., Kiniry, J., and Spanel, D.: The EPIC Crop Growth Model. T.
 ASAE, 32:479-511. 1989.
- Willcox, K., and Peraire J.: Balanced Model Reduction via the Proper Orthogonal
 Decomposition, AIAA J, 40(11), 2323-2330. https:// doi.org/10.2514/2.1570.
 2002.
- Xu, X., Sun, C., Qu, Z., Huang, Q., Ramos, T.B., and Huang, G.: Groundwater
 Recharge and Capillary Rise in Irrigated Areas of the Upper Yellow River Basin
 Assessed by an Agro-Hydrological Model. Irrig. Drain., 64:587-599. https://
 doi.org/10.1002/ird.1928. 2015.
- Xu, X., Sun, C., Huang, G., Mohanty, B.: Global sensitivity analysis and calibration of
 parameters for a physically-based agro-hydrological model. Environ Modell
 Softw., 83: 88-102. https:// doi.org/10.1016/j.envsoft.2016.05.013. 2016.

Xu, X., Huang, G., Sun, C., Pereira, L., Ramos, T., Huang, Q., Hao, Y.: Assessing the
effects of water table depth on water use, soil salinity and wheat yield: Searching
for a target depth for irrigated areas in the upper Yellow River basin. Agr Water
Manage, 125: 46-60. https:// doi.org/10.1016 /j.agwat.2013.04.004. 2013.

Xu, X., Huang, G., Qu, Z., and Pereira, L.S.: Assessing the groundwater dynamics
and impacts of water saving in the Hetao Irrigation District, Yellow River basin.
Agr Water Manage., 98:301-313. https:// doi.org/10.1016/j.agwat.2010.08.025.
2010.

- Xue, J., Huo, Z., Wang, F., Kang, S., and Huang, G.: Untangling the effects of shallow
 groundwater and deficit irrigation on irrigation water productivity in arid region:
 New conceptual model. Sci. Total Environ., 619-620:1170-1182. https://
 doi.org/10.1016/j.scitotenv.2017.11.145 2018.
- Yang, X., Chen, Y., Pacenka, S., Gao, W., Ma, L., Wang, G., Yan, P., Sui, P., and
 Steenhuis, T. S.: Effect of diversified crop rotations on groundwater levels and
 crop water productivity in the North China Plain, J. Hydrol., 522, 428–438,
 https://doi.org/10.1016/j.jhydrol.2015.01.010, 2015a.
- Yang, X., Chen, Y., Pacenka, S., Gao, W., Zhang, M., Sui, P., and Steenhuis, T. S.:
 Recharge and groundwater use in the North China Plain for six irrigated crops for
 an eleven year period, Plos One, 10, e0115269, http://doi.org/10.1371/journal.
 http://doi.org/10.1371/10.1371/journal.pone.0115269, 2015b.
- Yeh, P.J., and Famiglietti, J.S.: Regional groundwater evapotranspiration in Illinois. J.
 Hydrometeorol., 10:464-478. https:// doi.org/ 10.1175/2008JHM1018.1. 2009.
- Zhang, B., Kang, S., Zhang, L., Du, T., Li, S., Yang, X.: Estimation of seasonal crop
 water consumption in a vineyard using Bowen ratio-energy balance method.
 Hydrol. Process, 21(6): 3635-3641. https:// doi.org/ 10.1002/hyp.6568.
- Zhang, F., Zhou, G., Wang, Y., Yang, F., Nilsson, C.: Evapotranspiration and crop
 coefficient for a temperate desert steppe ecosystem using eddy covariance in
 Inner Mongolia, China. Hydrol. Process, 26(3): 379-386. https:// doi.org/
 10.1002/hyp.8136.