

# **Using multiple methods to investigate the effects of land-use changes on groundwater recharge in a semi-arid area**

Shovon Barua<sup>1</sup>, Ian Cartwright<sup>1</sup>, P. Evan Dresel<sup>2</sup>, Edoardo Daly<sup>3</sup>

<sup>1</sup>School of Earth, Atmosphere and Environment, Monash University, Clayton, Victoria 3800, Australia

<sup>2</sup>Agriculture Victoria, Department of Jobs, Precincts and Regions, Bendigo, Victoria 3554, Australia

<sup>3</sup>Department of Civil Engineering, Monash University, Clayton, Victoria 3800, Australia

*Correspondence to:* Shovon Barua (shovon.barua@monash.edu)

## Abstract

Understanding the applicability and uncertainties of methods for documenting recharge rates in semi-arid areas is important for assessing the successive effects of land-use changes and understanding groundwater systems. This study focuses on estimating groundwater recharge rates and understanding the impacts of land-use changes on recharge rates in a semi-arid area in southeast Australia. Two adjacent catchments were cleared ~180 years ago following European settlement and a eucalypt plantation forest was subsequently established ~15 years ago in one of the catchments. Chloride mass balance yields recharge rates of 0.2 to 61.6 mm yr<sup>-1</sup> (typically up to 11.2 mm yr<sup>-1</sup>). The lower of these values probably represent recharge rates prior to land clearing, whereas the higher likely reflects recharge rates following the initial land clearing. The low pre-land clearing recharge rates are consistent with the presence of old groundwater (residence times up to 24,700 years) and the moderate to low hydraulic conductivities (0.31 to 0.002 m day<sup>-1</sup>) of the aquifers. Recharge rates estimated from tritium activities and water table fluctuations reflect those following the initial land clearing. Recharge rates estimated using water table fluctuations (15 to 500 mm yr<sup>-1</sup>) are significantly higher than those estimated using tritium renewal rates (0.01 to 89 mm yr<sup>-1</sup>; typically <14.0 mm yr<sup>-1</sup>) and approach the long-term average annual rainfall (~640 mm yr<sup>-1</sup>). These recharge rates are unrealistic given the estimated evapotranspiration rates of 500 to 600 mm yr<sup>-1</sup> and the preservation of old groundwater in the catchments. It is likely that uncertainties in the specific yield results in the water table fluctuation method significantly overestimating recharge rates and that, despite the land-use changes, the present-day recharge rates are relatively modest. These results are ultimately important for assessing the impacts of land-use changes and management of groundwater resources in semi-arid regions in Australia and elsewhere.

# 1. Introduction

25 Groundwater is a critical resource for meeting the expanding urban, industrial and agricultural  
water requirements, especially in semi-arid areas that lack abundant surface water resources  
(de Vries and Simmers, 2002; Siebert et al., 2010). Groundwater also makes a significant  
contribution to the streamflow of rivers in semi-arid areas. Land-use changes may modify  
groundwater recharge rates, which thus affect groundwater systems as well as groundwater  
30 resources (Foley et al., 2005; Lerner and Harris, 2009; Owuor et al., 2016). In many semi-arid  
regions, there has been the conversion of native forests to agricultural land (Foley et al., 2005).  
Deep-rooted trees generally return more water to the atmosphere via transpiration than shallow-  
rooted crops and grasses (Hewlett and Hibbert, 1967; Bosch and Hewlett, 1982; Fohrer et al.,  
2001). In southeast Australia, the reduction in evapotranspiration following the land clearing  
35 has commonly resulted in a net increase in recharge and a rise of the regional water tables. In  
turn, this has resulted in waterlogging and salinization of cleared lands and increased stream  
salinity (Allison et al., 1990). Eucalyptus tree plantations were subsequently initiated partially  
to reduce groundwater recharge and thus prevent the rise of regional water tables (Gee et al.,  
1992; Benyon et al., 2006). In order to assess the impacts of successive land-use changes on  
40 the groundwater and surface water systems, estimates of recharge are required. Estimation of  
recharge rates is also important for groundwater modelling, because recharge represents the  
water flux used as a boundary condition at the water table.

Recharge is the water that infiltrates through the unsaturated zone to the water table and thus  
increases the volume of water stored in the saturated zone (Lerner et al., 1990; Healy and Cook,  
45 2002; Scanlon et al., 2002; Moeck et al., 2020). A distinction between gross and net recharge  
may also be made (Crosbie et al., 2005). The total amount of water that reaches the water table  
is the gross recharge, while the net recharge accounts for the subsequent removal of water from  
the saturated zone by evapotranspiration. In areas with shallow water tables and deep-rooted

vegetation, this subsequent water loss can be considerable. Estimating groundwater recharge  
50 rates, in general, is not straightforward (Lerner et al., 1990; Healy, 2010; Moeck et al., 2020)  
and recharge rates potentially vary in space and time (Sibanda et al., 2009).

Several techniques may be used to estimate groundwater recharge, including Darcy's Law,  
measuring water infiltration using lysimeters installed in the unsaturated zone, measuring and  
modelling soil moisture contents, use of heat flow calculations, catchment water budgets,  
55 remote sensing, numerical models, water table fluctuations, chemical (chloride) mass balance  
calculations, and/or the concentrations of radioisotopes such as  $^3\text{H}$  (tritium),  $^{14}\text{C}$  (carbon),  $^{36}\text{Cl}$   
(chloride) or other time-sensitive tracers (e.g., chlorofluorocarbon) in groundwater (Scanlon et  
al., 2002, 2006; Healy, 2010; Doble and Crosbie, 2017; Cartwright et al., 2017; Moeck et al.,  
2020; Gelsinari et al., 2020).

60 Different techniques estimate recharge over different spatial-temporal scales, and they may  
thus yield different results (Scanlon et al., 2002). Because each technique has different  
uncertainties and limitations, it is recommended that multiple methods are used to constrain  
recharge (Healy and Cook, 2002; Sophocleous, 2004; Scanlon et al., 2006). Understanding the  
broader hydrogeology also helps to understand recharge. For example, areas where recharge  
65 rates are high, should contain high proportions of young groundwater. Additionally, recharge  
rates are likely to be low if evapotranspiration rates approach rainfall totals.

This study estimates recharge rates using Cl mass balance, water table fluctuations, and  $^3\text{H}$   
renewal rate methods in a semi-arid area that has undergone successive land-use changes. We  
evaluate the applicability and uncertainties of these commonly applied methods to determine  
70 the changes in recharge rates caused by these successive land-use changes. While based on a  
specific area, the results of this study, in particular the comparison of present-day recharge rate  
estimates, will be applicable to similar semi-arid areas in southeast Australia and elsewhere.  
Specifically, predicting the impacts of changes to land-use on recharge rates is required to

understand and manage waterlogging and salinization of soils and streams. A brief description  
75 of the assumptions and limitations of these techniques is provided below.

### 1.1. Cl mass balance

The Cl mass balance (CMB) approach yields average regional net recharge rates (Bazuhair and  
Wood, 1996; Scanlon, 2000; Scanlon et al., 2002). The assumptions of this method are that all  
Cl in groundwater originates from rainfall and that Cl exported in surface runoff is negligible  
80 or well known. Under these conditions, the net groundwater recharge ( $R_{net}$  in  $\text{mm yr}^{-1}$ ) is  
estimated from:

$$R_{net} = P \frac{Cl_p}{Cl_{gw}} \quad (1)$$

(Eriksson and Khunakasem, 1969) where  $P$  is mean annual precipitation ( $\text{mm yr}^{-1}$ ),  $Cl_p$  is the  
weighted mean Cl concentration in precipitation ( $\text{mg L}^{-1}$ ), and  $Cl_{gw}$  is Cl concentration in  
85 groundwater ( $\text{mg L}^{-1}$ ). The CMB method estimates net recharge rates averaged over the time  
that the Cl contained within the groundwater is delivered; this may be several years to millennia.  
Uncertainties in the CMB method are mainly the long-term rate of Cl delivery and the  
assumptions that runoff has remained negligible over time.

### 1.2 Water table fluctuations

90 Water table fluctuations may be used to estimate gross recharge rates over the time period for  
which groundwater elevation data are available. Because bore hydrograph data are abundant,  
this probably is the most common method of estimating present-day recharge rates. The water  
table fluctuation (WTF) method strictly requires the water table to be located within the  
screened interval of the bore; however, it can be used in bores screened within a few metres of  
95 the water table (Healy and Cook, 2002). The method assumes that: evapotranspiration from the  
water table has not occurred; the rise in the water table is solely due to recharge following  
rainfall events; groundwater elevations are not influenced by pumping; and the water table falls  
in the absence of recharge.  $R_{gross}$  is calculated from

$$R_{gross} = S_y \frac{\Delta h}{\Delta t} \quad (2)$$

100 where  $S_y$  is the specific yield (dimensionless) of the aquifer, and  $\Delta h/\Delta t$  is the variation in the hydraulic head over the recharge event ( $\text{mm yr}^{-1}$  where there is an annual recharge event).

Despite its simplicity, there are several potential uncertainties in the WTF method.  $S_y$  is not commonly measured, and most studies rely on typical values based on aquifer materials. More importantly, the retention of moisture in the unsaturated zone between recharge events reduces  $S_y$  and results in  $S_y$  being spatially and temporally variable (Gillham, 1984; Sophocleous, 1985; Healy and Cook, 2002; Crosbie et al., 2019). However, many recharge studies assume that  $S_y$  is constant and close to the effective porosity. This may result in the WTF method significantly overestimating recharge rates (Gillham, 1984; Sophocleous, 1985; Crosbie et al., 2019). Other processes may also affect head measurements. These include entrapment of air during rapid 110 recharge events (the Lisse effect) and the impacts of barometric pressure changes and ocean or Earth tides, especially when the head is measured using sealed pressure transducers (Crosbie et al., 2005). The estimation of the recession curve of the groundwater hydrograph used to calculate  $\Delta h$  in Eq. (2) also involves some judgement.

### 1.3 $^3\text{H}$ renewal rate

115 The  $^3\text{H}$  renewal rate (TRR) method envisages that recharge mixes with pre-existing groundwater in a discrete zone at the top of the aquifer with an equivalent amount of water from this upper zone displaced lower into the groundwater system. The renewal rate ( $R_n$ ) represents the proportion of new water added in each recharge cycle. If there is an annual cycle of groundwater recharge, the  $^3\text{H}$  activity of groundwater in year  $i$  ( $^3H_{gw_i}$ ) is related to  $R_n$  by

$$120 \quad ^3H_{gw_i} = (1-R_n)^i ^3H_{gw_{i-1}} e^{-\lambda_i} + R_n ^3H_{p_i} \quad (3)$$

(Leduc et al., 2000; Le Gal La Salle et al., 2001; Favreau et al., 2002) where  $\lambda_i$  is the radioactive decay constant for  $^3\text{H}$  ( $0.0563 \text{ yr}^{-1}$ ), and  $^3H_{p_i}$  is the average  $^3\text{H}$  activity of rainfall in year  $i$  (in

Tritium Units, TU where 1 TU corresponds to  ${}^3\text{H}/{}^1\text{H} = 1 \times 10^{-18}$ ). The application of the TRR method requires the  ${}^3\text{H}$  input function over the past few decades to be known. The  ${}^3\text{H}$  activities of southern hemisphere groundwater recharged during the 1950s and 1960s atmospheric tests were several orders of magnitude lower than northern hemisphere groundwater (Morgenstern et al., 2010; Tadros et al., 2014). These  ${}^3\text{H}$  activities have now decayed and are lower than those of present-day rainfall, which results in individual  ${}^3\text{H}$  activities yielding a single  $R_n$  estimate (Cartwright et al., 2007, 2017, 2020); this is not yet the case in the northern hemisphere (Le Gal La Salle et al., 2001).

Groundwater recharge rates are related to  $R_n$  by

$$R_{net} = R_n b n \quad (4)$$

where  $b$  is the thickness of the upper part of the aquifer system that receives annual recharge and  $n$  is the effective porosity. Uncertainties in the TRR estimates include uncertainties in the  ${}^3\text{H}$  input function and having to estimate  $b$  and  $n$ , which may be variable and not well defined. The recharge rates are net estimates averaged over the residence time of groundwater in the upper part of the aquifer, which in an ideal system is  $R_n^{-1}$ .

## 2. Study area

Gatum is situated in western Victoria, southeast Australia (Fig. 1a). The native eucalyptus forests in this region were originally cleared for grazing following European settlement ~180 years ago (Lewis, 1985) and then partially replaced by eucalyptus plantation in the last ~15 years (Adelana et al., 2015). Gatum lies in the regional recharge area of the Glenelg River Basin to the south of the drainage divide between the Glenelg and Wannon Rivers, and surface water drains to the Wannon River via the Dundas River (Dresel et al., 2012). The area is predominantly composed of fine- to coarse-grained weathered Early Devonian ignimbrites containing abundant large locally derived clasts near their base (Cayley and Taylor, 1997). Post-Permian weathering has produced a deeply weathered saprolitic clay-rich regolith and

ferruginous laterite duricrust (Brouwer and Fitzpatrick, 2002). Some of the drainage areas contain Quaternary alluvium and colluvium (Adelana et al., 2015).

150 The study area consists of two catchments with contrasting land-use, one catchment is predominately dryland pasture used for sheep grazing, and the other is mostly occupied by plantation *Eucalyptus globulus* forestry. The pasture catchment is around 151 ha and is typical of the cleared land in this region. It is covered by perennial grasses with about 3% remnant eucalyptus trees. The forest catchment is around 338 ha and comprises approximately 62%  
155 plantation forest, established in 2005, and 38% grassland (Adelana et al., 2015). The elevations of the pasture and forest catchments range from 236 to 261 m and 237 to 265 m AHD (Australian Height Datum), respectively (Fig. 2). The two catchments were subdivided into the upper slope, mid-slope and lower slope, based on the elevation of the study area; the drainage zones are in the riparian zones of the small streams (Dresel et al., 2018). The catchments are  
160 drained by two small intermittent streams (Banool and McGill: Fig. 1a) that export ~8% of annual rainfall (Adelana et al., 2015; Dresel et al., 2018).

The regional groundwater is not extensively used in this area. However, the study area is one of many in southeast Australia that was identified as being impacted by dryland salinity due to land clearing and rising water tables (Clark and Harvey, 2008). During the Millennium Drought  
165 in the first decade of the century, the water tables dropped considerably and the emphasis on dryland salinity diminished. The focus of water management in this area switched from salinity to water sustainability and the effect of land-use changes on the water balance of this area (Dresel et al., 2012). In addition to the regional groundwater system, shallow (1 to 4 m deep) perched groundwater exists in the riparian zones (Brouwer and Fitzpatrick, 2002; Adelana et  
170 al., 2015).

The climate is characterized by cool, wet winters and hot, dry summers. From 1884 to 2018, the average annual rainfall at Cavendish (Station 089009) ~19 km southeast of Gatum (Fig. 1a)



was ~640 mm (Bureau of Meteorology, 2020), with most rainfall in the austral winter between May and October (Fig. 3a). Average annual actual evapotranspiration across the two  
175 catchments between 2011 and 2016 was estimated at about 580 mm (Dresel et al., 2018). The mean concentrations of Cl in rainfall range from 2.2 mg L<sup>-1</sup> at Cavendish (Hutton and Leslie, 1958) to 4.4 mg L<sup>-1</sup> at Hamilton (~34 km southeast of Gatum, Fig. 1a: Bormann, 2004; Dean et al., 2014). Similar Cl concentrations were recorded in rainfall across much of southeast Australia (Blackburn and McLeod, 1983; Crosbie et al., 2012).

## 180 **3. Methods and Materials**

### **3.1 Water sampling**

There are 19 monitoring bores at different landscape positions sampling the regional groundwater in the pasture and forest catchments (Fig. 1a) with sample depths ranging from 1.3 to 29.7 m (Supplementary Table S1). Hydraulic heads have been measured since 2010 at  
185 four hourly intervals using In Situ Aquatroll or Campbell CS450 WL pressure loggers corrected for barometric pressure variations using In Situ Barotroll loggers. Occasional spikes (generally resulting from the logger being removed from the bores) were removed. Twelve shallow piezometers (~1 m deep with ~10 cm wide screens at their base) were installed in 2018 near the monitoring bores in the drainage zones and the lower slopes of the pasture and forest  
190 catchments (Fig. 1a). These piezometers intercept the riparian groundwater that in places is perched above the regional groundwater. Regional groundwater was sampled from bores (n = 24) and riparian groundwater from shallow piezometers (n = 24) between May and November 2018. The groundwater samples were collected from the screened interval using a submersible pump or bailer following the removal of at least three bore volumes of groundwater or  
195 removing all water and allowing it to recover. Following sampling, hydraulic conductivities (K<sub>s</sub>; m day<sup>-1</sup>) were determined from the rate of recovery of the groundwater levels measured at 3-minute intervals using an In Situ Aquatroll pressure logger (Hvorslev, 1951). A one-year

aggregated rainwater sample was collected in a narrow-mouthed container with an open funnel. The sample was periodically removed from the container and aggregated into a single sample.

## 200 **3.2 Analytical techniques**

Geochemical data are presented in Table S1. Electrical conductivity (EC) was measured in the field using a calibrated hand-held TPS WP-81 multimeter and probe. Groundwater samples were collected in high-density polyethylene bottles and stored at  $\sim 4^{\circ}\text{C}$  prior to analysis. Alkalinity ( $\text{HCO}_3$ ) concentrations were measured within 12 hours of sampling by titration.

205 Major ion concentrations were measured at Monash University. Cation concentrations were determined on filtered ( $0.45\ \mu\text{m}$  cellulose nitrate filters) water samples that were acidified to  $\text{pH} < 2$  with double distilled 16 N  $\text{HNO}_3$  using ICP-OES (Thermo Scientific iCAP 7000). Concentrations of anion were determined on unacidified filtered water samples by ion chromatography (Thermo Scientific Dionex ICS-1100). Based on replicate analyses, the  
210 precision of cation and anion concentrations are  $\pm 2\%$ ; from the analysis of certified standards, accuracy is estimated at  $\pm 5\%$ . Total dissolved solids (TDS) concentrations are the sum of the cation and anion concentrations.

$^3\text{H}$  and  $^{14}\text{C}$  activities were measured at the Institute of Geological and Nuclear Sciences (GNS) in New Zealand. Samples for  $^3\text{H}$  activities were measured by liquid scintillation in Quantulus  
215 ultra-low-level counters following vacuum distillation and electrolytic enrichment as described by Morgenstern and Taylor (2009). The quantification limits are 0.02 TU and the relative uncertainties are typically  $\pm 2\%$  (Table S1).  $^{14}\text{C}$  activities were measured by AMS following Stewart et al. (2004). Dissolved inorganic carbon (DIC) was converted to  $\text{CO}_2$  by acidification with  $\text{H}_3\text{PO}_4$  in a closed evacuated environment. The  $\text{CO}_2$  was purified cryogenically and  
220 converted to graphite.  $^{14}\text{C}$  activities are normalised using the  $\delta^{13}\text{C}$  values and expressed as percent modern carbon (pMC), where the  $^{14}\text{C}$  activity of modern carbon is 95% of  $^{14}\text{C}$  activity

of the NBS oxalic acid standard in 1950. Uncertainties are between 0.27 and 0.35 pMC (Table S1).

### 3.3 Recharge calculations

225 Recharge rates were estimated using the methods discussed in sections 1.1-1.3. Net recharge rate estimates from the CMB (Eq. 1) utilised present-day average rainfall amounts (~640 mm) and Cl concentrations of 2.2 to 4.4 mg L<sup>-1</sup> together with the measured Cl concentrations of groundwater (Table S1). Gross recharge rates were estimated using the WTF method (Eq. 2) from the bore hydrographs that display seasonal variations in the water levels (Figs. 3b, 3c).  
230 There is a single pronounced annual increase in the hydraulic head following winter rainfall, and  $\Delta h$  was estimated as the difference between the highest head value and the extrapolated antecedent recession curve (Healy and Cook, 2002). The effect of evapotranspiration on the magnitude of the hydraulic heads is assumed to be low, especially during winter when radiation and temperature are lower.  $S_y$  was assumed to be close to  $n$  (0.03 to 0.1: Adelana et al. 2015; Dean et al., 2015), which will be the case if the unsaturated zone dries up between recharge events (Sophocleous, 1985). The TRR calculations (Eq. 3) used <sup>3</sup>H activities in Melbourne rainfall as the input function (Tadros et al., 2014). The annual average <sup>3</sup>H activity of present-day rainfall in both Melbourne and Gatum is ~2.8 TU (Tadros et al., 2014; Table S1) and the rainfall prior to the atmospheric nuclear tests was assumed to have had the same <sup>3</sup>H activity as  
240 present-day rainfall.  $n = 0.03$  to  $0.1$  was again used and estimates of  $b$  are discussed below.

### 3.4 Mean residence times

The mean residence times (MRTs) and the covariance of <sup>3</sup>H and <sup>14</sup>C activities in groundwater were estimated via lumped parameter models (LPMs: Zuber and Maloszewski, 2001; Jurgen et al., 2012). LPMs relate <sup>14</sup>C activity of water at time  $t$  ( $C_{out}$ ) to the <sup>14</sup>C input during recharge  
245 over time ( $C_{in}$ ) via the convolution integral

$$C_{out}(t) = \int_0^{\infty} q C_{in}(t - \tau_m) e^{-\lambda \tau_m} g(\tau_m) d\tau_m \quad (5)$$

(Zuber and Maloszewski, 2001; Jurgens et al., 2012) where  $q$  is the fraction of DIC derived from the rainfall or the soil zone,  $(t - \tau_m)$  is the age of the water,  $\tau_m$  is the MRT,  $\lambda_c$  is the decay constant for  $^{14}\text{C}$  ( $1.21 \times 10^{-4} \text{ yr}^{-1}$ ), and  $g(\tau_m)$  is the system response function that describes the distribution of residence times in the aquifer (described in detail by Maloszewski and Zuber, 1982; Zuber and Maloszewski, 2001; Jurgens et al., 2012).  $^3\text{H}$  activities may be calculated from the input of  $^3\text{H}$  over time in a similar way. Unlike  $^{14}\text{C}$ ,  $^3\text{H}$  activities are not changed by reactions between the groundwater and the aquifer matrix; hence the  $q$  term is omitted.

There are several commonly used LPMs. The partial exponential model (PEM) may be applied for the aquifers where only the deeper groundwater flow paths are sampled. The dimensionless PEM ratio defines the ratio of the unsampled to sampled depths of the aquifer (Jurgens et al., 2012). This study used PEM ratios of 0.05 to 0.5 that cover the ratios of unsampled to sampled portions of the aquifers at Gatum. The dispersion model (DM) is derived from the one-dimensional advection-dispersion transport equation and is applicable to a broad range of flow systems (Maloszewski and Zuber, 1982; Zuber and Maloszewski, 2001; Jurgens et al., 2012). The dimensionless dispersion parameter (DP) in this model describes the relative contributions of dispersion and advection. For flow systems of a few hundreds of metres to a few kilometres, DP values are likely to be in the range of 0.05 to 1.0 (Zuber and Maloszewski, 2001). Other commonly applied LPMs, such as the exponential-piston flow or the gamma model, produce similar estimates of residence times (Jurgens et al., 2012; Howcroft et al., 2017). The long-term variations of atmospheric  $^{14}\text{C}$  concentrations in the southern hemisphere (Hua and Barbetti, 2004; McCormac et al., 2004) were used as the  $^{14}\text{C}$  input function, and  $^3\text{H}$  activities in rainfall for Melbourne (Tadros et al., 2014) were used as the  $^3\text{H}$  input function.

## 4. Results

### 270 4.1 Hydraulic heads and properties

The hydraulic heads in regional groundwater from both pasture and forest catchments decrease from the upper to lower slopes implying that the regional groundwater flows southwards (Fig. 1b). In the pasture, the hydraulic heads in groundwater from all bores generally gradually increase over several weeks to months following the onset of winter rainfall (Fig. 3b). The increase in hydraulic heads was higher in 2016, which was a year of higher than average rainfall (~800 mm: Bureau of Meteorology, 2020). This was especially evident at bore 63 (Fig. 3b). In the forest, groundwater heads from bores in the upper (3663 and 3665) and mid (3668) slopes decline uniformly over the monitoring period, and the groundwater head from bore 3658 near the drainage zones does not show seasonal variations (Fig. 3c). However, fluctuations of the head from three bores near the drainage zones (3669) and the lower slopes (3656 and 3657) show seasonal variations similar to that of the groundwater in the pasture (Figs. 3b, 3c).

Values of  $K_s$  range from 0.06 to 0.31 m day<sup>-1</sup> in the pasture (Table S1, Fig. 2a) and from 0.002 to 0.18 m day<sup>-1</sup> in the forest catchments (Table S1, Fig. 2b). The aquifers in the upper and lower slopes of the pasture catchment have the highest  $K_s$  values of ~0.31 m day<sup>-1</sup>, whereas  $K_s$  values of the aquifers in the forest are lowest on the lower slopes (Table S1, Fig. 2). The aquifers contain rocks from the same stratigraphic unit, and the heterogeneous hydraulic properties probably reflect the degree of weathering, cementation, and clay contents.

### 4.2 Major ions

TDS concentrations of regional groundwater range from 282 to 7850 mg L<sup>-1</sup> in the pasture catchment and 1190 to 7070 mg L<sup>-1</sup> in the forest catchment (Table S1); the lowest salinity regional groundwater is from the upper slope of the pasture catchment. The TDS concentrations of the shallow riparian groundwater (≤1 m depth) are between 3890 and 8180 mg L<sup>-1</sup> in the pasture and from 169 to 13600 mg L<sup>-1</sup> in the forest (Table S1). Regional and riparian

groundwaters from both catchments have similar geochemistry. Na constitutes up to 67% of  
295 the total cations on a molar basis, and Cl accounts for up to 91% of total anions on a molar  
basis. Cl concentrations range between 45.2 and 8140 mg L<sup>-1</sup>, which significantly exceed the  
mean concentrations of Cl in local rainfall (2.2 to 4.4 mg L<sup>-1</sup>: Hutton and Leslie, 1958;  
Bormann, 2004; Dean et al., 2014). Molar Cl/Br ratios are between 180 and 884, with most in  
the range between 450 and 830 (Fig. 4a), which spans those of seawater and coastal rainfall  
300 (~650: Davies et al., 1998, 2001). Cl/Br ratios are significantly lower than those that would  
result from halite dissolution (10<sup>4</sup> to 10<sup>5</sup>: Kloppmann et al., 2001; Cartwright et al., 2004, 2006)  
and do not increase with increasing Cl concentrations. These observations indicate that, as is  
the case throughout southeast Australia (e.g., Herczeg et al., 2001; Cartwright et al., 2006), Cl  
is predominantly derived from rainfall and concentrated by evapotranspiration. There is also no  
305 halite reported in the aquifers in this region. Cl concentrations of the shallow and the deeper  
groundwater overlap (Fig. 4b) and there is no correlation between Cl and <sup>3</sup>H (Fig. 4c). Ca and  
HCO<sub>3</sub> concentrations are uncorrelated (Fig. 4d) indicating that the dissolution of calcite is not  
a major process influencing groundwater geochemistry.

### 4.3 Radioisotopes

310 <sup>3</sup>H activities of the regional groundwater are up to 1.48 TU (Table S1, Fig. 5). These are lower  
than the average annual <sup>3</sup>H activities of present-day rainfall in this region of ~2.8 TU (Tadros  
et al., 2014; Table S1). The highest <sup>3</sup>H activities (>1 TU) are from the regional groundwater in  
the upper slopes (15.5 m depth) and the drainage zone (~1.3 m depth) of the pasture catchment  
and between 15.8 and 28.8 m depths in the forest catchment (Table S1). The regional  
315 groundwater from ≥28 m depth in the lower slopes of the pasture catchment and the drainage  
zones of the forest catchment locally have below detection (<0.02 TU) <sup>3</sup>H activities (Table S1).  
The <sup>3</sup>H activities of the shallow riparian groundwater in the pasture vary from 0.26 to 0.79 TU  
with the highest activities from the lower slopes (Table S1, Fig. 5). The riparian groundwater

in the forest catchment has  $^3\text{H}$  activities ranging from 2.01 to 4.10 TU (Table S1, Fig. 5), which  
320 are locally higher than the annual average  $^3\text{H}$  activity of present-day rainfall (~2.8 TU). These  
high  $^3\text{H}$  activities probably reflect seasonal recharge by the winter rainfall that in southeast  
Australia has higher  $^3\text{H}$  activities than the annual average (Tadros et al., 2014).

$^{14}\text{C}$  activities in the regional groundwater from the pasture and forest catchments range from  
70.7 to 104 (pMC) and from 29.5 to 101 (pMC), respectively (Table S1, Fig. 5). The highest  
325  $^{14}\text{C}$  activities (>100 pMC) are from groundwater in the upper slopes of the pasture catchment  
and the lower zones of the forest catchment that also has high  $^3\text{H}$  activities (Table S1). The  
lowest  $^{14}\text{C}$  activities are from groundwater at 18 to 28.4 m depths in the mid-slope and the  
drainage lines of the forest catchment (Table S1).  $^{14}\text{C}$  activities of the shallow riparian  
groundwater are 85.5 to 102 pMC, with higher activities (>100 pMC) in the drainage zones of  
330 the forest catchment (Table S1, Fig. 5).

## 5 Discussion

The combined groundwater elevation and geochemical data allow residence times, mixing, and  
recharge rates at Gatum to be interpreted.

### 5.1. Mean residence times and mixing

335  $^3\text{H}$  and  $^{14}\text{C}$  activities help to understand water mixing within the aquifers (Le Gal La Salle et  
al., 2001; Cartwright et al., 2006, 2013) and the MRTs. The predicted  $^3\text{H}$  vs.  $^{14}\text{C}$  activities (Fig.  
5) were calculated for all DIC being introduced by recharge ( $q = 1$ ) and for 10% contribution  
of  $^{14}\text{C}$ -free DIC from the aquifer matrix ( $q = 0.9$ ). Mixing between older (low  $^3\text{H}$  and low  $^{14}\text{C}$ )  
and recently-recharged groundwater (high  $^3\text{H}$  and high  $^{14}\text{C}$ ) results in groundwater samples that  
340 plot to the left of the decay trends in Fig. 5. It is difficult to calculate MRTs for these mixed  
waters; however, it is possible to estimate MRTs from the  $^{14}\text{C}$  activities for groundwater lying  
close to the predicted decay trends. The aquifers are dominated by siliceous rocks, and the  
major ion geochemistry implies little calcite dissolution. Similar values of  $q$  were estimated for

groundwater from other siliceous aquifers in southeast Australia (Cartwright et al., 2010, 2012; 345 Atkinson et al., 2014; Raiber et al., 2015; Howcroft et al., 2017) and elsewhere (Vogel, 1970; Clark and Fritz, 1997). Much lower  $q$  values are precluded as samples cannot lie to the right of the  $^3\text{H}$  vs.  $^{14}\text{C}$  curves (Cartwright et al., 2006, 2013, 2017). This is because samples that are not a mixture of old and young groundwater, containing measurable  $^3\text{H}$  will be less than 200 years old. Over that time span, there has been negligible decay of  $^{14}\text{C}$ , and the initial  $a^{14}\text{C}$  of the 350 sample is  $a^{14}\text{C}/q$  (Clark and Fritz, 1997). If there were greater than 10% contribution of DIC from  $^{14}\text{C}$ -free calcite dissolution, the estimated initial  $a^{14}\text{C}$  would exceed the highest  $a^{14}\text{C}$  recorded in soil  $\text{CO}_2$  of  $\sim 120$  pMC.

The calculated MRTs are up to 3,930 years in the pasture and up to 24,700 years in the forest (Table 1, Fig. 6). While using LPMs is preferable to using a simple decay equation that assumes 355 piston flow and ignores variations in the  $^{14}\text{C}$  input function, there are uncertainties in the calculated MRTs. The different LPMs have different residence time distributions, and so yield different MRT estimates. Additionally, there are uncertainties in  $q$  and the input function of  $^{14}\text{C}$ . Previous studies (e.g., Atkinson et al., 2014; Howcroft et al., 2017) estimated overall uncertainties in MRTs were up to 25%. While these are considerable, much of the regional 360 groundwater undoubtedly have residence times of several thousands of years and were recharged prior to land clearing. These long residence times are consistent with the locally clay-rich nature of the aquifers and the moderate to low hydraulic conductivities.

## 5.2 Recharge rates

### 5.2.1 Cl mass balance

365 Recharge rates calculated from the CMB method (Eq. 1) using total rainfall of  $\sim 640$  mm  $\text{yr}^{-1}$  and Cl concentrations of 2.2 to 4.4 mg  $\text{L}^{-1}$  are similar between the pasture (0.3 to 61.6 mm  $\text{yr}^{-1}$ ) and forest (0.2 to 58.8 mm  $\text{yr}^{-1}$ ) catchments (Figs 2, 7a). The typical recharge rates for most of the regional groundwater are from 0.3 to 2.5 mm  $\text{yr}^{-1}$  in the pasture and 0.2 to 11.2 mm  $\text{yr}^{-1}$  in



the forest (Figs. 2, 7a). The Cl/Br ratios imply that the dissolution of halite is negligible, and  
370 all the Cl is delivered by the rainfall. Whether the rate of Cl delivery has been constant over  
long time periods is more difficult to assess; however, the rainfall Cl concentrations are typical  
of inland rainfall, and southeast Australia does not record major climate fluctuations such as  
glaciations or monsoons (Davies and Crosbie, 2018).

The CMB technique also assumes that the export of Cl by surface runoff is negligible. The  
375 streams at Gatam currently discharge ~8 % of local rainfall and much of the Cl that they export  
represents groundwater discharging into the stream (Adelana et al., 2015). This component of  
Cl does not impact the CMB recharge rate calculations. If some direct export of Cl has occurred,  
the recharge estimates would be slightly lower than estimated above. However, because the  
initial land clearing has most likely increased streamflow in this region (Dresel et al., 2018),  
380 streamflows and the export of Cl would have historically been lower than the present-day.

Because Cl in groundwater accumulates over hundreds to thousands of years (Scanlon et al.,  
2002, 2006), the CMB method generally yields longer-term recharge rates; these largely reflect  
pre-land clearing recharge in Australia (Alison and Hughes, 1978; Cartwright et al., 2007; Dean  
et al., 2015; Perveen, 2016). This conclusion is consistent with the long  $^{14}\text{C}$  residence times of  
385 much of the deeper regional groundwater at Gatam. The higher recharge rates (25.3 to 61.6  
 $\text{mm yr}^{-1}$ ) are from the regional groundwater in the upper slopes of the pasture (bore 63) and the  
shallow riparian groundwater in the drainage zones (piezometer FD2) and the lower slopes  
(piezometer FB1) of the forest (Figs. 2, 7a). The groundwater at these sites has high  $^3\text{H}$  and  $^{14}\text{C}$   
activities, and the recharge rates from the CMB technique are likely to represent present-day  
390 recharge.

### **5.2.2 Water table fluctuations**

The recharge rates were calculated using the WTF method (Eq. 2) from the bore hydrographs,  
which show seasonal head variations assuming  $S_y = 0.03$  to 0.1. The estimated recharge rates

range from 15 to 500 mm yr<sup>-1</sup> (2 to 78% of rainfall) in the pasture and 30 to 400 mm yr<sup>-1</sup> (5 to 395 63% of rainfall) in the forest (Figs. 2, 7b). As with the CMB estimates, the recharge rates are generally high at the upper slopes of the pasture catchment (Figs. 2, 7b). However, the highest recharge rates from the WTF method are unlikely given that evapotranspiration rates in this region approach the rainfall rates (Dean et al., 2016; Dresel et al., 2018; Azarnivand et al., 2020). The lower recharge rates estimated from the WTF method appear more reasonable but 400 are still larger than most recharge rates estimated from the TRR method. The observation that much of the older saline groundwater has not been flushed from the catchments also implies that present-day recharge rates cannot be very high.

The WTF method requires the hydrograph recession curves to be estimated. There are significant steep and straight recession curves in the bore hydrographs (Figs. 3b, 3c) that can 405 lead to errors in recharge estimates. The WTF method may overestimate recharge due to air entrapped during recharge (the Lisse effect: Crosbie et al., 2005). However, this occurs during rapid recharge, which is not observed in the Gatum area. Dean et al. (2015) suggested that the high recharge rates estimated from the WTF method in the adjacent Mirranatwa catchments might reflect focussed recharge from the streams. This is not the case at Gatum as high WTF 410 recharge rates are recorded at all landscape positions and the streams only export ~8% of rainfall (Adelana et al., 2015). Because the WTF estimates gross recharge and geochemical methods estimate net recharge, there may be differences if the water is removed from the water table by evapotranspiration, especially in spring after the water tables reach their seasonal peak. The plantation forest plausibly has high evapotranspiration rates (Benyon et al., 2006; Dean et 415 al., 2015; Dresel et al., 2018); however, this explanation is unlikely in the pasture where water tables are locally several metres below land surface, and there is not deep-rooted vegetation. It is most likely that the unrealistically high recharge rates estimated from the WTF method reflect an overestimation of  $S_y$  due to the presence of remnant moisture in the unsaturated zone

between the recharge events (Gillham, 1984; Sophocleous, 1985; Crosbie et al., 2005, 2019).

420 While this is not unexpected, it is difficult to determine realistic values of  $S_y$  to improve these estimates.

### 5.2.3 $^3\text{H}$ renewal rate

The recharge rates for bores and shallow piezometers were estimated using the  $^3\text{H}$  activities and the TRR method (Eqs. 3, 4). These recharge rates were calculated for those groundwater  
425 samples which do not show the mixing of recent and older groundwater (Fig. 5). Regional groundwater from nested bores commonly has different TDS contents, EC values,  $^3\text{H}$  and  $^{14}\text{C}$  concentrations (Table S1), indicating that the groundwater is stratified. Much of the deeper groundwater has low  $^3\text{H}$  and  $^{14}\text{C}$  activities implying that it is not recently recharged. Based on these differences in geochemistry (Table S1),  $b$  is estimated as being between 1 and 5 m in the  
430 regional groundwater.  $b$  values for the shallow riparian groundwater are estimated as 1 to 2 m, which is the approximate thickness of the shallow perched aquifers (Brouwer and Fitzpatrick, 2002). The estimated  $n$  values of 0.03 to 0.1 (Adelana et al., 2015; Dean et al., 2015) were used for these calculations.

Recharge rates from the regional groundwater are 0.5 to 14.0 mm yr<sup>-1</sup> in the pasture and 0.01  
435 to 59.5 mm yr<sup>-1</sup> in the forest with most in the range of 0.01 to 0.6 mm yr<sup>-1</sup> (Figs. 2, 7c). The higher recharge rates were from the upslopes of the pasture (14.0 mm yr<sup>-1</sup>) and the lower slopes of the forest (59.5 mm yr<sup>-1</sup>). The recharge rates in the riparian groundwater are from 0.05 to 0.5 mm yr<sup>-1</sup> in the pasture and 13.3 to 89.0 mm yr<sup>-1</sup> in the forest (Figs. 2, 7c).

The average annual  $^3\text{H}$  activity in present-day rainfall at Gatum (~2.8 TU) is within the  
440 predicted range of the  $^3\text{H}$  activities in present-day Melbourne rainfall ( $3.0 \pm 0.2$  TU), implying that the Melbourne  $^3\text{H}$  input function is appropriate to use for this area. Assuming uncertainty in the  $^3\text{H}$  input function of 5 to 10% (which is similar to the present-day variability of  $^3\text{H}$  activities reported by Tadros et al., 2014) results in <5% uncertainties in recharge estimates.

The variation resulting from analytical uncertainties are lower than this. Recharge rates are most sensitive to the  $b$  values, which are not explicitly known and may be variable. However,  $b$  is unlikely to be  $>5$  m based on the observed degree of chemical stratification. It may also be possible to estimate  $b$  from the fluctuation of the water table (on the basis that the rise in the water table corresponds to recharging water added to the top of the aquifer). If that is the case,  $b$  values would be typically 1 to 3 m (Figs. 3b, 3c), which is within the range used in these calculations. There is also an assumption of a homogeneous aquifer. However, older water with low  $^3\text{H}$  activities may locally be present in the zones of low hydraulic conductivity. Diffusion may reduce the  $^3\text{H}$  activities in the more mobile groundwater adjacent to those zones (Sudicky and Frind, 1981; Cartwright et al., 2006; 2017, 2020). Overall, the recharge rates from the TRR method are again generally higher than those calculated using the CMB, which reflects the effects of the initial land clearing. However, despite both reflecting post-land clearing recharge, they are significantly lower than those estimated using the WTF.

### 5.3. Predicting the effect of land-use changes

In large regions of southeast Australia (including the study area), understanding whether and by how much recharge increased following the initial land clearing is important in predicting the impact of a rising water table in causing salinization of the soils and the streams. For areas where plantation forests have been established, it is important to assess any subsequent impact of those plantations on recharge.

As expected, the recharge estimates from the CMB method are generally lower than those from the WTF and TRR methods and largely reflect those prior to the initial replacement of native eucalyptus vegetation by pasture. Although both methods determine present-day recharge rates (Scanlon et al., 2002, 2006), those estimated using the WTF method are significantly higher than the TRR estimates (Fig. 8). Having to estimate  $b$  represents a major uncertainty in the TRR calculations; however,  $b$  would have to be up to 50 m to achieve agreement between the

recharge estimates from these two methods. This is unlikely given the observations that major  
470 ion geochemistry,  $^3\text{H}$  and  $^{14}\text{C}$  activities of groundwater vary over vertical scales of a few metres  
(Table S1), implying that the groundwater is compartmentalised on those scales. It is also  
unlikely that  $b$  could be so large given the heterogeneous nature of the aquifers and the presence  
of clay layers. It is most likely that the WTF method systematically overestimates recharge due  
to issues in estimating  $S_y$ .

475 The recharge estimates from the TRR method differ little between the pasture and the forest;  
this is unexpected given that the establishment of plantation forests aimed to reduce the  
recharge rates. The evapotranspiration rates in the forest are also higher than in the pasture  
(Adelena et al., 2015; Dresel et al., 2018) and the water levels are declining in some areas of  
the forest with no corresponding decline in the pasture (Figs. 3b, 3c), suggesting higher water  
480 use by the trees. The plantation covers ~62% of the forest catchment, and many of the bores  
are in cleared areas between the stands of trees (Fig. 1a). Thus, the recharge rates may not be  
representative of the forest as a whole. Additionally, the TRR averages recharge rates over the  
timespan of the residence times of the aliquots of water contained in the water sample  
(Maloszewski and Zuber, 1982; Cartwright et al., 2017). If the zone at the top of the aquifer  
485 approximates a well-mixed reservoir, the timespan is  $1/R_n$  (Leduc et al., 2000; Favreau et al.,  
2002).  $R_n$  values at Gatum are  $3 \times 10^{-4}$  to  $4 \times 10^{-1}$ , implying that recharge rates are averaged over  
decades to centuries. Thus, the recharge rates in the forest catchment may reflect those from  
both before and following the recent reforestation.

## 6. Conclusions

490 As has been discussed elsewhere (Scanlon et al., 2002; Healy, 2010; Crosbie et al., 2010, 2019;  
Cartwright et al., 2017; Moeck et al., 2020), estimating recharge rates can be difficult and a  
range of techniques together with other data (such as estimates of residence times) is required  
to produce reliable results. By necessity, estimating pre- and post-land clearing recharge rates

requires different methods. Both the CMB and WTF methods use data that are readily available  
495 (or is relatively low cost to attain). The uncertainties in the CMB estimates are relatively  
straightforward to address, and this represents a viable method of estimating historic recharge  
rates; however, the commonly-used WTF method may not be able to be applied in a  
straightforward manner to estimate present-day recharge rates. Relatively high WTF recharge  
rates (up to 161 and 366 mm yr<sup>-1</sup>) were also calculated in adjacent catchments with similar  
500 land-use (Dean et al., 2015; Perveen, 2016). <sup>3</sup>H activities in groundwater from those catchments  
are similar to those at Gatum, implying that recharge estimates based on the TRR method  
would again be significantly lower. Cartwright et al. (2007) and Crosbie et al. (2010) also  
reported that the recharge estimates from the TRR method and other geochemical tracers in  
semi-arid catchments elsewhere in Australia are lower than those from the WTF method. A  
505 similar observation was made for temperate catchments (Cartwright et al., 2020). Some of the  
discrepancy may be caused by the local presence of older water in lower permeability regions;  
however, this probably does not entirely account for the systematic differences across a range  
of catchments.

Additionally, the recharge rates are likely to be spatially variable across both catchments, and  
510 even with a relatively high density of data such as at Gatum, it is difficult to estimate typical  
or area-integrated values. In the case of understanding recharge rates in the plantation forest,  
the necessity that bores are in cleared areas (between the stands of trees) also makes it  
questionable whether the recharge rates are representative. Finally, all the geochemical  
techniques integrate recharge rate estimates over years to centuries and are thus ineffective at  
515 determining changes over short-timescale than this.

Detailed soil moisture measurements that would improve  $S_y$  estimates and geochemical tracers,  
such as <sup>3</sup>H, may not always be available. Integrated surface and subsurface hydrogeologic  
models, which simulate coupled groundwater, surface water and soil water fluxes, might

provide additional tools to estimate recharge rates that could be used to support the field and  
520 geochemical data (Scudeler et al., 2016; Daneshmand et al., 2019). With the increasing  
availability of soil moisture, evapotranspiration, rainfall, streamflow and groundwater  
elevation data, catchment water balance models (e.g., Wada et al., 2010; Moeck et al., 2020)  
might also represent viable methods of estimating recharge, especially over large areas.

The results of this study inform the understanding of hydrogeological processes in this and  
525 similar semi-arid regions globally. The present-day recharge rates in the pasture, which is  
typical of cleared land in southeast Australia, are likely to be  $<10 \text{ mm yr}^{-1}$ . Despite these being  
significantly higher than the pre-land clearing recharge rates, they only result in the gradual  
replacement of the older saline water stored in these aquifers (as is implied by the trends of  
dbgs vs. Cl and  $^3\text{H}$  vs. Cl: Figs. 4b, 4c). Additionally, while there has been a rise in the water  
530 table caused by increased recharge, and in some cases increased drainage in the streams, the  
magnitude of these changes will be limited by the modest recharge rates. The results also  
indicate that care must be used in assigning recharge rates as boundary conditions numerical  
models.

*Author contribution:* Shovon Barua and Ian Cartwright conducted the sampling assisted by P.  
535 Evan Dresel and Edoardo Daly. Shovon Barua carried out the analytical work conducted at  
Monash University. P. Evan Dresel and Edoardo Daly manage the field site and provided pre-  
existing data. All authors were involved in writing the manuscript.

*Competing interests:* The authors declare that they have no conflict of interest.

*Acknowledgements:* We thank Rob Lawrence (farm owner) and Georgie Luckock (plantation  
540 manager at PF Olsen Australia) for allowing us to access their farm and forest. Special thanks  
to Peter Hekmeijer from the Department of Jobs, Precincts and Regions, Victoria for his keen  
support in this study. Dr. Massimo Raveggi and Mrs. Rachelle Pierson are thanked for their  
help with the analytical work. The comments of three anonymous referees helped clarify the

paper. This project was funded by the Australian Research Council through its Discovery  
545 Program (grant DP180101229).

*Data Availability:* All analytical data is presented in the Supplement. Groundwater head data  
are from Dresel et al. (2018).

## REFERENCES

Adelana, S. M., Dresel, P. E., Hekmeijer, P., Zydor, H., Webb, J. A., Reynolds, M., and Ryan,  
550 M.: A comparison of streamflow, salt and water balances in adjacent farmland and forest  
catchments in south-western Victoria, Australia, *Hydrological Processes*, 29, 1630-1643,  
doi.org/10.1002/hyp.10281, 2015.

Allison, G. B., and Hughes, M. W.: The use of environmental chloride and tritium to estimate  
555 total recharge to an unconfined aquifer, *Australian Journal of Soil Research*, 16, 181-195,  
doi.org/10.1071/SR9780181, 1978.

Allison, G., Cook, P., Barnett, S., Walker, G., Jolly, I., and Hughes, M.: Land clearance and  
river salinisation in the western Murray Basin, Australia, *Journal of Hydrology*, 119, 1-20,  
560 doi.org/10.1016/0022-1694(90)90030-2, 1990.

Atkinson, A. P., Cartwright, I., Gilfedder, B., Cendón, D., Unland, N., and Hofmann, H.: Using  
 $^{14}\text{C}$  and  $^3\text{H}$  to understand groundwater flow and recharge in an aquifer window, *Hydrology and  
Earth System Sciences*, 18, 4951-4964, doi:10.5194/hess-18-4951, 2014.

565 Azarnivand, A., Camporese, M., Alaghmand, S., and Daly, E.: Simulated response of an  
intermittent stream to rainfall frequency patterns, *Hydrological Processes*, 34, 615-632,  
doi.org/10.1002/hyp.13610, 2020.

570 Bazuhair, A. S., and Wood, W. W.: Chloride mass-balance method for estimating ground water  
recharge in arid areas: examples from western Saudi Arabia, 186, 153-159,  
doi.org/10.1016/S0022-1694(96)03028-4, 1996.



575 Benyon, R. G., Theiveyanathan, S., and Doody, T. M.: Impacts of tree plantations on  
groundwater in south-eastern Australia, *Australian Journal of Botany*, 54, 181-192,  
doi:10.1071/BT05046, 2006.

580 Blackburn, G., and McLeod, S.: Salinity of atmospheric precipitation in the Murray-Darling  
drainage division, Australia, *Australian Journal of Soil Research*, 21, 411-434,  
doi.org/10.1071/SR9830411, 1983.

585 Bormann, M. E.: Temporal and spatial trends in rainwater chemistry across central and western  
Victoria, Honours Thesis, School of Life Sciences, College of Science, Health and  
Engineering, La Trobe University, Bundoora, Victoria 3086, Australia, 2004.

Bosch, J. M., and Hewlett, J.: A review of catchment experiments to determine the effect of  
vegetation changes on water yield and evapotranspiration, *Journal of Hydrology*, 55, 3-23,  
doi:0022-1694/82/0000-0000/S02.75, 1982.

590 Brouwer, J., and Fitzpatrick, R.: Interpretation of morphological features in a salt-affected  
duplex soil toposequence with an altered soil water regime in western Victoria, *Australian  
Journal of Soil Research*, 40, 903-906, doi.org/10.1071/SR02008, 2002.

Bureau of Meteorology: Commonwealth of Australia, <http://www.bom.gov.au>, 2020.

595 Cartwright, I., Weaver, T. R., Fulton, S., Nichol, C., Reid, M., and Cheng, X.:  
Hydrogeochemical and isotopic constraints on the origins of dryland salinity,  
Murray Basin, Victoria, Australia, *Applied Geochemistry*, 19, 1233-1254,  
doi:10.1016/j.apgeochem.2003.12.006, 2004.

600 Cartwright, I., Weaver, T. R., and Fifield, L. K.: Cl/Br ratios and environmental isotopes as  
indicators of recharge variability and groundwater flow: An example from the southeast  
Murray Basin, Australia, *Chemical Geology*, 231, 38-56, doi.org/10.1007/s10040-003-0318-9,  
2006.

605 Cartwright, I., Weaver, T. R., Stone, D., and Reid, M.: Constraining modern and historical  
recharge from bore hydrographs,  $^3\text{H}$ ,  $^{14}\text{C}$ , and chloride concentrations: applications to dual-

porosity aquifers in dryland salinity areas, Murray Basin, Australia, *Journal of Hydrology*, 332, 69-92, doi:10.1016/j.jhydrol.2006.06.034, 2007.

610

Cartwright, I.: The origins and behaviour of carbon in a major semi-arid river, the Murray River, Australia, as constrained by carbon isotopes and hydrochemistry, *Applied Geochemistry*, 25, 1734-1745, doi:10.1016/j.apgeochem.2010.08.020, 2010.

615 Cartwright, I., and Morgenstern, U.: Constraining groundwater recharge and the rate of geochemical processes using tritium and major ion geochemistry: Ovens catchment, southeast Australia, *Journal of Hydrology*, 475, 137-149, doi.org/10.1016/j.jhydrol.2012.09.037, 2012.

620 Cartwright, I., Fifield, L. K., and Morgenstern, U.: Using  $^3\text{H}$  and  $^{14}\text{C}$  to constrain the degree of closed-system dissolution of calcite in groundwater, *Applied Geochemistry*, 32, 118-128, doi:10.1016/j.apgeochem.2012.10.023, 2013.

625 Cartwright, I., Cendón, D., Currell, M., and Meredith, K.: A review of radioactive isotopes and other residence time tracers in understanding groundwater recharge: Possibilities, challenges, and limitations, *Journal of Hydrology*, 555, 797-811, doi.org/10.1016/j.jhydrol.2017.10.053, 2017.

630 Cartwright, I., Morgenstern, U., Hofmann, H., Gilfedder, B.: Comparisons and uncertainties of recharge estimates in a temperate alpine catchment, *Journal of Hydrology*, 590, 125558, doi.org/10.1016/j.jhydrol.2020.125558, 2020.

Cayley, R. A., and Taylor, D. H.: Grampians special map area geological report, Geological Survey of Victoria Report 107, 150, ISBN 0730694127, 1997.

635 Childs, E. C.: The nonsteady state of the water table in drained land, *Journal of Geophysical Research*, 65, 780-782, doi.org/10.1029/JZ065i002p00780, 1960.

Clarke, I. D., and Fritz, P.: *Environmental Isotopes in Hydrogeology*, Lewis Publishers, New York, USA, ISBN 1566702496, 1997.

640

- Clark, R. M., and Harvey, W.: Dryland salinity in Victoria in 2007: an analysis of data from the soil salinity database and Victorian discharge monitoring network, Department of Primary Industries, Primary Industries Research Victoria, Bendigo, ISBN 9781742170374, 2008.
- 645 Crosbie, R., S., Binning, P., and Kalma, J. D.: A time series approach to inferring groundwater recharge using the water table fluctuation method, *Water Resources Research*, 41, 1-9, doi:10.1029/2004WR003077, 2005.
- 650 Crosbie, R. S., Jolly, I. D., Leaney, F. W., and Petheram, C.: Can the dataset of field based recharge estimates in Australia be used to predict recharge in data-poor areas? *Hydrology and Earth System Sciences*, 14, 2023-2038, doi:10.5194/hess-14-2023-2010, 2010.
- 655 Crosbie, R., Morrow, D., Cresswell, R., Leaney, F., Lamontagne, S., and Lefournour, M.: New insights to the chemical and isotopic composition of rainfall across Australia, *Water for a Healthy Country Flagship Report Series*, ISSN 1835095X, 2012.
- 660 Crosbie, R. S., Doble, R. C., Turnadge, C., and Taylor, A. R.: Constraining the magnitude and uncertainty of specific yield for use in the water table fluctuation method of estimating recharge, *Water Resources Research*, 55, 7343-7361, doi.org/10.1029/2019WR025285, 2019.
- 665 Daneshmand, H., Alaghmand, S., Camporese, M., Talei, A., and Daly, E.: Water and salt balance modelling of intermittent catchments using a physically-based integrated model, *Journal of Hydrology*, 568, 1017-1030, doi.org/10.1016/j.jhydrol.2018.11.035, 2019.
- 670 Davis, S. N., Whittemore, D. O., and Fabryka-Martin, J.: Uses of chloride/bromide ratios in studies of potable water, *Groundwater*, 36, 338-350, doi:10.1111/j.1745-6584.1998.tb01099.x, 1998.
- Davis, S. N., Cecil, L. D., Zreda, M., and Moysey, S.: Chlorine-36, bromide, and the origin of spring water, *Chemical Geology*, 179, 3-16, doi:10.1016/S0009-2541(01)00312-6, 2001.
- Davies, P. J., and Crosbie, R. S.: Mapping the spatial distribution of chloride deposition across Australia, *Journal of Hydrology*, 561, 76-88, doi.org/10.1016/j.jhydrol.2018.03.051, 2018.

- 675 Dean, J. F., Webb, J. A., Jacobson, G. E., Chisari, R., and Dresel, P. E.: Biomass uptake and fire as controls on groundwater solute evolution on a southeast Australian granite: aboriginal land management hypothesis, *Biogeosciences*, 11, 4099-4114, doi.org/10.5194/bg-11-4099-2014, 2014.
- 680 Dean, J. F., Webb, J. A., Jacobsen, G. E., Chisari, R., and Dresel, P. E.: A groundwater recharge perspective on locating tree plantations within low-rainfall catchments to limit water resource losses, *Hydrology and Earth System Sciences*, 19, 1107-1123, doi:10.5194/hess-19-1107, 2015.
- 685 Dean, J. F., Camporese, M., Webb, J. A., Grover, S. P., Dresel, P. E., and Daly, E.: Water balance complexities in ephemeral catchments with different land uses: Insights from monitoring and distributed hydrologic modeling, *Water Resources Research*, 52, 4713-4729, doi.org/10.1002/2016WR018663, 2016.
- 690 de Vries, J. J., and Simmers, I.: Groundwater recharge: An overview of processes and challenges, *Hydrogeology Journal*, 10, 5-17, doi.org/10.1007/s10040-001-0171-7, 2002.
- Doble, R. C., and Crosbie, R. S.: Review: Current and emerging methods for catchment-scale modelling of recharge and evapotranspiration from shallow groundwater, *Hydrogeology Journal*, 25, 3-23, doi.org/10.1007/s10040-016-1470-3, 2017.
- 695 Dresel, P. E., Zydor, H., Hekmeijer, P., and Adelana, S. M.: Catchment scale impacts of land use in south-western Victoria, Project CMI Number: 102920, ISBN 9781742642337, 2012.
- 700 Dresel, P. E., Dean, J. F., Perveen, F., Webb, J. A., Hekmeijer, P., Adelana, S. M., and Daly, E.: Effect of eucalyptus plantations, geology, and precipitation variability on water resources in upland intermittent catchments, *Journal of Hydrology*, 564, 723-739, doi.org/10.1016/j.jhydrol.2018.07.019, 2018.
- 705 Eriksson, E., and Khunakasem, V.: Chloride concentrations in groundwater, recharge rate and rate of deposition of chloride in the Israel coastal plain, *Journal of Hydrology (Amsterdam)*, 7, 178-197, doi.org/10.1016/0022-1694(69)90055-9, 1969.

Favreau, G., Leduc, C., Marlin, C., Dray, M., Taupin, J. D., Massault, M., Le Gal La Salle, C.,  
710 and Babic, M.: Estimate of recharge of a rising water table in semiarid niger from  $^3\text{H}$  and  $^{14}\text{C}$   
modeling, *Groundwater*, 40, 144-151, doi.org/10.1111/j.1745-6584.2002.tb02499.x, 2002.

Fohrer, N., Haverkamp, S., Eckhardt, K., and Frede, H. G.: Hydrologic response to land use  
changes on the catchment scale, *Physics and Chemistry of the Earth, Part B, Hydrology,*  
715 *Oceans and Atmosphere*, 26, 577-582, doi.org/10.1016/S1464-1909(01)00052-1, 2001.

Foley, J. A., de Fries, R., Asner, G. P., Barford, C., Bonan, G., Carpenter, S. R., Chapin, F. S.,  
Coe, M. T., Daily, G. C., Gibbs, H. K., Helkowski, J. H., Holloway, T., Howard, E. A.,  
Kucharik, C. J., Monfreda, C., Patz, J. A., Prentice, C., Ramankutty, N., and Snyder, P. K.:  
720 Global consequences of land use, *Science*, 309, 570-574, doi:10.1126/science.1111772, 2005.

Freeze, R. A., and Cherry, J. A.: *Groundwater*, Englewood Cliffs, New Jersey, Prentice-Hall,  
604, ISBN-13: 9780133653120, 1979.

725 Gee, G., Fayer, M., Rockhold, M., and Campbell, M.: Variations in recharge at the Hanford  
Site, *Northwest Science*, 66, 1992.

Gelsinari, S., Doble, R., Daly, E., and Pauwels, V. R. N.: Feasibility of improving  
groundwater modeling by assimilating evapotranspiration rates, *Water Resources*  
730 *Research*, 56, e2019WR025983, doi.org/10.1029/2019WR025983, 2020.

Gillham, R. W.: The capillary fringe and its effect on water-table response, *Journal of*  
*Hydrology*, 67, 307-324, doi.org/10.1016/0022-1694(84)90248-8, 1984.

735 Healy, R. W., and Cook, P. G.: Using groundwater levels to estimate recharge, *Hydrogeology*  
*Journal*, 10, 91-109, doi.org/10.1007/s10040-001-0178-0, 2002.

Healy, R. W.: *Estimating Groundwater Recharge*, Cambridge University Press, ISBN  
9780511780745, doi.org/10.1017/CBO9780511780745, 2010.

740

- Herczeg, A. L., Dogramaci, S. S., and Leaney, F. W. J.: Origin of dissolved salts in a large, semi-arid groundwater system: Murray Basin, Australia, *Australian Journal of Marine and Freshwater Research*, 52, 41-52, doi:10.1071/MF00040, 2001.
- 745 Hewlett, J. D., and Hibbert, A. R.: Factors affecting the response of small watersheds to precipitation in humid areas, *Forest Hydrology*, 1, 275-290, doi.org/10.1177%2F0309133309338118, 1967.
- 750 Howcroft, W., Cartwright, I., Fifield, L. K., and Cendón, D.: Differences in groundwater and chloride residence times in saline groundwater: The Barwon River catchment of southeast Australia, *Chemical Geology*, 451, 154-168, doi.org/10.1016/j.chemgeo.2017.01.015, 2017.
- 755 Hua, Q., and Barbetti, M.: Review of tropospheric bomb  $^{14}\text{C}$  data for carbon cycle modeling and age calibration purposes, *Radiocarbon*, 46, 1273-1298, doi.org/10.1017/S0033822200033142, 2004.
- Hutton, J., and Leslie, T.: Accession of non-nitrogenous ions dissolved in rainwater to soils in Victoria, *Australian Journal of Agricultural Research*, 9, 492-507, doi.org/10.1071/AR9580492, 1958.
- 760 Hvorslev, M. J.: Time lag and soil permeability in ground-water observations, Bulletin No. 36, Waterways Experiment Station, Corps of Engineers, United States Army, Vicksburg, Mississippi, 1951.
- 765 Jurgens, B. C., Bohkle, J. K., and Eberts, S. M.: TracerLPM (Version 1): An Excel® workbook for interpreting groundwater age distributions from environmental tracer data, United States Geological Survey, Techniques and Methods Report 4-F3, United States Geological Survey, Reston, USA, 60, doi.org/10.3133/tm4F3, 2012.
- 770 Kloppmann, W., Négrel, P., Casanova, J., Klinge, H., Schelkes, K., and Guerrot, C.: Halite dissolution derived brines in the vicinity of a Permian salt dome (N German Basin). Evidence from boron, strontium, oxygen, and hydrogen isotopes, *Geochimica et Cosmochimica Acta*, 65, 4087-4101, doi.org/10.1016/S0016-7037(01)00640-8, 2001.

- 775 Le Gal La Salle, C., Marlin, C., Leduc, C., Taupin, J. D., Massault, M., and Favreau, G.: Renewal rate estimation of groundwater based on radioactive tracers ( $^3\text{H}$ ,  $^{14}\text{C}$ ) in an unconfined aquifer in a semi-arid area, Iullemeden Basin, Niger, *Journal of Hydrology*, 254, 145-156, doi.org/10.1016/S0022-1694(01)00491-7, 2001.
- 780 Leduc, C., Sabljak, S., Taupin, J. D., Marlin, C., and Favreau, G.: Recharge of the Quaternary water table in the northwestern Lake Chad basin (southeastern Niger) estimated from isotopes, *Comptes Rendus de l'Académie des Sciences - Series IIA - Earth and Planetary Science*, 330, 355-361, ISSN 12518050, 2000.
- 785 Lerner, D. N., Issar, A. S., and Simmers, I.: Groundwater recharge: a guide to understanding and estimating natural recharge, *International Contributions to Hydrogeologists*, 10, International Association of Hydrogeologists, Goring, UK, 1990.
- Lerner, D. N., and Harris, B.: The relationship between land use and groundwater resources and quality, *Land Use Policy*, 26S, S265-S273, doi:10.1016/j.landusepol.2009.09.005, 2009.
- 790 Lewis, M. F.: Factors affecting the development of dryland salinity in a catchment on the Dundas tableland, western Victoria, Land Protection Service, Department of Conservation Forests and Lands, 7, 1-97, 1985.
- 795 Maloszewski, P., and Zuber, A.: Determining the turnover time of groundwater systems with the aid of environmental tracers: 1, Models and their applicability, *Journal of Hydrology*, 57, 207-231, doi.org/10.1016/0022-1694(82)90147-0, 1982.
- 800 McCormac, F. G., Hogg, A. G., Blackwell, P. G., Buck, C. E., Higham, T. F. G., and Reimer, P. J.: SHCal04 Southern Hemisphere Calibration, 0-11.0 cal kyr BP: *Radiocarbon*, 46, 1087-1092, doi.org/10.1017/S0033822200033014, 2004.
- 805 Moeck, C., Grech-Cumbo, N., Podgorski, J., Bretzler, A., Gurdak, J. J., Berg, M., and Schirmer, M.: A global-scale dataset of direct natural groundwater recharge rates: A review of variables, processes and relationships, *Science of the Total Environment*, 717, 137042. doi.org/10.1016/j.scitotenv.2020.137042, 2020.

810 Morgenstern, U., and Taylor, C. B.: Ultra low-level tritium measurement using electrolytic  
enrichment and LSC, *Isotopes in Environmental and Health Studies*, 45, 96-117,  
doi.org/10.1080/10256010902931194, 2009.

815 Morgenstern, U., Stewart, M. K., and Stenger, R.: Dating of streamwater using tritium in a post  
nuclear bomb pulse world: continuous variation of mean transit time with streamflow,  
*Hydrology and Earth System Sciences*, 14, 2289-2301, doi:10.5194/hess-14-2289-2010, 2010.

820 Owuor, S. O., Butterbach-Bahl, K., Guzha, A. C., Rufino, M. C., Pelster, D. E.,  
Díaz-Pinés, E., and Breuer, L.: Groundwater recharge rates and surface runoff  
response to land use and land cover changes in semi-arid environments, *Ecological  
Processes*, 5, 16, doi.org/10.1186/s13717-016-0060-6, 2016.

825 Perveen, F.: Assessing the impacts of changing land use and geology on groundwater and  
surface water resources in south-western Victoria, Australia, PhD Thesis, School of Life  
Sciences, College of Science, Health and Engineering, La Trobe University, Bundoora,  
Victoria 3086, Australia, 1-243, <http://hdl.handle.net/1959.9/560005>, 2016.

830 Raiber, M., Webb, J. A., Cendón, D. I., White, P. A., and Jacobsen, G. E.: Environmental  
isotopes meet 3D geologic modelling: conceptualising recharge and structurally controlled  
aquifer connectivity in the basalt plain of southwestern Victoria, Australia, *Journal of  
Hydrology*, 527, 262-280, doi.org/10.1016/j.jhydrol.2015.04.053, 2015.

835 Scanlon, B. R.: Uncertainties in estimating water fluxes and residence times using  
environmental tracers in an arid unsaturated zone, *Water Resources Research*, 36, 395-409,  
doi.org/10.1029/1999WR900240, 2000.

Scanlon, B. R., Healy, R. W., and Cook, P. G.: Choosing appropriate techniques for quantifying  
groundwater recharge, *Hydrogeology Journal*, 10, 18-39, doi.org/10.1007/s10040-001-0176-2,  
2002.

840 Scanlon, B. R., Keese, K. E., Flint, A. L., Flint, L. E., Gaye, C. B., Edmunds, W. M., and  
Simmers, I.: Global synthesis of groundwater recharge in semiarid and arid regions,  
*Hydrological Processes*, 20, 3335-3370, doi:10.1002/hyp.6335, 2006.




- 845 Scudeler, C., Pangle, L., Pasetto, D., Niu, Guo-Yue, Volkmann, T., Paniconi, C., Putti, M., and Troch, P.: Multiresponse modeling of variably saturated flow and isotope tracer transport for a hillslope experiment at the Landscape Evolution Observatory, *Hydrology and Earth System Sciences*, 20, 4061-4078, doi.org/10.5194/hess-20-4061-2016, 2016.
- 850 Sibanda, T., Nonner, J. C., and Uhlenbrook, S.: Comparison of groundwater recharge estimation methods for the semi-arid Nyamandhlovu area, Zimbabwe, *Hydrogeology Journal*, 17, 1427-1441, doi.org/10.1007/s10040-009-0445-z, 2009.
- 855 Siebert, S., Burke, J., Faures, M., Frenken, K., Hoogeveen, J., Döll, P., and Portmann, F. T.: Groundwater use for irrigation - a global inventory, *Hydrology and Earth System Sciences*, 14, 1863-1880, doi.org/10.5194/hess-14-1863-2010, 2010.
- Sophocleous, M.: The role of specific yield in groundwater recharge estimations: A numerical study, *Groundwater*, 23, 52-58, doi.org/10.1111/j.1745 6584.1985.tb02779.x, 1985.
- 860 Stewart, M. K., Thomas, J. T., Norris, M., and Trompeter, V.: Paleogroundwater in the Moutere gravel aquifers near Nelson, New Zealand, *Radiocarbon*, 46, 517-529, doi:10.1017/S0033822200035578, 2004.
- 865 Sudicky, E. A., and Frind, E. O.: Carbon 14 dating of groundwater in confined aquifers: implications of aquitard diffusion. *Water Resources Research*, 17, 1060-1064, doi.org/10.1029/WR017i004p01060, 1981.
- 870 Tadros, C. V., Hughes, C. E., Crawford, J., Hollins, S. E., and Chisari, R.: Tritium in Australian precipitation: A 50 year record, *Journal of Hydrology*, 513, 262-273, doi:10.1016/j.apgeochem.2014.04.016, 2014.
- Vogel, J. C.: Groningen radiocarbon dates IX, *Radiocarbon*, 12, 444-471, doi.org/10.1017/S0033822200008183, 1970.

875 Wada, Y., van Beek, L. P. H., van Kempen, C. M., Reckman, J. W. T. M., Vasak, S., and Bierkens, M. F. P.: Global depletion of groundwater resources, *Geophysical Research Letters*, 37, L20402, doi.org/10.1029/2010GL044571, 2010.

Zuber, A., and Maloszewski, P.: Lumped parameter models, chap. 2 of Mook, W. G., and Yurtsever, Y., eds., vol 6: *Modelling in Environmental Isotopes in the Hydrological Cycle: Principles and Applications*: Paris, France, UNESCO, Technical Documents in Hydrology, 39, 5-35, 2001.

# Figures



885 Figure 1: (a) Map of the Gatum pasture and forest catchments with the locations of groundwater  
 bores (3007 & 3008, 3666 & 3667, and 3656 & 3657 are nested bores); shallow piezometers  
 are at PD (pasture drainage zone), PB (pasture lower slope), FD (forest drainage zone), and FB  
 (forest lower slope). The catchment boundaries for the streams are from Dresel et al. (2018).  
 890 (b) Mean hydraulic heads of groundwater from 2010 to 2017 except for 3008 (from 2010 to  
 2015) and 3658 (from 2010 to 2016) with sample depths and flow directions. Background  
 ArcGIS® 10.5 image (Esri, HERE, Garmin, ©OpenStreetMap contributors and the GIS User  
 Community, Source: Esri, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS,  
 USDA, USGS, AeroGRID, IGN, and the GIS User Community).

895






Figure 2: Simplified cross sections of (a) pasture and (b) forest catchments showing variability of groundwater recharge estimated via WTF, CMB, <sup>3</sup>H methods and variable hydraulic conductivity of the aquifer lithologies. Transects are on Fig. 1a. PD and FD represent the shallow groundwater in the pasture drainage and forest drainage areas, respectively. Data from Table 1.


900



905 Figure 3: (a) Daily rainfall at Cavendish (Station 089009: ~19 km southeast of Gatun). Variation in groundwater heads from bores in (b) pasture and (c) forest (Dresel et al., 2018). The legend shows the sample depths (in parentheses) and landscape positions.



910 Figure 4: (a) Variation of molar Cl/Br ratios with molar concentrations of Cl. (b) Molar Cl concentrations across depth below ground surface (dbgs: m). (c) <sup>3</sup>H (TU) vs. molar Cl concentrations. (d) Molar Ca vs. HCO<sub>3</sub> concentrations. Cross and plus symbols are for the shallow riparian groundwater and other symbols are for the regional groundwater.



915 Figure 5: Activities of  $^3\text{H}$  (TU) and  $^{14}\text{C}$  (pMC) in the pasture and forest groundwater. PEM = partial exponential model (PEM ratio in brackets) and DM = dispersion model (DP parameter in brackets). Cross and plus symbols are for the shallow riparian groundwater and other symbols are for the regional groundwater. The single high  $^3\text{H}$  activity possibly reflects recharge by winter rainfall. Samples lying to the left of the covariance curves probably record mixing between younger and older groundwater (see text for discussion).

920




Figure 6: Ranges of groundwater residence times in k yr estimated using different LPMs. The numbers above the box represent sample IDs. PD and FD represent the shallow groundwater in the pasture drainage and forest drainage areas, respectively. Data from Table 1.

925







Figure 7: Recharge rates in  $\text{mm yr}^{-1}$  estimated from (a) CMB, (b) WTF and (c) TRR. PD and FD are for the shallow groundwater in the pasture drainage and forest drainage areas, respectively. Bars indicate the ranges of recharge rates from Table 1.



930

Figure 8: Comparison between recharge rates for the regional groundwater estimated from WTF and TRR. Bars represent the ranges of calculated recharge values from Table 1.

Table 1: Groundwater recharge rates and estimated residence times of groundwater.

Sample	Sample depth (m)	Landscape position	Recharge rates (mm yr <sup>-1</sup> )			Groundwater residence times (yr)							
			WTF	CMB	TRR	PEM (0.05)		PEM (0.5)		DM (0.05)		DM (1.0)	
						<i>q</i> = 0.9	<i>q</i> = 1.0	<i>q</i> = 0.9	<i>q</i> = 1.0	<i>q</i> = 0.9	<i>q</i> = 1.0	<i>q</i> = 0.9	<i>q</i> = 1.0
<b>Pasture Catchment</b>													
63	15.5	Upper	30-500	31.7-61.6	0.8-14.0		180	60	150	70	80		270
3013	19.2	Upper	30-300	0.7-1.5		210	780	140	690	90	680	270	780
3001	10.7	Mid	15-150	0.4-0.7									
3002	8	Mid	15-150	0.4-0.7		660	1470	540	1380	540	1290	650	1620
3004	10.6	Mid	30-350	0.6-1.2		2010	3200	1860	2910	1710	2730	2220	3650
3019	13.3	Mid	30-200	1.3-2.5									
3007	17	Drainage	30-200	0.5-0.9		190	720	160	600	90	600	270	720
3008	1.3	Drainage	30-100	0.3-0.6	0.5-8.0	70	390	110	200	80	120	90	420
PD1	1	Drainage		0.6-1.2	0.05-0.3	240	860	170	750	110	740	320	870
PD2	1	Drainage		0.4-1.2	0.08-0.5	390	1080	200	1020	120	960	420	1170
64	29.7	Lower	30-400	0.4-0.7		2240	3470	2070	3150	1920	2960	2510	3930
PB1	1	Lower		0.3-0.7									
PB2	1	Lower		0.3-0.7									
<b>Forest Catchment</b>													
3662	16.9	Upper	30-100	0.5-0.9									
3663	24.8	Upper		0.5-0.9	0.04-0.6	320	960	180	870	110	830	360	990
3665	13	Upper	30-200	0.6-1.3	0.02-0.3	170	660	150	540	90	560	250	660
3668	28.4	Mid		1.8-3.5		17000	19600	13100	14700	10800	11900	21400	24700
3658	15.8	Drainage		4.3-11.2									
3666	28	Drainage	30-100	0.4-0.8		11500	13600	9480	10900	8160	9230	14300	17100
3667	18	Drainage	30-100	0.4-0.9		5850	7440	5160	6450	4780	5870	6930	9000
3669	9	Drainage	30-300	0.7-1.5	0.01-0.2	330	990	180	930	110	870	380	1020
FD1	1	Drainage		4.6-8.9									
FD2	1	Drainage		30.3-58.8	<sup>3</sup> H (>2.8)		210	70	170	80	90		300
FD3	1	Drainage		1.4-2.7									
FD4	1	Drainage		1.2-2.9	13.3-89.0	260	860	170	750	90	740	320	870
3656	28.8	Lower	30-400	0.3-0.7									
3657	2.5	Lower	30-300	0.4-0.8	3.6-59.5		300	90	170	80	110		330
FB1	1	Lower		25.3-49.0									
FB2	1	Lower		1.7-6.8									
FB3	1	Lower		0.2-0.6									
FB4	1	Lower		0.3-1.2									

Landscape positions: Upper, Mid, and Lower slopes as discussed in text. Sample depth is the middle of the screened interval. The recharge rates from WTF method were calculated for bore hydrographs that show seasonal variations in hydraulic head. The recharge rates with TRR were calculated assuming *b* was 1 to 5 m (bores) and 1 to 2 m (shallow piezometers). The groundwater samples that do not show mixing of young and old groundwater, were calculated for recharge rates from TRR and residence times. Groundwater residence times not calculate for those samples which exceed the upper limit of <sup>14</sup>C concentrations in lumped parameter models.