

Dear Editor and reviewers,

We highly appreciate your review and useful suggestions for our manuscript. We have made corresponding revisions in our manuscript according to your comments. Hopefully these changes will fulfill your expectations. Below are the point-to-point responses to the comments. The comments from reviewers are in blue while our responses appear in black. The red color indicates the newly-added contents in the revised manuscript. The page and line numbers given below refer to the numbers in the version of revised manuscript without changes tracked.

Yours truthfully,

Kind regards, all authors

**Referee #1:**

**Comment #1:** Since the internal climate variability in this paper is represented by the simulations of SDRM-MCREM, whether the contribution of internal climate variability to the total uncertainty is directly relevant with the performances of SDRM-MCREM? For example, in Figure 10, the contribution of internal climate variability in annual maximum 1-day flow for larger return periods is obviously larger than smaller return periods, whether this indicates the poor performance of SDRM-MCREM in simulating extremes? Please explain.

**Authors' response:** Thanks for your question. There are two commonly-used approaches for the quantification of the internal variability of the climate system: the first one is using multiple members of GCMs to reflect internal climate variability (Bracegirdle et al., 2014); the second one is taking the randomness of weather generators or stochastic rainfall models as the internal climate variability (Lafaysse et al., 2014; Fatichi et al., 2016). In this way, it is unavoidable that the contribution of internal climate variability is dependent on the performances of the adopted methods. This means that the contribution of internal climate variability to the total uncertainty is not only directly dependent on the performance of SDRM-MCREM in this study, but also dependent on the performance of other methods if other methods were adopted. In this study, to avoid the impacts of a poor performance of a stochastic rainfall model on its randomness and affecting the representation of internal climate variability, we have made great efforts to apply the well-performing stochastic rainfall model SDRM-MCREM, which showed good results for simulation of both rainfall time-series characteristics and rainfall event characteristics. The advantages of SDRM-MCREM compared to other weather generators and stochastic rainfall models are described in Gao et al. (2020a). In addition, the inferior performance of weather generators and stochastic rainfall models in simulating extremes and inherent large uncertainties is a common problem. Compared to other weather

generators, the SDRM-MCREM performs relatively better in reproducing rainfall extremes (Gao et al. 2020a). To draw conclusions about the contributions of different uncertainty sources in a more accurate and reliable way in this study, we summarized the findings of this study for an average return period and also compared these results with previous studies (see Page 24, Line 450-457).

#### References:

- Bracegirdle, T. J., Turner, J., Hosking, J. S., and Phillips, T.: Sources of uncertainty in projections of twenty-first century westerly wind changes over the Amundsen Sea, West Antarctica, in *CMIP5 climate models*, *Clim. Dyn.*, 43, 2093-2104, <https://doi.org/10.1007/s00382-013-2032-1>, 2014.
- Lafaysse, M., Hingray, B., Mezghani, A., Gailhard, J., and Terray, L.: Internal variability and model uncertainty components in future hydrometeorological projections: The Alpine Durance basin, *Water Resour. Res.*, 50, 3317-3341, 2014.
- Fatichi, S., Ivanov, V. Y., Paschalis, A., Peleg, N., Molnar, P., Rimkus, S., Kim, J., Burlando, P., and Caporali, E.: Uncertainty partition challenges the predictability of vital details of climate change, *Earth Future*, 4, 240-251, <https://doi.org/10.1002/2015ef000336>, 2016.
- Gao, C., Booij, M. J., and Xu, Y.-P.: Development and hydrometeorological evaluation of a new stochastic daily rainfall model: coupling Markov chain with rainfall event model, *J. Hydrol.*, under revision, 2020a.

**Comment #2:** Another main usage of stochastic rainfall model is to downscale climate model outputs by adjusting parameters of stochastic rainfall models for climate change impact studies. The future GCMs rainfall data in this study are directly simulated by SDRM-MCREM using the bias corrected GCM future data rather than through downscaling by SDRM-MCREM. Can the authors explain why you conducted like this?

**Authors' response:** There are two reasons why we conducted the study in this way. Firstly, the bias-corrected future GCM rainfall data already contain sufficient information to reflect the impacts of climate change on rainfall characteristics. Gao et al. (2020b) investigated the changes of rainfall event characteristics using bias-corrected historical and future GCM data, and found that not only the distributions of rainfall duration and rainfall depth would change, but also the temporal patterns of rainfall events would change in the future. Secondly, obtaining realizations of future rainfall time series through simulating the bias-corrected future GCM data using SDRM-MCREM in order to consider future internal climate variability is more straightforward and easier. As far as we know, using weather generators or stochastic rainfall models to downscale GCM future simulations currently is mainly through perturbing the parameters of weather generators, like the transition probabilities of rainfall occurrence and parameters of the distribution of rainfall amount, using monthly averaged additive or multiplicative change factors of GCM projections (Chen et al., 2012; Li and Babovic, 2018). However, it cannot be guaranteed that these kinds of downscaling methods can fully incorporate changes of rainfall characteristics (e.g.

temporal patterns of rainfall events) although it has been commonly used in previous studies. In addition, it is complicated to carry out the whole downscaling process. Based on the above, it is considered more convenient and useful to directly simulate the bias-corrected GCM rainfall series using SDRM-MCREM in this study.

#### References:

- Gao, C., Booij, M. J., and Xu, Y. P.: *Impacts of climate change on characteristics of daily-scale rainfall events based on nine selected GCMs under four CMIP5 RCP scenarios in Qu River basin, east China*, *Int. J. Climatol.*, 40, 887-907, <https://doi.org/10.1002/joc.6246>, 2020b.
- Chen, J., Brissette, F. P., and Leconte, R.: *Downscaling of weather generator parameters to quantify hydrological impacts of climate change*, *Climate Research*, 51, 185-200, <https://doi.org/10.3354/cr01062>, 2012.
- Li, X., and Babovic, V.: *Multi-site multivariate downscaling of global climate model outputs: an integrated framework combining quantile mapping, stochastic weather generator and Empirical Copula approaches*, *Clim. Dyn.*, 52, 5775-5799, <https://doi.org/10.1007/s00382-018-4480-0>, 2018.

**Comment #3:** Obviously, there also exists uncertainty in the process of hydrological modelling. Why did your study only consider the uncertainty of RCPs, GCMs and internal climate variability and neglects the uncertainty of hydrological parameters that seems can be easily incorporated. Please explain.

**Authors' response:** Thanks for your question. In the process of hydrological modelling, uncertainty in hydrological model structures is also present besides uncertainty in hydrological parameters. There are two reasons why we did not take the uncertainty in hydrological modelling into consideration in this study. Firstly, many previous studies indicated that uncertainty originating from climate projections is generally larger than uncertainty in the hydrological simulation process (Teng et al., 2012; Karlsson et al., 2016), and uncertainty from hydrological model structures and parameters sets is less important for peak flows (Vetter et al., 2016; De Niel et al., 2019) (See Page 2, Line 56-63). Repeating their work seems not very necessary. In addition, the main purposes of this study are (1) to use the newly-developed well-performing stochastic rainfall model SDRM-MCREM to generate multiple realizations of GCM data and reflect internal climate variability; (2) to investigate how climate projection uncertainties, including RCP uncertainty, GCM uncertainty and internal climate variability, propagate into streamflow projections and estimate their contributions to streamflow projection uncertainty. This has also been described in the introduction section (see Page 3, Line 88-96). Because of this, we did not take the uncertainty of hydrological modelling into account in this study. For future research work, to obtain a comprehensive insight into projected changes of high flows and low flows and the contributions of different uncertainty sources, it is aimed to consider all sources of uncertainty arising from scenarios, climate models, internal climate variability, downscaling methods, hydrological models and hydrological parameters (See Page 25, Line 466-468).

## References:

- De Niel, J., Van Uytven, E., and Willems, P.: *Uncertainty Analysis of Climate Change Impact on River Flow Extremes Based on a Large Multi-Model Ensemble*, *Water Resour. Manag.*, 33, 4319-4333, <https://doi.org/10.1007/s11269-019-02370-0>, 2019.
- Karlsson, I. B., Sonnenborg, T. O., Refsgaard, J. C., Trolle, D., Børgesen, C. D., Olesen, J. E., Jeppesen, E., and Jensen, K. H.: *Combined effects of climate models, hydrological model structures and land use scenarios on hydrological impacts of climate change*, *J. Hydrol.*, 535, 301-317, <https://doi.org/10.1016/j.jhydrol.2016.01.069>, 2016.
- Teng, J., Vaze, J., Chiew, F. H. S., Wang, B., and Perraud, J.-M.: *Estimating the Relative Uncertainties Sourced from GCMs and Hydrological Models in Modeling Climate Change Impact on Runoff*, *J. Hydrometeorol.*, 13, 122-139, <https://doi.org/10.1175/jhm-d-11-058.1>, 2012.
- Vetter, T., Reinhardt, J., Flörke, M., van Griensven, A., Hattermann, F., Huang, S., Koch, H., Pechlivanidis, I. G., Plötner, S., Seidou, O., Su, B., Vervoort, R. W., and Krysanova, V.: *Evaluation of sources of uncertainty in projected hydrological changes under climate change in 12 large-scale river basins*, *Clim. Change*, 141, 419-433, <https://doi.org/10.1007/s10584-016-1794-y>, 2016.

**Comment #4:** L36. “responses of” <-> ”responses to”.

**Authors’ response:** Thank you. We have replaced “responses of” with “responses to”.

**Comment #5:** L39. “the coupled system” – the atmosphere-ocean coupled system?

Please make it clear.

**Authors’ response:** Thank you. “the coupled system” does refer to “the coupled atmosphere-ocean system”. We have revised it.

**Comment #6:** L48. “The relative importance” refers to what? Please make it clear.

**Authors’ response:** Thank you. Here “The relative importance” refers to the relative importance of different uncertainty sources. Therefore, the original content has been modified to “The relative importance of different uncertainty sources”, which can be found in Page 2, Line 48

**Comment #7:** L124. “In this study, we used the distribution mapping (DM) method to correct GCM-simulated climate variable” – at this point in the text, some further explanation about why choosing the DM method is needed in the context.

**Authors’ response:** Thank you. We have further explained why we chose the DM method to bias correct the simulations of GCMs in this study. The added contents can be found in Page 5, Line 126-130, which also can be seen as follows:

“Considering that the distribution mapping (DM) method usually shows a comprehensive skill in bias correcting the mean,

standard deviation and various frequency-based indices and even correcting unobserved extreme values compared with other existing bias correction approaches like power transformation (PT), local intensity scaling (LOCI), linear scaling (LS), delta change (DC) and quantile mapping (QM) (Fang et al., 2015;Teutschbein and Seibert, 2012;Ji et al., 2020), the DM method was selected to correct GCM-simulated climate variables based on observations in this study.”

Reference:

- Fang, G. H., Yang, J., Chen, Y. N., and Zammit, C.: Comparing bias correction methods in downscaling meteorological variables for a hydrologic impact study in an arid area in China, *Hydrol. Earth Syst. Sci.*, 19, 2547-2559, <https://doi.org/10.5194/hess-19-2547-2015>, 2015.
- Teutschbein, C., and Seibert, J.: Bias correction of regional climate model simulations for hydrological climate-change impact studies: Review and evaluation of different methods, *J. Hydrol.*, 456-457, 12-29, <https://doi.org/10.1016/j.jhydrol.2012.05.052>, 2012.
- Ji, X., Li, Y., Luo, X., He, D., Guo, R., Wang, J., Bai, Y., Yue, C., and Liu, C.: Evaluation of bias correction methods for APHRODITE data to improve hydrologic simulation in a large Himalayan basin, *Atmospheric Research*, 242, <https://doi.org/10.1016/j.atmosres.2020.104964>, 2020.

**Comment #8:** L129. Please check the correctness of Eq. (2).

**Authors' response:** Thank you for your comment. There is indeed a small error in Eq. (2). The variable “ $x_{sim,his}$ ” at the right hand side of the equation has been modified to “ $x_{sim,fut}$ ”.

**Comment #9:** L189. “is” <-> “was”. The tense of this paper in the method part is a bit confusing. Please check the whole paper and ensure proper use of the tense.

**Authors' response:** Thank you. We have corrected this. In addition, we have checked the tense throughout the whole manuscript and have made the corresponding corrections, especially in the description of the used methods, including the sections of methods and results. The detailed revision can be found in the revised manuscript with changes tracked.

**Comment #10:** L338. In this paper, when investigating the changes of high flows and low flows, the 5-, 10- and 20-year return periods are adopted. Why not use the larger return periods such 50-year and 100-year return periods that are more useful information for assessment of extreme hydrological events?

**Authors' response:** To avoid introducing additional uncertainty through fitting observed and simulated 30-year high and low flows series with a probability distribution, the empirical cumulative distribution was directly used to calculate the values of high flows and low flows at different return periods in this study. Therefore, the largest return period calculated in this study is nearly 30 years, which obviously is smaller than 50 years and 100 years. This is why the high flows and

low flows at 50-year and 100-year return periods are not reported in this study.

**Comment #11:** L421. “account for approximately 54-60% on average” – Does this mean the proportion of the total uncertainty? Please make it clear.

**Authors’ response:** Thank you. This is exactly the proportion of the total uncertainty. Therefore, we have modified the original content to “account for approximately 54-60% of the total uncertainty on average” in Page 24, Line 440.

**Referee #2:**

**Comment #1:** This manuscript only explained how to disaggregate monthly precipitation into daily precipitation considering the internal climate variability. How to downscale air temperature from monthly scale to daily scale should be also explained in the manuscript.

**Authors’ response:** Thanks for your comments. In this study, we did not disaggregate monthly rainfall into daily rainfall, because we directly used the daily rainfall and temperature data of GCMs downloaded from <https://data.cma.cn/> as described in Section 2. In fact, we spatially downscaled GCM simulated rainfall and temperature data in the historical and future periods rather than temporally downscaled the data, i.e. downscaling from the coarse GCM spatial resolution to the catchment resolution. This has been done using the distribution mapping (DM) method. The detailed downscaling methods are described in Section 3.1. In addition, this study indeed only considered the internal variability of rainfall through directly generating realizations of rainfall using the developed stochastic rainfall model SDRM-MCREM, the internal variability of temperature is not taken into consideration. Considering that the internal variability of rainfall is always large and comparable to or even greater than the recognized large uncertainty of GCMs (Hingray and Saïd, 2014; Giorgi, 2002), it should not be neglected in the analysis of different uncertainty sources in rainfall projections. Regarding the internal variability of temperature, several studies pointed out that it is usually very small compared with other uncertainty sources of temperature like GCM uncertainty and RCP uncertainty and therefore can be ignored without large consequences (Lafaysse et al., 2014; Hingray and Saïd, 2014; Fatichi et al., 2016). For that reason, we did not consider the internal variability of temperature in this study as an uncertainty source and this has also been explained in the discussion section (see Page 24, Line 435-439).

References:

*Hingray, B., and Saïd, M.: Partitioning Internal Variability and Model Uncertainty Components in a Multimember*

*Multimodel Ensemble of Climate Projections*, *J. Clim.*, 27, 6779-6798, <https://doi.org/10.1175/jcli-d-13-00629.1>, 2014.

Giorgi, F.: *Dependence of the surface climate interannual variability on spatial scale*, *Geophys. Res. Lett.*, 29, 16-11-16-14, <https://doi.org/10.1029/2002ql016175>, 2002.


Lafaysse, M., Hingray, B., Mezghani, A., Gailhard, J., and Terray, L.: *Internal variability and model uncertainty components in future hydrometeorological projections: The Alpine Durance basin*, *Water Resour. Res.*, 50, 3317-3341, 2014.

Fatichi, S., Ivanov, V. Y., Paschalis, A., Peleg, N., Molnar, P., Rimkus, S., Kim, J., Burlando, P., and Caporali, E.: *Uncertainty partition challenges the predictability of vital details of climate change*, *Earth Future*, 4, 240-251, <https://doi.org/10.1002/2015ef000336>, 2016.

**Comment #2:** Section 4.2.2: Since this paper focuses on extreme flow projections, please add a short paragraph on the performance of the hydrological model in extreme high and low flow simulations in the historical period.

**Authors' response:** Thank you for your useful suggestion. We have added a relevant figure and some information about the performance of the GR4J hydrological model with the selected optimum parameter set in reproducing extreme flows including high flows and low flows in Section 4.2.2. The added contents (see Page 15, Line 311-318) and figure (see Figure 7) can be seen as follows:

“Furthermore, the performances of GR4J model with the selected optimal parameter set in reproducing extreme flows including high flows and low flows are shown in Fig. 7. High flows are represented by annual maximum 1-day, 3-day and 5-day mean flow and low flows are represented by annual minimum 7-day, 30-day and 90-day mean flow. From Fig. 7, it can be seen that the exceedance probability distributions of high flows, particularly for the annual maximum 3-day and 5-day mean flow, are also very well reproduced by GR4J model with the optimum parameter set. The exceedance probability distributions of low flows are all slightly underestimated. Although the GR4J model slightly underestimates low flows, this underestimation can to some extent be eliminated as we use the relative change in results in the subsequent analyses.”




**Figure 7:** Performances of GR4J model in reproducing the exceedance probabilities of high flows: (a) annual maximum 1-day flow, (b) annual maximum 3-day mean flow and (c) annual maximum 5-day mean flow and low flows: (d) annual minimum 7-day mean flow, (e) annual minimum 30-day mean flow and (f) annual minimum 90-day mean flow with the selected optimum parameter set in the historical period.

**Comment #3:** Figure 2: Replace ‘dry spell’ with ‘Dry spell’. ‘Modium’ in the table should be ‘Medium’.

**Authors’ response:** Thank you. These have been modified accordingly, i.e. “dry spell” being replaced with “Dry spell” and “Modium” replaced with “Medium” in Figure 2, which can be seen as follows:






**Figure2:** Framework of SDRM-MCREM.

**Comment #4:** Figure 3 is not clear enough. Please enlarge the figures to improve the readability.

**Authors' response:** Thank you. We have redrawn Figure 3 to make it much clearer to read, which can be seen as follows:




**Figure 3:** Comparison of GCM simulations before and after bias correction with observations in the empirical cumulative distributions and monthly means of (a) daily rainfall, (b) daily maximum temperature, (c) daily minimum temperature and (d) daily mean temperature. The black line represents the observed values. The colorful lines represent raw GCM simulated values. The colorful dotted lines represent bias-corrected GCM simulated values.

**Comment #5:** Figure 4: In each sub-figure, there is a small plot box with three curves.

Please denote the plot box in the figure caption.

**Authors' response:** Thank you very much. We have added a description for these small plot boxes to the caption of Figure 4, which is as follows:



**Figure 4:** Ensemble averages of GCM simulated monthly mean (a) rainfall, (b) daily maximum temperature, (c) daily minimum temperature and (d) daily mean temperature for the historical and two future periods under four RCPs after bias correction. The small graph in each sub-figure shows the ensemble averages of all GCMs and RCPs for the corresponding variable in the historical period and the two future periods, i.e. 2050s and 2080s.

**Comment #6:** Figure 6: Replace ‘DRM-MCREM’ with ‘SDRM-MCREM’.

**Authors' response:** Sorry for the mistake. We have replaced “DRM-MCREM” with “SDRM-MCREM” in the caption of Figure 6.

**Comment #7:** Line 139: ‘he features’ should be ‘the features’.

**Authors' response:** Thank you. We have modified “he features” to “the features”.

# Assessment of extreme flows and uncertainty under climate change: disentangling the contribution of RCPs, GCMs and internal climate variability

Chao Gao<sup>1,2</sup>, Martijn J. Booij<sup>2</sup>, Yue-Ping Xu<sup>1</sup>

5 <sup>1</sup>Institute of Hydrology and Water Resources, Zhejiang University, Hangzhou 310058, China

<sup>2</sup>Water Engineering and Management Group, Faculty of Engineering Technology, University of Twente, Enschede 7500 AE, The Netherlands

*Correspondence:* Yue-Ping Xu (yuepingxu@zju.edu.cn)

**Abstract.** Projections of streamflow, particularly of extreme flows under climate change are essential for future water resources management and development of adaptation strategies to floods and droughts. However, these projections are subject to uncertainties originating from different sources. In this study, we explored the possible changes in future streamflow, particularly for high and low flows, under climate change in the Qu River basin, East China. ANOVA (Analysis of Variance) ~~is~~ ~~was~~ employed to quantify the contribution of different uncertainty sources from RCPs (Representative Concentration Pathways), GCMs (Global Climate Models) and internal climate variability, using an ensemble of four RCP scenarios, nine GCMs and 1,000 simulated realizations of each model-scenario combination by SDRM-MCREM (a stochastic daily rainfall model coupling a Markov chain model with a rainfall event model). The results show that annual mean flow and high flows are projected to increase and low flows will probably decrease in 2041-2070 (2050s) and 2071-2100 (2080s) relative to the historical period 1971-2000, suggesting a higher risk of floods and droughts in the future in the Qu River basin, especially for the late 21st century. Uncertainty in mean flows is mostly attributed to GCM uncertainty. For high flows and low flows, internal climate variability and GCM uncertainty are two major uncertainty sources for the 2050s and 2080s, while for the 2080s, the effect of RCP uncertainty is becoming more pronounced, particularly for low flows. The findings in this study can help water managers to get a better knowledge and understanding of streamflow projections and support decision making on adaptations to changing climate under uncertainty in the Qu River basin.

## 1 Introduction

25 Climate change has been demonstrated to produce profound impacts on hydrological processes all over the world, with its effects lasting throughout the whole 21st century (Bosshard et al., 2013; Addor et al., 2014). Future streamflow projections offer a valuable basis for the assessment of various hydrological extremes including floods and droughts (Giuntoli et al., 2018), which is beneficial for decision makers to plan effective countermeasures for a changing climate (Addor et al., 2014). However, these climate change projections are usually subject to high uncertainty, making it difficult to identify robust adaptation

30 strategies in the decision process (Whateley and Brown, 2016). Therefore, it is of fundamental importance to characterize and quantify uncertainty associated with projections in climate change impact studies (Deser et al., 2010).

35       Uncertainty in climate change projections mainly arises from three different sources, i.e. scenario uncertainty, model uncertainty and internal climate variability (Evin et al., 2019;Deser et al., 2010). Scenario uncertainty is interpreted as responses to different assumptions of future greenhouse gas emissions, which reflects the limited knowledge of external factors such as anthropogenic activities and social development strategies, that influence the climate system (Nakicenovic and Swart, 2000). Model uncertainty originates from different responses ~~of~~ to different model structures under the same future emission scenario that are mainly due to imperfect physical and numerical formulations representing the actual climate system (Stocker et al., 2013). Internal climate variability is the natural unforced variability of the climate system representing dynamical processes intrinsic to the ocean, the atmosphere and the coupled atmosphere-ocean system (Deser et al., 2010). The former 40 two sources of uncertainty are usually estimated using a multi-model ensemble of climate projections derived from different representative concentration pathways (RCPs) and a large number of regional climate models (RCMs) or global climate models (GCMs), respectively. It is considered possible to potentially reduce the uncertainty of these two sources by improving our scientific knowledge in accurately predicting future emissions and interpreting geophysical processes (Lafaysse et al., 2014). However, the internal climate variability can-not be reduced and will persistently exist because of its inherent property (Fatichi et al., 2016), and it is typically evaluated with members or runs representing different initial conditions for the same climate 45 model under the same emission scenario.

      These different uncertainty sources in climate projections have been quantified by multiple studies (Yip et al., 2011;Zhuan et al., 2018;Evin et al., 2019). The relative importance of different uncertainty sources varies depending on factors like the type of climate variable and temporal and spatial scales (Zhuan et al., 2018). For example, many studies have demonstrated 50 that model uncertainty is generally dominant in rainfall projections rather than scenario uncertainty throughout the 21st century, while scenario uncertainty becomes gradually more important in the late 21st century, particularly for temperature projections (Zhuan et al., 2018;Yip et al., 2011). In the near future, internal climate variability contributes largely to the total uncertainty, especially for rainfall projections, and becomes more important with decreasing temporal and spatial scales (Hingray and Saïd, 2014;Giorgi, 2002). A question arising is how these uncertainty sources in climate projections will affect future streamflow 55 projections? In recent years, different sources of uncertainty in streamflow projections have also been investigated (Bosshard et al., 2013;De Niel et al., 2019). Vetter et al. (2016) assessed different uncertainty sources in projections of hydrological changes using four RCPs, five GCMs and nine hydrological models (HMs), and concluded that GCMs generally resulted in the largest uncertainty contribution, followed by RCPs and HMs. De Niel et al. (2019) adopted a large multi-model ensemble consisting of different RCPs, GCMs, downscaling methods, hydrological model structures and hydrological parameter sets to 60 comprehensively evaluate the uncertainty existing in peak flows. The results showed that compared to the dominant uncertainty derived from GCMs and RCPs, HMs and parameter sets are less important for peak flows. Previous studies indicated that uncertainty originating from climate projections is generally larger than uncertainty in the hydrological simulation process (Teng et al., 2012;Karlsson et al., 2016). However, the majority of the studies only considered the uncertainty caused by


scenarios and climate models, but neglected the effect of internal climate variability on streamflow projections, although Jung et al. (2011) and Kay et al. (2008) demonstrated that natural variability is also critical with respect to hydrological changes. The focus of our study is thus quantifying how uncertainty of climate projections, i.e. scenario uncertainty, model uncertainty and internal climate variability, is propagated into streamflow projections, without taking into account uncertainty embedded in the simulation of hydrological processes.

Recently, analysis of variance (ANOVA) has been a widely-used approach to quantify the contributions of different uncertainty sources in climate change impact studies (Qi et al., 2016; Vetter et al., 2014; Bosshard et al., 2013). ANOVA is a model-based method to partition the total variance into different contributing components of variation and thus can quantify the contribution proportion of variance of each component to the total variance. The advantage of ANOVA is that it can not only interpret main single factors, but interactions of factors as well (Vetter et al., 2014). However, there is a problem in quantifying the contribution of internal climate variability using ANOVA since multiple members for each model are required (Evin et al., 2019). This multiple-member constraint results in many single-member models being discarded (Bracegirdle et al., 2014). Thus, only a limited number of climate models can be selected and the climate projection information cannot be fully utilized. To solve this problem, a simple alternative way is to use weather generators or stochastic rainfall models to generate multiple members for each model-scenario combination to interpret theirs\_ internal climate-variability of climate variables, similarly to Lafaysse et al. (2014) and Fatichi et al. (2016). When using these methods, the accuracy of weather generators and stochastic rainfall models is very essential. In this study, we adopt a newly developed stochastic rainfall model by the authors, named SDRM-MCREM (a stochastic daily rainfall model coupling a Markov chain model with a rainfall event model) (Gao et al., 2020a). Compared to previous stochastic rainfall models, SDRM-MCREM can comprehensively preserve rainfall characteristics of both rainfall time-series (e.g. monthly mean rainfall and various rainfall percentiles) and rainfall event characteristics (e.g. different classes of rainfall duration, rainfall depth, and dry spell events and rainfall temporal patterns of different rainfall types). These are all important for streamflow generation. Furthermore, outputs of SDRM-MCREM can well be used as inputs into a hydrological model to reproduce streamflow extremes to effectively conduct flood and drought risk assessment. Similarly, this study also employs ANOVA to quantify the contribution of different uncertainty sources.

The contribution of this study is that we adopt a well-performing stochastic rainfall model to better reflect internal climate variability, and then robustly investigate changes in streamflow projections and uncertainty therein propagated from different sources of climate uncertainty under climate change. We use four RCPs and nine GCMs to account for the uncertainty of scenarios and climate models, respectively. In this study, our main targets are: (1) to look into the overall change of streamflow, particularly for high flows and low flows, in the mid-future period (2041-2070) and the far-future period (2071-2100); (2) to quantify the contributions rate of different uncertainty sources, i.e. RCP uncertainty, GCM uncertainty and internal climate variability, in streamflow projections; and (3) to get insight into how different sources of uncertainty evolve with time in the future. Our study contributes to a better understanding of changes of hydrological extremes and provides useful information for designing adaptation strategies to flood and drought events under a changing climate.

## 2 Study area and data

The Qu River basin (Fig. 1) ~~is~~ was used as the study area, that is situated in the western part of Zhejiang Province, East China. The Qu River basin has an area of 5,536 km<sup>2</sup>, covering longitudes from 118° to 119°E and latitudes from 28° to 29°30'N, and is characterized by the Asian subtropical monsoon climate with a hot rainy summer and cold dry winter (Gao et al., 2020c). The annual mean temperature is around 15~18°C and the average annual rainfall is around 1800 mm with more than 50% occurring in April to July (Gao et al., 2020b). Available data were from 14 gauged rainfall stations, three meteorological stations and one hydrological station with observed rainfall, temperature and streamflow data for the historical period 1970-2000.



**Figure 1:** Study area and distribution of rainfall, meteorological and hydrological stations.

To conduct climate change impact analysis, projections of daily rainfall, daily maximum temperature, daily minimum temperature and daily mean temperature were obtained from nine GCMs (Table 1) for the mid-future period 2041-2070 (i.e. 2050s) and the far-future period 2071-2100 (i.e. 2080s) under four RCP emission scenarios, including RCP8.5, RCP6.0, RCP4.5, and RCP2.6. The historical period is 1971-2000, consistent with the observed data. The nine GCMs ~~had been~~ were selected out of 17 GCMs based on the evaluation results of Gao et al. (2020b), which showed that these GCMs can simultaneously well preserve rainfall time-series statistics and rainfall event characteristics after being bias corrected compared to other GCMs. The information of the nine selected GCMs is listed in Table 1.

**Table 1.** Name, Research Institution and Resolution of the nine selected GCMs

Name of GCMs	Research Institution, Country	Lon ×Lat Resolution
NorESM1-M	Norwegian Climate Center, Norway	~2.5000°×1.8947°
MIROC-ESM-CHEM	Center for Climate System Research, Japan	~2.8125°×2.7906°
MIROC-ESM		~2.8125°×2.7906°
IPSL-CM5A-MR	Institute Pierre-Simon Laplace, France	~2.5000°×1.2676°
IPSL-CM5A-LR		~3.7500°×1.8947°
HadGEM2-ES	Met Office Hadley Centre, UK	~1.8750°×1.2500°
HadGEM2-AO		~1.8750°×1.2500°
GFDL-ESM2G	Geophysical Fluid Dynamics Laboratory, America	~2.5000°×2.0225°
BCC-CSM1-1	Beijing Climate Center, China	~2.8125°×2.7673°

### 3 Methodology

The research was carried out at the catchment scale. Thiessen polygon method (Thiessen, 1911) was used to calculate the areal-averaged daily rainfall and daily maximum, minimum and mean temperatures in the Qu River basin. The areal-averaged daily potential evapotranspiration (PET) was computed using the areal-averaged daily maximum and minimum temperatures and the Hargreaves method (Hargreaves and Zohrab, 1985).

#### 3.1 Bias correction method for rainfall and temperature

Since current GCMs have insufficient spatial resolutions for the catchment scale, GCM outputs often show large deviations compared to observed data and cannot be directly applied for regional impact studies (Teng et al., 2015; Rätty et al., 2014).

Therefore, many bias correction approaches have been developed to correct the bias between GCM outputs and observations (Teutschbein and Seibert, 2012). Considering that the distribution mapping (DM) method usually shows a comprehensive skill in bias correcting the mean, standard deviation and various frequency-based indices and even correcting unobserved extreme values compared with other existing bias correction approaches like power transformation (PT), local intensity scaling (LOCI), linear scaling (LS), delta change (DC) and quantile mapping (QM) (Fang et al., 2015; Teutschbein and Seibert, 2012; Ji et al., 2020). In this study, we used the distribution mapping (DM) method was selected to correct GCM-simulated climate variables based on observations in this study. The underlying idea of DM is to identify the possible bias between GCM simulations and observations by projecting the distribution functions of GCM-simulated climate variables onto those of observations in the historical period (Eq. (1)) and then use the determined bias as a basis to correct future GCM simulations (Eq. (2)) (Miao et al., 2016).



$$135 \quad \tilde{x}_{sim, his} = F_{obs}^{-1} \left( F_{sim, his} \left( x_{sim, his} \right) \right) \quad (1)$$

$$\tilde{x}_{sim, fut} = x_{sim, fut} + F_{obs}^{-1} \left( F_{sim, fut} \left( x_{sim, fut} \right) \right) - F_{sim, his}^{-1} \left( F_{sim, fut} \left( x_{sim, fut} \right) \right) \quad (2)$$

in which,  $x_{sim, his}$  and  $x_{sim, fut}$  are the raw GCM simulations in the historical and future periods;  $F_{sim, his}$  and  $F_{sim, fut}$  are their corresponding cumulative distribution functions (CDFs);  $\tilde{x}_{sim, his}$  and  $\tilde{x}_{sim, fut}$  are the corresponding historical and future bias-corrected GCM simulations;  $F_{sim, his}^{-1}$  and  $F_{obs}^{-1}$  are the inverse CDFs of GCM simulations and observations in the historical  
140 period.

A double-gamma distribution that consists of two single gamma distributions was adopted in this study to fit rainfall (Rätty et al., 2014). Firstly, GCM-simulated and observed rainfall ~~are-were~~ respectively divided into two parts by their 95th percentiles, i.e. one part represents the normal rainfall (smaller than the 95th percentile) and the rest part represents the extreme  
145 rainfall (equal to or larger than the 95th percentile), and each part ~~is-was~~ subsequently fitted and bias corrected using the single gamma distribution shown in Eq. (3). The advantage of the double gamma distribution is that the features of extreme rainfall and normal rainfall can be captured at the same time (Olsson et al., 2015). The detailed bias correction procedure and the solution of the problem of excessive drizzle days existing in GCM-simulated rainfall can be found in Gao et al. (2020b).

For temperature series, the Gaussian distribution shown in Eq. (4) was used (Teutschbein and Seibert, 2012). The  
150 historical and future GCM-simulated temperatures were bias corrected according to Eq. (1) and Eq. (2), respectively. The method shown in Eq. (2) explicitly considers the changes between the historical and future distributions of GCM-simulated temperatures, which remains the same change factors (i.e. the difference between the future and historical monthly mean temperatures) before and after bias correction. For GCM-simulated rainfall and temperature series, the bias correction processes were conducted at the monthly scale.

$$155 \quad f_1(x_1 | \alpha_1, \beta_1) = \frac{\beta_1^{\alpha_1} \cdot e^{-\beta_1 x_1} \cdot x_1^{\alpha_1 - 1}}{\Gamma(\alpha_1)}, f_2(x_2 | \alpha_2, \beta_2) = \frac{\beta_2^{\alpha_2} \cdot e^{-\beta_2 x_2} \cdot x_2^{\alpha_2 - 1}}{\Gamma(\alpha_2)} \quad (3)$$

$$f(x | \mu, \sigma^2) = \frac{1}{\sigma \cdot \sqrt{2\pi}} e^{-\frac{(x-\mu)^2}{2\sigma^2}} \quad (4)$$


in which,  $\alpha_1, \beta_1$  and  $\alpha_2, \beta_2$  are the parameters of two single-gamma distributions, and  $\mu, \sigma$  are the parameters of the Gaussian distribution.

### 3.2 Stochastic daily rainfall model

160 The new stochastic daily rainfall model coupling a Markov chain model with a rainfall event model (SDRM-MCREM) was developed by Gao et al. (2020a). The framework of SDRM-MCREM is shown in Fig.2 and consists of the following steps:

- (1) The time series of rainfall occurrence with values of 1 (wet day) and 0 (dry day) is generated using a third-order Markov chain model. A wet day is defined when daily rainfall is larger than or equal to 0.1 mm, otherwise it is a dry day.
- 165 (2) Based on the occurrence of wet and dry days, rainfall events are extracted and the rainfall duration of each rainfall event is subsequently determined. In this study area, when continuous wet days are separated by one or more continuous dry days, the continuous wet days are considered as a rainfall event.
- (3) Given rainfall durations in Step 2, the rainfall depth (i.e. the total amount) of each rainfall event is simulated using a fitted conditional copula function. Copula functions are used to construct the joint probability distribution of the dependent rainfall depth and duration (Gao et al., 2018). The best-fitted probability distributions of rainfall duration and depth and the best-fitted copula function are selected based on the Akaike information criterion (AIC).
- 170 (4) The event class of each rainfall event is determined according to its depth and duration. Rainfall depths are classified into light, moderate, heavy and extreme events, and rainfall durations are classified into short, medium, long and extreme events, just like the table shown in Fig. 2.
- 175 (5) Following Step 4, one rainfall type is generated for each rainfall event based on the occurrence probability of different rainfall types for the given rainfall event class, and the corresponding dimensionless temporal pattern of this specific rainfall type is stochastically simulated. According to the location of a rainfall peak within one rainfall event, i.e. early, middle or late stage, the dimensionless temporal patterns of ~~observedgauged~~ rainfall events are grouped into three different rainfall types, namely Delayed-type (D), Central-peaked-type (C) and Advanced-type (A).
- 180 (6) For each rainfall event, its depth and duration are temporally allocated according to the dimensionless rainfall pattern to form the complete rainfall event. After allocating all the rainfall events, the complete rainfall time series can be ~~correspondingly~~ obtained.

Detailed information about the adopted probability distributions of rainfall depth and duration, copula functions, classification of rainfall event classes, rainfall types and the simulation procedure of temporal patterns of different rainfall types (step 3-5) in SDRM-MCREM can be found in Gao et al. (2020a). Using the constructed SDRM-MCREM, nine GCM bias-corrected rainfall time series for the historical period of 30 years and the two future periods of 30 years under four RCPs were stochastically simulated 1,000 times.






Figure2: Framework of SDRM-MCREM.

### 3.3 Hydrological model

The parsimonious and effective conceptual rainfall-runoff model with four parameters GR4J (Perrin et al., 2003) was used for hydrological modelling. The GR4J model has shown good performances in different climate regions (e.g. Van Esse et al. (2013) and Tian et al. (2013)), including the Asian subtropical monsoon climate region (Gao et al., 2020c; Tian et al., 2015). Thus, this model can be applied in the Qu River basin. The required input data are the drainage area, areal-averaged daily rainfall and areal-averaged daily PET, and the output is daily streamflow data. In this study, rigorous calibration and validation were carried out for GR4J: (1) a large number of parameter sets, i.e. 30,000, ~~is-was~~ generated using Latin hypercube sampling to

calibrate the model; (2) the split-sample cross validation method (Gao et al., 2020b; Chen et al., 2008) ~~is-was~~ employed to comprehensively select the optimum parameter set. The observed data of 1970 ~~are-were~~ used as the warming-up period, the first 20 years (1971-1990) ~~are-were~~ used for calibration and the last 10 years (1991-2000) for validation. Conversely, the last 20 years 1981-2000 ~~are-were~~ used for calibration and the first 10 years 1971-1980 for validation. The comprehensive evaluation indicator Y that combines NS (Nash-Sutcliffe coefficient) and RVE (Relative volume error) (Akhtar et al., 2009) in Eq. (5) ~ Eq. (7) ~~is-was~~ adopted as the objective function. When the average of Y in the two calibration periods reaches its highest value, the parameter set is considered to be the optimum one.

$$Y = \frac{NS}{1+|RVE|} \quad (5)$$

$$NS = 1 - \frac{\sum_{i=1}^N [Q_m(i) - Q_o(i)]^2}{\sum_{i=1}^N [Q_o(i) - \bar{Q}_o]^2} \quad (6)$$

$$RVE = 100 \cdot \frac{\sum_{i=1}^N [Q_m(i) - Q_o(i)]}{\sum_{i=1}^N Q_o(i)} \quad (7)$$

in which,  $N$  is the length of the time series,  $Q_m(i)$  and  $Q_o(i)$  are the simulated and observed streamflow of the  $i$ th day,  $\bar{Q}_o$  is the mean observed streamflow.

The GR4J model with the optimal parameter set was used to generate 1,000 realizations of 30-year streamflow data for each GCM in the historical period and the two future periods under four RCPs, driven by the corresponding 1,000 realizations of rainfall time series simulated by SDRM-MCREM and the PET data calculated using the Hargreaves method for each GCM. It should be noted that there is only one set of PET data for each GCM as its daily temperature data is not stochastically simulated.

### 3.4 Contribution of different uncertainty sources

In this study, ANOVA was adopted to calculate the contribution of different uncertainty sources, which is an effective tool that can decompose the total variance into variances of different sources and thus quantify the proportion of variance of different sources in the total variance. ANOVA has been widely used in climate change uncertainty analysis in recent years (Vetter et al., 2014; Qi et al., 2016; Vetter et al., 2016). As the 1,000 realizations of each GCM in the historical and future periods ~~were~~ all stochastically simulated from the same GCM under a specific RCP scenario (i.e. model-scenario combination), the stochastic uncertainty (i.e. internal climate variability) ~~is-was considered as~~ a set of independent realizations from an infinite population, known as the within-group variation. Under this condition, there ~~were~~ ~~are~~ two main effect factors (known as the between-group variation), i.e. GCMs and RCPs. Therefore, the two-way ANOVA analysis (Yip et al., 2011) was employed for this study.

225 The total sum of variance ( $SST$ ) can be split into four parts: stochastic error square sum ( $SS_{Stoc}$ ), main effect of RCPs  
 (230  $SS_{RCP}$ ) and GCMs ( $SS_{GCM}$ ), and interaction effect of RCPs and GCMs ( $SS_{RCP \times GCM}$ ) (Northrop and Chandler, 2014), which are  
 described in Eq. (8) ~ Eq. (14). To explicitly compare the relative importance of internal climate variability, GCM  
 uncertainty and RCP uncertainty, the interaction term of RCPs and GCMs ~~is-was~~ firstly divided by equal shares and then added  
 to the respective factors of RCPs and GCMs. The contribution<sub>s</sub> of the three uncertainty sources ~~is-were~~ calculated according  
 to Eq. (14).

$$SST = \sum_{i=1}^{N_{RCP}} \sum_{j=1}^{N_{GCM}} \sum_{k=1}^{N_{Stoc}} (y_{ijk} - \bar{y})^2 \quad (8)$$

$$SST = SS_{Stoc} + SS_{RCP} + SS_{GCM} + SS_{RCP \times GCM} \quad (9)$$

$$SS_{Stoc} = \sum_{i=1}^{N_{RCP}} \sum_{j=1}^{N_{GCM}} \sum_{k=1}^{N_{Stoc}} (y_{ijk} - \bar{y}_{ij\cdot})^2 \quad (10)$$

$$SS_{RCP} = N_{GCM} N_{Stoc} \sum_{i=1}^{N_{RCP}} (\bar{y}_{i\cdot\cdot} - \bar{y})^2 \quad (11)$$

$$240 \quad SS_{GCM} = N_{RCP} N_{Stoc} \sum_{j=1}^{N_{GCM}} (\bar{y}_{\cdot j\cdot} - \bar{y})^2 \quad (12)$$

$$SS_{RCP \times GCM} = N_{Stoc} \sum_{i=1}^{N_{RCP}} \sum_{j=1}^{N_{GCM}} (\bar{y}_{ij\cdot} - \bar{y}_{i\cdot\cdot} - \bar{y}_{\cdot j\cdot} + \bar{y})^2 \quad (13)$$

$$\eta_{Stoc}^2 = \frac{SS_{Stoc}}{SST}, \quad \eta_{RCP}^2 = \frac{SS_{RCP}}{SST} + \frac{1}{2} \frac{SS_{RCP \times GCM}}{SST}, \quad \eta_{GCM}^2 = \frac{SS_{GCM}}{SST} + \frac{1}{2} \frac{SS_{RCP \times GCM}}{SST} \quad (14)$$


in which,  $N_{RCP}$ ,  $N_{GCM}$  and  $N_{Stoc}$  are the number of RCPs, GCMs and stochastic simulations, respectively;  $y_{ijk}$  is the particular  
 value corresponding to the  $k$ th simulation of the  $j$ th GCM under the  $i$ th RCP scenario;  $\bar{y}$  is the overall mean;  $\bar{y}_{i\cdot\cdot}$ ,  $\bar{y}_{\cdot j\cdot}$  and  
 240  $\bar{y}_{ij\cdot}$  are the mean of all values under the particular index, respectively;  $\eta_{Stoc}^2$ ,  $\eta_{GCM}^2$  and  $\eta_{RCP}^2$  are the contribution of internal  
 climate variability, GCM uncertainty and RCP uncertainty, respectively.


## 4 Results

### 4.1 Bias correction of rainfall and temperature

245 The empirical cumulative distribution functions (ECDF) and monthly means of simulated climate variables from nine GCMs  
 before and after bias correction using the DM method ~~are-were~~ compared to those of observations in the historical period 1971-  
 2000 (shown in Fig.3). It can be clearly seen that before bias correction, the ability of GCMs to reproduce rainfall and  
 temperature values is relatively poor. In this study area, the majority of the GCMs tends to underestimate rainfall as well as  
 temperature. All rainfall and temperature bias-corrections significantly improve the raw GCM simulations, and currently the

bias-corrected GCM simulations are very close to the observations, which is indicated by the better matching ECDFs and  
 250 monthly means between observations and bias-corrected GCM simulations. In addition, the monthly-scale bias correction  
 method can effectively remove the mismatch of annual temporal pattern of climate variables between observations and GCM  
 simulations, particularly for rainfall. The detailed evaluation results of the bias-corrected rainfall of the nine GCMs can be  
 found in Gao et al. (2020b). The results further demonstrated that the GCM simulated rainfall after bias correction can well  
 255 preserve rainfall time-series characteristics like standard deviation, coefficient of variation and various rainfall  
 quantiles/percentiles, and simultaneously well reproduce rainfall event characteristics including different rainfall event classes  
 and rainfall temporal patterns. Since the bias-corrected temperature data usually performed better than rainfall (Teutschbein  
 and Seibert, 2012), the detailed evaluation results of bias-corrected temperature are not given here. Subsequently, the future  
 GCM simulated rainfall and temperature data under four RCPs for two future periods 2050s and 2080s were bias corrected  
 according to Eq. (2).






**Figure 3:** Comparison of GCM simulations before and after bias correction with observations in the empirical cumulative distributions and monthly means of (a) daily rainfall, (b) daily maximum temperature, (c) daily minimum temperature and (d) daily mean temperature. The black line represents the observed values. The colorful lines represent raw GCM simulated values. The colorful dotted lines represent bias-corrected GCM simulated values.

带格式的: 居中, 缩进: 首行缩进: 0 厘米, 左 0 字符, 右 0 字符



The ensemble averages of the nine GCM bias-corrected monthly mean rainfall and daily maximum, minimum and mean temperatures for the historical period and the two future periods are compared in Fig. 4. The results show that daily maximum, minimum and mean temperatures all present a consistent and stable increasing trend in the future periods being the largest for RCP8.5 followed by RCP6.0, RCP4.5 and RCP2.6, and always with larger increases for the 2080s compared to the 2050s. On average, daily maximum, mean and minimum temperatures for each month rise by 2.44 °C, 2.31 °C and 2.19 °C in the 2050s and by 3.46 °C, 3.29 °C and 3.12 °C in the 2080s, respectively. For rainfall, the change is not as distinct and regular as for temperature and different RCP scenarios show different changes in different seasons. Rainfall in the monsoon season (April-June) and September generally increases in the 2050s and 2080s with larger increases in the 2080s, and no obvious changes occur in other months. In summary, the annual rainfall in the 2050s and 2080s is expected to rise by 3.18% and 5.20%, respectively.




**Figure 4:** Ensemble averages of GCM simulated monthly mean (a) rainfall, (b) daily maximum temperature, (c) daily minimum temperature and (d) daily mean temperature for the historical and two future periods under four RCPs after bias correction. The small graph in each sub-figure shows the ensemble averages of all GCMs and RCPs for the corresponding variable in the historical period and the two future periods, i.e. 2050s and 2080s.

## 4.2 Performances of stochastic rainfall model and hydrological model


### 4.2.1 Evaluation of SDRM-MCREM

The stochastic rainfall model SDRM-MCREM was evaluated ~~for~~ ~~from~~ two aspects: rainfall time-series characteristics and rainfall event characteristics, through comparison of observations and the range of 1,000 simulations based on the observed rainfall in the historical period 1971-2000. The performance of SDRM-MCREM ~~is~~ ~~was~~ categorized into three classes, i.e. good, fair and poor, when the observations ~~are~~ ~~were~~ located in the 10th-90th percentile range, the minimum-maximum range and outside of the range of 1,000 simulations, respectively. The performance of SDRM-MCREM ~~for~~ ~~in~~ the rainfall time-series characteristics, i.e. monthly mean rainfall and cumulative probability distributions including various rainfall percentiles, is shown in Fig. 5. The results show that SDRM-MCREM performs very well for most of these rainfall characteristics, but the larger rainfall percentiles (90th-95th) are slightly underestimated. The exceedance probability distributions of rainfall extremes, including annual maximum 1-, 3- and 5-day rainfall are also assessed and presented in Fig. 6. Except that the annual maximum 1-day rainfall is slightly overestimated by SDRM-MCREM with a fair performance, the annual maximum 3- and 5-day rainfall are all reproduced very well, as observations and simulated medians are very close. For rainfall event characteristics, detailed evaluation of SDRM-MCREM can be found in Gao et al. (2020a), including the distribution of wet and dry spells, the occurrence frequency of different classes of rainfall duration, depth and dry spell events, the temporal patterns of different rainfall types and even the occurrence frequency of different rainfall types in different classes of rainfall events. The results demonstrated that SDRM-MCREM presents a good performance for these rainfall event characteristics as well.

In general, SDRM-MCREM can well reproduce most of the rainfall time-series characteristics and rainfall event characteristics, and also rainfall extremes, particularly for long-duration rainfall extremes, which are all important for subsequent streamflow analysis. In addition, the embedded uncertainty of SDRM-MCREM shown in Fig. 5 and Fig. 6 can be used to reflect the internal variability of rainfall.



**Figure 5:** Comparison of SDRM-MCREM simulations with observations in (a) monthly mean rainfall and (b) cumulative probability distribution of daily rainfall.




**Figure 6:** Comparison of SDRM-MCREM simulations with observations in extreme rainfall, i.e. annual maximum (a) 1-day, (b) 3-day and (c) 5-day rainfall.

#### 310 4.2.2 Calibration and validation of GR4J model

Based on the method described in Section 3.3, the optimal parameter set of GR4J was selected. The split-sample calibration and validation results with the chosen parameter set are displayed in Table 2. The results in the two rounds show that the GR4J model with the optimum parameter set performs very well, because the values of NS and Y in the calibration and validation periods are mostly above 0.90 and the absolute value of RVE is smaller than 3.2%. The RVE, NS and Y values for the historical period 1971-2000 are -1.72%, 0.93 and 0.92, respectively. Furthermore, the performances of GR4J model with the selected optimal parameter set in reproducing extreme flows including high flows and low flows are shown in Fig. 7. High flows are represented by annual maximum 1-day, 3-day and 5-day mean flow and low flows are represented by annual minimum 7-day, 30-day and 90-day mean flow. From Fig. 7, it can be seen that the exceedance probability distributions of high flows, particularly for the annual maximum 3-day and 5-day mean flow, are also very well reproduced by GR4J model with the optimum parameter set-performs. The exceedance probability distributions of low flows are all slightly underestimated. Although the GR4J model slightly underestimates peak-low flows-in-most-cases, this underestimation can to some extent be eliminated as we use the relative change in results in the subsequent analyses.

**Table 2.** Calibration and validation results of GR4J model

Periods	Y	NS	RVE
The first round			
Calibration (1971-1990)	0.90	0.91	-0.54%
Validation (1991-2000)	0.92	0.93	1.02%
The second round			
Calibration (1981-2000)	0.93	0.94	-1.06%
Validation (1971-1980)	0.89	0.91	-3.15%



**Figure 7:** Performances of GR4J model in reproducing the exceedance probabilities of high flows: (a) annual maximum 1-day flow, (b) annual maximum 3-day mean flow and (c) annual maximum 5-day mean flow and low flows: (d) annual minimum 7-day mean flow, (e) annual minimum 30-day mean flow and (f) annual minimum 90-day mean flow with the selected optimum parameter set in the historical period.

- 设置了格式: 字体: 加粗
- 设置了格式: 字体: 非加粗
- 设置了格式: 字体: 非加粗
- 设置了格式: 字体: 非加粗
- 设置了格式: 字体: 非加粗
- 设置了格式: 字体: 非加粗
- 设置了格式: 字体: (中文)+中文正文(宋体), 加粗, (中文)中文(中国)

325

330

### 4.3 Overall change in mean and extreme flows under climate change


With the 1,000 realizations of rainfall stochastically simulated using SDRM-MCREM for each bias-corrected GCM rainfall series and one set of PET calculated using bias-corrected temperature data for each GCM to drive the GR4J hydrological model with the selected optimal parameter set, the corresponding 1,000 sets of simulated streamflow for each GCM in the historical period 1971-2000 and the two future periods 2050s and 2080s under four RCP scenarios *ean-be were* obtained. The influences of climate change on mean flows and extreme flows, including high and low flows, *are were* investigated by means of relative changes (Fig. 78-Fig. 89) in this study. The mean flows *are were* represented by the indices of multi-year monthly and annual average flow. Annual maximum 1-, 3- and 5-day mean flow *are were* adopted to reflect high flows, while low flows *are were* represented by annual minimum 7-, 30- and 90-day mean flow (Gao et al., 2020a). The above annual maximum (or minimum) multi-day mean flow *is was* represented by the highest (or lowest) multi-day average value occurring for any given year (Richter et al., 1996; Kiesel et al., 2019). These adopted indices are all known as hydrological indicators, which have been widely used in hydrological analysis (Olden and Poff, 2003).

335


340

To investigate the overall change of mean, high and low flows under climate change, the medians of these indices in the mid-future 2050s and far-future 2080s *are were* compared to that in the historical period 1971-2000. As for high and low flows,

the exceedance probabilities of their indices ~~are-were~~ analysed. The medians in the historical period ~~are-were~~ extracted from 9,000 sets of simulated streamflow (9 GCMs \* 1,000 stochastic simulations), and the medians in the 2050s and 2080s ~~are-were~~ separately extracted from 36,000 sets of simulated streamflow (4 RCPs \* 9 GCMs \* 1,000 stochastic simulations). In general, the annual mean flow (Fig. 78) and high flows (Fig. 89) are projected to increase, while the low flows are projected to decline in the future (Fig. 89). Moreover, the changes in the far-future 2080s are greater than in the mid-future 2050s. For the monthly mean flow, there is an increase in peak-flow seasons (April to June), especially in June, which is probably the main reason for the increase of annual flow. However, the changes in other months are not so consistent, with decreases in July and August but increases in September and December and no significant changes are found in the other months. The annual mean flow is slightly increased by 0.81% in the 2050s and by 3.12% in the 2080s, respectively. For high flows, the changes of annual maximum 1-, 3- and 5-day mean flow in the 2080s increases with the increase of return periods while the changes in the 2050s become stable when the exceedance probability is smaller than 70%. Furthermore, with the longer duration of high flows, the magnitude of increase decreases. However, for the low flows an opposite result is found. The changes of annual minimum 7-, 30- and 90-day mean flow decline with increasing return periods, but rise with the longer duration of low flows, except for the annual minimum 90-day mean flow with a return period smaller than 2 years (i.e. exceedance probability larger than 50%). This phenomenon can be explained by that there is a larger probability for longer duration of low flows to contain large flow, particularly for the annual minimum 90-day mean flow with small return periods. The larger flow contained in the annual minimum 90-day mean flow may present an increase in the future that would probably lead to the decline in the magnitude of decrease. The detailed changes of high and low flows at specific return periods, i.e. 5, 10 and 20 years in the future are shown in Table 3. High flows with a return period of 20 years increase with around 11% in the 2050s and approximately 25% in the 2080s, while low flows with the same return period decrease with 9-11% and 10-12% in the 2050s and 2080s, respectively.



365 **Figure 78:** Change of mean flows in the 2050s and 2080s relative to the historical period 1971-2000.



**Figure 89.** Change of (a) high flows and (b) low flows in the 2050s and 2080s relative to the historical period 1971-2000. The symbols Max\_1, Max\_3 and Max\_5 represent the annual maximum 1-, 3- and 5-day mean flow, while Min\_7, Min\_30 and Min\_90 represent the annual minimum 7-, 30- and 90-day mean flow, respectively.

**Table 3.** Future change of high flows and low flows at specific return periods

Hydrological indicators	5-year return period		10-year return period		20-year return period	
	2050s	2080s	2050s	2080s	2050s	2080s
<b>High flows</b>						
Annual maximum 1-day flow	11.7%	22.3%	12.2%	24.4%	11.6%	25.1%
Annual maximum 3-day mean flow	10.8%	21.1%	11.0%	23.3%	10.9%	25.1%
Annual maximum 5-day mean flow	10.4%	20.3%	10.7%	22.9%	10.4%	24.5%
<b>Low flows</b>						
Annual minimum 7-day mean flow	-11.5%	-13.1%	-10.1%	-11.9%	-9.0%	-10.3%
Annual minimum 30-day mean flow	-12.3%	-14.1%	-10.8%	-12.7%	-9.5%	-11.0%
Annual minimum 90-day mean flow	-13.0%	-15.0%	-11.7%	-13.6%	-10.6%	-12.1%

#### 4.4 Contribution of different uncertainty sources for mean and extreme flows

Since the uncertainty of streamflow in the historical period can be largely attributed to internal climate variability, only the contribution of different uncertainty sources, i.e. from RCPs, GCMs and internal climate variability, in the future periods is shown (Fig. 910-Fig. 1314) in this study. For mean flows, the uncertainty stemming from GCMs dominates for all months except October in the 2050s, followed by internal climate variability and RCP uncertainty (Fig. 910). Specifically, GCMs contributes more than 70% to the total uncertainty in annual mean flow. Compared to the 2050s, the effect of RCP and GCM uncertainty in the 2080s in general becomes larger throughout the year, although the contribution of GCM uncertainty in the

380 annual mean flow shows a slight decrease. The fraction of internal climate variability consistently decreases in the 2080s compared to the 2050s.





Figure 910: Contribution of three uncertainty sources, i.e. from RCPs, GCMs and internal climate variability for mean flows in the 2050s and 2080s, respectively.


385 For high flows, internal climate variability and GCM uncertainty are clearly the major sources for the two future periods, with internal climate variability becoming dominant when return periods are larger than four years or smaller than 1.1 years (Fig. 4011). The contribution of RCP uncertainty in the 2050s increases with increasing return periods, while it is constant for all return periods in the 2080s. Similar results are found for annual maximum 1-, 3- and 5-day mean flow. Fig. 44-12 presents the contribution of the three uncertainty sources for high flows at return periods of 5, 10 and 20 years. Firstly, compared to the 2050s, internal climate variability and GCM uncertainty become even more pronounced and RCP uncertainty is less relevant in the 2080s. Secondly, with increasing return periods, internal climate variability contributes a larger fraction while GCM uncertainty contributes a smaller fraction. Lastly, the effect of RCP and GCM uncertainty becomes gradually obvious with the longer duration of high flows while internal climate variability shows the opposite behavior.

390




395 **Figure 4911:** Contribution of the three uncertainty sources for high flows in the 2050s and 2080s, respectively. Symbols Max\_1, Max\_3 and Max\_5 represent the annual maximum 1-, 3- and 5-day mean flow, respectively.






**Figure 13-12.** Contribution of the three uncertainty sources for high flows at 5-, 10- and 20-year return periods in the 2050s and 2080s, respectively. Symbols Max\_1, Max\_3 and Max\_5 represent the annual maximum 1-, 3- and 5-day mean flow, respectively. The figures on the bars represent the contribution values of different uncertainty sources.

However, different from the findings for high flows, the role of RCP uncertainty is more evident for low flows (Fig. 13-13). Especially in the far future, the uncertainty contributed by RCPs increases greatly, while the uncertainty due to internal climate variability reduces significantly. With longer projection horizons, GCM uncertainty also contributes a larger fraction to the total uncertainty and becomes the dominant factor in the 2080s. In addition, with the longer duration of low flows, the effect of internal climate variability becomes larger. This is possibly because there is a larger probability for longer duration of low flows to contain large flow and these large flows are greatly influenced by internal climate variability. Fig. 13-14 gives the detailed contribution of the three uncertainty sources for low flows at 5-, 10- and 20-year return periods.



410 **Figure 12.13:** Contribution of the three uncertainty sources for low flows in the 2050s and 2080s, respectively. Symbols Min\_7, Min\_30 and Min\_90 represent the annual minimum 7-, 30- and 90-day mean flow, respectively.



**Figure 13:14:** Contribution of the three uncertainty sources for low flows at 5-, 10- and 20-year return periods in the 2050s and 2080s, respectively. Symbols Min\_7, Min\_30 and Min\_90 represent the annual minimum 7-, 30- and 90-day mean flow, respectively. The figures on the bars represent the contribution values of different uncertainty sources.

Generally, the contribution of different uncertainty sources varies with streamflow characteristics, i.e. high, mean and low flows. The link between the relative importance of different uncertainty sources for flows and those for climate variables (i.e. rainfall and temperature) will be discussed in detail in Section 5.

## 420 5 Discussion

Projected streamflow changes shown in Fig. 78-8-9 indicate that the Qu River basin will probably have more water resources on an annual basis, but hydrological extreme events like high flows and low flows will become more serious in the mid-future period and particularly the far-future period. Both wet-seasonal and annual flows are expected to experience an increase in the future, keeping consistent with the increase of rainfall, but the change in streamflow is smaller than that in rainfall (by comparing Fig. 4 and Fig. 78). This is mainly due to the rise of temperatures (Fig. 4) that leads to more water loss in the form of evapotranspiration. In addition, there is a clear tendency toward a higher flood and drought risk in this study area (Fig. 89). This finding is in agreement with previous studies in the same river basin (Gao et al., 2020c), and also further confirms the

findings regarding changes of extreme rainfall event characteristics by Gao et al. (2020b) that are highly associated with the occurrence of floods and droughts. Gao et al. (2020b) concluded that the frequency of extreme dry spell events and extreme rainfall events will probably be projected to increase, implying that the Qu River basin will have a larger possibility to experience droughts and floods in the future. Furthermore, the rainfall temporal patterns are becoming more-centralized, particularly for the peak-delayed rainfall types and extreme rainfall events, which will result in larger peak flows and probably induce floods in this study area, especially in the late 21st century (Gao et al., 2020b). The above findings can provide important implications for water management in the Qu River basin. For example, this can guide water managers to store more excessive water in wet seasons and release water in dry seasons by appropriate regulation of reservoirs to alleviate flood and drought risks.

Uncertainty in projected streamflow is the result of uncertainty in projected climate variables, i.e. rainfall and temperature, and the relative importance of different uncertainty sources may vary with the variable of interest and given projection time. Fig. S1-S4 present the contribution of different uncertainty sources for rainfall and temperature. In this study, we did not take the internal variability of temperature into account, but this would not make a big difference. This is because most studies pointed out that the fraction of variance attributed to internal variability of the temperature is negligible when compared to scenario uncertainty and model uncertainty, especially in the second half of 21st century (Lafayesse et al., 2014; Hingray and Saïd, 2014; Fatichi et al., 2016). For rainfall (Fig. S1-S2), it can be clearly seen that the internal variability is the largest uncertainty source that can account for approximately 54-60% ~~on-average of the total uncertainty on average~~, followed by GCM uncertainty taking up about 32-35% and RCP uncertainty 8-11%, both in the 2050s and 2080s. However, in terms of temperatures (Fig. S3-S4), GCM uncertainty evidently prevails in the 2050s, contributing to more than 70% of the total uncertainty in daily maximum and mean temperatures, while RCP uncertainty begins to play a more significant role than GCM uncertainty in the 2080s. The effect of RCP uncertainty for daily minimum temperature is in general larger than that for daily maximum and mean temperatures. The above findings that both GCM uncertainty and internal climate variability contribute substantially to the overall uncertainty in rainfall changes and RCP uncertainty is the primary source for air temperature, particularly for far future projections, are consistent with previous climate impact studies (Hawkins and Sutton, 2009; Schewe et al., 2014; Yip et al., 2011). Due to the combined effects of rainfall and temperature on the streamflow formation, the impacts of RCP and GCM uncertainty on streamflow are larger than those for rainfall. This phenomenon becomes more pronounced for the mean flow and low flows. For example, the uncertainty due to internal climate variability and GCM uncertainty for high flows have become comparable, i.e. both accounting for about 44-48%, and RCP uncertainty accounts for about 10% of the total uncertainty in the future. Particularly for low flows, the contribution of GCM uncertainty and RCP uncertainty in the 2050s and 2080s has increased from 40% and 13% to 48% and 24%, respectively, and internal climate variability has decreased from 47% to 28% on average. Generally, it can be summarized that the uncertainty in high flows is still mainly influenced by that of rainfall while the uncertainty in low flows ~~is primarily affected by temperatures are almost equally affected by both rainfall and temperature~~, especially in the late 21st century. The relative importance of the three uncertainty sources for high flows found in this study is in agreement with the conclusions by Kay et al. (2008) and Jung et al. (2011). Nevertheless, since

the number of similar studies focusing on different kinds of flows is limited at present, the different results found for mean, high and low flows in this study need further comparison and verification.

Although this study mainly concentrated on investigating how the uncertainty of climate projections is propagated in to streamflow projections, there are other sources of uncertainty, like uncertainties originating from downscaling methods, hydrological model structures and hydrological parameters, etc. Chen et al. (2011) and Meaurio et al. (2017) found that downscaling methods might also have a large contribution to the uncertainty in peak-flow projections, as different types of downscaling methods might lead to significantly different extreme high flows, and uncertainty in simulated extreme low flows is also critically impacted by hydrological model structures as well as calibration strategies (De Niel et al., 2019; Vansteenkiste et al., 2014; Velázquez et al., 2013). Therefore, to obtain a comprehensive insight into projected changes of high flows and low flows and the uncertainty therein, all sources of uncertainty arising from scenarios, climate models, internal climate variability, downscaling methods, hydrological models and hydrological parameters can be considered in future studies.

## 6 Conclusions

In this study, we investigated the streamflow changes of the Qu River basin in the mid-future period 2050s and the far-future period 2080s relative to the historical period 1971-2000. The contribution of three different sources of uncertainty, i.e. RCP uncertainty, GCM uncertainty and internal climate variability was also quantified by using four scenarios, nine GCMs and 1,000 simulations of SDRM-MCREM (a stochastic daily rainfall model coupling a Markov chain model with a rainfall event model). The conclusions can be summarized as follows:

- (1) Annual mean flow and wet seasonal flow (April-June) are projected to increase in the two future periods, and hydrological extreme events are becoming more extreme, which are indicated by ~~that~~ high flows becoming inge higher and low flows becoming inge lower, especially for the 2080s. This indicates that the Qu River basin will be probably faced with a higher risk of floods and droughts in the future.
- (2) For mean flows, GCM uncertainty is generally the largest contributor to the total uncertainty, followed by internal climate variability and RCP uncertainty. The effect of GCM and RCP uncertainty on mean flows in the 2080s is generally greater than that in the 2050s.
- (3) For high flows, internal climate variability and GCM uncertainty play a comparable role in the total uncertainty and are the two major uncertainty sources. The uncertainty of high flows is mainly affected by that of rainfall extremes. The relative importance of different uncertainty sources for rainfall extremes from large to small are internal climate variability, GCM uncertainty and RCP uncertainty. For temperature, GCM uncertainty is dominant in the 2050s but RCP uncertainty gradually becomes dominant in the 2080s.
- (4) The role of RCP and GCM uncertainty is more pronounced for future low flow projections. Especially in the 2080s, GCM uncertainty has become the dominant uncertainty source, and RCPs have almost the same contribution to the total uncertainty as internal climate variability. The uncertainty of low flows is primarily-both influenced by the uncertainty in

~~rainfall and~~ temperature ~~so that~~and the effect of internal climate variability is much smaller than for high flows.

#### 495 **Supplements**

The supplement can be downloaded from the following LINK.

#### **Code and data availability**

A detailed simulation procedure of the rainfall event model using in the stochastic daily rainfall model SDRM-MCREM can be found from <https://doi.org/10.1016/j.jhydrol.2018.06.073>. The observed streamflow data and rainfall data from Zhejiang Bureau of Hydrology are available upon request from the corresponding author (yuepingxu@zju.edu.cn). The observed temperature data can be downloaded from <https://data.cma.cn/>. The GCM simulated rainfall and temperature data can be obtained from <https://esgf-node.llnl.gov/search/cmip5/>.

#### **Author contributions**

CG, MB, and Y-P Xu designed this study together. CG conducted the modelling, the analysis and preparation of the manuscript with support from all co-authors. All co-authors largely contributed to the discussion of the results and revising the paper.

#### **Competing interests**

The authors declare that they have no conflict of interest.

#### **Acknowledgements**

This study is financially supported by the National Key Research and Development Plan “Inter-governmental Cooperation in International Scientific and Technological Innovation” (2016YFE0122100) and [the Key Project of Zhejiang Natural Science Foundation](#) ~~the National Natural Science Foundation of China (91547106LZ20E090001)~~. We sincerely acknowledge Zhejiang Bureau of Hydrology and the National Climate Centre of China Meteorological Administration for providing us meteorological and hydrological data used in this study.

#### **References**

515 Addor, N., Rössler, O., Köplin, N., Huss, M., Weingartner, R., and Seibert, J.: Robust changes and sources of uncertainty in

设置了格式: 字体:(默认) Times New Roman, 10 磅, 字体颜色: 自动设置

设置了格式: 字体:(默认) Times New Roman, 10 磅, 字体颜色: 自动设置

带格式的: 缩进: 左侧: 0 厘米, 悬挂缩进: 1.5 字符, 首行缩进: -1.5 字符

- the projected hydrological regimes of Swiss catchments, *Water Resour. Res.*, 50, 7541-7562, 2014.
- Akhtar, M., Ahmad, N., and Booi, M. J.: Use of regional climate model simulations as input for hydrological models for the Hindukush-Karakorum-Himalaya region, *Hydrol. Earth Syst. Sci.*, 13, 1075-1089, 2009.
- 520 Bosshard, T., Carambia, M., Goergen, K., Kotlarski, S., Krahe, P., Zappa, M., and Schär, C.: Quantifying uncertainty sources in an ensemble of hydrological climate-impact projections, *Water Resour. Res.*, 49, 1523-1536, <https://doi.org/10.1029/2011wr011533>, 2013.
- Bracegirdle, T. J., Turner, J., Hosking, J. S., and Phillips, T.: Sources of uncertainty in projections of twenty-first century westerly wind changes over the Amundsen Sea, West Antarctica, in CMIP5 climate models, *Clim. Dyn.*, 43, 2093-2104, <https://doi.org/10.1007/s00382-013-2032-1>, 2014.
- 525 Chen, J., Brissette, F. P., Poulin, A., and Leconte, R.: Overall uncertainty study of the hydrological impacts of climate change for a Canadian watershed, *Water Resour. Res.*, 47, <https://doi.org/10.1029/2011wr010602>, 2011.
- Chen, M., Shi, W., Xie, P., Silva, V. B., Kousky, V. E., Wayne Higgins, R., and Janowiak, J. E.: Assessing objective techniques for gauge - based analyses of global daily precipitation, *J. Geophys. Res.-Atmos.*, 113, 2008.
- De Niel, J., Van Uytven, E., and Willem, P.: Uncertainty Analysis of Climate Change Impact on River Flow Extremes Based on a Large Multi-Model Ensemble, *Water Resour. Manag.*, 33, 4319-4333, <https://doi.org/10.1007/s11269-019-02370-0>, 2019.
- 530 Deser, C., Phillips, A., Bourdette, V., and Teng, H.: Uncertainty in climate change projections: the role of internal variability, *Clim. Dyn.*, 38, 527-546, <https://doi.org/10.1007/s00382-010-0977-x>, 2010.
- Evin, G., Hingray, B., Blanchet, J., Eckert, N., Morin, S., and Verfaillie, D.: Partitioning Uncertainty Components of an Incomplete Ensemble of Climate Projections Using Data Augmentation, *J. Clim.*, 32, 2423-2440, <https://doi.org/10.1175/jcli-d-18-0606.1>, 2019.
- 535 Fang, G. H., Yang, J., Chen, Y. N., and Zammit, C.: Comparing bias correction methods in downscaling meteorological variables for a hydrologic impact study in an arid area in China, *Hydrol. Earth Syst. Sci.*, 19, 2547-2559, <https://doi.org/10.5194/hess-19-2547-2015>, 2015.
- 540 Fatichi, S., Ivanov, V. Y., Paschalis, A., Peleg, N., Molnar, P., Rimkus, S., Kim, J., Burlando, P., and Caporali, E.: Uncertainty partition challenges the predictability of vital details of climate change, *Earth Future*, 4, 240-251, <https://doi.org/10.1002/2015ef000336>, 2016.
- Gao, C., Xu, Y.-P., Zhu, Q., Bai, Z., and Liu, L.: Stochastic generation of daily rainfall events: A single-site rainfall model with Copula-based joint simulation of rainfall characteristics and classification and simulation of rainfall patterns, *J. Hydrol.*, 564, 41-58, 2018.
- 545 Gao, C., Booi, M. J., and Xu, Y.-P.: Development and hydrometeorological evaluation of a new stochastic daily rainfall model: coupling Markov chain with rainfall event model, *J. Hydrol.*, under revision, 2020a.
- Gao, C., Booi, M. J., and Xu, Y. P.: Impacts of climate change on characteristics of daily - scale rainfall events based on nine selected GCMs under four CMIP5 RCP scenarios in Qu River basin, east China, *Int. J. Climatol.*, 40, 887-907, <https://doi.org/10.1002/joc.6246>, 2020b.
- 550 Gao, C., He, Z., Pan, S., Xuan, W., and Xu, Y.-P.: Effects of climate change on peak runoff and flood levels in Qu River Basin, East China, *J. Hydro-environ. Res.*, 28, 34-47, 2020c.
- Giorgi, F.: Dependence of the surface climate interannual variability on spatial scale, *Geophys. Res. Lett.*, 29, 16-11-16-14, <https://doi.org/10.1029/2002gl016175>, 2002.
- 555 Giuntoli, I., Villarini, G., Prudhomme, C., and Hannah, D. M.: Uncertainties in projected runoff over the conterminous United States, *Clim. Change*, 150, 149-162, <https://doi.org/10.1007/s10584-018-2280-5>, 2018.
- Hargreaves, G. H., and Zohrab, S. A.: Reference Crop Evapotranspiration from Temperature, *Appl. Eng. Agric.*, 1, 96-99, <https://doi.org/10.13031/2013.26773>, 1985.
- 560 Hawkins, E., and Sutton, R.: The Potential to Narrow Uncertainty in Regional Climate Predictions, *Bull. Amer. Meteorol. Soc.*, 90, 1095-1108, <https://doi.org/10.1175/2009bams2607.1>, 2009.
- Hingray, B., and Saïd, M.: Partitioning Internal Variability and Model Uncertainty Components in a Multimember Multimodel Ensemble of Climate Projections, *J. Clim.*, 27, 6779-6798, <https://doi.org/10.1175/jcli-d-13-00629.1>, 2014.
- 565 Ji, X., Li, Y., Luo, X., He, D., Guo, R., Wang, J., Bai, Y., Yue, C., and Liu, C.: Evaluation of bias correction methods for APHRODITE data to improve hydrologic simulation in a large Himalayan basin, *Atmospheric Research*, 242, <https://doi.org/10.1016/j.atmosres.2020.104964>, 2020.

- Jung, I. W., Chang, H., and Moradkhani, H.: Quantifying uncertainty in urban flooding analysis considering hydro-climatic projection and urban development effects, *Hydrol. Earth Syst. Sci.*, 15, 617-633, <https://doi.org/10.5194/hess-15-617-2011>, 2011.
- Karlsson, I. B., Sonnenborg, T. O., Refsgaard, J. C., Trolle, D., Børgesen, C. D., Olesen, J. E., Jeppesen, E., and Jensen, K. H.: Combined effects of climate models, hydrological model structures and land use scenarios on hydrological impacts of climate change, *J. Hydrol.*, 535, 301-317, <https://doi.org/10.1016/j.jhydrol.2016.01.069>, 2016.
- Kay, A. L., Davies, H. N., Bell, V. A., and Jones, R. G.: Comparison of uncertainty sources for climate change impacts: flood frequency in England, *Clim. Change*, 92, 41-63, <https://doi.org/10.1007/s10584-008-9471-4>, 2008.
- Kiesel, J., Gericke, A., Rathjens, H., Wetzig, A., Kakouei, K., Jähnig, S. C., and Fohrer, N.: Climate change impacts on ecologically relevant hydrological indicators in three catchments in three European ecoregions, *Ecol. Eng.*, 127, 404-416, <https://doi.org/10.1016/j.ecoleng.2018.12.019>, 2019.
- Lafaysse, M., Hingray, B., Mezghani, A., Gailhard, J., and Terray, L.: Internal variability and model uncertainty components in future hydrometeorological projections: The Alpine Durance basin, *Water Resour. Res.*, 50, 3317-3341, 2014.
- Meaurio, M., Zabaleta, A., Boithias, L., Epelde, A. M., Sauvage, S., Sánchez-Pérez, J.-M., Srinivasan, R., and Antiguiedad, I.: Assessing the hydrological response from an ensemble of CMIP5 climate projections in the transition zone of the Atlantic region (Bay of Biscay), *J. Hydrol.*, 548, 46-62, <https://doi.org/10.1016/j.jhydrol.2017.02.029>, 2017.
- Miao, C., Su, L., Sun, Q., and Duan, Q.: A nonstationary bias-correction technique to remove bias in GCM simulations, *J. Geophys. Res.-Atmos.*, 121, 5718-5735, <https://doi.org/10.1002/2015jd024159>, 2016.
- Nakicenovic, N., and Swart, R.: Emissions scenarios. Special report of the Intergovernmental panel on climate change, Cambridge University Press, Cambridge, 2000.
- Northrop, P. J., and Chandler, R. E.: Quantifying Sources of Uncertainty in Projections of Future Climate, *J. Clim.*, 27, 8793-8808, <https://doi.org/10.1175/jcli-d-14-00265.1>, 2014.
- Olden, J. D., and Poff, N. L.: Redundancy and the choice of hydrologic indices for characterizing streamflow regimes, *River Res. Appl.*, 19, 101-121, <https://doi.org/10.1002/rra.700>, 2003.
- Olsson, T., Jakkila, J., Veijalainen, N., Backman, L., Kaurola, J., and Vehviläinen, B.: Impacts of climate change on temperature, precipitation and hydrology in Finland – studies using bias corrected Regional Climate Model data, *Hydrol. Earth Syst. Sci.*, 19, 3217-3238, <https://doi.org/10.5194/hess-19-3217-2015>, 2015.
- Perrin, C., Michel, C., and Andréassian, V.: Improvement of a parsimonious model for streamflow simulation, *J. Hydrol.*, 279, 275-289, [https://doi.org/10.1016/s0022-1694\(03\)00225-7](https://doi.org/10.1016/s0022-1694(03)00225-7), 2003.
- Qi, W., Zhang, C., Fu, G., Sweetapple, C., and Zhou, H.: Evaluation of global fine-resolution precipitation products and their uncertainty quantification in ensemble discharge simulations, *Hydrol. Earth Syst. Sci.*, 20, 903-920, <https://doi.org/10.5194/hess-20-903-2016>, 2016.
- Räty, O., Räisänen, J., and Ylhäisi, J. S.: Evaluation of delta change and bias correction methods for future daily precipitation: intermodel cross-validation using ENSEMBLES simulations, *Clim. Dyn.*, 42, 2287-2303, <https://doi.org/10.1007/s00382-014-2130-8>, 2014.
- Richter, B. D., Baumgartner, J. V., Powell, J., and Braun, D. P.: A method for assessing hydrologic alteration within ecosystems, *Conserv. Biol.*, 10, 1163-1174, 1996.
- Schewe, J., Heinke, J., Gerten, D., Haddeland, I., Arnell, N. W., Clark, D. B., Dankers, R., Eisner, S., Fekete, B. M., Colon-Gonzalez, F. J., Gosling, S. N., Kim, H., Liu, X., Masaki, Y., Portmann, F. T., Satoh, Y., Stacke, T., Tang, Q., Wada, Y., Wisser, D., Albrecht, T., Frieler, K., Piontek, F., Warszawski, L., and Kabat, P.: Multimodel assessment of water scarcity under climate change, *Proceedings of the National Academy of Sciences*, 111, 3245-3250, <https://doi.org/10.1073/pnas.1222460110>, 2014.
- Teng, J., Vaze, J., Chiew, F. H. S., Wang, B., and Perraud, J.-M.: Estimating the Relative Uncertainties Sourced from GCMs and Hydrological Models in Modeling Climate Change Impact on Runoff, *J. Hydrometeorol.*, 13, 122-139, <https://doi.org/10.1175/jhm-d-11-058.1>, 2012.
- Teng, J., Potter, N. J., Chiew, F. H. S., Zhang, L., Wang, B., Vaze, J., and Evans, J. P.: How does bias correction of regional climate model precipitation affect modelled runoff?, *Hydrol. Earth Syst. Sci.*, 19, 711-728, <https://doi.org/10.5194/hess-19-711-2015>, 2015.
- Teutschbein, C., and Seibert, J.: Bias correction of regional climate model simulations for hydrological climate-change impact studies: Review and evaluation of different methods, *J. Hydrol.*, 456-457, 12-29,



<https://doi.org/10.1016/j.jhydrol.2012.05.052>, 2012.

Thiessen, A. H.: Precipitation averages for large areas, *Mon. Weather Rev.*, 39, 1082-1089, 1911.

Tian, Y., Booi, M. J., and Xu, Y.-P.: Uncertainty in high and low flows due to model structure and parameter errors, *Stoch. Environ. Res. Risk Assess.*, 28, 319-332, <https://doi.org/10.1007/s00477-013-0751-9>, 2013.

620 Tian, Y., Xu, Y.-P., Booi, M. J., and Wang, G.: Uncertainty in Future High Flows in Qiantang River Basin, China, *J. Hydrometeorol.*, 16, 363-380, <https://doi.org/10.1175/jhm-d-13-0136.1>, 2015.

Van Esse, W. R., Perrin, C., Booi, M. J., Augustijn, D. C. M., Fenicia, F., Kavetski, D., and Lobligeois, F.: The influence of conceptual model structure on model performance: a comparative study for 237 French catchments, *Hydrol. Earth Syst. Sci.*, 17, 4227-4239, <https://doi.org/10.5194/hess-17-4227-2013>, 2013.

625 Vansteenkiste, T., Tavakoli, M., Ntegeka, V., De Smedt, F., Batelaan, O., Pereira, F., and Willems, P.: Intercomparison of hydrological model structures and calibration approaches in climate scenario impact projections, *J. Hydrol.*, 519, 743-755, <https://doi.org/10.1016/j.jhydrol.2014.07.062>, 2014.

Velázquez, J. A., Schmid, J., Ricard, S., Muerth, M. J., Gauvin St-Denis, B., Minville, M., Chaumont, D., Caya, D., Ludwig, R., and Turcotte, R.: An ensemble approach to assess hydrological models' contribution to uncertainties in the analysis of climate change impact on water resources, *Hydrol. Earth Syst. Sci.*, 17, 565-578, <https://doi.org/10.5194/hess-17-565-2013>, 2013.

630 Vetter, T., Huang, S., Aich, V., Yang, T., Wang, X., Krysanova, V., and Hattermann, F.: Multi-model climate impact assessment and intercomparison for three large-scale river basins on three continents, *Earth System Dynamics Discussions*, 5, 849-900, <https://doi.org/10.5194/esdd-5-849-2014>, 2014.

635 Vetter, T., Reinhardt, J., Flörke, M., van Griensven, A., Hattermann, F., Huang, S., Koch, H., Pechlivanidis, I. G., Plötner, S., Seidou, O., Su, B., Vervoort, R. W., and Krysanova, V.: Evaluation of sources of uncertainty in projected hydrological changes under climate change in 12 large-scale river basins, *Clim. Change*, 141, 419-433, <https://doi.org/10.1007/s10584-016-1794-y>, 2016.

Whateley, S., and Brown, C.: Assessing the relative effects of emissions, climate means, and variability on large water supply systems, *Geophys. Res. Lett.*, 43, 11,329-311,338, <https://doi.org/10.1002/2016gl070241>, 2016.

Yip, S., Ferro, C. A., Stephenson, D. B., and Hawkins, E.: A simple, coherent framework for partitioning uncertainty in climate predictions, *J. Clim.*, 24, 4634-4643, 2011.

Zhuan, M., Chen, J., Xu, C. Y., Zhao, C., Xiong, L., and Liu, P.: A method for investigating the relative importance of three components in overall uncertainty of climate projections, *Int. J. Climatol.*, 39, 1853-1871, <https://doi.org/10.1002/joc.5920>, 645 2018.