Dear Editor,

Thank you for providing detailed guidance for our manuscript hess-2020-270 entitled "*Flowing wells: terminology, history and the role in the evolution of groundwater science*". We have considered all of the suggestions given by the referee. A detailed response to the referee is attached. We also improved the manuscript by making necessary modifications.

We now submit the revised manuscript for possible publication. If there is any problems, please let me know.

Thank you for your time and consideration of our work. I look forward to hearing from you.

Best regards, Xiao-Wei Jiang Professor of Hydrogeology

Reponses to Referee #2

Suggestions for revision by Garth van der Kamp

This manuscript provides a thorough and detailed summary of how the phenomenon of flowing wells has influenced the development of hydrogeological thinking over the centuries. As such it makes a solid contribution to understanding of the history of hydrogeology.

A few minor revisions are recommended to enhance clarity of the manuscript.

1. The terms "aquifer", "confined", and "unconfined" are used throughout the manuscript to distinguish two distinct classes of permeable formations. However, these terms are not explicitly defined in the manuscript. Clear unambiguous definitions should be included because these terms are not always used consistently in the hydrogeological literature. There is also a connection with the definition of the term "artesian" which is discussed extensively in this manuscript. In particular consideration should be given to whether the terms "confined" and/or "artesian" include permeable formations which are bounded above and below by aquitards but in which the water table exists below the bottom of the overlying aquitard. The definitions provided by the classic Freeze and Cherry (1979) text are pertinent in this regard and could be adopted, except that then the terms "confined" and "artesian" are synonymous.

Response: Thanks for the suggestion. According to Freezing and Cherry (1979), a confined aquifer is an aquifer that is confined between two aquitards, while an unconfined aquifer is an aquifer in which the water table forms the upper boundary. Because an aquifer is defined as a saturated permeable geologic unit that can transmit significant quantities of water under ordinary hydraulic gradients, when the water table exists below the bottom of the overlying aquitard, the aquifer belongs to an unconfined aquifer. We have added the definitions of "confined aquifer" and "unconfined aquifer" in Lines 47-48: "Following Freeze and Cherry (1979), a confined aquifer is a saturated permeable geologic unit that is confined between two aquitards, while an unconfined aquifer is the saturated part of a permeable geologic unit in which the water table forms the upper boundary."

2. LL 396-424 (The birth of Darcy's Law). In this section it is clear by modern understanding that the head loss in the aquifer was not the "head loss from the recharge area to the orifice" (L 415). It would likely take years or more for a new hydraulic gradient to be established between the recharge area and the newly changed elevation of the orifice. Presumably Darcy's measurements of flow rate for different elevations of the discharge orifice were taken after the flow rates appeared to be reasonably stabilized. The manuscript should make clear what Darcy's assumptions were in this respect and evaluate these in terms of present-day understanding of the theory of constant-head (drawdown) tests for confined aquifers.

Response: We agree that head loss in the aquifer should not be the "head loss from the recharge area to the orifice", but is the head loss from a position in the aquifer with constant head away from the flowing well to the discharge orifice. We have clarified this in Line 416.

We also added a sentence "From the angle of a constant-head well test, the first part of the left-hand side of Eq. (3b) is the difference in aquifer head loss at the well created by changing the elevation of the discharge orifice, and the second part is the difference in the well loss from riser pipes with different flow distances." in Lines 424-427.

3. LL 607-610. The manuscript makes an intriguing observation with reference to the classic and influential paper by Freeze and Witherspoon (1967): "However the computing capabilities at the time limited the permeability contrasts between aquifer and aquitard units to a factor of 100, which is far from what is reality in actual flow systems in the field and these simulations are then to some degree misleading in light of what we now know." Was this limitation in fact acknowledged by Freeze and Witherspoon, or was it recognized and published afterwards (if so provide the reference), or is this an observation by the authors of the present manuscript and if so, on what basis? This is important because the Freeze and Witherspoon paper continues to play an influential role in the teaching of flow systems and in the formulation of conceptual hydrogeological models.

Response: Thanks very much for raising this question. We have checked with Allan

Freeze and found our statement was not correct. In fact, Freeze and Witherspoon (1967) had considered a case of permeability contrasts between aquifer and aquitard to a ratio of 1000. Therefore, we have deleted the sentence "However the computing capabilities at the time limited the permeability contrasts between aquifer and aquitard units to a factor of 100, which is far from what is reality in actual flow systems in the field and these simulations are then to some degree misleading in light of what we now know."

Flowing wells: terminology, history and the role in the evolution of groundwater science

5

Xiao-Wei Jiang^{1,*}, John Cherry², Li Wan¹

1. MOE (Ministry of Education) Key Laboratory of Groundwater Circulation and Evolution, China University of Geosciences, Beijing 100083, China

2. G360 Institute for Groundwater Research, University of Guelph, Guelph, Ontario N1G 2W1, Canada
 *Correspondence to: Xiao-Wei Jiang (jxw@cugb.edu.cn)

10

15

20

Abstract

The gushing of water from flowing wells attracted public attention and scientific curiosity as early as early as the 17th century but little attention has been paid to the influence of flowing wells on the evolution of groundwater science. This study asserts that questions posed by flowing wells since the early 19th century led to the birth of many fundamental concepts and principles of physical hydrogeology. Due to the widespread occurrence of flowing wells in basins with regional aquitards, there is a longlasting misconception that flowing wells could only occur in regional confined aquifers. However, the recognition of possible occurrence of flowing wells in unconfined aquifers was anticipated at the turn of the 20th century based on observed increases in hydraulic head with depth in topographic lows of basins without apparent aquitards. This was later verified in the 1960s by field and modelling studies that gave

birth to quantitative analysis of topographically-driven groundwater flow systems, a paradigm shift in hydrogeology. Following this paradigm, several preconditions for flowing wells established in the 19th century were found unnecessary. Intermingled in the evolution of flow system concepts are inconsistencies and confusion concerning the use of the term "artesian", so we propose avoidance of this

25 term. This historical perspective of the causes of flowing well conditions and the influence of flowing wells on groundwater science could lead to a deeper understanding of the evolution of groundwater science, and guide future studies on hydraulics of flowing wells.

1 Introduction

- The primary motivation for the study of groundwater is its importance as a resource (Back and 30 Herman, 1997; Freeze and Cherry, 1979). Groundwater from springs was utilized in the Middle East some 10, 000 years ago (Beaumont, 1973), and produced from shallow flowing wells in the western desert of Egypt in the first millennium B.C. as dug wells reached greater depths (Commander, 2005). However, hydrogeology did not emerge as a distinct science until the 19th century (Fetter, 2004), which corresponds to a period when deeper drilled flowing wells was became a substantial source of water supply in Europe 35 (Howden and Mather, 2013). It is was acknowledged that the recognition of the great value of flowing wells in Europe in the 18th century stimulated the advancement of water well drilling technology (Davis and De Wiest (1966), and that the maturation of geological and hydrological sciences in the 19th century led to the birth of hydrogeology in the 19th century (Meyer et al., 1988). However, little attention has been paid to the importance of the scientific questions prompted by flowing wells in the early evolution of groundwater science in the 19th century.
- 40

This review aims to demonstrate that flowing wells contributed to not only the birth, but also the evolution of several aspects of hydrogeology. Freeze and Back (1983) divided physical hydrogeology into three domains, i.e., physics of groundwater flow, well hydraulics, and regional groundwater flow. Following these domains, studies directly or indirectly related to flowing wells are divided into four

45 threads (Fig. 1), covering all of the three domains. The first three threads shown in Fig. 1 stem from flowing wells in confined aquifers, while the fourth is from flowing wells in unconfined aquifers. Following Freeze and Cherry (1979), a confined aquifer is a saturated permeable geologic unit that is confined between two aquitards, while an unconfined aquifer is the saturated part of a permeable geologic unit in which the water table forms the upper boundary. Note that the The seven classical studies which 50 that were selected by both Freeze and Back (1983) and Anderson (2008) as benchmark papers of physical hydrogeology (groundwater hydrology) have been included in the four threads. Moreover, four out of the seven papers are directly related to flowing wells, implying that flowing wells can be considered as,

The paper is organized as follows. We first introduce the terms used to represent flowing wells, 55 with conceptual examples of the root difference between confined and unconfined sources for these wells (Sect. 2). Sect. 3 summarizes the history of drilling flowing wells in selected regions that have inspired

at least, one of the roots of physical hydrogeology.

hydrogeologists. Sect. 4 through 7 then historically sequence the principal hydrogeological publications through which flowing wells played a major role in the evolution of the science as we know it today. Finally, concluding remarks are given in Sect. 8.



60

65

Fig. 1 Four threads of evolution of physical hydrogeology stemmed from flowing wells. The yellow ellipses are field phenomena of flowing wells, the purple boxes are papers directly related to flowing wells, and the white boxes are papers less or not directly related to flowing wells but have connections to previous or follow-up studies on flowing wells. The publications labeled with a "*" are the seven classical studies identified by both Freeze and Back (1983) and Anderson (2008).

2 Terms related to flowing wells and confusion of "artesian"

2.1 Terms representing flowing wells

In the groundwater hydrology, hydrogeology or hydrology textbooks available to the authors, we found the phenomenon of a well that overflows at the surface is defined or at least mentioned in 34 textbooks. The widely used terms include "flowing well", "artesian well" and "flowing artesian well", which appear in 17, 15 and 13 textbooks, respectively (sometimes more than one term is used in <u>onea</u> book). Other less frequently used terms include "artesian flowing well", "overflowing well", and "free flowing well". For convenience of discussion, we divide these six terms into two categories, those using the term "artesian", and those not using "artesian".

75

The terms "flowing well", "overflowing well" and "free flowing well" stem purely from the phenomenon of water overflow at the well outlet, presumably at grade level. The term "overflowing well" has been used in Britain since at least as early as the 1820s (Anonymous, 1822), and currently is still widely used in Britain, as found in several textbooks (Hiscock and Bense, 2014;Price, 1996;Rushton,

2003). To the authors' knowledge, the term "flowing well" was first used in the USGS hydrogeologic

- 80 report Requsite and Qualifying Conditions of Artesian Wells (Chamberlin, 1885) and is currently the one most widely used. The term "free flowing well" can be found in three textbooks available to us (Fitts, 2013;Kruseman and de Ridder, 1990;Nonner, 2003). By including the adjectives "flowing", "overflowing" or "free flowing", these terms have clear meaning to represent wells that groundwater could flow out without the aid of- pumping.
- 85

The number of textbooks that use one or two of the terms "artesian well", "flowing artesian well" and "artesian flowing well" is as high as 28, indicating the popularity of the adjective "artesian"._The term "artesian well" originates from "well of Artois" ("Artesia" is the historical Latin name of Artois, an ancient province in northern France). It is unquestionable that it was the phenomenon of water overflow at the surface which attracted people's attention to wells of Artois drilled in 1126 (Fuller, 1906;Norton, 90 1897). The term "artesian fountain" was applied in French scientific literature to represent flowing wells in 1805 (Lionnais, 1805), and the term "artesian well" was widely used in France, Britain and the United States in the 1820s and 1830s (Arago, 1835;Buckland, 1836;de Thury, 1830;Garnier, 1822;Storrow, 1835). Currently, an artesian well is synonymous with a flowing well in the majority of European textbooks we have inspected (Hendriks, 2010;Kruseman and de Ridder, 1990;Price, 1996;Rushton,

95 2003;Brassington, 2017;Davie, 2008;de Marsily, 1986;Hölting and Coldewey, 2019) and in at least eight textbooks in North America (Deming, 2002; Domenico and Schwartz, 1998; Driscoll, 1986; Pinder and Celia, 2006; Yeh et al., 2015; Hornberger et al., 2014; Fitts, 2013; Alley and Alley, 2017). Since the late 19th century, the term artesian wells were not restricted to flowing wells, but were divided into flowing artesian wells and non-flowing artesian wells (Carpenter, 1891;Norton, 1897;Slichter, 1899). In ten 100 textbooks in North America we inspected (Fetter, 2001;Freeze and Cherry, 1979;Batu, 1998;Kasenow, 2010;LaMoreaux et al., 2009;Mays, 2012;McWhorter and Sunada, 1977;Heath, 1983;Schwartz and Zhang, 2003;Todd and Mays, 2004), the term flowing artesian well is used to represent a flowing well

and an artesian well is equivalent to a well penetrating a confined aquifer but not necessarily flowing at the surface .

105 Due to the widespread occurrence of aquitards, it was initially believed that only a confined aquifer bounded by aquitards has the possibility for the static water level to have hydraulic head higher than the ground surface elevation, i.e., flowing wells could occur only in confined aquifers. Later studies found that flowing wells could also occur in an unconfined aquifer, i.e., a homogeneous aquifer without aquitards (Hubbert, 1940;Tóth, 1966;Versluys, 1930). Because the adjective "artesian" indicates the type

- of aquifer in Artois, i.e., a confined aquifer, according to the definitions given by the USGS, the term "flowing artesian well" was restricted to flowing wells in confined aquifers (Lohman, 1972b), and it was explicitly pointed out that "a flowing well does not necessarily indicate artesian conditions" (Heath, 1983). To differentiate flowing wells in confined and unconfined aquifers, Tóth (1966) defined confinedflow flowing wells and unconfined-flow flowing wells as two end members of flowing wells, while
- Freeze and Cherry (1979) defined geologically-controlled flowing wells and topographically-controlled flowing wells. As shown in Fig. 2, geologically-controlled flowing wells are equivalent to Tóth's confined-flow flowing wells, while topographically-controlled flowing wells correspond to Tóth's unconfined-flow flowing wells. Note that in geologically-controlled flowing wells, topography is still the driving force of groundwater flow from the topographic highs to topographic lows. Therefore, we avoid the terms of geologically-controlled and topographically-controlled flowing wells, We-and use

Tóth's (1966) terminology in the following discussion.



Fig. 2 (a) Geologically-controlled or confined-flow flowing wells; (b) topographically-controlled or unconfined-flow flowing wells (Modified from Freeze and Cherry, 1979). It is assumed that the screened intake for the respective well is at its bottom.

2.2 Confusing uses of "artesian" in the literature

125

The adjective "artesian", which was initially used in terms "artesian fountain" and "artesian well", has been applied to such terms as "artesian water", "artesian aquifer", and "artesian pressure". Following the definitions given by the USGS (Lohman, 1972a), and as used in many USGS publications, the term

130 "artesian aquifer" is equivalent to "confined aquifer", "artesian water" refers to groundwater from or within a confined aquifer, and "artesian pressure" is the water pressure in a confined aquifer. An artesian basin was defined by Meinzer (1923b) to be a basin in which water is confined under artesian pressure, implying that the hydraulic head being greater than the elevation of ground surface is not a necessary condition. The Great Artesian Basin in Australia is one of the largest artesian basins in the world and is

well known for its numerous flowing wells in confined aquifers. In the United States, there are many artesian basins, like the artesian basin of the Dakotas (Darton, 1905;Swenson, 1968), the great Paleozoic artesian basin of the Mississippi Valley region (Meinzer, 1923a), the Roswell artesian basin in New Mexico (Fiedler and Nye, 1933), and the Grand Junction artesian basin in Colorado (Jacob and Lohman, 1952), all of which had many flowing wells in the initial stage of groundwater development, but many of which currently have static water levels significantly below grade.--

The different meanings of "artesian" caused confusion not only to beginners of hydrogeology, but also to professional hydrogeologists, which has been realized by some textbook authors. Deming (2002) and Younger (2007) both chose photos of a flowing well for their cover image, but they have quite opposite viewpoints on "artesian". Deming (2002) held the opinion that "artesian" implies that the hydraulic head is greater than the elevation of ground surface, and defining "artesian aquifer" to be identical to confined aquifer would make the definition not only conceptually useless, but also etymologically incorrect because wells drilled in Artois could flow spontaneously. On the contrary, Younger (2007) believed that "artesian" is a synonym of "confined", and pointed out that "artesian" is also widely misused to refer to any well from which water flows without pumping, a phenomenon which is not restricted to confined aquifers. Younger also discouraged further use of "artesian" because it lacks intuitive meaning in modern English.

To sum up, hydrogeologists are keenly interested in flowing wells, but the literature is confusing concerning the qualifier of "artesian". This confusion has likely led to the groundwater community underestimating the role that flowing wells have played in the evolution of its science. Given that the meaning of the adjective "artesian" has a few meanings in the literature, the meaning can be unclear unless it is defined in each publication of use. There is no necessity to preserve this term in groundwater science and therefore we propose that its use be avoided.

3 The history of drilling flowing well in selected regions

Many of the first deep wells that were drilled encountered static hydraulic heads significantly above
 the local land surface (Fetter, 2001). Here, we briefly review the history of both shallow and deep flowing well in regions that most directly contributed to the development of modern groundwater science.

3.1 France

155

As early as 1126, a shallow flowing well tapping the confined fringe of the chalk aquifer was

identified in Artois in northern France (Margat et al., 2013). <u>In the early 19th century, The the technique</u>
of cable-tool drilling (also called percussion drilling) resulted in drilling of deeper flowing wells in
France-in the early 19th century. Garnier (1822) published the first technical guidebook on drilling
"artesian" wells. It was stated that with the exception of some provinces, there are few parts of France where artesian wells are not be expected. Garnier obtained a prize from the Society for the Encouragement of Industry due to the publication of this book, which reflects the interest of the French
government in flowing wells.

According to Arago (1835), most flowing wells up to that time ranged in depth from 36 m to 177 m. Between 1833 and 1841, a flowing well with a depth of 548 m was drilled in Grenelle within the Paris Basin. The water level in this flowing well could rise to a height of 33 m above ground surface in a pipe supported by a wooden scaffolding accessible by steps (Fig. 3). In 1855, an article titled *The Artesian Well at Grenelle, in France* was reproduced in *California Farmer and Journal of Useful Sciences* in the United States (Anonymous, 1855). It was commented that "*This splendid achievement at that date may*

175

be looked upon as the pioneer effort, and at the present time and within a very few years, the most astonishing results may be expected." In 1861, another flowing well with a depth of 586 m was completed in Passy near Paris, which is the last flowing well in Paris still in use today. Darcy (1856) and Dupuit (1863) were both inspired by flow rate measurements at different orifices in these deep flowing wells. The details are given in Sect. 5.



Fig. 3 The wood engraving of the flowing well at Grenelle (uncopyrighted and freely distributed by http://www.antiqueprints.com). The external structure was demolished in 1903 (Ritzi and Bobeck, 2008).

3.2 Italy

185

According to Norton (1897), nearly equal in antiquity with the flowing wells of Artois are those of Modena in northern Italy, which might have disputed with Artois on the right to provide their name to flowing wells. It was noteworthy that two well-borer's augers were used in the municipal coat of arms,

- 190 indicating the influence of wells on the town. Giovanni Cassini (1625-1712), referred to flowing wells in Modena and Bologna, and developed one himself at the castle of Urbin (Merdinger, 1955). A shallow flowing well can be obtained by digging to a depth of ~20 m and boring a hole for the next ~1.5 m by using an auger (Biswas, 1970).
- Based on the famous flowing wells of Modena, Bernardino Ramazzini (1633–1714) and Antonio
 Vallisnieri (1661–1730) connected flowing wells to the water cycle and pioneered the theory of artesian water pressure in the late 1600s and early 1700s (Duffy, 2017). The details are to be introduced in Subsect.
 4.1.

3.3 Great Britain

By the end of the 1700s, some shallow flowing wells had been dug in Great Britain. In 1785, a
flowing well (artificial spring) with a depth of ~3.7 m was dug ~91 m away from the Darwent River in Derby (Darwin, 1785). One of the first flowing wells near London was completed in 1794 (Buckland, 1836). The successful experiences of water supply from flowing wells led to sinking of more flowing wells. According to Macintosh (1827), James Ryan obtained a patent on boring for minerals and water in 1805, while John Goode obtained a patent on boring for the purpose of obtaining and raising water in 1823, indicating that drilling was active in Great Britain in early 19th century. According to an article in *Monthly Magazine and British Register* (Anonymous, 1822), two flowing wells with depths of 32 m and 37 m were drilled in the town of Tottenham in 1821, and many flowing wells had existed for a period of time in various parts of the country by 1822.

The publication of Garnier (1822) in France aroused further interest in flowing wells in Great

210 Britain (Farey, 1823). Although many flowing wells had been drilled in the London Basin, many boreholes failed to become flowing wells. Therefore, Buckland (1836) called for a theory of flowing wells. The experience gained from the costly failures improved understanding of conditions necessary

for the success of a flowing well, the details of which are to be discussed in Subsect. 4.1.

3.4 The United States

215 Accompanying with the increase in the population due to immigration and Western expansion in the US, there was a higher demand of water resources for drinking and for agriculture. As a result of the increased drilling technology since the 19th century, deep groundwater was utilized by drilling numerous wells, many of which were flowing wells, at least in the initial stage of development. Here, we list some regions where flowing wells were drilled, resulting in significant advances in <u>the</u> groundwater science.

220

Development of the Cambrian-Ordovician aquifer system in the northern Midwest can be traced to 1864 when a flowing well with a depth of 217 m was drilled in Chicago (Konikow, 2013). By the end of the 19th century, flowing wells were common in topographically low areas in the Mississippi, Missouri, and Illinois River valleys, near Lake Michigan, and around Lake Winnebago in northeastern Wisconsin (Young, 1992). At the beginning of the 21st century, there were still many flowing wells newly drilled in

225 Michigan (Gaber, 2005). Chamberlin's (1885) classic report based on the hydrogeologic conditions in Wisconsin is considered as one of the roots of groundwater science in Wisconsin (Anderson, 2005). In 1876, a flowing well with a depth of 293 m and an initial flow rate of 3270 m³/d drilled in Prairie du Chien, Wisconsin was named *The Greatest Artesian Fountain in America* (Meiter, 2019). The photo of this flowing well served as the frontispiece of Chamberlin (1885) and Freeze and Back (1983), the cover

image of Deming (2002), and was also cited in Anderson (2005).

In the Great Plains, interest in groundwater emerged due to the irrigation demands beginning in the 1880s, due to the widespread drought. In early 20th century, flowing wells were common in topographic lows near rivers, for example, in the Arkansas River valley of southeastern Colorado, much of South Dakota, and parts of southeastern North Dakota and northeastern Nebraska in the Missouri River valley (Darton, 1905). In South and North Dakota within the Great Plains, some 400 deep wells were drilled into the Dakota sandstone by 1896, of which over 350 were flowing wells (Darton, 1897). Due to the introduction of the jetting method of drilling in around 1900, thousands of small-diameter wells were drilled to the Dakota sandstone during the following two decades. There were about 10,000 deep wells in South Dakota in 1915, and between 6,000 and 8,000 deep wells in North Dakota in 1923 (Meinzer and Hard, 1925). Due to the increased withdrawal of deep groundwater, many flowing wells became non-

9

flowing wells, accompanied by decreasing flow rates in the flowing wells that still flowed. The condition

of flowing wells led to improved understanding of the pattern of groundwater circulation in confined aquifers (Darton, 1905), while the changing production rates led to the birth of the concept of compressibility and the role of compressibility on production in confined aquifers (Meinzer and Hard,

245

250

1925; Meinzer, 1928). The details are discussed in Subsect. 6.1.

In flowing wells of the Dakota aquifer, it was noted that "the pressure increases for several hours or even days after the flow is shut off, and when opened the flow decreases in the same way until the normal flow is reached" (Meinzer, 1928). Several decades later, based on field observations of decreasing flow rate with time in flowing wells in the Grand Junction artesian basin and in the Roswell artesian basin in New Mexico, constant-drawdown aquifer tests were proposed to obtain hydraulic parameters (Jacob and Lohman, 1952;Hantush, 1959). More details are discussed in Subsect. 6.2.

3.5 Australia

The Great Artesian Basin, which covers one-fifth of the total area of Australia, is one of the largest and best-known groundwater basins in the world (Ordens et al., 2020). The first shallow flowing well
was dug to a depth of 43 m by using an auger near a spring in New South Wales in 1878, while the first deep machine-drilled flowing well was completed in 1887 at a depth of 393 m near Cunnamulla, Queensland (Williamson, 2013). By the end of the 19th century, there were already around 1000 flowing wells on the continent (van der Gun, 2019). The exploitation of flowing wells and artesian water contributed to the emergence of hydrogeology as a discipline in Australia (Williamson, 2013), and the development of such sources has played a vital role in the pastoral industry in the arid and semi-arid regions of Australia (Habermehl, 2020).

Due to the occurrence of intervening aquifers and aquitards, the Great Artesian Basin is a multilayered confined aquifer system. Although head drawdowns of up to 100 m have been recorded in highly developed areas, hydraulic heads in the Jurassic and Lower Cretaceous aquifers are still above ground

265 surface throughout most of the basin (Habermehl, 2020). A comprehensive review of the history and recent research status of the basin can be found in Ordens et al. (2020).

3.6 Canada

270

In this subsection we consider t<u>T</u>he hydrogeology of the Canadian Prairies which has been studied since the beginning of the 20th century. Groundwater in this region is largely obtained from surficial Pleistocene glacial drift and the underlying bedrock of Tertiary or Cretaceous age. Quaternary glacial deposits and the underlying Tertiary Paskapoo sandstone constitute a thick unconfined aquifer. A similarity between the potentiometric surface and the local topography were widely observed in many parts of the Canadian Prairies (Jones, 1962;Meyboom, 1962;Tóth, 1962;Farvolden, 1961).-Due to the occurrence of a large number of flowing wells, either in the glacial drift or in the bedrock, great attention was paid to the relation between topography, geology and areas with flowing wells during basin-scale groundwater surveys (Meyboom, 1966). <u>A similarity between the potentiometric surface and the local topography were widely observed in many parts of the Canadian Prairies (Jones, 1962;Meyboom, 1966).</u>

The Trochu area in central Alberta, which covers an area of 67 km², is representative of the hydrogeology of the Canadian Prairies. There were 10 shallow flowing wells ranging in depth from 9 m to 27 m in topographic lows (Tóth, 1966). Because the glacial deposits have low contents of clay, they are efficient for infiltration of rainfall and evaporation of soil water. Combined with previous theoretical findings on topographically-driven flow systems (Hubbert, 1940;Tóth, 1962, 1963), these flowing wells in unconfined aquifers were considered to be controlled by topography and are-typical manifestations of groundwater discharge (Tóth, 1966). The details are discussed in Sect. 7.

3.7 China

275

As early as in the 11th century, deep drilling using bamboo pipes was employed in Sichuan Province, China, to reach brines from 100-m-deep boreholes (Vogel, 1993). In the 16th century, a flowing well in Beijing became a site of tourism known as "Manjing" (literal meaning, a well full of water). In the 17th century, due to the success of developing flowing wells for brines, "Ziliujing" (meaning, flowing well) became the name of a town in Sichuan Province. In 1835, the 1001-meter-deep flowing well at <u>Shenhai</u> (frequently mistaken to be Xinhai in the English literature) was constructed for producing brines and gases (Vogel, 1993). However, these early drilling techniques and experiences of drilling deep flowing wells did not substantially produce follow-on activity in the development of groundwater science in China. In early 1950s, the large demand of groundwater in (semi-)arid regions led to exploration of groundwater and resulted in the establishment of hydrogeology as a distinct discipline in several universities. In late 1950s, the success of drilling some flowing wells led to a campaign of finding more flowing wells for agriculture in many basins of the country. Unfortunately, <u>due to overexploitation</u>, flowing wells have disappeared in many <u>basinsregions</u>, including the North China Plain. 300 One of the most intensively studied groundwater basins is the Ordos Plateau in northwestern China, composed mainly of a thick sandstone aquifer of Cretaceous age, up to around 1000 m thick. Because the overlying thin Quaternary deposits have much higher permeability, and there is no continuous aquitard within the Cretaceous sandstone, the Ordos Plateau can be conceptualized as a thick unconfined aquifer (Hou et al., 2008;Jiang et al., 2018). As early as the 1950s, several flowing wells were established in deep boreholes in the Cretaceous sandstone in topographic lows, and subsequently numerous flowing wells were drilled for agricultural water. For example, in the Wudu lake catchment, on this plateau with an area of approximately 200 km², there were 15 flowing wells in 2015 (Wang et al., 2015b). In recent years, additional flowing wells have been drilled. The majority of flowing wells in this catchment range in depth from 70 m to 300 m, with one well reaching the bottom of the Cretaceous sandstone at a depth of 800 m.

To reduce costs, the flowing wells drilled into the Cretaceous sandstone are cased only in the very shallow part that corresponds to the Quaternary deposits. These wells provide a prime example to study the hydraulics of flowing wells in a macroscopically homogeneous basin. The <u>steady-state hydraulics</u> of flowing wells in homogeneous basins is introduced in Subsect. 7.3.

315 4 Confined-flow flowing wells and confined flow bounded by aquitards (1690scurrent)

4.1 Conditions of confined-flow flowing wells

Based on his observations of flowing wells in Modena, Italy in 1691, Ramassini plotted a geological section showing the occurrence of flowing wells penetrating a confined aquifer, receiving its water from
an underground reservoir at a higher level in the surrounding mountain (Biswas, 1970). Therefore, for the occurrence of flowing wells, Ramassini already suspected the role of topography, or the hydraulic gradient between the well and the underground reservoir in the surrounding mountain (de Vries, 2007). Unfortunately, he thought the source of water in the underground reservoir in the surrounding mountain was more likely to be from the sea. Later, Valniseri argued in 1726 that the source of water in the flowing wells of Modena must be rainfall and snowmelt in the adjacent Apennine Mountains (Duffy, 2017), which was the start of thinking about the simultaneous control of topography and precipitation on flowing

wells.

In the evolution of thinking about groundwater, it was universally accepted by the early 19th century

that the water from flowing wells came from rainfall, which found its way through the pores or fractures

330 of a permeable stratum sandwiched between two water-tight strata at depth (Garnier, 1822). de Thury (1830) summarized three conditions of flowing wells. In his words, the first is to reach a flow of deep water coming from higher basins and passing along the bosom of the earth between compact and impermeable rocks; the second is to afford this deep water the possibility of rising to the surface by using an artificially bored well; and the third is to prevent the spreading of the ascending water into the 335 surrounding sand or rock by inserting tubes into the bored well.

345

Following the successful drilling of flowing wells in France, the theory of the mechanism of flowing wells became well understood in Britain. For example, Buckland (1836) illustrates the cause of two flowing wells in the confined aquifer of the London Basin. The successful experiences coupled with the costly failures of drilling in Britain led to the recognition of three necessary conditions for the success of

340 a flowing well (Bond, 1865). These are:

> "(1) The existence of a porous stratum having a sufficient outcrop on the surface to collect an adequate amount of rainfall, and passing down between two impermeable strata; (2) the level of the outcropping portion of the porous stratum must be above that of the orifice of the well, so as to give a sufficient rise to the water; (3) there must be no outlet in the porous stratum by which its drainage can leak out, either in the shape of a dislocation, by which it can pass into lower strata, or a natural vent, by which it can rise to the surface at a lower level than the well."

Based on his North American experience with the Wisconsin portion of the Cambrian-Ordovician aquifer system, Chamberlain (1885) published The Requisite and Qualifying Conditions of Artesian Wells and listed seven conditions of flowing wells, which include:

350 (1) A pervious stratum to permit the entrance and the passage of the water; (2) A water-tight bed below to prevent the escape of the water downward; (3) A like impervious bed above to prevent escape upward, for the water, being under pressure from the fountain-head, would otherwise find relief in that direction; (4) An inclination of these beds, so that the edge at which the waters enter will be higher than the surface at the well; (5) A suitable exposure of the edge of the porous stratum, 355 so that it may take in a sufficient supply of water; (6) An adequate rain-fall to furnish this supply; (7) An absence of any escape for the water at a lower level than the surface at the well."

In fact, the seven prerequisites given by Chamberlain (1885) are inclusive of the three conditions given by de Thury (1830) and Bond (1865) several decades earlier. However, Bonds (1865) did not cite de Thury (1830), and Chamberlin (1885) did not cite either Bonds (1865) or de Thury (1830), therefore, we assume their findings were obtained independently.

4.2 Confined flow bounded by aquitards

In the late 1890s, Darton (1897) with the USGS investigated the occurrence of flowing wells in the Dakotas and plotted the cross-section of the Dakota aquifer (Fig. 4). By constructing contours of hydraulic head of the Dakota confined aquifer across South Dakota, which shows the head loss through

the confined aquifer, Darton (1905) concluded that groundwater discharged by the flowing wells in the east had flowed hundreds of kilometers horizontally through the aquifer from outcrops in the west. This study popularized the pattern of groundwater flow in a confined aquifer that outcrops in topographic highs as shown in Fig. 2a. There was also a long-lasting conceptual model for the Great Artesian Basin of Australia that each aquifer can be considered to be laterally continuous across the extent of the basin
(Habermehl, 2020).



Fig. 4 The profile of the Dakota confined aquifer and the confined flow bounded by aquitards. (Modified from Darton, 1897)

375

380

360

As shown in Fig. 4, groundwater flow in a confined aquifer, which is bounded by the adjacent aquitards, is similar to flow through a pipe. Such a flow pattern is commonly utilized to interpret groundwater age in confined aquifers, which is known as piston flow age (Bethke and Johnson, 2008;Hinkle et al., 2010). Because many hydrogeochemical processes are dependent on travel time through the aquifer, hydrochemical facies (Back, 1960; 1966) usually evolve along the flow path bounded by aquitards. Therefore, such a flow pattern, which stemmed from analyzing confined-flow flowing wells,

is the cornerstone of sampling and analyzing groundwater geochemistry and isotopes in confined aquifers.

5 Darcy's law and steady-state well hydraulics inspired by flowing wells (1850s-1910s)

385 5.1 The birth of Darcy's law evoked by flowing wells

390

395

400

It is widely known that Darcy's law, which represents the beginning of groundwater hydrology as a quantitative science in 1856 (Freeze and Back, 1983), was established based on sand column experiments. In fact, the sand column experiments were designed to confirm a linear correlation between flow rate and head loss in sands which was first recognized in flowing wells (Brown, 2002;Ritzi and Bobeck, 2008). Flowing wells were important sources of water supply in the Paris Basin since the early 19th century, and this led to flow rates being measured at different elevations of discharge orifices in several flowing wells in the 1840s (Fig. 5). In fact, such experiments can be regarded as constant-head (drawdown) tests at multiple discharge orifices in single wells. As shown in Fig. 5a, in either September or November, the flow rates increased linearly as the elevation of discharge orifice decreased. Henry Darcy's <u>(1803-1858)</u> interest in this linear correlation instigated his famous lab experiments with sand column (Brown, 2002;Ritzi and Bobeck, 2008).



Fig. 5 (a) The changes in flow rate with elevation of discharge orifice of a flowing well (data from Darcy, 1856); (b) The device for measuring flow rate (only one discharge orifice is open during measurement). The higher flow rate in November shown in (a) can be a result of higher hydraulic head surrounding the flowing well, probably due to the contribution of groundwater recharge.

Theoretically, the head loss from the recharge area to the discharge orifice can be divided into head loss in the aquifer and head loss along the well pipe. According to the Chezy equation describing head

- 405 loss at high flow velocities in pipes, head loss in the well pipe should be proportional to the square of flow rate. Based on the linear trend between head loss and flow rate shown in Fig. 5a, it was inferred that the head loss in the short-distance well pipe with high velocities is limited compared with the well loss in the long-distance aquifer with low velocities. To identify the control of flow velocity on head loss, Darcy conducted pipe flow experiments during 1849 and 1851 and proposed equations on the dependence of head loss on flow rate. At low velocity, the head loss was found to be linear to discharge rate, which
- 410 of head loss on flow rate. At low velocity, the head loss was found to be linear to discharge rate, which can be written as

$$h_L = \frac{La}{\pi r^4} q \tag{1}$$

and at high water velocity, the head loss was found to be linear to the square of discharge rate, which can be written as

$$h_L = \frac{Lb}{\pi r^5} q^2 \tag{2}$$

where L is length, r is pipe radius, q is the volume discharge rate, and a and b are empirical coefficients of proportionality. Eq. (1) verified Poiseuille (1841) equation by experiments under completely different circumstances, and Eq. (2) can be considered as another form of the Chezy equation. Note that Eq. (2) led to the co-naming of the Darcy-Weisbach pipe friction formula. About 30 years later, Reynolds (1883) fully quantified the occurrence and differences between laminar and turbulent flow by introducing the Reynolds number.

By assuming that head loss from <u>a position in the aquifer with constant head away from the</u> <u>flowing well</u> the recharge area to the discharge orifice occurs in both the aquifer and the well pipe, equations similar to the following forms were obtained:

$$h_{1} + \frac{aL'}{\pi r'^{4}}q_{1} + \frac{bH_{1}}{\pi r^{5}}q_{1}^{2} \cong h_{2} + \frac{aL'}{\pi r'^{4}}q_{2} + \frac{bH_{2}}{\pi r^{5}}q_{2}^{2}$$
(3a)

$$(h_1 - h_2) + \frac{b}{\pi r^5} (H_1 q_1^2 - H_2 q_2^2) \cong -C(q_1 - q_2)$$
(3b)

where *L*' is flow distance in the aquifer from the position with constant head to the flowing wellrecharge area, *r*' is radius representative of pores in the aquifer, h_1 and h_2 are the elevations of the discharge orifices measured from the ground and can be considered as aquifer potentiometric heads, H_1 and H_2 are the lengths of well pipes from the bottom to the discharge orifice, and *C* is an unnamed constant. From the angle of a constant-head well test, the first part of the left-hand side of Eq. (3b) is the difference in aquifer head loss at the well created by changing the elevation of the discharge orifice, and the second part is the

425

430

415

420

<u>difference in the well loss from riser pipes with different flow distances.</u> The linear relationship between h_1 - h_2 and q_1 - q_2 shown in Fig. 5a indicates that the second <u>term-part</u> on the left<u>-hand</u> side of Eq. (3b) is negligible. Therefore, Eq. (3b) changes into

$$h_1 - h_2 \cong -C(q_1 - q_2) \tag{4}$$

where C can be interpreted as the slope shown in Fig. 5a.

To confirm Eq. (4), in 1855, Darcy conducted the sand column experiments by assuming that water flow through sands is similar to water flow through the aquifer and obtained the well-known empirical

440 equation of Darcy' law. Note that the coefficient today known as hydraulic conductivity was not named by Darcy. Hubbert (1940) rigorously interpreted hydraulic conductivity and examined Darcy's law in the light of the microscopic Navier-Stokes flow theory, which raised the sophistication of understanding of Darcy's law.

5.2 Steady-state well hydraulics in confined aquifers: Dupuit equation

In 1850, Jules Dupuit (1804-1866) succeeded Henry Darcy as Chief Director for Water and Pavements and started his research on groundwater hydraulics. The field data shown in Fig. 5a triggered Dupuit to quantify the constant C in Eq. (4). Dupuit realized that groundwater flow would radially converge to the flowing well and head loss in the confined aquifer away from the flowing well would form a cone of depression (Fig. 6).







435

Fig. 6 Plot from Dupuit (1863) showing the radial flow toward a flowing well penetrating a confined

aquifer, which caused head loss with a cone of depression in the potentiometric level ("niveau piezometrique"). It is clear that the potentiometric level of the cone of depression is still above the land surface.

455

460

In radial flow, Darcy's law can be written as

$$q = k \left(2\pi xB\right) \frac{dy}{dx} \tag{5}$$

where *B* is the thickness of the confined aquifer, *x* is the radius within the cone of depression, and *y* is the corresponding head with reference to the elevation of the discharge orifice. Dupuit (1863) obtained the following equation by integrating Eq. (5) from the radius of the well, r_w , to the radius of influence, *R*:

$$h_0 - h_w = \frac{q}{2\pi k B} \ln\left(\frac{R}{r_w}\right) \tag{6}$$

where h_w is the elevation of the discharge orifice, and h_0 is the hydraulic head at the radius of influence, which equals the initial hydraulic head of the flowing well when the well has been closed for a duration

465 of time. By comparing Eq. (4) and (6), it can be interpreted that $C = \frac{1}{2\pi kB} \ln \left(\frac{R}{r_w}\right)$. Dupuit (1863)

explicitly stated that Eq. (6) is supported by the measurements of flow rate versus elevation of discharge orifice of flowing wells reported in Darcy (1856).

Although Eq. (6) was derived based on the hydrogeologic condition of a flowing well in a confined aquifer, it is applicable to non-flowing wells in a confined aquifer. A limitation of the equation is the

difficulty of determining the radius of influence in the field. Thiem (1906) improved Eq. (6) by integrating Eq. (5) between two wells within the cone of depression and obtained an equation to determine hydraulic conductivity, which is known as the Thiem equilibrium method. Although the Thiem equation (Thiem, 1906) was introduced in almost all textbooks, Dupuit's pioneering study on steady-state radial flow to a flowing well in confined aquifers (Dupuit, 1863), which is applicable to non-flowing well in confined aquifers, was seldom mentioned in textbooks.

Dupuit (1863) also derived similar equations for a well in unconfined aquifers by neglecting the vertical hydraulic gradient, which is currently known as Dupuit-Forchheimer approximation. Although the vertical hydraulic gradient is neglected, the Dupuit-Forchheimer approximation is still useful in interpreting regional scale groundwater flow problems (Haitjema and Mitchell-Bruker, 2005).

480 6 Compressibility of confined aquifers and transient well hydraulics inspired by flowing wells (1920s-current)

6.1 Compressibility of confined aquifers: concepts instigated by flowing wells

In the 1920s, groundwater resources were undergoing development in the United States, therefore, much of the effort of the USGS turned toward developing an inventory of wells and their production (Domenico and Schwartz, 1998). The inventory of groundwater resources in the Dakota aquifer indicated that the number of flowing wells that were still flowing was decreasing., The imbalance between groundwater discharge through flowing wells and groundwater recharge led to significant insight into the role of aquifer compressibility (Meinzer, 1928;Meinzer and Hard, 1925).

- Groundwater development in the Dakota aquifer started with flowing wells in the 1880s. After
 active drilling in the 1900s, investigations in the 1910s showed that many flowing wells had stopped flowing. To determine the groundwater budget, a study area of 18 townships near Ellendale, North Dakota (Ranges 48 through 65 West along Township 129 North) with a total of 320 flowing wells supplied by the Dakota sandstone was selected. The rate of discharge through flowing wells was estimated to be close to 3000 gallons per minute during the 38-year period from 1886 to 1923, but the
 rate of lateral recharge through eastward percolation was inferred to be less than 1000 gallons per minute (Meinzer and Hard, 1925). Although these estimates could be very inaccurate, they were sufficient to demonstrate the excess of discharge through flowing wells over recharge. Meinzer and Hard (1925) concluded that most of the water discharged through the flowing wells was taken out of storage in the
- 500

505

485

manifestation of elasticity of the aquifer medium (Meinzer and Hard, 1925).

By summarizing these observations of flowing wells, as well as the evidences of compressibility and elasticity of compacted sand, land subsidence in an oil field, water level fluctuations produced by ocean tides, and water level fluctuations produced by railroad trains, Meinzer (1928) concluded that confined aquifers are compressible and elastic. Although geochemical and numerical studies several decades later showed that leakage also contributed to well discharge in the Dakota aquifer (Bredehoeft et al., 1983;Leonard et al., 1983;Swenson, 1968), this did not undermine the role of flowing wells that had intrigued the interest of hydrogeologists.

sandstone aquifer, indicating that the sandstone aquifer was compressible. It was also observed that the

artesian head would increase gradually for some time after a flowing well was shut off, which is a

Several years later, by assuming that discharge of groundwater from storage as head falls is similar

to release of heat as temperature decreases, Theis (1935) recognized that confined aquifers possess a property analogous to heat capacity and derived the equation characterizing the transient behavior of hydraulic head due to discharge of a well. Theis's solution was not understood by the groundwater hydrology community until Jacob (1940) defined the coefficient of storage as a combination of vertical compressibility of the porous medium and compressibility of water. Hereafter<u>Thereafter</u>, numerous efforts were devoted to determining the aquifer parameters using transient well hydraulics and identifying the behavior of drawdown/flow rate in other aquifers (leaky aquifers, unconfined aquifers).

6.2 Transient well hydraulics in flowing and non-flowing wells in confined aquifers

In the early 1930s, the high demand for groundwater led to evaluation of groundwater in different parts of the United States and pumping tests using the Thiem equilibrium method were conducted to 520 obtain hydraulic conductivity in several regions (Lohman, 1936;Theis, 1932;Wenzel, 1936). Unfortunately, it was found difficult to consistently obtain aquifer parameters because of the increasing drawdown with time (Wenzel, 1936).

To interpret the time-varying drawdown, Charles Vernon Theis (1900-1987) assumed that groundwater flow disturbed by a sink withdrawing water was analogous to heat conduction disturbed by a sink withdrawing heat and resorted to Clarence Isador Lubin (1900-1989), a mathematician at the University of Cincinnati, for the solution of temperature distribution of a uniform plate under two different conditions (White and Clebsch, 1993). The first condition is the introduction of a sink kept at 0 temperature, which corresponds to the constant-drawdown aquifer test problem and is applicable to flowing wells, and the second condition is the introduction of a sink with a uniform heat flow rate, which corresponds to the constant-rate pumping test problem. It was fortunate that the solution of the second problem was readily available in the field of heat conduction (Carslaw, 1921). In this way, Theis (1935) obtained the analytical solution of time-dependent drawdown induced by pumping and opened the door of determining aquifer parameters using transient well hydraulics.

When a flowing well has been shut off for a duration of time, upon reopening, the discharge rate 535 decreases with time, which can be considered as a constant-drawdown aquifer test. Based on Smith (1937) solution to the analogous problem in heat conduction (the first problem raised by Theis), Jacob and Lohman (1952) derived a solution to the constant-drawdown well test problem in a confined aquifer and verified the results based on flowing wells in the Grand Junction artesian basin, Colorado. Several years later, after the classical work on constant-rate pumping problem in leaky aquifers (Hantush and Jacob,

- 540 1955), Hantush (1959) derived a solution to the constant-drawdown well hydraulics to a flowing well in leaky aquifers. In fact, constant-drawdown tests can also be carried out in non-flowing wells either by using a specially designed pump or by connecting the well to a pressurized water container at the surface (Mishra and Guyonnet, 1992). Such constant-drawdown tests have been found to be particularly useful in low-permeability aquifers (Jones, 1993;Tavenas et al., 1990;Wilkinson, 1968).
- 545 In summary, although the door of transient well hydraulics was directly opened by Theis (1935) based on constant-rate pumping tests, constant-drawdown well tests triggered by flowing wells belong to an indispensable component of transient well hydraulics and are still receiving active attention in the current century (Chang and Chen, 2002;Wen et al., 2011;Tsai and Yeh, 2012;Feng and Zhan, 2019). It is worth noting that current models on transient well hydraulics did not fully account for the relationship between groundwater recharge from precipitation and groundwater discharge in wells, for example, the higher flow rate in November than that in September shown in Fig. 5a can not be explained by current theories.

7 Unconfined-flow flowing wells and topographically-driven flow systems (1890scurrent)

555 **7.1 Qualitative understanding of topographically-driven <u>groundwater</u> flow and unconfined-flow flowing wells**

At the turn of 20th century, there was initial field evidence of topographically-driven groundwater flow, namely, upward groundwater flow below surface water bodies (King, 1899) and increases in hydraulic head with depth in the discharge area (Pennink, 1905) in homogeneous aquifers. Versluys (1930) explicitly pointed out that the occurrence of artesian pressure exceeding the land surface corresponds to an increase in hydraulic head with depth, and would necessarily lead to upward groundwater flow. By calculating head distribution based on the analogy between temperature and hydraulic head, Versluys concluded that aquitards are not necessary conditions of flowing wells. Note that dDue to the poor understanding of potential of subsurface water, Versluys wrongly assumed that pressure head difference

is the driving force of groundwater flow.

Based on the principle of the conservation of mass and the laws of thermodynamics, Hubbert (1940) defined the potential of subsurface water and obtained graphical solutions of regional groundwater flow in a homogeneous and isotropic aquifer with a symmetrical topography between two streams (Fig. 7). Hubbert (1940) found that flowing wells could occur in topographic lows without an overlying confining bed, and pointed out that a confined aquifer outcrops in the highlands and overlain by impermeable strata in the lowlands as shown in Fig. 2a is by no means a necessary condition for flowing wells.



Fig. 7 The flow net of groundwater flow between two rivers obtained by Hubbert (1940) and the head in selected piezometers (Modified from Fetter, 1994).

575

570

Because there was no aquitard in the studies of Versluys (1930) and Hubbert (1940), the pattern of groundwater flow is mainly controlled by topography. Such flowing wells in homogeneous unconfined aquifers driven by topography belong to unconfined-flow flowing wells (Tóth, 1966).

7.2 **<u>Quantitative analysis of Topographicallytopographically</u>-driven groundwater flow systems**

580 advances from the Canadian Prairie Region in the 1960's

In the 1950s and 1960s, the high demand for water on the Canadian Prairies led to institutional programs of ground water exploration and research. The phenomena described by King (1899) and Hubbert (1940), like the mean water table closely follows the topography, and flowing wells occur in topographic lows, were quite common in the Canadian Prairies (Meyboom, 1962, 1966;Tóth, 1962, 1966). Based on the field observations, two similar but slightly different conceptual models of topographically-induced groundwater flow (Fig. 8) were developed by Tóth (1962) and Meyboom (1962). Because the mean water table which closely follows the topography can be considered as *priori* known, Tóth (1962) solved the Laplace equation for a homogeneous unit basin with a known water table that changes linearly from the divide to the valley (Fig. 8a). Based on intuitive thinking founded on field observations, Meyboom (1962) considered the permeability difference between the shallow and deep

22

aquifers and qualitatively obtained the flow pattern (Fig. 8b). They agreed that the combination of the two models "gives a good description of the unconfined region of groundwater flow in the western Canadian Prairies" (Tóth, 2005).

According to Tóth (1962), groundwater discharge could cover the entire lower half of the unit basin, and the whole discharge area has higher hydraulic head than the corresponding elevation of water table, which fulfills Meinzer's (1923) definition of "artesian water". To quantify the occurrence of flowing wells in topographic lows of homogeneous unconfined aquifers, Wang et al. (2015b) examined the zone with flowing wells under different water table undulations and basin width/depth ratios. By fixing the basin depth, increases in water table undulation and decreases in basin length both lead to increased hydraulic gradient between recharge and discharge areas. Based on the distribution of head exceeding surface (termed artesian head in their paper), it was found that the zone with flowing wells is always within the discharge area and the ratio of its size to the whole basin is proportional to the hydraulic gradient (Fig. 9). Therefore, in homogeneous basins, the hydraulic gradient is the main control factor of flowing wells.





605

23



Fig. 9 (a)The geometry of a unit basin with a length of $L_{-, and}$ depth of |D|, and three scenarios of water table undulations (corresponding to different α); (b-j) The distribution of head exceeding surface in the unit basin under three_different water table undulations (corresponding to different α) and basin length/width ratios (L/|D|). (Modified from Wang et al., 2015)

610

When the undulation of the topography is more complex, Tóth (1963) analytically obtained a flow 615 net showing the simultaneous occurrence of several local flow systems, one intermediate flow system and one regional flow system in a homogeneous basin. Note that the Canadian Prairies is semi-arid and the impetus for advancing flow systems thinking came from the need to understand terrain patterns of soil salinity, vegetation patterns and groundwater chemistry for which the spatial variations are flow system based. Several years later, R. Allan Freeze, who was a protégé of Meyboom, combined the ideas 620 of Meyboom and Tóth together in his PhD thesis by numerically simulating steady-state regional groundwater flow in heterogeneous basins with any desired water table configuration (Freeze, 2012). As reported in Freeze and Witherspoon (1967), it was demonstrated that heterogeneity would perturb the distribution of flow systems, but does not affect the basic topographically induced flow pattern induced by topography-from recharge to discharge areas (Fig. 10). It was also found that confined aquifers need 625 not outcrop to produce flowing well conditions (Fig. 10b and 10c). However the computing capabilities at the time limited the permeability contrasts between aquifer and aquitard units to a factor of 100, which is far from what is reality in actual flow systems in the field and these simulations are then to some degree misleading in light of what we now know. In some recent studies, it was found that depth-decaying hydraulic conductivity would lead to weakening of regional flow systems and thus deepening of local 630 flow systems (Jiang et al., 2009; Jiang et al., 2011; Wang et al., 2011; Zlotnik et al., 2011).





As illustrated above, although horizontal flow dominates when the basin width/depth ratio is high and/or hydraulic conductivity is the deep layer is much higher, vertical components of groundwater flow are widespread in either thick unconfined aquifers or aquitards overlying confined aquifers, which is quite different from the flow pattern shown in Fig. 2.1 and 4. The spatial distribution of groundwater age in thick unconfined aquifers is also more complicated than that in a confined aquifer (Jiang et al., 2010;Jiang et al., 2012). Therefore, quantitative analysis of the topographically-driven groundwater flow systems became a paradigm shift of hydrogeology. This paradigm shift has been expressed by others in similar words. Anderson (2008) comments that *"The Tóth model is an important early exploration of the analysis of regional flow systems.*" Bredehoeft (2018) points out that *"Tóth's conceptual model of groundwater flow*" represents the beginning of a new era in hydrogeology and termed the paradigm shift

to be "*the Tóth revolution*".

In his book about flow systems, Tóth (2009) states that since the 1960s, hydrogeology's basic paradigm has shifted from confined flow in aquifers (aquitard-bound flow) to cross-formational flow in drainage basins, i.e., flow paths change from through a confined aquifer to across aquitards and different depths of aquifers in heterogeneous basins. Although cross-formational flow (inter-aquifer leakage) had

already been anticipated by Chamberlin (1885), it was identified in the Dakota artesian basin through aquitards in the 1960s (Swenson, 1968), and was recently identified in the Great Artesian Basin through faults (Pandey et al., 2020;Smerdon and Turnadge, 2015). Moreover, although the concept of flowing wells in the context of aquitard bounding is introduced in almost every groundwater textbook, the concept of unconfined-flow flowing wells in homogeneous basins has been included in few textbooks (Domenico and Schwartz, 1998;Freeze and Cherry, 1979;Heath, 1983;Kasenow, 2010;Lohman, 1972b). Therefore, the acceptance of the new paradigm is a slow process.

7.3 Hydraulics of unconfined-flow flowing wells in unconfined aquifers

The steady-state hydraulics of confined-flow flowing wells had been examined by Glee in the 1930s, but the study of unconfined-flow flowing wells is most recent. Zhang et al. (2018b) simulated the water 660 exchange between the unconfined aquifer and a flowing well in a three-dimensional homogeneous unit basin. As a result of the increasing hydraulic head with depth in the discharge area of the aquifer, hydraulic head in the shallow part is smaller than hydraulic head of the flowing well, and in the deep part is larger than hydraulic head of the flowing well. Therefore, there is groundwater inflow from the aquifer to the flowing well (Q_{in}) in the deep part, and groundwater outflow from the flowing well to the aquifer 665 (Q_{out}) in the shallow part. Because Q_{in} is larger than Q_{out} , <u>cumulative</u> flow rate at the well outlet is above 0 (Fig. 11a), which results in water overflow at the surface. In some extreme cases, for example, if the water table coincide with the ground surface, or the shallow part is cased, Q_{out} equals 0 and <u>cumulative</u> flow rate at the well outlet is determined by Q_{in} (Fig. 11b). Zhang et al. (2018b) found that the simultaneous occurrence of inflow and outflow could also occur in a thick confined aquifer. Therefore, 670 the 3rd-third_condition proposed by both de Thury (1830) and Bond (1865), and the 7th-seventh_condition given by Chamberlin (1885), is not a necessary condition for flowing wells. Moreover, as shown in Fig. 11a, groundwater in the shallow part of the aquifer could not enter the flowing well, indicating that the well outlet is a "window" of the deep groundwater, i.e., groundwater sampled at the well outlet could represent deep groundwater (Zhang et al., 2019). This has been verified in the flowing wells in the Ordos 675 Plateau, China by using hydrochemistry and stable isotopes such as ²H, ¹⁸O, ⁸⁷Sr/⁸⁶Sr and ²⁶Mg (Wang et al., 2015a;Zhang et al., 2018a).



Fig. 11 Conceptual cross-sectional views of flow around flowing wells. (a) a flowing well with $Q_{in} > Q_{out}$; (b) a flowing well with $Q_{in} > Q_{out} = 0$. (Modified from Zhang et al., 2018b)

680

685

700

Based on the plots shown in Fig. 7 through 11, several qualifying conditions of flowing wells proposed in the 19th century have been found to be unnecessary since <u>1930the turn of the 20th century</u>. Although the transient behavior of groundwater flow to flowing wells in <u>leaky</u> confined aquifer has been studied in the 1950s (Hantush, 1959;Jacob and Lohman, 1952), there has been no research on the transient groundwater flow to flowing wells in unconfined aquifers. Moreover, research coupling groundwater recharge from precipitation and groundwater discharge through flowing wells, which is critical to interpret the increased flow rate with time as shown in Fig. 5a and the sustainability of flowing wells, is also missing.

8 Conclusions and suggestions

690 The thread of evolution of nearly all domains of physical hydrogeology <u>can be connects-connected</u> back-to flowing wells. The advent of modern cable-tool drilling equipment in Europe in the early 19th century made flowing wells common in the 19th century. Because flowing wells are spectacular visual evidence of groundwater occurrence, they became the impetus for both qualitative and quantitative groundwater science. The pursuit of answers to fundamental questions generated by flowing wells in confined aquifers bounded by aquitards moved the science forward for more than a century until pumping became the main form of groundwater development. Moreover, since the turn of 20th century, flowing wells in unconfined aquifers were an impetus for the paradigm shift from aquitard-bound flow to cross-formational flow driven by topography.

Given the spectacular flowing wells in Paris and London in the early 19th century, it was not a coincidence that Darcy (1856) did his monumental laboratory experiments soon after he did pipe flow experiments prompted by flowing wells. He was followed by his colleague Dupuit (1863) to develop the

hydraulics of steady flow to wells. The term "flowing well" was introduced by Chamberlain (1885) in
his classic USGS report, which provided the firsta comprehensive explanation of flowing wells using
hydrogeological principles. Based on field investigations of the Cambrian-Ordovician aquifer system in
Wisconsin, he recognized the role of confining beds in creating flowing well conditions and also that
these confining beds are leaky. This was followed soon after by the classic work by Darton (1897, 1905)
who studied the regional Dakota aquifer. Meinzer and Hard (1925) and Meinzer (1928) deduced from
declining discharge of flowing wells and excess of discharge over recharge that confined aquifers are
elastic and have storage capability related to compressibility. This prompted Theis (1935) of the USGS
to initiate transient well hydraulics for non-leaky aquifers, although leakage recognized decades earlier
set the stage for Hantush to pioneer the hydraulics of pumping wells and flowing wells in aquifers with
leaky confining beds in the 1950s (Hantush and Jacob, 1955; Hantush, 1959).

The wide occurrence of regional scale confined aquifers showing ubiquitous flowing wells in sedimentary rocks in France, Britain, the United States and Australia resulted in confined flow in aquifers 715 being a broadly useful conceptualization. However, this resulted in the common misconception that flowing wells must occur in confined aquifers bounded by aquitards, and the confusion of the term "artesian". Versluys (1930) and Hubbert (1940) realized flowing wells can occur in entirely unconfined and homogeneous conditions controlled only by topography, which was supported by Tóth's (1962, 1963, 1966) and Freeze and Witherspoon's (1967) quantitative studies of topographically-driven groundwater 720 flow systems. An introduction to confined-flow and unconfined-flow flowing wells has been given by Tóth (1966) in a journal paper and included in the textbook by Freeze and Cherry (1979), and thewhile quantitative analysis of topographically-driven groundwater flow systems has been considered to be a paradigm shift of modern hydrogeology (Bredehoeft, 2018;Madl-Szonyi, 2008;Tóth, 2005). The misconception that flowing wells must occur in confined aquifers is still impeding the acceptance of the 725 new paradigm, which is reflected by the limited number of textbooks introducing flowing wells in unconfined aquifers.-Generally in the earth Earth sciences it takes decades for the acceptance of the importance of a paradigm shift to achieve completeness when completeness is judged by the paradigm being the primary basis for teaching as manifested in what is included in textbooks. For example, the paradigm shift from steady-state to unsteady-state well hydraulics in confined aquifers that began in the 730 1930s was completed by the late 1950s and transient well hydraulics has been included in almost all groundwater textbooks since then. - and groundwater flow systems theory is no exception.

Although there have been great advances in how we think about groundwater flow systems and the current paradigm is well advanced, it is not yet comprehensive. The misconception that flowing wells must occur in confined aquifers is still impeding the acceptance of the new paradigm, which is reflected 735 by the limited number of textbooks introducing flowing wells in unconfined aquifers. Based on the summary of the role of flowing wells in the evolution of many concepts and principles of groundwater hydrology, it is desirable that integratingacknowledgement of the role of flowing wells as the main root of flowing wells into textbooks of groundwater hydrology would lead to a deeper understanding of the science of groundwater (Deming, 2016), as well as of the current paradigm shift of hydrogeology. 740 Avoidance of the term "artesian" is needed to eradicate confusion in terminology that crept into groundwater science long after the classic work by Darcy, Dupuit and others established the foundation. aA complete description of confined-flow and purely unconfined-flow flowing wells and their connections to evolution of hydrogeology, and quantitative methods for topographically-driven groundwater flow systems are expected in all future groundwater textbooks. Moreover, b However, 745 because purely confined-flow and purely unconfined-flow are two endmembers of groundwater flow, a generalized theoryclearer concepts for on the simultaneous control of aquitards and topography on the occurrence of flowing wells, the pattern of groundwater circulation and hydrogeochemical evolution is expected in future studies are needed.

750 Code/Data availability

Not apply to the review paper.

Author contribution

XJ and JC prepared the manuscript with contributions from LW.

755

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgements

760 This study was supported by the Teaching Reform Funds of China University of Geosciences, the National Natural Science Foundation of China (41772242), the National Program for Support of Top-notch Young Professionals, and the 111 Project (B20010). The authors thank Vitaly Zlotnik of University of Nebraska-Lincoln for discussion on the ambiguous term "artesian", Eileen Poeter of Colorado School of Mines and John Hermance of Brown University for suggestions on improving the manuscript. The authors also thank the handling editor, Okke Batelaan, and two reviewers (Garth van der Kamp and an

authors also thank the handling editor, Okke Batelaan, and two reviewers (Garth van der Kamp and an anonymous one) for suggestions.

References

780

770 Alley, W. M., and Alley, R.: High and Dry: Meeting the Challenges of the World's Growing Dependence on Groundwater, Yale University Press, New Haven, 2017.

Anderson, M. P.: The Wisconsin Roots of Ground Water Hydrology, Groundwater, 43, 142-145, 10.1111/j.1745-6584.2005.tb02294.x, 2005.

Anderson, M. P.: Groundwater, Benchmark Papers in Hydrology, IAHS Press, Oxfordshire, 2008.

- 775 Anonymous: The Social Economist, NO. 1-Bored springs or artificial fountains obtained by boring the earth, Monthly Magazine and British Register, 54, 32-35, 1822.
 - Anonymous: The Artesian Well at Grenelle, in France, in: California Farmer and Journal of Useful Sciences, 21, 1855.
 - Arago, M.: On springs, artesian wells, and sprouting fountains, The Edinburgh New Philosophical Journal, 18, 205-246, 1835.
 - Back, W., and Herman, J. S.: American Hydrogeology at the Millennium: An Annotated Chronology of 100 Most Influential Papers, Hydrogeology Journal, 5, 37-50, 10.1007/s100400050255, 1997.
 - Batu, V.: Aquifer Hydraulics: A Comprehensive Guide to Hydrogeologic Data Analysis, John Wiley & Sons, Inc., New York, NY, 1998.
- 785 Beaumont, P.: A Traditional Method of Ground-Water Utilisation in the Middle East, Groundwater, 11, 23-30, 10.1111/j.1745-6584.1973.tb02984.x, 1973.
 - Bethke, C. M., and Johnson, T. M.: Groundwater Age and Groundwater Age Dating, Annual Review of Earth and Planetary Sciences, 36, 121-152, 10.1146/annurev.earth.36.031207.124210, 2008.

Biswas, A. K.: The History of Hydrology, North - Holland Publishing Company, Amsterdam, 1970.

Bond, F. T.: The geology of mineral springs, Popular Science Reviews, 4, 203-213, 1865.
Brassington, R.: Field Hydrogeology, 3rd ed., John Wiley & Sons Ltd, Hoboken, NJ, 2017.
Bredehoeft, J. D., Neuzil, C. E., and Milly, P. C.: Regional flow in the Dakota aquifer; a study of the role of confining layers, USGS, Report 2237, 1983.

Bredehoeft, J. D.: The Toth Revolution, Groundwater, 56, 157-159, 10.1111/gwat.12592, 2018.

795 Brown, G. O.: Henry Darcy and the making of a law, Water Resources Research, 38, 11-11-11-12, 10.1029/2001wr000727, 2002.

Buckland, W.: Geology & Mineralogy, Considered with Reference to Natural Theology, Routledge,

London:, 1836.

800

810

- Carpenter, L. G.: Artesian Wells of Colorado and Their Relation to Irrigation, The State Agricultural College, Fort Collins, CO, 1891.
 - Carslaw, H. S.: Introduction to the Mathematical Theory of the Conduction of Heat in Solids, Macmillan London, 1921.
 - Chamberlin, T. C.: The requisite and qualifying conditions of artesian wells, in: Fifth Annual report of the United States Geological Survey to the Secretary of the Interior, 1883-1884, edited by: Powell,
- J. W., Washington Government Printing Office, Washington D.C., 125-173, 1885.
 - Chang, C.-C., and Chen, C.-S.: An integral transform approach for a mixed boundary problem involving a flowing partially penetrating well with infinitesimal well skin, Water Resources Research, 38, 1071, 10.1029/2001wr001091, 2002.

Commander, D. P.: Artesian Water, in: Water Encyclopedia, edited by: Lehr, J. H., and Keeley, J., 1-5, 2005.

- Darton, N. H.: Preliminary Report on Artesian Waters of a Portion of the Dakotas, in: Seventeenth Annual Report of the United States Geological Survey, Government Printing Office, Washington, 609-694, 1897.
- Darton, N. H.: Preliminary report on the geology and underground water resources of the central Great
- 815 Plains, Report 32, 1905.
 - Darwin, E.: An account of an artificial spring of water, Philosophical Transactions of the Royal Society of London, 75, 1-7, <u>http://www.jstor.com/stable/106744</u>, 1785.

Davie, T.: Fundamentals of Hydrology, 2nd ed., Routledge, Oxon, 2008.

Davis, S. N., and De Wiest, R. J. M.: Hydrogeology, John Wiley and Sons, New York, 1966.

- 820 de Marsily, G.: Quantitative Hydrogeology, Academic Press, 1986.
 - de Thury, H.: Observations on the cause of the spouting of overflowing wells or artesian fountains, Edinburgh New Philosophical Journal, 9, 157-165, 1830.
 - de Vries, J. J.: History of Groundwater Hydrology, in: The Handbook of Groundwater Engineering, Second ed., edited by: Delleur, J. W., CRC Press, Boca Raton, 2007.
- Deming, D.: Introduction to Hydrogeology, The McGraw-Hill Companies, Inc., New York, NY, 2002.
 Deming, D.: The Importance of History, Groundwater, 54, 745-745, 10.1111/gwat.12458, 2016.
 Domenico, P. A., and Schwartz, F. W.: Physical and Chemical Hydrogeology, 2nd ed., John Wdey &

Sons, Inc., New York, NY, 1998.

840

Driscoll, F. G.: Groundwater and Wells, second ed., Johnson Division, St. Paul, Minnesota, 1986.

B30 Duffy, C. J.: The terrestrial hydrologic cycle: an historical sense of balance, WIREs Water, 4, e1216, 10.1002/wat2.1216, 2017.

Farey, J.: On artesian wells and boreholes, Monthly Magazine and British Register, 56, 309, 1823.Farvolden, R. N.: Groundwater resources Pembina area, Alberta, Research Council of Alberta, 1961.Feng, Q., and Zhan, H.: Constant-head test at a partially penetrating well in an aquifer-aquitard system,

- B35 Journal of Hydrology, 569, 495-505, 10.1016/j.jhydrol.2018.12.018, 2019.Fetter, C. W.: Applied Hydrogeology, 4th ed., Pearson Education, Inc., 2001.
 - Fetter, C. W.: Hydrogeology: A Short History, Part 2, Groundwater, 42, 949-953, 10.1111/j.1745-6584.2004.t01-14-.x, 2004.
 - Fiedler, A. G., and Nye, S. S.: Geology and Ground-Water Resources of the Roswell Artesian Basin, New Mexico, Report 639, 1933.

Fitts, C. R.: Groundwater Science, 2nd ed., Academic Press, Waltham, MA, 2013.

- Freeze, R. A., and Witherspoon, P. A.: Theoretical analysis of regional groundwater flow: 2. Effect of water-table configuration and subsurface permeability variation, Water Resources Research, 3, 623-634, 10.1029/WR003i002p00623, 1967.
- Freeze, R. A., and Cherry, J. A.: Groundwater, Prentice-Hall. Inc., Englewood Cliffs, N.J., 1979.
 Freeze, R. A., and Back, W.: Benchmark Papers in Geology: Physical Hydrogeology, Hutchinson Ross
 Publishing Company, New York, NY, 1983.
 - Freeze, R. A.: Vignettes of a Life in Hydrogeology, Groundwater, 50, 485-490, 10.1111/j.1745-6584.2012.00921.x, 2012.
- Fuller, M. L.: Significance of the term "artesian", in: Underground-Water Papers 1906, edited by: Fuller,
 M. L., Government Printing Office, Washington, 9-15, 1906.
 - Gaber, M. S.: Michigan Flowing Well Handbook, Michigan Department of Environmental Quality Water Bureau, 2005.

Garnier, F.: De L'Art du Fontenier Sondeur et des Puits Artésiens, Paris, 1822.

Hölting, B., and Coldewey, W. G.: Hydrogeology, Springer-Verlag GmbH Germany, Berlin, 2019.
Habermehl, M. A.: Review: The evolving understanding of the Great Artesian Basin (Australia), from discovery to current hydrogeological interpretations, Hydrogeology Journal, 28, 13-36,

10.1007/s10040-019-02036-6, 2020.

860

885

- Haitjema, H. M., and Mitchell-Bruker, S.: Are Water Tables a Subdued Replica of the Topography?, Groundwater, 43, 781-786, 10.1111/j.1745-6584.2005.00090.x, 2005.
- Hantush, M. S.: Nonsteady flow to flowing wells in leaky aquifers, Journal of Geophysical Research (1896-1977), 64, 1043-1052, 10.1029/JZ064i008p01043, 1959.

Heath, R. C.: Basic Ground-Water Hydrology, USGS, Reston, Virginia, 1983.

Hendriks, M.: Introduction to Physical Hydrology, Oxford University Press, New York, 2010.

- Hinkle, S. R., Shapiro, S. D., Plummer, L. N., Busenberg, E., Widman, P. K., Casile, G. C., and Wayland,
 J. E.: Estimates of tracer-based piston-flow ages of groundwater from selected sites—National
 Water-Quality Assessment Program, 1992–2005, U.S. Geological Survey 90, 2010.
 - Hiscock, K. M., and Bense, V. F.: Hydrogeology: Principles and Practice, 2nd ed., John Wiley & Sons, Ltd., Oxford, 2014.
- Hornberger, G. M., Wiberg, P. L., Raffensperger, J. P., and D'Odorico, P.: Elements of Physical Hydrology,
 2nd ed., Johns Hopkins University Press, Baltimore, MA, 2014.
 - Hou, G. C., Liang, Y. P., Su, X. S., Zhao, Z. H., Tao, Z. P., Yin, L. H., Yang, Y. C., and Wang, X. Y.: Groundwater Systems and Resources in the Ordos Basin, China, Acta Geologica Sinica - English Edition, 82, 1061-1069, 10.1111/j.1755-6724.2008.tb00664.x, 2008.
- Howden, N., and Mather, J.: History of Hydrogeology, Taylor & Francis Group, LLC, Boca Raton, FL, 2013.
 - Hubbert, M. K.: The Theory of Ground-Water Motion, The Journal of Geology, 48, 785-944, 10.1086/624930, 1940.
 - Jacob, C. E.: On the flow of water in an elastic artesian aquifer, Eos, Transactions American Geophysical

```
880 Union, 21, 574-586, 10.1029/TR021i002p00574, 1940.
```

- Jacob, C. E., and Lohman, S. W.: Nonsteady flow to a well of constant drawdown in an extensive aquifer, Eos, Transactions American Geophysical Union, 33, 559-569, 10.1029/TR033i004p00559, 1952.
- Jiang, X.-W., Wan, L., Ge, S., Cao, G.-L., Hou, G.-C., Hu, F.-S., Wang, X.-S., Li, H., and Liang, S.-H.: A quantitative study on accumulation of age mass around stagnation points in nested flow systems, Water Resources Research, 48, 10.1029/2012wr012509, 2012.
- Jiang, X. W., Wan, L., Wang, X. S., Ge, S. M., and Liu, J.: Effect of exponential decay in hydraulic conductivity with depth on regional groundwater flow, Geophysical Research Letters, 36, L24402,

10.1029/2009GL041251, 2009.

- Jiang, X. W., Wan, L., Cardenas, M. B., Ge, S., and Wang, X. S.: Simultaneous rejuvenation and aging
 of groundwater in basins due to depth-decaying hydraulic conductivity and porosity, Geophysical
 Research Letters, 37, 10.1029/2010gl042387, 2010.
 - Jiang, X. W., Wang, X. S., Wan, L., and Ge, S.: An analytical study on stagnant points in nested flow systems in basins with depth-decaying hydraulic conductivity, Water Resources Research, 47, W01512, 10.1029/2010WR009346, 2011.
- Jiang, X. W., Wan, L., Wang, X. S., Wang, D., Wang, H., Wang, J. Z., Zhang, H., Zhang, Z. Y., and Zhao,
 K. Y.: A multi-method study of regional groundwater circulation in the Ordos Plateau, NW China,
 Hydrogeology Journal, 26, 1657-1668, 10.1007/s10040-018-1731-4, 2018.
 - Jones, J. F.: Reconnaissance groundwater study Swan Hills and adjacent areas, Alberta, Research Council of Alberta, 1962.
- 900 Jones, L.: A Comparison of Pumping and Slug Tests for Estimating the Hydraulic Conductivity of Unweathered Wisconsian Age Till in Iowa, Groundwater, 31, 896-904, 10.1111/j.1745-6584.1993.tb00862.x, 1993.
 - Kasenow, M.: Applied Ground-Water Hydrology and Well Hydraulics, 3rd ed., Water Resources Publications, LLC, Highlands Ranch, Colorado, 2010.
- 905 King, F. H.: Principles and conditions of the movements of groundwaters, in: Nineteenth Annual Report of the United States Geological Survey, Part 2, USGS, 59–295, 1899.
 - Konikow, L. F.: Groundwater depletion in the United States (1900-2008), USGS, Reston, VirginiaU.S. Geological Survey Scientific Investigations Report 2013–5079, 2013.
 - Kruseman, G. P., and de Ridder, N. A.: Analysis and Evaluation of Pumping Test Data, second ed.,
- 910 International Institute for Land Reclamation and Improvement, Wageningen, The Netherland, 1990.
 - LaMoreaux, P. E., Soliman, M. M., Memon, B. A., LaMoreaux, J. W., and Assaad, F. A.: Environmental Hydrogeology, 2nd ed., Taylor and Francis Group, LLC, Boca Raton, FL, 2009.
 - Leonard, R. B., Signor, D. C., Jorgensen, D. G., and Helgesen, J. O.: Geohydrology and hydrochemistry of the Dakota aquifer, central United States, JAWRA Journal of the American Water Resources Association, 19, 903-912, 10.1111/j.1752-1688.1983.tb05939.x, 1983.

915

Lionnais: Historie de 1a ville de Naney, Description de 1a fontaine artesienne de Jarville, Nancy, 1805. Lohman, S. W.: Geology and ground-water resources of the Elizabeth City area, North Carolina, Report 773A, 1936.

920

Lohman, S. W.: Definitions of Selected Ground-Water Terms - Revisions and Conceptual Refinements, USGS, Washington, 1972a.

Lohman, S. W.: Ground-Water Hydraulics, Report Geological Survey Professional Paper 708, 1972b.

Macintosh, A.: The Repertory of Patent Inventions, and Other Discoveries and Improvements in Arts, Manufactures, and Agriculture, London, 1827.

Madl-Szonyi, J.: From the Artesian Paradigm to Basin Hydraulics: The Contribution of Jozsef Toth to

- 925 Hungarian Hydrogeology, Publishing Company of Budapest University of Technology and Economics, Budapest, 2008.
 - Margat, J., Pennequin, D., and Roux, J.-C.: History of French hydrogeology, in: History of Hydrogeology, edited by: Howden, N., and Mather, J., Taylor & Francis Group, LLC, Boca Raton, FL, 2013.
 Mays, L. W.: Ground and Surface Water Hydrology, John Wiley & Sons, Inc., Hoboken, NJ, 2012.
- 930 McWhorter, D. B., and Sunada, D. K.: Ground-Water Hydrology and Hydraulics, Water Resources Publications, LLC, Highlands Ranch, Colorado, USA, 1977.
 - Meinzer, O. E.: The occurrence of ground water in the United States, with a discussion of principles, Washington, DC, Report 489, 373, 1923a.

Meinzer, O. E.: Outline of ground-water hydrology, with definitions, Report 494, 1923b.

- 935 Meinzer, O. E., and Hard, H. A.: The artesian water supply of the Dakota sandstone in North Dakota, with special reference to the Edgeley quadrangle: Chapter E in Contributions to the hydrology of the United States, 1923-1924, Washington, D.C., Report 520E, 73-95, 1925.
 - Meinzer, O. E.: Compressibility and elasticity of artesian aquifers, Economic Geology, 23, 263–291, https://doi.org/10.2113/gsecongeo.23.3.263, 1928.
- Merdinger, C. J.: Water Supply through the Ages: Part I. Early History, The Military Engineer, 47, 280-285, 1955.
 - Meyboom, P.: Patterns of groundwater flow in the Prairie Profile, Proceedings of Third Canadian Hydrology Symposium, 1962, 5-21, 1962.
 - Meyboom, P.: Groundwater Studies in the Assiniboine River drainage basin: Part 1 The evaluation of a
- flow system in south-central Saskatchewan, Geologic Survey of Canada, Bulletin 139, 1-65, 1966.
 Meyer, G., Davis, G., and LaMoreaux, P. E.: Historical perspective, in: Hydrogeology, edited by: Back,
 W., Rosenshein, J. S., and Seaber, P. R., The Geology of North America Vol. 0-2, The Geological

Society of America, Boulder, Colorado, 1988.

950

Mishra, S., and Guyonnet, D.: Analysis of Observation-Well Response During Constant-Head Testing,

Nonner, J. C.: Introduction to Hydrogeology, 2nd ed., A.A. BALKEMA PUBLISHERS, LISSE, 2003. Norton, W. H.: Artesian Wells of Iowa, Iowa Geological Survey Annual Report, 6, 113-428, 10.17077/2160-5270.1330, 1897.

Groundwater, 30, 523-528, 10.1111/j.1745-6584.1992.tb01528.x, 1992.

- Ordens, C. M., McIntyre, N., Underschultz, J. R., Ransley, T., Moore, C., and Mallants, D.: Preface:
 Advances in hydrogeologic understanding of Australia's Great Artesian Basin, Hydrogeology Journal, 28, 1-11, 10.1007/s10040-019-02107-8, 2020.
 - Pandey, S., Singh, D., Denner, S., Cox, R., Herbert, S. J., Dickinson, C., Gallagher, M., Foster, L., Cairns,B., and Gossmann, S.: Inter-aquifer connectivity between Australia's Great Artesian Basin and the overlying Condamine Alluvium: an assessment and its implications for the basin's groundwater
- 960 management, Hydrogeology Journal, 28, 125-146, 10.1007/s10040-019-02089-7, 2020.

Pennink, J. M. K.: Over de beweging van grondwater, De Ingenieur, 20, 482-492, 1905.

Pinder, G. F., and Celia, M. A.: Subsurface hydrology, John Wiley & Sons, Inc., Hoboken, NJ, 2006.

- Poiseuille, J. L.: Recherches expérimentales sur le mouvement des liquides dans les tubes de tre`s-petits diame`tres, comptes rendus, Académie des Sciences, Paris, 1841.
- 965 Price, M.: Introducing Groundwater, Chapman & Hall, London, 1996.
 - Ritzi, R. W., and Bobeck, P.: Comprehensive principles of quantitative hydrogeology established by Darcy (1856) and Dupuit (1857), Water Resources Research, 44, 10.1029/2008wr007002, 2008.
 - Rushton, K. R.: Groundwater Hydrology: Conceptual and Computational Models, John Wiley & Sons Ltd, London, 2003.
- 970 Schwartz, F. W., and Zhang, H.: Fundamentals of Ground Water, John Wiley & Sons, New York, NY, 2003.
 - Slichter, C. S.: Theoretical investigation of the motion of ground waters, in: 19th Annual Report of the United Stated Geological Survey, Government Printing Office, Washington, 1899.
- Smerdon, B. D., and Turnadge, C.: Considering the potential effect of faulting on regional-scale
 groundwater flow: an illustrative example from Australia's Great Artesian Basin, Hydrogeology
 Journal, 23, 949-960, 10.1007/s10040-015-1248-z, 2015.
 - Smith, L. P.: Heat Flow in an Infinite Solid Bounded Internally by a Cylinder, Journal of Applied Physics,

8, 441-448, 10.1063/1.1710319, 1937.

980

- Storrow, C. S.: A Treatise on Water-Works for Conveying and Distribution Supplies of Water, Hilliard Gray, Boston, Mass., 1835.
- Swenson, F. A.: New theory of recharge to the artesian basin of the Dakotas, GSA Bulletin, 79, 163–182, https://doi.org/10.1130/0016-7606(1968)79[163:NTORTT]2.0.CO;2, 1968.
- Tóth, J.: A theory of groundwater motion in small drainage basins in central Alberta, Canada, Journal of Geophysical Research (1896-1977), 67, 4375-4388, 10.1029/JZ067i011p04375, 1962.
- 985 Tóth, J.: A theoretical analysis of groundwater flow in small drainage basins, Journal of Geophysical Research (1896-1977), 68, 4795-4812, 10.1029/JZ068i016p04795, 1963.
 - Tóth, J.: Mapping and interpretation of field phenomena for groundwater reconnaissance in a prairie environment, Alberta, Canada, International Association of Scientific Hydrology Bulletin, 11, 20-68, 10.1080/026266666609493458, 1966.
- 990 Tóth, J.: The Canadian School of Hydrogeology: History and Legacy, Groundwater, 43, 640-644, 10.1111/j.1745-6584.2005.0086.x, 2005.
 - Tóth, J.: Gravitational Systems of Groundwater Flow: Theory, Evaluation, Utilization Cambridge University Press, New York, 2009.

Tavenas, F., Diene, M., and Leroueil, S.: Analysis of the in situ constant-head permeability test in clays,

995 Canadian Geotechnical Journal, 27, 305-314, 1990.

- Theis, C. V.: The relation between the lowering of the Piezometric surface and the rate and duration of discharge of a well using ground-water storage, Eos, Transactions American Geophysical Union, 16, 519-524, 10.1029/TR016i002p00519, 1935.
- Thiem, G.: Hydrologische methoden, Gebhardt, Leipzig, 1906.
 Todd, D. K., and Mays, L. W.: Groundwater Hydrology, 3rd ed., John Wiley & Sons, 2004.
 Tsai, C.-S., and Yeh, H.-D.: Wellbore flow-rate solution for a constant-head test in two-zone finite
 - confined aquifers, Hydrological Processes, 26, 3216-3224, 10.1002/hyp.8322, 2012.
 - van der Gun, J.: The Global Groundwater Revolution, in: the Oxford Research Encyclopedia, 1-30, 2019.
- 1005 Versluys, J.: The origin of artesian pressure, Proceedings Royal Academy of Sciences in Amsterdam, 33, 214-222, https://www.dwc.knaw.nl/DL/publications/PU00015879.pdf, 1930.

Vogel, H. U.: The great well of China, Scientific American, 116-121, 1993.

Theis, C. V.: Ground water in Curry and Roosevelt Counties, N. Mex., 99-160, 1932.

Wang, H., Jiang, X. W., Wan, L., Han, G., and Guo, H.: Hydrogeochemical characterization of groundwater flow systems in the discharge area of a river basin, Journal of Hydrology, 527, 433-441, https://doi.org/10.1016/j.jhydrol.2015.04.063, 2015a.

Wang, J. Z., Jiang, X. W., Wan, L., Wörman, A., Wang, H., Wang, X. S., and Li, H.: An analytical study on artesian flow conditions in unconfined-aquifer drainage basins, Water Resources Research, 51, 8658-8667, 10.1002/2015wr017104, 2015b.

1010

1030

- Wang, X. S., Jiang, X. W., Wan, L., Ge, S., and Li, H. L.: A new analytical solution of topography-driven
- 1015 flow in a drainage basin with depth-dependent anisotropy of permeability, Water Resources Research, 47, W09603, 10.1029/2011WR010507, 2011.
 - Wen, Z., Zhan, H., Huang, G., and Jin, M.: Constant-head test in a leaky aquifer with a finite-thickness skin, Journal of Hydrology, 399, 326-334, https://doi.org/10.1016/j.jhydrol.2011.01.010, 2011.
 - Wenzel, L. K.: The thiem method for determining permeability of water-bearing materials and its
- application to the determination of specific yield; results of investigations in the Platte river valley, Nebraska, Report 679A, 1936.
 - White, R. R., and Clebsch, A.: C.V. Theis, The Man and His Contributions to Hydrogeology, in: Selected Contributions to Ground-Water Hydrology by C.V. Theis, and a Review of His Life and Work, edited by: Clebsch, A., U.S. Geological Survey 1993.
- Wilkinson, W. B.: Constant Head in Situ Permeability Tests in Clay Strata, Géotechnique, 18, 172-194, 10.1680/geot.1968.18.2.172, 1968.
 - Williamson, W. H.: The history of hydrogeology in Australia, in: History of Hydrogeology, edited by: Howden, N., and Mather, J., Taylor & Francis Group, LLC, Boca Raton, FL, 2013.
 - Yeh, J. T. C., Khaleel, R., and Carroll, K. C.: Flow Through Heterogeneous Geologic Media, Cambridge University Press, New York, NY, 2015.
 - Young, H. L.: Summary of ground-water hydrology of the Cambrian-Ordovician aquifer system in the northern Midwest, United States: A in Regional aquifer system analysis, Report 1405A, 67, 1992.
 - Younger, P. L.: Groundwater in the Environment, Blackwell Publishing Ltd, Malden, MA, 2007.
- Zhang, H., Jiang, X. W., Wan, L., Ke, S., Liu, S. A., Han, G., Guo, H., and Dong, A.: Fractionation of
 Mg isotopes by clay formation and calcite precipitation in groundwater with long residence times
 in a sandstone aquifer, Ordos Basin, China, Geochimica et Cosmochimica Acta, 237, 261-274,
 https://doi.org/10.1016/j.gca.2018.06.023, 2018a.

Zhang, Z.-Y., Jiang, X.-W., Wang, X.-S., Wan, L., and Wang, J.-Z.: Why mixed groundwater at the outlet of open flowing wells in unconfined-aquifer basins can represent deep groundwater: implications for sampling in long-screen wells, Hydrogeology Journal, 27, 409-421, 10.1007/s10040-018-1842y, 2019.

1040

- Zhang, Z. Y., Jiang, X. W., Wang, X. S., Wan, L., and Wang, J. Z.: A numerical study on the occurrence of flowing wells in the discharge area of basins due to the upward hydraulic gradient induced wellbore flow, Hydrological Processes, 32, 1682-1694, 10.1002/hyp.11623, 2018b.
- 1045 Zlotnik, V. A., Cardenas, M. B., and Toundykov, D.: Effects of multiscale anisotropy on basin and hyporheic groundwater flow, Ground Water, 49, 576-583, 10.1111/j.1745-6584.2010.00775.x, 2011.