

A novel method for cold region streamflow hydrograph separation using GRACE satellite observations

Shusen Wang¹, Junhua Li¹, and Hazen A. J. Russell²

¹Canada Centre for Remote Sensing, Natural Resources Canada, Ottawa, K1A 0E4, Canada

5 ²Geological Survey of Canada, Natural Resources Canada, Ottawa, K1A 0E8, Canada

Correspondence to: Shusen Wang (Shusen.Wang@Canada.ca)

Abstract. Streamflow hydrograph analysis has long been used for separating streamflow into baseflow and surface-runoff components, providing critical information for studies in hydrology, climate and water resources. Defects known with established methods include the lack of physics and arbitrary choice of separation parameters, problems in identifying snowmelt runoff, and limitations on watershed size and hydrogeological conditions. In this study, a GRACE-based model was developed to address these weaknesses and improve hydrograph separation. The model is physically based and requires no arbitrary choice of parameters. The new model was compared with six hydrograph separation methods provided with the U.S. Geological Survey Groundwater Toolbox. The results demonstrated improved estimates by the new model particularly in filtering out the bias of snowmelt runoff in baseflow estimate. This new model is specifically suitable for applications over large watersheds which is complementary to the traditional methods that are limited by watershed size. The output from the model also includes estimates for watershed hydraulic conductivity and drainable water storage, which are useful parameters in evaluating aquifer properties, calibrating and validating hydrological and climate models, and assessing regional water resources.

1 Introduction

20 A streamflow hydrograph is the time-series record of streamflow at a gauging site. Streamflow includes baseflow (the longer-term delayed flow from natural water storage such as groundwater discharge from aquifers) and quick flow (or surface runoff, the short-term response to a rainfall event or snow melt). Separating streamflow observed at a gauging site into baseflow and surface runoff helps characterise watershed hydrogeology and understand the water dynamics such as rainfall-runoff relationships and climate change impact on groundwater discharge (van Dijk, 2010; Gao et al., 2015; Rudra et al., 2015; Foks et al., 2019). Information on baseflow and surface runoff is also critical when dealing with a wide range of water-related issues such as flow regulations, water quality, habitat, reservoir design and operation, and hydroelectric power generation (Boulton and Hancock, 2006; Santhi et al., 2008; U.S. Bureau of Reclamation, 2012; Miller et al., 2016; Nuhfer et al., 2017). Streamflow hydrograph analysis has long been used for separating streamflow into baseflow and surface runoff components and can be traced back to Boussinesq (1904) and Maillet (1905). A wide variety of approaches have evolved since then and

Deleted: does not

Deleted: a priori parametrisation

Deleted: shallow unconfined

Formatted: English (Canada)

several reviews have described this development including Hall (1968), Nathan and McMahon (1990), Tallaksen (1995), Smakhtin (2001), and Rudra et al. (2015). The approaches started with manual separation of the streamflow hydrograph into surface runoff and baseflow. Two commonly used manual methods include base-flow-recession methods, mostly by constructing a master recession curve to represent a watershed's typical recession behaviour (Rorabaugh, 1963; Stewart, 2015), and curve-fitting methods, mostly by identifying specific points in the hydrograph and connecting them via some predefined rule to account for the shape of the curve between these points (Natermann, 1951; Linsley et al., 1982; Chapman, 1999). Manual approaches are time consuming and inexact and results can be difficult to replicate among investigators. Attempts to automate manual methods with computers allowed fast and convenient baseflow estimation for multiple watersheds with various spatiotemporal scales, and removed some of the subjectivity inherent in the manual approaches (Arnold et al., 1995; Sloto and Crouse, 1996). However, these approaches basically rely on determining the points where baseflow intersects the rising and falling limbs of the surface runoff response, which are essentially arbitrary (Szilagyi and Parlange, 1998). Various digital filtering techniques with large variations in complexities have also been used for hydrograph separation, but they still suffer from the lack of hydrological basis and the disadvantage of arbitrary choice of separation parameters (Chapman, 1999; Furey and Gupta 2001; Eckhardt 2005; Piggott et al., 2005; Foks et al., 2019; Shao et al., 2020). The results from these approaches often need to be carefully assessed before they are considered to be hydrologically valid. In particular, most of the existing algorithms are developed and tested for rainfall-dominated watersheds, and few studies have examined their suitability for snowmelt-dominated systems. Applying algorithms and parameters obtained from rainfall-dominated systems to snowmelt-dominated systems could cause large uncertainties (Voutchkova et al., 2019). Indeed, incorrectly identifying snowmelt runoff as groundwater discharge has long been hypothesized but, to the best of our knowledge, no studies have quantified this bias. Another limitation for the existing approaches is that most of them are limited to watersheds size of no more than 1,000-2,000 km² (Rutledge, 1998). Despite these limitations, traditional hydrograph separation approaches are still widely used because of the modest data requirements and ease of implementation. Recent improvements in hydrograph separation includes new parameterisation strategies (Pelletier and Andréassian, 2020) and recognition of multiple baseflow components in the streamflow (Curtis et al., 2020; Stoelzle et al., 2020). Nevertheless, since traditional hydrograph separation methods are based on a number of simplifications and assumptions that limit their applicability, previous studies have widely recognised that more effort is required to evaluate the limitations and their effects, and when possible, the methods should be combined with other methods and data to address these limitations (Hooper and Shoemaker, 1986; Stewart et al., 2007; Rosenberry and LaBaugh, 2008; Miller et al., 2014;).

The subsurface drainable water storage (DWS) is a major driver of baseflow for most watersheds with certain hydrogeological settings. Due to the subsurface heterogeneity in soils and aquifers, subsurface water storage over a large spatial domain is difficult to determine using traditional observation methods such as in situ soil moisture sensors and groundwater wells. This poses a major challenge for studying the water storage-baseflow relationships. The development of the Gravity Recovery and Climate Experiment (GRACE) satellites, which were launched in 2002, has provided opportunity to overcome this challenge. GRACE provides monthly changes in total water storage (TWS) derived from time-variable gravity observations (Tapley et

Deleted: and

Deleted: . Results derived from manual approaches

Formatted: Superscript

Deleted: F

Deleted: a

Deleted: .

Deleted: baseflow is primarily driven by the subsurface drainable water storage.

al., 2004). As the first technique for large-scale TWS measurement, GRACE observations have enabled a wide range of novel
75 research advancing knowledge for water science and water resources. In the area of river flow hydrology, the innovations
include applying GRACE data for quantifying watershed-level **DWS** (Wang and Russell, 2016; Tourian et al., 2018; Macedo
et al., 2019; Riegger, 2020), estimating snow mass and snowmelt runoff (Wang et al., 2017), characterizing storage-streamflow
relationship and climate change impacts (Riegger and Tourian, 2014; Sproles et al., 2015; Wang, 2019), and assessing flood
80 potential (Reager et al., 2014). In particular, Macedo et al. (2019) used empirical approach and GRACE TWS to estimate non-
winter season baseflows at 12 gauge locations distributed throughout the Mississippi River basin in US. In contrast, Wang
(2019) and Wang et al. (2017) used winter season data to develop GRACE-based baseflow models for cold region watersheds
in Canada. Wang (2019) also revealed the dynamic change of watershed hydraulic conductivity with freezing temperature in
winter and expanded the foundation for modelling year-round baseflow using GRACE observations.

Deleted: drainable water storage

The objective of this paper is to present a novel method for streamflow hydrograph separation using GRACE satellite
85 observations. The method improves hydrograph separation through addressing the **forementioned** weaknesses of traditional
methods, **such as the lack of physics and arbitrary choice of separation parameters, problems in identifying snowmelt runoff,
and limitations on watershed size**. The model is demonstrated using the streamflow hydrograph measured at the gauge station
for the cold region Albany River watershed located in Canada. The results of our approach are compared with those obtained
from six widely accepted methods for streamflow hydrograph analysis provided by the U.S. Geological Survey (USGS)
90 Groundwater Toolbox (Barlow et al., 2015). The output from this study also includes watershed hydraulic conductivity and
drainable water storage. These parameters are useful in the evaluation of aquifer properties, for input to hydrological and
climate models, and for assessment of water resources. The rest of this paper is organized as follows: Section 2 describes the
method. Section 3 **identifies** the study region and datasets. The results are provided in Section 4 and discussed in Section 5,
followed by conclusion remarks in Section 6. A brief description of the six USGS hydrograph separation methods and more
95 details on the datasets used in this study are provided in the supplementary materials for this paper.

Deleted: gives

2 Method

Our GRACE-based hydrograph separation method is based on two assumptions. First, the total water storage change of a
watershed (S_{tot}) is contributed by the changes of (1) surface water (S_s) which contributes to surface runoff, (2) subsurface water
(S_g) which has a delayed discharge and contributes to baseflow and, (3) non-dischargeable water (S_n) which makes no
100 contributions either to surface runoff or baseflow. Second, the total streamflow observed at a gauge station (Q_{obs}) is composed
of surface runoff (Q_r) and baseflow (Q_b). With the assumptions, we have:

$$S_{tot}(t) = S_s(t) + S_g(t) + S_n(t) \quad (1)$$

$$Q_{obs}(t) = Q_r(t) + Q_b(t) \quad (2)$$

In this study, all the units are in mm (depth of water) for water amount variables (S_{tot} , S_s , S_g , S_n), and mm/day for water flow variables (Q_{obs} , Q_r , Q_b), unless specified otherwise. At long-time scales such as monthly (t), we ignore the possible desynchrony between storage change and the observed flow which could be due to the water travel time from the site of flow generation to the gauging station. The surface water is treated as being composed of two parts: (1) the part in excess of the surface water retention capacity (i.e., S_s), of which the change represents the amount of surface runoff Q_s ; and (2) the part under the surface water retention capacity, which temporarily stay on the soil surface and infiltrate into the soil in a later date and finally contributes to baseflow. This part of water is therefore integrated into S_g . For the water that is non-dischargeable and non-infiltratable such as snow, it is represented by the S_n .

The S_g is connected with Q_b by the following baseflow model developed in Wang (2019) for Albany River watershed:

$$Q_b(t) = k(T)(S_g(t) - a), \quad (3)$$

$$\text{where} \quad k(T) = k_0 \frac{T_c}{T_{acc}(t) + T_c}, \quad (T_{acc} \leq 0). \quad (3a)$$

The a (mm) in Equation (3) is a parameter representing the threshold value of water storage below which the watershed discharge (or baseflow) would be zero, or above which the water storage is defined as DWS_g , which can be regarded as the water in a basin that is connected to streamflow and, with no additional precipitation input, would drain out of the basin as time advances towards infinity (Macedo et al., 2019). This parameter was first introduced to baseflow modelling in Wang et al. (2017). It is necessary to include in constructing the storage-baseflow relationship when using GRACE observations since the GRACE TWS represents the anomaly rather than absolute amount of water storage in a watershed.

The k (day^{-1}) is a rate constant, measuring the watershed lump hydraulic conductivity for subsurface water to discharge. The k is commonly regarded as a static parameter being determined by watershed hydrogeological characteristics, such as geomorphology, soil properties, and aquifer settings. For cold region watersheds, Wang (2019) recently found that the k is quite dynamic in the winter season and it can be significantly reduced with freezing conditions. In this study, the k is estimated using Equation (3a) as proposed in Wang (2019), where T_{acc} ($^{\circ}\text{C day}$) is the accumulated daily air temperature (T) from the start of winter and it is reset to 0 when the winter season is over. The starting and ending dates for a winter season are estimated using several criteria based on temperature and they are detailed in Wang (2019). The T_{acc} represents the accumulated coldness at a specific time in winter and it is used as a proxy for freezing conditions. It has the advantage of being simple and easy to obtain. The k_0 in Equation (3a) is the base value of k , or the k when soil frost is not present. The T_c ($^{\circ}\text{C day}$) is a parameter and when T_{acc} reaches the value of T_c , the k will be reduced by half. The relationship is supported by results from process-based land surface model simulations for soil ice content variations with accumulated temperature in winter (see Fig. S1 in Wang, 2019).

The baseflow model contains three unknown parameters: k_0 , T_c , and a . For cold region watersheds in winter with frozen soil and snow-covered ground surface, the observed streamflow is solely contributed by baseflow so that $Q_b = Q_{obs}$. With this

Deleted: For a watershed without significant surface water retention capacities, the surface water storage change S_s represent the amount of surface runoff Q_s . Otherwise, S_s can be regarded as amount of water above the surface water holding capacity. In this case, the surface water which is under the surface water holding capacity is in fact included in S_g which doesn't contribute to surface runoff but to baseflow

Deleted: drainable water storage

Deleted: conductivity

Deleted: This provides

Deleted: an

155 advantage, the winter season data were used for the calibration of the baseflow model and the solution of these parameters. A triple-nested numerical iteration scheme was developed to find the optimum values of the k_0 , T_c , and a for achieving the maximum Nash-Sutcliffe efficiency (NSE) between observed and modelled baseflows. The initial values for the k_0 , T_c , and a can be estimated from either available information or expert knowledge. In this study, the values obtained in Wang (2019) were used.

With the assumptions of Equations (1) and (2), and the baseflow model of Equation (3), the baseflow contribution to the total streamflow can be obtained analytically:

$$160 \quad Q_b(t) = \frac{k_0 T_c [S_{tot}(t) - \sum Q_{obs}(t) - S_n(t) - a]}{T_{acc}(t) + T_c - k_0 T_c} \quad (4)$$

Surface runoff is then calculated as the difference between total streamflow and the estimated baseflow. The estimation for baseflow and surface runoff is made for their monthly values, constrained mainly by the monthly temporal resolution of GRACE data. The $\sum Q_{obs}(t)$ in Equation (4) thus represents the sum of observed daily streamflow in a month.

165 The six methods for streamflow hydrograph separation provided with the USGS Groundwater Toolbox (Barlow et al., 2015) include PART, HYSEP (Fixed Interval, Sliding Interval, and Local Minimum), and BFI (Standard and Modified). A brief description for each of the methods is provided in the supplementary material. More details can be found in Barlow et al. (2015) and Sloto and Crouse (1996). Results from these six USGS methods and our approach were compared, with a focus on seasonal variations and long-term averages in the estimated baseflow and baseflow index (BFI).

170 3 Study Region and Datasets

175 The streamflow hydrograph measured at the mouth of the Albany River was used for the model demonstration. The Albany River is located in the Far North of Ontario, Canada, predominantly between 49 and 52 degrees north (Fig. 1). It has a length of 982 kilometres and a drainage area of 137,230 km². The river flows northeast from Lake St. Joseph at an elevation of 371 metres into James Bay. The headwater of the watershed is situated in the Canadian Shield physiographic region which is characterized by a thin soil layer over Precambrian bedrock and moderate topographic relief. The middle and lower portions of the watershed are within the Hudson Bay Lowlands (HBL) physiographic region which is characterized by Paleozoic bedrock overlain by glacial sediment and poorly drained organic deposits with low topographic relief. Within the study area, the Canadian Shield landscape is dominated by Boreal forest which transitions into Barren Boreal and Taiga vegetation zones within the HBL. The Albany River watershed is highly vulnerable to flooding in spring due to snowmelt and sensitive to
180 climate change (McLaughlin and Webster, 2014).

Deleted: In addition, by using only-winter data the model calibration reduces the impact of a number of hydrological processes on quantifying the storage-baseflow relationships, such as evapotranspiration, soil surface infiltration and groundwater recharge. ...

Deleted: with the criteria of

Deleted: modelling

Deleted: was used in the model calibration

Deleted: T

Formatted: Font: Not Italic

Deleted: T



Figure 1. Location and geometry of the Albany River watershed and the gauge station. Study area in red on inset of Canada (© OpenStreetMap contributors 2020. Distributed under a Creative Commons BY-SA License).

195 Four main datasets were used in this study, which include air temperature (T) from the Global Land Data Assimilation System (GLDAS) V2 meteorological forcing, snow water equivalent (S_n) from the land surface model EALCO (Ecological
 200 Assimilation of Land and Climate Observations, Natural Resources Canada) V.4.2, river flow measurement at gauging station 04HA001 (Q_{obs}), and total water storage change (S_{tot}) from GRACE Release-06 V03 spherical harmonic (SH) solutions. Details of the datasets and their quality evaluations are given in the supplementary material. The study time period covers 15 years of
 205 2002–2016. The watershed hydroclimatic conditions characterised for this period from these datasets are summarised below. The watershed has a cold, humid climate. During the study period the watershed had a mean annual temperature of 1.0°C. Daily temperature dropped below 0°C on average in late October to early November, and rose above 0°C in middle April of the next year (Fig. 2). Both of the transitional periods have large inter-annual variations of more than a month. The lowest air temperature in the study period was colder than -25°C in late January. The extremely low temperature and low solar radiation
 in the winter season resulted in deep-frozen condition for the watershed in winter, which minimized the possible contribution of surface runoff to streamflow. Also, the long winter season commonly exceeded five months of each year and provided a relatively large amount of data for baseflow model calibration.

Deleted: times

Deleted: for





Figure 2. Daily air temperature for the Albany River watershed over the study period (2002-2016). Orange dots represent the 15-year mean values.

215 The watershed has a large water budget surplus for aquifer recharge and to sustain year-round river flow. Annual precipitation
 for the study period averaged 784 mm (Fig. 3), ~~more than twice~~ ~~the~~ annual evapotranspiration of 340 mm (Wang et al., 2013).
 Precipitation in summer (rain) accounted for 71% of the total annual precipitation. The rain intensity was mostly under 20
 mm/day, which is fairly low, and consequently large rain induced streamflow peaks are uncommon. The rest of
 the precipitation occurred in winter as snow, with an intensity rarely over 10 mm/day. ~~Snow~~ mostly accumulated from freeze-up
 220 till the melt season in the spring (Fig. 4).

Deleted: about

Deleted: of its


Deleted: The snow



225

Figure 3. Daily precipitation for the Albany River watershed over the study period (2002-2016). Orange line represents the accumulated precipitation in a year using the 15-year mean daily values.

Deleted: Blue dashed lines represent the time when air temperature rose above (left), or dropped below (right), 0°C.



230

Figure 4. Daily snow water equivalent for the Albany River watershed simulated by the EALCO model over the study period (2002-2016). Orange dots represent the 15-year mean values.

The Albany River had an annual mean flow, during the study period, of 1420 m³/s (1.04 mm day⁻¹), with an annual total of 44.8 km³ (380 mm). The peak flow for each year occurs mostly in May due to snowmelt (Fig. 5). The largest peak flow occurred in 2006 and was 8000 m³/s (5.86 mm day⁻¹). Summer flows have minor-peaks from rain events and occurred sporadically throughout the season. They were generally smaller than the spring snowmelt peak. The 15-year (2002-2016) average flows showed a pattern of sharp decrease from May to August, and then an increase in early autumn till freeze-up. River flow in the winter season decreased smoothly with time and it presented a typical baseflow recession process, confirming our assumption of absent surface runoff due to the frozen conditions. The inter-annual differences in the baseflow values were large in early winter, with a range from over 4600 m³/s (3.37 mm day⁻¹) to just 350 m³/s (0.26 mm day⁻¹) depending on the pre-winter water conditions of the watershed. After discharging over an entire winter season, and before the start of the snowmelt season, the river had flow values within a small range of 100-200 m³/s (0.07- 0.15 mm day⁻¹). The mean river flow for the winter season varied from 200 m³/s to 700 m³/s (0.15-0.51 mm day⁻¹), with an overall average of 420 m³/s (0.30 mm day⁻¹).

Deleted: less than

Deleted: half

Deleted: up to

Deleted: winter season




Figure 5. Daily streamflow measured at the gauge station 04HA001 (see Fig. 1) of the Albany River over the study period (2002-2016). Orange dots represent the 15-year mean values.

The watershed had a maximum variation for total water storage of 200 mm during the 15-year study period (Fig. 6). The lowest TWS values appeared in September and the highest values occurred in April before snowmelt began. Obviously, the increase in TWS in the fall-winter season is mainly due to the snow accumulation and low water loss from snow sublimation, and the decrease in TWS in the spring-summer season is mainly due to the large amount of discharge of snowmelt water and high evapotranspiration which reaches about 80 mm for land surface evapotranspiration and 130 mm for water surface evaporation

Deleted: total water storage

Deleted: range of

in July (Wang et al., 2014a). The inter-annual variations in TWS for a specific month was large, with a range of 100 mm on average. Note that the baseline (reference) value of the TWS, which is the average over the period of January 2004 to December 2009 in the original datasets, is adjusted to the minimum value found over the study period in this study.




Figure 6. Monthly total water storage (TWS) for the Albany River watershed over the study period (2002-2016, relative to the minimum value for the period). The grey lines represent the time period of GRACE observations used for deriving the TWS.

4 Results

The baseflow model calibration results and performance evaluation (Table 1) show that the modelled and observed monthly baseflow values in the winter seasons of 2002-2016 achieved a Pearson correlation coefficient (R) of 0.91 ($p < 0.001$). The Nash-Sutcliffe efficiency coefficient (NSE) of the model reached 0.823. The model suggested that the watershed had a k_d for subsurface water discharge of $7.45 \times 10^{-3} \text{ day}^{-1}$. The k_d was reduced by half when the accumulated freezing temperature reached $-595 \text{ }^\circ\text{C}\cdot\text{day}$ (T_c) in winter. When the watershed reached its lowest water storage during the 15 years, which was observed in September 2006, the watershed still had 45.7 mm (5.4 km^3) water available for discharge (a) (Fig. 7). On average, the model suggested that the DWS of the watershed was 152.4 mm (18 km^3) during the 15-year study period. The seasonal variation of DWS, from its lowest monthly mean value of 103.6 mm (12.2 km^3) in September to its highest value of 196.3 mm (23.2 km^3)

Deleted: of the

Formatted: Centered

Deleted: anomaly

Deleted: mean

Deleted: lump hydraulic conductivity (

Deleted:)

Deleted: conductivity

Deleted: drainable water storage

Deleted: the drainable water storage

in April, exceeded over 60% of its average value. The interannual variation of DWS_v was also large. The largest monthly interannual variation appeared in September, with a value of 118.7 mm (14 km³), and the lowest interannual variations appeared in March, with a value of 60.5 mm (7.1 km³). The overall annual variation range was 87.0 mm (10.3 km³).

Deleted: (Fig. 7)

Deleted: the drainable water storage

Table 1. Baseflow model calibration and test results.

Model	Parameter	Description	Value
$Q(t) = k_0 \frac{T_c}{T_{acc}(t) + T_c} (S(t) - a)$	k_0 ($\times 10^{-3} \text{ day}^{-1}$)	Baseflow rate constant	7.45
	T_c ($^{\circ}\text{C}\cdot\text{day}$)	Parameter for impact of freezing temperature in winter on k_0	-595
	a (mm)	Drainable water storage (DWS) threshold value, relative to the minimum S_{tot} observed during the study period	-45.7
Model Performance	MAE (mm day^{-1})	Mean absolute error	0.05
	R	Pearson correlation coefficient	0.91
	NSE	Nash–Sutcliffe model efficiency	0.823
	p	Significance level	<0.001

Deleted: Watershed lump conductivity for water discharge (baseflow)

295




Figure 7. Drainable water storage (DWS) estimated for the Albany River watershed. The blue line represents the mean values, and the vertical bars represent the range of variations for the 15-year of 2002-2016.

Deleted: annual

Deleted: per month

The baseflow hydrograph estimated by our model is shown in Fig. 8(a), compared with the corresponding results obtained from PART (Fig 8b), HYSEP (Fixed Interval, Sliding Interval, and Local Minimum) (Fig 8c), and BFI (Standard and Modified) (Fig 8d). The monthly means over the 15-year study period are compared in Fig. 9, with the corresponding Base Flow Index (BFI) values (or the ratio of baseflow to total streamflow) shown in Fig. 10. Overall, the baseflow and BFI estimated from these seven methods showed general agreement. Their similarities and differences can be generalised by the following three time periods.

(1) Winter Season. We used fairly strict criteria (Section 2) to select the winter months to ensure that the watershed was in frozen conditions and no rain and other events contributed to river flow by surface runoff. The PART, BFI-Std and BFI-Mod models basically showed BFI of 1.0 in mid-winter. With the assumption of baseflow as the only contribution to streamflow in the winter months, our model has a BFI value of 1.0 in December, January and February. This is consistent with the observation of the streamflow data in Fig. 5 which exhibited typical baseflow recession process (Fig. 5) during these periods. The temperature during these three winter months in each year of our study period all had values significantly below 0°C. The six USGS methods also showed similar results. In particular, PART and the two BFI methods (Standard and Modified) estimated baseflow basically being equal to the total streamflow in January and February, but they estimated small but noticeable contributions of surface runoff in December (4% for PART, 9% for BFI-Standard and Modified). The three HYSEP methods showed relatively large difference to our model. They all estimated surface runoff contributions in the streamflow in each of the three winter months. The results from the HYSEP Fixed and Slide methods were virtually the same, which showed BFI values increasing from 0.88 in December to 0.92 in January and 0.93 in February. In contrast, the HYSEP Minimum method showed different results from the other two HYSEP methods in December (BFI=0.77) and February (BFI=0.97). Close examinations of the data revealed no hydrological processes (e.g., rain or snowmelt from above 0 temperature) that could lead to surface runoff generation during these time periods, and the results from the three HYSEP methods are likely due to the defects with the algorithms of these methods and the observation noise. Despite the differences in BFI values among some of the methods as discussed above, they had little impact on the annual total baseflow estimates since the overall winter streamflow was very low (Fig. 5).

(2) Snowmelt Season. In the spring snowmelt season, total streamflow increased sharply to its annual peak in May. The baseflow estimated from our model also reached its annual peak at this time, representing 54% of the total streamflow (Fig. 10). In the rising limb of the streamflow peak, our model obtained its lowest BFI value in a year, which was 0.44 for April. This is consistent with the fact that in the early snowmelt season, the soil was in a frozen condition which prevented water from infiltrating the surface, resulting in snowmelt water mostly contributing to the streamflow as surface runoff. At the same time, aquifer discharge (baseflow) remained the lowest in the year. In the falling limb of the spring streamflow peak, our model estimated a much smaller decreasing rate in baseflow than the total streamflow (Fig. 9). The modelled BFI value for June was 0.69, a significant increase from its values in April (0.44) and May (0.54). The six USGS methods also showed similar patterns in the baseflow and BFI variations, but in some cases with substantial differences. Specifically, all six methods also obtained their highest baseflow values during the peak flow time in May (Fig. 9), their lowest BFI values in

Deleted: were present

Deleted: cause

Deleted: T

Deleted: for our model is that in winter season, when the watershed is in a frozen condition, there is no surface runoff and

Deleted: i

Deleted: . This can be seen from the

Deleted: results in December, January and February when the modelled baseflow was equal to the observed streamflow, with

Deleted: 9

Deleted: the

Deleted: ed

the rising limb in April (Fig. 10), and continuous increase in BFI values through the snowmelt season (Fig. 10). The large decrease in BFI from February to April (Fig. 10) reflects the snowmelt runoff contribution to the streamflow. Overall, our model showed the lowest baseflow and BFI values among the seven methods during the snowmelt season. It is worth noting that the baseflow/BFI values for April from our model was close to those from four of the USGS methods, namely HYSEP Minimum, the two BFI methods and PART. However, this better agreement in model results may not suggest more robust estimate in baseflow, which will be discussed later. Among the six USGS methods, the most striking difference was the high baseflow/BFI values by the HYSEP Fixed and Slide methods throughout the snowmelt season. For example, the BFI estimated by these two methods was about 0.64 for the month of April, while the estimates from the other five methods including our model were around 0.42. The BFI-Modified method estimated a relatively high baseflow/BFI value for the peak flow month of May, and it is worth mention that this is the only month in a year that the BFI-Modified method showed significantly different result from the BFI-Standard method. Another noticeable outlier is from PART in the falling limb (June), which showed a baseflow/BFI value similar to that in the peak flow time of May.

(3) Summer Season. The results estimated by the seven methods were fairly close in summer season (Fig. 9). The general pattern can be characterized by the low baseflow in August-September when the watershed had the lowest water storage, and a second peak around October before the winter season starts. In terms of BFI, all the methods estimated relatively high BFI values in August, with the highest value estimated by our model (Fig. 10). During the second peak in October, our model showed a large decrease of BFI (0.76) from the summer low-flow in August (BFI=0.96), suggesting the increased contribution of surface runoff from rain to the streamflow. In contrast, the decrease of BFI during this transitional period was not obvious for five other models except HYSEP Minimum.




Figure 8. Hydrograph separation of the Albany River for 2002-2016. Data shown are monthly values for the observed total streamflow (black line/dot in each panel) and the baseflow estimated by the methods of (a) this study, (b) PART, (c) HYSEP, including Fixed Interval, Sliding Interval, and Local Minimum, and (d) BFI, including Standard and Modified.

375




Figure 9. Observed total streamflow and estimated baseflow by different methods for the Albany River. Data shown are monthly means in the 15 years of 2002-2016.

380




Figure 10. Baseflow index (BFI) estimated by different methods for the Albany River. Data shown are calculated using the 15-year (2002-2016) means of baseflow and streamflow.

385 Overall, our model showed relatively larger seasonal variations in BFI compared with the six USGS methods (Fig. 10). The contribution of baseflow to the total streamflow estimated by our model was 71.7% for the 15 years. In comparison, the corresponding estimates by the six USGS methods ranged from 67.6% (HYSEP-Minimum) to 79.7% (HYSEP-Slide) (Table

2). The PART method showed the best agreement with our model, with a correlation coefficient of $R=0.92$ for the monthly baseflow estimates (Fig. 11). The difference between the results from HYSEP-Fixed and HYSEP-Slide was very small, but they differed significantly with the HYSEP-Minimum method. The HYSEP-Minimum method estimated lower baseflow than the other two HYSEP methods systematically year-round, and the difference was especially significant in the peak flow season and early winter. The BFI-Standard and Modified methods obtained very similar results, except only in three months during the 15 years when the Modified methods estimated much higher baseflow than the Standard method, and all three exceptions appeared in May, the month with peak streamflow.

Deleted: both

Table 2. Average baseflow and baseflow index (BFI) estimated for 2002-2016.

Method	This study	PART	HYSEP			BFI	
			Fixed	Minimum	Slide	Standard	Modified
Baseflow (mm/day)	0.585	0.605	0.649	0.552	0.650	0.587	0.609
BFI	0.717	0.742	0.795	0.676	0.797	0.719	0.746




Figure 11. Comparisons of baseflow estimated from this study (X-axis) with those from PART, HYSEP (Fixed Interval, Sliding Interval, and Local Minimum), and BFI (Standard and Modified) (Y-axis).

5 Discussion

405 Snowmelt is a known hydrologic process that could cause problems with the traditional hydrograph separation methods. Snowmelt in high latitudes can be a slow process which lasts for weeks depending on the rising temperature trend of the spring season. The hydrograph fluctuations caused by snowmelt runoff have very different characteristics from those caused by rain events. The algorithms for the traditional hydrograph separation methods may incorrectly identify streamflow increase contributed by snowmelt runoff as groundwater discharge (Barlow et al., 2015). Indeed, we found that the baseflow values
410 from the six USGS methods during the snowmelt season were all higher than that from our model, suggesting overestimation of baseflow due to inclusion of snowmelt runoff. This difference is particularly large with the HYSEP Fixed and Slide methods (Fig. 9). Our model ~~demonstrates improvement to this known bias in these traditional models, and~~ provides the most conservative estimate of baseflow. ~~Our data and results didn't suggest systematic bias coming from the calibration process. First, the range of drainable water storage used for model calibration reasonably covered the variation range during the summer season. Second, our model results reversed the relationship of baseflow when compared with other models in summer. In fact, our model obtained higher baseflow in the mid-summer months of July-September (Figure 9) than most of the other six models. Annually, our model showed baseflow close to BFI-Standard, higher than HYSEP-Minimum, and lower than the other 4 models (Table 2). Third, our results are in good agreement with, and supported by, the results obtained in other studies, including Rudra et al. (2015) which analysed BFI for 115 Ontario watersheds, and Wang and Russell (2016) and Wang et al. (2017) which explicitly estimated the snowmelt runoff.~~

420 It is worth noting that among the six USGS methods, the HYSEP Minimum method provided the lowest estimate of baseflow almost year-round in all seasons. Similar results were also report in Curtis et al. (2020) where the six USGS methods were applied to 312 watersheds in the USA for baseflow separation. They found that the HYSEP Minimum method provided the lowest estimate of baseflow, and thereafter suggested HYSEP Minimum as the most robust method for removing snowmelt runoff in baseflow estimates. From our analyses, we ~~found that the conservative estimate of baseflow during the snowmelt season by the HYSEP Minimum method is likely due to the systematic underestimation of baseflow in its hydrograph separation algorithm.~~

430 In the early snowmelt season of April before the streamflow peak, our model estimated similar baseflow values to four of the six USGS methods, in contrast to its consistent lower values for March, May and June than all of the USGS methods. Where there is better agreement in model results, it does not necessarily mean ~~there is a more~~ robust estimate. On the contrary, it is reasonable to believe that this could be due to the overestimation of baseflow by our model for April. One assumption of our model is that all the drainable liquid water storage under the surface water holding capacity belongs to the subsurface water storage and contributes to watershed discharge or river baseflow. In reality, in the early snowmelt season, the soil is still frozen, which will prevent the snowmelt water from surface infiltration and contributing to baseflow. This often results in surface

Deleted: may

Deleted: and may be the most robust for filtering out snowmelt runoff bias in baseflow estimates

Deleted: recommend

Deleted: more

440 water puddles in spring as commonly observed in cold regions. Our above model assumption could be challenged under this condition and it will lead to the overestimation of baseflow.

Large size and low relief of a watershed are also the factors of caution when using the traditional hydrograph separation methods. Rutledge (1998) recommended a maximum drainage area of about 1,300 km² for the application of these methods.

445 The low relief of a watershed may also affect the time period of surface runoff that can be determined by Equation (A1), and this effect could be exacerbated by the large drainage area of a watershed. Halford and Mayer (2000) and Halford (2008) also questioned the use of Equation A1 to determine the duration of surface runoff for large watersheds. In contrast, the algorithm of our model is not limited by Equation A1, rather it is limited by the GRACE footprint which is over 10⁵ km². In this study, we used the Albany River watershed for demonstration which has a total drainage area of over 137×10³ km², or two orders of magnitude larger than that suggested by traditional methods. The method could be applied to small watersheds when high-resolution information is available for water storage.

450 The Albany watershed in this study was among the watersheds with the smallest water imbalance (non-closure) in Canada (Wang et al., 2014a; Wang et al., 2014b). This suggests the high data qualities over this region, including GRACE TWS, EALCO snow water equivalent and river flow observations, and close connections between surface water and groundwater systems for the Albany watershed. The uncertainties with snow (Sn), surface water (Ss), and subsurface water (Sg) cannot be directly evaluated because no corresponding observations are available. However, they can be evaluated indirectly. We calculated the GRACE TWS measurement error, leakage error, and combined total error following Wahr et al. (2006) using the land surface model CLM4, and they were 13.2 mm, 15.8 mm, and 20.6 mm, respectively, for the watershed. The impact on the TWS error estimate due to the uncertainty in the CLM4 model was evaluated by comparing with the error estimate using a different land surface model of NOAH (Wang et al., 2014a). The magnitudes of errors from the two studies were found to be similar. Since our model is calibrated using observed baseflow measurement, systematic errors or biases in TWS would be reflected in the model calibration process and compensated in the parameter values, so their impact on the hydrograph separation results would be minimal. Random errors in TWS could directly affect the baseflow estimation. However, in the cold season since the TWS change is mainly due to snow variations which does not contribute to river flow, the uncertainties in TWS also have minor impact on baseflow estimate. In the non-frozen season, an error of 20 mm in TWS would result in an estimate error of 0.15 mm/day in baseflow, which is small compared with the flow magnitude in summer of the watershed. In fact, as suggested by the water budget closure study and error analyses (Wang et al., 2014a; Wang et al., 2015), the random error is much smaller than the measurement error of 20mm.

460 The uncertainties with snow can be further evaluated by comparing this study with Wang (2019), where the winter time drainable water was estimated by the difference of the TWS at the winter starting time and the accumulated streamflow (from winter start to a specific month). The advantage of Wang (2019) approach is that it doesn't need snow data in the modelling, while the disadvantage is that it increased the impact of the uncertainties of winter streamflow measurement in the modelling. Also, any errors with the TWS at the winter start will propagate into the modelling for all the months in that season. The modelling results show that this study, which used snow data, slightly improved that of Wang (2019) (NSE=0.823, r=0.91 vs.

Deleted: accurately

Deleted: is

Deleted: but

Deleted: not limited by watershed size and relief, and it is specifically suitable for applications over large watersheds using

Deleted: observations which has a large

Deleted: of

Deleted: the

Deleted: of

Deleted: the

Deleted: n't

Deleted: to

NSE=0.809; r=0.903), suggesting the impact of uncertainties from EALCO snow data is less than that from the uncertainties in streamflow measurements on the baseflow modelling.

The model was calibrated using all the available winter data during our study period. Even so, due to the limited GRACE observations and the strict selection criteria for winter months to ensure that the watershed was in frozen conditions and no rain or other events could occur to cause surface runoff, the sample number for model calibration was relatively small (~3 months/year on average). However, the calibration doesn't assume that the baseflow mechanism is stable over the years. In fact, possible variations in baseflow mechanism with watershed conditions (such as yearly weather changes as commented) were expected, and the impact, which causes deviations between modelled vs. observed flows, was reflected in the calibration results. Moreover, the model treated the baseflow coefficient dynamically using the accumulated freezing temperature function to account for the seasonal (e.g., winter vs. summer) and yearly changes in watershed conditions. This represents a major innovation for this method, and the improvement and advantage over traditional methods of treating baseflow parameters as constants have been discussed in detail in Wang (2019).

This study provides a technical framework for hydrograph separation using GRACE observations. It is demonstrated using streamflow measurement for a cold region watershed. Cold region watersheds in winter have frozen soil and snow-covered ground surface, so the observed streamflow is solely contributed by baseflow. This provides an advantage for the calibration of the baseflow model. Moreover, by using only-winter data the model calibration reduces the impact of a number of hydrological processes on the solution of model parameters, such as evapotranspiration, soil surface infiltration and groundwater recharge. For applications of our model over other climate regions, the model parameters could be estimated by different approaches, such as using dry season data over arid regions when rainfall-induced surface runoff is absent in streamflow measurements.

It is worth noting that the Albany groundwater discharge is mainly contributed by surficial aquifers and the baseflow-storage relationship is relatively stable (Wang 2019). The hydrogeological settings of the watershed are relatively simple, and the baseflow mechanism can be very different for watersheds that have steep slopes, complicated aquifer systems, permafrost layers, or large variations in water conditions, which often involve dynamic channel networks (e.g., time-varying geometry of saturated channeled sites) and result in complicated storage-baseflow relationships (Biswal and Kumar, 2014; Biswal & Marani, 2010; Streletskiy et al., 2015; Tallaksen, 1995). Indeed, the study of Wang (2019) tested different baseflow models and found that the Albany watershed follows a simple linear baseflow-storage relationship quite well when soil frost is absent (i.e., summer season), and the freezing temperature function (Eq. 3) allows the model to account for the dynamic changes in watershed winter condition. For watersheds with complicated hydrogeological settings, our approach may need to involve more comprehensive baseflow models or TWS-dependent dynamic parameters to address the complicated aquifer systems and flow mechanisms.

6 Conclusions

Deleted: are with

Deleted: and the baseflow mechanism can be very different for watersheds that have steep

Deleted: allows to

Deleted: ¶
¶

Formatted: Space Before: 24 pt, After: 12 pt

Formatted: Font: 10 pt

A GRACE-based hydrograph separation model is developed in this study to address the weaknesses of traditional methods in baseflow estimate, such as the lack of physics and arbitrary choice of separation parameters, problems in identifying snowmelt runoff, and limitations on watershed size and other conditions. The model first constructs a baseflow model using winter data, and then uses streamflow observations to solve the baseflow in all seasons. It is physically-based and does not require ~~arbitrary choice of parameters~~. The hydrograph separation results from our model can generally ~~be~~ characterized by the absence of surface runoff in winter when the watershed was covered by snow and in frozen conditions, high volume but low percentage contribution from baseflow to the streamflow in the snowmelt season, and low volume but high percentage contribution from baseflow to the streamflow in the summer dry season. Comparisons of the model with the six hydrograph separation methods provided with the U.S. Geological Survey Groundwater Toolbox show that our model effectively filtered out the snowmelt runoff from baseflow estimate. The algorithm of the model is not limited by watershed size and it is specifically suitable for applications over large watersheds using GRACE observations, which is complementary to the traditional methods that are mostly limited ~~to smaller~~ watersheds. The model output also includes estimates for watershed lump hydraulic conductivity and the drainable water storage, which are useful parameters in evaluating aquifer properties, calibrating and validating hydrological and climate models, and assessing regional water resources.

Deleted: a priori parametrisation

Deleted: be

Deleted: by the size

Deleted: of

Data availability. Data used in this study are openly available and can be downloaded from the following links: air temperature: <http://mirador.gsfc.nasa.gov/>, snow water equivalent: <ftp://ftp.ccrs.nrcan.gc.ca/ad/EMS/EALCO/>, river flow: <https://wateroffice.ec.gc.ca/>, total water storage change <https://podaac.jpl.nasa.gov/GRACE>.

Deleted: <http://www.ec.gc.ca/rhc-wsc/>

Author contributions. S.W. conceived and implemented the research. S.W. wrote the initial version of the paper. J.L. contributed Fig. 1. All authors contributed to discussion and improving the paper. H.A.J.R. contributed project managerial support.

Acknowledgements. This study was supported by the Cumulative Effects Project and Climate Change Geoscience Program of the Natural Resources Canada.

References

- Arnold, J. G., Allen, P. M., Muttiah, R., and Bernhardt, G.: Automated base flow separation and recession analysis techniques, *Ground Water*, 33, 1010-1018, 1995.
- Barlow, P.M., Cunningham, W.L., Zhai, T., and Gray, M.: U.S. Geological Survey Groundwater Toolbox, a graphical and mapping interface for analysis of hydrologic data (version 1.0)—User guide for estimation of base flow, runoff, and groundwater recharge from streamflow data: U.S. Geological Survey Techniques and Methods, book 3, chap. B10, 27 p. <http://dx.doi.org/10.3133/tm3B10>, 2015.

Biswal, B., & Kumar, D. N.: What mainly controls recession flows in river basins? *Advances in Water Resources*, 65, 25–33. <https://doi.org/10.1016/j.advwatres.2014.01.001>, 2014.

Biswal, B., & Marani, M.: Geomorphological origin of recession curves. *Geophysical Research Letters*, 37, L24403. <https://doi.org/10.1029/2010GL045415>, 2010.

Boulton, A.J. and Hancock, P.J.: Rivers as groundwater-dependent ecosystems: a review of degrees of dependency, riverine processes and management implications. *Australian Journal of Botany* 54 (2), 133–144. <https://doi.org/10.1071/BT05074>, 2006.

Boussinesq, J.: Recherches theoretique sur l'ecoulement des nappes d'eau infiltrées dans le sol et sur le debit des sources. *J. Math. Pure Appl.* 10 (5th Series), 5-78, 1904.

Chapman, T.: A comparison of algorithms for stream flow recession and baseflow separation. *Hydrol. Process.* 13, 701-714, 1999.

Curtis, J. A., Burns, E. R., and Sando, R.: Regional patterns in hydrologic response, a new three-component metric for hydrograph analysis and implications for ecohydrology, Northwest Volcanic Aquifer Study Area, USA, *Journal of Hydrology: Regional Studies*, 30, 100698. doi.org/10.1016/j.ejrh.2020.100698, 2020.

Eckhardt, K.: How to construct recursive digital filters for base flow separation. *Hydrol. Process.*, 19, 507–515, 2005.

Foks, S. S., Ruffensperger, J. P., Penn, C. A., and Driscoll, J. M.: Estimation of Base Flow by Optimal Hydrograph Separation for the Conterminous United States and Implications for National-Extent Hydrologic Models. *Water*, 11, 1629. [doi:10.3390/w11081629](https://doi.org/10.3390/w11081629), 2019.

Furey P. R. and Gupta V. K.: A physically based filter for separating base flow from streamflow time series. *Water Resources Research* 37(11): 2709-2722, 2001.

Gao, Z.; Zhang, L.; Cheng, L.; Zhang, X.; Cowan, T.; Cai, W.; Brutsaert, W. Groundwater storage trends in the Loess Plateau of China estimated from streamflow records. *J. Hydrol.*, 530, 281–290, 2015.

Halford, K.J.: Discussion on “Update on the use of the RORA program for recharge estimation,” by Al Rutledge: *Ground Water*, v. 46, no. 1, p. 10–11, 2008.

Halford, K.J. and Mayer, G.C.: Problems associated with estimating ground water discharge and recharge from stream-discharge records: *Ground Water*, v. 38, no. 3, p. 331–342, 2000.

Hall, F. R.: Base flow recessions: A review. *Water Resour. Res.*, 4, 973–983, 1968.

Hooper, R.P. and Shoemaker, C.A.: A comparison of chemical and isotopic hydrograph separation. *Water Resour. Res.*, 22, 1444–1454, 1986.

Institute of Hydrology: Research report, v. 1 of Low flow studies: Wallingford, United Kingdom, Institute of Hydrology, 42 p., 1980a.

Institute of Hydrology: Catchment characteristic estimation manual, v. 3 of Low flow studies: Wallingford, United Kingdom, Institute of Hydrology, 27 p., 1980b.

Formatted: French (Canada)

Formatted: English (Canada)

- 595 Landerer, F.: CSR/GFZ/JPL TELLUS GRACE Level-3 monthly land water-equivalent-thickness surface mass anomaly
Release 6.0 version 03 in netCDF/ASCII/GeoTiff format. Ver. RL06 v03. PO.DAAC, CA, USA. Dataset accessed [2020-
06-01] at <https://doi.org/10.5067/TELND-3AC63> (/TELND-3AG63 or /TELND-3AJ63), 2020.
- Landerer, F. and Swenson, S.C.: Accuracy of scaled GRACE terrestrial water estimates. *Water Resour. Res.*, Vol 48, W04531,
11pp. doi: 10.1029/2011WR011453, 2012.
- 600 Linsley, R.K., Kohler, M.A., and Paulhus, J.L.: *Hydrology for engineers* (3rd ed.): New York, McGraw-Hill, 508 p., 1982.
- Macedo, H. E., Beighley, R. E., David, C. H., and Reager, J. T.: Using GRACE in a streamflow recession to determine
drainable water storage in the Mississippi River basin. *Hydrol. Earth Syst. Sci.*, 23, 3269–3277. doi.org/10.5194/hess-23-
3269-2019, 2019.
- Maillet, E.: *Essais d'Hydraulique Souterraine et Fluviale*. Hermann Paris, 218pp, 1905.
- 605 McLaughlin, J. and Webster, K.: Effects of a climate change on peatlands in the Far North. of Ontario, Canada: a synthesis.
Arctic, Antarctic, and Alpine Research, 46, 84-102, 2014.
- Miller, M.P., Susong, D.D., Shope, C.L., Heilweil, V.M., and Stolp, B. J.: Continuous estimation of base flow in snowmelt-
dominated streams and rivers in the Upper Colorado River Basin: A chemical hydrograph separation approach. *Water
Resour. Res.*, 50, 6986–6999, 2014.
- 610 Miller, M.P.; Buto, S.G.; Susong, D.D.; Rumsey, C.A.: The importance of base flow in sustaining surface water flow in the
Upper Colorado River Basin. *Water Resour. Res.*, 52, 3547–3562, 2016.
- Natermann, E.: Die Linie des langfristigen Grundwassers (AuL) und die Trockenwetter-Abflußlinie (TWL). *Wawi*, 41, 12–
14, 1951.
- Nathan, R. J. and McMahon, T. A.: Evaluation of automated techniques for base flow and recession analyses, *Wat. Resour.
Res.*, 26, 1465-1473, 1990.
- 615 Nuhfer, A.J.; Zorn, T.G.; Wills, T.C. Effects of reduced summer flows on the brook trout population and temperatures of a
groundwater-influenced stream. *Ecol. Freshw. Fish.*, 26, 108–119, 2017.
- Pelletier, A. and Andréassian, V.: Hydrograph separation: an impartial parametrisation for an imperfect method. *Hydrol. Earth
Syst. Sci.*, 24, 1171–1187. doi.org/10.5194/hess-24-1171-2020, 2020.
- 620 Pettyjohn, W.A. and Henning, R.: Preliminary estimate of ground-water recharge rates, related streamflow and water quality
in Ohio: Columbus, Ohio State University, Water Resources Center Project Completion Report 552, 323 p., 1979.
- Piggott, A.R., Moin, S., and Southam, C.: A revised approach to the UKIH method for the calculation of baseflow:
Hydrological Sciences, v. 50, no. 5, p. 911–920, 2005.
- Reager, J., Thomas, B., and Famiglietti, J.: River basin flood potential inferred using GRACE gravity observations at several
months lead time, *Nat. Geosci.*, 7, 588–592. doi.org/10.1038/Ngeo2203, 2014.
- 625 Riegger, J. and Tourian, M. J.: Characterization of runoff-storage relationships by satellite gravimetry and remote sensing,
Water Resour. Res., 50, 3444–3466. doi.org/10.1002/2013WR013847, 2014.

Formatted: French (Canada)

Formatted: English (Canada)

Deleted:

Formatted: French (Canada)

- 630 Riegger, J.: Quantification of drainable water storage volumes on landmasses and in river networks based on GRACE and
river runoff using a cascaded storage approach – first application on the Amazon. *Hydrol. Earth Syst. Sci.*, 24, 1447–1465.
doi.org/10.5194/hess-24-1447-2020, 2020.
- Riggs, H.C., 1963, The base-flow recession curve as an indicator of ground water: International Association of Scientific
Hydrology Publication 63, p. 352-363.
- 635 Rorabaugh, M.I., Estimating changes in bank storage and ground-water contribution to streamflow: International Association
of Scientific Hydrology Publication 63, p. 432-441, 1963.
- Rosenberry, D.O. and LaBaugh, J.W.: Field techniques for estimating water fluxes between surface water and ground water:
U.S. Geological Survey Techniques and Methods, book 4, chap. D2, 128 p. <http://pubs.usgs.gov/tm/04d02/>, 2008.
- Rudra, R., Ahmed, I., Khan, A. A., Singh, K. G., Goel, P. K., Khayer, M., and Dickinson, T.: Use of Baseflow Indices to
Delineate Baseflow Dominated and Rapid Response Flow Dominated Watersheds. Canadian Biosystems Engineering 57,
640 1–11. doi.org/10.7451/CBE.2015.57.1.1, 2015.
- Rutledge, A.T.: Computer programs for describing the recession of ground-water discharge and for estimating mean ground-
water recharge and discharge from streamflow records—Update: U.S. Geological Survey Water-Resources Investigations
Report 98–4148, 43 p. <http://pubs.usgs.gov/wri/wri984148/>, 1998.
- 645 Santhi, C., Allen, P. M., Muttiah, R. S., Arnold, J. G., and Tuppai, P.: Regional estimation of base flow for the conterminous
United States by hydrologic landscape regions. Journal of Hydrology, 351(1–2), 139–153.
<https://doi.org/10.1016/j.jhydrol.2007.12.018>, 2008.
- Shao, G., Zhang, D., Guan, Y., Sadat, M. A., and Huang, F.: Application of Different Separation Methods to Investigate the
Baseflow Characteristics of a Semi-Arid Sandy Area, Northwestern China. *Water*, 12, 434. doi:10.3390/w12020434, 2020.
- 650 Sloto, R.A. and Crouse, M.Y.: HYSEP-A computer program for streamflow hydrograph separation and analysis: U.S.
Geological Survey Water Resources Investigations Report 96–4040, 46p. <http://pubs.er.usgs.gov/publication/wri964040>,
1996.
- Smakhtin, V. U.: Low flow hydrology: a review. *Journal of Hydrology*, 240, 147–186, 2001.
- Sproles, E. A., Leibowitz, S. G., Reager, J. T., Wigington, P. J., Famiglietti, J. S., and Patil, S. D.: GRACE storage-runoff
hysteresis reveal the dynamics of regional watersheds, *Hydrol. Earth Syst. Sci.*, 19, 3253–3272. doi.org/10.5194/hess-19-
655 3253-2015, 2015.
- Stewart, M., Cimino, J., and Ross, M.: Calibration of base flow separation methods with streamflow conductivity.
Groundwater, 45, 17–27, 2007.
- Stewart, M.K.: Promising new baseflow separation and recession analysis methods applied to streamflow at Glendhu
Catchment, New Zealand. Hydrol. Earth Syst. Sci., 19, 2587–2603, 2015.
- 660 Stoelzle, M., Schuetz, T., Weiler, M., Stahl, K., and Tallaksen, L. M.: Beyond binary baseflow separation: a delayed-flow
index for multiple streamflow contributions. *Hydrol. Earth Syst. Sci.*, 24, 849–867. doi.org/10.5194/hess-24-849-2020,
2020.

665 [Streletskiy, D.A., Tananaev, N.I., Opel, T., Shiklomanov, N.I., Nyland, K.E., Streletskaya, I.D., Tokarev, I., and Shiklomanov, A.I.: Permafrost hydrology in changing climatic conditions: Seasonal variability of stable isotope composition in rivers in discontinuous permafrost. *Environ. Res. Lett.* 10, 95003. <https://doi.org/10.1088/1748-9326/10/9/095003>, 2015.](#)

Szilagyi, J. and Parlange M.B.: Baseflow separation based on analytical solutions of the Boussinesq equation. *Journal of Hydrology* 204:251-260, 1998.

Tallaksen, L. M.: A review of baseflow recession analysis. *J. Hydrology*, 165, 349-370, 1995.

670 Tapley, B. D., Bettadpur, S., Watkins, M., and Reigber, C.: The gravity recovery and climate experiment: Mission overview and early results, *Geophys. Res. Lett.*, 31, L09607. doi.org/10.1029/2004GL019920, 2004.

Tourian, M. J., Reager, J. T., and Sneeuw, N.: The total drainable water storage of the Amazon river basin: A first estimate using GRACE. *Water Resources Research*, 54, 3290–3312. doi.org/10.1029/2017WR021674, 2018.

[U.S. Bureau of Reclamation: Colorado River Basin Water Supply and Demand Study, Study Report. U.S. Dept. of the Inter., pp. 95. Available at <http://www.usbr.gov/lc/region/programs/crbstudy/finalreport/studyrpt.html>, 2012.](#)

675 [van Dijk, A. I. J. M.: Climate and terrain factors explaining streamflow response and recession in Australian catchments. *Hydrology and Earth System Sciences*, 14\(1\), 159–169. <https://doi.org/10.5194/hess-14-159-2010>, 2010.](#)

Voutchkova, D. D., Miller, S. N., and Gerow, K. G.: Parameter sensitivity of automated baseflow separation for snowmelt-dominated watersheds and new filtering procedure for determining end of snowmelt period. *Hydrological Processes*, 33: 876–888. doi: 10.1002/hyp.13369, 2019.

680 [Wahr, J., Swenson, S., & Velicogna, I.: Accuracy of GRACE mass estimates. *Geophysical Research Letters*, 33, L06401. <https://doi.org/10.1029/2005GL025305>, 2006.](#)

Wang, S., Zhou, F., and Russell, H.A.J.: Estimating snow mass and peak river flows for the Mackenzie River basin using GRACE satellite observations. *Remote Sensing*, 9, 256. doi: 10.3390/rs9030256, 2017.

685 Wang, S. and Russell, H.A.J.: Forecasting snowmelt-induced flooding using GRACE satellite data: A case study for the Red River watershed. *Canadian Journal of Remote Sensing*, 42, 203-213. doi: 10.1080/07038992.2016.1171134, 2016.

Wang, S. and Li, J.: Terrestrial water storage climatology for Canada from GRACE satellite observations in 2002-2014. *Canadian Journal of Remote Sensing*, 42, 190-202. doi: 10.1080/07038992.2016.1171132, 2016.

690 Wang, S., Pan, M., Mu, Q., Shi, X., Mao, J., Brümmer, C., Jassal, R. S., Krishnan, P., Li, J., and Black, T. A.: Comparing evapotranspiration from eddy covariance measurements, water budgets, remote sensing, and land surface models over Canada. *Journal of Hydrometeorology*, 16, 1540-1560. doi: 10.1175/JHM-D-14-0189.1, 2015.

Wang, S., Yang, Y., and Rivera, A.: Spatial and seasonal variations in actual evapotranspiration over Canada's landmass. *Hydrology and Earth System Sciences*, 17, 3561–3575. doi: 10.5194/hess-17-3561-2013, 2013.

Wang, S.: Freezing temperature controls winter water discharge for cold region watershed. *Water Resources Research*, 55, 10,479-10,493. doi: 10.1029/2019WR026030, 2019.

695 [Wang, S., Huang, J., Li, J., Rivera, A., McKenney, D.W., and Sheffield, J.: Assessment of water budget for sixteen large drainage basins in Canada. *Journal of Hydrology*, 512, 1-15. doi:10.1016/j.jhydrol.2014.02.058, 2014a.](#)

Deleted: Wahl, K.L. and Wahl, T.L.: Determining the flow of Comal Springs at New Braunfels, Texas, in Proceedings of Texas Water 95, August 16–17, 1995, San Antonio, Tex.: American Society of Civil Engineers, p. 77–86, 1995.¶

Deleted: :

705 Wang, S., McKenney, D.W., Shang, J., and Li, J.: A national scale assessment of long-term water budget closures for Canada's watersheds. *Journal of Geophysical Research: Atmospheres*, 119, 8712–8725, doi:10.1002/2014JD021951, 2014b.

Wang, S., Huang, J., Yang, D., Pavlic, G., and Li, J.: Longterm water budget imbalances and error sources for cold region drainage basins. *Hydrological Processes*, 29, 2125–2136. doi: 10.1002/hyp.10343, 2015.

Wang, S., Zhou, F., and Russell, H.A.J.: Estimating snow mass and peak river flows for the Mackenzie River basin using GRACE satellite observations. *Remote Sensing*, 9, 256. doi: 10.3390/rs9030256, 2017.

Wang, S. and Russell, H.A.J.: Forecasting snowmelt-induced flooding using GRACE satellite data: A case study for the Red River watershed. *Canadian Journal of Remote Sensing*, 42, 203-213. doi: 10.1080/07038992.2016.1171134, 2016.

710 Zhang, Y., Wang, S., Barr, A.G., and Black, T.A.: Impact of snow cover on soil temperature and its simulation in the EALCO model. *Cold Regions Science and Technology*, 52, 355-370. doi.org/10.1016/j.coldregions.2007.07.001, 2008.

Deleted: ¶

Formatted: Normal, Line spacing: single