



The value of satellite soil moisture and snow cover data for the transfer of hydrological model parameters to ungauged sites

Rui Tong^{1,2}, Juraj Parajka^{1,2}, Borbála Széles^{1,2}, Isabella Pfeil^{1,3}, Mariette Vreugdenhil³, Jürgen Komma², Peter Valent^{2,4} and Günter Blöschl^{1,2}

5 ¹Centre for Water Resource Systems, TU Wien, Vienna 1040, Austria

²Institute of Hydraulic Engineering and Water Resources Management, TU Wien, Vienna 1040, Austria

³Department of Geodesy and Geoinformation, TU Wien, Vienna 1040, Austria

⁴Department of Land and Water Resources Management, Slovak University of Technology in Bratislava, Bratislava 810 05, Slovakia

10

Correspondence to: Rui Tong (tong@hydro.tuwien.ac.at)

Abstract.

The recent advances in remote sensing provide opportunities for more reliably estimating the parameters of conceptual hydrologic models. However, the question of whether and to what extent the use of satellite data in model calibration may assist in transferring model parameters to ungauged catchments has not been fully resolved. The aim of this study is to evaluate the efficiency of different methods for transferring model parameters obtained by multiple objective calibrations to ungauged sites and to assess the model performance in terms of runoff, soil moisture, and snow cover predictions relative to existing regionalization approaches. The model parameters are calibrated to daily runoff, satellite soil moisture (ASCAT), and snow cover (MODIS) data. The assessment is based on 213 catchments situated in different physiographic and climate zones of Austria. For the transfer of model parameters, eight methods (global and local variants of arithmetic mean, regression, spatial proximity, and similarity) are examined in two periods, i.e., the period in which the model is calibrated (2000-2010) and an independent validation period (2010-2014). The predictive accuracy is evaluated by leave-one-out cross-validation. The results show that the method by which the model is calibrated in the gauged catchment has a larger impact on runoff prediction accuracy in the ungauged catchments than the choice of the parameter transfer method. The best transfer methods are global and local similarity and the kriging approach. The performance of the transfer methods differs between lowland and alpine catchments. While the soil moisture and snow cover prediction efficiencies are higher in lowland catchments, the runoff prediction efficiency is higher in alpine catchments. A comparison of model transfer methods based on parameters calibrated to runoff, snow cover, and soil moisture with those based on parameters calibrated to runoff only indicates that the former outperforms the latter in terms of simulating soil moisture and snow cover. The performance of simulating runoff is similar, and the accuracy depends mainly on the weight given to the runoff objective in the multiple objective calibrations.

15
20
25
30



1 Introduction

Prediction of runoff hydrographs is one of the main scientific and practical hydrological applications. Understanding and representation of the processes and their interactions during runoff generation and their sensitivity to the controls are one of the unsolved problems in hydrology (Blöschl et al., 2019). It is also essential for many purposes of societal relevance, such as engineering design, for water resources management, hydropower operation or for risk assessment (Sachs and McArthur, 2005; Blöschl and Montanari, 2010; Kovacs et al., 2012; Parajka et al., 2013). However, in most places of interest, no runoff data are directly observed, so the runoff prediction needs to be based on additional information observed in the region or transferred from other gauged catchments.

Numerous studies have explored and evaluated methods for prediction of runoff in ungauged sites (He et al., 2011; Hrachowitz et al., 2013; Blöschl et al., 2013). The most frequently used method consists of applying a hydrological model driven by model parameters derived in catchments with runoff observations. The review and synthesis of studies and applications of hydrological models in ungauged sites presented in Parajka et al. (2013) and recently Guo et al. (2021) indicate that there is a variety of transfer approaches tested in different parts of the world, covering different climates, altitudes or landscape settings. These studies' main outcome is that the runoff predictions in ungauged catchments tend to be more accurate in humid than in arid regions and more accurate in large than in small catchments (Parajka et al., 2013). However, the selection and performance of methods differ between studies, and there is no general recommendation for the choice of the approach. There seems to be a consensus that the spatial proximity and similarity methods perform better in humid regions (Guo et al., 2021). In arid catchments similarity and parameter regression methods tend to be applied more frequently and perform slightly better (Parajka et al., 2013; Yang et al. 2018, 2020).

Recent studies have explored the role and impact of gauge density on the efficiency of the methods (Parajka et al., 2015; Lebecherel et al., 2016; Neri et al. 2020), as well as the advanced definition of similarity measures based on spatial patterns (Li and Zhang, 2017; Beck et al., 2020; Narbondo et al., 2020), or catchment response characteristics (Tegegne and Kim, 2018). Along with these investigations, one of the recent focuses in hydrological modelling evaluates the use of observations additional to runoff (Bouaziz et al., 2021). Multiple objective calibrations can help constrain hydrological models, reduce uncertainty, and improve hydrological predictions (Efstratiadis and Koutsoyiannis, 2010). Most of the previous studies investigated the potential of calibrating hydrological model parameters by using different runoff signatures or using some additional hydrological characteristics such as snow cover, cover, soil moisture, evaporation, groundwater level or their combinations (please see the review in Tong et al., 2021). However, only a few studies have investigated the application of multiple objective approaches for evaluating the transfer of model parameters to ungauged sites. Parajka et al. (2005 and 2006), examined the value of snow depth observation and scatterometer soil moisture measurements for improving hydrological simulations in ungauged catchments and showed that the use of scatterometer resulted in more consistent patterns of soil moisture estimates, but it did not improve the runoff model efficiencies in ungauged catchments. Zhang et al. (2020) recently used remotely sensed evapotranspiration to calibrate the hydrological model parameters without streamflow observations and



found the streamflow-free calibration could be satisfactory for monthly and mean annual runoff simulation in the humid
65 catchments. Huang et al. (2020) verified the effectiveness of this approach for the regionalization with spatial proximity method
in ungauged basins. They reported that using the bias-corrected remotely sensed evapotranspiration has great potential in
estimating daily and monthly runoff. However, the role and impact of using additional data for the prediction of daily
hydrographs in ungauged sites are still not well understood. Such assessment is essential in particular for projecting impacts
of changing climate or land use conditions on the hydrological cycle in general and specifically on runoff generation. The aim
70 of this study is to investigate the value of using model parameters obtained by multiple objective calibrations for daily
hydrological predictions in ungauged sites. Specifically, we test the efficiency of different methods for transfer of such model
parameters to ungauged sites and evaluate the model performance to observations of runoff and remotely sensed estimates of
soil moisture and snow cover. We extend the results of Tong et al. (2021) who assessed the value of Metop ASCAT and
MODIS satellites for calibration of conceptual hydrological models and to test to what extent it improves the performance of
75 existing regionalization approaches. The analysis and comparison of model simulations of runoff, soil moisture and snow
cover are performed for a large sample of catchments situated in different physiographic and climate zones of Austria, so
allows evaluating the potential of the application of remotely sensed data at the regional scale.

2 Method

2.1 Hydrological model

80 The transfer of the model parameters is evaluated for a conceptual hydrological model (TUWmodel, Viglione and Parajka,
2020). The TUWmodel is a variant of the HBV model (Bergström 1992; Parajka et al., 2007) implemented in the R-
environment (Astagneau et al., 2020). This study uses a semi-distributed version in which the inputs and outputs of the model
are processed for elevation zones of 200 meters, but model parameters are assumed lumped in each catchment. We used a
single soil layer version of TUWmodel. It simulates changes in snow, root zone and groundwater storages in each elevation
85 zone. The model runs on a daily time step and combines three routines: snow routine, soil moisture routine, and river flow
routing routine. The snow routine uses a degree-day concept to reflect snow accumulation and melt with a degree-day factor
and a threshold melt temperature. The snowfall part of precipitation and snow accumulation is calculated by using snow and
rain threshold temperatures. The soil moisture routine represents changes in the soil moisture state of the root zone due to
evapotranspiration and runoff generation.

$$90 \quad S_{SM,i} = S_{SM,i-1} + (PR + M - E_A) \cdot \Delta t \quad (1)$$

where S_{SM} is the root zone soil moisture, which controls runoff generation and actual evaporation E_A , PR is rain, M is snowmelt,
and Δt is the time step (one day). The contribution ΔS_{UZ} of rain and snowmelt to runoff is calculated by an explicit scheme
as a function of the S_{SM} using a non-linear relationship controlled by two model parameters, maximum soil storage FC and
nonlinearity parameter $BETA$ controlling characteristics of runoff generation



$$95 \quad \Delta S_{UZ} = (\theta)^{BETA} (PR + M) \cdot \Delta t \quad (2)$$

$$\theta = \frac{S_{SM}}{FC} \quad (3)$$

Actual evapotranspiration is estimated from potential evaporation (model input) and a model parameter representing the soil moisture state above which the actual equals potential evaporation. For a comparison with satellite soil moisture estimates, simulated root zone soil moisture is scaled by the maximum soil moisture storage FC model parameter and represents hence
 100 the relative root zone soil moisture θ .

The runoff routing module represents routing on the hillslopes and river flow routing in the stream. The runoff response function consists of two reservoirs, representing the upper and lower storage zones. The outflows from reservoirs in each elevation zone is summed up and routed by a triangular transfer function.

The model involves 15 model parameters. They are automatically calibrated using the multi-objective calibration strategy of
 105 Tong et al., (2021). The joint objective function O_F consists of weighting three individual parts related to runoff (O_Q), soil moisture (O_{SM}), and snow cover (O_{SC}).

$$O_F = w_Q \cdot O_Q + w_{SM} \cdot O_{SM} + w_{SC} \cdot O_{SC} \quad (4)$$

where w_Q is the weight to the runoff objective function, w_{SM} and w_{SC} are the weights to the soil moisture and snow cover objectives, respectively. Multiple objective approaches for each regionalization method are examined for 11 runoff weights
 110 w_Q (ranging from 0.0 to 1.0 with a step of 0.1). The combinations of weights are taken from Tong et al. (2021), where the weights of soil moisture and snow are equal, and the total sum of all weights is 1.0. More details about the combinations of the objective functions are presented in Tong et al. (2021).

The runoff objective function O_Q emphasizes both high and low flows (Parajka and Blöschl, 2008) and is described by a
 115 logarithmic-transformed river flow values (Nash and Sutcliffe, 1970):

$$O_Q = 0.5 \cdot NSE + 0.5 \cdot NSE_{log} \quad (5)$$

$$NSE = 1 - \frac{\sum_{i=1}^n (Q_{obs,i} - Q_{sim,i})^2}{\sum_{i=1}^n (Q_{obs,i} - \overline{Q_{obs}})^2} \quad (6)$$

$$NSE_{log} = 1 - \frac{\sum_{i=1}^n (\log(Q_{obs,i}) - \log(Q_{sim,i}))^2}{\sum_{i=1}^n (\log(Q_{obs,i}) - \log(\overline{Q_{obs}}))^2} \quad (7)$$

where $Q_{obs,i}$ and $Q_{sim,i}$ are the river flow observation and simulation of day i .



- 120 The measure of soil moisture agreement (O_{SM}) is determined by the Pearson correlation coefficient (O_{SM}) between the satellite soil water index (SWI) and simulated relative soil moisture in each elevation zone:

$$O_{SM} = \frac{\sum_{i=1}^{N_{days}} \sum_{j=1}^{N_{zones}} ((\theta_{sim,i,j} - \overline{\theta_{sim}})(\theta_{obs,i,j} - \overline{\theta_{obs}}))}{\sqrt{\sum_{i=1}^{N_{days}} \sum_{j=1}^{N_{zones}} ((\theta_{sim,i,j} - \overline{\theta_{sim}})^2 (\theta_{obs,i,j} - \overline{\theta_{obs}})^2)}} \quad (8)$$

- where $\theta_{sim,i,j}$ is the simulated relative soil moisture from the hydrological model and $\theta_{obs,i,j}$ is the averaged value of the observed Soil Water Index (SWI) from ASCAT pixels for the day i and elevation zone j . $\overline{\theta_{sim}}$ and $\overline{\theta_{obs}}$ are the mean value of the simulations and observations for the days and elevation zones which are not masked in the ASCAT SWI product due to presence of snow or frozen ground. It assesses the correspondence of the satellite soil moisture (assumed as ground truth) and simulated time series. The use of O_{SM} has the advantage of not being sensitive to the units and it also allows comparison with the results of previous studies (e.g., Parajka et al., 2006; Gruber et al., 2020; Beck et al., 2021).

- 130 The snow cover objective function O_{SC} minimises the sum of snow overestimation S_O and underestimation S_U errors (Parajka and Blöschl, 2008):

$$O_{SC} = 1 - (S_O + S_U) \quad (9)$$

The snow overestimation error shows the percentage of the condition if the snow is simulated from the model, but the snow cover is not retrieved by the satellite (MODIS):

$$135 \quad S_O = \frac{1}{\sum_{i=1}^{N_{days}} \sum_{j=1}^{N_{zones}} A_{i,j}} \sum_{i=1}^{N_{days}} \sum_{j=1}^{N_{zones}} A_{i,j} \cap (SWE_{i,j} > \xi_{SWE}) \cap (SCA_{i,j} = 0) \quad (10)$$

where $A_{i,j}$ is the area of zone j that is cloud-free according to MODIS observation on the day i . $SWE_{i,j}$ is the simulated snow water equivalent in elevation zone j greater than 10mm (Parajka and Blöschl, 2008), $SCA_{i,j}$ is the MODIS snow covered area within this zone, and N_{days} is the number of days with cloud cover less than a threshold (ξ_C) 50%.

- The snow underestimation error indicates the percentage of the condition if no snow is simulated, but snow cover retrieved by the MODIS is over a threshold (ξ_{SCA}) of 25% in the zone, i.e.:

$$140 \quad S_U = \frac{1}{\sum_{i=1}^{N_{days}} \sum_{j=1}^{N_{zones}} A_{i,j}} \sum_{i=1}^{N_{days}} \sum_{j=1}^{N_{zones}} A_{i,j} \cap (SWE_{i,j} = 0) \cap (SCA_{i,j} > \xi_{SCA}) \quad (11)$$



2.2 Transfer of model parameters to ungauged sites

The hydrological predictions at the ungauged sites are, in this study, based on model simulations driven by model parameters transferred from the gauged locations where the model has been calibrated, i.e. the sites with runoff observations. For the transfer (i.e. regionalization), four groups of methods are evaluated (Table 1). The first group estimates model parameters as the arithmetic mean of all calibrated values in the study region (termed “global mean”) or, alternatively, as the arithmetic mean of model parameters within a radius of 50 km from the catchment of interest (termed “local mean”). This arithmetic mean regionalization approach assumes similarity of all catchments within a specified radius where differences in the parameter values are caused only by random factors.

In the second group, the model parameters for ungauged sites are independently estimated from linear regressions between calibrated model parameters and catchment attributes. Similarly, as in the first group, two approaches are tested. The global multiple linear regression uses attributes and model parameters from all gauged catchments. The local multiple linear regression is applied within a 50 km search radius from an ungauged site. In all cases, the regression coefficients are estimated by the ordinary least squares method. For consistency with previous studies, a set of three catchment attributes associated with the largest multiple correlation coefficient for each ungauged site and each model parameter is used. To avoid multicollinearity, the variance inflation factor (Hirsch et al., 1992) is examined. For the transfer of model parameters, such a regression model is used, which has the largest correlation coefficient for the inflation factor less than 10.

The third group of transfer methods is based on the spatial proximity (or spatial distance) between the ungauged and the gauged catchments. The spatial distance between the two catchments is characterized by the distance between the respective catchment centroids. We test two methods of this group: the inverse distance weighting and the ordinary kriging. In both methods, individual parameters from several donor catchments are independently interpolated to a centroid of the ungauged catchment and then combined and used in the hydrological model. The power parameter in inverse distance interpolation is set to two. The ordinary kriging method is based on a fixed exponential variogram with a nugget of 10% of the observed variance, a sill equal to the variance, and a range of 60 km. The test calculations in previous studies (Merz and Blöschl, 2004; Parajka et al., 2005) showed that this setting is consistent with the empirical variograms of most of the calibrated model parameters.

The fourth group of methods is based on the similarity between catchments with runoff observations and ungauged sites. The main idea of the similarity group of methods is to find for an ungauged site a donor catchment that is most similar in terms of certain catchment attributes. The entire collection of model parameters calibrated for a donor catchment is then transferred to the ungauged site. The similarity is defined by a similarity index Φ (Burn and Boorman, 1993; Merz and Blöschl, 2004),

$$\Phi = \sum_{i=1}^k \frac{|x_i^G - x_i^U|}{\Delta x_i} \quad (12)$$

where X^G represents a vector of the normalized catchment attributes of the gauged (donor) catchments; X^U are the normalized attributes of the ungauged catchment; and ΔX is the normalized range of attributes. In previous studies (e.g. Parajka et al., 2005) a large number of catchment attributes and their combination have been tested in the study region. Based on the results and preliminary analyses (not shown here) for this study, we selected the approach with the best results. This variant is based



180 on an *a priori* defined combination of the following catchment attributes: mean catchment elevation, stream network density, lake attenuation index and areal proportion of porous aquifers, land use, soils and geologic units. Similar to other approaches, also in this approach, we examine two variants. While the global similarity combination uses all study catchments for estimation of the similarity, the local similarity combination estimates the similarity only within 50 km radius around the ungauged site.

Table 1 The list of model parameter transfer methods tested in the study.

Group	Transfer method	Abbreviation
Arithmetic mean	Global mean	GM
	Local mean	LM
Regression	Global regression	GR
	Local regression	LR
Spatial proximity	Inverse distance weighting	ID
	Kriging	KR
Similarity	Global combination of physiographic attributes	GS
	Local combination of physiographic attributes	LS

185 2.3 Evaluation of the prediction accuracy

The performance and efficiency of parameter transfer methods are evaluated by leave-one-out cross validation. Each catchment with observed runoff is considered in turn as ungauged and the transfer methods are used to estimate the parameter sets from other gauged catchments. The hydrological model is applied to simulate daily runoff, soil moisture and snow cover in the ungauged catchment. These simulations are then compared with the observations. The accuracy is quantified by three objectives O_Q , O_{SM} , and O_{SC} in two periods, i.e. in the period used for model calibration (2000-2010, 2007-2010 for O_{SM}) and in an independent validation period (2010-2014). The efficiencies of the transferred model parameters are estimated for eleven different calibration variants (i.e. weight given to runoff) and compared to the efficiency obtained by a transfer of model parameters calibrated to runoff only.

3 Data

195 3.1 Study region

The study region is Austria which represents a wide range of physiographic conditions. The topography varies from flat land in the East and North to Alpine terrain in the West and South. Mean annual precipitation is less than 400 mm/year in the East



and more than 2500 mm/year in the West. Land use is mainly agricultural in the lowlands and forest in the medium elevation ranges. Alpine vegetation and rocks prevail in the highest alpine regions.

200 The analysis is carried out for 213 catchments (Fig. 1). These catchments have been selected following previous studies (Viglione et al., 2013, Sleziaik et al., 2020, Tong et al., 2021) and represent catchments with no significant anthropogenic effects on the water balance. The size of the catchments ranges from 13.7 to 6214 km² and the averaged slope varies from 1.74% to 43.91%. As previous studies have shown that the performance of regionalization methods differs between climatic zones (Parajka et al., 2013; Yang et al., 2020), separation of the effect of elevation and climate on the results was deemed
205 important and the catchments were split into two groups representing drier lowland and hilly regions (catchments with mean elevation below 900 m a.s.l.) and wetter alpine conditions (catchments with mean elevation above 900 m a.s.l.). Out of the 213 catchments, 94 are classified as lowland catchments, and 119 as alpine catchments (Fig. 1). The threshold of 900 m is chosen as a compromise between balancing the number of catchments in the groups and representing different physiographic regions.

210

[Figure 1]

3.2 Hydrologic and climate data

The runoff data have been obtained from Central Hydrographical Bureau (HZB, ehyd.gv.at). The analysis period is from Sep. 2000 to Aug. 2014, which is split into the calibration (September 2000-August 2010) and validation periods (September 2010-August 2014).

215

Model inputs (i.e. mean of daily climate characteristics for elevation zones) are derived from the SPARTACUS gridded dataset (Hiebl and Frei, 2016, 2018). This dataset includes grid maps of maximum and minimum daily air temperature and precipitation with a spatial resolution of 1km. Daily mean air temperature is estimated as the mean between minimum and maximum air temperature. Potential evaporation model input is estimated by the Blaney-Criddle approach (Parajka et al.,
220 2003). This approach estimates potential evaporation from mean daily air temperature and a potential sunshine duration index, which is calculated from a 1 km digital elevation model of Austria.

3.3 MODIS snow cover

The snow cover maps used in model calibration and regionalization validation are based on the combination of the daily, 500m resolution, Terra (MOD10A1) and Aqua (MYD10A1) MODIS datasets (Hall and Riggs, 2016a, 2016b). We use the latest
225 collection 6 snow cover products, which includes the Normalized Difference Snow Index (NDSI). Snow cover mapping from MODIS products is performed in two steps. In the first step, NDSI pixels are classified into snow and land cover classes based on seasonally varying NDSI thresholds (Tong et al., 2020). In the second step, resulting the snow cover maps from Aqua and Terra products are combined to reduce the impact of clouds (Parajka and Blöschl, 2008). Finally, for each elevation zone of



each catchment, the frequency of pixels classified as clouds, snow and land is calculated. This allows estimating the percent
230 snow cover area of each catchment needed for the calculation of the snow cover model objective function.

3.4 ASCAT soil moisture

The satellite soil moisture data used in this study is the Soil Water Index (SWI) derived from an experimental version of the
upcoming Disaggregated Metop ASCAT Surface Soil Moisture v2 product (H28) provided by the EUMETSAT Satellite
Application Facility on Support to Operational Hydrology and Water Management (H SAF). The original ASCAT surface soil
235 moisture dataset at 12.5 km (before disaggregation) is based on a new parameterization for the vegetation correction (Hahn et
al., 2020), which has shown improved performance over Austria (Pfeil et al., 2018). The disaggregation process consists of a
directional resampling method utilizing the connection between regional (12.5 km) and local (0.5 km) scale Sentinel-1
backscatter observations describing temporally stable soil moisture patterns also reflected in the radar backscatter
measurements (Wagner et al. 2008). Surface and root zone soil moisture are available, where the root zone soil moisture is
240 represented by the Soil Water Index (SWI), which is determined by an exponential filter introduced by Wagner et al. (1999a,b)
and Albergel et al. (2008) with a characteristic time lag (T). The T-value represents the smoothing of soil moisture dynamics
by infiltration, with higher T-values corresponding to a higher degree of smoothing. In order not to lose information on short-
term soil moisture dynamics still present in deeper soil layers, T should be carefully chosen. Paulik et al (2014) compared the
ASCAT SWI dataset to in situ soil moisture and found that the SWI agrees better with in situ soil moisture from deeper layers
245 than the original surface soil moisture dataset. Moreover, they related the T-value with soil depth layers and found that the T-
values 10 and 20 led to the highest correlations in the shallow subsurface (around 0-20 cm). To prevent the loss of short-term
soil moisture dynamics, T-value=10 days was selected in this study. Besides, to exclude invalid ASCAT measurements
affected by snow and frozen ground, soil moisture is masked using soil temperature and snow cover from the ECMWF
Copernicus Climate Service (C3S) ERA5-Land, when soil temperatures at a soil depth of 0-7 cm are below 1°C or snow cover
250 exceeds 30 % of the pixel.

4 Results

4.1 Efficiency of transfer methods to simulate runoff

Figure 2 shows the median of runoff leave-one-out cross-validation efficiency for eight parameter transfer methods (panels)
and 11 calibration variants (i.e. different runoff weight w_Q used in model calibration) in the calibration (blue symbols) and
255 validation (red symbols) period. Panels on the left and right show the results for the lowland and alpine group of catchments,
respectively. The results for the runoff weight $w_Q = 1.0$ represent the case when the model is calibrated to runoff only. The
case $w_Q = 0.0$ represents the case when the model is calibrated to satellite soil moisture and snow cover without using observed
runoff.



260 The results show that the differences between the transfer methods are smaller than those between the different calibration
variants, i.e. the different methods of calibrating the model in gauged catchments, for weights below 0.4. The impact of the
choice of calibration variant (weight on runoff w_Q) is smaller if the w_Q is larger than 0.4. In this case, the differences between
the transfer methods are larger, and the choice of transfer method is more important than that of the calibration variant. The
worst parameter transfer (i.e. regionalisation) methods are the global mean and the local regression approach. The median of
runoff efficiency is particularly low, i.e. between 0.24 and 0.41, for calibration variants using $w_Q < 0.3$ in the calibration period.
265 If w_Q is larger than 0.7, the median of runoff efficiency of global mean and local regression is between 0.42 and 0.5 for the
lowland and between 0.61-0.63 for the alpine catchments. The best transfer methods are global and local similarity and kriging
interpolation. If the w_Q is larger than 0.4, the median efficiency is between 0.67 and 0.69 in the lowland and between 0.71 and
0.74 in the alpine region. The efficiency of the transfer of model parameters calibrated by multiple objective approaches (for
 $w_Q > 0.4$) for the similarity and kriging methods is the same as that for the transfer of model parameters obtained by calibration
270 to runoff only ($w_Q = 1$). In the validation period, the median of multiple objective calibrations ($w_Q = 0.8$) of kriging in the lowland
and similarity in the alpine catchments is even larger than the runoff efficiency obtained by a transfer (kriging or similarity)
based on parameters calibrated to runoff only (variant $w_Q = 1$). Additionally, Table 2 also shows that the regional variability
(runoff model efficiency between catchments) is small for kriging while large for local regression methods. A comparison of
local and global variants of the transfer methods indicates that the local methods are only slightly better than the global methods
275 in terms of runoff efficiency. The largest difference occurs for the mean approach, but the runoff efficiency of the local mean
is noticeably lower than for the spatial proximity or similarity approaches. An exception is the regression of model parameters,
which has a larger runoff efficiency for the global than the local approach. The results also show that the performance of
transfer methods is better in the alpine than in the lowland catchments. In both groups, however, similarity and kriging are the
best approaches for predicting daily runoff.

280

[Figure 2]

285

290



Table 2. Scatter (difference of 75% and 25% quantiles of model efficiency) of leave-one-out runoff model efficiency (Eq. 5) obtained by eight groups of parameter transfer methods and eleven calibration weights for lowland (94) and alpine (119) catchments in the calibration (2000-2010, first value) and validation (2010-2014, second value) periods.

w_Q	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
Lowlands	GM	0.17/0.32	0.22/0.56	0.25/0.47	0.23/0.39	0.22/0.34	0.21/0.34	0.22/0.35	0.21/0.32	0.21/0.31	0.20/0.30	0.21/0.31
	LM	0.32/0.29	0.15/0.27	0.15/0.22	0.14/0.24	0.15/0.23	0.15/0.19	0.19/0.21	0.17/0.22	0.16/0.25	0.17/0.25	0.18/0.27
	GR	0.26/0.28	0.27/0.66	0.18/0.37	0.25/0.37	0.22/0.33	0.20/0.31	0.24/0.38	0.18/0.24	0.17/0.21	0.15/0.26	0.17/0.32
	LR	0.94/1.82	0.51/0.85	0.88/1.45	0.56/0.72	0.56/0.55	1.10/1.61	0.63/1.05	0.68/1.15	0.58/0.86	0.61/0.84	0.61/0.84
	ID	0.23/0.30	0.13/0.29	0.13/0.25	0.14/0.22	0.14/0.20	0.15/0.23	0.15/0.23	0.15/0.21	0.15/0.23	0.15/0.22	0.16/0.23
	KR	0.45/0.47	0.13/0.19	0.12/0.16	0.13/0.16	0.13/0.15	0.15/0.19	0.14/0.18	0.12/0.17	0.12/0.18	0.13/0.18	0.13/0.21
	GS	0.50/0.57	0.12/0.15	0.12/0.13	0.14/0.15	0.15/0.12	0.15/0.13	0.16/0.12	0.17/0.11	0.17/0.11	0.17/0.11	0.17/0.13
	LS	0.53/0.57	0.12/0.15	0.12/0.14	0.14/0.16	0.15/0.14	0.15/0.13	0.16/0.12	0.16/0.11	0.17/0.12	0.17/0.11	0.17/0.12
Alpine	GM	0.22/0.29	0.21/0.26	0.18/0.24	0.20/0.26	0.18/0.23	0.19/0.24	0.18/0.25	0.19/0.24	0.19/0.23	0.19/0.22	0.18/0.22
	LM	0.29/0.35	0.23/0.24	0.19/0.19	0.18/0.19	0.14/0.17	0.15/0.18	0.15/0.18	0.15/0.19	0.15/0.20	0.15/0.19	0.15/0.19
	GR	0.29/0.35	0.26/0.25	0.20/0.24	0.18/0.24	0.19/0.21	0.18/0.18	0.19/0.17	0.19/0.17	0.20/0.19	0.16/0.16	0.17/0.18
	LR	0.96/0.99	0.51/0.59	0.61/0.61	0.58/0.61	0.45/0.46	0.35/0.37	0.38/0.51	0.37/0.43	0.57/0.71	0.38/0.45	0.48/0.53
	ID	0.24/0.34	0.25/0.25	0.21/0.21	0.19/0.19	0.16/0.19	0.16/0.17	0.16/0.18	0.15/0.17	0.17/0.17	0.16/0.18	0.15/0.17
	KR	0.33/0.46	0.21/0.23	0.18/0.20	0.15/0.18	0.13/0.16	0.12/0.16	0.11/0.15	0.11/0.17	0.11/0.15	0.11/0.15	0.11/0.14
	GS	0.48/0.59	0.24/0.22	0.21/0.22	0.17/0.20	0.14/0.17	0.16/0.19	0.17/0.21	0.16/0.22	0.17/0.20	0.17/0.21	0.18/0.23
	LS	0.50/0.53	0.23/0.20	0.22/0.22	0.17/0.18	0.13/0.16	0.16/0.17	0.15/0.20	0.16/0.18	0.16/0.19	0.14/0.19	0.16/0.21

295

4.2 Efficiency of transfer methods to simulate soil moisture

The evaluation of eight parameter transfer methods to simulate root zone soil moisture is presented in Fig. 3. The results show the median correlation between the satellite root zone soil moisture index and simulated relative root zone soil moisture in lowland (left two panels) and alpine (right two panels) catchments. The comparison of different transfer methods and calibration variants indicates that the difference between the transfer methods is similar as that found for the prediction of daily runoff. The best transfer methods are kriging and similarity (local and global) approaches. In the lowland catchments, the median of soil moisture correlation ranges between 0.62 and 0.70 for these methods. The impact of the calibration variants is, for each transfer method, smaller than found for runoff. Generally, the correlation increases with decreasing w_Q and the soil moisture agreement tends to be larger if the w_Q is smaller than 0.4. A much smaller agreement (correlation) between soil moisture estimates is found in the alpine catchments. Also here, the best transfer methods are local and global similarity and kriging, but the median correlation varies only between 0.14 and 0.22. From Table 3, the regional variability of soil moisture correlation is similar for each method and larger in the lowlands than that in the alpine regions. The comparison between the correlations of the calibration and validation periods shows a similar pattern. Interestingly, in the alpine catchments, the

300

305



validation period correlations are slightly higher than those found for the transfer in the calibration period. This is likely related
 310 to the warmer validation period. Warming decreases snow cover area particularly in the alpine regions and hence decreases
 the frequency of pixels which need to be masked in the soil moisture dataset.

[Figure 3]

315 **Table 3. Scatter (difference of 75% and 25% quantiles of model efficiency) of leave-one-out soil moisture correlation (Eq. 8) obtained
 by eight groups of parameter transfer methods and eleven calibration weights for lowland (94) and alpine (119) catchments in the
 calibration (2007-2010, first value) and validation (2010-2014, second value) periods.**

w_Q	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
Lowlands	GM	0.24/0.22	0.24/0.22	0.25/0.22	0.25/0.23	0.26/0.24	0.26/0.23	0.27/0.24	0.28/0.24	0.28/0.24	0.29/0.24	0.28/0.24
	LM	0.30/0.31	0.31/0.28	0.32/0.28	0.32/0.29	0.32/0.29	0.32/0.28	0.32/0.28	0.31/0.26	0.31/0.26	0.31/0.25	0.30/0.25
	GR	0.29/0.24	0.23/0.26	0.29/0.26	0.29/0.31	0.27/0.27	0.30/0.23	0.30/0.27	0.30/0.25	0.30/0.25	0.30/0.24	0.28/0.24
	LR	0.28/0.26	0.27/0.24	0.27/0.22	0.30/0.25	0.31/0.29	0.34/0.34	0.33/0.31	0.27/0.25	0.27/0.25	0.30/0.29	0.30/0.29
	ID	0.29/0.27	0.28/0.27	0.28/0.27	0.29/0.28	0.30/0.28	0.30/0.28	0.29/0.28	0.29/0.25	0.31/0.24	0.30/0.24	0.29/0.24
	KR	0.29/0.26	0.29/0.26	0.29/0.27	0.29/0.26	0.29/0.27	0.29/0.28	0.29/0.29	0.28/0.25	0.31/0.25	0.29/0.25	0.30/0.26
	GS	0.29/0.26	0.30/0.28	0.30/0.27	0.30/0.26	0.30/0.26	0.30/0.27	0.31/0.28	0.30/0.27	0.30/0.26	0.30/0.24	0.27/0.25
	LS	0.29/0.26	0.31/0.28	0.31/0.27	0.30/0.27	0.31/0.26	0.30/0.27	0.31/0.28	0.31/0.27	0.33/0.27	0.31/0.26	0.31/0.27
Alpine	GM	0.23/0.19	0.23/0.18	0.23/0.19	0.24/0.19	0.24/0.19	0.23/0.20	0.23/0.20	0.23/0.19	0.23/0.19	0.23/0.19	0.22/0.19
	LM	0.26/0.25	0.20/0.25	0.18/0.25	0.17/0.26	0.17/0.26	0.21/0.26	0.19/0.26	0.20/0.26	0.21/0.24	0.21/0.24	0.22/0.23
	GR	0.22/0.21	0.16/0.25	0.14/0.39	0.15/0.37	0.17/0.26	0.18/0.28	0.20/0.24	0.16/0.25	0.20/0.28	0.20/0.22	0.19/0.24
	LR	0.27/0.32	0.22/0.30	0.17/0.37	0.19/0.37	0.16/0.34	0.20/0.30	0.22/0.30	0.21/0.39	0.16/0.37	0.16/0.35	0.15/0.34
	ID	0.25/0.24	0.24/0.25	0.21/0.26	0.20/0.25	0.17/0.24	0.21/0.27	0.23/0.28	0.22/0.28	0.21/0.25	0.20/0.23	0.21/0.22
	KR	0.23/0.29	0.20/0.29	0.21/0.28	0.21/0.29	0.19/0.27	0.21/0.30	0.22/0.28	0.19/0.28	0.21/0.26	0.20/0.25	0.21/0.23
	GS	0.24/0.29	0.20/0.28	0.23/0.25	0.18/0.25	0.16/0.24	0.17/0.23	0.18/0.23	0.18/0.24	0.18/0.21	0.17/0.20	0.17/0.19
	LS	0.22/0.31	0.20/0.28	0.24/0.26	0.20/0.25	0.18/0.24	0.19/0.25	0.20/0.24	0.20/0.24	0.20/0.21	0.19/0.21	0.16/0.19

4.3 Efficiency of transfer methods to simulate snow cover

320 The efficiency of eight transfer methods to simulate snow cover is evaluated in Fig.4. The results indicate the smallest
 difference in snow efficiency between the transferred methods. A much larger difference and impact on snow efficiency is
 linked to the weight used in model calibration. The difference in snow efficiency between transfer methods for the same w_Q
 is mostly between 1 and 3%, but the snow efficiency for different w_Q (and the same transfer method) ranges between 8 and
 17%. The snow efficiency decreases with increasing w_Q , and it is generally larger in the lowland than in the alpine catchments.
 325 Interestingly, in the alpine catchments, the similarity-based approaches and kriging have the smallest efficiency, and the most



accurate results are obtained by the global mean and global regression methods. At the same time, the regional variability of the snow model efficiencies (Table 4) has a small difference between different w_Q . Also indicated in the table 4, the local regression method performed relatively unstable for simulating snow, and in the Alpine regions the regional variability of snow model efficiency is larger than that in the lowlands. The impact of the calibration variant is, however, much more important than the selection of transfer method. The comparison between calibration and validation periods indicates an overall larger snow efficiency in the validation period. This is likely linked with a warmer validation period and generally fewer days with snow cover associated with an increase in air temperature in the last decades (Duethmann and Blöschl, 2018).

[Figure 4]

Table 4. Scatter (difference of 75% and 25% quantiles of model efficiency) of leave-one-out snow model efficiency (Eq. 9) obtained by eight groups of parameter transfer methods and eleven calibration weights for lowland (94) and alpine (119) catchments in the calibration (2000-2010, first value) and validation (2010-2014, second value) periods.

w_Q	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
Lowlands	GM	0.05/0.02	0.05/0.03	0.06/0.04	0.06/0.05	0.06/0.05	0.06/0.06	0.06/0.06	0.06/0.06	0.06/0.06	0.06/0.06	0.06/0.06
	LM	0.04/0.03	0.04/0.02	0.06/0.04	0.07/0.05	0.08/0.07	0.08/0.07	0.08/0.07	0.08/0.07	0.08/0.06	0.07/0.07	0.06/0.07
	GR	0.05/0.03	0.05/0.02	0.06/0.04	0.07/0.06	0.06/0.06	0.06/0.06	0.07/0.07	0.06/0.06	0.07/0.06	0.07/0.06	0.07/0.07
	LR	0.04/0.03	0.05/0.03	0.07/0.05	0.10/0.07	0.13/0.12	0.10/0.09	0.09/0.07	0.08/0.09	0.10/0.09	0.09/0.08	0.09/0.08
	ID	0.04/0.03	0.04/0.02	0.06/0.04	0.06/0.05	0.06/0.05	0.06/0.05	0.06/0.05	0.07/0.06	0.07/0.06	0.07/0.06	0.07/0.06
	KR	0.04/0.02	0.04/0.02	0.06/0.04	0.06/0.05	0.06/0.05	0.06/0.05	0.06/0.05	0.07/0.05	0.07/0.05	0.07/0.05	0.07/0.06
	GS	0.04/0.03	0.04/0.03	0.07/0.04	0.07/0.05	0.06/0.05	0.07/0.05	0.07/0.05	0.06/0.05	0.07/0.05	0.07/0.05	0.07/0.06
	LS	0.04/0.03	0.04/0.03	0.07/0.04	0.07/0.05	0.06/0.05	0.06/0.05	0.07/0.05	0.07/0.06	0.07/0.06	0.08/0.06	0.07/0.06
	Alpine	GM	0.09/0.08	0.09/0.08	0.10/0.09	0.12/0.10	0.12/0.11	0.13/0.11	0.13/0.12	0.13/0.12	0.13/0.12	0.13/0.12
LM		0.10/0.10	0.12/0.11	0.13/0.12	0.15/0.12	0.15/0.13	0.16/0.14	0.17/0.14	0.17/0.14	0.17/0.14	0.16/0.14	0.16/0.14
GR		0.11/0.11	0.11/0.11	0.14/0.12	0.14/0.12	0.15/0.12	0.15/0.13	0.16/0.15	0.17/0.15	0.16/0.15	0.16/0.14	0.15/0.14
LR		0.14/0.12	0.17/0.14	0.20/0.19	0.17/0.14	0.18/0.17	0.18/0.18	0.19/0.18	0.20/0.18	0.16/0.16	0.17/0.15	0.18/0.17
ID		0.10/0.11	0.13/0.12	0.15/0.14	0.16/0.13	0.16/0.14	0.16/0.14	0.16/0.14	0.16/0.14	0.16/0.14	0.16/0.14	0.16/0.14
KR		0.11/0.11	0.14/0.14	0.17/0.15	0.17/0.14	0.16/0.15	0.16/0.16	0.16/0.15	0.15/0.14	0.16/0.15	0.17/0.15	0.16/0.14
GS		0.11/0.10	0.15/0.14	0.16/0.16	0.18/0.15	0.17/0.14	0.16/0.14	0.16/0.14	0.17/0.14	0.14/0.13	0.16/0.13	0.16/0.14
LS		0.11/0.10	0.14/0.13	0.16/0.15	0.18/0.16	0.18/0.14	0.17/0.14	0.17/0.15	0.17/0.14	0.16/0.13	0.16/0.13	0.15/0.13

4.4 Improvement of multi objective regionalization vs runoff only regionalization

This section analyses the impact of calibration and runoff weight on the efficiency of different transfer methods to simulate runoff, soil moisture and snow cover. We compared the efficiencies between predictions obtained by transferring model parameters obtained by multiple-objective calibration (i.e. $w_Q < 1$) and by parameters calibrated to runoff only ($w_Q = 1$). Positive



efficiency values thus mean an improvement when using a multiple-objective calibration compared to a runoff-only calibration. The results are shown in Fig. 5 for the calibration period and in Fig. 6 for the validation period. Figure 5 and 6 show the relative
345 improvement in snow cover (x-axis), soil moisture (y-axis) and runoff (colour of symbol) efficiencies for eight transfer methods (panels) and ten calibration weights (symbol size) in the lowland (left) and alpine (right) catchments. The results show that the runoff predictions are very similar (i.e. within 1% range) if the runoff weight is larger than 0.5. The largest impact of the multiple objective calibration is found for the soil moisture prediction, where the improvement is larger than for snow cover. In the lowland catchments, the soil moisture improvement is about 1 to 7% for w_Q larger than 0.4. In the case of
350 snow cover, the improvement is within 5% when w_Q larger than 0.4. The patterns of improvement for the best transfer methods (kriging and similarity approaches) are very similar. The improvement increases with decreasing runoff weight but at the expense of decreasing runoff efficiency. The largest improvement of soil moisture (i.e. over 25%) is found for the similarity approaches in the alpine catchments, but the overall soil moisture efficiency is rather low. The patterns of improvement are very consistent with those obtained for the transfer of model parameters in the validation period (Fig 6). The improvement in
355 soil moisture and snow cover increases with decreasing of runoff weight and the improvement is larger in the alpine than the lowland catchments.

[Figure 5]

360

[Figure 6]

5 Discussion and conclusion

The main aim of the study was to test to what extent satellite data can improve the prediction of daily runoff in ungauged catchments. Tong et al. (2021) showed that ASCAT and MODIS satellites in hydrological model calibration improve
365 simulations of a conceptual hydrological model, and that the improvements of runoff and soil moisture simulations were larger in low elevation and agricultural catchments. Here, we tested different methods for transferring model parameters from gauged to ungauged sites in the study region (Merz and Blöschl, 2004, Parajka et al., 2005). We examined which method and to what extent transferring model parameters calibrated to different objectives improves the prediction of runoff, soil moisture and snow cover at ungauged sites. The results showed that the improvement is largest in the simulation of soil moisture and snow
370 cover without a significant impact on runoff prediction accuracy. The assessment of the efficiencies of the different transfer methods indicates that the similarity approach and kriging of model parameters are the best in the study region. This finding is in line with that of Yang et al. (2020) who concluded that the spatial proximity and similarity approaches are relatively better than the parameter average or regression method in Norwegian catchments. This finding is also entirely consistent with the results of Parajka et al. (2005), who calibrated the model parameters in a larger number of catchments but using only runoff



375 and interpolated snow depth (but not soil moisture). While in this study we examined all 30 transfer approaches of Parajka et
al. (2005), for clarity, we present only the results for the main transfer approaches. The results and efficiency of other similarity
combinations tested in Parajka et al. (2005) are slightly lower or very similar in terms of runoff, soil moisture and snow cover
efficiency. The efficiency of global and local regression and arithmetic mean methods are very similar, even though here we
use 107 catchments (33%) fewer than tested in Parajka et al. (2005). Overall, the lower prediction accuracy of global mean or
380 local regression is also consistent with the global assessment of the accuracy of the transfer methods presented in Parajka et
al. (2013).

The results of Tong et al. (2021) show that using only satellite soil moisture and snow cover data is not sufficient for calibrating
a conceptual hydrological model in ungauged catchments. The lower runoff accuracy of the calibration variants with no or
only small weight to runoff is also reflected in the performance of the transfer methods. Satellite soil moisture and snow cover
385 data are very useful for constraining model parameters related to the simulation of snow cover and soil moisture (Nijzink et
al., 2018, Tong et al., 2021). However, the use of runoff is still essential for the accurate prediction of the complete runoff
hydrographs. This finding agrees with the previous assessment of using soil moisture estimates from ERS scatterometer
observations to improve hydrological simulations in gauged and ungauged catchments (Parajka et al., 2006). The scatterometer
data assimilation did not improve the prediction in ungauged sites but provided more consistent patterns of soil moisture
390 estimates. The use of the experimental disaggregated ASCAT dataset showed that the detailed spatial and temporal resolution
of satellite soil moisture improves the application and agreement of soil moisture estimates in smaller lowland catchments.
Similarly, as found in Széles et al. (2020) for a small Austrian catchment, the use of soil moisture data has a larger impact on
the overall consistency of the model simulations compared to snow cover observations.

This study suggests that the future evaluation of the transfer of model parameters to ungauged sites will benefit from examining
395 what type of information will improve the calibration and transfer of model parameters related to the runoff generation and
routing. It will also be interesting to examine the role of nested catchments in parameter transfer and the impact of streamgauge
density on the results. A suitable choice of a combination of estimated runoff signatures and satellite observations is also one
of the possible future research directions. The results of this study show that the recent advances in remote sensing of water
balance components may indeed contribute to improving the predictions of daily hydrographs in ungauged catchments.

400

Data availability

The streamflow observation data can be obtained from HZB (<https://ehyd.gv.at/>), BMLRT, 2021). The meteorological data
from the ZAMG are currently not open to the public, requests should be sent to klima@zamg.ac.at. The ASCAT soil moisture
data is available via Copernicus Global Land Service (<https://land.copernicus.eu/>). MODIS C6 snow cover products are from
405 NASA National Snow & Ice Data Center (<https://nsidc.org/>). Processed ASCAT SWI and MODIS snow cover maps used in
this study are available upon request. Landuse information is from Copernicus Land Monitoring Service
(<https://land.copernicus.eu/>). The R package of TUWmodel can be downloaded from CRAN ([https://cran.r-
project.org/web/packages/TUWmodel/index.html](https://cran.r-project.org/web/packages/TUWmodel/index.html)).



410 **Author contribution**

RT and JP conceived and designed the study, wrote the codes, performed the analyses, and prepared the manuscript. BS, JK and PV were responsible for the data management, including quality control, processing, and validating. IP and MV were responsible for developing, processing and validation of the ASCAT soil moisture data. GB supervised the study and contributed to the study design and interpretation of the results. All authors took part in the discussion of the results and
415 revisions of the paper.

Competing interests

The authors declare that they have no conflict of interest.

420 **Acknowledgment**

The authors would like to acknowledge financial support provided by the Austrian Science Funds (FWF) as part of the Vienna Doctoral Program on Water Resource Systems (DK W1219-N28), the Austrian Research Promotion Agency (FFG) through the BMon project (Contract No. 866031). They would like to thank Sebastian Hahn for his support in developing and processing the ASCAT soil moisture data. Rui Tong is grateful for the scholarship from China Scholarship Council (CSC).
425

References

- Albergel, C., Rüdiger, C., Pellarin, T., Calvet, J. C., Fritz, N., Froissard, F., Suquia, D., Petitpa, A., Pignatelli, B., and Martin, E.: From near-surface to root-zone soil moisture using an exponential filter: an assessment of the method based on in-situ observations and model simulations, *Hydrol. Earth Syst. Sci.*, 12, 1323-1337, <https://doi.org/10.5194/hess-12-1323-2008>, 2008.
430
- Astagneau, P. C., Thirel, G., Delaigue, O., Guillaume, J. H. A., Parajka, J., Brauer, C. C., Viglione, A., Buytaert, W., and Beven, K. J.: Hydrology modelling R packages: a unified analysis of models and practicalities from a user perspective, *Hydrol. Earth Syst. Sci. Discuss.*, 2020, 1-48, <https://doi.org/10.5194/hess-2020-498>, 2020.
- Beck, H. E., Pan, M., Lin, P., Seibert, J., van Dijk, A. I. J. M., and Wood, E. F.: Global Fully Distributed Parameter Regionalization Based on Observed Streamflow From 4,229 Headwater Catchments, *Journal of Geophysical Research: Atmospheres*, 125, e2019JD031485, <https://doi.org/10.1029/2019JD031485>, 2020.
435
- Beck, H. E., Pan, M., Miralles, D. G., Reichle, R. H., Dorigo, W. A., Hahn, S., Sheffield, J., Karthikeyan, L., Balsamo, G., Parinussa, R. M., van Dijk, A. I. J. M., Du, J., Kimball, J. S., Vergopolan, N., and Wood, E. F.: Evaluation of 18 satellite- and model-based soil moisture products using in situ measurements from 826 sensors, *Hydrol. Earth Syst. Sci.*, 25, 17-40, [10.5194/hess-25-17-2021](https://doi.org/10.5194/hess-25-17-2021), 2021.
440



- Bergström S: The HBV model—its structure and applications. Report No. 4, Swedish Meteorological and Hydrological Institute, 1992.
- Blöschl, G., and Montanari, A.: Climate change impacts—throwing the dice?, *Hydrological Processes*, 24, 374-381, <https://doi.org/10.1002/hyp.7574>, 2010.
- 445 Blöschl, G., Sivapalan, M., Wagener, T., Viglione, A., and Savenije, H. H. G. (Eds.): *Runoff Prediction in Ungauged Basins – Synthesis across Processes, Places and Scales*, Cambridge University Press, Cambridge, UK, 465 pp., 2013.
- Blöschl, G., Bierkens, M. F. P., Chambel, A., Cudennec, C., Destouni, G., Fiori, A., Kirchner, J. W., McDonnell, J. J., Savenije, H. H. G., Sivapalan, M., Stumpff, C., Toth, E., Volpi, E., Carr, G., Lupton, C., Salinas, J., Széles, B., Viglione, A., Aksoy, H., Allen, S. T., Amin, A., Andréassian, V., Arheimer, B., Aryal, S. K., Baker, V., Bardsley, E., Barendrecht, M. H., Bartosova, A., Batelaan, O., Berghuijs, W. R., Beven, K., Blume, T., Bogaard, T., Borges de Amorim, P., Böttcher, M. E., Boulet, G., Breinl, K., Brilly, M., Brocca, L., Buytaert, W., Castellarin, A., Castelletti, A., Chen, X., Chen, Y., Chen, Y., Chiffard, P., Claps, P., Clark, M. P., Collins, A. L., Croke, B., Dathe, A., David, P. C., de Barros, F. P. J., de Rooij, G., Di Baldassarre, G., Driscoll, J. M., Duethmann, D., Dwivedi, R., Eris, E., Farmer, W. H., Feiccabrino, J., Ferguson, G., Ferrari, E., Ferraris, S., Fersch, B., Finger, D., Foglia, L., Fowler, K., Gartsman, B., Gascoin, S., Gaume, E., Gelfan, A., Geris, J., Gharari, S., Gleeson, T., Glendell, M., Gonzalez Bevacqua, A., González-Dugo, M. P., Grimaldi, S., Gupta, A. B., Guse, B., Han, D., Hannah, D., Harpold, A., Haun, S., Heal, K., Helfricht, K., Herrnegger, M., Hipsey, M., Hlaváčiková, H., Hohmann, C., Holko, L., Hopkinson, C., Hrachowitz, M., Illangasekare, T. H., Inam, A., Innocente, C., Istanbuluoglu, E., Jarihani, B., Kalantari, Z., Kalvans, A., Khanal, S., Khatami, S., Kiesel, J., Kirkby, M., Knoben, W., Kochanek, K., Kohnová, S., Kolechkina, A., Krause, S., Kreamer, D., Kreibich, H., Kunstmann, H., Lange, H., Liberato, M. L. R., Lindquist, E., Link, T., Liu, J., Loucks, D. P., Luce, C., Mahé, G., Makarieva, O., Malard, J., Mashtayeva, S., Maskey, S., Mas-Pla, J., Mavrova-Guirguinova, M., Mazzoleni, M., Mernild, S., Misstear, B. D., Montanari, A., Müller-Thomy, H., Nabizadeh, A., Nardi, F., Neale, C., Nesterova, N., Nurtaev, B., Odongo, V. O., Panda, S., Pande, S., Pang, Z., Papacharalampous, G., Perrin, C., Pfister, L., Pimentel, R., Polo, M. J., Post, D., Prieto Sierra, C., Ramos, M.-H., Renner, M., Reynolds, J. E., Ridolfi, E., Rigon, R., Riva, M., Robertson, D. E., Rosso, R., Roy, T., Sá, J. H. M., Salvadori, G., Sandells, M., Schaefli, B., Schumann, A., Scolobig, A., Seibert, J., Servat, E., Shafiei, M., Sharma, A., Sidibe, M., Sidle, R. C., Skaugen, T., Smith, H., Spiessl, S. M., Stein, L., Steinsland, I., Strasser, U., Su, B., Szolgay, J., Tarboton, D., Tauro, F., Thirel, G., Tian, F., Tong, R., Tussupova, K., Tyrallis, H., Uijlenhoet, R., van Beek, R., van der Ent, R. J., van der Ploeg, M., Van Loon, A. F., van Meerveld, I., van Nooijen, R., van Oel, P. R., Vidal, J.-P., von Freyberg, J., Vorogushyn, S., Wachniew, P., Wade, A. J., Ward, P., Westerberg, I. K., White, C., Wood, E. F., Woods, R., Xu, Z., Yilmaz, K. K., and Zhang, Y.: Twenty-three unsolved problems in hydrology (UPH) – a community perspective, *Hydrological Sciences Journal*, 64, 1141-1158, <https://doi.org/10.1080/02626667.2019.1620507>, 2019.
- 455
- 460
- 465
- 470
- BMLRT: ehyd – Hydrographic data and analyses, available at: <https://ehyd.gv.at/>, last access: 13 April 2021.



- 475 Bouaziz, L. J. E., Fenicia, F., Thirel, G., de Boer-Euser, T., Buitink, J., Brauer, C. C., De Niel, J., Dewals, B. J., Drogue, G.,
Grelier, B., Melsen, L. A., Moustakas, S., Nossent, J., Pereira, F., Sprokkereef, E., Stam, J., Weerts, A. H., Willems,
P., Savenije, H. H. G., and Hrachowitz, M.: Behind the scenes of streamflow model performance, *Hydrol. Earth Syst.
Sci.*, 25, 1069-1095, 10.5194/hess-25-1069-2021, 2021.
- Burn, D. H., and Boorman, D. B.: Estimation of hydrological parameters at ungauged catchments, *Journal of Hydrology*, 143,
429-454, [https://doi.org/10.1016/0022-1694\(93\)90203-L](https://doi.org/10.1016/0022-1694(93)90203-L), 1993.
- 480 Duethmann, D., and Blöschl, G.: Why has catchment evaporation increased in the past 40 years? A data-based study in Austria,
Hydrol. Earth Syst. Sci., 22, 5143-5158, 10.5194/hess-22-5143-2018, 2018.
- Efstratiadis, A., and Koutsoyiannis, D.: One decade of multi-objective calibration approaches in hydrological modelling: a
review, *Hydrological Sciences Journal*, 55, 58-78, <https://doi.org/10.1080/02626660903526292>, 2010.
- 485 Gruber, A., De Lannoy, G., Albergel, C., Al-Yaari, A., Brocca, L., Calvet, J. C., Colliander, A., Cosh, M., Crow, W., Dorigo,
W., Draper, C., Hirschi, M., Kerr, Y., Konings, A., Lahoz, W., McColl, K., Montzka, C., Muñoz-Sabater, J., Peng,
J., Reichle, R., Richaume, P., Rüdiger, C., Scanlon, T., van der Schalie, R., Wigneron, J. P., and Wagner, W.:
Validation practices for satellite soil moisture retrievals: What are (the) errors?, *Remote Sensing of Environment*,
244, 111806, <https://doi.org/10.1016/j.rse.2020.111806>, 2020.
- Guo, Y., Zhang, Y., Zhang, L., and Wang, Z.: Regionalization of hydrological modeling for predicting streamflow in ungauged
490 catchments: A comprehensive review, *WIREs Water*, 8, e1487, <https://doi.org/10.1002/wat2.1487>, 2021.
- [Dataset] Hall, D. K., and Riggs, G. A.: MODIS/Terra Snow Cover Daily L3 Global 500m Grid, Version 6, [September 2002
to August 2014], Boulder, Colorado USA, NASA National Snow and Ice Data Center Distributed Active Archive
Center, <https://doi.org/10.5067/MODIS/MOD10A1.006>, 2016a.
- [Dataset] Hall, D. K., and Riggs, G. A.: MODIS/Aqua Snow Cover Daily L3 Global 500m Grid, Version 6, [September 2002
495 to August 2014], Boulder, Colorado USA, NASA National Snow and Ice Data Center Distributed Active Archive
Center, <https://doi.org/10.5067/MODIS/MYD10A1.006>, 2016b.
- Hahn, S., Wagner, W., Steele-Dunne, S. C., Vreugdenhil, M., and Melzer, T.: Improving ASCAT Soil Moisture Retrievals
With an Enhanced Spatially Variable Vegetation Parameterization, *IEEE Transactions on Geoscience and Remote
Sensing*, 1-16, <https://doi.org/10.1109/TGRS.2020.3041340>, 2020.
- 500 He, Y., Bárdossy, A., and Zehe, E.: A review of regionalisation for continuous streamflow simulation, *Hydrol. Earth Syst.
Sci.*, 15, 3539-3553, <https://doi.org/10.5194/hess-15-3539-2011>, 2011.
- Hiebl, J., and Frei, C.: Daily temperature grids for Austria since 1961—concept, creation and applicability, *Theoretical and
applied climatology*, 124, 161-178, <https://doi.org/10.1007/s00704-015-1411-4>, 2016.
- Hiebl, J., and Frei, C.: Daily precipitation grids for Austria since 1961—Development and evaluation of a spatial dataset for
505 hydroclimatic monitoring and modelling, *Theoretical and applied climatology*, 132, 327-345,
<https://doi.org/10.1007/s00704-017-2093-x>, 2018.




- Hirsch, R. M., Helsel, D. R., Cohn, T. A., and Gilroy, E. J.: Statistical analysis of hydrological data, in: Handbook of Hydrology, edited by: Maidment, R., McGraw-Hill, New York, 17.1–17.55, 1992.
- 510 Hrachowitz, M., Savenije, H. H. G., Blöschl, G., McDonnell, J. J., Sivapalan, M., Pomeroy, J. W., Arheimer, B., Blume, T., Clark, M. P., Ehret, U., Fenicia, F., Freer, J. E., Gelfan, A., Gupta, H. V., Hughes, D. A., Hut, R. W., Montanari, A., Pande, S., Tetzlaff, D., Troch, P. A., Uhlenbrook, S., Wagener, T., Winsemius, H. C., Woods, R. A., Zehe, E., and Cudennec, C.: A decade of Predictions in Ungauged Basins (PUB)—a review, *Hydrological Sciences Journal*, 58, 1198-1255, <https://doi.org/10.1080/02626667.2013.803183>, 2013.
- 515 Huang, Q., Qin, G., Zhang, Y., Tang, Q., Liu, C., Xia, J., Chiew, F. H. S., and Post, D.: Using Remote Sensing Data-Based Hydrological Model Calibrations for Predicting Runoff in Ungauged or Poorly Gauged Catchments, *Water Resources Research*, 56, e2020WR028205, <https://doi.org/10.1029/2020WR028205>, 2020.
- Kovacs, A., Honti, M., Zessner, M., Eder, A., Clement, A., and Blöschl, G.: Identification of phosphorus emission hotspots in agricultural catchments, *Science of The Total Environment*, 433, 74-88, <https://doi.org/10.1016/j.scitotenv.2012.06.024>, 2012.
- 520 Lebecherel, L., Andréassian, V., and Perrin, C.: On evaluating the robustness of spatial-proximity-based regionalization methods, *Journal of Hydrology*, 539, 196-203, <https://doi.org/10.1016/j.jhydrol.2016.05.031>, 2016.
- Li, H., and Zhang, Y.: Regionalising rainfall-runoff modelling for predicting daily runoff: Comparing gridded spatial proximity and gridded integrated similarity approaches against their lumped counterparts, *Journal of Hydrology*, 550, 279-293, <https://doi.org/10.1016/j.jhydrol.2017.05.015>, 2017.
- 525 Merz, R., and Blöschl, G.: Regionalisation of catchment model parameters, *Journal of Hydrology*, 287, 95-123, <https://doi.org/10.1016/j.jhydrol.2003.09.028>, 2004.
- Naeimi, V., Scipal, K., Bartalis, Z., Hasenauer, S., and Wagner, W.: An Improved Soil Moisture Retrieval Algorithm for ERS and METOP Scatterometer Observations, *IEEE Transactions on Geoscience and Remote Sensing*, 47, 1999-2013, <https://doi.org/10.1109/TGRS.2008.2011617>, 2009.
- 530 Narbondo, S., Gorgoglione, A., Crisci, M., and Chreties, C.: Enhancing Physical Similarity Approach to Predict Runoff in Ungauged Watersheds in Sub-Tropical Regions, *Water*, 12, 528, <https://doi.org/10.3390/w12020528>, 2020.
- Nash, J. E., and Sutcliffe, J. V.: River flow forecasting through conceptual models part I—A discussion of principles, *Journal of hydrology*, 10, 282-290, [https://doi.org/10.1016/0022-1694\(70\)90255-6](https://doi.org/10.1016/0022-1694(70)90255-6), 1970.
- 535 Neri, M., Parajka, J., and Toth, E.: Importance of the informative content in the study area when regionalising rainfall-runoff model parameters: the role of nested catchments and gauging station density, *Hydrol. Earth Syst. Sci.*, 24, 5149-5171, <https://doi.org/10.5194/hess-24-5149-2020>, 2020.
- Nijzink, R. C., Almeida, S., Pechlivanidis, I. G., Capell, R., Gustafssons, D., Arheimer, B., Parajka, J., Freer, J., Han, D., Wagener, T., van Nooijen, R. R. P., Savenije, H. H. G., and Hrachowitz, M.: Constraining Conceptual Hydrological Models With Multiple Information Sources, *Water Resources Research*, 54, 8332-8362, <https://doi.org/10.1029/2017wr021895>, 2018.
- 540



- Parajka, J., Merz, R., and Blöschl, G.: Estimation of daily potential evapotranspiration for regional water balance modeling in Austria. In 11th International Poster Day and Institute of Hydrology Open Day “Transport of Water, Chemicals and Energy in the Soil - Crop Canopy - Atmosphere System”, Slovak Academy of Sciences, Bratislava, 299-306, 2003.
- 545 Parajka, J., Merz, R., and Blöschl, G.: A comparison of regionalisation methods for catchment model parameters, *Hydrol. Earth Syst. Sci.*, 9, 157-171, <https://doi.org/10.5194/hess-9-157-2005>, 2005.
- Parajka, J., Naeimi, V., Blöschl, G., Wagner, W., Merz, R., and Scipal, K.: Assimilating scatterometer soil moisture data into conceptual hydrologic models at the regional scale, *Hydrol. Earth Syst. Sci.*, 10, 353-368, <https://doi.org/10.5194/hess-10-353-2006>, 2006.
- 550 Parajka, J., Merz, R., and Blöschl, G.: Uncertainty and multiple objective calibration in regional water balance modelling: case study in 320 Austrian catchments, *Hydrological Processes*, 21, 435-446, <https://doi.org/10.1002/hyp.6253>, 2007.
- Parajka, J., and Blöschl, G.: The value of MODIS snow cover data in validating and calibrating conceptual hydrologic models, *Journal of Hydrology*, 358, 240-258, <https://doi.org/10.1016/j.jhydrol.2008.06.006>, 2008.
- 555 Parajka, J., Viglione, A., Rogger, M., Salinas, J. L., Sivapalan, M., and Blöschl, G.: Comparative assessment of predictions in ungauged basins – Part 1: Runoff-hydrograph studies, *Hydrol. Earth Syst. Sci.*, 17, 1783-1795, <https://doi.org/10.5194/hess-17-1783-2013>, 2013.
- Parajka, J., Merz, R., Skøien, J. O., and Viglione, A.: The role of station density for predicting daily runoff by top-kriging interpolation in Austria, *Journal of Hydrology and Hydromechanics*, 63, 228-234, <https://doi.org/10.1515/johh-2015-0024>, 2015.
- 560 Paulik, C., Dorigo, W., Wagner, W., and Kidd, R.: Validation of the ASCAT Soil Water Index using in situ data from the International Soil Moisture Network, *International Journal of Applied Earth Observation and Geoinformation*, 30, 1-8, <https://doi.org/10.1016/j.jag.2014.01.007>, 2014.
- Pfeil, I., Vreugdenhil, M., Hahn, S., Wagner, W., Strauss, P., and Blöschl, G.: Improving the seasonal representation of ASCAT soil moisture and vegetation dynamics in a temperate climate, *Remote Sensing*, 10, 1788, <https://doi.org/10.3390/rs10111788>, 2018.
- 565 Sachs, J. D., and McArthur, J. W.: The Millennium Project: a plan for meeting the Millennium Development Goals, *The Lancet*, 365, 347-353, [https://doi.org/10.1016/S0140-6736\(05\)17791-5](https://doi.org/10.1016/S0140-6736(05)17791-5), 2005.
- Sleziak, P., Szolgay, J., Hlavčová, K., Danko, M., and Parajka, J.: The effect of the snow weighting on the temporal stability of hydrologic model efficiency and parameters, *Journal of Hydrology*, 583, 124639, <https://doi.org/10.1016/j.jhydrol.2020.124639>, 2020.
- 570 Széles, B., Parajka, J., Hogan, P., Silasari, R., Pavlin, L., Strauss, P., and Blöschl, G.: The Added Value of Different Data Types for Calibrating and Testing a Hydrologic Model in a Small Catchment, *Water Resources Research*, 56, e2019WR026153, <https://doi.org/10.1029/2019WR026153>, 2020.
- Tegegne, G., and Kim, Y.-O.: Modelling ungauged catchments using the catchment runoff response similarity, *Journal of Hydrology*, 564, 452-466, <https://doi.org/10.1016/j.jhydrol.2018.07.042>, 2018.



- 575 Tong, R., Parajka, J., Komma, J., and Blöschl, G.: Mapping snow cover from daily Collection 6 MODIS products over Austria, *Journal of Hydrology*, 590, 125548, <https://doi.org/10.1016/j.jhydrol.2020.125548>, 2020.
- Tong, R., Parajka, J., Salentinig, A., Pfeil, I., Komma, J., Széles, B., Kubáň, M., Valent, P., Vreugdenhil, M., Wagner, W., and Blöschl, G.: The value of ASCAT soil moisture and MODIS snow cover data for calibrating a conceptual hydrologic model, *Hydrol. Earth Syst. Sci.*, 25, 1389-1410, 10.5194/hess-25-1389-2021, 2021.
- 580 Viglione, A., Parajka, J., Rogger, M., Salinas, J., Laaha, G., Sivapalan, M., and Blöschl, G.: Comparative assessment of predictions in ungauged basins-Part 3: Runoff signatures in Austria, *Hydrology and Earth System Sciences*, 17, 2263, <https://doi.org/10.5194/hess-17-2263-2013>, 2013.
- Viglione, A. and Parajka, J.: TUWmodel: Lumped/Semi-Distributed Hydrological Model for Education Purposes. R package version 1.1-1. <https://CRAN.R-project.org/package=TUWmodel>. 2020
- 585 Wagner, W., Lemoine, G., Borgeaud, M., and Rott, H.: A study of vegetation cover effects on ERS scatterometer data, *IEEE Transactions on Geoscience and Remote Sensing*, 37, 938-948, <https://doi.org/10.1109/36.752212>, 1999a.
- Wagner, W., Lemoine, G., and Rott, H.: A Method for Estimating Soil Moisture from ERS Scatterometer and Soil Data, *Remote Sensing of Environment*, 70, 191-207, [https://doi.org/10.1016/S0034-4257\(99\)00036-X](https://doi.org/10.1016/S0034-4257(99)00036-X), 1999b.
- Yang, X., Magnusson, J., Rizzi, J., and Xu, C.-Y.: Runoff prediction in ungauged catchments in Norway: comparison of regionalization approaches, *Hydrology Research*, 49, 487-505, <https://doi.org/10.2166/nh.2017.071>, 2017.
- 590 Yang, X., Magnusson, J., Huang, S., Beldring, S., and Xu, C.-Y.: Dependence of regionalization methods on the complexity of hydrological models in multiple climatic regions, *Journal of Hydrology*, 582, 124357, <https://doi.org/10.1016/j.jhydrol.2019.124357>, 2020.
- 595 Zhang, Y., Chiew, F. H. S., Liu, C., Tang, Q., Xia, J., Tian, J., Kong, D., and Li, C.: Can Remotely Sensed Actual Evapotranspiration Facilitate Hydrological Prediction in Ungauged Regions Without Runoff Calibration?, *Water Resources Research*, 56, e2019WR026236, <https://doi.org/10.1029/2019WR026236>, 2020.



600 **Figure 1: Topography of the study region and location of 94 lowland (red symbols) and 119 alpine (blue symbols) catchments.**






Figure 2: Median of leave-one-out runoff model efficiency (Eq. 5) obtained by eight groups of parameter transfer methods and eleven calibration weights for lowland (94) and alpine (119) catchments in the calibration (2000-2010, blue symbols) and validation (2010-2014, red symbols) periods.




605

Figure 3: Median of leave-one-out soil moisture correlation (Eq. 8) obtained by eight groups of parameter transfer methods and eleven calibration weights for lowland (94) and alpine (119) catchments in the calibration (2007-2010, blue symbols) and validation (2010-2014, red symbols) periods.



610 **Figure 4: Median of leave-one-out snow model efficiency (Eq. 9) obtained by eight groups of parameter transfer methods and eleven calibration weights for lowland (94) and alpine (119) catchments in the calibration (2000-2010, blue symbols) and validation (2010-2014, red symbols) periods.**



615 **Figure 5: The relative difference (%) in the median of snow cover (horizontal axis), soil moisture (vertical axis) and runoff (colour of symbols) efficiency between model simulations obtained by transferring model parameters calibrated by multiple-objective calibration and calibration to runoff only. The relative difference is estimated for eight model transfer methods (panels) applied in the lowland (left panels) and alpine (right panels) catchments in the calibration period 2000-2010 (soil moisture: 2007-2010).**




Figure 6: Same as Fig. 5, but for the validation period (2010-2014)