

Future water temperature of rivers in Switzerland under climate change investigated with physics-based models

Adrien Michel^{1,2}, Bettina Schaeffli^{3,4}, Nander Wever⁵, Harry Zekollari^{6,7,8}, Michael Lehning^{1,2}, and Hendrik Huwald^{1,2}

¹School of Architecture, Civil and Environmental Engineering, École Polytechnique Fédérale de Lausanne (EPFL), Lausanne, Switzerland

²WSL Institute for Snow and Avalanche Research (SLF), Davos, Switzerland

³Institute of Geography & Oeschger Centre for Climate Change Research, University of Bern, Bern, Switzerland

⁴Institute of Earth Surface Dynamics (IDYST), University of Lausanne, Lausanne, Switzerland

⁵Department of Atmospheric and Oceanic Sciences, University of Colorado Boulder, Boulder, USA

⁶Laboratory of Hydraulics, Hydrology and Glaciology (VAW), Eidgenössische Technische Hochschule (ETH), Zürich, Switzerland

⁷Swiss Federal Institute for Forest, Snow and Landscape Research (WSL), Birmensdorf, Switzerland

⁸Department of Geoscience and Remote Sensing, Delft University of Technology, Delft, the Netherlands

Correspondence: Adrien Michel (adrien.michel@epfl.ch)

Abstract. River ecosystems are highly sensitive to climate change and projected future increase in air temperature is expected to increase the stress for these ecosystems. Rivers are also an important socio-economical factor impacting, amongst others, agriculture, tourism, electricity production, and drinking water supply and quality. In addition to changes in water availability, climate change will impact river temperature. This study presents a detailed analysis of river temperature and discharge evolution over the 21st century in Switzerland. In total, 12 catchments are studied, situated both in the lowland Swiss Plateau and in the Alpine regions. The impact of climate change is assessed using a chain of physics-based models forced with the most recent climate change scenarios for Switzerland including low, mid, and high emission pathways. The suitability of such models is discussed in detail and recommendations for future improvements are provided. The model chain is shown to provide robust results while remaining limitations are identified. These are mechanisms missing in the model to correctly simulate water temperature in Alpine catchments during the summer season. A clear warming of river water is modelled during the 21st century. At the end of the century (2080-2090), the median annual river temperature increase ranges between +0.9°C for low emission and +3.5°C for high emission scenarios for both lowland and Alpine catchments. At the seasonal scale, the warming on the lowland and in the Alpine regions exhibits different patterns. For the lowland the summer warming is stronger than the one in winter, but still moderate. In Alpine catchments, only a very limited warming is expected in winter. The period of maximum discharge in Alpine catchments, currently occurring during mid-summer, will shift to earlier in the year by a few weeks (low emission) or almost two months (high emission) by the end of the century. In addition, a noticeable soil warming is expected in Alpine regions due to glacier and snow cover decrease. All results of this study are provided with the corresponding source code used for this manuscript.

1 Introduction

River systems are considered to be among the ecosystems most sensitive to Climate Change (CC) (Watts et al., 2015) and the projected future increase in air temperature (IPCC, 2021) is expected to increase the stress for these ecosystems. Water temperature is one of the most important variables for aquatic ecosystems, influencing both chemical and biological processes (Benyahya et al., 2007; Temnerud and Weyhenmeyer, 2008). Certain fish species are highly sensitive to warm water, which can promote specific diseases (e.g. proliferative kidney disease, PKD) or prevent reproduction (Caissie, 2006; Carraro et al., 2016), while higher temperatures might be favorable for some other species, enhancing biological invasion, (Paillex et al., 2017; Niedrist and Füreder, 2021). In Alpine regions, together with water temperature, glacier retreat is also expected to contribute to accelerated changes in ecosystems (Cauvy-Fraunié and Dangles, 2019; Fell et al., 2021).

Hence, river temperature is an important socio-economic factor. The literature clearly identified several vulnerable sectors: agriculture, tourism, electricity production, as well as drinking water supply and quality (e.g. Hock et al., 2005; Barnett et al., 2005; Schaeffli et al., 2007; Bourqui et al., 2011; Viviroli et al., 2011; Beniston, 2012; Hannah and Garner, 2015). For example, during the exceptional heat wave and dry period in central and northern Europe from April through August 2018, local electricity production at the Swiss nuclear power plant Mühleberg, canton Bern, had to be temporarily reduced due to unusually high water temperature of the Aare river. Increase in surface water temperature is also expected to affect ground water temperatures through river water infiltration, with significant consequences on the biochemistry of these reservoirs (Epting et al., 2021).

Several global scale studies have shown a clear trend in river temperature (Morrison et al., 2002; Webb and Nobilis, 2007; van Vliet et al., 2013; Null et al., 2013; Ficklin et al., 2014; Hannah and Garner, 2015; Watts et al., 2015; Santiago et al., 2017; Dugdale et al., 2018; Jackson et al., 2018) as well as in lake surface temperature (Dokulil, 2014; O'Reilly et al., 2015; Woolway and Merchant, 2017; Woolway et al., 2020a, b) at various locations over the last decades. For Switzerland, a recent study found a mean increase in river temperature of 0.33 ± 0.03 °C per decade between 1980 and 2018, which is associated with an increase in air temperature (Michel et al., 2020). This study also showed that the response to CC in Alpine catchments is different from those on the Swiss Plateau (lowland). So far, the warming rate of rivers in Swiss Plateau catchments has been almost twice that of Alpine catchments. Studies investigating the future evolution of water temperature in Switzerland are sparse and cover only few catchments (see e.g. CH2011, 2011; Råman Vinnå et al., 2018).

For all the above reasons, quantitative information on the future evolution of river temperature is necessary. River temperature is expected to be affected by CC mainly through the influence of rising air temperature, changes in precipitation, and changes in snow and ice melt. For simulating the future river temperature evolution, a wide range of existing hydrological models is available. Systematic reviews of such models exist in the literature (e.g. Benyahya et al., 2007; Gallice et al., 2015). These models are generally divided into two main families: statistical and physics-based models. Statistical models might not be valid outside of the observed temperature range, which is an important drawback in case of CC studies (Benyahya et al., 2007; Leach and Moore, 2019). In addition, a more physics-based representation of the snow and ice related processes in space and time, despite requiring usually more input data, allows for improved snow-runoff modelling during the snowmelt season, which is

crucial in Alpine catchments (Martin and Etchevers, 2005; Magnusson et al., 2011; Lisi et al., 2015; Brauchli et al., 2017; Du et al., 2021; Carletti et al., 2021). Therefore, a physics-based models approach was chosen.

The present study has two main objectives: i) Assess the ability of a physics-based model chain to simulate discharge and water temperature. This is achieved by using performance metrics over calibration and validation periods, and by assessing in how far the models are able to reproduce currently observed trends. ii) Investigate the impact of CC on river temperature. Despite the existence of extensive recent studies on discharge evolution under CC in Switzerland over a larger set of catchments (Brunner et al., 2019a, b; Muelchi et al., 2020, 2021), discharge is included in our analysis given the coupling of water temperature and discharge. For both objectives, the comparison of lowland versus Alpine catchments is one of the focal points of this research.

The focus is on Switzerland, a country presenting a wide topographic heterogeneity leading to different discharge and thermal regimes between the lowland Swiss Plateau regions, where the hydrological cycle is mainly precipitation driven, and the high altitude Alpine regions, where snow and glacier melt play an important role.

We use the snowmelt and runoff model Alpine3D (Lehning et al., 2006) coupled to the semi-distributed hydrological model StreamFlow (Gallice et al., 2016). This model chain has already been successfully applied in Alpine discharge modelling studies by Comola et al. (2015), Wever et al. (2017), Brauchli et al. (2017), and Griessinger et al. (2019).

2 Data

2.1 Catchments

For this study, 12 catchments are selected; they are shown in Figure 1 and their characteristics are listed in Table 1. They cover a wide range of catchment sizes (from 3.4 to 973 km²). The objective is to include representative catchments both on the Swiss Plateau and in the Swiss Alps. Further selection is based on the availability of hydrological and meteorological measurements, as well as CC scenarios. Other selection criteria are minimal anthropogenic disturbances and absence of larger lakes along the watercourse since the models do not take into account these effects (Section 3.3). Dams being very abundant in Switzerland (Belletti et al., 2020; Mulligan et al., 2020), the choice of Alpine catchments to be simulated is rather limited, resulting in the set of Inn, Kander, Landwasser, Lonza, and Lütschine catchments.

For the Swiss Plateau, more catchments satisfy the requirements. Considering a range of catchment sizes, the following catchments are retained: Birs, Broye, Ergolz, Eulach, Kleine Emme, Rietholzbach, and Suze. This selection is also based on the use of those catchments for groundwater studies (Epting et al., 2021).

For some catchments, the simulations are extended further downstream of the hydrological gauging station being used for calibration, to allow for connection to lakes, and for the use of the simulation results in a related ground water study of Epting et al. (2021). A detailed map showing the topography, catchment boundaries, stream network, and locations of hydrological and meteorological stations for each catchment is shown in Figure S1.

Table 1. Details of the selected catchments. Details of land-cover are given in Section 2.5 and S3; built-up areas are treated as rock. Details of discharge stations (Q stations) and water temperature stations (T stations) are given in Table S1. Details of meteorological stations are given in Table S2. Mean annual water temperature and discharge are given at the gauging stations, which do not necessarily correspond to the outlets simulated with CC scenarios (see text); they are computed over the period 2005-2015, except for the Ergolz (2014-2018).

Catchment	Area (km ²)	Mean elevation (m)	Min–Max elevation (m)	Glacier cover (%)	Field cover (%)	Forest cover (%)	Rock cover (%)	Mean annual discharge (mm h ⁻¹)	Mean annual water temperature (°C)	Q station	T station	Meteo stations
Swiss Plateau Catchments												
Birs	973.4	747	257–1436	0	44.1	48.5	7.4	1.57	11.0	2106	2106	BAS CHA RUE
Broye	627.3	667	429–1509	0	71.0	22.5	6.5	1.47	11.2	2034	2034	CDF NEU PAY
Ergolz	301.3	564	261–1151	0	45.4	43.5	11.2	1.11	12.0	2202	ER1	BAS BUS RUE
Eulach	74.2	535	410–884	0	44.3	32.7	23	0.95	10.7	ZH523	ZH523	KLO SMA TAE
Kleine Emme	479.9	1053	436–2319	0	51.6	44.9	3.5	2.7	9.6	2634	2634	LUZ NAP PIL
Reitholzbach	3.4	794	672–927	0	78.7	21.3	0	2.5	8.5	2414	2414	TAE STG
Suze	214.9	985	432–1602	0	47.2	46.5	6.2	2.1	9.0	A024	A024	CDF CHA NEU
Alpine Catchments												
Inn	625.2	2463	903–4029	6.4	46.4	11.7	35.5	2.8	5.0	2462	2462	COV SAM BER2 BER3 KES2 ZNZ2
Kander	180.2	2139	774–3662	13.3	31.7	16.3	38.7	4.2	6.8	A017	A017	ABO INT JUN
Landwasser	295.4	2134	958–3127	0.2	55.3	24.1	20.4	1.5	4.3	2355	2327	DAV WFJ DAV2 DAV3 DAV4 KLO2 PAR2 SLF2 ZNZ2
Lonza	78.6	2619	1513–3864	26.4	23	6	44.6	5.1	4.1	2269	2269	ABO INT JUN VIS GAN2
Lütschine	384.7	2032	575–4121	14.7	37	22.3	26.0	4.2	6.0	2109	2109	ABO INT JUN LHO2 SCH2




Figure 1. Map of Switzerland showing the location of the simulated catchments. Maps providing details of individual catchments are shown in Supplementary Figure S1. Data source: Swiss Federal Office of Topography (Swisstopo).

2.2 Hydrological data

Quality controlled water temperature and discharge measurements at hourly resolution are provided by the Federal Office for the Environment, FOEN (FOEN, 2019), the Office for Water and Waste of the Canton of Bern, AWA (AWA, 2019), the Office for Waste, Water, Energy and Air of the Canton Zurich, AWEL (AWEL, 2019) and by Holinger AG. Details of the hydrological stations used are given in Table S1 and Figure S1.

2.3 Meteorological data

Meteorological data used in this study are provided by the MeteoSwiss (MCH) automatic monitoring network, distributed through IDAWEB (2020), and by the Inter-Cantonal Measurement and Information System (IMIS, 2019). Each catchment is simulated using forcing data from 2 to 9 IMIS and/or MCH stations, depending on the number of available stations within or nearby the catchment (for details see Tables 1, S2, and Figure S1). The variables used at hourly resolution to force the model are: air temperature (TA), precipitation accumulation (PSUM), wind velocity (VW), relative humidity (RH) and incoming shortwave radiation (ISWR). Only variables that are available at measurement stations and in the downscaled CH2018 CC

scenarios dataset (see Section 2.4) are used, to ensure that the historical and CC model runs use the exact same set of forcing data.

Note that IMIS stations do not measure ISWR; they are also not equipped with heated precipitation gauges. For these stations, precipitation is deduced from snow depth variations during the winter season using the snow settling calculated by the SNOWPACK model (Lehning et al., 2002b) and from interpolation of nearby MCH stations with heated rain gauges in case of absence of snow.

Incoming longwave radiation (ILWR), required to force the models, is measured at some MCH stations. However, this variable is not included in the CH2018 dataset used to force the model during CC simulations. As a consequence, both for historical and CC periods, ILWR is calculated at the location of the meteorological stations applying an "all sky" approach described in Omstedt (1990), which uses TA, RH, and ISWR to estimate the cloud cover fraction and the longwave downward radiation. Methods used for interpolating the input data are described in Section 3.2.

2.4 Climate change scenarios

Recent climate change scenarios are available for Switzerland from the CH2018 dataset (NCCS, 2018) at daily resolution, based on the European Coordinated Regional Climate Downscaling Experiment, EURO-CORDEX. Since detailed physics-based snow models require sub-daily granularity, a downscaled version of this dataset at hourly resolution and at stations scale is used (Michel et al., 2021b, a). This dataset also includes an extension of the CH2018 scenarios to the IMIS station network. The temporal downscaling is performed using an improved delta change approach which is shown to correctly preserve the seasonal means of the CC scenarios. Since this method requires longer historical time series than the procedure used to derive the CH2018 scenarios, some stations had to be excluded from the original dataset. In addition, the used downscaling method requires the results to be analyzed at a monthly or seasonal scale, since shorter time periods may not be correctly captured (see discussion in Michel et al., 2021b).

Most IMIS stations were installed after 2000, entailing that only 10-year periods of downscaled CC scenarios can be constructed. For all IMIS stations, the temporally downscaled dataset for CC scenarios is computed for each individual decade between 1990 and 2100. For the MCH stations, which generally have much longer data availability, also scenarios for 30-year periods between 1980 and 2100 were constructed in addition to the 10-year periods. Using the time series derived over 30 years would be beneficial since 30-year periods are generally considered to capture the climatic trends better than 10-year periods (Michel et al., 2021b) and are often the standard length for CC studies (WMO, 2017). However, this would prevent the usage of IMIS stations. Magnusson et al. (2011) and Schlögl et al. (2016) have shown that increasing the number of stations used to force the model indeed improves the simulations over Alpine catchments. Accordingly, we use the 10-year time series in this work. In Section S7 we assess the impact of using 10-year versus 30-year periods and show that only the range of warming is impacted, not the median values.

Out of the 68 CC scenarios provided in Michel et al. (2021b), 21 are used in the present study: 7 for the RCP2.6 emission scenarios (low to negative emission), 7 for the RCP4.5 emission scenarios (moderate emission), and 7 for the RCP8.5 scenarios (business-as-usual). These CC scenarios originate from 7 chains of GCMs and RCMs as detailed in Table 2. Only these 7 model

Table 2. Climate change model chains used in this study. For each model chain the RCP2.6, RCP4.5 and RCP8.5 scenarios are used.

GCM	RCM	Seed	Resolution
ICHEC-EC-EARTH	DMI-HIRHAM5	r3i1p1	0.11°
ICHEC-EC-EARTH	SMHI-RCA4	r12i1p1	0.11°
MIROC-MIROC5	SMHI-RCA4	r1i1p1	0.44°
MOHC-HadGEM2-ES	KNMI-RACMO22E	r1i1p1	0.44°
MOHC-HadGEM2-ES	SMHI-RCA4	r1i1p1	0.44°
MPI-M-MPI-ESM-LR	SMHI-RCA4	r1i1p1	0.44°
NCC-NorESM1-M	SMHI-RCA4	r1i1p1	0.44°

chains contain all the variables and RCPs needed for the simulations performed here. The CC simulations are run over the hydrological years 1991-2000, 2006-2015, 2031-2040, 2056-2065, and 2081-2090, referred to as CC periods. For simplicity, we use full decade names further in this paper (e.g. 1990-2000 for the hydrological years 1991-2000, meaning 1 October 1990 to 30 September 2000). The period 2005-2015 is used to validate the CC simulations against measurements for catchments where long enough historical measurements are available. In the following, the meteorological seasons used for the analysis are abbreviated as follows: Winter = DJF (December, January, and February), Spring = MAM (March, April, and May), Summer = JJA (June, July and August), and Fall = SON (September, October, and November).

2.5 Elevation, glacier, catchment geometry, and land cover data

To perform simulations with Alpine3D, a digital elevation model is needed, as well as a land use classification to initialize the pixels in the model in an appropriate state and to define the soil and canopy properties. For glaciated catchments, the ice area and thickness need to be provided.

The digital elevation model (DEM) is derived from the DTM25 dataset at 25 m resolution provided by Swisstopo, averaged to the resolutions used for the simulations (100 m and 500 m). Land cover data are derived from the 2006 version of the Copernicus CORINE Land Cover (European Environment Agency, 2013) dataset (CLC) at 100 m resolution (upscaled to 500 m resolution). CLC land cover classes are translated into the land cover classes available in Alpine3D (see Table S3). The catchment and hydrological network, together with sub-catchments attached to each river reach, are derived using the TauDEM software (Tarboton, 1997) with a wrapper to force it to reproduce exactly the river network provided by the Swiss Federal Office for the Environment (FOEN) (Swiss Federal Office for the Environment, 2013, 2020). Details of this method along with an evaluation are given in Section S3.

Detailed glacier thickness maps (i.e. ice thickness above bedrock surface) are used at the starting point for each simulation. The evolution of the glacier geometry is simulated with the model GloGEMflow (Zekollari et al., 2019). Details are presented in Section 3.1. The glacier maps overwrite the CLC land cover classes and pixels considered as glacier in CLC but not in the glacier model are turned into bare rock pixels.

Glacier coverage and mean elevation indicated in Table 1 are obtained from the glacier height grids and DEM described above, which means that they might differ slightly from values given by the data provider for the gauging stations.

3 Models

The models used in this study, GloGEMflow, Alpine3D and StreamFlow, are presented in detail in Zekollari et al. (2019), Lehning et al. (2006) and Gallice et al. (2016), respectively. Here we only provide a short overview of the models and emphasize aspects relevant for the present application. The main workflow of Alpine3D and StreamFlow is shown in Figure 2.

For Alpine3D, as well as for StreamFlow, significant optimization work was necessary in order to use the model chain for such a computationally intensive study. Details of the optimization procedure are presented in Michel (2021).




Figure 2. Details of the models' workflow. The calibration and validation periods indicated are valid for all catchments except for the Eulach catchment (where the periods 2015-2016 and 2017-2018 are used instead). Figure adapted from (Gallice et al., 2016).

3.1 GloGEMflow

GloGEMflow calculates the evolution of all individual glaciers along their flowlines by explicitly accounting for both surface mass balance and ice flow processes. The mass balance is calculated from a positive degree-day approach (Huss and Hock, 2015), while ice flow is described through the shallow-ice approximation (Hutter, 1983). GloGEMflow was extensively evaluated over the European Alps, by relying on observed mass balances, surface velocities, and glacier changes, and by comparing the simulated glacier changes to those from high-resolution 3D modelling studies that focus on individual glaciers (e.g. Jouvét et al., 2009; Zekollari et al., 2014). The simulated glacier extents under the CH2018 CC scenarios considered in this study were

transformed from the GloGEMflow 1D model grid to the 2D model grid (at both 100 m and 500 m resolution) by ensuring that the area and volume was conserved for each elevation band. This conversion was performed by taking the 2D reference glacier geometry (Huss and Farinotti, 2012) as a starting point, and applying a uniform absolute change in ice thickness per elevation band to match the GloGEMflow modelled area. Subsequently, the resulting 2D ice thickness was changed uniformly (same relative change) per elevation band to match the modelled GloGEMflow volume.

3.2 Alpine3D

Alpine3D is a spatially distributed version of the multi-layer snow and soil model SNOWPACK, which explicitly solves the mass and energy balance equations and simulates the snow micro-structure (Lehning et al., 2002b, a). As discussed in the introduction, previous studies have shown the added value of a complex snow model in Alpine environments, while we argue that for Swiss Plateau regions, such complex models may not be required. However, Alpine3D provides the vertically resolved soil temperature, which is required in StreamFlow and not provided in simpler models. In addition, using Alpine3D throughout allows to have a consistent land-surface model between all catchments. Alpine3D is run at 500 m resolution for all catchments except the small Rietholzbach catchment, where a resolution of 100 m is used. The resolution is chosen to reduce the computational cost and it has been shown to have only a minor impact on simulated snow depth (Schlögl et al., 2016). The input data for Alpine3D are interpolated to the grids using various algorithms provided by the MeteIO library (Bavay and Egger, 2014). The air temperature is first de-trended for elevation (using a vertical lapse rate computed from the measurements), then interpolated using an inverse distance weighting, and finally re-trended. An analog procedure is applied for longwave radiation (using a constant lapse rate of $-31.25 \text{ W m}^{-2} \text{ km}^{-1}$ to mimic the effect of decreasing air temperature), for wind velocity (using the lapse rate computed from the measurements) and for precipitation, where values of the vertical lapse rate range between $10 \% \text{ km}^{-1}$ and $50 \% \text{ km}^{-1}$ (see Section 3.4). Finally, cloud cover is derived at each meteorological station from ISWR (if available) and interpolated to the grids using an inverse distance weighting algorithm. This cloud cover is then used to adjust the theoretical diffuse and direct radiation at each pixel (Helbig, 2009). Topographical shading is taken into account and a simple model of reflected radiation from surrounding terrain is used.

Alpine3D contains a two-layer canopy module simulating the micro-meteorology in the forest, the evapotranspiration, and the interaction between trees and snow, including snow interception (Gouttevin et al., 2015). Grass, crops and other land covers are not directly simulated by the canopy module, and the evapotranspiration here is parameterized through the value of the roughness length used in the computation of the latent heat flux. Water infiltration in snow and soil is handled through a simple bucket model. As shown in previous studies, the bucket scheme provides adequate performance on daily and seasonal timescales (Wever et al., 2014, 2015). Alpine3D does not handle partially covered snow pixels, which might delay the melt at the end of the snow season due to overestimated albedo.

Both Alpine3D and StreamFlow are run at hourly resolution. The model writes gridded output for all interpolated forcing variables, together with the soil temperature at various depths and the runoff at the bottom of the soil column.

3.3 StreamFlow

StreamFlow is a semi-distributed model concurrently simulating discharge and temperature in each river segment. The runoff at the bottom of the soil column as calculated by Alpine3D is totalized at the scale of each sub-catchment in StreamFlow (see Figure 2), and the residence time in the soil is determined with an approach using two linear reservoirs in series (Perrin et al., 2003) with reservoirs calibrated coefficients. A parameter representing a fraction of water loss (emulating deep soil infiltration or the difference between surface and subsurface catchment area) can be calibrated in addition. A single parameter set is calibrated for the entire catchment, with the reservoir parameters being scaled to the sub-catchment size (Gallice et al., 2016).

Based on this sub-catchment runoff, the model uses either a lumped approach (where each stream reach is resolved as a single element, receiving input from its related sub-catchment) or a discretized approach (where reaches are separated into sub-elements based on the resolution used) to compute reach-scale water temperature and runoff routing to the outlet.

For water routing at the reach scale or at the sub-element scale, either an instant routing is considered or a routing scheme based on the Muskingum-Cunge approach, which solves a diffusive-wave approximation of the shallow water equation (Cunge, 1969; Ponce and Changanti, 1994). Regardless of the water routing scheme, heat is explicitly advected together with the mass.

The water temperature in the soil reservoirs at the sub-catchment scale (which determines the water temperature when leaving the reservoirs and entering the river reaches) can be computed in StreamFlow either by (a) using the approach of Comola et al. (2015) based on energy balance between groundwater and soil temperature (where one parameter needs to be calibrated), (b) using the approach of the Hydrological Simulation Program–Fortran, HSPF (Bicknell et al., 1997), or (c) simply taking the soil temperature at a given depth. The HSPF approach essentially approximates the time evolution of the water temperature in the reservoirs by smoothing and adding an offset to the time series of air temperature (the smoothing factor and offset are calibrated parameters). For all three approaches, forcing values averaged over each sub-catchment are used. Different routing and soil water temperature schemes are tested for choosing the most suitable one.

Once the water is routed to the river, the evolution of the water temperature is obtained by computing the energy balance for each reach considering short- and longwave radiation, sensible and latent heat fluxes, heat exchange and friction with the streambed, and heat advection from upstream reaches and from water input from the stream-hillslope interface. The latent heat flux is computed using a simplified Penman equation (Hannah et al., 2004; Haag and Luce, 2008; Magnusson et al., 2012) and the sensible heat flux is computed from a classical approach (Brown, 1969). The coefficient of heat transfer between the ground and the river needs to be calibrated. Note that the soil depth used for streambed exchange and for the infiltrating water temperature in the approach (a) and (c) are the same. Different depths are tested and the soil depth leading to the best results is used (Section S5 shows that the soil depth chosen for streambed exchange has only a weak impact).

Input data from Alpine3D used in StreamFlow benefits from the treatment performed in Alpine3D, i.e. topographic shading and shading from vegetation present in the land cover dataset used (see Section 2.5) combined with the impact of vegetation on wind speed. Small-scale riparian vegetation shading is not accounted for, which might lead to an overestimation of the radiation input in small streams. However, Section S9 shows that this has only a minor impact.

3.4 Calibration and validation of models

For the calibration/validation process, Alpine3D is run for the hydrological years 2012-2018. Each Alpine3D simulation is started in July and the first 3 months serve as spin-up. Before formal parameter calibration in StreamFlow, multiple model runs of Alpine3D are performed with different values of the precipitation vertical lapse rate to adjust the yearly total mass balance in Alpine catchments. In addition, modeled snow heights are compared to measurements to assess the capacity of Alpine3D in reproducing observed snow season dynamics in terms of season duration. Alpine3D has therefore undergone some parameter adjustment but is not calibrated in a strict sense.

After this initial performance check of Alpine3D, StreamFlow is calibrated over the years 2012-2014 and validated over the years 2015-2018. The only exception is the Eulach catchment, where due to the lack of water temperature measurements before 2014, Alpine3D is run over 2015-2018, while the calibration and validation periods are 2015-2016 and 2017-2018. Every StreamFlow simulation is run using the first two years of data for spin-up and then re-starts from the beginning of the time period. Section S4 shows sensitivity tests for the Broye and Lonza catchments using a longer simulation time period (2002-2018). Different calibration periods are used within these 17 years to test for a significant influence on the hydrological model output (Myers et al., 2021), which was not the case.

Depending on the setup, between 5 and 7 parameters need to be calibrated in StreamFlow (4 for discharge, the remaining for water temperature, see Table 3). The calibration is performed with a Monte Carlo approach, first for the 4 parameters of the discharge module (50'000 runs), and then for the parameters of the water temperature module (10'000 runs). The calibration for water temperature is run only for the best parameter set obtained from the discharge calibration, and is run with soil temperature calculated by Alpine3D at different depths (the depth leading to the best results being kept, see Section S5).

The sequential calibration is motivated by the fact that the model is significantly faster when only discharge is computed. The random sets are drawn from uniform distributions, with bounds indicated in Table 3 (taken and slightly adapted from the work of Gallice et al., 2016). All other model parameters, such as aspect ratio of the reach cross-section, are taken from Gallice et al. (2016). As performance metrics, we use the Kling-Gupta efficiency (KGE) coefficient (Gupta et al., 2009) for discharge and the root mean square error (RMSE) for water temperature.

4 Results

4.1 StreamFlow calibration and validation results

Before proper calibration, the performance of the different StreamFlow modules is assessed (see details in Section S5). To this end, the calibration is performed using either the lumped or discretized, and the direct or Muskingum-Cunge approaches for reach-scale water routing (4 combinations), and the three sub-catchment temperature schemes. These are tested both at 100 m and 500 m resolution (24 combinations in total), and the 100 m resolution is retained. The more complex and computationally demanding water routing schemes do not improve the performance, consequently the lumped and direct approaches are used (Table S5). Finally, the HSPF approach for sub-catchment temperature yielded the best results across all studied

Table 3. Calibration parameters and range of values used in StreamFlow, see Gallice et al. (2016) for details.

Parameter	Range	Units
Discharge parameters		
Maximum infiltration rate	[0,100]	mm day ⁻¹
Upper reservoir τ	[1,50]	day
Lower reservoir τ	[100,1000]	day
Fraction of lost water	[0,40]	%
Water temperature parameters		
Streambed heat transfer coefficient	[0,100]	W m ⁻² K ⁻¹
Offset (HSPF module)	[-3,1]	s
Smoothing factor (HSPF module)	[1e-7,5e-6]	K s ⁻¹
Diffusion time (energy balance module)	[1e-3,100]	day

catchments and is therefore selected (Table S7, Figures S4 and S5). Note that employing the HSPF scheme results in a lower impact of the soil temperature on the simulated water temperature (only through conduction between water and streambed).

Table 4 shows the KGE and RMSE values from the calibration and validation of StreamFlow using the retained setup. For each catchment, all calibrated parameter values are summarized in Table S8 and detailed per-catchment plots for the calibration and validation phase are shown in Section S6, Figures S6 to S29. Figures S30 to S33 show the snow depth for Alpine catchments simulated by Alpine3D at the location of stations measuring snow depth. Daily time series of simulated and measured water temperature of four catchments are shown in Figure 3. These time series show that catchments with similar performance metrics (Table 4) can still show a different quality of fit to corresponding observed data. This is best visible by an overestimation of water temperature in Alpine catchments in summer, which underlines the limitation of using lumped model performance metrics such as KGE and RMSE over the entire year, and the need to perform a more detailed analysis, as presented below and in Sections 5.1 and S9.

4.1.1 Swiss Plateau catchments

Validation results of the Swiss Plateau catchments show that the KGE ranges between 0.67 and 0.87 and the RMSE between 0.91 and 1.81 °C (Table 4) These values indicate a good performance compared to previous studies (e.g. Köplin et al., 2010; Råman Vinnå et al., 2018). The simulated validation time series for both discharge and water temperature lie in the range of the historical variability of the measurements (Figures S6 to S19). The dynamics of high river temperature and discharge events as well as the annual cycles are well captured. There are no strong seasonal patterns of errors in river temperature (except for a slight underestimation in spring), and there is no correlation between errors in simulated discharge and river temperature (Figures S6 to S19). However, there is an overestimation of discharge in winter, but without an impact on the simulated water temperature.

Table 4. Performance of the StreamFlow model during the calibration and validation periods evaluated with Kling-Gupta efficiency (KGE) for discharge and RMSE for water temperature.

Catchment	Calibration period		Validation period	
	KGE (-)	RMSE (°C)	KGE (-)	RMSE (°C)
Swiss Plateau Catchments				
Birs	0.84	1.06	0.86	1.20
Broye	0.75	0.91	0.78	0.91
Ergolz	0.85	1.17	0.84	1.39
Eulach	0.74	1.18	0.67	1.08
Kleine Emme	0.79	1.08	0.70	1.07
Rietholzbach	0.74	1.63	0.75	1.81
Suze	0.84	1.68	0.87	1.50
Alpine Catchments				
Inn	0.94	1.02	0.87	1.25
Kander	0.89	0.69	0.78	1.18
Landwasser	0.83	0.92	0.72	1.15
Lonza	0.92	0.89	0.91	1.01
Lütschine	0.89	1.28	0.84	1.37

The error on river temperature is slightly larger for the Suze catchment compared to the other Swiss Plateau catchments (see Table 4 and Figure 3). We attribute this to the fact that this region is karstic, with enhanced water infiltration and resurgence to the surface, which impacts the water temperature. In addition, the gauging station is situated downstream of a cement factory, making anthropogenic influence on the stream temperature likely (see Michel et al., 2020). In the Eulach catchment, a large fraction of water (about 33 %) is directly lost to deeper groundwater via the calibrated water loss parameter. This is coherent with the ratio of precipitation and discharge observed in this catchment as described in Huggenberger and Epting (2011). A sizeable soil water loss is also modelled for the Birs. Again, this is not surprising since both the Birs and Eulach catchments have been selected deliberately because of their river-fed ground-watershed in order to be used in the study of Epting et al. (2021). Finally, the longer run performed for the Broye catchment (2002-2018, Figure S3) shows that river temperature in the extremely warm years 2003, 2015, and 2017 and the relatively cooler years 2007 and 2014 is well captured by the model.

4.1.2 Alpine catchments

Alpine3D and StreamFlow perform very well in terms of snow cover and discharge simulation in 2 of the 5 Alpine catchments. The annual discharge cycle is well reproduced for the Kander (Figures S22, S23, and S31) and the Lütschine (Figures S28, S29, and S33). The results are less good for the Inn (Figures S26, S27, and S30) and the Lonza (Figures S26 and S27); this is visible from the discharge plots, even though it is not necessarily reflected in the KGE values. For the Landwasser (Figures S24, S25, and S32), the melt season starts too early, as shown by the negative correlation between discharge and river temperature errors in spring and summer. These issues highlight the difficulty of accurately reproducing snow and glacier melt-induced




Figure 3. Daily mean water temperature observed (black) and simulated (red) over the calibration periods (left of dotted line) and over the validation period (right of dotted line) for four catchments: the Broye (Swiss Plateau), the Inn (Alpine), the Landwasser (Alpine), and the Suze (Swiss Plateau). These four catchments were chosen to represent the variation in the catchment type. Note that the extent of the y-axes (daily mean water temperature range) is different for every panel. Other catchments are shown in Section S6.

runoff dynamics in Alpine environments, even when using a very sophisticated snow model. A possible explanation is the scarcity of meteorological measurements in Alpine regions, which according to Magnusson et al. (2011) and Schlögl et al. (2016) decreases the performance of models.

Regarding water temperature, lower model performance is obtained for Alpine catchments in summer compared to Swiss Plateau catchments. Sudden water temperature peaks of up to $+4^{\circ}\text{C}$ above the corresponding measurements are occasionally simulated in summer, leading to an error of up to $+2^{\circ}\text{C}$ in the summer seasonal mean (Figure 3).

Another illustration of overestimated summer water temperatures is the summer of 2003. Michel et al. (2020) used historical measurements to show that large amounts of snow and glacier melt contribute to mitigate increased river temperature during hot summers. In their analysis, Alpine catchments in Switzerland were not affected by the extremely warm summer of 2003. In the present study, the model overestimates the temperature anomaly for the year 2003 in the high-alpine Lonza catchment, while

it produces correct results for the lowland Broye catchment (Figure S3). Ample discussion on this issue and its consequences is presented in Section 5.1.

4.2 Climate change simulations

Simulation results are shown in terms of changes (delta) compared to the reference period 1990-2000. Absolute change is used for water, soil, and air temperature, and relative change for other variables. Detailed plots for each catchment are included in Section S10, Figures S60 to S97. The results for annual mean river temperature for all catchments are summarized in Table 5. Annual and seasonal values for all catchments are presented in Tables S9 to S12. Boxplots presented in this section are constructed from all CC scenarios and all individual years, so the range shows both the model uncertainty, the natural inter-annual variability, and the catchment's variability when multiple catchments are combined.

Before simulating the future discharge and river temperature, the performance of the models when forced with CC scenarios over the historical period was assessed. Section S8 shows that forcing the models with CC scenarios leads to small over- or underestimation of the total discharge in Alpine catchments. This is expected since the used CC scenarios show lower performance for precipitation in Alpine areas compared to Swiss Plateau areas (Warscher et al., 2019). Overall, it is confirmed that the output of Alpine3D and StreamFlow, when forced with CC scenarios over an historical time period, is consistent with the output obtained when forcing the models with measured meteorological inputs.

4.2.1 Swiss Plateau catchments

The model results from CC simulations over the Swiss Plateau catchments are similar among all considered catchments. The similarities in river warming between catchments show that catchment size does not play a noticeable role for the warming rate, as already observed for past periods (Michel et al., 2020).

Figure 4 shows the combined results for all considered Swiss Plateau catchments. For short-term projections, i.e. the period 2030-2040, the mean trend of averaged annual river temperature for the Swiss Plateau catchments is $+0.27 \pm 0.03$ °C per decade (combining all 3 RCPs, the uncertainty indicated is the standard deviation), which is in line with the $+0.33 \pm 0.03$ °C per decade observed over entire Switzerland for the period 1979-2018 (Michel et al., 2020). No significant annual discharge trends are modelled for this period.

Over the same period, the mean air temperature trend over Swiss Plateau catchments is 0.33 ± 0.02 °C per decade, corresponding to a ratio between river and air temperature trends of 0.8 for this period, which compares very well to the ratio obtained from historical observations (Michel et al., 2021b) and in the studies of Null et al. (2013) and Leach and Moore (2019). This result underlines the ability of the model chain to correctly capture the observed changes in the contemporary period. The expected water temperature increase is consistently more pronounced in summer than in winter for all studied catchments, time periods, and CC change scenarios.

For the periods 2055-2065 and 2080-2090, some differences between the RCP emission scenarios appear. For RCP2.6, no relevant additional changes are expected beyond 2030-2040. For RCP4.5, the situation between 2055-2065 and 2080-2090 remains similar, while for RCP8.5 there is an acceleration of changes in discharge and temperature. By the end of the century,




Figure 4. Changes in river temperature (ΔT), air temperature (ΔTA), discharge (ΔQ), and precipitation ($\Delta PSUM$), from left to right column, over the periods 2030-2040, 2055-2065, and 2080-2090, compared to the reference period 1990-2000 for the Swiss Plateau catchments and for the 3 RCPs. The first row shows the annual changes, the second row the winter seasonal changes, and the last row the summer seasonal changes.

the median annual river temperature increase reaches $+3.5^{\circ}\text{C}$ for RCP8.5. For some specific summers and CC scenarios, the warming can reach up to $+6.5^{\circ}\text{C}$ (Table S9). These results are in line with recent predictions of Swiss lake surface water temperature over the 21st century (Råman Vinnå et al., 2021). They are also comparable to results in the literature for other regions of the world with a comparable climate regime and using similar climate change scenarios and time periods. For example, Piotrowski et al. (2021) obtain an annual warming of $+2$ to $+3^{\circ}\text{C}$ for the period 2070-2100 for RCP8.5 in lowland catchments situated in the United States and in Poland using statistical and machine learning models. Similarly, a large-scale study by van Vliet et al. (2013) predicted a warming of $+3^{\circ}\text{C}$ by the end of the century for rivers in central Europe using the former SRES A2 scenarios (which predict a warming slightly lower than RCP8.5).

Changes in annual discharge patterns, linked to precipitation changes, appear with RCP4.5 and RCP8.5 in the periods 2055-2065 and 2080-2090 (more marked for RCP8.5 and for the latter period). An increase in winter discharge and a decrease in summer discharge are simulated with no significant change at the annual scale, except for RCP8.5 by the end of the century due to enhanced evapotranspiration (ET). Simulated changes in ET for four catchments are shown in Figure S96, indicating an median increase in ET of about $+15\%$ by the end of the century in the summer season, combined with a deficit of precipitation

Table 5. Change of annual mean river temperature for all 3 periods and 3 RCPs compared to the reference period 1990-2000. The median value of all years and scenarios is indicated together with the range of the values.

Catchment	Δ River temperature ($^{\circ}$ C)								
	2030-2040			2055-2065			2080-2090		
	RCP2.6	RCP4.5	RCP 8.5	RCP2.6	RCP4.5	RCP 8.5	RCP2.6	RCP4.5	RCP 8.5
Plateau	+0.9 [+0.1,+1.4]	+1.1 [+0.5,+1.4]	+1.1 [+0.5,+1.5]	+0.9 [+0.3,+1.2]	+1.5 [+0.8,+2.1]	+2.1 [+1.2,+2.5]	+0.9 [+0.1,+1.6]	+1.7 [+0.8,+2.5]	+3.3 [+2.1,+4.4]
Birs	+1.0 [+0.2,+1.3]	+1.0 [+0.8,+1.3]	+1.2 [+0.5,+1.5]	+1.0 [+0.5,+1.2]	+1.4 [+1.0,+2.1]	+2.0 [+1.4,+2.4]	+0.9 [+0.4,+1.5]	+1.8 [+1.2,+2.4]	+3.3 [+2.5,+4.4]
Broye	+1.1 [+0.0,+1.6]	+1.1 [+0.7,+1.4]	+1.2 [+0.5,+1.7]	+1.0 [+0.5,+1.3]	+1.5 [+0.9,+2.3]	+2.2 [+1.4,+2.6]	+1.0 [+0.3,+1.7]	+1.8 [+1.1,+2.5]	+3.6 [+2.6,+4.7]
Ergolz	+1.0 [+0.2,+1.3]	+1.0 [+0.7,+1.2]	+1.1 [+0.5,+1.4]	+0.9 [+0.5,+1.2]	+1.3 [+0.9,+2.1]	+1.9 [+1.4,+2.4]	+0.9 [+0.4,+1.5]	+1.7 [+1.1,+2.3]	+3.2 [+2.3,+4.4]
Eulach	+1.0 [-0.0,+1.4]	+1.0 [+0.6,+1.2]	+1.0 [+0.3,+1.6]	+1.0 [+0.4,+1.3]	+1.4 [+0.8,+2.3]	+1.9 [+1.2,+2.6]	+0.9 [+0.3,+1.6]	+1.6 [+1.0,+2.4]	+3.2 [+2.4,+4.6]
Kleine Emme	+1.1 [+0.3,+1.7]	+1.2 [+0.7,+1.5]	+1.3 [+0.7,+1.7]	+1.0 [+0.7,+1.5]	+1.7 [+1.0,+2.4]	+2.4 [+1.6,+2.8]	+1.1 [+0.4,+1.9]	+2.0 [+1.3,+2.9]	+4.2 [+2.8,+5.3]
RHB	+1.0 [+0.3,+1.5]	+1.1 [+0.5,+1.6]	+1.1 [+0.5,+1.6]	+1.0 [+0.5,+1.4]	+1.4 [+0.8,+2.4]	+2.1 [+1.4,+2.7]	+0.9 [+0.3,+1.8]	+1.7 [+1.0,+2.6]	+3.6 [+2.2,+5.0]
Suze	+0.9 [+0.1,+1.4]	+1.1 [+0.5,+1.4]	+1.1 [+0.5,+1.5]	+0.9 [+0.3,+1.2]	+1.5 [+0.8,+2.1]	+2.1 [+1.2,+2.5]	+0.9 [+0.1,+1.6]	+1.7 [+0.8,+2.5]	+3.3 [+2.1,+4.4]
Alpine	+0.7 [+0.3,+1.2]	+0.8 [+0.6,+1.1]	+0.9 [+0.4,+1.4]	+0.8 [+0.5,+1.2]	+1.3 [+0.7,+2.0]	+1.7 [+1.1,+2.3]	+0.8 [+0.4,+1.6]	+1.6 [+0.9,+2.4]	+3.3 [+1.9,+4.7]
Inn	+0.8 [+0.3,+1.3]	+0.9 [+0.5,+1.3]	+0.8 [+0.6,+1.4]	+0.8 [+0.5,+1.2]	+1.3 [+0.7,+2.1]	+1.8 [+0.9,+2.6]	+0.8 [+0.2,+1.3]	+1.5 [+0.5,+2.3]	+3.1 [+2.1,+4.6]
Kander	+0.6 [+0.3,+0.9]	+0.7 [+0.3,+0.9]	+0.7 [+0.4,+1.1]	+0.7 [+0.3,+1.2]	+1.2 [+0.5,+1.8]	+1.6 [+0.8,+2.5]	+0.7 [+0.3,+1.4]	+1.4 [+0.7,+2.4]	+2.9 [+1.4,+4.3]
Landwasser	+1.0 [+0.3,+1.6]	+1.1 [+0.6,+1.4]	+1.2 [+0.6,+1.7]	+1.0 [+0.6,+1.5]	+1.7 [+0.5,+2.4]	+2.2 [+1.1,+3.1]	+1.1 [+0.2,+1.8]	+1.9 [+0.9,+2.8]	+3.9 [+2.3,+5.3]
Lonza	+0.8 [+0.1,+1.2]	+0.8 [+0.5,+1.1]	+0.9 [+0.6,+1.3]	+0.8 [+0.4,+1.3]	+1.3 [+0.4,+1.9]	+1.8 [+0.8,+2.6]	+0.9 [-0.0,+1.4]	+1.5 [+0.8,+2.5]	+3.1 [+1.6,+4.8]
Lutschine	+0.7 [+0.3,+1.2]	+0.8 [+0.6,+1.1]	+0.9 [+0.4,+1.4]	+0.8 [+0.5,+1.2]	+1.3 [+0.7,+2.0]	+1.7 [+1.1,+2.3]	+0.8 [+0.4,+1.6]	+1.6 [+0.9,+2.4]	+3.3 [+1.9,+4.7]

of -13 % for the emission scenario RCP8.5. A special case is the Eulach catchment, which is much more urbanised compared to the other studied catchments, explaining the lower change in ET observed there. The changes in ET are similar for the RCP4.5 and RCP8.5 scenarios and only about 1.5 times larger than the one expected with the RCP2.6 scenarios, showing that ET will be limited mainly by water availability and that potential additional water during wetter summers will have a very high potential to evaporate. This is also seen from the large variability in ET for the RCP8.5 scenarios.

4.2.2 Alpine catchments

At annual scale, the simulated water temperature increase in Alpine catchments is close to that observed across the Swiss Plateau (see Table 5), despite a slightly higher air temperature increase (see Figures 4 and 5). The warming is more limited for the early periods in Alpine environments, but reaches the same level as in the Swiss Plateau catchments towards the end

of the century. This slower warming in Alpine catchments compared to Swiss the Plateau catchments in early periods of the 21st century is coherent with current trends observed in Switzerland (Michel et al., 2020). At seasonal time scale, the change in river temperature is different between Swiss Plateau and Alpine catchments. In the Swiss Plateau catchments (Figure 4), the warming is slightly higher in summer than in winter, with the spring and fall seasons in between. In Alpine catchments (Figure 5), the warming is rather limited in winter and spring, but 2 to 3 times higher during summer and fall.

To expand the analysis to other quantities simulated by Alpine3D, Figure 6 shows the simulated evolution of snow and ice water equivalent, of solid precipitation, and of soil surface temperature on a yearly and seasonal basis, for all considered Alpine catchments combined (for individual catchments, see Figures S672 to S76). The annual discharge and temperature cycles for the 4 time periods and the 3 RCPs are shown for the Inn catchment in Figure 7 (see also Figures S77 to S80 for the other Alpine catchments). Finally, maps of snow and glacier covers for the five Alpine catchments, the periods 1990-2000 and 2080-2090, RCP2.6 and 8.5, and for the months of February, May, and December are shown in figures S81 to S95.

During the winter season (Figure 5), despite an air temperature increase similar to that projected for the Swiss Plateau, the river temperature increase is very limited, only reaching a median value of $+1.4^{\circ}\text{C}$ at the end of the century with RCP8.5 scenarios. This reduced winter warming in Alpine catchments is consistent with observations from the past decades (Michel et al., 2020). At the same time, an increase in discharge between $+9\%$ in 2030-2040 (for the 3 RCP scenarios) and up to $+35\%$ for RCP8.5 at the end of the century is expected. On the long term, no significant difference in winter precipitation is expected. The combination of the lower fraction of solid precipitation (i.e. more rain) and the enhanced snowmelt explains the increase in winter discharge.

The most important limiting factor for the Alpine river temperature rise in winter (even with a mean air temperature rise of up to $+4.2^{\circ}\text{C}$ for RCP8.5 at the end of the century compared to the reference period), is that the air temperature mostly remains below freezing at higher elevations, especially during the night. In these periods, the river temperature stays above the air temperature and does not experience any warming. In addition, for near-future periods or low emission scenarios, the snow cover often prevents an increase in soil temperature in winter (Figure 6).

During the spring season, earlier snowmelt occurs (Figure 6), which gets even more pronounced towards the end of the century and for RCP8.5 (the melt contribution to runoff will increase up to 20%). In addition, a significant reduction of solid precipitation is expected in future spring seasons. These effects combined lead to a considerable increase in discharge and a shift of the peak runoff towards earlier times in the year. Even for the low and moderate emission scenarios RCP2.6 and RCP4.5, this shift is clearly visible at the end of the century. For RCP8.5, we observe a flatter peak occurring almost 2 months earlier than during the reference period (see Figure 7 and S77 to S80). These results are consistent with findings of Muelchi et al. (2020) concerning the evolution of discharge. Despite this increase in spring discharge, the river warming is slightly more marked in spring than in winter for the periods 2055-2065 and 2080-2090. As discussed in Section 5.1, the advection of cold water from snowmelt is not captured in the used model chain. Accordingly, the river temperature warming might be overestimated in spring since the predicted enhanced melting might inject considerable amounts of cold water to the stream network.




Figure 5. Changes in river temperature (ΔT), air temperature (ΔTA), discharge (ΔQ), and precipitation ($\Delta PSUM$), from left to right column, over the periods 2030-2040, 2055-2065, and 2080-2090 and for the 3 RCPs, compared to the reference period 1990-2000, averaged over all considered Alpine catchments. Row 1 shows the annual change, row 2 the winter seasonal change, row 3 the summer seasonal change, row 4 the spring seasonal change, and row 5 the fall seasonal change.

The summer season shows distinctively different changes in river temperature patterns and intensity between RCPs and time periods. For the near future (2030-2040), the expected river temperature increase remains below the air temperature increase, alike for the Swiss Plateau catchments. Advancing in time and looking especially at RCP8.5 scenarios, the river warming catches up with the air temperature rise leading to a median river warming of $+5.4^{\circ}\text{C}$ ($+5.9^{\circ}\text{C}$ for the air temperature, Table S9




Figure 6. Changes in snow water equivalent in the catchments (Δ SWE), in ice water equivalent (mass of glacier ice and snow in glacier pixels) in the catchments (Δ IWE), in solid precipitation (Δ PSUM snow), and in soil surface temperature (Δ TS), from left to right column, over the periods 2030-2040, 2055-2065, and 2080-2090 and for the 3 RCP scenarios, compared to the reference period 1990-2000, averaged over all considered Alpine catchments. Row 1 shows the annual change, row 2 the winter seasonal change, row 3 the summer seasonal change, row 4 the spring seasonal change, and row 5 the fall seasonal change.

and S10). However, since overestimation was observed during the model validation for summer over the Alpine catchments, these results need to be carefully interpreted and discussed (see Section 5.1).

During fall, a discharge reduction occurs at the beginning of the season, caused by the shift of annual peak discharge to earlier in spring and summer, followed by a discharge increase later in the season due to an increased fraction of liquid precipitation




Figure 7. Annual cycle of discharge (top) and river temperature (bottom) of the Inn catchment. The cycles are obtained by computing the average for each day of the year and by applying a circular moving average of 30 days. Dark lines show the mean for each RCP over each period, light lines show individual scenarios. Black dashed lines indicate the mean over the reference period 1990-2000 (only shown in subsequent periods to ease comparison).

and rapid melting of occasional snowfall. Such fall melt events contribute to cool the soil; accordingly, the water temperature increase is similar to the one predicted over the Swiss Plateau.

5 Discussion

5.1 Model chain performance

For the Swiss Plateau catchments, the errors in river temperature (RMSE) obtained during the calibration and validation periods are far below the CC signal for RCP4.5 and RCP8.5, which underlines the robustness of the simulated trends. The results obtained are coherent with past and current observations in Switzerland and in central Europe (Moatar and Gailhard, 2006; Webb and Nobilis, 2007; Arora et al., 2016; Michel et al., 2020) and are in agreement with other results in the literature, both in terms of predicted changes in discharge and water temperature, and in terms of processes and CC sensitivity (Null et al., 2013; Ficklin et al., 2014; Du et al., 2019; Leach and Moore, 2019; Wondzell et al., 2019; Muelchi et al., 2020; Piotrowski et al., 2021). The studied catchments can be assumed to be representative for undisturbed Swiss catchments in general (Michel et al., 2020).

For Alpine catchments, the calibration results for discharge and water temperature show a low model error in winter, spring and fall. Over these seasons, results are coherent with observed trends. Summer discharge and snow depletion in the melt season are not perfectly captured in all catchments, but results are coherent with the literature (Brunner et al., 2019a; Muelchi et al., 2020). During summer, simulated river temperatures show instances of sudden overestimation in four out of the five studied Alpine catchments. These overestimations do not appear during all summers and there is no temporal coincidence between the instances of temperature overestimation and low discharge conditions. Furthermore, only two of the rivers concerned with this overestimation problem (the Inn and the Landwasser) show a correlation between river temperature and discharge errors (Figures S21, S23, S25, S27, and S29), suggesting that the underestimation of summer discharge cannot explain the overestimation of river temperature.

Section S9 extensively discusses the influence of solar radiation and other energy fluxes on temperature simulation errors in Alpine catchments. In summary, it can be stated that the approximation of topographic shading due to the spatial resolution of Alpine3D and the underestimation of riparian vegetation shading can slightly contribute to the overestimation of summer river temperature, but does not explain the magnitude and behaviour of the observed errors. The analysis rather suggests that the small upstream reaches are overly sensitive to variations in the forcing, causing too high temperature in the upper part of the catchment, which then gets advected downstream.

The most probable hypothesis explaining this over sensitivity is that some mechanisms are not explicitly captured in the model. All the water draining from the snowpack is assumed to infiltrate the soil at the pixel scale in Alpine3D, while the runoff at the bottom of the soil column is collected in StreamFlow at the sub-catchment scale, after a transfer through the two linear reservoirs emulating fast and delayed lateral subsurface runoff. The water leaving these two reservoirs inherits the temperature determined by the sub-catchment temperature scheme in use. The fact that the model performs well in Swiss Plateau catchments regardless of catchment size and local topography suggests that the problem for Alpine catchments is related to processes that are only at play at high elevations. The following processes are not explicitly simulated in StreamFlow (in any of the implemented schemes for infiltrating soil water temperature) and can all contribute to the mentioned temperature overestimation during summer: i) cold water advection from remaining, hydrologically well connected snow patches (connected

via surface and subsurface flow, see Yan et al., 2021), ii) cold water advection from local groundwater systems (see Thornton et al., 2021), iii) cold water advection from melting glacier ice (if present, see Du et al., 2021).

The chosen HSPF approach for sub-catchment infiltrating water temperature is shown to generally perform well in comparison to other approaches (see Section 3.4 and Leach and Moore, 2015), but it is exclusively based on air temperature and cannot explicitly capture any of the three processes mentioned above (note that the other two available approaches lead to even more problematic results during the summer season). This has only little impact on the simulated river temperatures in spring, when the air temperature is still relatively low. In summer, however, ignoring these cooling mechanisms can explain the exaggerated sensitivity of small upstream reaches. Figure S59 shows the infiltrating water temperature simulated by the HSPF scheme over the Landwasser catchment and its correlation with the simulated overestimation in summer, confirming that the HSPF scheme might be the cause of the overestimation. Our results suggest that this simple approach is not suited for complex Alpine terrain and that a different and probably more complex method should be developed.

The cooling effect from snow and glacier melt, which are missing in the model, can be expected to become less important in the future, because of the general glacier retreat and the increase of the average winter snow line. In addition, the Alpine3D simulations performed here show that in spring, the median of the SWE reduction under RCP8.5 by the end of the century is about -60 %, meaning that the available snow to be melted in summer is reduced by the same amount.

In fact, the lack of proper cold water input parameterization can even be expected to actually result in an underestimation of the computed river warming in Alpine catchments. This would arise if the CC signal is computed with respect to a past period with summer temperature overestimation caused by missing cold water advection, and if this effect disappears in the future (Du et al., 2021). However, we cannot conclusively attribute the overestimation to snow and glacier melt being not captured, and other factors might be at play here.

Consequently, the results obtained for summer warming in Alpine rivers should be interpreted with caution. The main result of this part of the study is to show the need for more complex models to reliably simulate all the water flowpaths and thermal interactions in Alpine terrain.

Despite the limitations for the summer season in Alpine catchments, the simulated seasonal warming pattern, particularly pronounced in summer, is in agreement with results by Du et al. (2019) for the partially glaciated Athabasca catchment in Canada, by Piotrowski et al. (2021) for the mountainous Cedar catchment in Poland, and by Ficklin et al. (2014) over the Columbia river basin in the western US and Canada. For the period 2081-2100 and RCP8.5, Ficklin et al. (2014) obtained river temperature warming comparable or higher than that of the air temperature for the upper part of the catchment, similar to our results for Alpine catchments.

In summary, we show the high skill of the used physics-based model chain to reproduce discharge and water temperature in the Swiss Plateau catchments. For the Alpine catchments, good results are obtained in all seasons except for summer and mechanisms explaining this lower performance are provided.

5.2 Climate change impact

The expected increase in river temperature will have a large impact on both natural and societal systems. To evaluate this future impact, we use two metrics introduced by Michel et al. (2020): i) The number of days per year when the daily maximum river temperature is above 25°C (this is a legal threshold in Switzerland for unrestricted water usage, e.g. for industrial cooling), and
5 ii) a metric indicating the number of days per year when salmonid fish are exposed to Proliferative Kidney Disease (PKD). The latter metric is based on the model of Carraro et al. (2016) counting the number of days per year for which the minimum daily temperature exceeds 15°C for at least 28 consecutive days. Values for these two indicators are shown for four catchments in Figure 8. Note that these two metrics are meaningful only for Swiss Plateau catchments.

The metrics values obtained over the historical period match well the corresponding values obtained from measurements
10 (Michel et al., 2020), underlining again the robustness of the results obtained when the models are forced with CC scenarios. For each of the four catchments shown in Figure 8, both indicators grow over time and with increased greenhouse gas emissions. Catchments such as the Birs and the Eulach, which are currently less prone to high river temperatures, will reach and exceed both the legal threshold of 25°C and the PKD critical value more frequently in the future. By the middle of the century, river temperatures conditions during summer will be favourable for the spread of PKD in all 7 investigated catchments (for
15 all RCPs), with possibly devastating impact on salmonid fish population. For catchments with relatively warm river water under current conditions, such as the Broye and the Kleine Emme, the legal limit of 25°C will be reached almost every year already by 2030-2040 regardless of the emission scenario. By the end of the century and with high emission scenarios, the river temperature will be above this threshold for around 2 months per year in these 2 catchments. This will prompt either stopping regular water usage for industry and cooling in such catchments, or a necessary adaptation of current regulation and legislation,
20 at the risk of further enhancing the impacts and increasing the stress and pressure on these ecological systems.

In Alpine catchments, the large decrease in summer snow cover and the shrinking of glaciers (Huss and Hock, 2018; Compagno et al., 2021) lead to a drastic warming of the soil surface owing to lower surface albedo and the absence of a thermally insulating layer (Figure 6). In 2030-2040 (all scenarios) and during the second part of the 21st century under RCP2.6, this soil warming remains limited, with an increase lower than that of the air temperature. However, for RCP4.5 and RCP8.5 and
25 periods further ahead, these changes in land cover cause a substantial soil temperature increase, which can exceed the warming of the air temperature. Such an increase in soil temperature is not simulated for the lowland catchments (Figure S97). In addition, Alpine catchments will experience a sharp decrease in discharge during the second half of the summer (see Figure 7), which might exacerbate the sensitivity of the rivers to energy input and contribute to higher temperatures in the summer season. Therefore, despite the uncertainty linked to the simulated summer river temperatures, our results provide strong evidence of
30 a more pronounced warming during summer in Alpine rivers compared to lowland rivers (which is also consistent with the literature).

Discharge reduction is mentioned in the previous paragraph as a factor of enhanced water warming. From simple thermodynamics, we can expect reduced discharge to have a direct impact on river temperature. However, historical data do not exhibit a strong correlation between changes in discharge and changes in river temperature during summer, except during unusually




Figure 8. Left: Number of days per year when the river temperature is above the threshold of 25°C, for each year in each time period and for each scenario, for 4 Swiss Plateau catchments. Right: Number of days per year when salmonid populations are exposed to PKD, based on the metric presented in Michel et al. (2020), for each year in each time period and for each scenario, for 4 Swiss Plateau catchments. These 4 catchments were chosen to represent the variation in the Swiss Plateau catchment type.

warm and dry summers when low discharge exacerbates the warming (Michel et al., 2020). In Alpine catchments, the summer mean water temperature has been shown to have a low inter-annual variability, even during dry and warm summers (Michel et al., 2020).

To investigate the relationship between changes in river temperature and discharge during summer, we apply uni- and multi-
 5 variate linear models on ΔT , taking ΔTA , ΔQ , or both as predictors. The models are applied separately for the Swiss Plateau and for the Alpine catchments for the summer season, the period 2080-2090, and for RCP8.5 (Table 6 and Figure S98). For the Swiss Plateau catchments, both ΔTA and ΔQ are identified as significant predictors when used separately (with an adjusted- R^2 of only 0.06 when using ΔQ), but when used together the significance of ΔQ disappears and the explanatory power of the model is not improved compared to using ΔTA alone. Thus, in the Swiss Plateau catchments, there is no strong correlation
 10 between changes in summer discharge and changes in river temperature. This is coherent with historical observations and with results by Wondzell et al. (2019), which show a much weaker impact of discharge change on water temperature compared to changes in air temperature for the upper Middle Fork John Day River, northeast Oregon, USA.

In Alpine catchments, ΔQ remains significant in the multivariate model and increases the R^2 value from 0.69 (when using only ΔTA) to 0.81. In addition, using ΔQ alone allows to explain almost half of the variability in ΔT . Due to the problem of
 15 overestimated summer river temperatures in Alpine catchments, we have low confidence in this specific result and cannot draw

a convincing conclusion on possible differences between lowland and Alpine catchments concerning the sensitivity of river temperature to discharge. Accurately quantifying this sensitivity in Alpine regions in a changing climate, with the expected decrease in snow and glacier cover, would be of great interest in further studies.

Table 6. Summary of the linear models for changes in river temperature (ΔT) using changes in air temperature (ΔTA), water discharge (ΔQ), or both, as predictors. Changes in the period 2080-2090 compared to the reference period 1990-2000 are used for RCP8.5. The table shows the coefficients, the *p-values* associated to each predictor, and the adjusted R^2 (discounting the effect of additional explanatory variables) of each model. The linear models are applied separately for the Swiss Plateau catchments (top) and the Alpine catchments (bottom).

Swiss Plateau catchments			
Predictor(s)	Coefficient(s)	<i>p-value(s)</i>	R^2
ΔTA	0.82 ± 0.02	$<2e-16$	0.71
ΔQ	-0.01 ± 0.001	$3e-8$	0.06
ΔTA and ΔQ	0.82 ± 0.02 and $4e-7 \pm 8e-4$	$<2e-16$ and 1	0.71
Alpine catchments			
Predictor(s)	Coefficient(s)	<i>p-value(s)</i>	R^2
ΔTA	1.14 ± 0.04	$<2e-16$	0.69
ΔQ	-0.05 ± 0.003	$<2e-16$	0.44
ΔTA and ΔQ	0.92 ± 0.04 and -0.03 ± 0.002	$<2e-16$ and $<2e-16$	0.81

5.3 Current limitations and future model development

- 5 Besides the problem of simulating summer river temperature in Alpine catchments, there are a few other shortcomings in the models used. Riparian vegetation is not completely accounted for in the model chain Alpine3D-StreamFlow, while it is shown to have a strong local effect on river temperature (see among other Kalny et al., 2017; Trimmel et al., 2018; Dugdale et al., 2018; Wondzell et al., 2019). The integration of riparian vegetation would be a necessary addition in such models to assess its effectiveness as a mitigation strategy. Also, no dynamic interaction with the water table is represented in the model.
- 10 with groundwater might be a significant factor for water temperature in some catchments (Qiu et al., 2019; Johnson et al., 2020; O’Sullivan et al., 2020). Further model improvement to better represent the interplay of water infiltration in soil, cold water advection and groundwater dynamics might be key elements in future CC impact assessments on water temperature because this might come in parallel with recently developed methods for groundwater and irrigation water management (García-Gil et al., 2015). Such methods could even include specific thermodynamic water management, such as water infiltration during
- 15 winter for river cooling during summer (Epting et al., 2013).

Further extensions are needed to account for anthropogenic influences like dams, pumping, deviations, intakes or discharge, which influence the water temperature (Michel et al., 2020; Seyedhashemi et al., 2021) but are not considered in the model used, limiting the current study to mostly natural undisturbed catchments. In addition, Michel et al. (2020) showed with historical

data that the presence of lakes along the watercourse changes the warming rate of rivers. This two-way interaction in river-lake-river systems also remains to be investigated in more detail in future studies, especially considering the expected shifts in lake mixing (Råman Vinnå et al., 2021) and in the Alpine flow regime.

Future extreme events are not covered here because the used models are not validated for extreme events and the forcing time series are not capturing such events (Michel et al., 2021b). In central Europe, a clear link between summertime dry spells and heat waves has been found (Fischer et al., 2007b, a) and both are expected to increase in frequency and amplitude in the future (NCCS, 2018). As a consequence, it is likely that even more pronounced warming than predicted here will result during extremely warm and dry summers in the future.

Finally, only one model chain is used for the snow and hydrological simulations, while significant differences can be obtained across models in terms of discharge and water temperature simulation over climate change periods (Carletti et al., 2021; Piotrowski et al., 2021).

6 Conclusion

This work presents the first extensive study of climate change (CC) impact on river temperatures in Switzerland and, to the best of our knowledge, in Alpine areas. A chain of physics-based models is used with 21 CC scenarios, spanning three different emission pathways (RCP2.6, RCP4.5, and RCP8.5). The model chain is applied to two categories of catchments, namely the lowland Swiss Plateau catchments, and the higher elevation Alpine catchments, which exhibit different discharge and thermal regimes.

We demonstrate the ability of a physics-based model chain to reliably simulate the river temperature in a variety of catchments in Switzerland, with a notable exception for summer water temperature in Alpine catchments. We tested several aspects of the physics-based models, such as the impact of using different calibration periods, using a lumped approach versus a discretized approach for water routing, or using a simple in-stream routing computation versus a more complex scheme. Higher complexity routing and discretization schemes do not improve the quality of the simulations. Results show the critical importance of correctly computing the water temperature entering the stream network in Alpine catchments; the results furthermore underline that omitting processes, such as cold water advection originating from snow and ice melt or local cold water storage, could lead to an overestimation of the river temperature during summer. In this sense, this study offers a broad and solid foundation for future development and application of physics-based hydrological models in the context of CC modelling. The study identifies a few flaws of the models and provides evidence for necessary improvements in these models.

The results of the climate change impact study show that a distinct warming of river water is expected for the 21st century in all investigated regions. By the end of the century (2080-2090), the median annual river temperature increase in the studied catchments amounts to +0.9°C for RCP2.6, (with a range of 0.0-1.9°C), and to +3.3°C for RCP8.5 (1.4-5.3°C) compared to the reference period 1990-2000. A significant reduction in summer discharge is predicted for high emission scenarios by the end of the century, with a median value of -27 % for the Swiss Plateau catchments and of -31 % for the Alpine catchments. At the seasonal time scale, the warming on the Swiss Plateau and in the Alpine regions exhibits different patterns. On the

Swiss Plateau the summer warming only slightly exceeds the winter one (by about 20 %), and it is only weakly affected by changes in discharge. In the Alpine catchments, the warming is rather limited during the cold months. In summer, the identified model limitations regarding river temperature simulation lower our confidence in the exact value of the predicted warming. However, we show that sizeable decrease in snow and ice cover expected during summer will lead to a significant increase in soil temperature, which then will most likely lead to large further river warming. In addition, this study quantifies the expected reduction in cold water advection from melting glacier and snow, which is also expected to contribute to the summertime river warming in Alpine catchments.

Our results show that river systems in Switzerland (and likely the entire Alps and adjacent regions) will undergo substantial changes in the near future, both in terms of water temperature and water availability. Two metrics have been used to quantify future impacts of river warming on ecology and on industrial cooling water use. This highlights the urgent need for both adaptation and mitigation strategies. The current rapid advances in water temperature modelling should thus cross the boundaries of purely scientific applications and be made available to a broader public for operational use in water temperature forecast and warning systems. Future development of monitoring systems will also be of great importance for improving the understanding of water temperature processes and their representation in models.

Author contributions. The paper was written by Adrien Michel with contributions from all co-authors. Adrien Michel compiled the data, further developed and ran the models, and performed the analysis. Nander Wever supported the model development. Harry Zekollari performed the GloGEMflow simulations. Adrien Michel, Bettina Schaeffli, Michael Lehning, and Hendrik Huwald designed the study. All authors gave critical feedback on the manuscript.

Competing interests. BS is editor at HESS. The other authors declare that they have no conflict of interest.

Code and data availability. All results produced throughout this paper are either publicly available on Envidat at <https://www.envidat.ch/#/metadata/dataset-for-future-water-temperature> (Michel et al., 2022) or available upon request to the main author for large datasets. The source codes of MeteoIO, SNOWPACK, Alpine3D, and StreamFlow are available at <https://models.slf.ch>. The following versions have been used in this work: MeteoIO 3.0.0 (rev 2723), SNOWPACK 3.6.1 (rev 1878), Alpine3D 3.2.1 (rev 570), and StreamFlow 1.2.2 (rev 368). Additional pre- and post-processing tools, the setup of the simulations and necessary data are also available on Envidat at <https://www.envidat.ch/#/metadata/dataset-for-future-water-temperature> (Michel et al., 2022). The source code of the model GloGEMflow can be obtained upon request to the corresponding author. The downscaled climate change scenarios are also available on Envidat at <https://www.envidat.ch/#/metadata/climate-change-scenarios-at-hourly-resolution> (Michel et al., 2021a). Unfortunately, the historical meteorological and hydrological measurements can not be shared publicly, but they are available upon request from the respective data providers or via the corresponding author.

Acknowledgements. This research was funded by the Swiss Federal Office for the Environment (FOEN), Hydrology Division, CH-3003 Bern under grant no. 15.0003.PJ / Q102-0785. The Federal Office of Meteorology and Climatology (MeteoSwiss), the WSL Institute for Snow and Avalanche Research (SLF), the Swiss Federal Office of Topography (Swisstopo), the Federal Office for the Environment (FOEN), the Office for Water and Waste of the Canton of Bern (AWA), the Office for Waste, Water, Energy and Air of the Canton Zurich (AWEL), and Holinger AG are acknowledged for free access to their data.

Petra Schmocker-Fackel and Fabia Hüsler (FOEN) are sincerely acknowledged for their support. We thank Jannis Epting (University of Basel) for instructive discussions about groundwater, Ionut Iosifescu (WSL) for his help regarding the data portal Envidat, Mathias Bavay (SLF) for his help in Alpine3D model development, and Tristan Brauchli (Crealp) for helpful discussions throughout this project. Harry Zekollari acknowledges the funding received from WSL (internal innovative project), the BAFU Hydro-CH2018 project and a Marie Skłodowska-Curie Individual Fellowship (Grant 799904).

The vast majority of work was performed with open and free languages and software (mainly C, C++, bash, Python, R, MeteoIO, Snowpack, Alpine3D, StreamFlow, TauDEM, GDAL, SQL, and QGIS, and countless libraries). The authors acknowledge the open-source community for its invaluable contribution to science. The simulations were performed on the Piz Daint supercomputer of the Swiss National Supercomputing Center (CSCS, grants s938 and s1031). The CSCS technical team is acknowledged for its help and support during this project.

References

- Arora, R., Tockner, K., and Venohr, M.: Changing river temperatures in northern Germany: trends and drivers of change, *Hydrological Processes*, 30, 3084–3096, <https://doi.org/10.1002/hyp.10849>, 10.1002/hyp.10849, 2016.
- Barnett, T. P., Adam, J. C., and Lettenmaier, D. P.: Potential impacts of a warming climate on water availability in snow-dominated regions, *Nature*, 438, 303 EP –, <http://dx.doi.org/10.1038/nature04141>, 2005.
- 5 Bavay, M. and Egger, T.: MeteIO 2.4.2: a preprocessing library for meteorological data, *Geoscientific Model Development*, 7, 3135–3151, <https://doi.org/10.5194/gmd-7-3135-2014>, <https://www.geosci-model-dev.net/7/3135/2014/>, 2014.
- Belletti, B., Garcia de Leaniz, C., Jones, J., Bizzi, S., Börger, L., Segura, G., Castelletti, A., van de Bund, W., Aarestrup, K., Barry, J., Belka, K., Berkhuisen, A., Birnie-Gauvin, K., Bussettini, M., Carolli, M., Consuegra, S., Dopico, E., Feierfeil, T., Fernández, S., Fernandez Garrido, P., Garcia-Vazquez, E., Garrido, S., Giannico, G., Gough, P., Jepsen, N., Jones, P. E., Kemp, P., Kerr, J., King, J., Łapińska, M., Lázaro, G., Lucas, M. C., Marcello, L., Martin, P., McGinnity, P., O’Hanley, J., Olivo del Amo, R., Parasiewicz, P., Pusch, M., Rincon, G., Rodriguez, C., Royte, J., Schneider, C. T., Tummers, J. S., Vallesi, S., Vowles, A., Verspoor, E., Wanningen, H., Wantzen, K. M., Wildman, L., and Zalewski, M.: More than one million barriers fragment Europe’s rivers, *Nature*, 588, 436–441, <https://doi.org/10.1038/s41586-020-3005-2>, 10.1038/s41586-020-3005-2, 2020.
- 10 Beniston, M.: Is snow in the Alps receding or disappearing?, *Wiley Interdisciplinary Reviews: Climate Change*, 3, 349–358, <https://doi.org/10.1002/wcc.179>, <https://onlinelibrary.wiley.com/doi/abs/10.1002/wcc.179>, 2012.
- Benyahya, L., Caissie, D., St-Hilaire, A., Ouarda, T. B., and Bobée, B.: A Review of Statistical Water Temperature Models, *Canadian Water Resources Journal / Revue canadienne des ressources hydriques*, 32, 179–192, <https://doi.org/10.4296/cwrj3203179>, 10.4296/cwrj3203179, 2007.
- 20 Bicknell, B. R., Imhoff, J. C., Kittle, J. L., Donigan, A. S., and Johanson, R. C.: *Hydrological Simulation Program–FORTRAN User’s Manual for Version 11*, U.S. Environmental Protection Agency, National Exposure Research Laboratory, Athens, GA, USA., <https://books.google.ch/books?id=oDfTPAAACAAJ>, 1997.
- Bourqui, M., Hendrickx, F., and Le Moine, N.: Long-term forecasting of flow and water temperature for cooling systems: Case study of the Rhone River, France, *AHS Publ*, 348, 135–142, 2011.
- 25 Brauchli, T., Trujillo, E., Huwald, H., and Lehning, M.: Influence of Slope-Scale Snowmelt on Catchment Response Simulated With the Alpine3D Model, *Water Resources Research*, 53, 10 723–10 739, <https://doi.org/10.1002/2017WR021278>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1002/2017WR021278>, 2017.
- Brown, G. W.: Predicting Temperatures of Small Streams, *Water Resources Research*, 5, 68–75, <https://doi.org/10.1029/WR005i001p00068>, 1969.
- 30 Brunner, M. I., Björnson Gurung, A., Zappa, M., Zekollari, H., Farinotti, D., and Stähli, M.: Present and future water scarcity in Switzerland: Potential for alleviation through reservoirs and lakes, *Science of The Total Environment*, 666, 1033–1047, <https://doi.org/10.1016/j.scitotenv.2019.02.169>, <https://www.sciencedirect.com/science/article/pii/S0048969719306576>, 2019a.
- Brunner, M. I., Farinotti, D., Zekollari, H., Huss, M., and Zappa, M.: Future shifts in extreme flow regimes in Alpine regions, *Hydrology and Earth System Sciences*, 23, 4471–4489, <https://doi.org/10.5194/hess-23-4471-2019>, <https://hess.copernicus.org/articles/23/4471/2019/>, 2019b.
- 35 Caissie, D.: The thermal regime of rivers: a review, *Freshwater Biology*, 51, 1389–1406, <https://doi.org/10.1111/j.1365-2427.2006.01597.x>, <https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1365-2427.2006.01597.x>, 2006.

- Carletti, F., Michel, A., Casale, F., Bocchiola, D., and Lehning, M.: A comparison of hydrological models with different levels of complexity in Alpine regions in the context of climate change, To be submitted to Hydrology and Earth System Sciences, 2021.
- Carraro, L., Mari, L., Hartikainen, H., Strepparava, N., Wahli, T., Jokela, J., Gatto, M., Rinaldo, A., and Bertuzzo, E.: An epidemiological model for proliferative kidney disease in salmonid populations, *Parasites & Vectors*, 9, 487, <https://doi.org/10.1186/s13071-016-1759-z>, 2016.
- 5 Cauvy-Fraunié, S. and Dangles, O.: A global synthesis of biodiversity responses to glacier retreat, *Nature Ecology & Evolution*, 3, 1675–1685, <https://doi.org/10.1038/s41559-019-1042-8>, 2019.
- CH2011: Swiss Climate Change Scenarios CH2011, Tech. rep., C2SM, MeteoSwiss, ETH, NCCR Climate, and OcCC, <https://doi.org/10.3929/ethz-a-006720559>, 2011.
- 10 Comola, F., Schaeffli, B., Rinaldo, A., and Lehning, M.: Thermodynamics in the hydrologic response: Travel time formulation and application to Alpine catchments, *Water Resources Research*, 51, 1671–1687, 2015.
- Compagno, L., Eggs, S., Huss, M., Zekollari, H., and Farinotti, D.: Brief communication: Do 1.0 °C, 1.5 °C or 2.0 °C matter for the future evolution of Alpine glaciers?, *The Cryosphere Discussions*, 2021, 1–9, <https://doi.org/10.5194/tc-2021-31>, <https://tc.copernicus.org/preprints/tc-2021-31/>, 2021.
- 15 Cunge, J. A.: On The Subject Of A Flood Propagation Computation Method (Muskingum Method), *Journal of Hydraulic Research*, 7, 205–230, <https://doi.org/10.1080/00221686909500264>, 1969.
- Dokulil, M. T.: Impact of climate warming on European inland waters, *Inland Waters*, 4, 27–40, <https://doi.org/10.5268/IW-4.1.705>, <https://www.tandfonline.com/doi/abs/10.5268/IW-4.1.705>, 2014.
- Du, X., Shrestha, N. K., and Wang, J.: Assessing climate change impacts on stream temperature in the Athabasca River Basin using SWAT equilibrium temperature model and its potential impacts on stream ecosystem, *Science of The Total Environment*, 650, 1872–1881, <https://doi.org/10.1016/j.scitotenv.2018.09.344>, 2019.
- 20 Du, X., Silwal, G., and Faramarzi, M.: Investigating the impacts of glacier melt on stream temperature in a cold-region watershed: coupling a glacier melt model with a hydrological model, *Journal of Hydrology*, p. 127303, <https://doi.org/10.1016/j.jhydrol.2021.127303>, <https://www.sciencedirect.com/science/article/pii/S0022169421013536>, 2021.
- 25 Dugdale, S. J., Malcolm, I. A., Kantola, K., and Hannah, D. M.: Stream temperature under contrasting riparian forest cover: Understanding thermal dynamics and heat exchange processes, *Science of The Total Environment*, 610-611, 1375–1389, <https://doi.org/10.1016/j.scitotenv.2017.08.198>, <http://www.sciencedirect.com/science/article/pii/S0048969717321952>, 2018.
- Epting, J., Händel, F., and Huggenberger, P.: Thermal management of an unconsolidated shallow urban groundwater body, *Hydrology and Earth System Sciences*, 17, 1851–1869, <https://doi.org/10.5194/hess-17-1851-2013>, <https://hess.copernicus.org/articles/17/1851/2013/>, 2013.
- 30 Epting, J., Michel, A., Affolter, A., and Huggenberger, P.: Climate change effects on groundwater recharge and temperatures in Swiss alluvial aquifers, *Journal of Hydrology X*, 11, 100071, <https://doi.org/10.1016/j.hydroa.2020.100071>, <https://www.sciencedirect.com/science/article/pii/S2589915520300225>, 2021.
- Fell, S. C., Carrivick, J. L., Cauvy-Fraunié, S., Crespo-Pérez, V., Hood, E., Randall, K. C., Nicholass, K. J. M., Tieg, S. D., Dumbrell, A. J., and Brown, L. E.: Fungal decomposition of river organic matter accelerated by decreasing glacier cover, *Nature Climate Change*, <https://doi.org/10.1038/s41558-021-01004-x>, 2021.
- Ficklin, D. L., Barnhart, B. L., Knouft, J. H., Stewart, I. T., Maurer, E. P., Letsinger, S. L., and Whittaker, G. W.: Climate change and stream temperature projections in the Columbia River basin: habitat implications of spatial variation in hydrologic drivers, *Hydrology and*

- Earth System Sciences, 18, 4897–4912, <https://doi.org/10.5194/hess-18-4897-2014>, <https://www.hydrol-earth-syst-sci.net/18/4897/2014/>, 2014.
- Fischer, E. M., Seneviratne, S. I., Lüthi, D., and Schär, C.: Contribution of land-atmosphere coupling to recent European summer heat waves, *Geophysical Research Letters*, 34, <https://doi.org/10.1029/2006GL029068>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2006GL029068>, 2007a.
- Fischer, E. M., Seneviratne, S. I., Vidale, P. L., Lüthi, D., and Schär, C.: Soil Moisture–Atmosphere Interactions during the 2003 European Summer Heat Wave, *Journal of Climate*, 20, 5081–5099, <https://doi.org/10.1175/JCLI4288.1>, 10.1175/JCLI4288.1, 2007b.
- Gallice, A., Schaeffli, B., Lehning, M., Parlange, M. B., and Huwald, H.: Stream temperature prediction in ungauged basins: review of recent approaches and description of a new physics-derived statistical model, *Hydrology and Earth System Sciences*, 19, 3727–3753, <https://doi.org/10.5194/hess-19-3727-2015>, <https://www.hydrol-earth-syst-sci.net/19/3727/2015/>, 2015.
- Gallice, A., Bavay, M., Brauchli, T., Comola, F., Lehning, M., and Huwald, H.: StreamFlow 1.0: an extension to the spatially distributed snow model Alpine3D for hydrological modelling and deterministic stream temperature prediction, *Geoscientific Model Development*, 9, 4491–4519, <https://doi.org/10.5194/gmd-9-4491-2016>, <https://www.geosci-model-dev.net/9/4491/2016/>, 2016.
- García-Gil, A., Vázquez-Suñé, E., Ángel Sánchez-Navarro, J., and Mateo Lázaro, J.: Recovery of energetically overexploited urban aquifers using surface water, *Journal of Hydrology*, 531, 602–611, <https://doi.org/10.1016/j.jhydrol.2015.10.067>, <https://www.sciencedirect.com/science/article/pii/S0022169415008525>, 2015.
- Gouttevin, I., Lehning, M., Jonas, T., Gustafsson, D., and Mölder, M.: A two-layer canopy model with thermal inertia for an improved snowpack energy balance below needleleaf forest (model SNOWPACK, version 3.2.1, revision 741), *Geoscientific Model Development*, 8, 2379–2398, <https://doi.org/10.5194/gmd-8-2379-2015>, <https://www.geosci-model-dev.net/8/2379/2015/>, 2015.
- Griessinger, N., Schirmer, M., Helbig, N., Winstral, A., Michel, A., and Jonas, T.: Implications of observation-enhanced energy-balance snowmelt simulations for runoff modeling of Alpine catchments, *Advances in Water Resources*, 133, 103410, <https://doi.org/10.1016/j.advwatres.2019.103410>, <https://www.sciencedirect.com/science/article/pii/S0309170818310236>, 2019.
- Gupta, H. V., Kling, H., Yilmaz, K. K., and Martinez, G. F.: Decomposition of the mean squared error and NSE performance criteria: Implications for improving hydrological modelling, *Journal of Hydrology*, 377, 80–91, <https://doi.org/10.1016/j.jhydrol.2009.08.003>, <http://www.sciencedirect.com/science/article/pii/S0022169409004843>, 2009.
- Haag, I. and Luce, A.: The integrated water balance and water temperature model LARSIM-WT, *Hydrological Processes*, 22, 1046–1056, <https://doi.org/10.1002/hyp.6983>, 2008.
- Hannah, D. M. and Garner, G.: River water temperature in the United Kingdom: Changes over the 20th century and possible changes over the 21st century, *Progress in Physical Geography: Earth and Environment*, 39, 68–92, <https://doi.org/10.1177/0309133314550669>, 10.1177/0309133314550669, 2015.
- Hannah, D. M., Malcolm, I. A., Soulsby, C., and Youngson, A. F.: Heat exchanges and temperatures within a salmon spawning stream in the Cairngorms, Scotland: seasonal and sub-seasonal dynamics, *River Research and Applications*, 20, 635–652, <https://doi.org/10.1002/rra.771>, 2004.
- Helbig, N.: Application of the radiosity approach to the radiation balance in complex terrain, Ph.D. thesis, University of Zurich, Zürich, 10.5167/uzh-30798, 2009.
- Hock, R., Jansson, P., and Braun, L. N.: Modelling the Response of Mountain Glacier Discharge to Climate Warming, pp. 243–252, Springer Netherlands, Dordrecht, https://doi.org/10.1007/1-4020-3508-X_25, 10.1007/1-4020-3508-X_25, 2005.

- Huggenberger, P. and Epting, J.: Urban geology : process-oriented concepts for adaptive and integrated resource management, Springer Basel, <https://doi.org/10.1007/978-3-0348-0185-0>, 2011.
- Huss, M. and Farinotti, D.: Distributed ice thickness and volume of all glaciers around the globe, *Journal of Geophysical Research: Earth Surface*, 117, F04 010, <https://doi.org/10.1029/2012JF002523>, 2012.
- 5 Huss, M. and Hock, R.: A new model for global glacier change and sea-level rise, *Frontiers in Earth Science*, 3, 1–22, <https://doi.org/10.3389/feart.2015.00054>, 2015.
- Huss, M. and Hock, R.: Global-scale hydrological response to future glacier mass loss, *Nature Climate Change*, 8, 135–140, <https://doi.org/10.1038/s41558-017-0049-x>, 10.1038/s41558-017-0049-x, 2018.
- Hutter, K.: *Theoretical Glaciology*, Reidel Publ. Co., Dordrecht, 1983.
- 10 IPCC: Summary for Policymakers. In: *Climate Change 2021: The Physical Science Basis. Contribution of Working Group I to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change*, Cambridge University Press, In Press, Cambridge, United Kingdom and New York, NY, USA, 2021.
- Jackson, F. L., Fryer, R. J., Hannah, D. M., Millar, C. P., and Malcolm, I. A.: A spatio-temporal statistical model of maximum daily river temperatures to inform the management of Scotland’s Atlantic salmon rivers under climate change, *Science of The Total Environment*, 15 612, 1543–1558, <https://doi.org/10.1016/j.scitotenv.2017.09.010>, <http://www.sciencedirect.com/science/article/pii/S0048969717323525>, 2018.
- Johnson, Z. C., Johnson, B. G., Briggs, M. A., Devine, W. D., Snyder, C. D., Hitt, N. P., Hare, D. K., and Minkova, T. V.: Paired air-water annual temperature patterns reveal hydrogeological controls on stream thermal regimes at watershed to continental scales, *Journal of Hydrology*, 587, 124 929, <https://doi.org/10.1016/j.jhydrol.2020.124929>, 2020.
- 20 Jouvét, G., Huss, M., Blatter, H., Picasso, M., and Rappaz, J.: Numerical Simulation of Rhonegletscher from 1874 to 2100, *J. Comput. Phys.*, 228, 6426–6439, <https://doi.org/10.1016/j.jcp.2009.05.033>, 10.1016/j.jcp.2009.05.033, 2009.
- Kalny, G., Laaha, G., Melcher, A., Trimmel, H., Weihs, P., and Rauch, H. P.: The influence of riparian vegetation shading on water temperature during low flow conditions in a medium sized river, *Knowl. Manag. Aquat. Ecosyst.*, p. 5, <https://doi.org/10.1051/kmae/2016037>, 10.1051/kmae/2016037, 2017.
- 25 Köplin, N., Viviroli, D., Schädler, B., and Weingartner, R.: How does climate change affect mesoscale catchments in Switzerland? – a framework for a comprehensive assessment, *Advances in Geosciences*, 27, 111–119, <https://doi.org/10.5194/adgeo-27-111-2010>, <https://adgeo.copernicus.org/articles/27/111/2010/>, 2010.
- Leach, J. A. and Moore, R. D.: Observations and modeling of hillslope throughflow temperatures in a coastal forested catchment, *Water Resources Research*, 51, 3770–3795, <https://doi.org/10.1002/2014WR016763>, 2015.
- 30 Leach, J. A. and Moore, R. D.: Empirical Stream Thermal Sensitivities May Underestimate Stream Temperature Response to Climate Warming, *Water Resources Research*, 0, <https://doi.org/10.1029/2018WR024236>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2018WR024236>, 2019.
- Lehning, M., Bartelt, P., Brown, B., and Fierz, C.: A physical SNOWPACK model for the Swiss avalanche warning: Part III: meteorological forcing, thin layer formation and evaluation, *Cold Regions Science and Technology*, 35, 169–184, [https://doi.org/10.1016/S0165-232X\(02\)00072-1](https://doi.org/10.1016/S0165-232X(02)00072-1), <http://www.sciencedirect.com/science/article/pii/S0165232X02000721>, 2002a.
- 35 Lehning, M., Bartelt, P., Brown, B., Fierz, C., and Satyawali, P.: A physical SNOWPACK model for the Swiss avalanche warning: Part II. Snow microstructure, *Cold Regions Science and Technology*, 35, 147–167, [https://doi.org/10.1016/S0165-232X\(02\)00073-3](https://doi.org/10.1016/S0165-232X(02)00073-3), <http://www.sciencedirect.com/science/article/pii/S0165232X02000733>, 2002b.

- Lehning, M., Völsch, I., Gustafsson, D., Nguyen, T. A., Stähli, M., and Zappa, M.: ALPINE3D: a detailed model of mountain surface processes and its application to snow hydrology, *Hydrological Processes*, 20, 2111–2128, <https://doi.org/10.1002/hyp.6204>, <https://onlinelibrary.wiley.com/doi/abs/10.1002/hyp.6204>, 2006.
- Lisi, P. J., Schindler, D. E., Cline, T. J., Scheuerell, M. D., and Walsh, P. B.: Watershed geomorphology and snowmelt control stream thermal sensitivity to air temperature, *Geophysical Research Letters*, 42, 3380–3388, <https://doi.org/10.1002/2015GL064083>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1002/2015GL064083>, 2015.
- Magnusson, J., Farinotti, D., Jonas, T., and Bavay, M.: Quantitative evaluation of different hydrological modelling approaches in a partly glacierized Swiss watershed, *Hydrological Processes*, 25, 2071–2084, <https://doi.org/10.1002/hyp.7958>, <https://onlinelibrary.wiley.com/doi/abs/10.1002/hyp.7958>, 2011.
- 10 Magnusson, J., Jonas, T., and Kirchner, J. W.: Temperature dynamics of a proglacial stream: Identifying dominant energy balance components and inferring spatially integrated hydraulic geometry, *Water Resources Research*, 48, W06 510, <https://doi.org/10.1029/2011WR011378>, 2012.
- Martin, E. and Etchevers, P.: Impact of Climatic Changes on Snow Cover and Snow Hydrology in the French Alps, pp. 235–242, Springer Netherlands, Dordrecht, https://doi.org/10.1007/1-4020-3508-X_24, 10.1007/1-4020-3508-X_24, 2005.
- 15 Michel, A.: Past and future impacts of climate change on Swiss river temperature and discharge investigated with data analysis and numerical modelling, Ph.D. thesis, EPFL, Lausanne, <https://doi.org/10.5075/epfl-thesis-8871>, <https://infoscience.epfl.ch/record/287935>, 2021.
- Michel, A., Brauchli, T., Lehning, M., Schaeffli, B., and Huwald, H.: Stream temperature and discharge evolution in Switzerland over the last 50 years: annual and seasonal behaviour, *Hydrology and Earth System Sciences*, 24, 115–142, <https://doi.org/10.5194/hess-24-115-2020>, <https://hess.copernicus.org/articles/24/115/2020/>, 2020.
- 20 Michel, A., Sharma, V., Lehning, M., and Huwald, H.: Dataset for: Climate change scenarios at hourly time-step over Switzerland from an enhanced temporal downscaling approach, <https://doi.org/10.16904/envidat.201>, <https://www.envidat.ch/#/metadata/climate-change-scenarios-at-hourly-resolution>, 2021a.
- Michel, A., Varun, S., Lehning, M., and Huwald, H.: Climate change scenarios at hourly time-step over Switzerland from an enhanced temporal downscaling approach, *International Journal of Climatology*, n/a, <https://doi.org/10.1002/joc.7032>, <https://rmets.onlinelibrary.wiley.com/doi/abs/10.1002/joc.7032>, 2021b.
- 25 Michel, A., Schaeffli, B., Wever, N., Zekollari, H., Lehning, M., and Huwald, H.: Dataset for: Future water temperature of rivers in Switzerland under climate change investigated with physics-based models, <https://doi.org/10.16904/envidat.272>, <https://www.envidat.ch/#/metadata/dataset-for-future-water-temperature>, 2022.
- Moatar, F. and Gailhard, J.: Water temperature behaviour in the River Loire since 1976 and 1881, *Comptes Rendus Geoscience*, 338, 319–328, <https://doi.org/10.1016/j.crte.2006.02.011>, <http://www.sciencedirect.com/science/article/pii/S1631071306000332>, 2006.
- 30 Morrison, J., Quick, M. C., and Foreman, M. G.: Climate change in the Fraser River watershed: flow and temperature projections, *Journal of Hydrology*, 263, 230–244, [https://doi.org/10.1016/S0022-1694\(02\)00065-3](https://doi.org/10.1016/S0022-1694(02)00065-3), <http://www.sciencedirect.com/science/article/pii/S0022169402000653>, 2002.
- Muelchi, R., Rössler, O., Schwanbeck, J., Weingartner, R., and Martius, O.: Future runoff regime changes and their time of emergence for 93 catchments in Switzerland, *Hydrology and Earth System Sciences Discussions*, 2020, 1–25, <https://doi.org/10.5194/hess-2020-516>, <https://hess.copernicus.org/preprints/hess-2020-516/>, 2020.
- 35

- Muelchi, R., Rössler, O., Schwanbeck, J., Weingartner, R., and Martius, O.: Moderate runoff extremes in Swiss rivers and their seasonal occurrence in a changing climate, *Hydrology and Earth System Sciences Discussions*, 2021, 1–28, <https://doi.org/10.5194/hess-2020-667>, <https://hess.copernicus.org/preprints/hess-2020-667/>, 2021.
- Mulligan, M., van Soesbergen, A., and Sáenz, L.: GOODD, a global dataset of more than 38,000 georeferenced dams, *Scientific Data*, 7, 31, <https://doi.org/10.1038/s41597-020-0362-5>, 10.1038/s41597-020-0362-5, 2020.
- Myers, D. T., Ficklin, D. L., Robeson, S. M., Neupane, R. P., Botero-Acosta, A., and Avellaneda, P. M.: Choosing an arbitrary calibration period for hydrologic models: How much does it influence water balance simulations?, *Hydrological Processes*, 35, e14045, <https://doi.org/10.1002/hyp.14045>, <https://onlinelibrary.wiley.com/doi/abs/10.1002/hyp.14045>, 2021.
- NCCS: CH2018 - Climate Scenarios for Switzerland, National Centre for Climate Services, Zürich, 2018.
- 10 Niedrist, G. H. and Füreder, L.: Real-time warming of Alpine streams: (re)defining invertebrates' temperature preferences, *River Research and Applications*, 37, 283–293, <https://doi.org/10.1002/rra.3638>, <https://onlinelibrary.wiley.com/doi/abs/10.1002/rra.3638>, 2021.
- Null, S. E., Viers, J. H., Deas, M. L., Tanaka, S. K., and Mount, J. F.: Stream temperature sensitivity to climate warming in California's Sierra Nevada: impacts to coldwater habitat, *Climatic Change*, 116, 149–170, <https://doi.org/10.1007/s10584-012-0459-8>, 10.1007/s10584-012-0459-8, 2013.
- 15 Omstedt, A.: A coupled one-dimensional sea ice–ocean model applied to a semi-enclosed basin, *Tellus A: Dynamic Meteorology and Oceanography*, 42, 568–582, <https://doi.org/10.3402/tellusa.v42i5.11899>, 10.3402/tellusa.v42i5.11899, 1990.
- O'Reilly, C. M., Sharma, S., Gray, D. K., Hampton, S. E., Read, J. S., Rowley, R. J., Schneider, P., Lenters, J. D., McIntyre, P. B., Kraemer, B. M., Weyhenmeyer, G. A., Straile, D., Dong, B., Adrian, R., Allan, M. G., Anneville, O., Arvola, L., Austin, J., Bailey, J. L., Baron, J. S., Brookes, J. D., Eyto, E., Dokulil, M. T., Hamilton, D. P., Havens, K., Hetherington, A. L., Higgins, S. N., Hook, S., Izmet'eva, L. R.,
- 20 Joehnk, K. D., Kangur, K., Kasprzak, P., Kumagai, M., Kuusisto, E., Leshkevich, G., Livingstone, D. M., MacIntyre, S., May, L., Melack, J. M., Mueller-Navarra, D. C., Naumenko, M., Noges, P., Noges, T., North, R. P., Plisnier, P.-D., Rigosi, A., Rimmer, A., Rogora, M., Rudstam, L. G., Rusak, J. A., Salmaso, N., Samal, N. R., Schindler, D. E., Schladow, S. G., Schmid, M., Schmidt, S. R., Silow, E., Soylu, M. E., Teubner, K., Verburg, P., Voutilainen, A., Watkinson, A., Williamson, C. E., and Zhang, G.: Rapid and highly variable warming of lake surface waters around the globe, *Geophysical Research Letters*, 42, 10,773–10,781, <https://doi.org/10.1002/2015GL066235>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1002/2015GL066235>, 2015.
- 25 O'Sullivan, A. M., Devito, K. J., Ogilvie, J., Linnansaari, T., Pronk, T., Allard, S., and Curry, R. A.: Effects of Topographic Resolution and Geologic Setting on Spatial Statistical River Temperature Models, *Water Resources Research*, 56, e2020WR028122, <https://doi.org/10.1029/2020WR028122>, 2020.
- Paillex, A., Schuwirth, N., Lorenz, A. W., Januschke, K., Peter, A., and Reichert, P.: Integrating and extending ecological river assessment: Concept and test with two restoration projects, *Ecological Indicators*, 72, 131–141, <https://doi.org/10.1016/j.ecolind.2016.07.048>, <http://www.sciencedirect.com/science/article/pii/S1470160X16304460>, 2017.
- 30 Perrin, C., Michel, C., and Andréassian, V.: Improvement of a parsimonious model for streamflow simulation, *Journal of Hydrology*, 279, 275–289, 2003.
- Piotrowski, A. P., Osuch, M., and Napiorkowski, J. J.: Influence of the choice of stream temperature model on the projections of water temperature in rivers, *Journal of Hydrology*, 601, 126 629, <https://doi.org/10.1016/j.jhydrol.2021.126629>, 2021.
- 35 Ponce, V. and Changanti, P.: Variable-parameter Muskingum-Cunge method revisited, *Journal of Hydrology*, 162, 433–439, [https://doi.org/10.1016/0022-1694\(94\)90241-0](https://doi.org/10.1016/0022-1694(94)90241-0), <http://www.sciencedirect.com/science/article/pii/0022169494902410>, 1994.

- Qiu, H., Blaes, P., Comer-Warner, S., Hannah, D. M., Krause, S., and Phanikumar, M. S.: Evaluating a Coupled Phenology-Surface Energy Balance Model to Understand Stream-Subsurface Temperature Dynamics in a Mixed-Use Farmland Catchment, *Water Resources Research*, 55, 1675–1697, <https://doi.org/10.1029/2018WR023644>, 2019.
- Råman Vinnå, L., Wüest, A., Zappa, M., Fink, G., and Bouffard, D.: Tributaries affect the thermal response of lakes to climate change, *Hydrology and Earth System Sciences*, 22, 31–51, <https://doi.org/10.5194/hess-22-31-2018>, <https://www.hydrol-earth-syst-sci.net/22/31/2018/>, 2018.
- Råman Vinnå, L., Medhaug, I., Schmid, M., and Bouffard, D.: The vulnerability of lakes to climate change along an altitudinal gradient, *Communications Earth & Environment*, 2, 35, <https://doi.org/10.1038/s43247-021-00106-w>, 10.1038/s43247-021-00106-w, 2021.
- Santiago, J. M., Muñoz Mas, R., Solana-Gutiérrez, J., García de Jalón, D., Alonso, C., Martínez-Capel, F., Pórtoles, J., Monjo, R., and Ribalaygua, J.: Waning habitats due to climate change: the effects of changes in streamflow and temperature at the rear edge of the distribution of a cold-water fish, *Hydrology and Earth System Sciences*, 21, 4073–4101, <https://doi.org/10.5194/hess-21-4073-2017>, <https://www.hydrol-earth-syst-sci.net/21/4073/2017/>, 2017.
- Schaepli, B., Hingray, B., and Musy, A.: Climate change and hydropower production in the Swiss Alps: quantification of potential impacts and related modelling uncertainties, *Hydrology and Earth System Sciences*, 11, 1191–1205, <https://doi.org/10.5194/hess-11-1191-2007>, <https://www.hydrol-earth-syst-sci.net/11/1191/2007/>, 2007.
- Schlögl, S., Marty, C., Bavay, M., and Lehning, M.: Sensitivity of Alpine3D modeled snow cover to modifications in DEM resolution, station coverage and meteorological input quantities, *Environmental Modelling & Software*, 83, 387–396, <https://doi.org/10.1016/j.envsoft.2016.02.017>, <http://www.sciencedirect.com/science/article/pii/S1364815216300378>, 2016.
- Seyedhashemi, H., Moatar, F., Vidal, J.-P., Diamond, J. S., Beaufort, A., Chandesris, A., and Valette, L.: Thermal signatures identify the influence of dams and ponds on stream temperature at the regional scale, *Science of The Total Environment*, 766, 142 667, <https://doi.org/10.1016/j.scitotenv.2020.142667>, <https://www.sciencedirect.com/science/article/pii/S0048969720361969>, 2021.
- Tarboton, D.: TauDEM, Utah State University <http://hydrology.usu.edu/taudem/taudem5/>, 1997.
- Temnerud, J. and Weyhenmeyer, G.: Abrupt changes in air temperature and precipitation: Do they matter for water chemistry?, *Global Biogeochemical Cycles*, 22, 2008.
- AWA: Fliessgewässer, Bau-, Verkehrs- und Energiedirektion, Canton Bern, <https://www.bve.be.ch/bve/de/index/wasser/wasser/messdaten/fliessgewaesser.html>, 2019.
- AWEL: Messdate, Amt für Abfall, Wasser, Energie und Luft, Canton Zürich, <https://awel.zh.ch/internet/baudirektion/awel/de/wasser/messdaten.html>, 2019.
- European Environment Agency: CORINE Land Cover (CLC) 2006, Version 17, Copenhagen K, Denmark, <https://land.copernicus.eu/pan-european/corine-land-cover/clc-2006>, 2013.
- FOEN: Hydrological data and forecast, Swiss Federal Office for the Environment, <https://www.hydrodaten.admin.ch/en>, 2019.
- IDAWEB: MeteoSwiss, Federal Office of Meteorology and Climatology, <https://gate.meteoswiss.ch/idaweb/login.do>, 2020.
- IMIS: WSL Institute for Snow and Avalanche Research, SLF, IMIS measuring network, <https://www.slf.ch/en/avalanche-bulletin-and-snow-situation/measured-values/description-of-automated-stations.html>, 2019.
- Swiss Federal Office for the Environment: L'ordre des cours d'eau selon Strahler pour le réseau hydrographique numérique au 1:25'000 de la Suisse, <https://www.bafu.admin.ch/bafu/fr/home/themes/eaux/etat/cartes/reseau-hydrographique-suisse/reseau-hydrographique--ordre-des-cours-deau-pour-le-reseau-hydro.html>, 2013.

- Swiss Federal Office for the Environment: Subdivision de la Suisse en bassins versants (Bassins versants Suisse), ref: J417-0015, <https://www.bafu.admin.ch/bafu/fr/home/themes/eaux/etat/cartes/geodonnees-sur-la-subdivision-de-la-suisse-en-bassins-versant.html>, 2020.
- Thornton, J., Therrien, R., Mariethoz, G., Linde, N., and Brunner, P.: Simulating fully-integrated hydrological dynamics in complex Alpine headwaters, Submitted to *Water Resources Research*, pp. 1–28, <https://doi.org/10.31223/X5RG7Q>, 2021.
- 5 Trimmel, H., Weihs, P., Leiding, D., Formayer, H., Kalny, G., and Melcher, A.: Can riparian vegetation shade mitigate the expected rise in stream temperatures due to climate change during heat waves in a human-impacted pre-alpine river?, *Hydrology and Earth System Sciences*, 22, 437–461, <https://doi.org/10.5194/hess-22-437-2018>, <https://www.hydrol-earth-syst-sci.net/22/437/2018/>, 2018.
- van Vliet, M. T., Franssen, W. H., Yearsley, J. R., Ludwig, F., Haddeland, I., Lettenmaier, D. P., and Kabat, P.: Global river discharge and water temperature under climate change, *Global Environmental Change*, 23, 450–464, <https://doi.org/10.1016/j.gloenvcha.2012.11.002>,
 10 <https://www.sciencedirect.com/science/article/pii/S0959378012001331>, 2013.
- Viviroli, D., Archer, D. R., Buytaert, W., Fowler, H. J., Greenwood, G. B., Hamlet, A. F., Huang, Y., Koboltschnig, G., Litaor, M. I., López-Moreno, J. I., Lorentz, S., Schädler, B., Schreier, H., Schwaiger, K., Vuille, M., and Woods, R.: Climate change and mountain water resources: overview and recommendations for research, management and policy, *Hydrology and Earth System Sciences*, 15, 471–504, <https://doi.org/10.5194/hess-15-471-2011>, <https://www.hydrol-earth-syst-sci.net/15/471/2011/>, 2011.
- 15 Warscher, M., Wagner, S., Marke, T., Laux, P., Smiatek, G., Strasser, U., and Kunstmann, H.: A 5 km Resolution Regional Climate Simulation for Central Europe: Performance in High Mountain Areas and Seasonal, Regional and Elevation-Dependent Variations, *Atmosphere*, 10, <https://doi.org/10.3390/atmos10110682>, <https://www.mdpi.com/2073-4433/10/11/682>, 2019.
- Watts, G., Battarbee, R. W., Bloomfield, J. P., Crossman, J., Daccache, A., Durance, I., Elliott, J. A., Garner, G., Hannaford, J., Hannah, D. M., Hess, T., Jackson, C. R., Kay, A. L., Kernan, M., Knox, J., Mackay, J., Monteith, D. T., Ormerod, S. J., Rance, J., Stuart, M. E.,
 20 Wade, A. J., Wade, S. D., Weatherhead, K., Whitehead, P. G., and Wilby, R. L.: Climate change and water in the UK – past changes and future prospects, *Progress in Physical Geography: Earth and Environment*, 39, 6–28, <https://doi.org/10.1177/0309133314542957>,
 10.1177/0309133314542957, 2015.
- Webb, B. W. and Nobilis, F.: Long-term changes in river temperature and the influence of climatic and hydrological factors, *Hydrological Sciences Journal*, 52, 74–85, <https://doi.org/10.1623/hysj.52.1.74>, 2007.
- 25 Wever, N., Fierz, C., Mitterer, C., Hirashima, H., and Lehning, M.: Solving Richards Equation for snow improves snowpack meltwater runoff estimations in detailed multi-layer snowpack model, *The Cryosphere*, 8, 257–274, <https://doi.org/10.5194/tc-8-257-2014>, <https://www.the-cryosphere.net/8/257/2014/>, 2014.
- Wever, N., Schmid, L., Heilig, A., Eisen, O., Fierz, C., and Lehning, M.: Verification of the multi-layer SNOWPACK model with different water transport schemes, *The Cryosphere*, 9, 2271–2293, <https://doi.org/10.5194/tc-9-2271-2015>, <https://www.the-cryosphere.net/9/2271/>
 30 2015/, 2015.
- Wever, N., Comola, F., Bavay, M., and Lehning, M.: Simulating the influence of snow surface processes on soil moisture dynamics and streamflow generation in an alpine catchment, *Hydrology and Earth System Sciences*, 21, 4053–4071, <https://doi.org/10.5194/hess-21-4053-2017>, <https://www.hydrol-earth-syst-sci.net/21/4053/2017/>, 2017.
- WMO: WMO Guidelines on the Calculation of Climate Normals, Tech. rep., World Meteorological Organization, 2017.
- 35 Wondzell, S. M., Diabat, M., and Haggerty, R.: What Matters Most: Are Future Stream Temperatures More Sensitive to Changing Air Temperatures, Discharge, or Riparian Vegetation?, *JAWRA Journal of the American Water Resources Association*, 55, 116–132, <https://doi.org/10.1111/1752-1688.12707>, 2019.

- Woolway, R. I. and Merchant, C. J.: Amplified surface temperature response of cold, deep lakes to inter-annual air temperature variability, *Scientific Reports*, 7, 4130, <https://doi.org/10.1038/s41598-017-04058-0>, 10.1038/s41598-017-04058-0, 2017.
- Woolway, R. I., Jennings, E., and Carrea, L.: Impact of the 2018 European heatwave on lake surface water temperature, *Inland Waters*, 10, 322–332, <https://doi.org/10.1080/20442041.2020.1712180>, 10.1080/20442041.2020.1712180, 2020a.
- 5 Woolway, R. I., Kraemer, B. M., Lenters, J. D., Merchant, C. J., O'Reilly, C. M., and Sharma, S.: Global lake responses to climate change, *Nature Reviews Earth & Environment*, 1, 388–403, <https://doi.org/10.1038/s43017-020-0067-5>, 10.1038/s43017-020-0067-5, 2020b.
- Yan, H., Sun, N., Fullerton, A., and Baerwalde, M.: Greater vulnerability of snowmelt-fed river thermal regimes to a warming climate, *Environmental Research Letters*, 16, 054006, <https://doi.org/10.1088/1748-9326/abf393>, 2021.
- Zekollari, H., Fürst, J. J., and Huybrechts, P.: Modelling the evolution of Vadret da Morteratsch, Switzerland, since the Little Ice Age and
10 into the future, *Journal of Glaciology*, 60, 1155–1168, <https://doi.org/10.3189/2014JoG14J053>, 2014.
- Zekollari, H., Huss, M., and Farinotti, D.: Modelling the future evolution of glaciers in the European Alps under the EURO-CORDEX RCM ensemble, *The Cryosphere*, 13, 1125–1146, <https://doi.org/10.5194/tc-13-1125-2019>, <https://tc.copernicus.org/articles/13/1125/2019/>, 2019.