

Combining passive- and active-DTS measurements to locate and quantify groundwater discharge variability into a headwater streams.

5 Nataline Simon¹, Olivier Bour¹, Mikaël Faucheux², Nicolas Lavenant¹, Hugo Le Lay², Ophélie Fovet²,
Zahra Thomas² and Laurent Longuevergne¹

¹Univ Rennes, CNRS, Géosciences Rennes, UMR 6118, 35000 Rennes, France

²UMR SAS, INRAE, Institut Agro, Rennes, France

Correspondence to: Nataline Simon (nataline.simon2@gmail.com) and Olivier Bour (olivier.bour@univ-rennes1.fr)

Abstract. Exchanges between groundwater and surface water play a key role for ecosystem preservation, especially in headwater catchments where groundwater discharge into streams highly contributes to streamflow generation and maintenance. Despite several decades of research, investigating the spatial variability of groundwater discharge into streams still remains challenging mainly because groundwater/surface water interactions are controlled by multi-scale processes. In this context, we evaluated the potential of using FO-DTS (Fiber Optic Distributed Temperature Sensing) technology to locate and quantify groundwater discharge at high resolution. To do so, we propose to combine, for the first time,
15 FO-DTS (Fiber Optic Distributed Temperature Sensing) technology has been widely developed to quantify exchanges between groundwater and surface water during the last decade. In this study, we propose, for the first time, to combine long-term passive-DTS measurements and active-DTS measurements by deploying FO cables in the streambed sediments of a first- and second-order stream in gaining conditions, in order to highlight their respective potential to locate and quantify groundwater discharge into streams. The passive-DTS experiment provided eight months monitoring of streambed temperature fluctuations along more than 530 m of cable, while the puntual active-DTS experiment allowed a detailed and accurate investigation of groundwater discharge variability over a 60 m-length over a 60 meters long heated section.
20 Results show that long-term passive-DTS measurements turn out to be an efficient method to detect and locate groundwater discharge along several hundreds of meters and to investigate the temporal pattern of exchanges over the annual hydrological cycle. However, the quantification of fluxes with this approach remains limited as shown by given the the high uncertainties associated to the estimates, especially due to on the assumptions made about thermal properties. On the contrary, active-DTS measurements, which have never been in streambed sediments up to now, allow estimating the spatial distribution of both thermal conductivities and the groundwater fluxes at high resolution with very low uncertainties all along the heated section of FO cable. The method allows describing the variability of streambed properties at an unprecedented scale and reveals the variability of groundwater inflows at small scale. In the end, this study shows the potential and the interest of the complementary use of passive- and active-DTS experiments to quantify groundwater discharge at different spatial and temporal scales. Results show that groundwater discharges are mainly concentrated in the upstream part of the watershed.
25
30

where steepest slopes are observed, confirming the importance of the topography in the stream generation in headwater catchments. Through the high spatial resolution of measurements, it was also possible to highlight the presence of local and highly contributive groundwater inflows, probably driven by local changes of hydraulic properties. These results about groundwater discharge variability offer promising perspectives for the characterization of distributed responses times, but also for studying biogeochemical hotspots and hot moments.

~~On the one hand, passive DTS measurements consist in monitoring natural temperature fluctuations to detect and localize groundwater inflows and characterize the temporal pattern of exchanges. Although easy to set up, the quantification of fluxes with this approach often remains difficult since it relies on energy balance models or on the coupling of distributed temperature measurements with additional punctual measurements. On the other hand, active DTS methods, recently developed in hydrogeology, consist in continuously monitoring temperature changes induced by a heat source along a FO cable. Recent developments showed that this approach, although more complex to set up than passive DTS measurements, can address the challenge of quantifying groundwater fluxes and their spatial distribution. Yet it has almost never been conducted in streambed sediments. In this study, both methods are combined by deploying FO cables in the streambed sediments of a first and second order stream within a small agricultural watershed. A numerical model is used to interpret passive DTS measurements and highlight the temporal and spatial dynamic of groundwater discharge over the annual hydrological cycle. We underline the difficulties and the limitations of deploying a single FO cable to investigate groundwater discharge and show the impact of uncertainty on sediments thermal properties on the quantification of groundwater inflows. On the opposite, the active DTS experiment allows estimating the spatial distribution of both the thermal conductivity and the groundwater flux at high resolution with very low uncertainties all along the heated section of FO cable. Our results highlight the added values of conducting active DTS experiments, eventually combined with passive DTS measurements, to fully investigate and characterize patterns of groundwater stream water exchanges at the stream scale. The combination of both methods allows discussing the impact of topography and hydraulic conductivity variations on the variability of groundwater inflows in headwater catchments.~~

1 Introduction

Understanding groundwater and stream water interactions as integral components of a stream catchment continuum is crucial for efficient development and management of water resources (Bencala, 1993; Brunke and Gonser, 1997; Sophocleous, 2002). Particularly essential for the preservation of groundwater dependent ecosystems and riparian habitats (Kalbus et al., 2006), these interactions play a major role on physical, geochemical and biological processes occurring in the stream or in the hyporheic zone (Frei et al., 2019; Jones and Mulholland, 2000). More specifically, these exchanges control water quality affecting river ecohydrology and hydrochemistry, particularly during dry periods when groundwater is the principal contribution to stream discharge (Brunke and Gonser, 1997). This is particularly true in headwater catchments where groundwater discharge highly contribute to streamflow generation (Winter, 2007). However, localizing and quantifying exchanges between groundwater and stream water is often difficult as these exchange are controlled by multi-

scale processes and are therefore highly variable in time and in space (Brunke and Gonser, 1997; Fleckenstein et al., 2006; Flipo et al., 2014; Harvey and Bencala, 1993; Kalbus et al., 2009; Varli and Yilmaz, 2018; Woessner, 2000).

A wide range of methods exists to estimate water fluxes between stream and groundwater including solute tracer concentrations (Brandt et al., 2017; Liao et al., 2021), seepage meter measurements (Rosenberry et al., 2020) or the use of heat as a groundwater tracer (Anderson, 2005; Constantz, 2008), which is particularly efficient in identifying patterns of focused discharge. The approach relies on the detection of temperature anomalies observed at the sediment-water interface (Tyler et al., 2009; Sebok et al., 2013; Westhoff et al., 2011) or into the streambed (Krause et al., 2012; Lowry et al., 2007) when significant differences exist between groundwater and stream water temperatures. Then, the comparison of temperature variations monitored at different depths in the streambed provides information on groundwater discharge (Anderson, 2005; Constantz, 2008; Hatch et al., 2006; Keery et al., 2007; Lapham, 1989; Stallman, 1965; Webb et al., 2008; Winter et al., 1998). Indeed, the diurnal or seasonal water temperature variations propagates deeper for losing streams (downward conditions) than for gaining streams (upward conditions), since heat transfer is either attenuated or enhanced by groundwater discharge (Constantz, 2008; Goto et al., 2005). Thus, the use of Vertical Thermal Profiles (VTP) is widely applied for determining flow directions, quantifying groundwater discharge (Hatch et al., 2006; Lapham, 1989; Keery et al., 2007) and estimating hydraulic parameters (Constantz and Thomas, 1996). ~~Nevertheless, only a local scale characterization punctual measurements of the stream-aquifer interactions is-are achievable with this approach. with this approach~~ Considering the spatial variability and the complexity of flow at the GW/stream interface, while extensive information on spatial and temporal temperature patterns are required to gain a more complete understanding of flows at reach scale, and even more at watershed scale.

This was made possible by the development and the use of the Fiber Optic Distributed Temperature Sensing (FO-DTS) technology for environmental applications (Selker et al., 2006b, a; Shanafield et al., 2018; Tyler et al., 2009). FO-DTS provides continuous temperature data through space and time along fiber optic cables at high spatial resolution (Habel et al., 2009; SEAFOM, 2010; Ukil et al., 2012). By deploying FO cables at the bottom of the stream, the DTS technology allows temperature monitoring of the longitudinal linear stream/sediments interface allowing detecting thermal anomalies induced by groundwater discharge into the stream (Briggs et al., 2012; Gilmore et al., 2019; Koruk et al., 2020; Moridnejad et al., 2020; Rosenberry et al., 2016; Selker et al., 2006b, a; Westhoff et al., 2007, 2011). This approach was also used to study seasonal and temporal fluctuations of groundwater discharge into streams (Matheswaran et al., 2014; Slater et al., 2010) and into a lake (Sebok et al., 2013). Energy balance models have been efficiently applied to interpret passive-DTS measurements and quantify groundwater/stream water exchanges (Selker et al., 2006b; Westhoff et al., 2011). However their use remains limited because it requires monitoring significant temperature changes over time, limiting the application of the method to large groundwater inflows or small headwater streams. To go further and in order to avoid signal temperature loss induced by larger river flows, To overcome such limitations, some studies proposed to detect thermal anomalies in the streambed by burying the FO cable into the streambed sediments in the hyporheic zone (Krause et al., 2012; Le Lay et al., 2019b; Lowry et al., 2007), to improve the possibility of localizing groundwater inflows. ~~However, beyond the localization of inflows,~~

100 ~~Despite that, the quantification of fluxes from passive-DTS measurements remained challenging. the distributed~~
~~quantification of fluxes from passive DTS measurements remains even more challenging. In theory, the implementation of~~
~~three FO cables buried at different depths, as proposed by Mamer and Lowry (2013), would be ideal to measure the~~
~~attenuation of the stream temperature variations into the sediments in order to get high-resolution fluxes estimates.~~
~~Unfortunately, such approach is technically very difficult to apply in the field. Considering this difficulty, Le Lay et al.~~
105 ~~(2019a) proposed coupling FO-DTS data collected along a single fiber-optic cable at a given depth with punctual~~
~~temperature measurements from thermal lances. In the approach, it is assumed that temperature boundary conditions can be~~
~~characterized from the temperature measurements collected with the thermal lances and extrapolated all along the stream to~~
~~be combined with FO-DTS measured at a given depth. Moreover, the question of sediments thermal properties and their~~
~~spatial variability remained unexplored, even though thermal conductivity highly impacts flux estimates (Sebok and Müller,~~
110 ~~2019).-Based on these assumptions, they showed the temporal variability of exchanges associated to the annual hydrological~~
~~cycle and the possibility of estimating diffuse groundwater inflows (Le Lay et al., 2019a). Consequently, in many~~
~~applications, DTS measurements are exclusively used to locate thermal anomalies and~~
~~It often requires additional localized~~
~~methods are used to measure or estimate fluxes estimates or measurements (Briggs et al., 2012; Koruk et al., 2020; Krause et~~
~~al., 2012; Rosenberry et al., 2016), which highly suggests that the potential of passive DTS measurements is yet to fully~~
115 ~~realized. Otherwise, energy balance models require monitoring significant temperature changes over time that often limits~~
~~the application of the method to large groundwater inflows or small headwater streams. The implementation of distributed~~
~~vertical temperature profiling as proposed by Mamer and Lowry (2013) remains particularly difficult to apply in the field. It~~
~~requires coupling distributed temperature measurements with punctual vertical temperature profiles (Le Lay et al., 2019a),~~
~~which raises the question of the extrapolation of punctual measurements to the whole profile. It also raises the question of~~
120 ~~the estimation of associated uncertainties.~~

Alternatively, To address the difficulty of using natural temperature variations for estimating fluxes, active-DTS
methods, consisting in heating the FO cable, have been recently developed to improve the capabilities of FO-DTS methods
for estimating fluxes in different environmental conditions applications (Bense et al., 2016; Simon et al., 2021). Contrary to
passive DTS methods, active DTS methods, consisting in injecting a heat source in the sediments, better constrain the
125 signature of diffusion and advection along a FO cable (Bense et al., 2016). Indeed, In particular, it was demonstrated that
the difference of temperature measured between an electrically heated and a non-heated FO cable is directly dependent on
water fluxes, offering the possibility to determine estimates fluxes (Bense et al., 2016; Read et al., 2014; Sayde et al., 2015)
(Bense et al., 2016; Read et al., 2014; Sayde et al., 2015), and their spatial distribution over a large range with an excellent
accuracy (Simon et al., 2021). Thus, Although a Active heat tracer experiments using fiber optic-DTS methods have been
130 used to estimate wind speed in the low atmosphere (Lapo et al., 2020; Sayde et al., 2015; van Ramshorst et al., 2020), (Lapo
et al., 2020; Sayde et al., 2015), in dam monitoring (Ghafoori et al., 2020; Perzlmaier et al., 2004; Su et al., 2017), for
groundwater fluxes measurements in open (Banks et al., 2014; Klepikova et al., 2018; Read et al., 2014, 2015) and sealed
boreholes (Munn et al., 2020; Selker and Selker, 2018) or else in direct contact within sedimentary aquifers (del Val et al.,

2021; des Tombe et al., 2019)–Despite promising developments, active-DTS methods have been seldom used in hydrology to estimate groundwater/surface water interactions. Kurth et al. (2015) coupled passive and active-DTS measurements and highlighted areas with lower and higher flow rates over the cable, but the quantification of fluxes remained unexplored. Briggs et al. (2016) developed a novel probe. High-resolution vertical temperature profiling has been used to quantify vertical fluxes at high resolution using active-DTS measurements, but only the probe only permits a local-scale characterization of the stream-aquifer dynamic. Although Kurth et al., (2015) coupled passive and active DTS measurements and highlighted areas with lower and higher flow rates over the cable, the quantification of fluxes remains unexplored.

In this study, we propose in this study to couple and compare long term passive DTS measurements with use for the first time active-DTS measurements to characterize quantify groundwater discharge into the stream in of a headwater catchment. The application of Active-DTS methods in such context –is particularly promising since the interpretation of active-DTS measurements in saturated porous media provides estimates of both sediments’s thermal conductivities and groundwater fluxes, over a large range and with an excellent accuracy (Simon et al., 2021). Thus, This method should allow quantifying groundwater discharge and characterizing the streambed thermal properties at an unprecedented spatial scale. The In complement of active-DTS measurements, experiment, which remains were limited in space and time, a long-term passive-DTS experiment was conducted at the catchment scale in order to infer the location and dynamics of groundwater discharge. Thus therefore, this study also investigates how these two experiments could be compared and combined to characterize both the spatial and the temporal dynamics of groundwater discharge, which has never been achieved until now. In particular, we aim to discuss the advantages and limitations of high resolution DTS measurements to locate and quantify groundwater discharge into streams. For doing so To do so, FO cables were deployed in the streambed sediments of a headwater stream within a small agricultural watershed. In the following, we first present the headwater watershed catchment and the experimental setup before presenting the methods used to interpret both passive- and active-DTS measurements. The fluxes estimates obtained with both passive- and active-DTS measurements are then compared and the advantages and limitations of each method are finally discussed.

2 Materiel and methods

2.1 The experimental setup on the Kerrien watershed

2.1.1 The Kerrien watershed

The experiment has been achieved on conducted in the Kerrien watershed located in South-western Brittany (4°7'24.87''O:47°56'26.97''N). It is part of the AgrHys Environmental Research Observatory, whose principal aim is to understand and characterize transit times in small agricultural catchments (https://www6.inra.fr/ore_agrhys). The site is a part of the French network of critical zone observatories (Gaillardet et al., 2018) and supports extensive hydrological and geochemical researches. Consequently, many instruments and equipment are installed on this experimental site (Fovet et al.,

2018), as detailed in Fovet et al. (2018), which is an advantage to test new methods and measurement tools in the field. This site was selected because it presents the advantage of readily installed equipment and instruments (Fovet et al., 2018).

As shown in Fig. 1, the watershed is a headwater watershed with a second-order stream, subdivided in three first-order sub-watersheds namely the Kerrien, the Kerbernez and the Gerveur sub-watersheds. The Kerrien sub-watershed is a small agricultural watershed (9.5 ha) with higher steeper slopes in the upper parts (14% slopes) than in the bottom lands (5% slopes), where characterized by a large wetland was developed (Ruiz et al., 2002). As pointed out in Fig. 1, downstream the wetland, the fields were converted into a golf course. This is a man-made environment where the In this man-made environment, the stream has been completely restored and dammed to facilitate maintenance. Drainage pipes contribute to drain precipitation from the watershed area directly into the stream, limiting the potential groundwater recharge by draining precipitation from the watershed area into the stream. Further downstream, the stream reaches a natural wood plain.





Figure 1: Description of the watershed with the location of piezometers, gauging station and fiber optic cables.


2.1.2 Hydrological dynamics of the study site

180 The Kerrien watershed has been particularly studied and instrumented for estimating transit times in a small agricultural watershed (Fovet et al., 2015a; Martin, 2003), as shown in Fig. 1. For this study, we are using the data from the piezometer transect F (Fig. 1) including the hillslope piezometer F5b (20 m depth) and the mid-slope piezometer F4 (15 m depth) as markers for the deep groundwater storage dynamics and the riparian piezometers F2 (2 m depth) and F1b (5 m depth) as markers for the riparian groundwater storage dynamics. The gauging station E30 provides stream flow rate.

185 | ~~Previous studies demonstrated that R~~unoff is negligibleinsignificant, so that most of effective precipitations ~~are is~~ infiltrating in this headwater watershed. The annual rainfall (1114 mm ~~on~~ⁱⁿ average) is well-distributed over the year but recharge mainly occurs in autumn and winter. Therefore, the contribution of groundwater to the stream flow reaches 80-90% (Fovet et al., 2015b; Martin et al., 2006; Ruiz et al., 2002) with the stream discharge during high water periods being highly correlated with hillslope head gradient (Martin, 2003). As shown in Fig. 2a, piezometric levels show clear seasonal
190 fluctuations with high levels during winter and spring and low levels during summer and autumn. The hydraulic gradient between the aquifer and the stream as well as the evolution of the stream discharge suggest that groundwater discharge into the stream should be particularly expected during the high water level period (From December to June).

Piezometric level and Temperature





195 **Figure 2: a. Changes in stream flow and in piezometric levels along the transect F over three years. b. Stream and groundwater temperature fluctuations over time along the transect F. The red-colored area corresponds to the period of passive-DTS measurements, conducted from December 2015 to the July 15th, 2016.**

Figure 2b shows temperature fluctuations in the stream and in piezometers over a time period from July 2013 to May 2017. While the groundwater temperature is almost constant in the upslope domain (piezometers F5b and F4), temperature variations recorded in the stream and in the downslope domain (F2 and F1b) show larger variations following daily and seasonal temperature variations. It can easily be easily shown that temperature variations recorded in F2 and F1b result from the diffusion of air temperature variations through the water columns of piezometers. -The detection in the stream of- thermal anomalies induced by groundwater discharge requires a significant contrast of temperature between stream and groundwater as well as a significant groundwater discharge compared to the stream flow. Here, Considering the relatively

200

205 | small difference of temperature between groundwater and stream water and in order to detect potential diffusive inflows, the choice was made to burying the FO cable within the sediments, which should facilitate the detection of potential temperature anomalies as marker of groundwater discharge (Krause et al., 2012; Le Lay et al., 2019b; Lowry et al., 2007). Otherwise, active-DTS measurements should highlight advective heat transfer, controlled by groundwater discharge.

2.2 Passive DTS measurements and data interpretation

210 2.2.1 FO cable deployment and data acquisition

To investigate the temporal and spatial dynamics of groundwater discharge, a FO cable has been deployed in the streambed sediments in the southern part of the study site, as shown in Fig. 1. Streambed temperature variations were recorded along this cable using the DTS technology from December 2015 to July 2016 experiment corresponding to the long term monitoring of temperature in the streambed was achieved conducted from December 2015 to July 2016 in the southern part of the study site, as shown in Fig. 1. The FO cable has been deployed downstream from the Kerrien spring, and ~~in~~ total, more than 530 m length of BruSens FO cable has been buried directly into the streambed. Due to some obstacles (coarse gravels, cobbles, gauging stations, etc.), it was not possible to bury the FO cable in few places. Everywhere else, the average burial depth was estimated to be 8 cm ~~the burial depth was estimated in average at 8 cm~~. The first 165 meters of the FO cable have been deployed in the Kerrien sub-watershed, where the stream is surrounded by a wetland. The streambed is 220 formed by sand and sludge whose thickness is low but large enough to bury properly the cable. Then, besides a harder substrate, the FO cable was deployed in the golf area. In few local places, the burying was not possible and FO cable was set on the streambed. The last 70 meters of the FO cable have been deployed in a wood plain, a natural environment, where a ~~deeperthick~~ sandy riverbed facilitates cable burying. As highlighted in Fig. 2a, the nineeight-months experiment insured the monitoring of streambed temperature during both high and low water tables. The highest levels were recorded from January 225 to mid-April, period over which the wetland is saturated up to the surface.

The FO cable has been connected to a FO-DTS control unit, a Silixa XT-DTS instrument (5 km range). The DTS unit was configured in double-ended configuration (van de Giesen et al., 2012) to collect data at 25 cm and 10 minutes sampling interval. Two calibration baths (one at the ambient temperature and a fridge), as well as PT100 probes (0.1°C) and RBR SoloT probes (0.002°C accuracy) were used to calibrate the data. To assess the accuracy of temperature measurements, 230 a RBR SoloT probe was set up at the gauging station E30 located at the entrance of the wood. Comparison between DTS measurements and RBR SoloT probes validated the temperature measurements, with a relative uncertainty of measurements (standard error) estimated at 0.05°C and absolute uncertainty of measurement that can reach at maximum estimated at 0.2°C depending on the period of measurement.

In complement, 4 vertical temperature profiles (VTP) were installed in the streambed in the wetland area by 235 deploying temperature sensors at 12.5 and 22 cm-depth in the streambed sediments. The position of these punctual sensors in the stream is shown in Fig. 1 and was chosen at locations where groundwater discharge has been observed using preliminary

results obtained from FO-DTS monitoring. From upstream to downstream, the VTP are numbered from 1 to 4. For each location, the evolution of temperature was recorded from April 07th, 2016 to May 03rd, 2017 using HOBO U12-015-02 sensors ($\pm 0.25^\circ\text{C}$ precision). These VTP will be used to quantify local groundwater discharge and results will be compared with estimates from FO-DTS measurements.

2.2.2 Data interpretation

~~Groundwater inflows can be detected by~~ ~~The localization of groundwater inflows can be done by~~ localizing temperature anomalies. Those can be easily identified by plotting the evolution of the temperature over time and space, especially for long time series. Thermal anomalies can also be identified using an analysis of the standard deviation (SD) of temperature for a given period (Sebok et al., 2015), ~~since~~ ~~Indeed~~, the calculation of the standard deviation provides insights about amplitudes of temperature variations. In case of groundwater discharge, the value of the SD of streambed temperature is expected to be much lower than the value of the SD of the stream temperature. Therefore, relative variations of fluxes along the cable could be determined from relative variations of SD. ~~provides insights about the thermal inertia mostly linked to groundwater fluxes towards the surface and can therefore be used to highlight relative variations of fluxes along the cable.~~

Then, to quantify vertical fluxes, we use the FLUX-BOT model, a code proposed by Munz and Schmidt (2017), using a numerical heat transport model to solve the 1D heat transport equation (Carslaw and Jaeger, 1959; Domenico and Schwartz, 1998). This 1D model ~~aims to calculate~~ allows calculating the specific discharge in the z direction (i.e. the vertical Darcy flux) vertical fluxes by inverting measured time series observed at least at three different depths. Temperature variations are simulated according to the optimized fluxes. The quality criteria calculated between the simulated temperatures and the measured one (NSE, R^2 and RMSE) allow discussing the quality of flux estimates. Thus, the model estimates the direction and the intensity of the flow and may highlight the temporal variability of exchanges.

To apply the model, the stream temperature and the groundwater temperature ~~measured in the piezometer F4, steady over time (Fig. 2b),~~ were chosen as upper and lower boundary conditions respectively. The stream temperature was measured for the wetland area at the Kerrien spring with a ~~punctual~~ temperature sensor and at the gauging station E30 (RBR SoloT) for the wood plain area. ~~The stream temperature is assumed homogeneous for each area since shade and lighting conditions and water depths are similar. Moreover, the transit time from the spring to the gauging station is relatively rapid due to the short distances and the river slopes. The temperature signal recorded at 15-m depth in the piezometer F4 (Fig. 2b) was used to set the groundwater temperature.~~ The FLUX-BOT model was first used for interpreting the temperature measurements of the four VTP installed in the streambed. Considering the upper and lower boundary conditions previously defined, the numerical model reproduces the temperature evolution collected at 12.5- and 22-cm depth and provides an estimate of vertical fluxes for each profile. Details about the interpretation of VTP using the FLUX-BOT model are provided as supplement (Fig. S1 and S2). The results are compared in the section 3.3 with estimated fluxes from passive- and active-DTS measurements. Identically, the FLUX-BOT model is used to reproduce and interpret passive-DTS measurements


270 collected at various spots along the cable. A loop was added in the initial code allowing the interpretation of data collected
for each measurement point. For both applications, the vertical mesh size of the model was set at 0.01 m, as recommended
by Munz and Schmidt (2017). Concerning the thermal properties of the saturated sediments, the volumetric heat capacity
was set at $3 \times 10^6 \text{ J.m}^{-3} \cdot \text{K}^{-1}$. The streambed sediments being composed of saturated clay, silt, sand and gravel, the thermal
conductivity may typically range between 0.9 and 4 $\text{W.m}^{-1} \cdot \text{K}^{-1}$ (Stauffer et al., 2013). Thus, considering the importance of
the sediment thermal conductivity on groundwater fluxes estimates (Sebok and Müller, 2019), the model was applied for 3
values of thermal conductivity (1, 2.5 and 4 $\text{W.m}^{-1} \cdot \text{K}^{-1}$).
~~and various values of thermal conductivities, ranging between 0.9 and 4 $\text{W.m}^{-1} \cdot \text{K}^{-1}$, were tested. Indeed, the model was
applied for 3 values of thermal conductivity (1, 2.5 and 4 $\text{W.m}^{-1} \cdot \text{K}^{-1}$). The streambed sediments being composed of saturated
clay, silt, sand and gravel, the thermal conductivity may typically range between 0.9 and 4 $\text{W.m}^{-1} \cdot \text{K}^{-1}$ (Stauffer et al., 2013).~~

280 2.3 Active DTS measurements

2.3.1 FO cable deployment and data acquisition

The first 3 months of passive DTS measurements showed clear and significant temperature anomalies along the
cable, especially in the wetland area, interpreted as potential groundwater exfiltration zones (See the results section below).
Consequently, a Active-DTS measurements were conducted in April 2016 concurrently with passive-DTS measurements by
285 deploying an additional FO cable ~~in~~ within the streambed in the wetland, as shown in Fig. 1. While the active-DTS
experiment was conducted, passive-DTS measurements had already been collected for three months, which allowed
highlighting clear and significant temperature anomalies along the cable deployed in the wetland area (See results section
below). Assuming that these temperature anomalies could be associated to potential groundwater exfiltration zones, the
choice was made to conduct the active-DTS experiment in this area.

290 Figure 3 presents the experimental setup of the active-experiment. A FO cable is electrically heated through its steel
~~armoring~~armouring and the elevation in temperature, associated to the heat injection, is continuously monitored all along the
heated section using the FO inside the cable. Without any flow, heat transfers occur through the porous media only by
conduction (Constantz, 2008) and a gradual and continuous increase of temperature is therefore expected (Simon et al.,
2021). If water flows through the porous medium, advection partly controls the thermal response by dissipating a part of the
295 heat produced by the heat source. The higher the water flow, the lower should be the temperature increase (Simon et al.,
2021). Contrary to passive-DTS measurements, one of a main advantage of the method is the possibility. Thus, contrary to
passive DTS measurements, to of investigating groundwater fluxes can be investigated in any conditions, independently of
natural temperature gradients. However, the same hypothesis similarly to most thermal-based methods (Constantz, 2008), it is
assumed about 1D flow considered as that groundwater flows are perpendicular to FO cables (Simon et al., 2021).



300

Figure 3: Experimental setup of the active experiment: a 60 meter-section of a heatable cable has been electrically isolated, buried in the sediments and then heated by connecting to a power controller.

305

For the active DTS experiment, a 150 meters length of BruSens FO cable has been connected to a FO-DTS control unit, a Silixa Ultima S instrument. The unit was configured in double-ended configuration to collect data at 12.5 cm sampling and 60 seconds time interval. The effective spatial resolution of DTS measurements with this unit was estimated varying between 66 and 90 cm following the methodology proposed in Simon et al. (2020). The calibration process applied was almost similar to the one applied for calibrating passive-DTS measurements. The only difference is that a warm calibration bath was used as reference section during the active-DTS experiment while a bath at ambient temperature was used for the passive-DTS experiment. To do so, heating resistors were set in the bath and air pumps were used to homogenize the temperature within. Considering the important temperature rise expected during the active experiment, using a warmed calibration bath is essential because the bath temperatures must preferably bracket the full range of temperatures expected to occur along the cable (van de Giesen et al., 2012).

310

315

Note that, while passive-DTS measurements have been monitored all along the stream, a much shorter section of FO cable has been used for the active DTS experiment and this for technical reasons. A 60-meters section of the 150 m FO cable has been buried in the streambed in parallel with the FO cable previously installed for the passive experiment. As the heating experiment induces a very localized thermal perturbation within the streambed, the non-heated cable was not affected by the heat injection. Thus, natural streambed temperature fluctuations were monitored during the experiment using the non-heated cable. It should be noted that, during the FO cable deployment in the streambed, local heterogeneities led to

the impossibility to deploy the whole FO heating section in the streambed. Thanks to cable numbering, these non-buried sections were accurately located. For buried sections, the burial depth was measured in situ and estimated to be around 8 to 10 cm. This 60-m section has been electrically isolated and heated using a power controller (provided by CTEMP, <https://ctemps.org/>) supplying a constant and uniform heating rate power of 35 W.m^{-1} along the heated FO cable. The heated cable has been energized continuously during 4 hours and the recovery was also monitored for an additional 3 hours after turning off the power controller.

2.3.3 Data interpretation

Before interpreting the data, data were processed to remove the measurement points corresponding to sections where the cable was not buried in the streambed but liedaid in the bottom of the stream. These sections were precisely marked during the cable installation. Moreover, since the temperature increase is mainly controlled by convection in the stream, the thermal responses measured during the heating phase in non-buried sections of cable are different from the thermal responses observed in buried section and are easily identifiable with temperature rises that reaching steady-state in one or two minutes (Read et al., 2014). Then, the data processing method developed in Simon et al. (2020) which consists in calculating the derivative of the temperature with respect to distance was applied. It allows highlighting areas where the temperature changes occur at a scale smaller than the spatial resolution of measurements, which leads to identify measurements that are representative of the effective temperature.

Finally, among all the section used for active-DTS measurements, 172 measurements points are thought to be significant. Note that the raw data of active-DTS measurements, the data processing (sorting and quality check) and the definition of significant points are presented in detail in the supplement material. Here, weThe data were further interpreted the data using the ADTS Toolbox proposed by Simon and Bour (Submitted) for automatically interpreting active-DTS measurements. The ADTS Toolbox contains several MATLAB codes that allow estimating the thermal conductivities and the groundwater fluxes (specific discharge) and their respective spatial distribution all along the heated section. It uses for the data interpretationThe method is based on an analytical approach proposed and validated by Simon et al. (2021), that consists in defining, for each measurement point along the heated section, the optimized values of thermal conductivity and flux that allow reproducing at best the associated temperature increase measured over the heating period. The use of the ADTS toolbox also provides an estimate of the associated uncertainties (Simon and Bour, Submitted).


3 Results

In the following, we first focus on the interpretation of passive-DTS measurements with the aim of locating groundwater discharges and characterizing its temporal dynamics. Then we present and analyse results of the punctual active-DTS experiment. Both results are further compared.

3.1 Passive-DTS measurements

350 3.1.1 Spatial variability of temperature signals

Figure 4a synthesizes the results of the passive-DTS experiment and shows temperature signals monitored all along the FO cable deployed in the streambed sediments. The x-axis indicates the distance between the Kerrien spring (located at 0 m) and each measurement point in the streambed. Temperature variations are presented from December 2015 to July 2016 (y-axis). In June and July, despite very low flows, the stream never dried up. Two different behaviours are highlighted in the figure. On the one hand, vertical yellow lines can be observed near the Kerrien Spring in the first 150 meters of cable. These lines emphasize that the temperature recorded in these areas is relatively constant over time (few temperature variations are recorded). On the other hand, away from the spring, beyond 300 m, clear and large differences in temperature are observed between colder periods (from December to mid-April) and warmer periods (from mid-April to July).




360 **Figure 4:** a. Long-term monitoring of streambed temperature along the river using DTS. Sections S1, S2 and S3 match with spots
 365 where the cable lies on the bank because of obstacles in the stream (gauging stations). Temporary thermal anomalies located for
 instance in 425 m and around 500 m correspond to air-exposed periods during which the cable was not held at the sediment/water
 interface. b. Standard Deviation (SD) of the temperature calculated over the experiment duration for each measurement point
 along the FO cable. Sections where the cable was outside the stream or punctually unburied were removed. The red line represents
 the SD of the stream temperature (1.38°C) measured at the gauging station E30.

To highlight the spatial variability of the temperature signal, the Standard Deviation (SD) of temperature was calculated for each measurement point over the whole duration of the experiment as presented in Fig. 4b. The value of the SD of stream temperature ($\approx 1.375\text{ }^{\circ}\text{C}$) directly reflects the amplitude of daily temperature fluctuations. Concerning the SD of streambed temperature, its value is relatively stable and very low (around $0.37\text{ }^{\circ}\text{C}$) in the first 50-m of measurements,

370 | near the spring, ~~the value of the SD of temperature is relatively stable and very low (around 0.37 °C)~~. Then, it progressively
increases from upstream to downstream and stabilizes around the value of the SD of the stream temperature (≈ 1.375 °C) at
around 300 meters (in the middle of the golf area). ~~Interestingly, the value of the SD directly reflects the amplitude of daily
temperature fluctuations.~~

375 | The lowest SD values are recorded in the upstream wetland ($d < 160$ m in Fig. 4b). In this area, as illustrated in Fig.
5a by the red curve (94.56 m, $\sigma = 0.2$ °C), the temperature is relatively stable over time (around 12.5°C) and the daily stream
temperature fluctuations are widely attenuated, (the SD varies between 0.19 and 0.93°C while the SD of the stream
temperature is 1.38°C). However, significant differences are observed between temperature measurements from upstream to
downstream, as highlighted by the progressive increase of SD measured from the spring to 160 m. This increase reflects the
increase of the amplitudes of daily temperature fluctuations collected from upstream (orange line in Fig. 5b, $\sigma = 0.36$ °C) to
380 | downstream (grey line in Fig. 5b, $\sigma = 0.95$ °C). In addition, the profile of SD (Fig. 4b) also shows ~~punctual isolated~~
“~~peakspikes~~” associated ~~with~~ very low SD values, in agreement with the yellow lines observed in Fig. 4a. These
~~peakspikes~~ can be associated ~~with~~ spots where the amplitude of temperature is low all over the period of measurements, as
illustrated by blue curve in Fig. 5b (53.38 m), where the value of the SD is equal to 0.24 °C. As we shall see in the next
sections, the relative temperature stability suggests that these ~~peakspikes~~ or “hotspots” may be associated to local
385 | groundwater discharges.

Further downstream (from 220 m up to 300 m in the first part of the golf area), while the value of the SD
progressively increases (Fig. 4b), higher amplitudes of daily temperature variations are monitored as illustrated in the Fig. 5a
by the blue curve (227.5 m, $\sigma = 0.93$ °C). In this area, SDs values are lower than the one calculated in the stream (1.3 °C,
Fig. 4b) meaning that the daily temperature fluctuations are slightly attenuated. Once again, the progressive increase of the
390 | value of the SD highlights differences in temperature amplitude (the further, the higher the amplitudes of temperature).
Finally, in the second part of the golf area and in the wood (starting from approximately 300 m), SDs values tend towards the
value of the SD of the stream (1.3 °C, Fig. 4b). The associated streambed temperature variations are almost identical to the
stream variations, as illustrated in the Fig. 5a by the yellow line (357.91 m, $\sigma = 1.42$ °C). Note here that the SD evolution
shows a well-marked step at 300 m from 1.2 to 1.4°C, exactly at the confluence between the Kerrien and the Gerueur
395 | streams (see Fig. 1). Moreover, very ~~punctual isolated~~ decreases of SDs can be observed between 402 and 425 m, where
significant thermal anomalies are monitored from mid-February to mid-April.



400 **Figure 5:** a. Examples of streambed temperature variations measured with the FO-DTS a. at 94.56 m, 227.5 m and 357.91 m from upstream with respective SD values equals to 0.2 $^{\circ}\text{C}$, 0.93 $^{\circ}\text{C}$ and 1.42 $^{\circ}\text{C}$; b. in the wetland area at 11.44 m, 53.38 m and 137.27 m from upstream with respective SD values equals to 0.36 $^{\circ}\text{C}$, 0.24 $^{\circ}\text{C}$ and 0.95 $^{\circ}\text{C}$.

Streambed temperature measurements clearly show a general trend with an increase of the amplitudes of temperature variations measured from upstream (the spring) to downstream, up to around 300 m. In the first 300 meters,

temperature fluctuations appear attenuated compared to the daily temperature fluctuations and the streambed temperature variations measured more downstream (beyond 300 m). Thus, lower temperature amplitude variations suggest groundwater inflows, especially for the measurement points where the lowest values of SD are recorded (minimal peakspikes of SD digressing from the general trend, as illustrated by the blue line in Fig. 5b). Indeed, for these “hotspots”, thermal anomalies are clearly recorded and the temperature is relatively stable over time according to the stable groundwater temperature (around 12.5-13°C). The general increase of SD from the spring up to 300 m may be associated to a global decrease of groundwater inflows from upstream to downstream in the first 300 meters of the watershed. Higher and punctual very localized inflows would be located in spots where the value of the SD is clearly lower than the general trend. Nevertheless, the gradual increase of the SD could also be alternatively explained due toby the fact that the stream water temperature, equal to the groundwater temperature at the spring, may progressively equilibrate with the air temperature when travelling along the stream.

To summarize, hotspots associated to minimal peakspikes of SD are certainly associated to local groundwater discharges, but the general evolution of temperature SD may be due to different factors.

3.1.2 Temporal variability of temperature signals

~~Three different time periods were clearly identified with passive DTS measurements according to the behaviour of the streambed temperature evolution over time: P1, P2 and P3 (Fig. 4 and 5). In order to characterize the temporal dynamic of groundwater discharge, the daily SD of temperature was calculated along the FO cable for each day of measurement as shown in Fig. 6. During the first month of monitoring (period P1 in Fig. 4a), quite similar temperature variations are observed all along the cable independently of the localization of the measurement point over the watershed. The temperature fluctuates between 9 and 14°C according to daily temperature fluctuations, as illustrated in Fig. 5a. The red line in the Fig. 6 is a representative example of the daily SD profiles calculated in December. During this period, the value of the daily SD calculated in the wetland area, is higher than the daily SD of the stream temperature (horizontal red line) and also higher than the daily SDs calculated in the golf or in the wood areas. Note also the piezometric levels measured near the stream during P1 are lower than the stage level and very low flow rate are measured in the stream in December (mean $\approx 2 \text{ L}\cdot\text{s}^{-1}$) (Fig. 2a).~~

~~The second period from January to mid April (period P2 in Fig. 4a) is characterized by well marked temperature anomalies observed in the wetland area, where the streambed temperature stabilizes around 12.5°C (red line in Fig. 5a). During this period, the longitudinal profiles of daily SD of temperature, represented by the green line in Fig. 6, are identical to the one calculated over the experiment duration (Fig. 4b). This period is also marked by an increase of the piezometric level and water stage (Fig. 2a). Recharge starts end of December and the elevation of the groundwater table becomes higher than the elevation of the stream stage early January.~~

~~Lastly, from mid April to the end of the monitoring (period P3 in Fig. 4a), the mean streambed temperature measured all along the cable and the daily temperature amplitudes both increase. However, the increase of the daily temperature amplitude, and thus of the SD, is more important in the downstream section ($> 300\text{m}$), as highlighted in Fig. 5a. Contrary to temperature measurements recorded during P1 (December), the temperature variations measured during P3 in upstream sections (red and blue lines in Fig. 5a) are very different of the one measured downstream (orange line in Fig. 5a).~~

Note also that the piezometric level measured during P3 gradually decreases as well as the stream flow (Fig. 2a). According to Fig. 6, the behaviour of the temperature SD is clearly different from each period of time. This suggests therefore that the temperature SD may be a good marker of possible groundwater inflows although it provides only qualitative information.




Figure 6: Examples of longitudinal profiles of daily SD of temperature calculated the Dec. 12, 2015 (red line), the Feb. 20, 2016 (green line) and the Jul. 17, 2016 (blue line). These profiles are representative of daily SD profiles calculated during the periods P1, P2 and P3 respectively. The coloured horizontal lines correspond to the daily SD of stream temperature calculated the same days.

3.1.3.2 Quantifying groundwater/ stream water exchanges


To go further ~~and in the~~ interpretation of streambed temperature variations, the FLUX-BOT model was applied for each measurement point. A detailed example of the application of the FLUX-BOT model on a single measurement point ($d = 5.08$ m) including the quality criteria associated to the fluxes estimates is presented in Fig. S3. Although the model was applied for each measurement point, simulated temperature variations are consistent only with DTS measurements located in the first 150 meters of the temperature profile ($SD < 1^\circ\text{C}$) with ~~values of~~ $NSE_s > 0.74$, $R^2 > 0.85$ and $RMSEs < 0.9^\circ\text{C}$. Beyond 150 m, the quality of the results considerably decreases with ~~values of~~ $NSE_s < 0.6$, $R^2 < 0.65$ and $RMSEs > 1.8^\circ\text{C}$. Thus, the uncertainties on fluxes estimates are too large in this lower part of the watershed (for $d > 150$ m) to estimate groundwater discharge. Consequently, the model is found not applicable to interpret temperature measurements and results are not provided here.

Figure 7-6 shows the results of the application of the FLUX-BOT model on passive-DTS measurements collected along the cable deployed in streambed sediments in the wetland area, for $d < 150\text{m}$, where the model is applicable. The model predicts negative values of fluxes all along the interpreted section, indicating upward water flow, which strengthens the assumption of groundwater discharge into stream. However, as shown in Fig. 7b6b, groundwater fluxes estimates are strongly dependent on the value of thermal conductivity of the sediments used in the model. ~~Indeed, the model was applied for 3 values of thermal conductivity (1, 2.5 and 4 $\text{W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$). The streambed sediments being composed of saturated clay, silt, sand and gravel, the thermal conductivity may typically range between 0.9 and 4 $\text{W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (Stauffer et al., 2013).~~ By varying the thermal conductivity from 1 $\text{W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (blue line) to 4 $\text{W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (green line), the estimated discharge is around 4 times higher. For instance, at $d = 75\text{ m}$, the mean flux is estimated $-3.43 \times 10^{-6}\text{ m}\cdot\text{s}^{-1}$ for $\lambda = 1\text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ against $-1.48 \times 10^{-5}\text{ m}\cdot\text{s}^{-1}$ for $\lambda = 4\text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$. Note however that the results are more sensitive to the value of the thermal conductivity when groundwater inflows are higher (see Fig. S3 for more details).

~~Whatever the~~ Regardless of uncertainties, the model also predicts a general decrease of groundwater discharge from upstream to downstream. higher Higher groundwater inflows are estimated upstream, at the head of the catchment and close to the spring (Fig. 7b6b). The inflows are estimated twice higher near the spring than downstream. Hence, assuming a thermal conductivity of the sediments $\lambda = 2.5\text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (orange line in Fig. 6b), the mean flux is estimated $-1.24 \times 10^{-5}\text{ m}\cdot\text{s}^{-1}$ near the spring ($d = 0\text{ m}$) while it only reaches $-6.55 \times 10^{-6}\text{ m}\cdot\text{s}^{-1}$ for $d = 150\text{ m}$. The comparison with the SD profile (Fig. 7a6a) tends to confirm the correlation between the value of the SD of streambed temperature and the importance of groundwater discharge. ~~The increase of SD from upstream to downstream seems associated to a decrease of groundwater discharge. The inflows are estimated twice higher near the spring than downstream. Hence, assuming a thermal conductivity of the sediments $\lambda = 2.5\text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (orange line in Fig. 7b6b), the mean flux is estimated $-1.24 \times 10^{-5}\text{ m}\cdot\text{s}^{-1}$ near the spring ($d = 0\text{ m}$) while it only reaches $-6.55 \times 10^{-6}\text{ m}\cdot\text{s}^{-1}$ for $d = 150\text{ m}$.~~ Results also suggest that local peakspikes of SD (at 95 or 100 m for instance) can be associated to punctual preferential pathways, where groundwater discharge is locally estimated four times higher than elsewhere.

Finally, Figure 7e-6c shows the temporal variability evolution in time of groundwater discharges estimated for six different measurement points-, assuming thermal conductivity $\lambda = 2.5\text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$. The range variability of fluxes is larger greater from January to May with groundwater inflows varying between 5×10^{-6} and $2.5 \times 10^{-5}\text{ m}\cdot\text{s}^{-1}$ ~~by considering $\lambda = 2.5\text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$.~~ Lower groundwater inflows are detected during the first month of the experiment ($< 7.5 \times 10^{-6}\text{ m}\cdot\text{s}^{-1}$) and at the end of the experiment ($< 6 \times 10^{-6}\text{ m}\cdot\text{s}^{-1}$), which seems consistent with stream gauging evolution. The same temporal dynamic is observed for all data collected in the wetland area.

485




490 | **Figure 67:** a. Profile of SD of the streambed temperature calculated over the experiment duration for each measurement point located along the FO cable and deployed in the wetland area; b. Profiles of mean fluxes estimated over the experiment duration using the FLUX-BOT model from DTS measurements collected in streambed sediments in the wetland area considering 3 values of thermal conductivity (Negative values indicate upward water flux); c. Temporal evolution of the estimated flow considering $\lambda=2.5 \text{ W.m}^{-1}.\text{K}^{-1}$.

3.2 Active-DTS measurements

3.2.1 Data interpretation

495 ~~Among active DTS measurements, 172 measurements points, selected following the data processing method developed in Simon et al. (2020), are thought to be significant. Note that the raw data of active DTS measurements, are presented in the Fig. S4 and that the data processing (sorting and quality check) and the definition of significant points are presented in detail in the supplement. Hereafter,~~

500 ~~As explained in section 2.3, many some measurements points were excluded from the analysis either because the heated FO cable could not have been correctly buried or because temperature measurements were not representative of the effective temperature signal. The data interpretation was thus focused on data interpretation and fluxes estimates of the~~
505 ~~selected significant data points as shown in Fig 7a. This Figure presents the increase of temperature ΔT measured 3.45 hrs after the start of the heat experiment. We recall that the temperature rise $\Delta T(t)$ measured during active-DTS experiments depends on the thermal conductivity of the sediments which controls the rate of increase through time and on groundwater flow which limits the temperature rise (Simon et al., 2021). Despite some areas without data, the values of ΔT measured 3.45 hrs after the start of the heat experiment are distributed over less than 55 m offering a large view of the variability of thermal responses. The value of ΔT is particularly variable and ranges between 19.42 °C (at 11.2 m) and 36°C (at 132.5 m). However, despite the variability observed, adjacent points present in general a similar dynamic with similar values of ΔT , suggesting similar behaviours over a certain range or scale.~~



510 | **Figure 87:** a. Significant ΔT values measured 3.45hrs after the start of the heating period measured along the buried FO section. b. Examples of data interpretation on three thermal response curves observed in the data (black lines). The MILS model was used to reproduce the temperature increase during both the conduction- and advection-dominant periods (red lines).

515 | ~~Figure 8a 7a shows the variability of ΔT measured 3.45hrs after the start of the heat experiment. Despite some areas without data, due to noise in the data or imperfect burying, the measurement points are distributed over less than 55 m offering a clear view of the variability of thermal responses. The value of ΔT is particularly variable and ranges between 19.42 °C (at 11.2 m) and 36°C (at 132.5 m). However, despite the variability observed, adjacent points present in general a similar dynamic with similar values of ΔT , suggesting similar behaviours over a certain range or scale.~~

520 | Each ~~validated~~ data point was interpreted using the ADTS Toolbox (~~Simon and Bour, Submitted~~) to estimate thermal conductivities and fluxes. Figure ~~8b-7b~~ shows three examples of thermal response curves observed in the data collected along the heated FO section (black lines) and their respective interpretation with the ADTS Toolbox (red lines). The data interpretation focuses on the interpretation of the second part of the temperature increase (for $t > 90$ sec)


corresponding to the temperature increase controlled by heat conduction and advection in the sediments (Simon et al., 2021).

As illustrated in Fig. 8b7b, the thermal conductivity highly controls the thermal response and the variability of ΔT . For instance, at $d = 32.38$ m, the temperature rise reaches 34.7 °C after 3.45 hrs of heating, in concordance with the very low thermal conductivity estimated ($0.94 \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$). On the opposite, at $d = 7.21$ m, where the temperature rise is much lower and reaches only 19.7 °C, λ is estimated at $2.8 \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$. The fluxes are then estimated using the temperature at later times, as the intensity of the flux controls temperature stabilization (Simon et al., 2021). Thus, for instance, the following fluxes values of $7 \times 10^{-6} \text{ m}\cdot\text{s}^{-1}$ and $4.52 \times 10^{-5} \text{ m}\cdot\text{s}^{-1}$ are estimated at $d = 59.70$ m and $d = 7.21$ m respectively. However, for some points, as illustrated by the temperature evolution measured at $d = 32.38$ m, the temperature does not stabilize for later times and keeps increasing with no inflexion over the whole heating period. This implies either no-flow conditions ($q = 0 \text{ m}\cdot\text{s}^{-1}$) or very low-flow conditions which presume that the heat duration was not long enough to reach temperature stabilization (Simon et al., 2021). In these cases, only an estimate of q_{lim} can be provided, which corresponds to the highest value of flow that would induce such temperature increase. For instance, at $d = 32.38$ m, the flux is estimated to be lower than $2 \times 10^{-6} \text{ m}\cdot\text{s}^{-1}$.

3.2.2 Spatial variability of thermal conductivities and water fluxes estimates

Figure 9-8 shows the estimation of both the thermal conductivities (Fig. 9a8a) and the fluxes (Fig. 9b8b) obtained from active-DTS measurements using the ADTS Toolbox. It provides an estimate of their respective spatial distribution at very small scale. As shown in Fig. 9a8a, the thermal conductivities estimated along the heated section vary between 0.8 and $3.14 \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$, with a median value at $1.65 \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$. The RMSE calculated between observed data and the best-fit model was systematically lower than 0.05 °C. Seeing the data noise (< 0.1 °C), the maximal uncertainty of these estimates is estimated to be $\pm 0.2 \text{ W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$.

As shown in Fig. 9b8b, estimated groundwater fluxes vary between 2×10^{-6} and $4.74 \times 10^{-5} \text{ m}\cdot\text{s}^{-1}$, with a mean value at $1.34 \times 10^{-5} \text{ m}\cdot\text{s}^{-1}$ and a SD of $9.18 \times 10^{-6} \text{ m}\cdot\text{s}^{-1}$. For 9 locations (blue points), only the value of q_{lim} was evaluated since the departure of the conduction regime towards temperature stabilization was not reached at the end of the heating period. Note that the data interpretation does not provide the flow direction, the temperature increase being identical for upward and downward conditions. Although significant measurements are not available all along the sections, results show a decrease of the flux from upstream to downstream, particularly in the first twenty meters of measurements. At greater distances, fluxes are more diffuse in space, except at few locations, for instance at 43, 50 and 52 m from the start of the heated section where higher values are observed. Interestingly, very local and high fluxes values, spreading on less than 2 m, can be observed, as for instance at $d = 10$ m.



550

Figure 89: The interpretation of active-DTS measurements along the heated section of FO cable leads to estimate the spatial distribution of both a. the thermal conductivity ($\text{uncertainty} = \pm 0.2 \text{ W.m}^{-1}.\text{K}^{-1}$) and b. the water fluxes and their associated errors (error bars). Blue points mark locations where the temperature stabilization is not reached and where an estimate of q_{lim} is provided. Errors bars corresponding to uncertainties on flow estimates calculated with respect to data noise for each measurement points.

555

3.3 Comparison between passive- and active-DTS measurements

Figure 10-9 compares estimated values of groundwater fluxes for the 7th April 2016. The flow direction is assumed upward in agreement with passive-DTS measurements (Fig. 7b6b).

560


For passive-DTS measurements, the two light grey curves correspond to fluxes estimates considering $\lambda = 1 \text{ W.m}^{-1}.\text{K}^{-1}$ and $\lambda = 4 \text{ W.m}^{-1}.\text{K}^{-1}$, assuming that the effective values of fluxes vary-should range between these two thresholds estimates. It appears thatThe estimation of the flow quantification groundwater discharges -clearly remains highly uncertain especially because of the lack of knowledge about thermal conductivity variations. Results show nevertheless a slight decrease of groundwater discharge from upstream to downstream but the large range of estimated fluxeshigh uncertainty probably blurs the actual trend.

565

On the opposite, Fluxes-flux estimates from active-DTS measurements (pink points) present a much smaller uncertainty (Fig 9), confirming the interest of using a heat source to improve fluxes measurements. Flux estimates from both passive and active DTS measurements roughly agree, but active-DTS measurements reveal a larger spatial variability regarding groundwater discharge. Interestingly, flux estimates from active-DTS measurements can be qualitatively compared with the evolution of the SD of temperature (green line). The lowest SD values are located in the first 55 m of the stream, which is in good agreement with active-DTS measurements that highlighted highest groundwater discharges between 47 and

570

53 m (between 1.7×10^{-5} and 4.9×10^{-5} m.s^{-1}). Between approximately 55 and 60 m, the value of SD increases rapidly (from 1.25 $^{\circ}\text{C}$ at 54 m to 2°C at 60 m) while the fluxes estimated from active-DTS measurements decrease linearly (from 2.1×10^{-5} at 56.8 m to 4.2×10^{-6} m.s^{-1} at 58.5 m). From 60 m, the SD increases and the associated values of fluxes estimated from active-DTS are particularly low, varying for instance between 2×10^{-6} and 1.1×10^{-5} m.s^{-1} . Interestingly, the locations of ~~punctual~~ local increases of groundwater discharge detected with the active experiment at 87.5 m, 95 m and 100 m (black arrows) match well with ~~punctual~~ isolated decreases of SD values. Note also that flux estimates from active-DTS measurements are in very good agreement with the results of VTPs (blue line). The estimated flux based on passive-DTS measurements at 53.4 m is also in good agreement with active-DTS results despite the large uncertainty.



580 | **Figure 910:** Comparison of flow estimated the 7th April 2016 using the vertical temperature profiles (VTP), the passive-DTS measurements and the active-DTS measurements. Results are compared with the evolution of SD of the temperature calculated from passive-DTS measurements. The black arrows highlight localized groundwater discharge.

~~groundwater discharge from passive DTS measurements. For passive DTS measurements, fluxes estimates can be~~
 585 ~~Theoretically, considering~~ the effective value of thermal conductivity ~~is considered~~ in the model, ~~should~~ highly improved ~~the results obtained from passive-DTS measurements. Actually~~ Thus, the thermal conductivity estimates providing from ~~active-DTS measurements were used to~~ the data have been once again fully re-interpreted the passive-DTS measurements with using the FLUX-BOT model ~~by considering the thermal conductivity estimated from active-DTS measurements.~~ As a result, the estimated range of fluxes was highly reduced and ~~was found~~ in much better agreement with other estimates, as shown by dark grey lines in Fig. 909. For instance, between 63 and 72 m, the thermal conductivity was evaluated from active-DTS measurements between 1 and $1.9 \text{ W.m}^{-1}.\text{K}^{-1}$ depending on measurement points (Fig. 9a8a). Using such values, the fluxes estimated from passive-DTS measurements in this area vary between -9.5×10^{-6} and -4.3×10^{-5} m.s^{-1} (dark grey lines), whereas initially estimated between -2.2×10^{-5} and -5.4×10^{-6} m.s^{-1} considering λ between 1 and $4 \text{ W.m}^{-1}.\text{K}^{-1}$ (light grey

590

lines). As shown in Fig. 409, except between 48 and 52 m where small discrepancies remain, this approach significantly reduces the range of fluxes estimated and shows that passive-DTS results are in good agreement with active-DTS results when an independent and more precise estimate of the thermal conductivity is considered. ~~Note however that the exact location of the non heated cable (passive measurements) in relation to the heated cable is difficult to establish precisely which limits the precise location of the thermal conductivity estimates.~~

4 Discussion

In the following, we discuss the advantages and limitations of applying either passive- or active-DTS experiments depending on the objectives of the study and on technical limitations. Thus, we first focus on the possibilities of detecting and localizing groundwater inflows and their spatial and temporal dynamics before discussing the ability of quantify groundwater discharges. Besides comparing both approaches, we show the interest of combining both methods to infer the spatial and temporal variability of groundwater discharge at the catchment scale.

4.1 Passive DTS measurements Detecting, localizing and monitoring groundwater discharge

4.1.1 Interpretation of streambed temperature measurements

Results show that long-term passive-DTS measurements turn out to be an efficient method to detect, locate and monitor thermal anomalies that can be further interpreted as marker of groundwater discharge. ~~along several hundreds of meters.~~ The approaches consisted in ~~B~~ burying a FO cable in the streambed along several hundreds of meters, in order ~~allowed to recording~~ streambed temperature variations at high resolution during several months ~~along several hundreds of meters.~~ The high spatial and temporal resolution of measurements This is clearly the main advantage of the passive-DTS ~~method experiment~~ since such achievement would not have been possible with individual temperature probes. ~~Once the FO is installed in the streambed, which can be difficult depending on the streambed nature, the long term recording of temperature is relatively easy and autonomous. Moreover, although~~ Once the FO installation is installed in the streambed, can be difficult depending on the streambed nature, the long-term recording of temperature is relatively easy and autonomous.

Streambed temperature measurements recorded with the FO cable allow making first assumptions about the spatial and temporal dynamics occurring in the watershed if used over a several-month-long monitoring. ~~For doing so~~ To do so, the calculation of the Standard Deviation (SD) of streambed temperature over time appears a reliable proxy for locating inflows (Fig. 4 and 5), since higher-lower SDs values ~~reflect can be associated to~~ larger attenuation of daily temperature amplitudes. Here, the SD of temperature increases progressively from upstream to downstream up to reaching the SD of stream temperature around $d = 300$ m (Fig. 4b). ~~and~~ Very localized and low values of SD, described previously as minimal peakspikes of SD digressing from the general trend, also appear along the profile. Theoretically, temperature variations recorded in the streambed depend on the stream temperature variations and on the intensity of stream water/groundwater

625 exchanges (Constantz, 2008). Interpreting the data without measuring stream temperature variations along the stream
requires assuming that the stream temperature is uniform along the investigated section. In this case, the value of SD of the
stream temperature can be assumed uniform as well along the investigated section and any value of SD measured in the
streambed lower to the SD of the stream temperature could actually be interpreted as the result of groundwater inflows.
Here, this assumption seems reasonable since shade and lighting conditions as well as water depths are very similar along the
630 investigated section. Moreover, the transit time from the spring to the gauging station is relatively rapid due to the short
distances, and the river slopes and the very-low water depths imply a fast balance between the air temperature and the
stream temperature. This assumption is partly confirmed with the stream temperature recorded near the spring with the DTS,
in an area where the FO cable is not buried but lies in the bottom of the stream. At this location, the SD of the temperature
equals 1.03°C, which is a little less 1.375 °C, the value recorded in the stream at the gauging station E30, located at around
635 490 m of the spring. However, this suggests that the SD of the stream temperature signal should be relatively high, greater
than 1°C all along the stream and consequently much larger than the SD recorded within the streambed, especially in the
upstream section of the stream (first 300 meters).

Consequently, results suggest a decrease of groundwater inflows from upstream to downstream in the first 300 meters of the
watershed with higher and localized inflows in spots characterized by SDs values clearly lower than the general trend. This
is strengthened by the fact that the lowest values of SD (minimal 'spikes' of SD illustrated by the blue line in Fig. 5b)
640 correspond to clear thermal anomalies for which the temperature appears relatively stable over time. Beyond 300 m, the
values of the SD are almost equal to the SD of the stream temperature and the recorded temperature variations are
approximately similar to stream temperature variations. Concerning the second part of the golf area (from 300 to around 470
m), the data interpretation remains difficult because of the hard substrate that limited the burying of the FO cable. However,
in the last 70 meters of the FO cable (wood plain), the cable was easily buried in a thick sandy riverbed. Thus, values of SDs
645 in this area, equals to the one recorded in the stream, would suggest the absence of groundwater inflows, which would
remain limited to the wetland and therefore to the upper part of the watershed with highest topographic changes, as we shall
discuss below.

~~We have already made the assumption that these hotspots could be interpreted as groundwater discharges while the~~
650 ~~general increase of SD from the spring up to 300 meters could be interpreted either as a general decrease of groundwater~~
~~discharge from upstream to downstream or as a possible equilibrium between the stream temperature and the atmosphere.~~

~~We have already made the assumption that these hotspots could be interpreted as groundwater discharges while the general~~
655 ~~increase of SD from the spring up to 300 meters could be interpreted either as a general decrease of groundwater discharge~~
~~from upstream to downstream or as a possible equilibrium between the stream temperature and the atmosphere.~~

~~Theoretically, to interpret the data and conclude about groundwater/surface water exchanges, the temperature~~
~~variations recorded in the streambed should be compared with the stream temperature variations and the groundwater~~

660 temperature variations (Constantz, 2008). In practice, it would require deploying at least 3 FO cables in the field (Mamer and Lowry, 2013), which seems technically impossible. Therefore, the data interpretation requires assuming the stream temperature homogeneous along the investigated section, which is consistent in our study case since shade and lighting conditions and water depths are similar. Moreover, the transit time from the spring to the gauging station is relatively rapid due to the short distances and the river slopes and the very low water depths certainly support the fast balance between the air temperature and the stream temperature. This assumption is partly confirmed with the stream temperature recorded near the spring with the DTS, in an area where the FO cable is not buried but lies in the bottom of the stream. At this location, the SD of the temperature equals 1.03°C , which is a little less 1.375°C , the value recorded in the stream at the gauging station E30, located at around 490 m of the spring. However, this suggests that the SD of the stream temperature signal should be relatively high, greater than 1°C all along the stream and consequently much larger than the SD recorded within the streambed, especially in the upstream section of the stream (first 300 meters).

670 If stream temperature variations are assumed almost uniform along the studied section, the values of SDs inferior to the SD of the stream temperature could actually be interpreted as groundwater inflows. For these lower values, daily temperature variations are more or less attenuated in proportion to the value of the SD (as shown in Fig. 5). This is strengthened by the fact that, for the measurements points located in the wetland where the lowest values of SD are recorded (minimal 'peaks' of SD illustrated by the blue line in Fig. 5b), clear thermal anomalies are recorded and the temperature appears relatively stable over time according to the stable groundwater temperature (around $12.5\text{--}13^{\circ}\text{C}$). Therefore, results suggest a decrease of groundwater inflows from upstream to downstream in the first 300 meters of the watershed with higher and punctual inflows in spots where the SD with clearly lower than the general trend.

680 Beyond 300 m, the values of the SD are almost equal to the SD of the stream temperature and the recorded temperature variations are approximately similar to stream temperature variations. Concerning the second part of the golf area (from 300 to around 470 m), the data interpretation remains difficult because of the hard substrate that limited the burying of the FO cable. However, in the last 70 meters of the FO cable (wood plain), the cable was easily buried in a thick sandy riverbed. Thus, the value of the SD in this area, equals to the one recorded in the stream, would suggest the absence of groundwater inflows, which would remain limited to the wetland and therefore to the upper part of the watershed with highest topographic changes, as we shall discuss later.

685 Active-DTS measurements could also be used for localizing inflows, since the approach allows the accurate quantification of groundwater fluxes. However, contrary to passive-DTS measurements that ~~may directly~~ can be easily used to provide groundwater discharge areas, their identification from active-DTS measurements is indirect and requires going through flux quantification, which can be more constraining. Moreover, this method requires more instrumentation and the length of the heated section is limited depending on the power supply available electrical injection limitation (Simon et al., 2021). Thus, ~~contrary to passive DTS measurements, the~~ flow investigation at the watershed scale is way more difficult to achieve unless multiplying the installation of heated sections in the streambed. Furthermore (v) ~~Active-DTS~~

690

695 measurements provide a punctual estimate of fluxes. To characterize the temporal dynamic of flow, these experiments must be often repeated, which is clearly more constraining than conducting long-term passive-DTS measurements, because (active-DTS experiments require more instrumentation (heat-pulse system, electrical cables...) that require less instrumentation during data acquisition). However, the repetition of active-DTS measurements offer very promising perspectives for environmental monitoring as recently shown by Abesser et al. (2020) who repeated surveys under different meteorological or hydrological conditions in order to monitor the evolution of thermal and hydraulic properties of the soil subsurface.

700 4.2 Quantification of groundwater discharge

4.12.2-1 Quantification of groundwater inflows About the large uncertainties associated to the interpretation of passive-DTS measurements

705 To go further, the inverse numerical FLUX-BOT model was used to quantify the vertical fluxes from passive-DTS measurements in the first 150 meters of the temperature profile, which represents 545 measurements points, recorded all along the FO cable. Although this approach provided fluxes estimates, their relevance can clearly be discussed. Indeed, the estimates are highly uncertain, which demonstrates the difficulty of quantifying groundwater fluxes using passive-DTS measurements recorded along a single FO cable. The large uncertainties on estimates are due to several sources of uncertainties. Firstly, the model relies on the comparison of temperature variations recorded at 3 different depths. Ideally, the approach would require deploying at least 3 FO cables in the field (Mamer and Lowry, 2013) in order to continuously measure temperature conditions at high resolution at upper and lower boundaries, which was technically impossible in the field. Thus, as discussed above, the stream temperature variations were assumed uniform along the studied section, which seems consistent here. Moreover, the temperature signal recorded in the piezometer F4 was used to set the lower boundary condition of the model. This piezometer seems to be a good proxy for groundwater temperature. These assumptions seem consistent since the temperature signal measured at 20 m-depth in the piezometer F5b is similar to the one measured at 15 m-depth in the piezometer F4. This also suggests that the temperature of groundwater discharging into the stream is uniform along the investigated portion of the catchment. After all, however, although the assumptions about stream and groundwater temperatures seem reasonable, it considerably increases the uncertainties on fluxes estimates. However, secondly, the model requires defining the burial depth of the cable to calculate vertical fluxes and while results are very sensitive to this parameter, the numerical model requires making assumptions about boundary conditions or the burial depth of the cable, which appears to be a main limitation for quantifying groundwater inflows. For instance, although the burial depth was estimated around 8 cm, the precise determination of this depth all over the cable was not possible. Complementary tests (not shown here), conducted by varying the depth of the FO cable in the model, suggest that varying the burial depth of ± 2 cm induces in average a difference of $\pm 50\%$ on fluxes estimates, showing the high uncertainty associated to the uncertainty on the burial depth. Last but not least, most of all, results showed that thermal conductivity values have a very

725 strong impact on fluxes estimates, which is consistent with the results of Briggs et al. (2014), Duque et al. (2016), Lapham
(1989) and Sebok and Müller (2019). The lack of knowledge and assumptions on thermal conductivities values lead to high
uncertainties on fluxes estimates using both VTP and passive-DTS measurements (Fig. 6b). *In-situ* estimates of thermal
conductivities using thermal conductivity probes could considerably improve the fluxes estimates, as demonstrated by
730 Duque et al. (2016), who reported up to 89% increase in flux estimates when using *in situ* measured sediment thermal
conductivities. However, seeing the high spatial variability of the thermal conductivity highlighted through the active-DTS
experiment, it would certainly require a tremendous effort in the field to characterize such variability with single probes.
Moreover, it will not remove others sources of uncertainties associated to the burial depth of the FO cable or to the lack of
temperature measurements at different depths all along the section.

Consequently, uncertainties on fluxes estimates are so large that passive-DTS experiment does not appear as a
735 reliable and accurate method for estimating seepage rates. However, in the first 150 m, the model allows determining
the flow direction (upwelling fluxes), demonstrating that thermal anomalies can definitely be associated to groundwater
inflows confirming the spatial and temporal dynamics of exchanges occurring in the wetland. Note that the model was not
even applicable in the lower part of the watershed (for $d > 150$ m) to estimate flow direction. Thus, despite the values of the
SD recorded between $d = 150$ m and $d = 300$ m suggesting potential groundwater inflows, groundwater inflows are probably
740 too low or diffuse in this part of the watershed to apply the model and validate even the flow direction.

To summarize, fluxes quantification from passive-DTS measurements depends on several assumptions about
thermal properties and boundary conditions, which induces high uncertainties on fluxes estimates. Burying a single FO cable
745 in the streambed, although very promising and interesting, is limited to fully characterize and quantify groundwater/surface
water interactions, even in a headwater watershed. For further applications, results suggest the necessity of deploying an
additional FO cable at the bottom of the stream in order to measure also stream temperature variations at high resolution all
along the studied section. This seems the only way to fully and efficiently extend the heat-based classical methods
(Constantz, 2008; Hatch et al., 2006) at high spatial resolution. A third buried FO cable would be the optimal configuration
to estimate distributed vertical fluxes (Mamer and Lowry, 2013) and reduce the uncertainties on fluxes estimations based on
750 passive-DTS measurements.

Once again, the stream temperature variations were assumed uniform along the studied section. The model was clearly not
applicable in the lower part of the watershed (for $d > 150$ m) because of too large uncertainties on fluxes estimates. Thus,
despite the values of the SD recorded between $d = 150$ m and $d = 300$ m, slightly lower than the SD of the stream temperature
755 variations suggesting potential groundwater inflows, the fluxes quantification remains too uncertain in this area to be
validated. This is probably because groundwater inflows are too low or diffuse in this part of the watershed.

In the first 150 m, where the model can be successfully used, results firstly allow determining the flow direction,
showing that thermal anomalies can be associated to groundwater inflows. This confirms the spatial and temporal dynamics

of exchanges occurring in the wetland. However, the numerical model requires making assumptions about boundary conditions or the burial depth of the cable, which appears to be a main limitation for quantifying groundwater inflows. For instance, although the burial depth was estimated around 8 cm, the precise determination of this depth all over the cable was not possible. Complementary tests (not shown here), conducted by varying the depth of the FO cable in the model, suggest that varying the burial depth of ± 2 cm induces in average a difference of $\pm 50\%$ on fluxes estimates, showing the high uncertainty linked to the burial depth.

Most of all, results showed that thermal conductivity value has an impact on fluxes estimates, which is consistent with the results of Briggs et al. (2014), Duque et al. (2016), Lapham (1989) and Sebok and Müller (2019). The ignorance and assumptions on thermal conductivities values lead to high uncertainties on fluxes estimates using both VTP and passive DTS measurements. Thus, *in situ* estimates of thermal conductivities using thermal conductivity probes could considerably improve the fluxes estimates, as demonstrated by Duque et al. (2016), who reported up to 89% increase in flux estimates when using *in situ* measured sediment thermal conductivities. However, seeing the high spatial variability of the thermal conductivity highlighted through the active DTS experiment, it would certainly require a tremendous effort in the field to characterize such variability with single probes.

To summarize, passive DTS measurements can provide streambed temperature variations at high resolution during several months. As previously demonstrated (Krause et al., 2012; Le Lay et al., 2019b, a; Lowry et al., 2007), this approach can help highlighting possible groundwater inflows. The calculation of the SD is an efficient approach to rapidly identify strong thermal anomalies (Sebok et al., 2015) and to compare the temperature amplitudes recorded all along the FO cable (Le Lay et al., 2019b). However, the interpretation of temperature measurements and the fluxes quantification depend on strong assumptions about thermal properties and boundary conditions, and especially about the stream temperature. This suggests that burying a single FO cable in the streambed, although very promising and interesting, is not enough to fully characterize groundwater/surface water interactions. For further applications, results suggest the necessity of deploying an additional FO cable at the bottom of the stream in order to measure also stream temperature variations at high resolution all along the studied section. This seems the only way to fully and efficiently extend the heat based classical methods (Constantz, 2008; Hatch et al., 2006) at high spatial resolution. A third buried FO cable would be the optimal configuration to estimate distributed vertical fluxes (Mamer and Lowry, 2013) and reduce the uncertainties on fluxes estimations.

4.2.2 About the ability of Active-DTS methods to provide accurate fluxes estimates

Contrary to passive-DTS measurements, the active-DTS measurements turned out to be an efficient method to estimate fluxes at high resolution and with a very low uncertainty. From only 4 hrs of measurements, the approach provides an estimate of both the thermal conductivities and the fluxes along the heated cable confirming the high variability of these two parameters in space (Fig. 98). Despite some difficulties to install the heated FO cable, fluxes were even so estimated for 172 measurements points along a 60-meter section of cable, which is an excellent performance. This high resolution is

795 particularly interesting to characterize spatial variabilities at small scale. Such results cannot be achieved with any other methods commonly used in this context. Note that the installation of the heated FO cable was entirely manual and rapid, which probably partly explains the relatively large number of measurement points removed from data processing. Nevertheless, the use of tools like ploughs should improve the burying of the cable, limit the alteration of the riverbed and allow for a much better control of the burial depth. It clearly appears that the main advantage of the approach is the low uncertainty on fluxes estimates. Note that the use of the ADTS Toolbox, that automatically interprets active DTS measurements (Simon and Bour, Submitted), highly facilitates the data interpretation, which is finally much easier than the interpretation of passive DTS measurements.

800 Results show that streambed thermal conductivities are relatively variable in space, typically between 0.9 to 3.1 $\text{W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (Fig. 8a), but which is consistent with streambed sediments, composed of saturated clay and silt, and saturated sand and gravel, whose thermal conductivity values commonly range respectively between 0.9 and 4 $\text{W}\cdot\text{m}^{-1}\cdot\text{K}^{-1}$ (Stauffer et al., 2013). The large range of thermal conductivities observed in this relatively small section of streambed (less than 60m) demonstrates the interest of distributed measurements to fully characterize the streambed heterogeneity. No other method
805 could provide an estimate of the thermal properties at this spatial resolution.

Groundwater fluxes were estimated between 2×10^{-6} and 4.74×10^{-5} $\text{m}\cdot\text{s}^{-1}$, in very good agreement with the results of the VTPs (Fig. 409). The results suggest a decrease of the groundwater discharge from upstream to downstream, with the most significant inflows located in the first 20-m of the heated section. Elsewhere, groundwater discharge is more diffuse in space although significant groundwater discharge areas can be locally observed. Results also highlight very
810 local increases of groundwater discharge matching match with punctual isolated decreases of streambed temperature SD values, calculated from passive-DTS measurements (Fig. 409). This confirms the possibility of investigating very punctual local groundwater inflows and the capability of investigating the spatial evolution of fluxes at very small scale. Thus, active-DTS measurements allow validating the hypothesis made to interpret passive-DTS measurements (diffuse inflows with very punctual increases of groundwater discharge).

815 The magnitude of groundwater flux is also in good agreement with the measured stream flow. Considering the width and the length of the investigated stream where groundwater inflows have been estimated, contribution to the stream can be roughly evaluated around 4 $\text{L}\cdot\text{s}^{-1}$. This means that 57% of the stream flow at the time of the experiment was contributed by groundwater (knowing that the average flow measured at the downstream gauging station was 7 $\text{L}\cdot\text{s}^{-1}$ for this period).

820 It clearly appears that the main advantages of the approach are i) the low uncertainty on fluxes estimates and ii) the associated estimates of thermal conductivities. The use of the ADTS Toolbox, that automatically interprets active-DTS measurements (Simon and Bour, Submitted), highly facilitates data interpretation, which is finally much easier than the interpretation of passive-DTS measurements. Contrary to passive-DTS measurements, the interpretation of active-DTS
825 measurements provides estimates of thermal conductivities with a very good accuracy. Thus, the approach does not require

830 assuming thermal conductivity values which considerably reduce the uncertainties of the fluxes estimates. However, the burial depth of the heated cable might potentially affect the thermal response, ~~to heating. Indeed,~~ if the cable is too close to the stream. In this case, the stream temperature could limit the temperature elevation by dissipating the heat produced and, ~~for~~ further investigations should be done to quantify the effect of the near stream on estimates. However here, the active-DTS experiment was conducted straight after the installation of the cable, ensuring that the burial depth was sufficient to limit the effect of the near stream (results from modelling showed that the heating is particularly localized around the heated cable). Finally, in gaining streams, active-DTS measurements are independent of temperature boundary conditions, as long as the groundwater temperature is constant over time. Indeed, in gaining conditions, with no groundwater temperature variations, the temperature evolution measured along the FO cable is exclusively due to heat injection, streambed sediment properties and groundwater flows intensity. Here, over the heating experiment, an average temperature of 12.1 °C with a standard deviation of 0.12 °C has been recorded in sediments along non-heated buried sections of the cable demonstrating that the streambed temperature was not affected by potentials air/stream variations and that the temperature variations recorded along the heated section are exclusively due to the heat experiment. In losing conditions, since diurnal water temperature variations propagates deeper, it could be necessary to separate the temperature evolution induced by the heat injection and the one depending on stream temperature variations.

840 4.2.3 About the complementary use of both approaches

845 Finally, the complementary of both approaches should be noted. First, the data interpretation of active-DTS measurements does not provide the flow direction contrary to the interpretation of passive-DTS measurements. ~~The determination of the flow direction requires coupling the data with complementary approaches, such as passive DTS measurements, piezometric gradients, etc.~~ Note that ~~the~~ the temperature variations recorded before the heating period and after the end of the recovery can be used to determine the flow direction as soon as the stream temperature variations are assumed uniform along the heated section. Of course, results of active-DTS measurements are useful to validate the general behaviour/trend highlighted through passive-DTS measurements, that is a baseline of groundwater discharge associated to local and important spikes of discharge. They do not fully allow validating the different hypothesis made to interpret passive-DTS measurements but they permit to check the consistency of the results obtained. Results also show (Fig. 409) that the interpretation of active-DTS measurements can be directly used to improve the interpretation of passive-DTS measurements. Indeed, the values of thermal conductivities, estimated from active-DTS measurements, can be used to calibrate the inverse model and therefore to reduce the uncertainties on fluxes estimates from passive-DTS measurements. This is a very promising result since it highly facilitates the interpretation of passive-DTS measurements. Once thermal conductivity distribution is known along the section, passive-DTS-experiments could therefore be considered as an independent and full tool to quantify GW discharge at high resolution through long-term monitoring. ~~It can lead to a much better quantification of groundwater inflows at a new temporal and spatial scale~~ (although the assumption on the stream temperature remains an issue).

Finally, some limitations and inconveniences should be noted:

(i) The installation of the heated FO cable was entirely manual and rapid, which probably partly explains the large number of measurement points removed before the data interpretation. Nevertheless, the use of tools like ploughs should improve the burying of the cable, limit the alteration of the riverbed and allow for a much better control of the burial depth.

(ii) In gaining streams, the burial depth of the heated cable might potentially affect the thermal response to heating. Indeed, if the cable is too close to the stream, the stream temperature could limit the temperature elevation by dissipating the heat produced. Further investigations should be done to quantify the effect of the near stream on estimates.

(iii) The data interpretation does not provide the flow direction contrary to the interpretation of passive DTS measurements. The determination of the flow direction requires coupling the data with complementary approaches, such as passive DTS measurements, piezometric gradients, etc. The temperature variations recorded before the heating period and after the end of the recovery can also be used as soon as the stream temperature variations are assumed uniform along the heated section.

(iv) Active DTS experiments might cause more technical problems than passive DTS experiments and requires a significant instrumentation (heat pulse system, electrical cables...). Moreover, the length of the heated section is limited, due to the electrical injection limitation (Simon et al., 2021). Thus, contrary to passive DTS measurements, the flow investigation at the watershed scale is nearly impossible unless multiplying the installation of heated sections in the streambed.

(v) Active DTS measurements provide a punctual estimate of fluxes. To characterize the temporal dynamic of flow, these experiments must be often repeated, which is clearly more constraining than conducting long term passive DTS measurements (that require less instrumentation during data acquisition). However, the repetition of active DTS measurements offer very promising perspectives for environmental monitoring such as recently showed by Abesser et al. (2020) who repeated surveys under different meteorological or hydrological conditions in order to monitor the thermal and the hydraulic properties of the soil subsurface.

Finally, note also that for the interpretation of both passive- and active-DTS measurements, the flow is assumed to be vertical and perpendicular to the FO cable. Although ~~the absence of nonvertical~~ flow ~~components~~ is generally assumed vertical when using ~~the~~ heat as a tracer for studying groundwater/stream interactions (Constantz, 2008; Hatch et al., 2006; Lapham, 1989), nonvertical fluxes can affect natural temperature profiles and associated fluxes estimates (Bartolino and Niswonger, 1999; Cranswick et al., 2014; Cuthbert and Mackay, 2013; Lautz, 2010; Reeves and Hatch, 2016), ~~and~~ Obviously, like for most thermal-based methods, this is a main limitation so when using passive-DTS measurements to detect interpretation and quantify groundwater discharge. Likewise, nonvertical fluxes could also affect the interpretation of active-DTS measurements. Thus, some studies suggest that the impact of the angle of the flow against the cable is significant as soon as it differs more than $\pm 30^\circ$ from being perpendicular (Aufleger et al., 2007; Chen et al., 2019; Perzmaier et al., 2004).

4.3 Groundwater/stream water exchanges Characterizing groundwater discharge dynamics

The complementary use of these two DTS approaches allows characterizing spatial and temporal patterns of groundwater/stream water exchanges discharge in this headwater catchment in order to better describe the hydrological behaviour in this headwater watershed. Results and associated fluxes estimates are consistent with previous studies that predicted that 80-90% of the stream flow was induced by groundwater discharge (Fovet et al., 2015b; Martin, 2003). Interestingly, the two approaches allows characterizing the groundwater discharge dynamic at two different scales. This is a particularly promising and exciting achievement since groundwater/surface water interactions are generally controlled by multi-scale processes, making their characterization particularly challenging in the field (Brunke and Gonser, 1997; Fleckenstein et al., 2006; Flipo et al., 2014; Harvey and Bencala, 1993; Kalbus et al., 2009).

First, conducting measurements over more than 530 m-linear allow describing groundwater discharge dynamic at the catchment scale. Thus, results suggest that the groundwater contribution is concentrated-localized in the very head of the catchment, in the wetland and more especially in the upstream near the spring, where the steepest slopes can be observed. Further downstream, beyond 60 m from the spring, the groundwater discharge decreases progressively and rapidly. This confirms the importance of the topography in the stream generation in headwater area (Harvey and Bencala, 1993; Sophocleous, 2002; Tóth, 1963; Winter, 2007) and the role of local topography variations on groundwater discharge (Baxter and Hauer, 2000; Flipo et al., 2014; Frei et al., 2010; Jencso et al., 2009; Stonedahl et al., 2010; Tonina and Buffington, 2011; Unland et al., 2013).

Secondly, the high resolution of DTS measurements allows studying groundwater discharge dynamic at very small scale and thus highlighting local heterogeneities, which would not have been possible with more integrative methods. Therefore, Beyond the role of topography which acts as the main driver of groundwater inflows, variations of hydraulic conductivity could also explain the presence of local hotspots with high groundwater inflows, highlighted with both methods in the wetland area, upstream near the spring. Indeed, these hotspots peakspikes that would highly contribute to the stream flow may be driven by local changes in the hydraulic gradient, induced by the successive streambed topography changes, but are more likely due to hydraulic properties changes given the amplitude and scale of variations. Such hydraulic conductivity variations could come from uneven bedrock weathering or to the presence of fractures which is very common in such bedrock geology (Buss et al., 2008; Guihéneuf et al., 2014). Such heterogeneities may control flow in the subsurface but can also influence the nature of the streambed. This would also explain why the values of fluxes seem correlated, at least at some places, with the values of thermal conductivities (Fig. 98). Indeed, our results suggest that local hotspots with high groundwater inflows are also associated to higher values of thermal conductivities. This is consistent with a change of streambed properties. Indeed, clay and silt have much lower hydraulic conductivities than sand but also lower thermal conductivities (Stauffer et al., 2013). Although cross-correlation analysis would be useful to go further in the interpretation, such correlation would not be surprising since the nature of the streambed affects both its hydraulic conductivity and its thermal properties.

925 Concerning temporal variations, three different time periods were clearly identified ~~with from~~ the passive-DTS
measurements according to the behaviour of the streambed temperature evolution over time (Fig. 4, ~~and 5 and 6~~). ~~It seems~~
~~that~~ ~~†~~The increase in precipitations in winter certainly leads to increase gradually the hydraulic gradient, which induces
groundwater exfiltration into the stream once the elevation of the groundwater table becomes higher than the elevation of the
stream stage. ~~During the~~In spring, the groundwater table decreases progressively and so do the groundwater contribution to
930 stream flow. Since changes in piezometric levels are periodic with alternating periods of high and low water table levels, we
can assume that exchanges have a similar temporal dynamic from year to year, which can help managing water resources.
These results are consistent with the temporal dynamic of exchanges observed under temperate climate where the intensity
of groundwater/surface water exchanges fluctuates according to seasonal patterns (Brunke and Gonser, 1997; Sophocleous,
2002). More important, these results highlight the interest of the long-term monitoring of streambed temperature with ~~the~~
935 DTS. Here, with only 6 eight months of measurements, the experiment allowed continuously monitoring hydrological
conditions changes and clearly identifying “hot-moments” corresponding to groundwater discharge periods. In headwater
catchments, these tools should allow in the near future investigating the distribution of response times of groundwater
discharges to some specific events, which is very promising. ~~Here, with only 6 months of measurements, the experiment~~
~~allowed continuously monitoring hydrological conditions changes and clearly identifying “hot moments” corresponding to~~
940 ~~groundwater discharge periods.~~ This was made possible through T the high spatial and temporal resolutions frequency of
measurements, allow monitoring the rapid change of hydrological conditions and therefore to precisely identify the moments
when groundwater inflows to the stream. Thus, long term DTS measurements can provide the precise identification of
hotspots of groundwater discharge and of “hot moments”, corresponding to the groundwater discharge periods.

945 These results are useful to understand the hydrological behaviour in the watershed but also for studying biogeochemical
hotspots and hot moments (Krause et al., 2017; Singh et al., 2019; Trauth and Fleckenstein, 2017). (Ferencz et al., 2019;
Gomez Velez et al., 2017; Pinder and Sauer, 1971; Harvey and Gooseff, 2015)

5 Conclusions

950 To summarize, ~~passive DTS measurements can provide streambed temperature variations at high resolution during several~~
~~months.~~ As previously demonstrated (Krause et al., 2012; Le Lay et al., 2019b, a; Lowry et al., 2007), this approach can help
highlighting possible groundwater inflows. The calculation of the SD is an efficient approach to rapidly identify strong
thermal anomalies (Sebok et al., 2015) and to compare the temperature amplitudes recorded all along the FO cable (Le Lay
et al., 2019b). However, the interpretation of temperature measurements and the fluxes quantification depend on strong
955 assumptions about thermal properties and boundary conditions, and especially about the stream temperature. This suggests
that burying a single FO cable in the streambed, although very promising and interesting, is not enough to fully characterize
groundwater/surface water interactions. For further applications, results suggest the necessity of deploying an additional FO
cable at the bottom of the stream in order to measure also stream temperature variations at high resolution all along the

studied section. This seems the only way to fully and efficiently extend the heat-based classical methods (Constantz, 2008; Hatch et al., 2006) at high spatial resolution. A third buried FO cable would be the optimal configuration to estimate distributed vertical fluxes (Mamer and Lowry, 2013) and reduce the uncertainties on fluxes estimations.

Passive- and active-DTS measurements were conducted concurrently in the same experimental site in order to characterize the spatial and temporal patterns of groundwater/stream interactions discharge of into a first and second-order stream. The long-term passive-DTS measurements monitoring can easily be used to assess the spatial and the temporal dynamics of groundwater discharge. The analysis of streambed temperature recordings allows identifying thermal anomalies that can be interpreted as markers of groundwater inflows into the stream. Here, results suggest that groundwater discharge is localized in the upper part of the watershed where topographic gradients are the highest, and the associated quantification of vertical fluxes demonstrated the potential but also the limits of the approach to characterize both the temporal and spatial variability of groundwater discharge into the stream at the headwater stream scale. Thus, results highlighted preferential discharge areas depending on the streambed properties and topography, showing that the head of the watershed highly contributes to stream flow. The temporal variations of groundwater inflows over time were also clearly identified depending on the annual hydrological cycle and on changes in meteorological and hydrological conditions at the watershed scale. These results are consistent with the results of Martin (2003) showing that hydraulic gradients on the hillslope of the watershed imply a high contribution of the shallow groundwater to the stream discharge during high water periods.

——— However, this study also demonstrates the limitations of passive-DTS measurements for quantifying groundwater discharges. When a single FO cable is buried in the streambed, the data interpretation requires making strong assumptions about the thermal conductivity of sediments and about the stream temperature. Uncertainties may be reduced if previous and independent measurements of the variability of streambed thermal conductivities are available, conducted through active-DTS measurements, for instance. ~~However~~ Nevertheless, the interpretation of passive-DTS measurements would still rely on the assumption that the stream temperature is uniform along the studied section. In practice, the proper estimation of passive-DTS measurements conducted in streambeds would require measuring the stream temperature with the same spatial resolution and thus deploying a second FO cable at the bottom of the stream.

Active-DTS measurements allowed going way further in the characterization of groundwater inflows through the estimate of fluxes and their spatial distribution with a very low uncertainty in comparison with passive-DTS measurements and *in situ* thermal methods. The quantification of groundwater fluxes through the active-DTS measurements clearly shows the co-existence of both local hotspots, characterized by very localized and high groundwater inflows, and more diffuse groundwater inflows elsewhere along the heated section. This allowed to confirming the role of topography on the large-scale variations of groundwater discharge, but also the role of heterogeneities at small scales. Such small-scale variability of groundwater discharge is certainly associated to hydraulic conductivity variations. Firstly Moreover, the active-DTS experiment allowed identifying and quantifying describing the high variability of thermal conductivity in space. ~~Secondly, the quantification of groundwater fluxes through the active DTS measurements clearly showed the co-existence of local hotspots, characterized by very localized and high groundwater inflows and more diffuse groundwater inflows elsewhere~~

along the heated section. The method considerably decreases the uncertainty on fluxes estimates and allows describing the variability of streambed properties at an unprecedented scale.

The complementarity of passive and active DTS measurements to fully characterize the dynamic of groundwater/surface water interactions should also be highlighted. Indeed, while long-term passive DTS measurements can be relatively easily conducted, the application of active DTS measurements in the field is more constraining, meaning that active DTS experiments are generally punctual and provide a single punctual estimate of the variability of thermal conductivity and fluxes. Thus, Finally, it should be noted that passive-DTS measurements permitted to locate the spatial and temporal patterns of groundwater inflows on relatively large distances, while active-DTS measurements allowed a much more precise and robust estimate of both thermal conductivities and fluxes which can highly contribute to improve passive-DTS methods interpretation. Hence, the combination of active- and passive-DTS methods provided an imaging of the spatial variability of groundwater inflows. It allowed better inferring the role of topography, which acts as the main driver of groundwater inflows in the upper part of the watershed, and also the impact of hydraulic conductivity variations which may explain the presence of very localized and high groundwater inflows.

-Thus, these methods and especially active-DTS measurements conducted in the streambed open very promising perspectives for novel characterization of the groundwater/stream interfaces, especially if surveys are repeated under different meteorological or hydrological conditions. Being able to continuously monitoring the temporal dynamic of exchanges is a very promising achievement that could be useful to understand the hydrological behaviour in the watershed but also for characterizing the distribution of response times of groundwater discharge. This can be particularly useful for studying biogeochemical hotspots and hot moments (Krause et al., 2017; Singh et al., 2019; Trauth and Fleckenstein, 2017) or to couple this approach with natural tracers to assess the residence times in the hyporheic zone (Biehler et al., 2020; Liao et al., 2021).

Data availability

The data presented in this study are available online.

Link through data related to the active-DTS experiment: <http://geowww.agrocampus-ouest.fr/geonetwork/apps/georchestra/?uuid=535a3738-0ed7-4376-99f1-9a7a652b893d>

Link through data related to the passive-DTS experiment: <http://geowww.agrocampus-ouest.fr/geonetwork/apps/georchestra/?uuid=a5f2a68f-bf63-469c-839b-1e1edf1f8624>

Supplement link:

Author contribution

Conceptualization: NS, OB, LL, OF and ZT; Data curation: NS; Formal analysis: NS; Funding acquisition: OB; Investigation: NS, OB, NL, MF, OF, HLL and ZT; Methodology: NS; Project administration: OB, OF and ZT; Resources: 1025 NL and MF; Software: NS; Supervision: OB; Validation: NS and OB; Visualization: NS; Writing – original draft preparation: NS; Writing – review & editing: NS, OB, OF, ZT and LL.

Competing interests

The authors declare that they have no conflict of interest.

Acknowledgements

1030 This research was funded by the Agence de l'Eau Loire Bretagne and by the ANR project EQUIPEX CRITEX (grant number ANR-11-EQPX-0011).

References

- 1035 Abesser, C., Ciocca, F., Findlay, J., Hannah, D., Blaen, P., Chalari, A., Mondanos, M., and Krause, S.: A distributed heat pulse sensor network for thermo-hydraulic monitoring of the soil subsurface, *Quarterly Journal of Engineering Geology and Hydrogeology*, 53, 352–365, <https://doi.org/10.1144/qjegh2018-147>, 2020.
- Anderson, M. P.: Heat as a ground water tracer, *Ground Water*, 43, 951–968, <https://doi.org/10.1111/j.1745-6584.2005.00052.x>, 2005.
- Aufleger, M., Conrad, M., Goltz, M., Perzlmaier, S., and Porras, P.: Innovative dam monitoring tools based on distributed temperature measurement, *Jordan Journal of Civil Engineering*, 1, 29–37, 2007.
- 1040 Banks, E., Shanafield, M., and Cook, P.: Induced Temperature Gradients to Examine Groundwater Flowpaths in Open Boreholes, 52, <https://doi.org/10.1111/gwat.12157>, 2014.
- Bartolino, J. R. and Niswonger, R. G.: Numerical simulation of vertical ground-water flux of the Rio Grande from ground-water temperature profiles, central New Mexico, Reston, VA, <https://doi.org/10.3133/wri994212>, 1999.
- 1045 Baxter, C. and Hauer, F.: Geomorphology, Hyporheic Exchange, and Selection of Spawning Habitat by Bull Trout (*Salvelinus Confluentus*), *Canadian Journal of Fisheries and Aquatic Sciences - CAN J FISHERIES AQUAT SCI*, 57, 1470–1481, <https://doi.org/10.1139/cjfas-57-7-1470>, 2000.
- Bencala, K.: A Perspective on Stream-Catchment Connections, *J. N. Am. Benthol. Soc.*, 12, 44–47, <https://doi.org/10.2307/1467684>, 1993.

- 1050 Bense, V. F., Read, T., Bour, O., Le Borgne, T., Coleman, T., Krause, S., Chalari, A., Mondanos, M., Ciocca, F., and Selker, J. S.: Distributed Temperature Sensing as a downhole tool in hydrogeology, *Water Resour. Res.*, 52, 9259–9273, <https://doi.org/10.1002/2016WR018869>, 2016.
- Biehler, A., Chaillou, G., Buffin-Bélanger, T., and Baudron, P.: Hydrological connectivity in the aquifer–river continuum: Impact of river stages on the geochemistry of groundwater floodplains, 590, 125379, <https://doi.org/10.1016/j.jhydrol.2020.125379>, 2020.
- 1055 Brandt, T., Vieweg, M., Laube, G., Schima, R., Goblirsch, T., Fleckenstein, J. H., and Schmidt, C.: Automated in Situ Oxygen Profiling at Aquatic–Terrestrial Interfaces, *Environ. Sci. Technol.*, 51, 9970–9978, <https://doi.org/10.1021/acs.est.7b01482>, 2017.
- 1060 Briggs, M. A., Lautz, L. K., and McKenzie, J. M.: A comparison of fibre-optic distributed temperature sensing to traditional methods of evaluating groundwater inflow to streams, *Hydrol. Process.*, 26, 1277–1290, <https://doi.org/10.1002/hyp.8200>, 2012.
- Briggs, M. A., Lautz, L. K., Buckley, S. F., and Lane, J. W.: Practical limitations on the use of diurnal temperature signals to quantify groundwater upwelling, *J. Hydrol.*, 519, 1739–1751, <https://doi.org/10.1016/j.jhydrol.2014.09.030>, 2014.
- 1065 Briggs, M. A., Buckley, S. F., Bagtzoglou, A. C., Werkema, D. D., and Lane, J. W.: Actively heated high-resolution fiber-optic-distributed temperature sensing to quantify streambed flow dynamics in zones of strong groundwater upwelling, *Water Resour. Res.*, 52, 5179–5194, <https://doi.org/10.1002/2015WR018219>, 2016.
- Brunke, M. and Gonsler, T.: The ecological significance of exchange processes between rivers and groundwater, *Freshw. Biol.*, 37, 1–33, <https://doi.org/10.1046/j.1365-2427.1997.00143.x>, 1997.
- 1070 Buss, H. L., Sak, P. B., Webb, S. M., and Brantley, S. L.: Weathering of the Rio Blanco quartz diorite, Luquillo Mountains, Puerto Rico: Coupling oxidation, dissolution, and fracturing, *Geochimica et Cosmochimica Acta*, 72, 4488–4507, <https://doi.org/10.1016/j.gca.2008.06.020>, 2008.
- Carslaw, H. S. and Jaeger, J. C.: *Conduction of heat in solids*, Oxford Univers. Press, 1959.
- Chen, J., Xiong, F., Zheng, J., Ge, Q., and Cheng, F.: The influence of infiltration angle on the identification effect of seepage with linear heat source method, *Measurement*, 148, 106974, <https://doi.org/10.1016/j.measurement.2019.106974>, 2019.
- 1075 Constantz, J.: Heat as a tracer to determine streambed water exchanges, *Water Resources Research*, 44, <https://doi.org/10.1029/2008WR006996>, 2008.
- Constantz, J. and Thomas, C. L.: The use of streambed temperature profiles to estimate the depth, duration, and rate of percolation beneath arroyos, *Water Resour. Res.*, 32, 3597–3602, <https://doi.org/10.1029/96WR03014>, 1996.
- 1080 Cranswick, R. H., Cook, P. G., Shanfield, M., and Lamontagne, S.: The vertical variability of hyporheic fluxes inferred from riverbed temperature data, *Water Resources Research*, 50, 3994–4010, <https://doi.org/10.1002/2013WR014410>, 2014.
- Cuthbert, M. O. and Mackay, R.: Impacts of nonuniform flow on estimates of vertical streambed flux, *Water Resources Research*, 49, 19–28, <https://doi.org/10.1029/2011WR011587>, 2013.
- Domenico, P. A. and Schwartz, F. W.: *Physical and chemical hydrogeology*. Second edition, New York: John Wiley&Sons Inc., 1998.

- 1085 Duque, C., Müller, S., Sebok, E., Haider, K., and Engesgaard, P.: Estimating groundwater discharge to surface waters using heat as a tracer in low flux environments: the role of thermal conductivity, 30, 383–395, <https://doi.org/10.1002/hyp.10568>, 2016.
- Fleckenstein, J. H., Niswonger, R. G., and Fogg, G. E.: River-aquifer interactions, geologic heterogeneity, and low-flow management, *Ground Water*, 44, 837–852, <https://doi.org/10.1111/j.1745-6584.2006.00190.x>, 2006.
- 1090 Flipo, N., Mouhri, A., Labarthe, B., Biancamaria, S., Rivièrè, A., and Weill, P.: Continental hydrosystem modelling: the concept of nested stream-aquifer interfaces, 18, 3121–3149, <https://doi.org/10.5194/hess-18-3121-2014>, 2014.
- Fovet, O., Ruiz, L., Hrachowitz, M., Faucheux, M., and Gascuel-Oudou, C.: Hydrological hysteresis and its value for assessing process consistency in catchment conceptual models, *Hydrol. Earth Syst. Sci.*, 19, 105–123, <https://doi.org/10.5194/hess-19-105-2015>, 2015a.
- 1095 Fovet, O., Ruiz, L., Faucheux, M., Molénat, J., Sekhar, M., Vertès, F., Aquilina, L., Gascuel-Oudou, C., and Durand, P.: Using long time series of agricultural-derived nitrates for estimating catchment transit times, *Journal of Hydrology*, 522, 603–617, <https://doi.org/10.1016/j.jhydrol.2015.01.030>, 2015b.
- Frei, S., Lischeid, G., and Fleckenstein, J. H.: Effects of micro-topography on surface–subsurface exchange and runoff generation in a virtual riparian wetland — A modeling study, *Advances in Water Resources*, 33, 1388–1401, <https://doi.org/10.1016/j.advwatres.2010.07.006>, 2010.
- 1100 Frei, S., Durejka, S., Le Lay, H., Thomas, Z., and Gilfedder, B. S.: Quantification of Hyporheic Nitrate Removal at the Reach Scale: Exposure Times Versus Residence Times, *Water Resources Research*, 55, 9808–9825, <https://doi.org/10.1029/2019WR025540>, 2019.
- Gaillardet, J., Braud, I., Hankard, F., Anquetin, S., Bour, O., Dörfli, N., de Dreuzy, J.-R., Galle, S., Galy, C., Gogo, S., Gourcy, L., Habets, F., Laggoun, F., Longuevergne, L., Borgne, T., Naaim-Bouvet, F., Nord, G., Simonneaux, V., Six, D., and Zitouna, R.: OZCAR: The French network of critical zone observatories, *Vadose Zone Journal*, 17, <https://doi.org/10.2136/vzj2018.04.0067>, 2018.
- Ghafoori, Y., Vidmar, A., Říha, J., and Kryžanowski, A.: A Review of Measurement Calibration and Interpretation for Seepage Monitoring by Optical Fiber Distributed Temperature Sensors, 20, <https://doi.org/10.3390/s20195696>, 2020.
- 1110 van de Giesen, N., Steele-Dunne, S. C., Jansen, J., Hoes, O., Hausner, M. B., Tyler, S., and Selker, J.: Double-Ended Calibration of Fiber-Optic Raman Spectra Distributed Temperature Sensing Data, *Sensors*, 12, 5471–5485, <https://doi.org/10.3390/s120505471>, 2012.
- Gilmore, T., Johnson, M., Korus, J., Mittelstet, A., Briggs, M., Zlotnik, V., and Corcoran, S.: Streambed Flux Measurement Informed by Distributed Temperature Sensing Leads to a Significantly Different Characterization of Groundwater Discharge, *Water*, 11, 2312, <https://doi.org/10.3390/w11112312>, 2019.
- 1115 Goto, S., Yamano, M., and Kinoshita, M.: Thermal response of sediment with vertical fluid flow to periodic temperature variation at the surface, *J. Geophys. Res.-Solid Earth*, 110, B01106, <https://doi.org/10.1029/2004JB003419>, 2005.
- Guihéneuf, N., Boisson, A., Bour, O., Dewandel, B., Perrin, J., Amélie, D., Viossanges, M., Chandra, S., Ahmed, S., and Maréchal, J.-C.: Groundwater flows in weathered crystalline rocks: Impact of piezometric variations and depth-dependent fracture connectivity, *Journal of Hydrology*, 511, 320–334, <https://doi.org/10.1016/j.jhydrol.2014.01.061>, 2014.
- 1120

- Habel, W., Baumann, I., Berghmans, F., Borzycki, K., Chojetzki, C., Haase, K.-H., Jaroszewicz, L., Kleckers, T., Nikles, M., Schluter, V., Thévenaz, L., Tur, M., and Wuilpart, M.: Guideline for Use of Fibre Optic Sensors, 2009.
- Harvey, J. and Bencala, K.: The Effect of Streambed Topography on Surface-Subsurface Water Exchange, *Water Resour. Res.*, 29, 89–98, <https://doi.org/10.1029/92WR01960>, 1993.
- 1125 Hatch, C. E., Fisher, A. T., Revenaugh, J. S., Constantz, J., and Ruehl, C.: Quantifying surface water-groundwater interactions using time series analysis of streambed thermal records: Method development, *Water Resour. Res.*, 42, W10410, <https://doi.org/10.1029/2005WR004787>, 2006.
- 1130 [Jencso, K. G., McGlynn, B. L., Gooseff, M. N., Wondzell, S. M., Bencala, K. E., and Marshall, L. A.: Hydrologic connectivity between landscapes and streams: Transferring reach- and plot-scale understanding to the catchment scale, *Water Resources Research*, 45, <https://doi.org/10.1029/2008WR007225>, 2009.](https://doi.org/10.1029/2008WR007225)
- Jones, J. B. and Mulholland, P. J. (Eds.): AQUATIC ECOLOGY Series, in: Streams and Ground Waters, Academic Press, San Diego, ii, <https://doi.org/10.1016/B978-0-12-389845-6.50020-X>, 2000.
- Kalbus, E., Reinstorf, F., and Schirmer, M.: Measuring methods for groundwater - surface water interactions: a review, *Hydrol. Earth Syst. Sci.*, 10, 873–887, 2006.
- 1135 Kalbus, E., Schmidt, C., Molson, J. W., Reinstorf, F., and Schirmer, M.: Influence of aquifer and streambed heterogeneity on the distribution of groundwater discharge, *Hydrol. Earth Syst. Sci.*, 13, 69–77, 2009.
- Keery, J., Binley, A., Crook, N., and Smith, J. W. N.: Temporal and spatial variability of groundwater-surface water fluxes: Development and application of an analytical method using temperature time series, *J. Hydrol.*, 336, 1–16, <https://doi.org/10.1016/j.jhydrol.2006.12.003>, 2007.
- 1140 Klepikova, M., Roques, C., Loew, S., and Selker, J.: Improved Characterization of Groundwater Flow in Heterogeneous Aquifers Using Granular Polyacrylamide (PAM) Gel as Temporary Grout, *Water Resources Research*, 54, <https://doi.org/10.1002/2017WR022259>, 2018.
- 1145 Koruk, K., Yilmaz, K. K., Akyurek, Z., and Binley, A.: A multi-technique approach to determine temporal and spatial variability of groundwater–stream water exchange, *Hydrological Processes*, 34, 2612–2627, <https://doi.org/10.1002/hyp.13754>, 2020.
- Krause, S., Blume, T., and Cassidy, N. J.: Investigating patterns and controls of groundwater up-welling in a lowland river by combining Fibre-optic Distributed Temperature Sensing with observations of vertical hydraulic gradients, *Hydrol. Earth Syst. Sci.*, 16, 1775–1792, <https://doi.org/10.5194/hess-16-1775-2012>, 2012.
- 1150 Krause, S., Lewandowski, J., Grimm, N. B., Hannah, D. M., Pinay, G., McDonald, K., Martí, E., Argerich, A., Pfister, L., Klaus, J., Battin, T., Larned, S. T., Schelker, J., Fleckenstein, J., Schmidt, C., Rivett, M. O., Watts, G., Sabater, F., Sorolla, A., and Turk, V.: Ecohydrological interfaces as hot spots of ecosystem processes, *Water Resources Research*, 53, 6359–6376, <https://doi.org/10.1002/2016WR019516>, 2017.
- Kurth, A.-M., Weber, C., and Schirmer, M.: How effective is river restoration in re-establishing groundwater-surface water interactions? - A case study, *Hydrol. Earth Syst. Sci.*, 19, 2663–2672, <https://doi.org/10.5194/hess-19-2663-2015>, 2015.
- 1155 Lapham, W. W.: Use of temperature profiles beneath streams to determine rates of vertical ground-water flow and vertical hydraulic conductivity, *Water-Supply.*, Denver, Colorado: USGS, 1989.

- Lapo, K., Freundorfer, A., Pfister, L., Schneider, J., Selker, J., and Thomas, C.: Distributed observations of wind direction using microstructures attached to actively heated fiber-optic cables, 13, 1563–1573, <https://doi.org/10.5194/amt-13-1563-2020>, 2020.
- 1160 Lautz, L. K.: Impacts of nonideal field conditions on vertical water velocity estimates from streambed temperature time series, *Water Resources Research*, 46, <https://doi.org/10.1029/2009WR007917>, 2010.
- Le Lay, H., Thomas, Z., Rouault, F., Pichelin, P., and Moatar, F.: Characterization of Diffuse Groundwater Inflows into Stream Water (Part II: Quantifying Groundwater Inflows by Coupling FO-DTS and Vertical Flow Velocities), *Water*, 11, 2430, <https://doi.org/10.3390/w11122430>, 2019a.
- 1165 Le Lay, H., Thomas, Z., Rouault, F., Pichelin, P., and Moatar, F.: Characterization of Diffuse Groundwater Inflows into Streamwater (Part I: Spatial and Temporal Mapping Framework Based on Fiber Optic Distributed Temperature Sensing), *Water*, 11, 2389, <https://doi.org/10.3390/w11112389>, 2019b.
- Liao, F., Cardenas, M. B., Ferencz, S. B., Chen, X., and Wang, G.: Tracing Bank Storage and Hyporheic Exchange Dynamics Using ²²²Rn: Virtual and Field Tests and Comparison With Other Tracers, *Water Resources Research*, 57, e2020WR028960, <https://doi.org/10.1029/2020WR028960>, 2021.
- 1170 Lowry, C. S., Walker, J. F., Hunt, R. J., and Anderson, M. P.: Identifying spatial variability of groundwater discharge in a wetland stream using a distributed temperature sensor, *Water Resour. Res.*, 43, W10408, <https://doi.org/10.1029/2007WR006145>, 2007.
- Mamer, E. A. and Lowry, C. S.: Locating and quantifying spatially distributed groundwater/surface water interactions using temperature signals with paired fiber-optic cables, *Water Resour. Res.*, 49, 7670–7680, <https://doi.org/10.1002/2013WR014235>, 2013.
- Martin, C.: Mécanismes hydrologiques et hydrochimiques impliqués dans les variations saisonnières des teneurs en nitrate dans les bassins versants agricoles. Approche expérimentale et modélisation, phdthesis, Université Rennes 1, 2003.
- 1180 Martin, C., Molénat, J., Gascuel-Oudou, C., Vouillamoz, J.-M., Robain, H., Ruiz, L., Faucheux, M., and Aquilina, L.: Modelling the effect of physical and chemical characteristics of shallow aquifers on water and nitrate transport in small agricultural catchments, *Journal of Hydrology*, 326, 25–42, <https://doi.org/10.1016/j.jhydrol.2005.10.040>, 2006.
- Matheswaran, K., Blemmer, M., Rosbjerg, D., and Boegh, E.: Seasonal variations in groundwater upwelling zones in a Danish lowland stream analyzed using Distributed Temperature Sensing (DTS), *Hydrol. Process.*, 28, 1422–1435, <https://doi.org/10.1002/hyp.9690>, 2014.
- 1185 Moridnejad, M., Cameron, S., Shamseldin, A. Y., Verhagen, F., Moore, C., Melville, B. W., and Ward, N. D.: Stream Temperature Modeling and Fiber Optic Temperature Sensing to Characterize Groundwater Discharge, *Groundwater*, 58, 661–673, <https://doi.org/10.1111/gwat.12938>, 2020.
- Munn, J. D., Maldaner, C. H., Coleman, T. I., and Parker, B. L.: Measuring Fracture Flow Changes in a Bedrock Aquifer Due to Open Hole and Pumped Conditions Using Active Distributed Temperature Sensing, *Water Resources Research*, 56, e2020WR027229, <https://doi.org/10.1029/2020WR027229>, 2020.
- 1190 Munz, M. and Schmidt, C.: Estimation of vertical water fluxes from temperature time series by the inverse numerical computer program FLUX-BOT, *Hydrol. Process.*, 31, 2713–2724, <https://doi.org/10.1002/hyp.11198>, 2017.

- 1195 Perzmaier, S., Aufleger, M., and Conrad, M.: Distributed fiber optic temperature measurements in hydraulic engineering: Prospects of the heat-up method, in: Proceedings of a Workshop on Dam Safety Problems and Solutions, 72nd ICOLD Annual Meeting, Seoul, South Korea. 16–22 May 2004, 2004.
- [van Ramshorst, J. G. V., Coenders-Gerrits, M., Schilperoort, B., van de Wiel, B. J. H., Izett, J. G., Selker, J. S., Higgins, C. W., Savenije, H. H. G., and van de Giesen, N. C.: Revisiting wind speed measurements using actively heated fiber optics: a wind tunnel study, 13, 5423–5439, https://doi.org/10.5194/amt-13-5423-2020, 2020.](https://doi.org/10.5194/amt-13-5423-2020)
- 1200 Read, T., Bour, O., Selker, J. S., Bense, V. F., Borgne, T. L., Hochreutener, R., and Lavenant, N.: Active-distributed temperature sensing to continuously quantify vertical flow in boreholes, *Water Resources Research*, 50, 3706–3713, <https://doi.org/10.1002/2014WR015273>, 2014.
- Read, T., Bense, V. F., Hochreutener, R., Bour, O., Le Borgne, T., Lavenant, N., and Selker, J. S.: Thermal-plume fibre optic tracking (T-POT) test for flow velocity measurement in groundwater boreholes, 4, 197–202, <https://doi.org/10.5194/gi-4-197-2015>, 2015.
- 1205 Reeves, J. and Hatch, C. E.: Impacts of three-dimensional nonuniform flow on quantification of groundwater-surface water interactions using heat as a tracer, *Water Resources Research*, 52, 6851–6866, <https://doi.org/10.1002/2016WR018841>, 2016.
- Rosenberry, D. O., Briggs, M. A., Delin, G., and Hare, D. K.: Combined use of thermal methods and seepage meters to efficiently locate, quantify, and monitor focused groundwater discharge to a sand-bed stream, *Water Resour. Res.*, 52, 4486–4503, <https://doi.org/10.1002/2016WR018808>, 2016.
- Rosenberry, D. O., Duque, C., and Lee, D. R.: History and evolution of seepage meters for quantifying flow between groundwater and surface water: Part 1 – Freshwater settings, *Earth-Science Reviews*, 204, 103167, <https://doi.org/10.1016/j.earscirev.2020.103167>, 2020.
- 1215 Ruiz, L., Abiven, S., Durand, P., Martin, C., Vertes, F., and Beaujouan, V.: Effect on nitrate concentration in stream water of agricultural practices in small catchments in Brittany : I. Annual nitrogen budgets, *Hydrol. Earth Syst. Sci.*, 6, 497–505, 2002.
- Sayde, C., Thomas, C. K., Wagner, J., and Selker, J.: High-resolution wind speed measurements using actively heated fiber optics, *Geophys. Res. Lett.*, 42, 10064–10073, <https://doi.org/10.1002/2015GL066729>, 2015.
- 1220 SEAFOM: Measurement Specification for Distributed Temperature Sensing (SEAFOM-MSP-01), <http://www.seafom.com/>, 2010.
- Sebok, E. and Müller, S.: The effect of sediment thermal conductivity on vertical groundwater flux estimates, 23, 3305–3317, <https://doi.org/10.5194/hess-23-3305-2019>, 2019.
- 1225 Sebok, E., Duque, C., Kazmierczak, J., Engesgaard, P., Nilsson, B., Karan, S., and Frandsen, M.: High-resolution distributed temperature sensing to detect seasonal groundwater discharge into Lake Vaeng, Denmark, *Water Resour. Res.*, 49, 5355–5368, <https://doi.org/10.1002/wrcr.20436>, 2013.
- Sebok, E., Duque, C., Engesgaard, P., and Boegh, E.: Application of Distributed Temperature Sensing for coupled mapping of sedimentation processes and spatio-temporal variability of groundwater discharge in soft-bedded streams, *Hydrological Processes*, 29, 3408–3422, <https://doi.org/10.1002/hyp.10455>, 2015.

- 1230 Selker, F. and Selker, J. S.: Investigating Water Movement Within and Near Wells Using Active Point Heating and Fiber Optic Distributed Temperature Sensing, 18, <https://doi.org/10.3390/s18041023>, 2018.
- Selker, J. S., Thevenaz, L., Huwald, H., Mallet, A., Luxemburg, W., de Giesen, N. van, Stejskal, M., Zeman, J., Westhoff, M., and Parlange, M. B.: Distributed fiber-optic temperature sensing for hydrologic systems, *Water Resour. Res.*, 42, W12202, <https://doi.org/10.1029/2006WR005326>, 2006a.
- 1235 Selker, J. S., van de Giesen, N., Westhoff, M., Luxemburg, W., and Parlange, M. B.: Fiber optics opens window on stream dynamics, *Geophys. Res. Lett.*, 33, L24401, <https://doi.org/10.1029/2006GL027979>, 2006b.
- Shanafield, M., Banks, E. W., Arkwright, J. W., and Hausner, M. B.: Fiber-Optic Sensing for Environmental Applications: Where We Have Come From and What Is Possible, *Water Resources Research*, 54, 8552–8557, <https://doi.org/10.1029/2018WR022768>, 2018.
- 1240 Simon, N. and Bour, O.: An ADTS Toolbox for automatically interpreting Active Distributed Temperature Sensing measurements, Submitted.
- Simon, N., Bour, O., Lavenant, N., Porel, G., Nauleau, B., Pouladi, B., and Longuevergne, L.: A Comparison of Different Methods to Estimate the Effective Spatial Resolution of FO-DTS Measurements Achieved during Sandbox Experiments, 20, <https://doi.org/10.3390/s20020570>, 2020.
- 1245 Simon, N., Bour, O., Lavenant, N., Porel, G., Nauleau, B., Pouladi, B., Longuevergne, L., and Crave, A.: Numerical and Experimental Validation of the Applicability of Active-DTS Experiments to Estimate Thermal Conductivity and Groundwater Flux in Porous Media, *Water Resources Research*, 57, e2020WR028078, <https://doi.org/10.1029/2020WR028078>, 2021.
- 1250 Singh, T., Wu, L., Gomez-Velez, J. D., Lewandowski, J., Hannah, D. M., and Krause, S.: Dynamic Hyporheic Zones: Exploring the Role of Peak Flow Events on Bedform-Induced Hyporheic Exchange, *Water Resources Research*, 55, 218–235, <https://doi.org/10.1029/2018WR022993>, 2019.
- Slater, L. D., Ntarlagiannis, D., Day-Lewis, F. D., Mwakanyamale, K., Versteeg, R. J., Ward, A., Strickland, C., Johnson, C. D., and Lane, J. W.: Use of electrical imaging and distributed temperature sensing methods to characterize surface water-groundwater exchange regulating uranium transport at the Hanford 300 Area, Washington, *Water Resour. Res.*, 46, W10533, <https://doi.org/10.1029/2010WR009110>, 2010.
- 1255 Sophocleous, M.: Interactions between groundwater and surface water: the state of the science, *Hydrogeol. J.*, 10, 52–67, <https://doi.org/10.1007/s10040-001-0170-8>, 2002.
- Stallman, W.: Steady One-Dimensional Fluid Flow in a Semi-Infinite Porous Medium With Sinusoidal Surface Temperature, 2821 pp., <https://doi.org/10.1029/JZ070i012p02821>, 1965.
- 1260 Stauffer, F., Bayer, P., Blum, P., Molina Giraldo, N., and Kinzelbach, W.: Thermal Use of Shallow Groundwater, <https://doi.org/10.1201/b16239>, 2013.
- Stonedahl, S. H., Harvey, J. W., Wörman, A., Salehin, M., and Packman, A. I.: A multiscale model for integrating hyporheic exchange from ripples to meanders, *Water Resources Research*, 46, <https://doi.org/10.1029/2009WR008865>, 2010.
- Su, H., Tian, S., Kang, Y., Xie, W., and Chen, J.: Monitoring water seepage velocity in dikes using distributed optical fiber temperature sensors, *Automation in Construction*, 76, 71–84, <https://doi.org/10.1016/j.autcon.2017.01.013>, 2017.

- 1265 des Tombe, B. F., Bakker, M., Smits, F., Schaars, F., and van der Made, K.-J.: Estimation of the Variation in Specific Discharge Over Large Depth Using Distributed Temperature Sensing (DTS) Measurements of the Heat Pulse Response, *Water Resources Research*, 55, 811–826, <https://doi.org/10.1029/2018WR024171>, 2019.
- Tonina, D. and Buffington, J. M.: Effects of stream discharge, alluvial depth and bar amplitude on hyporheic flow in pool-riffle channels, *Water Resour. Res.*, 47, W08508, <https://doi.org/10.1029/2010WR009140>, 2011.
- 1270 Tóth, J.: A theoretical analysis of groundwater flow in small drainage basins, *Journal of Geophysical Research (1896-1977)*, 68, 4795–4812, <https://doi.org/10.1029/JZ068i016p04795>, 1963.
- Trauth, N. and Fleckenstein, J. H.: Single discharge events increase reactive efficiency of the hyporheic zone, *Water Resources Research*, 53, 779–798, <https://doi.org/10.1002/2016WR019488>, 2017.
- 1275 Tyler, S. W., Selker, J. S., Hausner, M. B., Hatch, C. E., Torgersen, T., Thodal, C. E., and Schladow, S. G.: Environmental temperature sensing using Raman spectra DTS fiber-optic methods, *Water Resour. Res.*, 45, W00D23, <https://doi.org/10.1029/2008WR007052>, 2009.
- Ukil, A., Braendle, H., and Krippner, P.: Distributed Temperature Sensing: Review of Technology and Applications, *IEEE Sensors Journal - IEEE SENS J*, 12, 885–892, <https://doi.org/10.1109/JSEN.2011.2162060>, 2012.
- 1280 Unland, N., Cartwright, I., Anderson, M., Rau, G., Reed, J., Gilfedder, B., Atkinson, A., and Hofmann, H.: Investigating the spatio-temporal variability in groundwater and surface water interactions: A multi-technique approach, *Hydrology and Earth System Sciences*, 17, 3437–3453, <https://doi.org/10.5194/hess-17-3437-2013>, 2013.
- del Val, L., Carrera, J., Pool, M., Martínez, L., Casanovas, C., Bour, O., and Folch, A.: Heat Dissipation Test With Fiber-Optic Distributed Temperature Sensing to Estimate Groundwater Flux, *Water Resources Research*, 57, e2020WR027228, <https://doi.org/10.1029/2020WR027228>, 2021.
- 1285 Varli, D. and Yilmaz, K.: A Multi-Scale Approach for Improved Characterization of Surface Water—Groundwater Interactions: Integrating Thermal Remote Sensing and in-Stream Measurements, *Water*, 10, 854, <https://doi.org/10.3390/w10070854>, 2018.
- Webb, B. W., Hannah, D. M., Moore, R. D., Brown, L. E., and Nobilis, F.: Recent advances in stream and river temperature research, *Hydrol. Process.*, 22, 902–918, <https://doi.org/10.1002/hyp.6994>, 2008.
- 1290 Westhoff, M. C., Savenije, H. H. G., Luxemburg, W. M. J., Stelling, G. S., van de Giesen, N. C., Selker, J. S., Pfister, L., and Uhlenbrook, S.: A distributed stream temperature model using high resolution temperature observations, *Hydrol. Earth Syst. Sci.*, 11, 1469–1480, 2007.
- Westhoff, M. C., Gooseff, M. N., Bogaard, T. A., and Savenije, H. H. G.: Quantifying hyporheic exchange at high spatial resolution using natural temperature variations along a first-order stream, *Water Resour. Res.*, 47, W10508, <https://doi.org/10.1029/2010WR009767>, 2011.
- 1295 Winter, T., Harvey, J., Franke, O., and Alley, W.: Ground water and surface water a single resource, *U.S. Geol. Surv. Circ.*, 1139, 1998.
- 1300 Winter, T. C.: The Role of Ground Water in Generating Streamflow in Headwater Areas and in Maintaining Base Flow1, *JAWRA Journal of the American Water Resources Association*, 43, 15–25, <https://doi.org/10.1111/j.1752-1688.2007.00003.x>, 2007.

Woessner, W. W.: Stream and fluvial plain ground water interactions: Rescaling hydrogeologic thought, *Ground Water*, 38, 423–429, <https://doi.org/10.1111/j.1745-6584.2000.tb00228.x>, 2000.