

# Event controls on intermittent streamflow in a temperate climate

Nils Hinrich Kaplan<sup>1</sup>, Theresa Blume<sup>2</sup>, Markus Weiler<sup>1</sup>

<sup>1</sup>Hydrology, Faculty of Environment and Natural Resources, University of Freiburg, 79098 Freiburg, Germany

<sup>2</sup>Hydrology, Helmholtz Centre Potsdam, GFZ German Research Centre for Geosciences, 14473 Potsdam, Germany

5 *Correspondence to:* Nils H. Kaplan (nils.kaplan@hydrology.uni-freiburg.de)

**Abstract.** Intermittent streams represent a substantial part of the worldwide total stream network and their occurrence is expected to increase due to climate change. Thus, it is of high relevance to provide detailed information of the temporal and spatial controls of streamflow intermittency to support management decisions. This study presents an event-based analysis of streamflow responses in intermittent streams in a meso-scale catchment with a temperate climate. According to the streamflow 10 responses, precipitation events were classified into flow or no-flow classes. Response controls like precipitation, soil moisture, and temperature were used as predictors in a random forest model to identify the temporally changing factors that explain temporal controls of streamflow intermittency at the event-scale. Soil moisture was revealed as the most important predictor in the catchment, but the However, different patterns of predictor importance were found among varied among the three dominant geologies in the catchment. Streamflow responses in the slate geology were controlled by soil moisture in the shallow 15 and deep soil layers, while streamflow in the marl geology was primarily controlled by the soil moisture in the upper soil layer. Streamflow responses in catchments covering underlain by both marls and sandstone were dependent on soil moisture whereas streamflow in the only catchment with a pure sandstone geology depended on precipitation characteristics. In both all the slate and marl geology catchments, streamflow intermittency also showed a relationship with seasonal fluctuations of varied also with soil temperature, which is probably as a proxy-variable of for seasonal changes in evapotranspiration as well as an 20 indicator of freezing conditions.

## 1. Introduction

The scientific literature contains a variety of terms and definitions to define the different degrees of streamflow intermittency for streams that cease to flow during certain parts of the year, including temporary, ephemeral, seasonal and episodic streams, 25 and intermittent rivers , which are all characterised by ceasing flow during certain periods of the year (Uys and O'Keeffe, 1997; Costigan et al., 2016; Datry et al., 2017; Fritz et al. 2020). The stream network changes its spatial extent with the wetting and drying of these intermittent and ephemeral reaches. Even larger perennial reaches rivers are becoming expected to shift to intermittent streamflow as a result of climate change and the numbers are expected to increase in the future (Datry et al., 30 2014; Reynolds et al., 2015). Management of these transforming perennial reaches and current intermittent streams can adapt if controls of streamflow intermittency are better understood. In numerous studies, climate, geology, soil, topography, and

land use ~~were have been~~ identified as major spatial controls of streamflow intermittency (Olson and Brouillette, 2006; Reynolds et al., 2015; Trancoso et al., 2016; Costigan et al., 2016; Zimmer and McGlynn, 2017; Ward et al., 2018; Jaeger et al., 2019; Gutiérrez-Jurado et al., 2019; 2021; Prancevic and Kirchner, 2019; Kaplan et al., 2020a). The temporal dynamics of ~~runoff streamflow~~ were shown to result from fluctuating contributions of ~~base groundwater~~ flow and storm flow depending on 5 the antecedent wetness state of the catchment (e.g. Zehe et al., 2007, Zimmermann et al., 2014; Jaeger et al., 2019). ~~Since Horton (1933) first described the infiltration excess overland flow, later followed by the description of shallow subsurface stormflow (Hewlett, 1961; Tsukamoto, 1961; Weyman 1973) and saturation excess overland flow (Dunne and Black, 1970; Dunne et al., 1975), these three dominant processes were identified to control storm flow generation. At the hillslope and catchment scale, antecedent moisture conditions and storm size were identified as key controls of streamflow response (James and Roulet, 2009). Storm flow is frequently mentioned as the predominant source of runoff in ephemeral reaches (e.g. Boulton et al., 2017; Zimmer and McGlynn, 2017), whereas runoff in intermittent streams is dominantly driven by the seasonal fluctuations of the near surface groundwater table (e.g. Uys and O'keeffe, 1997; Sophocleous. 2002; Goodrich et al., 2018; Fritz et al., 2020). This study follows the definition of Busch et al. (2020) who define intermittent rivers as "a non-perennial river or stream with a considerable connection to the groundwater table, having variable cycles of wetting and flow cessation, and with flow that is sustained longer than a single storm event. These waterways are hydrologically gaining the majority of the time when considering long term flow patterns". Accordingly, ephemeral streams are defined as "a type of non-perennial river or stream without a considerable groundwater connection that flows for a short period of time, typically only after precipitation events. These waterways are hydrologically losing the majority of the time when considering long term flow patterns" (Busch et al., 2020). Storm flow is frequently mentioned as the predominant source of streamflow in ephemeral reaches (e.g. Boulton et al., 2017; Zimmer and McGlynn, 2017), whereas streamflow in intermittent streams is dominantly driven by the seasonal fluctuations of the near-surface groundwater table (e.g. Uys and O'keeffe, 1997; Sophocleous. 2002; Goodrich et al., 2018; Fritz et al., 2020).~~

Although extensive research on storm flow generation at the hillslope and reach scale, as well as baseflow contributions to perennial streams has been conducted, there are still few studies on the ~~temporal dynamic~~ controls on ~~the presence of flow in~~ 25 ~~the ephemeral and intermittent reaches (James and Roulet, 2009; Zimmer and McGlynn, 2017). In recent years, an increasing pool of low cost sensor technology has been developed to monitor the presence and duration of streamflow at multiple sites (Blasch et al., 2002; Goulsbra et al., 2009; Bhamjee and Lindsay, 2011; Bhamjee et al., 2016; Jensen et al., 2019; Kaplan et al., 2019). From the new opportunities provided by these sensors, a growing number of studies emerged which focused on investigating the controls of streamflow intermittency (e.g. Jaeger and Olden, 2012; Zimmermann et al., 2014; Jensen et al., 2019; Prancevic et al., 2019; Kaplan et al., 2020a). These studies of intermittent streams on controls of intermittency~~ can be roughly categorised into four ~~types scales~~: (1) ~~continental scale studies based on discharge measurements (Reynolds et al., 2015; Eng et al., 2016; Trancoso et al., 2016; Jaeger et al., 2019)~~ continental scale studies based on datasets from environmental agencies, which are usually not specifically dedicated to intermittent streams (Reynolds et al., 2015; Eng et al., 2016; Trancoso et al., 2016; Jaeger et al., 2019), (2) ~~(nested) catchment scale studies based on wet/dry mapping of the stream~~

network (Godsey and Kirchner, 2014; Sando and Blasch, 2015; Shaw, 2016; Goodrich et al., 2018; Jensen et al. 2017, 2018) (nested) catchment scale studies which often rely on a limited number of stream mapping campaigns (Godsey and Kirchner, 2014; Sando and Blasch, 2015; Shaw, 2016; Goodrich et al., 2018; Jensen et al. 2017, 2018), (3) single sites or the hillslope scale studies based on conventional discharge measurements (Sidle et al., 1995, Ries et al., 2017, Moreno-de-las-Heras et al., 2020) (Sidle et al., 1995, Ries et al., 2017, Moreno de las Heras et al., 2020), and (4) the recently emerging (multi)-catchment

5 scale studies that are based on continuous observations measurements of stream flow presence and absence with low-cost sensors (i.e. temperature, electric conductivity or flow-sensors and time-lapse cameras) at multiple locations along the stream which that are specifically aimed at monitoring the intermittent stream network (Jaeger and Olden 2012; Zimmermann et al. 2014; Zimmer and McGlynn, 2017; Jensen et al. 2019, Kaplan et al., 2020a).

10 The continental scale studies are based on datasets from environmental agencies, which are usually not specifically dedicated to intermittent streams (Reynolds et al., 2015; Eng et al., 2016; Trancoso et al., 2016; Jaeger et al., 2019). The first type (continental scale) These studies of streamflow intermittency studies commonly uses statistical models to predict intermittency at the large continental to regional scale and tries try to incorporate the dynamic climatic controls at coarse temporal resolution such as mean or total annual precipitation (Reynolds et al., 2015; Trancoso et al., 2016; Jaeger et al., 2019), annual

15 evapotranspiration (Trancoso et al., 2016), snowpack persistence from e.g. March to July/August or share of total precipitation in form of snow contribution of total annual precipitation in form of snow (Reynolds et al., 2015; Sando and Blasch, 2015; Jaeger et al., 2019), as well as measures like the annual average number of days of measurable precipitation (Reynolds et al., 2015), dryness or seasonality index (Trancoso et al., 2016), or streamflow indices like zero flow days (Eng et al., 2016). These

20 rather static climatic predictors are used to identify the likelihood of the stream network being spatially intermittent (Reynolds et al., 2015; Trancoso et al., 2016; Jaeger et al., 2019) or to identify long-term changes of streamflow intermittency under a changing climate (Eng et al., 2016). Reynolds et al. (2015) found a generally poor agreement of single climate predictors explaining zero-flow days in the Upper Colorado River Basin and emphasise the importance of interplay between composite of precipitation and temperature to predict zero-flow days. They also highlight the high correlation of the Palmer Draught Severity Index with the degree of stream intermittency. Eng et al. (2016) identify different types of intermittent streams in the

25 USA based on the climatic seasonality that was in some cases overwritten by the geographical layout of the catchments (e.g. local geology). They found intermittency in fall-to-winter primarily caused by precipitation storage in form of snow and ice while streamflow starts again with the onset of snowmelt and sustained only by the stored snow, while summer-to-winter intermittency was mainly caused by a periods of low precipitation coinciding with maximum potential evaporation. Precipitation events with amounts similar to those that were not able to initiate flow during the summer-to-winter streamflow

30 intermittency were able to cause flow events later in the year when soil moisture content was higher due to antecedent precipitation events. Non-seasonal intermittent streams mainly appeared in regions with high variability of precipitation and large water deficits caused by evapotranspiration (Eng et al., 2016). Jaeger et al. (2019) present a regional scale model approach for the Pacific Northwest of the USA and found total annual precipitation, minimum annual temperature and the percent forest cover as the most important predictors for flow permanence, while submodels for specific regions highlight the importance of

evapotranspiration during the dryer months. The regional variation of intermittency on continental scale in eastern Australia could be best described by the dryness index (Budyko, 1974) and photosynthetically active radiation (fPAR), while soil properties had an significant effect on streamflow intermittency at the regional scale (Trancoso et al., 2016).

The (nested) catchment scale studies which often rely on a limited number of stream wet/dry mapping campaigns of the stream network (Godsey and Kirchner, 2014; Sando and Blasch, 2015; Shaw, 2016; Goodrich et al., 2018; Jensen et al. 2017, 2018;

5 Durighetto et al., 2020) The second type of studies with nested catchments These uses the data from mapping campaigns is used to validated models that predict to predict the channel network dynamics of the wetted channel network at. Predictors used in these models vary from the catchment scale based on observed discharge (Godsey and Kirchner, 2014; Jensen et al., 2017) or,

10 the recession rate at the catchment outlet as predictors (Shaw, 2016), or to by modelling the dynamic stream network with groundwater recharge data (Goodrich et al., 2018). Godsey and Kirchner (2014) identify total flow length of the drainage

network in four California headwater catchments explained by a power-law functions of streamflow with very similar log-log slopes for all catchments. However, drainage network extent does not necessarily correspond to the timing of streamflow recession as shown by Shaw (2016) for a headwater catchment in the state of New York. He noticed the presence of seeps at the channel head of multiple subchannels that were contributing to flow even when the lower reaches ceased to flow. This

15 suggests that multiple local water tables devlop due to the structure of subsurface features (geological layering, bedrock fractures) and contribute to channel outflow at the seeps (Shaw, 2016). The importance of geology on the occurrence of intermittent streamflow is also shown in other climatic settings (Buttle et al., 2012; Jensen et al., 2017; Durighetto et al., 2020). Rainfall timing and intensity were good predictors of stream network dynamics in an Alpine headwater catchment, whereas evapotranspiration had little predictive power (Durighetto et al., 2020).

20 In hillslope scale studies of the third type at the hillslope scale, streamflow is usually measured continuously with conventional streamflow gauges at a single site or in nested sub-catchments and hillslopes (Sidle et al., 1995, Ries et al., 2017, Moreno-de-las-Heras et al., 2020), where intermittent streamflow is detected by zero flow observations. The streamflow dynamics are typically analysed in combination with high-temporal resolution soil moisture data (Penna et al., 2011; Ries et al., 2017; Zimmer and McGlynn, 2017), local shallow groundwater measurements (Zimmer and McGlynn, 2017; Sidle et al., 1995), and trench

25 subsurface flow observations at a trench (Sidle et al., 1995), as well as with high-resolution local precipitation data. These studies aim towards a separation of streamflow into to distinguish between streamflow contributions from of Hortonian overland flow (HOF), saturation excess overland flow (SEOF) or subsurface storm flow (SSF) and groundwater contributions at the event scale. The dependency of runoff initiation on thresholds of antecedent soil moisture at 10-30cm depth was demonstrated for several climates, topographies and land use characteristics (James and Roulet, 2009; Penna et al., 2011).

30 Penna et al. (2011) found no indication for SOF on the hillslopes and conclude that hillslope contribution to streamflow were primarily SSF. However, the saturated zones from the riparian expanded towards the hillslopes with increasing wetness, which made them hydrologically active. Ries et al. (2017) showed for Mediterranean ephemeral streams that event precipitation sums below 50mm lead to streamflow fed by HOF. Above this threshold they found streamflow primarily explained by bedrock permeability, soil water storage and rainfall intensity which control the timing of SOF. The importance of storage variability

was also addressed by Zimmer and McGlynn (2017), who found seasonally distinct flow paths depending on the catchment storage state. These seasonal fluctuation of catchment storage were driven by changes in evapotranspiration. During events with low antecedent storage shallow, perched, transient groundwater at the upper hillslope contributed to streamflow with SOF after a period of HOF at the beginning of the event. In more saturated conditions the deeper groundwater provided 5 baseflow before and after an event and all eventflow was SOF. During this wet state of the system also the stream network extended to its maximum length including zero-order hollows. The understanding of streamflow intermittency controls and drainage network connectivity at the continental, headwater catchment and hillslope-scale have been addressed by the different types of studies described above, but studies of intermittency in meso-scale catchments and for temperate climates still remains scarce.

10 The fourth type of Some of the recent studies is are based on streamflow duration data captured by newly developed sensor technology, such as electric conductivity (EC), temperature- and self-made flow-detection-sensors, monitoring multiple sites or time-lapse cameras along the stream network (Jaeger and Olden 2012; Zimmermann et al. 2014; Bhamjee et al., 2016, Zimmer and McGlynn, 2017; Jensen et al. 2019, Kaplan et al., 2020a, Warix et al., 2021). These studies evolved from research which was initially strongly focused on the validation evaluation of the capability of these new sensor technologies by 15 comparing timeseries of precipitation inputs to sensor responses (e.g. Bhamjee and Lindsay, 2011; Bhamjee et al., 2016). The temporal dynamics of the longitudinal connectivity and the streamflow continuity in the stream network was analysed based on the temporal high and spatially coarse (2 km spacing) resolution data of streamflow presence and absence through a comparison of the obtained streamflow data and network dynamics with precipitation data (Jaeger and Olden, 2012, Bhamjee et al., 2016). Jaeger and Olden (2012) found that positioning of streams in the channel network (headwater vs. lower parts) 20 had a higher explanatory power than geology to differentiate between perennial and non-perennial streams. Recent studies have broadened these initial approaches with to event-based analyses and the inclusion of additional measures by including the antecedent precipitation index (API) for timespans between 1 and 128 days to capture the antecedent wetness state of the catchment and precipitation measures like rainfall amount, intensity and duration (Zimmermann et al., 2014; Jensen et al., 2019). These studies also had a lower sensor spacing of 5 and 40 meters. Jensen et al. (2019) investigated the link between 25 peak runoff discharge at the catchment outlet and the maximum wetted fraction of the stream network during an precipitation events with principal component analysis. They find found that 60% of the variance was explained by the antecedent wetness proxy of 7 to 30 days antecedent precipitation prior to the a precipitation events (a proxy for catchment wetness) and an additional 16% by the event precipitation. Zimmermann et al. (2014) modeled the connectivity of the drainage network at the event scale using as predictors precipitation characteristics using a predictor set comprising precipitation characteristics such 30 as (ie. event duration, maximum precipitation intensity, and total rainfall) as well as the antecedent precipitation index (API) as surrogate for the antecedent wetness of the system. Zimmermann et al. (2014). Connectivity of the drainage network was defined as the total active streamlength devided by the maximum length of the channel network (Zimmermann et al., 2014). They identified total rainfall and maximum precipitation intensity as the major controls and the long-term antecedent wetness (API including 128 days prior to the event) as a minor control of the drainage network connectivity. Warix et al. (2021) found

a poor correlation between groundwater residence times and seasonal flow permanence in a semi-arid catchments in southwestern Idaho that are underlain by volcanics, basalt and latite. They observed continuous streamflow at some reaches with seasonally stable groundwater inputs. The seasonal flow permanence in these catchments showed a high correlation with topographic metrics (contributing area, slope, topographic wetness index), but groundwater and topography only explained 5 half of the observed variability in streamflow intermittency.

Although controls of intermittency at the continental, headwater catchment and hillslope scale are well represented by the different types of studies described above, studies of intermittency in meso-scale catchments and for temperate climates remain scarce.

With this study we aim to close this the research gap of temporally variable drivers of intermittent streams in temperate climates 10 and diverse geologies. We benefit from a large dataset of observations on the presence or absence of flow binary streamflow monitoring (Kaplan et al., 2019), high-resolution precipitation (Neuper and Ehret, 2019), and soil moisture and temperature data (Zehe et al., 2014; Demand et al., 2019; Mälicke et al., 2020) collected in the meso-scale Attert catchment. These data was collected and processed in the framework of the research project “Catchments As Organized Systems” (German Research Foundation (DFG), Research Unit FOR 1598). In a previous study, The three distinct main geologies in the catchment were 15 identified as major static spatial controls of streamflow intermittency (Kaplan et al., 2020a). We now take this a step further and evaluate Thus, in this study, the influence relationship between of geological parent material geology on and the temporal controls dynamic predictors of streamflow intermittency is evaluated. Following the approaches of Zimmermann et al. (2014) and Jensen et al. (2019), we present an event-based analysis of precipitation and the corresponding reactions of streamflow 20 responses. Similar to their approaches, measures of antecedent and event precipitation and precipitation event characteristics measures are considered. However we furthermore also include but, additionally, soil moisture and soil temperature are utilised in a random forest modelling approach. We aim to answer the following questions: (1) which types of rainfall events trigger a runoff reactions streamflow response in intermittent streams and which do not, (2) what are the main dynamic controls/predictors of streamflow streamflow responses reactions in intermittent streams, and (3) are the controls/predictors of intermittent streamflow dependent on the geological setting of the catchment?


## 25 2. Research area

The Attert catchment is located in the mid-western part of Luxembourg, with a minor area located in Belgium, and has a catchment area of 247 km<sup>2</sup> at the outlet at Useldange (Hellebrand et al., 2008). The geological setting comprises of three dominant geologies. Devonian slate is the dominant bedrock in the northern part of the catchment in the Luxembourg Ardennes, the central part consists of Keuper marls, and the southern part of the Jurassic Luxembourg Sandstone-sandstone 30 formation (Fig. 1, Martínez-Carreras et al., 2012). The topographical layout of the catchment shows the elevation is highest altitudes in the Ardennes and Luxembourg sandstone formation at 549 m a.s.l. and 440 m a.s.l., respectively, while the catchment outlet in Useldange has an altitude of 245 m a.s.l. (Martínez-Carreras et al., 2012; Pfister et al., 2018).

The Luxembourg Ardennes are characterised by steep inclined valleys with forested hillslopes (ca. 15-25°) and plateaus with agricultural land use. The central part of the catchment consists of gentle hills (slope ca. 3°) that are mainly used for agriculture, grassland, and forest. The ~~s~~Sandstone areas are characterised by steep hillslopes ~~which that~~ are dominantly forested and in the lower part used as grassland and for agriculture (Kaplan et al., 2020a). Soils in the Attert catchment are linked to lithology, 5 land cover and land use (Cammeraat et al., 2018). Soils in the slate geology are dominated by stony silty soils, while the soils in Keuper ~~m~~Marls ~~comprise have~~ silty clayey texture and the Luxembourg ~~s~~Sandstone region is largely covered by sandy and silty soils (Müller et al., 2016). On slate the soil depth to the weathered C horizon is usually below 50cm, while the soils on the marls are more heterogenous with a clay rich layer (> 50 % clay) starting between 20 and 50cm depth (Demand et al., 2019). The soil depth to the unweathered bedrock can reach more than 2 m in Sandstone and Bt horizons are often deeper than 10 1m (Sprenger et al., 2015).

The climate is classified as pluvial oceanic (Wrede et al., 2014). Annual precipitation amounts vary ~~in space~~ from ~~1000 mm~~ in the Ardennes in the north-west with 1000 mm to roughly 800 mm in the Luxembourg ~~s~~Sandstone in the south-east (Pfister et al., 2017). The ~~mean seasonal variability~~mean monthly precipitation ranges ~~between~~from 70 mm in August and September, to 100 mm in December until February (Wrede et al., 2014). ~~However, e~~Evapotranspiration fluctuates significantly ~~with the seasonal changes of temperature~~ and is higher during summer (82 mm) observed in July when the average temperature is 17°C and lowest in winter ~~with monthly evapotranspiration rates of (13 mm) in December when the average temperature is 0°C in December (average temperature 0°C) and highest in July with monthly evapotranspiration of 82 mm (average temperature 17°C;~~ (Wrede et al., 2014). These seasonal fluctuations in precipitation and evapotranspiration ~~control influence~~ the runoff regime, resulting in high flows during the winter season, while low flows occur in the summer months (Wrede et al., 2014).

20 Spatial differences in the seasonal ~~variance between summer and winter variation in runoff streamflow were shown to be strongly dependent~~ on the bedrock permeability which controls the storage mixing and release of water in the Attert catchment (Pfister et al., 2017). The sandstone geology in the Attert catchment provides the largest total and active storage (defined as the maximum interannual variability in catchment storage) compared to marl and slate (Pfister et al., 2017). Thus, the sandstone geology has the lowest proportion of active storage compared to total storage (15-26%), while this relationship shows higher 25 values in the slate (69-82%) and marls (69%). Closeby marly catchments showed a up to 100% of total storage was active storage on the Keuper marls (Pfister et al., 2017). Kaplan et al. (2020) ~~have~~ demonstrated the importance of bedrock permeability and soil hydraulic conductivity ~~as drivers offor~~ streamflow intermittency in the Attert catchment. They also highlighted the potential of streamflow alteration through either artificial surface and subsurface drainage, dams and trenches in the agricultural areas as reported by Schaich et al. (2011) ~~and~~ the return ~~of waste water flows~~ from ~~water~~wastewater 30 treatment plants on the plateaus of the Ardennes. The drainage density of the perennial streamnetwork derived from the topographic map of the region (Le Gouvernement du Grand-Duché de Luxembourg, 2009) is 1.4 km/km<sup>2</sup> and 0.6 for intermittent streams. The drainage density varies among the three geologies with 0.8 km/km<sup>2</sup> for perennial streams and 0.2 km/km<sup>2</sup> for intermittent on sandstone, 0.7 km/km<sup>2</sup> for perennial streams and 0.3 km/km<sup>2</sup> for intermittent streams on marls and 1.0 km/km<sup>2</sup> for perennial streams and 1.0 km/km<sup>2</sup> for intermittent streams on slate.



5 **Figure 1: Geology and stream network of the Attert catchment and for the locations of streamflow monitoring at artificial channels, forest roads and natural channels, as well as the sites of as well as soil moisture and temperature measurements. Sites with**

10 **intermittent flow were used for analyses in this study, while the sites with perennial flow have been were used as pour point sites to delineate the catchment boundaries for the eight sub-catchments “Noumtemerbaach”, “Colpach”, “Foulshchterbaach”, “Beschruederbaach”, “Schammicht”, “Hei”, “Pall” and “Schwebec” (catchment boundaries derived from a 15m DEM). The map sections show the more intensively instrumented areas in each predominant geology: slate (blue frame), marls (red frame) and sandstone (green frame). Selected sites in the sandstone geology are labeled with their ID (e.g. SA1) as reference used in in the discussion. The geological map from 1947 was provided by the Geological Service of Luxembourg (adapted from Kaplan et al., 2019), the stream network was derived from a topographic map (Le Gouvernement du Grand-Duché de Luxembourg, 2009).**

### 3. Methods

#### 3.1 Data acquisition

We used areal precipitation estimations derived from weather radar data combined with data from six disdrometers, two micro rain radars, regular rain gauges, and weather radar reflectivity using an information theory approach. The precipitation data has a temporal resolution of one hour and was extracted from a gridded dataset with 100m resolution at the locations of the gauging sites (data from Neuper and Ehret (2019)). The precipitation data at the sites was thereafter used to calculate precipitation averages for eight sub catchments for a catchment scale analysis of precipitation events.

We used the intermittency dataset described in Kaplan et al. (2019), which is a binary data set of streamflow presence or absence for 182 gauging sites in the Attert catchment. The gauging sites in this dataset were predominantly located at natural streams, but also comprise smaller channels at ditches and at three sites in the sandstone erosion channels on forest roads. Gauging sites at artificial channels were mainly located in the less natural landscape on the marl geology (see Fig. 1). Thus, the definition of “an intermittent stream” in this study is a natural or artificial channel with occasional surface runoff. The data were collected using various sensors, including time-lapse imagery (Dörr Snapshot Mini 5.0), electric conductivity sensors (Onset HOBO Pendant waterproof temperature and light data logger), and conventional gauges (METER/Decagon CTD pressure transducers in stilling wells at weirs). Time lapse imagery was predominantly installed at sites that were expected to have intermittent streamflow, EC-sensors at locations with expected perennial flow and conventional gauges at catchment outlets as well as close to the soil moisture measurement sites (Kaplan et al., 2019). Therefore, a subset of gauges with intermittent streamflow was selected comprising the sites which were monitored by time-lapse camera (C) and conventional gauges (CG). Intermittent streamflow is here defined for the observed streamflow at gauging sites showing at least a period of one hour with no flow. The subset was split into further subsets according to the dominant geology (marl, sandstone, slate) of the upslope contributing area. For the different geological regions these subsets comprised 22 gauging sites in slate, 23 in marl and nine in sandstone (See Figure 1 and Figure 3). The contributing area derived from GIS-analysis using a DEM (15m resolution) of all intermittent streamflow gauging sites (Kaplan et al., 2020a) is shown in figure S1 in the supplement. The streamflow data was aggregated from the original temporal resolution of 15 min to one-hour intervals by calculating the mean of the binary values and rounding (threshold: 0.5) the resulting value to one digit, i.e. back to binary values (0/1).

Soil moisture and soil temperature were measured at 45 sites (hereafter “soilmoisture sites”) distributed across the catchment with each site having three soil profiles with providing a total of 135 soil profiles (Figure 1Figure 1). Three In each profile, combined soil moisture and temperature sensors were installed in each soil profile at depths of 10, 30 and 50cm below the surface and recorded data have a temporal resolution measured with a temporal resolution of five minutes. The soil moisture sites were located in each of the three main geologies in the catchment in either forest or grassland (see Table 1). Combined, these two land cover classes represent the predominant land cover in the catchment (Kaplan et al. 2019). In the marls and slate regions, agricultural land use has a substantial share of 41% and 42%. However, in agricultural land use permanent sensor installations are not feasible and the natural stream network is heavily altered by artificial drainage systems. The soil moisture

sites were chosen for the best possible representation of the combined land use and geology at a variety of slope gradients, expositions (North, South) and position on the slope (top, mid, valley) and thus, were arranged along different hillslope transects, covering different positions on the hillslope, different slopes and aspects. The soil moisture sites were part of a sensor cluster network (e.g. climate variables, sap flow, local groundwater) that was initially set up to experimentally test the concept of elementary functional units as proposed by Zehe et al. (2014). Eleven sites were located in the marl region, 22 sites were in the slate region and 12 sites in the Sandstone with a total of 33, 66 and 36 soil moisture measurement profiles per geology, respectively (Table 1). Although some land cover classes are not covered by the sites, the assumption was made that the sites represent the general soil moisture dynamics in the three geologies. The first measurements started in March 2012 to October 2013 and ended in February 2018. In this study, a subset of the data for the period from 01.04.2016 until 17.07.2017 was used, which because it has the largest overlap between the other data sources used in this study. The initially we installed sensors were 5TE capacitance sensors (Decagon Devices/METER Environment, USA). but Due to sensor malfunction, 43 sensors were replaced with SMT100 (TRUEBNER GmbH, Neustadt, Germany) and nine sensors with GS3 sensors (Decagon Devices/METER Environment, USA) in 2016. The data was visually checked and offsets between soil moisture measurements after sensor replacement were detected in four timeseries. Additionally, seven timeseries with strong artifacts sensor noise and/or extensive plateaus periods of constant soil moisture values were identified and removed from the dataset. Measured absolute values of the soil moisture values were normalised to the minimum and maximum of the time series for each sensor to be independent from avoid possible bias among sensors. Soil moisture dynamics of at each geology is are represented by the mean of the normalised time series for all sites located in the corresponding geology. The soil moisture data was aggregated to hourly means. The averaged soil moisture was assigned to the streamflow gauging sites based on the main geology at the site.

Neuper and Ehret (2019) estimated precipitation from weather radar data combined with data from six disdrometers, two micro rain radars, regular rain gauges, and weather radar reflectivity (locations see Fig. 1) using an information theory approach. This precipitation dataset was used in this study due to its high temporal (1 hour) and spatial (100 m) resolution. The precipitation data from this gridded dataset was used at the locations of the intermittent stream gauging sites. The precipitation data at the gauging sites was thereafter used to calculate precipitation averages for the eight sub-catchments (Fig. 1) for a catchment scale analysis of precipitation events. Averages of the precipitation time series were calculated as the average of precipitation at all stream gauging sites within the catchment without further spatial interpolation.

Table 1: Number of soil moisture and temperature measurement sites for each geology and land use. Each site has three soil profiles with soil moisture and temperature sensors in 10, 30 and 50 cm depth.

Geology	Land use	
	Forest	Grassland
Slate	16	7
Marls	5	6

The measurement sites were located in each of the three main geologies in the catchment with land cover of either forest or grassland. Combined, these two land cover classes represent the predominant land cover in the catchment (Kaplan et al. 2019).

5 However, in the marls and slate regions, agricultural land use has a substantial share of 41% and 42%. Sites were mainly arranged along different hillslope transects, covering different positions on the hillslope, different slopes and aspects. Eleven sites were located in the Marl region, 22 sites were in the Slate region and 12 sites in the Sandstone with a total of 33, 66 and 36 profiles per geology, respectively. Although some land cover classes are not covered by the distribution of the sites, the assumption was made that the sites represent the general soil moisture dynamics in the three geologies.

10 We used the intermittency dataset described in Kaplan et al. (2019), which is a binary data set of streamflow presence and absence. This data was monitored at 182 sites in the Attert catchment using various sensors, including time lapse imagery, electric conductivity sensors, and conventional gauges. Due to the temporal resolution of the precipitation data, the streamflow data was aggregated from the original temporal resolution of 15 min to one-hour intervals by calculating the mean of the binary values and rounding the resulting value to one digit, i.e. back to binary values (0/1). A subset of gauges was selected from the 15 sites which were monitored by time lapse camera (C) and conventional gauges (CG) and showed intermittent streamflow, here defined as sites showing at least one period of no flow. The subset was split into further subsets according to the dominant geology (Marl, Sandstone, Slate) of the upslope contributing area. For the different geological regions, 22 sites were identified in slate, 23 in marl and nine in sandstone (See Figure 1 and Figure 3). The contributing area of all sites is shown in figure S6 in the supplement.

20

### 3.2 Definition of precipitation events and runoff streamflow response

Precipitation (P)-Event analysis was carried out for the time period from 01.04.2016 to 17.07.2017, which covers the period which covers the maximum temporal overlap of the available data. In accordance with Wiekenkamp et al. (2016) and Demand et al. (2019), a precipitation event was defined as having a minimum precipitation sum of 1 mm. The required time period of 25 no precipitation to separate two successive events was defined as three hours (3h), after testing a set of four different values (3, 6, 12 and 24 hours without rain, Penna et al. 2011; Penna et al. 2015; Demand et al., 2019). The maximum time between the start of a precipitation event and the start of the runoff streamflow response was limited to 48 hours after testing, with both the 24 and 48 hours as thresholds (Figure 2Figure 2). In the case of multiple precipitation events within 48 hours before the runoff streamflow response, the latest precipitation event before the runoff streamflow response was chosen as the initialising 30 precipitation event. The following characteristics were calculated for each event: Cumulative Antecedent Precipitation (CAP) within 24h before the precipitation event and the seven and 14 day antecedent precipitation index (API) defined as:

$$API = \sum_{t=-1}^{-i} P_t k^{-t}$$

(1)

with  $P_t$  as the precipitation during time step  $t$ ,  $i$  the number of antecedent time steps (7 or 14 days) and  $k$  as a decay constant (Kohler and Linsley, 1951). Values for the decay constant usually range between 0.80 and 0.98 (Heggen, 2001). A lower range value of 0.85 was used in this study. This value was chosen to minimise the correlation between the API and CAP measure.

Additional event characteristic measures included the maximum precipitation intensity ( $P_{\max}$ ), mean precipitation intensity ( $P_{\text{mean}}$ ), total sum of precipitation ( $P_{\text{sum}}$ ), duration of the precipitation event ( $P_D$ ), and the normalised soil moisture (averaged per geology) in-at 10 cm ( $\theta_{10}$ , Fig. S24), 30 cm ( $\theta_{30}$ ) and 50 cm ( $\theta_{50}$ ) depth at the first and last time step of the precipitation event, as well as the minimum, mean, and maximum soil moisture. Soil moisture data was assigned to gauging sites based on the predominant geology in the catchments of the gauging sites, and We also used the minimal soil temperature during the precipitation event ( $T_{\min}$ , Fig. S23) as a proxy of seasonal changes in temperature and the corresponding fluctuations in evapotranspiration (Wrede et al., 2014) as well as a potential identifier of freezing conditions. The soil temperature was used due to its lower daily variability and lower dependency on the microclimate at the site which allows for a better representation of an average temperature for each geology.




Figure 2: Precipitation events are defined with-by a minimum precipitation sum of 1mm and a minimum of separated by at least three hours on no precipitation between separate precipitation events ( $\Delta T > 3h$ ). Flow events are assigned to the last precipitation event within 48 hours before the flow initialisation ( $\Delta T < 48h$ ). Precipitation events are classified as either triggering or maintaining events for the corresponding runoff-streamflow events and summarised in the “flow class” or classified as “no-flow” in cases without streamflow response within 48 hours after the precipitation event.

Events were classified according to the presence or absence of flow at the stream gauges. Precipitation events which triggered the initialisation of a runoff streamflow response within 48h after the event – according to the definition above – were classified as “flow initialising”. Precipitation events which have no flow responses are classified as “no-flow”. Those precipitation events that are classified neither as flow initialising nor as no-flow response and happen during flow events, are classified as “flow maintaining”. For the purpose of modelling runoff streamflow responses, the two classes flow-initialising and flow-maintaining were merged into one response class named “flow” (Figure 2), because we assume from the event data that preconditions for flow initiation and maintenance are highly similar. The event definition and runoff streamflow classification were carried out both for rainfall measured locally in the grid cell at the stream flow monitoring sites as well as catchment averaged rainfall for each of the eight sub-catchments “Pall”, “Beschruederbaach”, “Hei”, “Schammicht” (marl geology), “Schwebich” (sandstone geology), “Noutemerbaach”, “Colpach” and “Foulschterbaach” (slate geology, Figure 1). Table 2: Number of gauging sites per sub-catchment, precipitation sums and the percentage of catchment geology. Missing values to 100% for the geology represent minor geologies and alluvium.). At the sub-catchment scale all precipitation events for a sub-catchment are based on the same spatially averaged catchment precipitation data and thus the precipitation events for each sub-catchment are based on the same spatially averaged catchment precipitation data and are thus identical for all sites within a sub-catchment. The spatial aggregation of precipitation data is possible due to the very high correlation between the precipitation measured at the single sites in the sub-catchments (fig. S44). Thus, for each site responses to the precipitation event can be “flow”, “no-flow” or “NA” in cases of larger data gaps in the flow data.

Table 2: Number of gauging sites per sub-catchment, precipitation sums and the percentage of catchment geology. Missing values to 100% for the geology represent minor geologies and alluvium.

Catchment	Number of sites per catchment & geology			Catchment geology [%]			
	Slate	Marls	Sandstone	Slate	Marls	Sandstone	P <sub>sum</sub> [mm]
Foulschterbaach	5	0	0	86	0	14	687
Colpach	14	1	0	81	15	1	634
Noutemerbaach	3	0	0	98	0	0	637
Pall	0	7	1	0	64	22	592
Beschruederbaach	0	4	0	0	73	16	593
Hei	0	2	0	0	93	0	645
Schammicht	0	8	0	0	100	0	603
Schwebich	0	0	9	0	47	41	573

### 3.3 Random forest model for intermittency

In general, a random forest (RF) model contains an ensemble of regression trees. Predictions of a RF model are based on the averaged predictions of all trees in the forest (Breiman, 2001). A RF model is created by bootstrapping several random samples from the original data and fitting a single classification tree to a bootstrapped sample (Out Of Bag samples (OBB)). Validation

5 of the OBB classification is performed with the data remaining outside of the bootstrap sample (OBB). This data is used for independent predictions for each OBB based tree. From these predictions the OBB error rate is calculated over all trees to provide a measure of the predictive performance of the model (Breiman, 2001).

Multiple RF models were used to model the classes of ~~runoff-streamflow~~ responses (flow or no-flow) as a function of the predictor variables (Table 3~~Table 1~~). Table 4~~2~~ includes the selected predictor variables. Only ~~the~~ maximum soil moisture ~~at~~

10 ~~10cm and 50cm depth~~ ( $\theta_{10}$  and  $\theta_{50}$ ) were selected due to high correlations (Kendall's  $\tau > 0.8$ ) among the other soil moisture predictors:  ~~$\theta_{10}, \theta_{30}, \theta_{50}$  as initial, end, minimum and mean soil moisture during a precipitation event in the different depths,~~

~~(see Fig. S5~~3~~). The correlation among the predictors in table 1 was low among most of the predictors only the soil moisture measures in the two depths and API with the two periods had higher correlations for most sites (see Fig. S6 – S8).~~ For each

site an individual random forest model with the ~~site-specific~~ dataset containing the classification of ~~runoff-streamflow~~

15 responses and the corresponding predictor variables was set up. This is necessary as the number of ~~complete precipitation events with streamflow responses~~ ~~s~~ varies considerably among the sites ~~due to gaps in the streamflow observations and the variance of precipitation patterns and timing in the catchment~~ (40 to 119 ~~precipitation~~ events, see Fig. 3 and Tab. S1~~3~~, S2~~4~~,

S3~~5~~) and hence a common dataset is not feasible. However, despite the varying number of precipitation events, ~~the importance of the temporal controls predictors on the streamflow reactions responses to the precipitation events~~ can still be analysed for

20 each site.

The dataset was split into a training dataset (70% of the data) for model fitting and a test dataset (30% of the data) for model validation. Several training datasets showed highly unequal numbers ~~between the classes of~~ flow or no-flow ~~responses~~, which would lead to an overfitting ~~by of~~ the model to the class with a higher number of ~~events responses~~. Thus, the two methods of data resampling from the R-package ROSE (Random Over-Sampling Examples, Lunardon et al., 2014) were used to avoid the

25 overrepresentation of one class. ~~The oversampling function from the ROSE package performs simple oversampling with replacement from the minority class until the specified sample size N is reached. With the option both of the ROSE package the minority class is oversampled with replacement and the majority class is undersampled without replacement until the sample size N is reached. The resampling is carried out with the probability for the minority class given by the value p (in this study 0.5; Lunardon et al., 2014).~~ Oversampling was set up to generate a dataset holding twice the number of observations of

30 the overrepresented class, whereas the over-/under-sampling ~~was aiming~~ aims for the 1.5-fold number of all events contained in the original dataset. ~~In this way Thus,~~ three different datasets were tested as training data: a) the original training dataset, b) a resampled training dataset ~~after~~ using the oversampling function of ROSE and c) a resampled training dataset using the over-/under-sampling (called "both") function of ROSE. ~~The oversampling function from the ROSE package performs simple~~

oversampling with replacement from the minority class until the specified sample size N is reached. With the option *both* of the ROSE package the minority class is oversampled with replacement and the majority class is undersampled without replacement until the sample size N is reached. The resampling is carried out with the probability for the minority class given by the value p (in this study 0.5; Lunardon et al., 2014). Oversampling was set up to generate a dataset holding twice the number of observations of the overrepresented class, whereas the over /under sampling was aiming for the 1.5 fold number of all events contained in the original dataset. In a first run, the three different datasets for each site were used to fit three random forest models which were validated with the corresponding test dataset. The random forest models were run with the R-package “randomForest” (Liaw and Wiener 2002) with a randomly chosen seed set to 123 to ensure reproducibility of the statistical model, the number of trees was set to 2500 after reaching stable OOB error rates around this threshold and three predictor variables tried at each split as the default value. The confusionMatrix function from the R-package “caret” (Kuhn et al., 2015) was used for validation. The confusion matrix compares the modelled with the observed values and allows e.g. to quantify the percentage of correct and false classified classes and overall accuracy of model results as total correct classifications. Only models with an averaged sensitivity (correct flow predictions / total flow observations) and specificity (correct no-flow predictions / total no-flow observations ) of > 0.5 and a sum of both measures higher than one were considered for further analysis. The dataset with the highest averaged sensitivity/specificity at one site was chosen for each site for further analysis for this site. In cases where multiple datasets for one a site had the same values of sensitivity/ specificity, the original data was chosen over the resampled datasets. The model accuracy (total correctly classified events / total number of modelled events) was used as an additional indicator for the assessment of the model quality but was not used during the evaluation process. With one the selected dataset selected for each sites, one model was run for each site and the mean decrease Gini (MDG) calculated was obtained only for each those models based on the selected datasets by using the “importance” function from the R-package “randomForest”. The MDG is calculated for each predictor variable X in the random forest model. For each decision tree in the model, the summed-up decrease of the node impurity measure (the Gini index) is weighted by the proportion of data points reaching the nodes that are split by the specific predictor variable. These decreases in Gini index for single trees are averaged over all trees in the forest to obtain the mean decrease Gini (Louppe et al., 2013). A higher mean decrease in Gini indicates higher variable importance. The MDG is recognised as a robust measure to rank the importance of the predictor variables of the random forest models (Calle and Urrea, 2010).

**Table 34: Predictor variables used in the random forest model selection.**

Predictor	Abbreviation
Mean event precipitation intensity [mm/h]	P <sub>mean</sub>
Event precipitation sum [mm]	P <sub>sum</sub>
Maximum Event precipitation intensity [mm/h]	P <sub>max</sub>
Cumulative antecedent precipitation (24h) [mm]	CAP
Antecedent precipitation index (7 days) [mm]	API_7

Antecedent precipitation index (14 days) [mm]	API_14
Maximum normalized soil moisture <del>at</del> 10 cm depth <del>in</del> during the event [-]	$\theta_{10}$
Maximum normalized soil moisture <del>at</del> 50 cm depth <del>in</del> during the event [-]	$\theta_{50}$
Duration of the precipitation event [h]	$P_D$
Minimum soil temperature during an event [°C]	$T_{\min}$

## 4. Results


### 4.1 Event analysis

#### 4.1.1 Event analysis based on local rainfall characteristics

5 For the 22 sites in the slate geology, between 64 and 119 events were identified ([Figure 3](#)[Figure 3](#), Tab. S1). The differences in detected precipitation events ~~are were~~ caused by the natural spatial variability of precipitation ~~events~~ but also by ~~missing~~ data ~~gaps~~ in the ~~runoff streamflow~~ response dataset. For 17 sites, the precipitation events lead predominantly to flow responses, while no-flow responses ~~are were~~ only dominant for five sites ([Figure 3](#)[Figure 3](#)). The share of no-flow responses at the sites ranged ~~ds~~ from ~~0-3%~~ to 89%. ~~This means that for one site – although showing having~~ intermittent flow – no precipitation event

10 was observed which ~~caused had~~ a no-flow ~~response even tr~~. For the 23 sites located in the marl geology, between 51 and 114 events were identified. Twelve of these ~~sites show a higher number of had more~~ flow responses to precipitation ~~than no-flow responses~~, while eleven sites ~~have had~~ more no-flow responses (Tab. S2, [Figure 3](#)[Figure 3](#)). The ~~proportion percentage~~ of no-flow responses ~~compared to the total number of events~~ ranged ~~ds~~ between ~~0-14%~~ and 93%, ~~but for one site. This is due to one site without there were not~~ any detected no-flow response. The total number of precipitation events for the nine sites in the

15 sandstone geology varied ~~sd~~ between 40 and 110 (Tab. S3, [Figure 3](#)[Figure 3](#)). ~~These sites show There was a~~ nearly an equal split of sites with predominance in flow (5 sites) and no-flow (4 sites) responses. The proportion of no-flow responses to the total number of precipitation events ranged ~~ds~~ from 3 to 82 %. Generally, the number of flow ~~reactions responses~~ to precipitation events ~~are were~~ lower in the ~~marl sandstone~~ geology ([Figure 3](#)[Figure 3](#)).



**Figure 3:** Number of precipitation events having resulted in either a flow or no-flow response for the sites underlain by different reactions in the geologies: slate, marls, and sandstone. The average percentage of flow to no-flow responses per geology are 70,8 % to 29,2% in slate, 47,4% to 52,6% in marls, and 57,2 % to 42,8 % in sandstone.




Figure 4: Flow (blue x-axis labels) and no-flow (red labels) responses in the three geologies (slate, marls, sandstone) are shown with their (a) averaged maximum soil moisture in 10 cm and 50 cm depth during precipitation events, (b) the averaged minimum soil temperature in 10 cm depth during the precipitation event, (c) the precipitation measures P<sub>mean</sub> and P<sub>max</sub>, (d) the cumulative antecedent precipitation (CAP) and the cumulative event precipitation (P<sub>sum</sub>), (e) the 7 and 14-day antecedent precipitation index (API\_7 / API\_14) and (f) the duration of precipitation events (P<sub>D</sub>) as well as the time between initial precipitation and flow initiation ( $\Delta T_{P \text{ to } Q}$ ). One outlier of P<sub>mean</sub> (6.5 mm/h) in slate is not shown to enhance the readability of the plot by reducing the scale maximum. The boxes show the 25<sup>th</sup> and 75<sup>th</sup> percentile, outliers are marked if they reach values higher than 1.5 of the interquartile range from the box boundaries of quantiles Q1 and Q3. Significant differences (two sided t-test) between flow and no-flow responses for predictor values within a geology are marked with a star symbol.

The differences of the averaged values of the predictors at each site between flow and no-flow responses were tested with a two sided t-test separately for each geology. The results of the t-test show on average significantly ( $p < 0.05$ ) higher average soil moisture at sites during flow events responses compared to the no-flow events responses at all sites (Figure 4Figure 4a). The largest differences of soil moisture in both depths between flow and no-flow responses are observed in the marl 5 geology, with a mean  $\theta_{10}$  of 0.63 and  $\theta_{50}$  of 0.66 during flow conditions responses averaged over all sites and events compared to 0.38 ( $\theta_{10}$ ) and 0.44 ( $\theta_{50}$ ) during no-flow conditions responses (Figure 4Figure 4). The difference of in soil moisture values in were smallest for the sandstone are the lowest with  $\theta_{10}$  of 0.48 and  $\theta_{50}$  of 0.47 during flow responses and 0.35 and 0.36 respectively during no-flow conditions responses. Soil moisture of sites in the slate was slightly higher than in the sandstone with  $\theta_{10}$  of 0.52 and  $\theta_{50}$  of 0.55 during flow events responses and 0.37 in both depths ( $\theta_{10/50}$ ) during no-flow 10 events responses. In contrast to soil moisture, the averages for minimum soil temperature show no significant differences did not differ significantly between flow and no-flow events responses (Figure 4Figure 4). Also, the precipitation measures  $P_{\text{mean}}$ ,  $P_{\text{sum}}$  and  $P_{\text{max}}$  are very similar when comparing for flow and no-flow responses at sites within the slate and marl geologys (Figure 4Figure 4c). However, the t-test showed significantly higher values for  $P_{\text{sum}}$  and  $P_{\text{max}}$  for flow responses ( $P_{\text{sum}} = 6.4$  mm,  $P_{\text{max}} = 3$  mm/h) compared to no-flow responses ( $P_{\text{sum}} = 4.3$  mm,  $P_{\text{max}} = 2$  mm/h) are found in for the sandstone as well as 15 a significantly higher  $P_{\text{sum}}$  during flow responses ( $P_{\text{sum}} = 5.5$  mm) to than no-flow responses ( $P_{\text{sum}} = 4.6$  mm) in for the marl. The pre event precipitation measures show contrasting results: while the API\_7 and API\_14 varied significantly between flow and no-flow responses across all geologies, the 24 hour cumulative antecedent precipitation is was significantly higher for flow responses in marl ( $CAP_{\text{flow}} = 4.7$  mm,  $CAP_{\text{no-flow}} = 2.7$  mm) and sandstone ( $CAP_{\text{flow}} = 3.1$  mm,  $CAP_{\text{no-flow}} = 1.9$  mm) (Figure 4Figure 4d, e) compared to no-flow responses, whereas but the differences in the slate were not significant. The 20 duration of a precipitation event was not significantly different between shows no significant difference between flow or no-flow responses as they are very similar in most geologies despite a small increase of slightly longer precipitation duration for flow responses in the sandstone (Figure 4Figure 4f). However, there are noteworthy differences between geologies result in the lag between initiation of the precipitation events and the begin of the runoff streamflow response (Figure 4Figure 4f). The sites in Marl have the shortest, slate sites intermediate and sandstone sites the longest response times.

25

#### 4.1.2 Event analysis based on sub-catchment averaged rainfall characteristics

At the sub catchment scale all precipitation events for a sub catchment are based on the same spatially averaged catchment precipitation data and thus the precipitation events for each sub catchment are identical for all sites within a sub catchment. The spatial aggregation of precipitation data is possible due to the very high correlation between the precipitation measured at 30 the single sites in the sub catchments (fig. S4). Thus, for each site responses to the precipitation event can be "flow", "no-flow" or "NA" (No Data) in cases of larger data gaps in the flow data (Figure 5). The response data is shown in Figure 5 for the catchments "Pall", "Beschruederbaach", "Hei", "Schammicht" (Marls catchments depicted in grey), "Schwebich" (sandstone catchment depicted in green Sandstone), "Noutemerbaach", "Colpach" and "Foulschterbaach" (Slate catchments

depicted in blue) is shown in Figure 5. The mapped data reveals large differences in flow responses, even between catchments which that are located close to each other. The two small sub-catchments within the of the Hei catchment are prominent examples of two catchments with gauging sites that are were less than 500m apart but had which show very different shares of flow (eastern site: 56% ; western site: 15%) and no-flow responses (0.44%; 0.85%; (Figure 5Figure 5).

5




Figure 5: **Spatial distribution Maps** of the sites and their corresponding proportion of flow responses to event precipitation. The prevalent geology at the majority of the sites in each catchment is indicated by the colour of the catchment shape: blue = slate, grey = marls and green = sandstone. The dominant geology at the site does not always reflect the dominant geology of the entire catchment.

10




Figure 6: Event dynamics for each catchment ordered by their temporal succession. Catchment geology is colour coded in the header of the sub-plot (blue = slate, gray = marls, green = sandstone). The header also includes the number (n) of sites in the catchment. Each sub-plot consists of shows the mean event precipitation (top), soil moisture in 10 cm depth (mid) and the proportional share of sites in the catchment with the response categories “flow”, “no data” or “no-flow”. In cases of For sub-catchments having with sites in two different geologies, the soil moisture dynamics in-for each of the geologies are included in the corresponding plot shown. In addition, the events in the months February, March and April are highlighted with a blue background representing a period with a high number of sites in the Attert catchment showing with flow, whereas the months June, July and August highlighted with a gray background indicate a dry period. Specific events are highlighted with dashed lines and labeled with letters for reference. The colour of the header of the sub-plot represents the dominant geology (blue = slate, gray = marls, green = sandstone). The header also

5

10

includes the number (n) of sites in the catchment. Note Beware that the event numbers on the x-axis differ between the plots, i.e. Event #40 does not refer the same event across all sites.

The temporal succession of the events responses in the catchments, the precipitation as well as the soil moisture dynamics are

5 shown in Figure 6: The Colpach catchment hads more sites with no-flow reactionsresponses during precipitation events with  
low soil moisture compared to these precipitation events with higher soil moisture (Figure 6a). However, for few events with  
very high mean precipitation, all sites of the Colpach catchment hadve flow, econditions, mostly with a little delay. In the  
Foulschterbaach catchment all sites maintaineded flow for a first sequence of events, even with low soil moisture, while some of  
the sites fall dry during events with lower precipitation and intermediate soil moisture. Flow is-was regained at all sites when  
10 the normalised soil moisture reacheds a threshold of around 0.65. The Noumtemerbaach showeds a gradual decline of flowing  
sites with a corresponding decline in soil moisture. Also, in this catchment, a sequence of average precipitation intensity events  
but rising soil moisture of high mean precipitation intensity ledads to an-the activation of flow for all sites in the catchment  
(Figure 6: Figure 6:, Event# 80a). This behaviour  
15 Also precipitation events with high intensity during periods of lower  
normalised soil -moisture (<0.50) can be repeatedly found initiated for a few more two events streamflow reactions (Figure  
6c Events b and c) during the period of lower normalised soil moisture (<0.50). Subsequent events with soil moisture above  
that threshold led to are connected with the initiation of flow at all sites in the Noutemerbaach catchment. The Schammicht  
catchment is located in marl geology and monitored sites represent many smaller sub-catchments. Five series of precipitation  
events with high corresponding proportions of flowing streams can were be identified (Figure 6: Figure 6: Events g-h, i-j, k-l,  
m-n; o-p). Two of these sequences series with the most subsequent precipitation events triggering flow responses showed  
20 relatively high soil moisture values of higher than( >0.72 (Events# g-h, o-p1-16), while a third period is-was associated with  
some missing values and a very dynamic soil moisture, but successive events of larger higher mean precipitation compared to  
the average mean precipitation intensity in this catchment (Events# k-l-23-35). Further, two short series of precipitation events  
(Events#s 18- 20 and 42- 44i-j and m-n) of flow correspond to successive events of larger higher mean precipitation. It is  
worth noting that a single event of very high mean precipitation (60mm/h) does did not lead to flowing conditions in the  
25 complete at all sites in the catchment in times of when low soil moisture was low (Event# 94q). The temporal flow dynamics  
for the Beschruederbaach are were generally closely related to those observed at the Schammicht catchment, as both  
catchments are very close to each other and have a similar geologyle and land use setting (Figure 1Figure 4). The Hei  
catchment hads rarely flowing conditions at both monitored sites. These flow responses mostly corresponded to either  
comparably high mean event precipitation and/or high soil moisture (> 0.8, Figure 6: Figure 6:). The Pall catchment has one  
30 site in the Pall catchment was located in the sandstone region while all others are were situated in the marls (Figure 1Figure  
4). For this catchment, The share of sites without flow reactions in response to precipitation events is notably higher during  
times of lower soil moisture (Figure 6h Events# r-u, v-x 37-70, 85-110). However, in these dry periods, rapid flow activation  
was introduced by larger event precipitation is possible (e.g. Events# s-t 40-43 and #97w). Other periods with a higher number  
of sites having active flow responses are were linked to higher soil moisture values (higher than 0.73). In the Schwebich

catchment, the majority of the sites ~~are-were~~ located in the sandstone geology. Unfortunately, the share of “No-Data” observations ~~are-were~~ quite significant during the first third of the events (Figure 6: ~~Figure 6:~~). Nevertheless, ~~there was a~~ relation between higher soil moisture and a high proportion of sites with ~~flow flow seems to apply to for~~ the sites in the sandstone but with less clear indication ~~compared to the marl and slate geology~~. Notable ~~runoff streamflow~~ responses from the 5 majority of the streams in the catchment ~~occurred~~ at comparably low soil moisture but a higher mean precipitation intensity during events #36d, #53e and #96f.

## 4.2 Random forest model results

### 4.2.1 Site selection

10 ~~Not all models for all sites were able to meet~~ The evaluation criteria for a good model (sensitivity (correct flow predictions / total flow observations) and specificity (correct no-flow predictions / total no-flow observations)  $> 0.5$ ) were not met for all sites. ~~Thus, those sites were rejected excluded~~ to avoid the inclusion of results ~~of with~~ bad performing models in the further analysis. The site selection ~~is was~~ based on a combination of the evaluation criteria (specificity and sensitivity) during validation. ~~A site was selected for further analysis if the specificity and sensitivity was higher than 0.5 and the sum of both measures was higher than one. In the marl region models, For 20 out of 23 sites in the marl region did the models meet met~~ the evaluation criteria and had a mean model accuracy of 0.84 with a standard deviation of 0.10 (Figure 7~~Figure 7~~, Tab. S5-7). The ~~approved~~ sites were selected with datasets from all types of resampling methods (no resampling, over-sampling, over- and under-sampling). The three sites ~~which that~~ did not match the evaluation criteria were ~~among~~ the sites with the lowest number of observed precipitation events and had a notably unequal distribution of flow to no-flow responses (in case of site MA6, 15 even only flow responses). These sites ~~are-were~~ located in the Schammicht and Pall sub-catchments (Figure 8~~Figure 8~~). For ~~the sandstone models~~, four of nine sites ~~in the sandstone, the models did did~~ not meet the evaluation criteria, with either very high sensitivity and very low specificity, or vice versa (Figure 7~~Figure 7~~). ~~This also corresponds~~ These sites also had to an unequal distribution of the flow responses (Figure 3~~Figure 3~~). All of the sites in the sandstone geology ~~are-were~~ located ~~at on~~ very small reaches ~~or and three of them on~~ steep ~~logging tracks unpaved forest roads~~ on the hillslopes (Figure 8~~Figure 8~~). The 20 mean model accuracy over all sites that matched the evaluation criteria was 0.79 (standard deviation: 0.12). All sites in the sandstone geology ~~for which the models were acceptable had that qualified showed~~ the best results with the over- and under-sampling approach. Eight out of 22 sites in the slate geology were rejected from further analysis based on the model evaluation criteria (Figure 7~~Figure 7~~). After rejection of the unsuccessful models, the mean accuracy over all sites in the slate ~~reaches was~~ 25 0.90 with a standard deviation of 0.08. The rejected sites in the slate geology ~~are-were~~ distributed over all sub-catchments (~~Figure 8Figure 8~~). However, the Foulsharterbaach catchment had a ~~remarkably~~ high share of sites (3 out of 5) that did not meet the evaluation criteria. All of the rejected sites in the slate geology ~~haved~~ a ~~comparably~~ low number of no-flow responses 30 ~~compared to the other sites in slate~~ (Figure 3~~Figure 3 and 7~~). In the case of SL5 and SL10, ~~the~~ splitting of the dataset into

training and test data ~~was leading led~~ to zero samples of the no-flow class. For SL2 the ratio of 116:3 of flow to no-flow responses could not be compensated through the resampling of the data. Roughly two-thirds of the sites in the slate geology ~~that~~ selected for further analysis ~~showed had~~ better ~~results with model performance for~~ the resampled data.





Figure 7: Cumulative sensitivity and specificity of the random forest models at for the different sites using the three data samples original data (OD), oversampling dataset (OS), and over- and undersampling dataset (OUS). Sites that meet the selection criteria for a good model fit are indicated with coloured boxes corresponding to the dominant geology in the catchment (blue = slate, gray = marls, green = sandstone). Sites that didn't meet the selection criteria were discarded for further analysis are indicated with non-colored boxes.



**Figure 8: Sensitivity and specificity of the random forest models at the different sites in the sub-catchments (including the sites that did not fulfil the evaluation criteria). Both measures range from 0 to 1, thus the larger the proportion of the circle that is filled with colour, the better the model quality.**


5

#### 4.2.2 Predictor importance

The predictor importance at each site is was defined by the ranked mean decrease Gini measure of the predictors in the site-specific model. The rank of a model predictor shows the relative importance in relation to the other predictors in the model with 10 as the highest rank of the 10 predictors (Figure 9Figure 9). For the sites located in marl the soil moisture at 10 cm

10 depth is was by far the key predictor with the highest average rank (8.9) – being among the top three most important predictors for nearly all sites (Figure 9Figure 9). The soil moisture at 50 cm depth is was ranked as slightly less important with an average rank of 7.55, but is was also among the most important predictors for nearly allalmost of the sites. The API measures completed the highly important predictors with the long-term API<sub>14</sub> measure being on average the second most important predictor (rank

8.05) having a slightly higher importance than the API<sub>7</sub> measure. The highly top ranked predictors included soil moisture and API and hence represent either directly or indirectly the soil moisture conditions during the precipitation event. However, the correlations between the two API measures and between the two soil moisture were rather low (0.1 – 0.58) for the sites in marls, but high correlations were indicated within the two API measures API<sub>7</sub> and API<sub>14</sub> (0.78 – 0.86) as well as within the  
5 soil moisture predictors in the two depths (0.15 – 0.75). While the precipitation measures (P<sub>mean</sub>, P<sub>sum</sub>, P<sub>max</sub>) played only a minor role at for three-quarters of the marl sites, the cumulative antecedent precipitation was ranked as important for two-thirds of the sites. The comparably high lowest average rankss (6.15) and the a wide spre – of ranks (3 - 10) for the minimum soil temperature in the marl geology compared to the other two geologies (6.6 and 7.93) are remarkable – as is the low importance of the duration of a precipitation event (average rank 1.55), indicating that precipitation events of all duration were  
10 able to induce runoff responses in this geology. Sites in on slate have had similar patterns of predictor importance to sites those on in marl (Figure 9Figure 9). In contrast to the marl sites, in the slate geology the soil moisture at 50 cm depth has awas on average higher rankeding (8.93) than that at 10 cm depth (8.71). On average both predictors are were among the first two most important predictors for the majority of slate the sites on slate. Minimum soil temperature is was the third key predictor in the slate region with many two thirds of the sites having it between as the third and to first most important predictor. Short  
15 and long-term API had anwas on average intermediate rankeding in (API<sub>7</sub>: 5.5 and API<sub>14</sub>: 6.29) for the slate geology with a variability of the ranks in a lower to mid range (rank 1-8). Precipitation measures were among the second to fourth most important predictors (rank 8 and 9) only one for one third quater of the slate sites, while the duration of a precipitation event was not important for any sites in on slate (average rank 1.71). The sites in the sandstone geology showed a more diverse patterns of predictor importance (Figure 9Figure 9). Soil moisture at 10 cm and 50 cm is was also among the most important  
20 predictors for most of the sites in sandstone with ranks of nine and 10. In contrast to the other geologies +The precipitation sum is was very important for one site (rank 10) in the sandstone geology. but Additionally, the precipitation sum was still notably more more important for the other sites on sandstone compared to the sites in the other geologies being on average the third most important predictor in the sandstone geology., representing the third most important predictor in the sandstone geology. Furthermore, mean event precipitation rankeds high (rank 8) for two sites in the sandstone geology. Compared to the API<sub>14</sub>  
25 which was the only important antecedent precipitation measure at two sandstone sites, the API<sub>7</sub> and CAP haved lower rankings. The importance of minimum temperature has a much lower importance in the sandstone compared to was with a average rank of 6.6 in the mid range compared to the other geologies. One of the two sites on sandstone with higher importance ranks of precipitation duration (ranks 7 and 9) also showeds a higher importance of other event precipitation measures (P<sub>mean</sub>, P<sub>sum</sub>, P<sub>max</sub>) while these measures are were not important for the other site. For all other sites in the sandstone geology, the  
30 duration of the precipitation event plays a minor role was ranked low.



**Figure 9: Rank of the parameter importance of each model predictor at the different sites counted in each geology. The rank is colour-coded, with the highest rank in red representing the most important predictor and the lowest rank in blue representing the least important predictor. The average rank of a predictor in each geology is indicated at the top of each bar.**

5

## 5. Discussion

### 5.1 Factors affecting Controls of streamflow intermittency

Hydrological researchers identified three major controlling The three main runoff generation mechanisms of resulting in event runoff streamflow generation are: infiltration (Hortonian) overland flow, saturation excess overland flow and subsurface

10 stormflow (Sidle et al., 1995; Zimmermann et al., 2014). The drivers that are involved in these processes are always inputs of water to the system either in the form of precipitation rainfall or melt water (e.g. Horton, 1933; Weyman, 1973; Dunne and

Black, 1970; Sando and Blasch, 2015; Tolonen et al., 2019). The ability of the system to buffer the incoming precipitation is limited by the infiltration capacity, ~~the storage capacity the ability to channel subsurface storm flow~~, and the antecedent soil moisture (e.g. Tromp-van Meerveld and McDonnell, 2006; Bachmair and Weiler, 2014; Stewart et al., 2019; Gutierrez-Jurado et al., 2019; 2021; Warix et al., 2021).

5 The event analysis of ~~this~~ study reveals that the average soil moisture ~~at the sites in all geologies shows~~ was significantly different ~~between~~ for precipitation events ~~with that resulted in~~ flow, and ~~precipitation events those~~ without flow responses (Figure 4~~Figure 4~~). This was the case for the sites on all three geologies. Additionally, the antecedent precipitation (7 day and 14 day API) ~~was important for showed notable importance in~~ the marl and slate geologies. The high potential to distinguish the two classes of flow responses by soil moisture is confirmed by the ~~results high importance of the corresponding predictors~~ 10 ~~in of~~ the random forest models (Figure 9~~Figure 9~~). ~~The importance of soil moisture in the system is in line with the findings of Kaplan et al. (2020) who identified catchment area and curvature, which are surrogates of the topographic wetness index, as the two crucial predictors in the spatial model of streamflow intermittency.~~ The event analysis in this study indicates a ~~certain seasonal~~ timing (Figure 6~~Figure 6~~) and thresholds (Figure 4~~Figure 4~~) of soil moisture at which streamflow is initiated. Times of low or high soil moisture and respective responses of no-flow or flow roughly follow the seasonal fluctuations ~~in evapotranspiration~~. Thus, in the winter months with higher soil moisture, a succession of multiple precipitation events with flow ~~reactions~~ ~~responses~~ are more common than in the summer months with lower soil moisture (Figure 6~~Figure 6~~). Annual variations of ~~runoff streamflow~~ in temperate regions are usually explained by the seasonal fluctuations of evapotranspiration which affects the soil moisture conditions of the catchment (e.g. La Torre Torres et al., 2011; Penna et al., 2011, 2015; Trancoso et al., 2016; Zimmer and McGlynn, 2017). ~~The importance of those seasonal fluctuations on streamflow initiation in the Attert catchment is underlined by the lower precipitation (26 mm to 30 mm of average event precipitation sums) during the “wet” periods with higher soil moistures compared to the higher precipitation sum during the “dry” periods (43 mm to 50 mm of average event precipitation sums; see Figure 6).~~ The seasonal variations of soil moisture are visible in all geologies of the catchment. ~~This seasonality is more pronounced for the catchments on slate and marls, while in the sandstone half of the sites were dependent on soil moisture while the other half were dependent on the precipitation characteristics. The lower dependency 20 of flow responses on soil moisture at sites on sandstone potentially indicate that other sources like deeper storage, local and perched groundwater has a higher influence on the streamflow responses than in the other geologies. The prolonged supply of streamflow by local, perched groundwater tables on sandstone geologies above less permeable layers was shown to control streamflow intermittency in a Mediterranean (Gutiérrez-Jurado et al., 2019; 2021) and on slate in a subtropical, humid climate (Zimmer and McGlynn 2017). In contrast the large differences in soil moisture between flow and no-flow responses at sites 25 on marl as well as the larger volatility of active sites in catchments with marls indicate a faster saturation of the soil with quicker and shorter SOF responses.~~

30

Besides the seasonal ~~fluctuating soil moisture, due to temperature/evapotranspiration, dynamics variation~~, soil moisture can increase rapidly in reaction to precipitation events. These fast ~~increases in~~ soil moisture ~~reactions~~ ~~responses were supporting the initiation of~~ streamflow responses also during the dry periods. Streamflow responses to these dynamically increasing soil

moisture values were mainly observed for the marl sites (Figure 6). A majority of the sites in marl sub-catchment had streamflow responses during these short living phases of risen soil moisture, while the effect was less pronounced on slate and sandstone predominantly in the marl geology but also in weaker form in the other geologies (Figure 6). The importance of soil moisture in both soil depths in the marl geology is reflected by the results of the random forest model which ranks those predictors and the API the highest (Figure 9Figure 9). The importance of soil moisture in the system is in line with the findings of Kaplan et al. (2020) who identified catchment area and curvature, which are surrogates of the topographic wetness index, as the two crucial predictors in the spatial model of streamflow intermittency. Topography, hydraulic conductivity and transmissivity as well as the water storage capacity of a catchment defined by bedrock geology and soil type were identified as dominant predictors for streamflow timing and the spatial dynamics of the intermittent stream network in different climates and topographies (e.g. Tanaka et al., 2005; Jencso and McGlynn, 2011; Sando and Blasch, 2015; Ward et al., 2018; Prancevic and Kirchner, 2019; Gutiérrez-Jurado et al., 2019; 2021; Kaplan et al., 2020; Shanafield et al., 2020). The dependency of streamflow intermittency on seasonal dynamics of evapotranspiration as found in this study was also reported for a catchment with sub-tropical humid climate and rather homogenous precipitation sums and associated with the catchment storage state (Zimmer and McGlynn, 2017). These changes in catchment storage were reported to change the streamflow contributions from shallow, perched groundwater dominated runoff production during dryer periods with low storage states to deeper groundwater that was rising into the contributing soil layers at higher storage states.

The importance of the event precipitation measures ( $P_{\max}$ ,  $P_{\text{mean}}$ ,  $P_{\text{sum}}$ ,) that can play a major role for the establishment of hydrological connectivity (e.g. Bracken and Croke, 2007) was surprisingly low. This may result from the small share of precipitation events exceeding the infiltration capacity in all geologies of the catchment as found by (Demand et al., 2019) and thus limiting the probability for Hortonian overland flow. Gutierrez-Jurado et al. (2019) simulated intermittent streams on different soil types and demonstrated that HOF was the dominating streamflow contribution on sandy loam soils with low hydraulic conductivity. Soils with the lowest hydraulic conductivity in the Attert catchment located on marl, however the soils are very heterogeneous and higher effective hydraulic conductivity was observed in various studies (e.g. Demand et al., 2019; Kaplan et al., 2020). Strong influence of precipitation characteristics on the appearance of intermittent streamflow were also observed in humid tropical climate (Zimmermann et al.; 2014) or in arid climates (Ries et al., 2017) with large seasonal or spatial variability in event precipitation sums. This variability in precipitation is reflected by precipitation characteristic related predictors having a high explanatory power of streamflow initiations in these climates. In contrast, precipitation related predictors become less important in situations where strong influence of the fluctuations of soil moisture or groundwater inputs control saturated conditions and the associated SOF and SSF, because the high importance of predictors like groundwater, soil moisture and antecedent precipitation will superimpose the importance of precipitation (Wrede et al., 2014; Ward et al., 2018; Jensen et al., 2019; Gutierrez-Jurado et al., 2021).

Generally, the importance of precipitation event characteristics may also result from the definition of the precipitation event and the temporal resolution of the data. Zimmer and McGlynn (2014) identified the interannual variability of evapotranspiration as the major driver of stream network dynamics while they report variable storm intensity during a single

precipitation event period. In their study precipitation events are defined as two events separated by at least 12 hours and > 8 mm of precipitation while in this study the events need to be separated by 3 hours and had a minimum precipitation of 1 mm. This implicates that a single precipitation event in our study has potentially lower sums but would be potentially merged to one large event according to the definition of Zimmer and McGlynn (2014). This effect becomes even stronger in the study of Jensen et al. (2019) who separated precipitation events by a minimal period of 24 h without rain. They found 16% of the variance of stream network extend explained by precipitation characteristics. With our precipitation event definition, the variability between precipitation events may become less pronounced, but the assignment of a specific precipitation event to a streamflow response and the associated state of soil moisture at that time may have a more precise and thus, soil moisture becomes more relevant compared to the precipitation event characteristics. Event definitions that support prolonged periods of multiple precipitation events as one event hamper the identification of the actual precipitation that triggered the streamflow response. Thus, the characteristic of the precipitation event gains in relevance because it potentially has “pre-event precipitation” submerged within the actual event. This also means that pre-event saturation measures (e.g. API / soil moisture) close before the triggering precipitation event may become less relevant, as this information is partially included in the event precipitation of the entire period. Kaplan et al. (2020) identified bedrock geology and saturated soil conductivity as one of the major spatial controls of streamflow intermittency in the Attet catchment. This influence of geology and soil on the appearance of intermittency and on the dominant runoff processes was confirmed by other studies (e.g., Tanaka et al., 2005; Jeneso and McGlynn, 2011; Sando and Blasch, 2015; Gutiérrez Jurado et al., 2019; Pate et al., 2020). Thus, the temporal controls of streamflow intermittency are separately discussed for each of the dominant geologies in the following sections.

### 20 5.1.1 Factors affecting streamflow responses for sites on Intermittency controls in marl geology

The soils in the marl geology ~~were reported to~~ have the highest ~~flow hydraulic conductivity velocities of the geological regions~~ in the Attet catchment (Demand et al., 2019). However, the underlying marl geology is characterised by a low permeability (Wrede et al., 2014). Beiter et al. (2020) ~~analysed the interaction between precipitation events, local groundwater and streamflow responses in the sub-catchments Beschruederbaach and Schammicht, which are located in the marl geology (Figure 1).~~ They found that after a dry period ~~showed~~ strong transmissivity feedback ~~of event precipitation through the local groundwater to the streamflow response~~ ~~were possible after only few precipitation events that raised the groundwater level to a threshold level near the surface. Below that threshold the dynamics of groundwater and streamflow were less synchronised, after only a few precipitation events through shallow groundwater to the stream response in the sub catchments Beschruederbaach and Schammicht, which are located in the marl geology (Figure 1).~~ Under ~~For~~ lower antecedent ~~soil~~ moisture conditions, they found a change towards higher incidences of overland flow and runoff contributions through preferential subsurface flow paths during precipitation events. Also, Wrede et al. (2014) linked the fast responses of event water in the Wollefsbach catchment – a sub-catchment in the marl region of the Attet catchment – to lateral subsurface flow of pre-event water and contributions of event water through preferential pathways. This process is accompanied by saturation-

excess overland flow during periods of higher saturation (Wrede et al., 2014). They assume that the deeper groundwater table does not raise above the highly impermeable boundary layer even during the wet season, while the stream was ceasing flow during the dry season without major streamflow responses during storm events. Wrede et al. (2014) describe the streamflow responses on marls as flashy which also agrees to the fasted response times for the streamflow responses in the event analysis

5 (Figure 4f). During low catchment storage states a fast expansion of the stream network followed by a quick but lagging saturation of the upper soil as described by Jensen et al. (2019) may sustain short living streamflow responses during the dry period. In contrast, during the dormant season a perched saturated zone above the less permeable soil layer as described by Gutierrez-Juardo et al. (2019) may develops and sustains the streamflow in the intermittent streams. The findings of Demand et al. (2019) and Beiter et al. (2020), combined with the strong dependency of streamflow initiation by increased on soil

10 moisture as indicated by the random forest model, suggest that saturation excess overland flow and shallow subsurface stormflow are among the dominant processes controlling the streamflow responses in the marl geology. This finding is supported by the importance of the 14-day API, which indicates an increased probability of streamflow initiation and continuation following larger antecedent precipitation. Demand et al. (2019) also analysed precipitation events of a time period overlapping with the one in this study and found no events exceeding the infiltration capacity of the soil matrix at for sites

15 located in the forests. This finding is in accordance with the low importance of all precipitation measures in the models for sites located in the marl region, which were predominantly forested. This suggests, that in case the shallow storage system becomes saturated, smaller and larger precipitation events can trigger SOF and this hinders the random forest models to split the dataset based on the precipitation characteristics leading to the low importance of these predictors.

Soil temperature showed high importance in the random forest model for the majority of sites in the marl geology (Figure 20 9Figure 9). This underlines the dependency of flow initiation on the seasonal changes of temperature and evapotranspiration in the Attert catchment, which were also found in other temperate catchments (Wrede et al., 2014; Zimmer and McGlynn, 2017). Overall, the models showed a good ability to separate flow and no-flow responses with the random forest models dominated by soil moisture and temperature data, indicating shallow sub-surface storm flow and saturation excess overland flow in the marl geology.

25

### **5.1.2 Factors affecting streamflow responses on slate geology Intermittency controls in slate**

The most important model predictors in for the sites on the slate are soil moisture in the upper and the lower soil layer followed by temperature and the API measures, while precipitation related predictors play a minor role (Figure 9Figure 9). The soil moisture at 50 cm depth is slightly more important than the soil moisture at 10 cm depth at several of the sites. This can be 30 caused by the high fraction of preferential flow paths in the clay-rich soils as frequently found in the forested regions in the slate geology of the Attert catchment (Demand et al., 2019). This would allow event water to travel quickly into deeper soil layers and to trigger sub-surface storm flow. This hypothesis is supported by the higher mean soil moisture in 50cm depth compared to those in 10 cm depths at which flow and no-flow responses were separated by the random forest models at most

of the sites (Fig. S9). Additionally, slate bedrock is – as the layers of low permeability in marl – relatively impermeable but in contrast to those layers in marl the bedrock – soil interface in slate is rather fractured and soil depths to bedrock is deeper (>50cm, Demand et al., 2019). Runoff Previous studies in the Weierbach catchment – a sub-catchment of the Colpach catchment that also shows intermittent streamflow (Figure 1) highlighted the presence of a “fill and spill” mechanism of subsurface stormflow based on the isotopic signature of the streamflow and local groundwater observations (e.g., Wrede et al., 2014; Martínenz-Carreras, 2016; Beiter et al., 2020). responses in the Weierbach catchment – a sub catchment of the Colpach catchment (Figure 1) – support a “fill and spill” mechanism of subsurface stormflow (e.g., Wrede et al., 2014; Martínenz-Carreras, 2016; Beiter et al., 2020). Tromp van Meerveld and McDonnell (2006) explain This mechanism appears when depressions at the bedrock surface have to be filled until water spills over the bedrock relief (Tromp-van Meerveld and McDonnell, 2006). They present It leads to a distinct precipitation threshold that has to be reached to trigger strongly enhanced subsurface stormflow in their study area. For the Weierbach catchment, this mechanism was identified as inducing double peak runoff streamflow when the catchment storage state reaches a certain threshold during the dormant season or after intense precipitation events in the dry season (Martínenz-Carreras, 2016). The dependency of the streamflow responses on the seasonal variations of the temperature and evapotranspiration which are influencing the catchment storage state is also supported by the importance of temperature as a predictor in the random forest model. Single peak runoff streamflow was observed events occur below the threshold – which resulted from direct precipitation into the stream channel and saturation excess overland flow in the riparian areas (Martínenz-Carreras, 2016), but also partly by subsurface stormflow through macropores and fractures on the hillslopes which are connected to the saturated riparian areas (Angermann et al., 2017; Jackisch et al., 2017). This rather direct inputs to streamflow through the shallower soil layers during the dry season were connoted with hillslope contributions (Martínenz-Carreras, 2016). This may result in the importance of soil moisture in the upper soil layers (10cm depth) for the intermittent streams in this storage state. Double peak hydrographs showed a first peak of younger water fractions followed by a second, delayed peak with During the wet season, higher fractions of old water from activated catchment storage at the plateaus on top of the hillslopes which appeared as become active and contributes via subsurface stormflow and shallow groundwater reactions (Martínenz-Carreras, 2016; Schwab et al., 2017; Beiter et al., 2020). This shift from the dry to wet state of the system and the activation of flow through deeper soil layers may explain the higher importance of the soil moisture in 50 cm depth for the activation of the majority of streamflow responses in the intermittent stream network on slate. Although the soil moisture dynamics do not allow to draw direct conclusions to groundwater dynamics, local groundwater tables in the slate catchments were found between 0.5m to 3m depth and were synchronising with the soil moisture dynamics in the unsaturated zone above certain thresholds during the wet season (Martínenz-Carreras, 2016). The higher variability and stronger intermittency of streamflow during the dry season with hillslope contributions as the predominant source of streamflow and the reconnection of the stream network with the onset of groundwater contributions in the wet season was also observed and modelled by Ward et al. (2018) and Warix et al. (2021).

As the only site in slate, Site SL12 is the only site on slate shows deviations in the composition of predictor importance in the models with very low importance of soil moisture (Figure 9,  $\theta_{10}$  and  $\theta_{50}$  in blue colors rank 4 and 5). This site is located

in the Foulshterbaach catchment (Figure 1Figure 4), where the majority of the sites did not match the evaluation criteria for the model selection (Figure 8Figure 8) and soil moisture was not representative for the catchment (detailed discussion in section 5.2). The low model performance might be due to the spatial distance between the measurement sites of soil moisture and temperature which were mainly obtained in the Colpach catchment and the streamflow observations from the Foulshterbaach catchment. Thus, the soil moisture of the Colpach catchment might not be representative for the Foulshterbaach catchment (Figure 1). This assumption is supported by CAP and API\_14 being the second and third most important predictors at this site after temperature. The different behaviour between those two catchments in the slate geology is also recognisable in the succession of events and soil moisture dynamics plotted in Figure 4. The water ceased to flow for the period 28.10.2016 until 23.02.2017, with only one single flow response with a duration of three hours on 16.02.2017. This long dry period in the winter months was notable at several sites in the slate geology (Figure 6). However, the first streamflow response after this dry period lags nine events behind in the Foulshterbaach catchment compared to the other catchments in the slate. One reason for this might be due to the differences of the precipitation input. The Foulshterbaach catchment has an overall higher precipitation than the Colpach catchment (Kaplan et al., 2020ab), but for these events the precipitation events are very similar. Due to the different precipitation sums, differences in the soil moisture dynamics need to be expected, something that is also underlined by the importance of API as an alternative soil moisture measure at the sites of the Foulshterbaach catchment (Figure 6).

### 5.1.3 Factors affecting streamflow responses on sandstone geology Intermittency controls in sandstone

Sandstone layers are generally characterised by a high permeability which provides a large aquifer storage that feeds permanent springs (Colbach, 2005). The high permeability also supports a high infiltration capacity and limits surface runoff during precipitation events (Wrede et al., 2014). In fact, identifying monitoring sites which show with a regular intermittency of streamflow was challenging for the site selection (Kaplan et al., 2019). As intermittent streamflow in the sandstone is less common and the relatively low number of initial sites in this geology had to be reduced after the model evaluation (Figure 7Figure 7), a general pattern of typical controls of intermittent streamflow in this geology could not be identified. Thus, the predictor importance and the potential controls of streamflow intermittency are discussed at the site scale rather than at the scale of the entire geology.

The sites SA5 and SA9 were quasi-perennial and the number of events showing no-flow was therefore too small for a balanced class representation in the random forest model. However, the site SA6 (fig. 1), which was located downstream of the two springs feeding the reaches at SA5 and SA9, could often be observed to cease flow 10 to 15 m downstream during field visits. This site shows a strong dependence on soil moisture, the duration of precipitation events and the antecedent precipitation. This indicates that either a specific soil moisture threshold- or that a long period of precipitation is required to produce streamflow and to compensate the transmission losses. This type of flow cessation through transmission losses was reported

for small catchments with low or moderate channel gradients and coarse sediments (e.g. Constantz et al., 2002; Costa et al., 2013). Streamflow in the perennial streams in the Luxembourg sandstone were associated with the contributions of a large aquifer that provides the necessary storage to sustain highly continuous baseflow rates (Wrede et al., 2014). However, in the case of intermittent streams the existence of shallow perched groundwater storages that develop at the boundary layer between less permeable geology and the overlying permeable sandy geology as described by Gutierrez-Jurado et al. (2019 and 2021) are likely the source for streamflow at the sites SA5 and SA9.

Sites SA7 and SA8 are located in the marly zones at the foot of sandstone hillslopes (Fig. 1). Both sites may acquire a certain share of streamflow from nearby groundwater springs which are also used as wells for drinking water. The two sites also share the same important model predictors: soil moisture in both depths and temperature. At these sites, the controls of on flow cessation during dry periods can either relate to natural controls caused by seasonal fluctuations of soil moisture and transmission losses in the marl layer, or can be amplified by higher rates of water withdrawal in the wells during summer seasons. This kind of anthropogenically induced alteration of streamflow intermittency has been reported for many rivers worldwide (Chiu et al., 2017).

The most important predictors for site SA4 were soil moisture in the two depths followed by maximum precipitation intensity and precipitation sum. The geological setting characterised by marls in the upstream part and sandstone in the lower part of the catchment may influence the streamflow at this site. In contrast to the other sites, which show a high importance of soil moisture, the streamflow response of SA4 is always flashy with longer events during periods of high soil moisture saturation. The predictor ranks of maximum and cumulative event precipitation are also comparably high at this site (Rank 7 and 8). This might indicate indicating that large precipitation events are needed to compensate for the transmission losses through the sandy streambed. This assumption is supported by the regularly ceasing streamflow 100 to 150m downstream of the gauging point (Fig. 1) which is also indicated in the topographic map of the region (Le Gouvernement du Grand-Duché de Luxembourg, 2009).

The stream channel at the site SA1 is characterised by a steeply inclined logging track. The most important predictors at this site are precipitation sum and maximum precipitation intensity, while mean precipitation intensity and cumulative antecedent precipitation show a minor and soil moisture the lowest importance are less important predictors. This is a clear indication for infiltration excess overland flow being the main process at this site. This contradicts the findings of Wrede et al. (2014) who did not notice considered infiltration excess overland flow as to not be a relevant process in the sandstone sub-catchment of the Attert, Huewelerbaach. The differing different result at SA1 might result from the specific constitution of the site's surrounding setting, where a logging track had been eroded down to the bedrock. Notable traces of finer sediment were found at the flow tracks at the foot of the hillslope which potentially caused weak forms of clogging similar to that described by Shanafield et al. (2020) for intermittent streams crossing different geologies. The most likely reason for the initiation of Infiltration excess overland HOF flow are the high precipitation sums during the events and the steep slopes of the tracks as similar conditions were observed to cause HOF on steep slopes in a sandstone catchments was also observed in other catchments (Scherrer and Naef, 2003; Tanaka et al., 2005; Gutierrez-Jurado et al., 2019; 2021).

## 5.2 Uncertainties of event analysis and random forest model

This study relied on the availability of ~~data for runoff controls, such as~~ precipitation, soil temperature and soil moisture data.

The event classification was based on two assumptions: a) snow can be neglected and b) every flow response ~~was is~~ induced

5 by a rainfall event. ~~Based on those assumptions, three potential scenarios can lead to a m~~ Misclassification of the events ~~could happen if~~: (1) precipitation occurs as snowfall delaying the flow response (e.g. Floyd and Weiler, 2008), (2) water in the channel ceases to flow during a period of temperatures below zero (Tolonen et al., 2019) ~~then the so that the~~ flow response is not ~~related to captured as a direct response to~~ a precipitation event and thus ignored by the event analysis or (3) inaccuracies or gaps in the streamflow observations ~~exist~~, as described by Kaplan et al., 2019. However, scenarios (1) and (2) occur only 10 for short timespans in the studied period and the streamflow data ~~observed through from~~ time-lapse photography was carefully quality checked. The occurrence of snowfall and ~~freezing frozen~~ water in the channel was validated by the time-lapse images from which the binary streamflow information was obtained (Kaplan et al., 2019). Freezing and thawing of water in the channel was only the main control of flow cessation and reactivation at the sites MA6, SL21 and potentially influenced the flow responses of SL2 and SL5 (~~Figure 3~~Figure 3), ~~and these~~ These sites were rejected by the model evaluation procedure.

15 Uncertainty of the models can also arise from simplifications or misrepresentation of the predictor data. Soil moisture is highly heterogenous in space and time. The approach of using averaged soil moistures of multiple sites per geology tries to overcome this spatial and temporal heterogeneity by representing the general trend of soil moisture in the catchment. The temporal sucession of infiltration signals along the sensors in the three depths (10, 30 and 50 cm) was used by Demand et al. (2019) to differentiate between infiltration processes at the plot scale. However, at the scale of a geological unit the dynamic of soil

20 moisture did not differ as significant between all depths, resulting in discarding the soil moisture in 30 cm depth. While the whole time series of soil moisture in 10 and 50 cm depth had no high correlations, the soil moisture measures at the event scale extracted for each site showed high correlations for some sites (fig. S6-S8). Limits in the representability of geology wide soil moisture were revealed at the sites of the Foulshterbaach catchment where soil moisture and antecedent precipitation indices had very low correlations. All sites in the Foulshterbaach have a lower total number of events due to a delayed installation

25 (Figure 5), but the reason for poor model results most likely result from non-representative soil moisture data (See also section 5.1.2). Mälcke et al. (2020) identified rainfall and the seasonal dynamics of evapotranspiration as the two major controls of soil moisture in the Colpach catchment. While the seasonal component is expected to be similar in the Colpach and the Foulshterbaach catchment, soil moisture responses to rainfall differ (Figure 6). Despite the weak representation of soil moisture in this catchment, the value of the general soil moisture dynamics in a catchment geology over the proxy variable

30 API is underlined by the predictor importance of soil moisture in the random forest models. It may be possible that a better representation of the soil moisture dynamics through API can be reached by extending the represented precipitation periods to 30, 64 or 128 days as i.e. used by Zimmermann et al. (2014) or Jensen et al. (2019). However, it needs to be investigated which parametrisation of the API measure fits best for a certain geology or soil type to adequately represent the soil moisture dynamic.

In cases where the random forest models are not capable to represent flow responses correctly, this is usually caused either by a small test dataset (Ließ et al., 2012) or by an imbalance of the modelled classes (Lunardon et al., 2014) but and in also in one the Fouschterbaach watershed potentially also by the differences between the locations of the observational sites where the predictor data (soil moisture and temperature) were collected and the locations of the gauging sites where (i.e. the response variables). The misrepresentation of the soil moisture in the Fouschterbaach catchment by the soil moisture obtained in the Colperbach catchment is supported by the very low correlation between the API and soil moisture values for the sites in this catchment. (streamflow) were collected).

The comparison between the mapped event responses (Figure 5Figure 5) and the model specificity and sensitivity (Figure 8Figure 8) reveals that the number of events has a major effect on the accuracy of the model in all geologies. Sites with low numbers of events where this is likely to have an impact are the sites MA3, MA23, SA2 and SA3 (Figure 3Figure 3). The flow responses classes at the sites SL1 and SL15 (both in the Colpach sub-catchment) were highly imbalanced with significantly more flow (> 100) than no-flow responses (4 - 10). This reduced the likelihood to select a representative dataset for the training datasets for these sites.

The class imbalance is generally a major problem of all statistical approaches and for those sites that cannot be adequately represented due to small datasets. If resampling approaches as used in this study are not able to balance out the classes only longer study periods with additional events are capable to overcome this drawback. In cases where the classes are well balanced and sufficient events are available but the model has still a low performance it might be an indication that either the data is not matching or alternative predictors are needed to describe the modeled dependencies.

Overall, the model accuracy was generally quite high (geology averages from 0.79 – 0.90) for the selection of models used in the predictor importance analysis. The models for a majority of the sites had excellent performance in predicting flow and no-flow responses with the test-dataset leading to high values of cumulative sensitivity and specificity close to the maximum of 2 (Figure 7). Despite the good predictions at the sites with the test data, model transfers between sites is not possible to the site specific statistics of each random forest. Generally, the random forest approach and the selected predictors were capable to predict the flow responses at most of the sites. However, for future studies it would be interesting how different event definitions would affect the outcome of model predictor importance and if additional event based predictors would allow for even higher accuracies of the models. The inclusion of spatial and event based predictors in future models can provide further interesting insights into the temporal and spatial dynamics of the intermittent stream network. Recent advances of modelling approaches show promising results (Gutierrez-Jurado et al., 2021; Botter et al., 2021). Ultimately, the model selection has to be tailored to the available data as

Additionally, all sites in the Fouschterbaach have a lower total number of events due to a delayed installation (Figure 5), but the reason for poor model results may also result from non representative soil moisture data which was obtained in a different sub catchment (See also Section 5.1.2). Mälicke et al. (2020) identified rainfall and the seasonal dynamics of evapotranspiration as the two major controls of soil moisture in the Colpach catchment. While the seasonal component is expected to be similar in the Colpach and the Fouschterbaach catchment, soil moisture responses to rainfall differ (Figure 6).

The flow at the sites SL9–SL11 may also be influenced anthropogenically. Surge tanks are indicated on the plateaus of the eastern and western hillslopes of the Fouschterbaach catchment in the topographic map of the region (Le Gouvernement du Grand-Duché de Luxembourg, 2009). The flow responses classes at the sites SL1 and SL15 (both in the Colpach sub-catchment) were highly imbalanced with significantly more flow ( $> 100$ ) than no flow responses (1–10). This reduced the 5 likelihood to select a representative dataset for the training datasets for these sites.

data imbalance will remain as a challenge for future studies choosing random forest or other statistical approaches. If, during the process of splitting data into training and test datasets only few events of the no flow classification remain in the training dataset for the resampling, this leads to a non adequate representation of the class with fewer events in the model. Based on the findings of this study, we recommend a longer monitoring period to capture a higher number of events. Additionally, it has 10 to be underlined that a good representation of the temporal soil moisture dynamics for all analysed catchments is important as the soil moisture was identified as the most crucial predictor for streamflow intermittency.

Uncertainty may also arise from the final step of the analysis in which the importance of model predictors at each site are used 15 in a comparison to the other sites which are located in the same geology, due to the variation of the catchment sizes. According to the findings of Kaplan et al. (2020), catchment size is among the strongest spatial predictors of intermittent streamflow occurrence in space in the Attert catchment, thus superimposing the effect of geology. The catchments included in this study have a notable range in catchment size in each geology ranging between 450m<sup>2</sup> and 734.223m<sup>2</sup> (Figure S16). Catchment size was not included in the analyses when the importance of model predictors at each site were compared to the other sites on the same geology. However, there was no significant correlation between catchment size and parameter importance or mean decrease Gini was found (Figures S117, S812, S139).

## 20 6. Summary and conclusions

This study provides insight into the characteristics of rainfall events that either do or do not trigger a runoff-streamflow reactions-response in intermittent streams in watersheds of with a temperate climate. The results underline that controls of on 25 intermittent streamflow are dependent on the geological setting of the catchment. The main findings are summarised as follows:

(1) The classification of precipitation events into “flow” and “no-flow” responses provided an appropriate basis for further analysis in a random forest model. The number of detected events varied significantly among the different sites due to data gaps in streamflow data as a result of technical problems and delayed installation at some of the sites.

(2) A random forest model was applied for each site to model flow response classes based on the predictors of precipitation characteristics ( $P_{\text{mean}}$ ,  $P_{\text{max}}$ ,  $P_{\text{sums}}$  and  $P_D$ ), antecedent precipitation indices (7 and 14-day API), maximum soil moisture in at two soil-depths ( $\theta_{10}$  and  $\theta_{50}$ ) and minimum soil temperature. For the majority of the random forest models, maximum soil 30 moisture during the precipitation event was identified as the main temporal control of that could explain the streamflow responses.

(23) ~~The controls of streamflow responses to precipitation events were revealed differed for the three geological regions. Overall, soil moisture was the most prominent predictor for intermittency in the random forest models for the sites in the sandstone region in this study. However, a detailed evaluation of site location in the sandstone regions revealed either parts of marl geology in the contributing area or the presence of permanent springs, which are likely to be located at the marl-sandstone boundary. In both cases streamflow intermittency is likely caused by transmission losses. Only one site, which might be the most representative site for stream flow intermittency in sandstone, showed ephemeral streamflow controlled solely by precipitation and infiltration excess overland flow. Due to the limited number of sites with intermittent streamflow in the sandstone geology, no overarching pattern of streamflow controls could be identified.~~ In regions characterised by marl geology the predominant controls were soil moisture in the top soil layer followed by antecedent precipitation, soil moisture in the deeper soil layer and soil temperature, suggesting saturation excess overland flow are the most important processes for runoff streamflow generation, which are governed by the overlaying seasonal fluctuations in evapotranspiration of temperature. A soil layer of very low permeability in 20 to 50 cm depths may support the development of shallow, perched groundwater on marls during the wet periods which contributes to streamflow. -For the slate regions, soil moisture in the lower soil layer constitutes a slightly stronger predictor than soil moisture in the upper layer and also the average splitting values of the the lower soil moisture values in the random forest models were higher for most sites on slate. This finding corresponds with results from earlier studies that hypothesised shallow subsurface flow during the dryer periods with and a fill and spill mechanism at the subsurface topography during the wet periods as the dominant control of streamflow generation in an Attert sub-catchment located in the slate region of the Attert. The marl and slate geologies share the importance of the temperature predictor which is interpreted as the indicator of seasonal changes in evapotranspiration which is a known control of the storage dynamics in the Attert catchment.

Overall, soil moisture was the most prominent predictor for intermittency in the random forest models for the sites in the sandstone region in this study. However, a detailed evaluation of site location in the sandstone regions revealed either parts of marl geology in the contributing area or the presence of permanent springs, which are likely to be located at the marl-sandstone boundary. In both cases streamflow intermittency is likely caused by transmission losses. Only one site, which might be the most representative site for stream flow intermittency in sandstone, showed ephemeral streamflow controlled solely by precipitation and infiltration excess overland flow. Due to the limited number of sites with intermittent streamflow in the sandstone geology, no overarching pattern of streamflow controls could be identified.

The combined dataset of intermittent streamflow observations, precipitation, soil moisture, and soil temperature and the methodology of using classified events in a random forest modelling approach allowed us to identify characteristic controls of streamflow intermittency in the marl and slate geologies. The control of soil moisture on flow responses seems to be threshold driven, while a threshold control of soil temperature was less clear and requires future research to disentangle the temperature effect as an intermittency control in temperate climates. A combined investigation of seasonal changes in evapotranspiration, snow accumulation and melt, temporary freezing of the water bodies as well as seasonal variations in the interception capacity and their effect on intermittent streamflow may have larger potential for future studies. Overall, the results of this study

highlight the importance of soil moisture and temperature as controls of intermittency in a temperate climate and the different controls in the three geological settings. Future studies may increase the understanding of the spatio-temporal controls of streamflow intermittency by analysing it at geological boundary zones in the headwater catchments of the temperate climates.

## 5 **Code and data availability**

Data and the analysis code are available from the authors upon request.

## **Author contributions**

NHK installed the monitoring network of time-lapse cameras, prepared the data, designed the analysis and carried it out. TB and MW designed the overall study and the sensor cluster monitoring network. NHK prepared the manuscript with  
10 contributions from the co-authors TB and MW.

## **Competing interests**

The authors declare that they have no conflict of interest. Markus Weiler and Theresa Blume are editors of the journal.

## **Acknowledgements:**

This study was funded by the German Research Foundation (DFG) within the Research Unit FOR 1598 Catchments As  
15 Organized Systems (CAOS) – subproject G “Hydrological connectivity and its controls on hillslope and catchment scale stream flow generation”. We thank Malte Neuper and Uwe Ehret for providing the precipitation data. We are grateful the work of Britta Kattenstroth and Tobias Vetter who were responsible for the installation, maintenance and data processing at the soil moisture and temperature sensor measurement sites. We thank our project partners from the Catchment and Eco-hydrology group at the Luxembourg Institute for Science and Technology (LIST) who provided the geodata for the catchment overview.

20 Special thanks to Dominic Demand and Daniel Beiter for helpful discussions about event classification. We like to thank the two anonymous referees who provided suggestions for significant improvements of the study and the manuscript. The underlying streamflow intermittency data is available at <http://doi.org/10.5880/FIDGEO.2019.010> and is described in detail by Kaplan et al., (2019).

## References

Angermann, L., Jackisch C., Allroggen N., Sprenger M., Zehe E., Tronicke J., Weiler M. and Blume T.: Form and function in hillslope hydrology: characterization of subsurface flow based on response observations. *Hydrol. Earth Syst. Sci.*, 21, 3727–3748, doi: <https://doi.org/10.5194/hess-21-3727-2017>, 2017.

Bachmair, S. and Weiler, M.: Interactions and connectivity between runoff generation processes of different spatial scales, *Hydrol. Process.*, 28, 1916–1930, doi:10.1002/hyp.9705, 2014.

10 Beiter, D., Weiler, M. and Blume, T.: Characterising hillslope–stream connectivity with a joint event analysis of stream and groundwater levels, *Hydrol. Earth Syst. Sci.*, 24, 5713–5744, <https://doi.org/10.5194/hess-24-5713-2020>, 2020.

Bhamjee, R. and Lindsay, J. B.: Ephemeral stream sensor design using state loggers, *Hydrol. Earth Syst. Sci.*, 15, 1009–1021, <https://doi.org/10.5194/hess-15-1009-2011>, 2011.

15 Bhamjee, R., Lindsay, J. B., and Cockburn, J.: Monitoring ephemeral headwater streams: a paired-sensor approach, *Hydrol. Process.*, 30, 888–898, <https://doi.org/10.1002/hyp.10677>, 2016.

Blasch, K. W., Ferré, T. P. A., Christensen, A. H., and Hoffmann, J. P.: New Field Method to Determine Streamflow Timing  
20 Using Electrical Resistance Sensors, *Vadose Zone J.*, 1, 289–299, 2002.

Boulton, A. J., Rolls, R. J., Jaeger, K. L., and Datry, T.: Hydrological Connectivity in Intermittent Rivers and Ephemeral Streams, 79–108, <https://doi.org/10.1016/B978-0-12-803835-2.00004-8>, in: *Intermittent Rivers and Ephemeral Streams*, edited by: Datry, T., Bonada, N., and Boulton, A., *Ecol. Manage.*, <https://doi.org/10.1016/B978-0-12-803835-2.00004>, 2017.

25 ~~Bracken, L. J. and Croke, J.: The concept of hydrological connectivity and its contribution to understanding runoff dominated geomorphic systems, *Hydrol. Process.*, 21, 1749–1763, doi:10.1002/hyp.6313, 2007.~~

Breiman, L.: Random Forests, *Machine Learning*, 45, 5–32, 2001.

30 Budyko, M. I.: Climate and life. In International geophysics series, 18). New York: Academic press New York, 1974.

Calle, M. L. and Urrea, V.: Letter to the Editor: Stability of Random Forest importance measures, *Briefings in Bioinformatics*, 12, 1, 86- 89, doi:10.1093/bib/bbq011, 2010.

5 Cammeraat, L. H., Sevink, J., Hissler, C., Juilleret, J., Jansen, B., Kooijman, A. M., Pfister, L., and Verstraten, J. M.: Soils of the Luxembourg Lias Cuesta Landscape, in: Kooijman, A. M., Seijmonsbergen, A. C., and Cammeraat, L. H., *The Luxembourg Gutland Landscape*, 107–130, [https://doi.org/10.1007/978-3-319-65543-7\\_6](https://doi.org/10.1007/978-3-319-65543-7_6), 2018.

10 Chiu, M., Leigh C., Mazor, R., Cid, N. and Resh, V. : Chapter 5.1 - Anthropogenic Threats to Intermittent Rivers and Ephemeral Streams. In : Datry T., Bonada N. and Boulton A. (Ed.) : *Intermittent Rivers and Ephemeral Streams*. Academic Press, 433-454, ISBN 9780128038352, <https://doi.org/10.1016/B978-0-12-803835-2.00017-6>, 2017.

Colbach, R.: Overview of the geology of the Luxembourg Sandstone(s), *Ferrantia*, 44, 155-160, 2005.

15 Constantz, J., Stewart, A. E., Niswonger, R. and Sarma, L.: Analysis of temperature profiles for investigating stream losses beneath ephemeral channels, *Water Resources Research*, 38, 12, 1316, doi:10.1029/2001WR001221, 2002.

Costa, A. C., Foerster, S., de Araújo, J. C. and Bronstert, A.: Analysis of channel transmission losses in a dryland river reach in north-eastern Brazil using streamflow series, groundwater level series and multi-temporal satellite data, *Hydrol. Process.*, 27, 1046-1060, doi:10.1002/hyp.9243, 2013.

20 Costigan, K. H., Jaeger, K. L., Goss, C. W., Fritz, K. M. and Goebel, P. C.: Understanding controls on flow permanence in intermittent rivers to aid ecological research: integrating meteorology, geology and land cover. *Ecohydrology*, 9, 7, <https://doi.org/10.1002/eco.1712>, 2016.

25 Datry, T., Bondana, N., and Boulton, A. J.: Chapter 1 – General introduction, in: *Intermittent Rivers and Ephemeral Streams – Ecology and Management*, edited by: Datry, T., Bondana, N., and Boulton, A. J., Academic Press, London, <https://doi.org/10.1016/B978-0-12-803835-2.00001-2>, 2017.

30 Demand, D., Blume, T. and Weiler, M.: Spatio-temporal relevance and controls of preferential flow at the landscape scale, *Hydrol. Earth Syst. Sci.*, 23, 4869–4889, <https://doi.org/10.5194/hess-23-4869-2019>, 2019.

Dunne, T., and Black, R. D.: Partial area contributions to storm runoff in a Small New England Watershed, *Water Resour. Res.*, 6(5), 1296–1311, 1970.

~~Dunne, T., Moore, T.R. and Taylor C.H.: Recognition and prediction of runoff producing zones in humid regions. In: Hydrological Sciences Bulletin 20, 305–327, 1975.~~

Eng, K., Wolock, D. M. and Dettinger, M. D.: Sensitivity of intermittent streams to climate variations in the USA, *River Res.*

5 *Appl.*, 32, 885–895, doi:10.1002/rra.2939, 2016.

Floyd, W. and Weiler, M.: Measuring snow accumulation and ablation dynamics during rain-on-snow events: innovative measurement techniques, *Hydrol. Process.*, 22, 4805–4812, doi:10.1002/hyp.7142, 2008.

10 Fritz, K. M., Nadeau, T.-L., Kelso, J. E., Beck, W. S., Mazor, R. D., Harrington, R. A., and Topping B. J.: Classifying Streamflow Duration: The Scientific Basis and an Operational Framework for Method Development, *Water* 2020, 12, 2545, doi:10.3390/w12092545, 2020.

15 Godsey, S. E. and Kirchner, J. W.: Dynamic, discontinuous stream networks: hydrologically driven variations in active drainage density, flowing channels and stream order, *Hydrol. Process.*, 28, 5791–5803, <https://doi.org/10.1002/hyp.10310>, 2014.

Goodrich, D. C., Kepner, W. G., Levick, L. R., and Wigington Jr., P. J.: Southwestern intermittent and ephemeral stream connectivity, *J. Am. Water Resour. As.*, 54, 400–422, <https://doi.org/10.1111/1752-1688.12636>, 2018.

20

~~Goulsbra, C. S., Lindsay, J. B., and Evans, M. G.: A new approach to the application of electrical resistance sensors to measuring the onset of ephemeral streamflow in wetland environments, *Water Resour. Res.*, 45, W09501, [https://doi.org/10.1029/2009WR007789, 2009.](https://doi.org/10.1029/2009WR007789)~~

25 Gutiérrez-Jurado, K. Y., Partington, D., Batelaan, O., Cook, P., and Shanafield, M.: What triggers streamflow for intermittent rivers and ephemeral streams in low-gradient catchments in Mediterranean climates, *Water Resources Research*, 55, 9926–9946, <https://doi.org/10.1029/2019WR025041>, 2019.

30 ~~Gutiérrez-Jurado, K. Y., Partington, and Shanafield, M.: Taking theory to the field: streamflow generation mechanisms in an intermittent Mediterranean catchment. *Hydrol. Earth Syst. Sci.*, 25, 4299–4317, [https://doi.org/10.5194/hess-25-4299-2021, 2021.](https://doi.org/10.5194/hess-25-4299-2021)~~

Heggen J.R.: Normalized Antecedent Precipitation Index, *J. Hydrol. Eng.* 2001.6, 377–381, 2001.

Hellebrand, H., van den Bos, R., Hoffmann, L., Juilleret, J., and Pfister, L.: The potential of winter stormflow coefficients for hydrological regionalization purposes in poorly gauged basins of the middle Rhine region, *Hydrolog. Sci. J.*, 53, 773–788, <https://doi.org/10.1623/hysj.53.4.773>, 2008.

5 5 ~~Hewlett, J.: Soil moisture as a source of base flow from steep mountain watersheds, Stn. Pap. 132. U.S. Department of Agriculture, Forest Service, Southeastern Forest Experiment Station, Asheville, 1961.~~

Horton, R. E.: The role of infiltration in the hydrological cycle. *Eos, Transactions American Geophysical Union* 14, 460-466, 1933.

10

Jackisch, C., Angermann, L., Allroggen, N., Sprenger, M., Blume, T., Tronicke, J., and Zehe, E.: Form and function in hillslope hydrology: in situ imaging and characterization of flow-relevant structures, *Hydrol. Earth Syst. Sci.*, 21, 3749–3775, <https://doi.org/10.5194/hess-21-3749-2017>, 2017.

15

Jaeger, K. L. and Olden, J. D.: Electrical Resistance Sensor Arrays as a Means to Quantify Longitudinal Connectivity of Rivers, *River Res. Appl.*, 28, 1843–1852, <https://doi.org/10.1002/rra.1554>, 2012.

20

Jaeger, K. L., Sando, R., McShane, R. R., Dunham, J. B., Hockman-Wert, D. P., Kaiser, K. E., Hafen, K., Risley, J. C., and Blasch, K. W.: Probability of Streamflow Permanence Model (PROSPER): A spatially continuous model of annual streamflow permanence throughout the Pacific Northwest, *J. Hydrol.*, 2, 100005, <https://doi.org/10.1016/j.hydroa.2018.100005>, 2019.

James, A. L., and Roulet, N. T.: Antecedent moisture conditions and catchment morphology as controls on spatial patterns of runoff generation in small forest catchments, *Journal of Hydrology*, 377, 351-366, doi:10.1016/j.jhydrol.2009.08.039, 2009.

25

Jencso, K. G. and McGlynn, B. L.: Hierarchical controls on runoff generation: Topographically driven hydrologic connectivity, geology, and vegetation, *Water Resour. Res.*, 47, W11527, <https://doi.org/10.1029/2011WR010666>, 2011.

Jensen, C. K., McGuire, K. J., and Prince, P. S.: Headwater stream length dynamics across four physiographic provinces of the Appalachian Highlands, *Hydrol. Process.*, 31, 3350–3363, <https://doi.org/10.1002/hyp.11259>, 2017.

30

Jensen, C. K., McGuire, K. J., Shao, Y., and Dolloff, C. A.: Modeling wet headwater stream networks across multiole flow conditions in the Appalachian Highlands, *Earth Surf. Proc. Land.*, 43, 2762–2778, <https://doi.org/10.1002/esp.4431>, 2018.

Jensen, C. K., McGuire, K. J., McLaughlin, D. L., and Scott, D. T.: Quantifying spatiotemporal variation in headwater stream length using flow intermittency sensors, *Environ. Monit. Assess.*, 191, 226, <https://doi.org/10.1007/s10661-019-7373-8>, 2019.

Kaplan, N. H., Sohrt, E., Blume, T., and Weiler, M.: Monitoring ephemeral, intermittent and perennial streamflow: a dataset from 182 sites in the Attert catchment, Luxembourg, *Earth Syst. Sci. Data*, 11, 1363–1374, <https://doi.org/10.5194/essd-11-1363-2019>, 2019.

Kaplan, N. H., Blume, T., and Weiler, M.: Predicting probabilities of streamflow intermittency across a temperate mesoscale catchment. *Hydrol. Earth Syst. Sci.*, 24, 5453–5472, <https://doi.org/10.5194/hess-24-5453-2020>, 2020a.

10

Kaplan, N. H., Blume, T., and Weiler, M.: Supplement of Predicting probabilities of streamflow intermittency across a temperate mesoscale catchment. *Hydrol. Earth Syst. Sci.*, 24, 5453–5472, <https://doi.org/10.5194/hess-24-5453-2020-supplement>, <https://doi.org/10.5194/hess-24-5453-2020-supplement>, 2020b.

15

Kohler, M. A., and Linsley, R. K., Jr.: Predicting runoff from storm rainfall. Res. Paper 34, U.S. Weather Bureau, Washington, D.C, 1951.

20

Kuhn, M., Wing, J., Weston, S., Williams, A., Keefer, C., Engelhardt, A., Cooper, T., Mayer, Z., Kenkel, B., the R Core Team, Benesty, M., Lescarbeau, R., Ziem, A., Scrucca, L., Tang, Y. and Candan, C.: caret: Classification and Regression Training. R package version 6.0-71. <https://CRAN.R-project.org/package=caret> (last access: 16 November 2020), 2015.

Le Gouvernement du Grand-Duché de Luxembourg – Administration du cadastre et de la topographie: Carte Topographique régionale touristique, R4 Steinfort, Redange, Luxembourg, 2009.

25

Liaw, A. and Wiener, M.: Classification and Regression by randomForest. *R News*, 2(3), 18-22, 2002.

Ließ, M., Glaser, B. and Huwe, B.: Uncertainty in the spatial prediction of soil texture: Comparison of regression tree and Random Forest models. *Geoderma*, 170, 70-79, <https://doi.org/10.1016/j.geoderma.2011.10.010>, 2012.

30

Louppe, G., Wehenkel, L., Sutera, A. and Geurts, P.: Understanding variable importances in forests of randomized trees, NIPS'13: Proceedings of the 26th International Conference on Neural Information Processing Systems - Volume 1, December 2013, 431–439, 2013.

Lunardon, N., Menardi, G., and Torelli, N.: ROSE: a Package for Binary Imbalanced Learning. *R Journal*, 6(1), 82-92, 2014.

Mälicke, M., Hassler, S. K., Blume, T., Weiler, M. and Zehe, E.: Soil moisture: variable in space but redundant in time, *Hydrol. Earth Syst. Sci.*, 24, 2633–653, <https://doi.org/10.5194/hess-24-2633-2020>, 2020.

5 Martínez-Carreras, N., Krein, A., Gallart, F., Iffly, J.-F., Hissler, C., Pfister, L., Hoffmann, L., and Owens, P. N.: The Influence of Sediment Sources and Hydrologic Events on the Nutrient and Metal Content of Fine-Grained Sediments (Attert River Basin, Luxembourg), *Water Air Soil Poll.*, 223, 5685–5705, <https://doi.org/10.1007/s11270-012-1307-1>, 2012.

10 Martínez-Carreras, N., Hissler, Ch, Gourdol, L., Klaus, L., Juilleret, J., Iffly, J. F. and Pfister, L.: Storage controls on the generation of double peak hydrographs in a forested headwater catchment, *Journal of Hydrology*, 543, 255-269, <http://dx.doi.org/10.1016/j.jhydrol.2016.10.004>, 2016.

15 Moreno-de-las-Heras, M., Merino-Martín, L., Saco, P. M., Espigares, T., Gallart, F. and Nicolau, J M.: Structural and functional control of surface-patch to hillslope runoff and sediment connectivity in Mediterranean dry reclaimed slope systems, *Hydrol. Earth Syst. Sci.*, 24, 2855-2872, <https://doi.org/10.5194/hess-24-2855-2020>, 2020.

20 Müller, B., Bernhardt, M., Jackisch, C., and Schulz, K.: Estimating spatially distributed soil texture using time series of thermal remote sensing – a case study in central Europe, *Hydrol. Earth Syst. Sci.*, 20, 3765–3775, <https://doi.org/10.5194/hess-20-3765-2016>, 2016.

Neuper, M. and Ehret, U.: Quantitative precipitation estimation with weather radar using a data- and information-based approach, *Hydrol. Earth Syst. Sci.*, 23, 3711–3733, <https://doi.org/10.5194/hess-23-3711-2019>, 2019.

25 Olson, S. A. and Brouillette, M. C.: A logistic regression equation for estimating the probability of a stream in Vermont having intermittent flow, US Geological Survey Scientific Investigations Report 2006-5217, US Geological Survey, p. 15, available at: <https://pubs.usgs.gov/sir/2006/5217/> (last access: 16 November 2020), 2006.

30 Pate, A. A., Segura, C. and Bladon, K. D.: Streamflow permanence in headwater streams across four geomorphic provinces in Northern California, *Hydrological Processes*, 34, 4487–4504, [doi:10.1002/hyp.13889](https://doi.org/10.1002/hyp.13889), 2020.

Penna, D., Tromp-van Meerveld, H. J., Gobbi, A., Borga, M. and Dalla Fontana, G.: The influence of soil moisture on threshold runoff generation processes in an alpine headwater catchment, *Hydrol. Earth Syst. Sci.*, 15, 689–702, [doi:10.5194/hess-15-689-2011](https://doi.org/10.5194/hess-15-689-2011), 2011.

Penna, D., van Meerveld, H. J., Oliviero, O., Zuecco, G., Assendelft, R. S., Dalla Fontana, G. and Borga, M.: Seasonal changes in runoff generation in a small forested mountain catchment, *Hydrol. Process.*, 29, 2027–2042, doi:10.1002/hyp.10347, 2015.

Pfister, L., Martínez-Carreras, N., Hissler, C., Klaus, J., Carrer, G. E., Stewart, M. K., and McDonnell, J. J.: Bedrock geology 5 controls on catchment storage, mixing, and release: A comparative analysis of 16 nested catchments, *Hydrol. Process.*, 31, 1828–1845, <https://doi.org/10.1002/hyp.11134>, 2017.

Pfister, L., Hissler, C., Iffly, J. F., Coenders, M., Teuling, R., Arens, A. and Cammeraat, L. H.: Contrasting Hydrologic Response in the Cuesta Landscapes of Luxembourg, in: Kooijman A., Cammeraat L., Seijmonsbergen A. (eds) The 10 Luxembourg Gutland Landscape. Springer, Cham., doi:10.1007/978-3-319-65543-7\_4, 2018.

Prancevic, J. P. and Kirchner, J. W.: Topographic Controls on the Extension and Retraction of Flowing Streams, *Geophys. Res. Lett.*, 46, 2084–2092, <https://doi.org/10.1029/2018GL081799>, 2019.

15 Reynolds, L. V., Shafroth P. B., and Poff, N. L.: Modeled intermittency risk for small streams in the Upper Colorado River Basin under climate change, *Journal of Hydrology* 523, 768–780, <https://doi.org/10.1016/j.jhydrol.2015.02.025>, 2015.

Ries, F., Schmidt, S., Sauter, M. and Lange, J.: Controls on runoff generation along a steep climatic gradient in the Eastern Mediterranean, *Journal of Hydrology, Regional Studies* 9, 18–33, <http://dx.doi.org/10.1016/j.ejrh.2016.11.001>, 2017.

20 Sando, R. Blasch, K. W.: Predicting alpine headwater stream intermittency: a case study in the northern Rocky Mountains, *Ecohydrology & Hydrobiology*, 15, 68–80, <http://dx.doi.org/10.1016/j.ecohyd.2015.04.002>, 2015.

25 Schaich, H., Karier, J., and Konold, W.: Rivers, Regulation and Restoration: Land Use History of Floodplains in a Peri-Urban Landscape in Luxembourg, 1777–2000, *Europ. Countrys.*, 4, 241–264, <https://doi.org/10.2478/v10091-012-0007-6>, 2011.

Scherrer, S. and Naef, F.: A decision scheme to indicate dominant hydrological flow processes on temperate grassland, *Hydrol. Process.*, 17, 391–401, doi: 10.1002/hyp.1131, 2003.

30 Schwab, M. P., Klaus, J., Pfister, L. and Weiler, M.: How runoff components affect the export of DOC and nitrate: a long-term and high-frequency analysis, *Hydrol. Earth Syst. Sci. Discuss.*, <https://doi.org/10.5194/hess-2017-416>, 2017.

[Shanafied, M., Gutiérrez-Jurado, K., White, N., Hatch, M. and Keane R.: Catchment-scale characterization of intermittent stream infiltration: a geophysics approach. \*Journal of Geophysical Research: Earth Surface\*, 125, e2019JF005330, <https://doi.org/10.1029/2019JF005330>, 2020.](https://doi.org/10.1029/2019JF005330)

5 Shaw, S. B.: Investigating the linkage between streamflow recession rates and channel network contraction in a mesoscale catchment in New York state, *Hydrol. Process.*, 30, 479–492, <https://doi.org/10.1002/hyp.10626>, 2016.

Sidle, R. C., Tsuboyama, Y., Noguchi, S., Hosoda, I., Fujieda, M. and Shimizu, T.: Seasonal hydrologic response at various spatial scales in a small forested catchment, Hitachi Ohta, Japan, *Journal of Hydrology*, 168, 227-250, 10 [https://doi.org/10.1016/0022-1694\(94\)02639-S](https://doi.org/10.1016/0022-1694(94)02639-S), 1995.

Sophocleous, M.: Interactions between groundwater and surface water: the state of the science, *Hydrogeol. J.*, 10, 52–67, <https://doi.org/10.1007/s10040-001-0170-8>, 2002.

15 Stewart, R. D., Bhaskar, A.S., Parolari, A. J., Herrmann, D. L., Jian, J., Schifman, L. A. and Shuster, W. D.: An analytical approach to ascertain saturation-excess versus infiltration-excess overland flow in urban and reference landscapes, *Hydrological Processes*, 33, 3349–3363, , DOI: 10.1002/hyp.13562, 2019.

Tanaka, Y., Matsukura, Y., Batnasan, N. and Tuvshinjargal, D.: Distinct runoff processes in granite and sandstone drainage 20 basins near Ulaanbaatar, Mongolia, *Environ Geol.*, 47, 640-646, doi:10.1007/s00254-004-1189-7, 2005.

Tolonen, K. E., Picazo, F., Vilmi, A., Datry, T., Stubbington, R., Pařil, P., Rocha, M. P. and Heino, J.: Parallels and contrasts between intermittently freezing and drying streams: From individual adaptations to biodiversity variation, *Freshwater Biology*, 64, 1679–1691, doi:10.1111/fwb.13373, 2019.

25 La Torre Torres, I. B. L. T., Amatya, D. M., Sun, G. and Callahan, T. J.: Seasonal rainfall–runoff relationships in a lowland forested watershed in the southeastern USA, *Hydrol. Process.*, 25, 2032-2045, doi:10.1002/hyp.7955, 2011.

Trancoso, R., Phinn, S., McVicar, T. R., Larsen, J. R. and McAlpine, C. A.: Regional variation in streamflow drivers across a 30 continental climatic gradient, *Ecohydrology*, 10, 1816, doi:10.1002/eco.1816, 2016.

Tromp-van Meerveld, H. J. and McDonnell, J. J.: On the interrelations between topography, soil depth, soil moisture, transpiration rates and species distribution at the hillslope scale, 2006.

Uys, M. C., and O'Keeffe, J. H.: Simple Words and Fuzzy Zones: Early Directions for Temporary River Research in South Afrika, Environmental Management, 21, 517-531, 1997.

5

Ward, A.S., Schmadel, N.M. and Wondzell, S.M.: Simulation of dynamic expansion, contraction, and connectivity in a mountain stream network. Advances in Water Resources, 114, 64-82, 2018.

10 Warix, S. R., Godsey, S. E., Lohse, K. A., & Hale, R. L.: Influence of groundwater and topography on stream drying in semi-arid headwater streams. Hydrological Processes, 35(5), DOI: 10.1002/hyp.14185, 2021.

Weyman, D. R.: Measurements of the downslope flow of water in a soil. J. Hydrol., 20, 267–288, 1973.

15 Wiekenkamp, I., Huisman, J. A., Bogena, H. R., Lin, H. S., and Vereecken, H.: Spatial and temporal occurrence of preferential flow in a forested headwater catchment, J. Hydrol., 534, 139-149, <https://doi.org/10.1016/j.jhydrol.2015.12.050>, 2016.

Wrede, S., Fenicia, F., Martínez-Carreras, N., Juilleret, J., Hissler, Ch., Krein, A., Savenije, H. H. G., Uhlenbrook, S., Kavetski, D. and Pfister, L.: Towards more systematic perceptual model development: a case study using 3 Luxembourgish catchments, Hydrol. Process., doi:10.1002/hyp.10393, 2014.

20

Zehe, E., Elsenbeer, H., Lindenmaier, F., Schulz, K., and Blöschl, G.: Patterns of predictability in hydrological threshold systems. Water Resources Research 43: W07434, doi:10.1029/2006WR005589, 2007.

25 Zehe E., U. Ehret, L. Pfister, T. Blume, B. Schröder, M. Westhoff, C. Jackisch, S. J. Schymanski, M. Weiler, K. Schulz, N. Allroggen, J. Tronicke, L. van Schaik, P. Dietrich, U. Scherer, J. Eccard, V. Wulfmeyer, and A. Kleidon: HESS Opinions: From response units to functional units: a thermodynamic reinterpretation of the HRU concept to link spatial organization and functioning of intermediate scale catchments. Hydrol. Earth Syst. Sci., 18, 4635–4655, 2014 doi:10.5194/hess-18-4635-2014.

30 Zimmer, M. A. and McGlynn, B. L.: Ephemeral and intermittent runoff generation processes in a low relief, highly weathered catchment, Water Resour. Res., 53, 7055–7077, <https://doi.org/10.1002/2016WR019742>, 2017.

Zimmermann, B., Zimmermann, A., Turner, B. L., Francke, T., Elsenbeer, H.: Connectivity of overland flow by drainage network expansion in a rain forest catchment, Water Resources Research, 50, 1457–1473, doi:10.1002/2012WR012660, 2014.