A hydrological framework for persistent pools along non 2 perennial rivers

Sarah A. Bourke¹, Margaret Shanafield², Paul Hedley³, Sarah Chapman^{1,3}, Shawan Dogramaci^{1,3}

⁵ ¹School of Earth Sciences, University of Western Australia, Crawley WA 6009 Australia

6 ²College of Science and Engineering, Flinders University, Bedford Park, SA 5042, Australia

⁷ ³Rio Tinto Iron Ore, Perth, WA 6000 Australia

8 *Correspondence to*: Sarah A. Bourke (<u>sarah.bourke@uwa.edu.au</u>)

9 Abstract

10 Persistent surface water pools along non-perennial rivers represent an important water resource for 11 plants, animals, and humans. While ecological studies of these features are not uncommon, these are 12 rarely accompanied by a rigorous examination of the hydrological and hydrogeological characteristics 13 that create or support persistent river pools. Here we present an overarching framework for 14 understanding the hydrology of persistent pools. Perched surface water, alluvial water through-flow and 15 groundwater discharge are the key hydraulic mechanisms that control the persistence of pools along 16 river channels. Groundwater discharge can be further categorized into that controlled by a geological contact or barrier, and discharge controlled by topography. Emphasis is put on clearly defining through-17 flow of alluvial water and the different drivers of groundwater discharge. The suite of regional-scale 18 19 and pool-scale diagnostic tools available for elucidating these hydraulic mechanisms are summarized 20 and critiqued. Water fluxes to pools supported by through-flow alluvial and groundwater discharge can 21 vary spatially and temporally and quantitatively resolving pool water balance components is commonly 22 non-trivial. This framework allows the evaluation of the susceptibility of persistent pools along river 23 channels to changes in climate or groundwater withdrawals. Finally, we demonstrate the application of this framework using a suite of the available tools to conduct a regional and pool-scale assessment of
the hydrology of persistent river pools in the Hammersley Basin of north-western Australia.

26 **1 Introduction**

27 Permanent or almost permanent water features along non-perennial rivers (hereafter referred to as "persistent pools") represent an important water resource for plants, animals, and humans. These 28 29 persistent pools typically hold residual water from periodic surface flows, but also may receive input 30 from underlying aquifers, and have alternately been termed pools (Bogan and Lytle, 2011; Jaeger and 31 Olden, 2011; John, 1964), springs (Cushing and Wolf, 1984), waterholes (Arthington et al., 2005; Bunn 32 et al., 2006; Davis et al., 2002; Hamilton et al., 2005; Knighton and Nanson, 2000; Rayner et al., 2009), 33 and wetlands (Ashley et al., 2002). Non-perennial streams are globally distributed across all climate types (Shanafield et al., 2021; Messager et al., 2021). The occurrence of persistent pools along non-34 35 perennial streams has been well-documented (Bonada et al., 2020), particularly in the arid southwest of 36 the U.S. (Bogan and Lytle, 2011) and across Australia (Arthington et al., 2005; Bunn et al., 2006; Davis 37 et al., 2002).

38 Several studies have confirmed that persistent river pools support a highly diverse community of flora 39 and fauna (Shepard, 1993; Bonada et al., 2020) and can vary significantly in water quality (Stanley et 40 al., 1997). Persistent pools are also often of cultural significance (Finn and Jackson, 2011; Yu, 2000), 41 providing key connectivity across landscapes for biota (Sheldon et al., 2010; Goodrich et al., 2018), and 42 early hominid migration (Cuthbert et al., 2017). Paradoxically, the unique ecosystems they support are 43 also sensitive to changing climate and human activities (Bunn et al., 2006; Jaeger and Olden, 2011). 44 Persistent pools may dry out naturally after successive dry years (Shanafield et al., 2021) and recent 45 studies have shown that persistent pools are also changing over time in response to alterations in climate 46 and sediment transport (Pearson et al., 2020, Bishop-Taylor et al., 2017). However, their hydrology is 47 typically poorly understood, and the treatment of the hydrology of persistent river pools in published 48 literature to date has been largely descriptive, vague, or tangential to the main theme of the paper

49 (Thoms and Sheldon, 2000). As a result, effective water resource management is limited by a lack of50 understanding of the mechanisms and water sources that support these persistent pools.

51 By far, the published literature on persistent pools focuses on the ecological processes and patterns. 52 They have received attention for the role they play as a seasonal refuge (Goodrich et al., 2018), and 53 with regards to connectivity between riparian ecosystems (Godsey and Kirchner, 2014). For example, 54 they have been shown to host unique fish assemblages (Arthington et al., 2005; Labbe and Fausch, 55 2000), macroinvertebrate communities (Bogan and Lytle, 2011), and play a vital role in primary 56 productivity (Cushing and Wolf, 1984). Recently, it was shown that the structure, but not composition, 57 of persistent pools mirrors that of perennial rivers (Kelso and Entrekin, 2018). However, rarely are these 58 ecological studies accompanied by a rigorous examination of the hydrological and hydrogeological 59 characteristics that provide a setting for these ecologic communities. Although there are isolated studies 60 that examine the composition of water and propose sources within specific pools (Hamilton et al., 2005; 61 Fellman et al., 2011), more frequently they simply describe the seasonal persistence of flow and basic 62 hydrologic parameters (typically temperature and salinity, sometimes also oxygen).

63 From a hydrogeological perspective, classification of persistent pools, and springs in general, dates back to the early 20th Century, when geological drivers such as faults and interfaces between bedrock and the 64 65 overlying alluvial sediments were first discussed in relation to springs (Bryan, 1919; Meinzer, 1927). 66 Subsequently, a diverse, modern toolbox of hydrologic and hydrogeologic field and analysis methods 67 to analyse water source, age, and composition has evolved. Yet contemporary work on springs (Alfaro and Wallace, 1994; Kresic, 2010), and hydrogeology textbooks (e.g. Fetter, 2001; Poeter et al., 2020) 68 69 are still based primarily on these early classifications. More recent classifications, moreover, are either 70 descriptive or focus on the context (karst vs desert) or observable spring water quality (Springer and 71 Stevens, 2009; Shepard, 1993; Alfaro and Wallace, 1994) and are not readily applied to understand the 72 hydrology of persistent river pools (not all persistent pools are springs). There has also been a robust 73 body of literature developed around surface water – groundwater interaction of the past 20 years (e.g. Stonedahl et al., 2010; Winter et al., 1998), some of which informs our understanding of persistent river 74

75 pools, but has not yet been explicitly applied in this context. Similarly, our understanding of the 76 hydrology of non-perennial streams and their links to groundwater systems continues to expand 77 (Costigan et al., 2015; Gutiérrez-Jurado et al., 2019; Blackburn et al., 2021; Bourke et al., 2021). The 78 existence of rain-fed freshwater rock-pools that are not connected to the groundwater system has also 79 been documented in the context of understanding their ecology (Joque et al., 2010) but the discussion 80 of their hydrology is limited. Thus, while many of the hydrologic concepts relevant to persistent river 81 pools can be found in existing literature, a comprehensive hydrologic framework is lacking (Costigan 82 et al. 2016; Leibowitz et al., 2018). Such a framework should incorporate the relevant elements of literature on groundwater springs and surface - groundwater interaction, along with the modern suite of 83 84 diagnostic tools, to provide a robust platform for understanding the hydraulic mechanisms that support 85 persistent river pools.

86 The aim of this paper is to consolidate the hydrologic processes and observational diagnostic tools 87 within existing literature into a cohesive framework to support the characterization the hydrology of 88 persistent pools along non-perennial rivers. To this end, we i) identify the range of hydraulic 89 mechanisms supporting river pool persistence during periods of no-flow and show how these 90 mechanisms can manifest in the landscape, ii) discuss the resulting susceptibility of pools to changing 91 climate or groundwater withdrawals and iii) present and critique field-based observational tools 92 available for identifying these hydraulic mechanisms. The application of this framework is 93 demonstrated a regional-scale assessment and three pool-scale studies from the Hamersley Basin of 94 north-western Australia.

95

96 2 Hydraulic mechanisms supporting the persistence of in-stream pools

97 Here we propose a framework for classifying the key hydraulic mechanisms that support the persistence 98 of pools along non-perennial rivers in environments where the shallow, unconfined aquifer does not 99 support year-round flow-(summarized in Table 1). Geologically, we start by considering the general 100 case of a non-perennial river along an alluvial channel (inundated and/or flowing during contemporary 101 flood events) within valley-fill sediments deposited over bedrock, where tributaries flow either across 102 the bedrock or the valley-fill sediments (Sections 2.2). 2.1 and 103 We then move onto a discussion of the ways in which geological structures and outcrops can underpin 104 the persistence of river pools by facilitating the outflow of regional groundwater (Section 2.3). The range of geological settings for non-perennial streams is vast (Shanafield et al., 2021); we have 105 106 endeavoured to provide sufficient general guidance so that the principles can be applied to specific river 107 systems as required. Hydrologically, we only consider the water balance of residual river pools after 108 surface flows have ceased. Any water that has infiltrated to the subsurface saturated zone (which may 109 be a perched aquifer) is considered to be groundwater, irrespective of the residence time of that water 110 in the subsurface. This groundwater may be alluvial groundwater, stored within the alluvium beneath 111 and adjacent to the contemporary river, or regional groundwater stored within regional aquifers. The 112 conceptual diagrams presented in this section are intended as generalized diagrams to represent key hydrological features; they do not represent specific locations and are not drawn to scale. 113

114

115

Mechanism supporting	Physical characteristics	Hydrochemical characteristics	Susceptibility to stressors
pool persistence and water balance*			
Perched water $\frac{\partial V}{\partial t} = EA$	Topographic low that catches rainfall/runoff. Present in i) elevated hard-rock headwaters of catchments and ii) regionally low-lying topographic location. Water levels in aquifer lower than pool water levels. Vertical head gradient between pool and aquifer with unsaturated zone below pool.	Highly variable; hydrochemistry is a function of rainfall and subsequent evaporation. Substantial enrichment of solutes and water isotopes during dry season. Precipitated salts usually wash away in next flood, (or do not form because of low solute concentrations in streamflow source). enrichment in nutrients and dissolved organic matter by evpo- concentration and the vegetation-related accumulation may contribute to the eutrophication of the pool water.	Relies on surface flows and overland runoff, which is directly tied to precipitation. Sensitive to climate but largely independent of groundwater use. Where infiltration capacity is high pools in downstream areas are more vulnerable to reduced rainfall. <u>Water ingestion by</u> <u>animals and/or transpiration of riparian</u> <u>vegetation can dry out the pool.</u>
Alluvium through-flow $\frac{\partial V}{\partial t} = 0$	Expression of river alluvium water table and through-flow. Head gradient reflects water table in alluvium. Water levels in pool coincident with	Pool hydrochemically similar to local alluvial water; enrichment of solutes and water isotopes in pool during dry season	Relatively small changes in rainfall or groundwater level can result in pool drying if the water level in the unconfined
$\frac{\partial t}{\partial t} = Q_{\rm i} - Q_{\rm o} - EA$	water level in adjacent alluvium (cm-scale gradients expected at influent or effluent zones). Bank storage is important for pool water balance. Absence of surface geological features (e.g. hard-rock ridges) or waterfalls. Physical location may migrate as flood-scour re-shapes alluvium bedform.	solutes and isotopes in successive pools as you move down-stream. Flood water flushes through the alluvium and replaces or mixes with any residual stored water (i.e. hydrochemically flood and alluvial groundwater are the same after a flood). More through-flow means shorter pool residence time and less enrichment.	(alluvial) aquifer is reduced to below the base of the pool. Impact of withdrawals (either pumping or uptake by phreatophytes) from alluvium depends on volume and proximity to pool. Abstraction from regional aquifers that are hydraulically connected to alluvium may also affect pool water levels by inducing downward leakage from alluvium.
Groundwater discharge			
1) Geological contacts and barriers to flow $\frac{\partial V}{\partial t} = Q_i - Q_o - EA$	Two sub-types: i) Catchment constriction across ridges, or ii) aquifer thinning due to geological barrier intersecting topography. Presence of waterfalls or surface geological features (hard- rock ridges). Hydraulic head step-changes across pool feature. Carbonate deposits if source aquifer has sufficient alkalinity.	Consistent hydrochemical composition at point of contact/barrier. Evapo- concentration and evaporative enrichment down-gradient of discharge point. Initial pulse of water from runoff may be saline, pool salinity equilibrates with groundwater at low water levels.	Susceptibility to groundwater abstraction depends on scale of source groundwater reservoir (if large then potentially more resilient) and location of groundwater abstraction. Water persistence is less susceptible to changes in rainfall than other pool types. Presence of geological barrier between pool and groundwater abstraction may limit impacts.
 Topographically controlled seepage from regional aquifer 	Topography intersects i) water table or ii) preferential flow from artesian aquifer. Standing water persists during dry season due to groundwater discharge in absence of rainfall. Negligible recharge to aquifer during flood event	Consistent hydrochemical composition at point of seepage. Initial pulse of water from runoff may be saline, pool salinity equilibrates with groundwater at low water levels	Susceptibility to groundwater abstraction depends on scale of source groundwater reservoir (if large then potentially more resilient) and location of groundwater abstraction. Hydraulic gradient supporting
$\frac{\partial V}{\partial t} = Q_{\rm i} - EA$	(pool is regional discharge zone). Carbonate deposits if source aquifer has sufficient		pools may be similar to pool depth. No geological barrier to limit susceptibility.

116 Table 1 Summary of hydrological framework for persistent pools

alkalinity.

- *Water balance of residual pool when disconnected from surface water flows in the absence of rainfall and if only one mechanism is operating. $\frac{V \text{ is the volume of water in the pool (L³), t is time (T), Q_i is the water flux from the subsurface into the pool (L³T⁻¹), Q_o is the water flux out$ of the pool into the subsurface (L³T⁻¹), E is the evapotranspiration rate (LT⁻¹) and A is the surface area of the pool (L²).
- 120

121 **2.1 Perched surface water**

122 Perched surface water can be retained persist in topographic lows that retain rainfall and runoff during the dry season but are disconnected from the groundwater system (Fig. 1). This can be the case if the 123 124 pool directly overlies impermeable bedrock, or -if there is a low-permeability layer between the pool 125 and the water table (Brunner et al., 2009). The presence of this low-permeability layer is essential to 126 maintain a surface water body that is disconnected from the groundwater system. In the absence of a low-permeability layer, the surface water will slowly infiltrate into the subsurface (Shanafield et al., 127 128 2021). This low-permeability layer typically consists of clay, cemented sediments (e.g. calcrete) or 129 bedrock (Melly et al., 2017, Joque et al., 2010). The persistence of water in these pools will depend on a) shading from direct sunlight and/or, b) sufficient water volume so that it is not completely depleted 130 131 by evapotranspiration during the dry season (which will be largely a function of pool depth). Given the 132 lack of a water replenishment mechanism during the dry season these pools may persist for some, but 133 not all, of the dry season.

134

The occurrence and biological significance of such perched pools has been described particularly for 135 rivers in inland Australia, where contribution of groundwater has been ruled out on the basis of pool 136 hydrochemistry (e.g. Bunn et al., 2006, Fellman et al., 2016). For example, along Cooper Creek in 137 central Australia, geochemical and isotopic studies revealed a lack of connection to groundwater, and 138 that convergence of flows at the surface and subsequent evaporative water loss-controlled water 139 140 volumes in many pools (Knighton and Nanson, 1994; Hamilton et al., 2005). These pools are situated 141 in depressions caused by erosion through sandy subsurface layers (note that the low-conductivity layer 142 for perching was not elucidated). It should be noted, that definitive characterization of perched surface

water (i.e. disconnected from the groundwater system) requires the measurement of a vertical hydraulic gradient between the water level in the pool and local groundwater, as well as identification of a lowpermeability layer at the base of the surface water (Brunner et al. 2009). Although the ecological significance of perched in-stream pools is documented within the literature (Boulton et al., 2003; Arthington et al., 2005; Bonada et al, 2020), there is typically no detailed analysis of the hydrology and sampling is synoptic, so the mechanism of persistence is unclear.

149



Figure 1 Schematic illustration of perched pools where rainfall-runoff collects in a depression that has morphology that limits evaporation and/or low permeability lithology beneath the pool that limit infiltration, allowing water to be retained for an extended duration.

154

155 **2.2 Through-flow of alluvial groundwater**

During rainfall events, increases in water levels in rivers result in water storage and flow within the unconsolidated alluvial sediments in the beds and banks of stream channels (Cranswick and Cook., 2015). As the streamflow recedes after a flood, continuous surface flow ceases, resulting in isolated pools along the river channel. Some vertical thickness of the alluvial sediments that line the stream channel will remain saturated with water beyond the period of surface water flow; this water is hereafter referred to as alluvial groundwater. Although the subsurface residence times of this alluvial water may be on the order of months to years (Doble et al., 2012), this water can be accurately described as groundwater. As such, alluvial water can be considered as a groundwater storage (Leibowitz and Brooks 2008). Persistent river pools can be expressions of this water within streambed sediments (Fig. 2); this source of water, limited to the floodplain, distinguishes the through-flow mechanism from regional groundwater discharge.

167 Alluvial groundwater can be either perched above, or connected to, the regional unconfined aquifer 168 depending on the depth of the regional water table and the presence of a low- permeability layer to 169 enable perching (Villeneuve et al. 2015, Rhodes et al., 2017). Once within the alluvial sediments, this 170 water can subsequently 1) flow laterally through the alluvial sediments towards the bottom of the 171 catchment 2) be lost to the atmosphere through evapotranspiration, or 3) migrate vertically downward 172 into lower geological layers (Brooks and Hayashi, 2002; Shanafield et al., 2021; Leibowitz and Brooks, 173 2008). The recession of groundwater levels in the alluvium will therefore depend on the amount of 174 water stored, hydraulic gradients and the permeability of the sediments (which control lateral 175 groundwater flow), hydraulic connections to underlying aquifers (facilitating vertical leakage) and 176 evpo-transpiration (Brooks and Hayashi 2002; Doble et al., 2012; McCallum and Shanafield, 2016,). The water level and hydraulic gradients adjacent to persistent pools supported by alluvial through-flow 177 178 can therefore change seasonally in response to alluvial recharge by rainfall events, and subsequent 179 depletion of water stored in the sediments through water flowing into the pool, evapotranspiration and 180 subsurface groundwater flow (Käser et al., 2009; McCallum and Shanafield, 2016).

The storage and movement of water within alluvial sediments beneath and adjacent to streams has been described extensively in literature on hyporheic exchange (e.g. Stonedahl 2010) with water fluxes across temporal (days to weeks) and spatial scales (centimetres to tens of metres). From a hydrological perspective, the key feature of the hyporheic zone, and hyporheic exchange fluxes, is that it is a zone of mixing between surface water and shallow groundwater. The scales and mechanisms of hydraulic fluxes (water movement in and out of the streambed) are determined by streamflow and channel morphology, which control hydraulic gradients (Stonedahl et al., 2010, Bourke et al., 2014a). Thus, when the stream is not flowing, the in-and-out hyporheic exchange fluxes that are driven by streamflow are not operating.
However, there can still be exchange of water between surface pools and alluvial water driven by
hydraulic gradients between the pool and alluvial water.

191 Some authors have considered this exchange through the lens of the hyporheic zone (Käser et al., 2009; 192 Rau et al., 2017, del Vecchia et al., 2022). However, the hydraulic gradients controlling water fluxes 193 between pool and alluvium in a stream that is not flowing are not related to changes in stream elevation 194 along pool-riffle sequences; rather, they are controlled by hydraulic gradient between the pool and water 195 within the alluvium. While alluvial water that is perched above, and not connected to, the regional 196 aquifer, does not fit the dominant conceptualization of hyporheic exchange, the physical process that 197 links streambed elevation changes to flow paths beneath pool-riffle sequences in flowing streams can 198 be relevant to persistent in-stream pools, regardless of connection status (del Vecchia et al., 2022). 199 When considering the hydraulic gradient between the pool and the water beside it (as opposed to 200 beneath it) this can be described as parafluvial flow (Bourke et al., 2014a). The transient process of 201 alluvial groundwater recharge and subsequent draining of stored water is also analogous to "bank 202 storage" adjacent to flowing streams.

203 An alternative lens through which to consider the exchange of water between persistent river pools and 204 alluvial groundwater is provided by through-flow lakes, a well-established concept in literature on 205 surface water – groundwater interaction (Winter et al., 1998). There is a comprehensive body of 206 literature on the dynamics of through-flow lakes (Pidwirny et al., 2006; Zlotnik et al., 2009; Ong et al., 207 2010; Befus et al., 2012). Based on this conceptualization, alluvial water will flow into the pools from 208 the subsurface across the up-stream portion, and out of the pool, into the subsurface across the down-209 stream portion (Townley and Trefry, 2000; Zlotnik et al., 2009). This conceptualization has the 210 advantage of concisely describing theoretical hydraulic gradients and water exchange between the pool 211 and the entirety of the surrounding alluvial groundwater, while also accounting for the modification of 212 the hydraulic head distribution of alluvial groundwater caused by the pool itself. The water level in 213 pools supported by this alluvial groundwater is effectively a window into the water table within the

streambed sediments (Townley and Trefry, 2000). The rate of inflow to (and outflow from) the pool is dependent on the hydraulic conductivity of the sediments (Käser et al., 2009) and the balance of inflow and outflow controls the depth and residence time of water in the pools (Cardenas and Wilson, 2007). The duration of persistence of the pool will also depend on the storage capacity of the alluvial sediments that support it; these pools may dry seasonally (Rau et al. 2017) or persist throughout the dry season if the water level in the alluvial sediments remains above the elevation of the pool.





- water in these alluvial sediments can be either a) connected to the unconfined aquifer, or b) form a perched aquifer if
- 223 the water is stored over a low permeability layer.
- 224

220

225 **2.3 Regional groundwater discharge**

226 Similar to springs, rivers can be discharge points for regional groundwater, and this discharge can 227 support the persistence of in-stream pools during periods without surface flow. Groundwater discharge 228 through springs has been articulated into a range of detailed and complex categories, which are not 229 consistent within the literature (Bryan, 1919; Springer and Stevens, 2009; Kresic and Stevanovic, 2010). 230 These existing spring classifications are based on geological mechanism, hydrochemical properties, 231 landscape setting, or a combination of all three, leading to broad categories such as thermal or artesian, 232 as well as nuanced distinctions based on detailed geological structures (Alfaro 1994). For the purposes 233 of understanding persistent river pools, this array of categories is both overly complex and incomplete 234 from a hydraulic point of view. For example, Springer (2009) presents a classification of springs based 235 on their "sphere of influence", which is the setting into which the groundwater flows. A "limnocrene 236 spring" is simply any groundwater that discharges to a pool, as distinct from say a "cave spring", which 237 emerges into a cave. On this basis, one might consider all persistent pools that are not perched as 238 limnocrene springs. However, the schema also articulates 'helocrene springs' which are associated with 239 wetlands and "rheocrene springs" that emerge into stream channels. These also seem to be potentially 240 fitting labels for persistent river pools, which does one choose? And what would it matter for water 241 resource management and the conservation of pool ecosystems if you chose one category over the other? 242 We suggest two broad categories can encompass the range of hydraulic mechanisms supporting 243 persistent pools in intermittent stream channels; geological features (i.e. lithologic contacts and barriers 244 to flow), and topographic lows. This distinction is valuable because it facilitates an understanding of 245 the source of groundwater discharge (shallow, near-water table vs deeper groundwater) and the size of 246 the reservoir supporting the pool, both of which contribute to the susceptibility of pool persistence to 247 groundwater pumping. This distinction can also be useful for identifying the dominant hydrogeological 248 control on the influx of regional groundwater to the pool; in hard-rock settings with geological contacts 249 and barriers the influx may be limited by the effective hydraulic conductivity, whereas in a topographic

low the influx will be controlled by hydraulic head gradient between the pool and the groundwatersource (see Case Studies below).

252 **2.3.1** Geological contacts and barriers to flow

253 Geological contacts are well-established as potential drivers of groundwater discharge through springs 254 (Bryan, 1919; Meinzer, 1927). For example, contact springs occur where groundwater discharges over 255 a low-permeability layer, commonly associated with springs along the side of a hill or mountain (Kresic 256 and Stevanovic, 2010; Bryan, 1919). Similarly, pool peristence can be supported by groundwater discharge into a stream channel over a low-permeability geological layer caused by the reduced the 257 vertical span of the aquifer (Fig. 3a); where this vertical span reduces to zero is known colloquially as 258 259 the aquifer "pinching out". This mechanism has been identified as driving regional groundwater discharge to streams (Gardener et al., 2011), but to our knowledge has not yet been explicitly discussed 260 261 in the context of persistent river pools.

Outflow of groundwater where a catchment is constrained by hard-rock ridges that constrict groundwater flow (by reducing the lateral span of surface flow and the aquifer) can also support the persistence of surface water pools (Fig. 3b). Although the importance of catchment constriction has been identified by practitioners (e.g. Queensland Government, 2015), to our knowledge the discharge of groundwater caused by catchment constriction as a mechanism for surface water generation has not previously been described in published literature (springs or otherwise).



Figure 3 Schematic illustration of a groundwater discharge pools where surface water persistence is driven by geological barriers that a) cause a regional aquifer to pinch out vertically, or b) form a lateral constraint on the catchment and underlying regional aquifer.

272 **2.3.2** Topographically controlled seepage from regional aquifers

Pool persistence can be sustained by groundwater seepage from regional aquifers in the absence of geological barriers or contacts if there is a topographic low that intersects the regional water table (Fig. 4). This mechanism will generally occur where differential erosion causes a difference in topography, which is equivalent to depression springs (Kresic and Stevanovic, 2010; Bryan, 1919) and analogous to the lakes that form in pit voids left after mining ceases (McJannet et al., 2017). For example, pools likely supported by this mechanism have been identified within the Adelaide region of South Australia where erosion within a syncline has exposed bedrock, facillitating groundwater discharge (Lamontagne 280 et al., 2021). Within the humid landscape of south-eastern USA, Deemy and Rasmussen (2017) also 281 describe a vast number of pools along intermittent streams. These pools, which are seasonally connected 282 by surface flows during the wet season, are expressions of the karst groundwater networks that underlie them and may be considered special cases of topographically-controlled groundwater discharge pools. 283 284 Topographic depressions that fill seasonally with water, known as "sloughs" on the North American 285 prairie, operate similarly hydraulically (seasonal snow melt inputs, evaporation induces groundwater inflow), but these sloughs are not within river channels and commonly reside within low-permeability 286 287 glacial clays so that they are supported by the local-scale groundwater system (Van der Kamp and Hayashi, 2009). Even some Arctic lakes, formed in shallow topographic depressions, receiving 288 289 groundwater input and seasonally situated within a stream of snowmelt runoff (Gibson, 2002) can be 290 considered as pools supported by topographically-controlled groundwater discharge.

291 Pools may also be sustained by topographically controlled seepage from confined aquifers if there is a 292 fault or fissure that acts as a conduit to groundwater flow (different to Fig. 3a because there is no 293 geological transition to sustain a hydraulic gradient across the pool). Topographically controlled 294 discharge from a confined aquifer is analogous to artesian mound springs like those found in the Great 295 Artesian Basin of central Australia (Ponder, 1986), but these do not reside within non-perennial streams. 296 Groundwater discharge along fractures or faults has been identified as an important mechanism for 297 groundwater discharge to the Fitzroy River in northern Australia (Harrington et al., 2013), but the 298 significance of this regional groundwater discharge to individual persistent pools is not yet known.



15

Figure 4 Schematic illustration of a pool receiving topographically controlled groundwater outflow from a
 regional aquifer.

302 3 Management implications: Susceptibility of persistent pools to changing 303 hydrological regimes

Robust water resource management in semi-arid regions requires an understanding of the ways in which human activities or shifting climates can alter water balances and/or the duration of pool water persistence (Caldwell et al., 2020; Huang et al., 2020). In the absence of published literature quantifying the susceptibility of persistent pools, we present general guidance on the susceptibility of pools to changes in rainfall and groundwater withdrawals based on hydrologic principles (Table 1).

309 Intuitively, the size of the reservoir (surface catchment or groundwater storage) that supplies water to 310 the pool should be a key factor in determining the susceptibility of persistent pools to changing 311 hydrological regimes. However, the patchiness of rainfall and substantial transmission losses typical of 312 semi-arid zone intermittent river catchments (Shanafield and Cook, 2014) mean that for pools reliant 313 on surface catchments (perched or supported by alluvial through-flow), catchment size alone is unlikely 314 to be a robust predictor of resilience. As has been demonstrated for arid zone wetlands in Australia 315 (Roshier et al., 2001), pools that are storage-limited can be highly sensitive to climate variability. 316 However, increasing heavy rainfall events may not necessarily result in increased pool persistence 317 (particularly in pools closest to the location of rainfall) if subsurface storage up-gradient of the pool is 318 already filling during the wet season. In this case, subsequent rainfall will increase streamflow 319 downstream, but not result in increased subsurface storage in the reservoir supporting the pool. 320 Moreover, recent work has shown that groundwater response times are sensitive to aridity, with longer 321 response times associated with increased aridity (Cuthbert et al., 2019), so that there may be substantial 322 time-lags between climate variability and hydrologic response in pools supported by groundwater 323 discharge.

We have distinguished between geological or topographic control on groundwater discharge, but this distinction may not always be critical from a management perspective. In any system connected to groundwater, perturbation of the dynamic equilibrium between groundwater recharge and discharge can impact surface water-groundwater interactions; the timing and extent of the change will depend on the magnitude and rate of alteration (Winter et al., 1998). The hydraulic head gradients (and groundwater discharge rates) supporting persistent river pools may be small (Δ h on the order of cms), so that small decreases in groundwater level (either due to successive low-rainfall years, or groundwater withdrawals) can potentially have a detrimental impact on the pool and cause the pool to dry out (particularly for topographically controlled groundwater discharge to pools).

333 For pools supported by alluvial through-flow, the water balance is dominated by water outflow from 334 contemporary fluvial deposits but withdrawals from regional groundwater could impact the pool if these 335 two subsurface reservoirs are hydraulically connected. The volume of groundwater storage in the source 336 reservoir can indicate the resilience of pools to hydrological change (i.e. a longer groundwater system 337 response time), but impacts will also depend on the distance from the recharge zone or groundwater 338 withdrawals (which could include pumping or uptake by phreatophytes) (Cook et al., 2003). The time-339 lag prior to a decrease in groundwater outflow to the pool, and shape of the response (i.e. a slow decline 340 or sharp decrease), will also depend on the spatial distribution of the forcing (pool distance from 341 recharge or groundwater withdrawals) (Cook et al., 2003; Manga, 1999). Thus, focussed groundwater 342 withdrawals close to a pool will cause a larger and faster reduction in groundwater outflow than diffuse 343 withdrawals across the aquifer, or withdrawals further away (Cook et al., 2003; Theis, 1940). For 344 example, groundwater withdrawals from within 1 km of a pool will result in a rapid decrease in discharge (months to years) but the same volume of withdrawal distributed throughout the catchment 345 346 will result in a more gradual decline in groundwater discharge to the pool (years to decades). 347 Susceptibility can be further modified by geological barriers, which may not be obvious from the 348 surface topography or regional geological maps (Bense et al., 2013), but can isolate pools from the 349 regional groundwater system and either i) increase susceptibility to pumping within the connected aquifer, or ii) reduce susceptibility if the pumping is on the other side of the barrier (Marshall et al. 350 351 2019).

4 Diagnostic tools for elucidating hydraulic mechanisms supporting pool persistence

354 Several tools in the hydrologist's toolbox are appropriate for gathering the data needed to distinguish 355 between the hydraulic mechanisms that support pool-persistence as outlined in the previous section. For 356 most of these, there are no examples in published literature that are specific to persistent pools along 357 intermittent rivers. Therefore, this section provides general background and suggested considerations 358 for the application of these methods to characterize the hydrology of persistent pools (Table 2). A 359 selection of these tools may be deployed at a given site to characterize a) the relationship of the pool to 360 the groundwater system, and b) the relative contributions of evaporation, transpiration, and groundwater 361 fluxes (alluvial and regional) to the pool water balance. 362 363

364

Table 2 Summary of pros and cons of available diagnostic tools for assessing the hydraulic mechanisms supporting persistent river pools.

Diagnostic tool	Strengths	Limitations
Regional scale		
Landscape position and geological context	Low cost, can be assessed using publicly available data.	May be misleading if interpretation made in the absence of robust understanding of subsurface geology and groundwater system. Water balance components not quantified. Surface geology maps may not adequately capture subsurface structures that are important drivers of groundwater discharge.
Hydrogeological context	Low cost if the regional hydrogeological system has been previously characterized and water table map (or data) are publicly available.	Hydrogeological maps are not as ubiquitous as surface geology maps and may have been developed based on sparse data sets so that surface water -groundwater interaction is not adequately captured.
Remote sensing	Existing data sets available. Requires expertise in spatial data analysis.	Spatial or temporal resolution of data may not be adequate to capture pool hydrology. Water balance components not quantified.
Pool hydrography	Water level measuring equipment relatively low cost and readily available.	Equipment may be washed out during flood events. Pool water levels need to be combined with adjacent alluvial and groundwater level data to enable quantification of water balance components. Needs to be combined with bathymetry data to quantify water storage volume in pool.
Pool scale		
Pool hydrochemistry	Salinity (electrical conductivity) can be measured as a time-series using relatively inexpensive equipment (approx. double the cost of a water level logger).	Multiple discrete samples required to develop time-series. Overlapping values between end-members and spatio- temporal variation can complicate interpretation.

	Stable isotopes of water	Readily available, low-cost analyses. Mixing and fractionation processes relatively well understood.	Snapshot data interpreted in the absence of an understanding of pool water volumes may be misleading. Sample preservation required for some analytes. Overlapping values between end-members and spatio-temporal variation can complicate interpretation.
	Radon-222	Distinct end-members between surface and subsurface waters. Can measure in-situ time-series using a portable sampler Rad-7.	Some rock types have naturally low radon concentrations. Requires specialist equipment to measure. Cannot easily distinguish between alluvial and regional groundwater.
	Temperature	Sensors are relatively cheap, well-established technique for inferring vertical water fluxes in streambeds. Can rapidly and cheaply measure pool- bed temperature. Relatively simple to collect time- series data at multiple depths and estimate vertical water fluxes.	Alluvial and regional groundwater fluxes not easily separated. Can indicate locations of water inflow but not outflow. While vertical fluxes are relatively simple to estimate, lateral fluxes are often overlooked.
367			

368

369 4.1 Regional-scale tools

370 4.1.1 Remote sensing and image analysis

371 Mapping the persistence of vegetation and water in the landscape based on remotely sensed data (i.e. 372 NDVI or NDWI) or aerial photos can be useful to identify river pools that persist in the absence of rainfall (Haas et al., 2009; Soti et al., 2009; Alaibakhsh et al., 2017). This can be valuable for identifying 373 374 hydrologic assets that may require risk assessment and protection but does not elucidate the hydraulic 375 mechanism supporting the persistence of the pool. Interpretation of the key hydraulic mechanism(s) 376 supporting a pool requires additional information on the landscape position and hydrogeological context 377 of the pool. In combination, these regional-scale approaches are likely to be particularly useful in remote 378 regions that are difficult to access and pool-specific data collection is challenging.

379 4.1.2 Landscape position and geological context

Landscape position can provide some clues as to the mechanism controlling the persistence of a given pool. For example, a pool located high in the catchment on impermeable basement rock is likely to be a perched pool. Pools that reside within extensive alluvial deposits are likely to be supported at least in part by through-flow of alluvial groundwater. The presence or absence of alluvial deposits capable of hosting a significant volume of groundwater can often be determined by visual inspection, but geophysical tools or drilling are required to confirm the vertical extent of the alluvial aquifer. Similarly, 386 a pool that is immediately prior to a topographic ridge that constrains the catchment is likely to be 387 supported by geologically constrained groundwater discharge. Lateral catchment constriction can 388 commonly be identified from publicly available aerial imagery, but identification of vertical catchment 389 constriction will usually require geological data from drilling or regional-scale geophysical surveys. 390 Aerial geophysics (e.g. AEM) in particular can aid in identifying subsurface lithologic geometries and 391 low-permeability layers that can be important controls on groundwater outflow, but may not be obvious from aerial photographs or surface geology maps (Bourke et al., 2021). While the locations of 392 393 geological can be evident from readily available maps of surface geology, the hydraulic properties of 394 geological contacts are not always known a-priori. Geological transitions can be zones of high 395 permeability or barriers, or a combination of both (e.g. faults with high permeability in the vertical, low 396 permeability laterally) depending on the depositional and deformational history of the area (Bense et 397 al., 2013).

398 4.1.3 Hydrogeological context

399 Regional groundwater mapping can provide insights into the mechanisms supporting persistent pools, 400 particularly if the geology has also been well-characterized (see Case Studies below for examples). 401 Water table maps can articulate areas of groundwater recharge and discharge, and steep hydraulic 402 gradients that may (but not definitely) reflect the presence of geological barriers (e.g. Fitts, 2013). 403 Hydraulic head gradients can provide valuable insights; a step-change in hydraulic head can be a key 404 indicator for the presence of a hydraulic barrier. If an interpreted water table surface suggests that the 405 regional water table is tens of meters below ground in the vicinity of a pool, then the surface water is 406 likely (but not definitely) perched. If a pool is situated in a region that has been identified as a regional 407 groundwater discharge zone, then this groundwater discharge is likely to be supporting pool persistence. 408 The presence of active deposition of geological precipitates can also be indicative of pool mode of 409 occurrence with carbonates associated with groundwater discharge and subsequent degassing of CO2 410 (Mather et al., 2019).

411 **4.2 Pool-scale tools**

412 **4.2.1** Pool hydrography and water balance

If instrumentation can be installed in the pool, then it may be possible to characterize the pool water 413 414 balance. Once a pool becomes isolated from the flowing river, a general pool water balance is given by; $\frac{\partial V}{\partial t} = Q_i - Q_o - EA$, where V is the volume of water in the pool (L³), t is time (T), Q_i is the water flux 415 from the subsurface into the pool (L³T⁻¹), Q_o is the water flux out of the pool into the subsurface (L³T⁻¹) 416 ¹), E is the evapotranspiration rate (LT⁻¹) and A is the surface area of the pool (L²). Here we neglect 417 418 rainfall on the basis that a significant rainfall event is likely to initiate streamflow, but if this is not the 419 case, then rainfall can be included as an additional term PA, where P is the precipitation rate (LT⁻¹). The water level in the pool, h_p (L), can be routinely measured by installing pressure transducers, but 420 421 conversion of water levels to pool water volume (and/or pool area) requires knowledge of pool bathymetry, and the relationship between h_p and V-will change during the dry season as the pool water 422 423 level recedes (reducing the pool area A), or if pool bathymetry is altered by scour and/or sediment 424 deposition during flood events. Evapotranspiration rates can be taken from regional data or empirical 425 equations, but actual losses can vary depending on solar shading, wind exposure and transpiration 426 (McMahon et al., 2016). For pools with visible surface inflow or outflow, these rates can potentially be 427 measured using flow gauging (or dilution gauging), but relatively small flow rates and bifurcation of 428 flow can make this challenging.

429 Modified versions of this general water balance can be defined for particular pools, depending on the 430 hydraulic mechanism(s) supporting pool persistence (see Table 1). For perched pools, which are 431 disconnected from the groundwater system, $Q_i = Q_o = 0$, so that the only component of the water balance 432 is water loss through evaporation. Pools that are supported by alluvial through-flow are hydraulically connected to the water stored in the streambed alluvium. Water levels within this alluvium will be more 433 dynamic than regional groundwater levels, so that influx and efflux rates that can change over time in 434 435 response to rainfall events or seasonal drying (of the near-subsurface). Where uptake of water by 436 riparian vegetation from the groundwater store is substantial this may need to be accounted for explicitly

437 in a water balance model. For pools supported by groundwater discharge, influx will dominate over efflux $(Q_i > Q_0)$. If the groundwater discharge is over an impermeable aquiclude (see Fig. 3b) there 438 439 will commonly be a seepage zone up-gradient of the pool so that water influx is via surface inflow, but 440 outflow to the subsurface can form a source of groundwater recharge to the adjacent (down-gradient) 441 aquifer. If the groundwater discharge is controlled by topography, then the pool will be a site of regional groundwater discharge so that local groundwater recharge (and Q_0) should be negligible. An 442 443 understanding of pool water balances can be particularly important for interpreting hydrochemical data 444 (see 4.3)

If a pool is connected to the groundwater system Q_i (or Q_0) can be estimated from Darcy's Law; $Q_i =$ 445 $K \frac{\Delta h}{\Delta x} A_i$, where K is hydraulic conductivity, $\frac{\Delta h}{\Delta x}$ is the hydraulic gradient between the pool and the source 446 447 aquifer, and A_i is the area over which the groundwater inflow occurs (which will usually be less than 448 the total area of the base of the pool). The major limitations of this approach are that K of natural 449 sediments varies by ten orders of magnitude (Fetter, 2001), and that the area of groundwater inflow 450 needs to be assumed or estimated using a secondary method. Hydraulic gradients between pools and streambed sediments can be measured using monitoring wells or temporary drive points, with Δh 451 452 usually on the order of centimetres at most. Determination of the hydraulic gradient between regional 453 aquifers requires that the water level in the pool has been surveyed to a common datum and there is a 454 monitoring well near the pool to measure the groundwater level relative to that datum. In shallow, groundwater dominated lakes, geophysical methods have also been used to determine local hydraulic 455 456 gradients, and therefore the direction of the water flux(es) between groundwater and surface water (Ong 457 et al., 2010; Befus et al., 2012). Blackburn et al (2021) similarly applied shallow geophysical surveys, 458 combined with mapping of hydraulic conductivities, to identify they key structures and processes 459 controlling water fluxes between groundwater systems and the streams that host persistent pools 460 (Blackburn et al., 2021).

461 **4.2.2 Pool hydrochemistry and salinity (electrical conductivity)**

462 Numerous studies of streams and lakes have employed hydrochemical and mass balance approaches to quantify water sources (Cook, 2013; Sharma and Kansal, 2013) and groundwater recharge (Scanlon et 463 464 al., 2006). Some of these methods are also applicable in persistent pools, but may require modification, 465 or an iterative approach that allows for refinement of the methods as the mechanism supporting the pool 466 is elucidated. In its simplest form, snapshot measurements of pool hydrochemistry (salinity, pH, major 467 ions) can help distinguish pools that are connected to groundwater from those that are not (Williams 468 and Siebert, 1963). Dissolved ions are relatively cheap and easy to measure and have been used extensively to estimate recharge/discharge, groundwater flow, and ecohydrology in arid climates 469 470 (Herczeg and Leaney, 2011). Electrical conductivity (EC) as an indicator of salinity can be measured 471 at high temporal resolution using readily available loggers, which can be connected to telemetry systems 472 if required. Time series of EC through flood-recession cycles can indicate relative rates of evaporation and through-flow (Siebers et al., 2016; Fellman et al., 2011) and allow identification of the hydraulic 473 474 mechanism(s) supporting pool persistence. For example, if a pool is supported by regional groundwater 475 discharge, the EC will re-equilibrate towards the groundwater EC value during the dry-season (see case 476 studies in Section 5); in a perched pool, the pool EC will not plateau, but continue to evapo-concentrate 477 until the next flood event. However, in systems with large flood events, loggers can regularly become lost as the flood moves through, so EC loggers may need to be collected and downloaded prior to 478 479 anticipated flood events, which isn't always practical.

480 **4.2.3 Stable isotopes of water**

Stable isotopic values of pool water (δ^{18} O and δ^{2} H) can be interpreted similarly to electrical conductivity; groundwater seepage from a regional aquifer will have a relatively consistent isotopic value, while a pool isolated from the groundwater source will experience isotopic enrichment through evaporation (Hamilton et al., 2005), as demonstrated in Case Study 2 (Section 5.2.2). Pools receiving alluvial throughflow will have isotopic values that reflect the balance of inputs (from alluvial groundwater) and outputs (evapotranspiration and outflow to alluvial groundwater). However, the 487 interpretation stable isotopic values can be limited by overlapping ranges of values across different 488 water sources (Bourke et al., 2015), and spatiotemporal variability (see Case Studies). The isotopic 489 values in the alluvial water itself can become enriched through evapotranspiration during the dry season 490 resulting in variability over time, along the stream and throughout the catchment (Dogramaci et al., 491 2015), so that end-member values should be defined locally. In one case, strontium isotopes were found 492 to be more useful than stable isotopes of water for identifying groundwater contributions to in-stream 493 pools because the strontium values in the groundwater end-member was far more constrained than 494 salinity or stable isotope values (Bestland et al., 2017). Importantly, although these data are relatively 495 easy to measure, their interpretation should ideally be supported by a robust understanding of the pool 496 geometry, water flow paths and the surrounding geology to ensure that the hydraulic mechanisms 497 identified are physically plausible (see Discussion).

498 4.2.4 Radon-222 and groundwater age indicators

Radon-222 is a commonly applied tracer in studies of surface water – groundwater interaction, and ²²²Rn mass balances have been effective for quantifying groundwater contributions to streams and lakes (Cook, 2013; Cook et al., 2008). Preliminary measurements of ²²²Rn in persistent pools indicate substantial spatial variability in ²²²Rn activity along the pools, reflecting the spatial distribution of groundwater influx and gas exchange. This spatial variability will limit quantification of groundwater discharge based on the ²²²Rn mass balance but can allow for hot-spots of groundwater discharge to be identified (see Case Studies).

506 Other groundwater age indicators (³H, ⁴He, ¹⁴C) have been measured along streams to identify 507 groundwater sources (Gardener et al., 2011; Bourke et al., 2014b), but their applicability in pools is yet 508 to be determined. Given that shallow, stagnant water is common, tracers such as ¹⁴C or ³H, which don't 509 rapidly equilibrate with the atmosphere (Bourke et al., 2014b; Cook and Dogramaci, 2019), are likely 510 to be better than gaseous isotopic tracers (e.g. ⁴He) that equilibrate rapidly (Gardner et al., 2011). If a 511 mass balance approach is applied, then hydraulic measurements to constrain the pool water balance 512 should be made in conjunction with hydrochemical sampling to ensure that the water balance is 513 appropriately reflected in the mass balance.

514 **4.2.5 Temperature as a tracer**

515 Temperature measurements have been used extensively to identify and quantify water fluxes across streambeds and lakebeds (e.g. Shanafield et al., 2010; Lautz, 2012). Diel amplitudes of subsurface 516 517 temperatures have been used to identify the transition from flowing stream to dry channel (with isolated 518 pools) in ephemeral systems (Rau et al., 2017). In persistent pools, temperatures at the water sediment 519 interface can be used to map zones of groundwater inflow (Conant, 2004). In arid zones, groundwater 520 temperatures will often be warmer than pool temperatures and this type of survey is best conducted at 521 dawn when the temperature gradient between pool and groundwater is at a maximum and there are no 522 confounding effects from direct solar radiation. This mapping can be conducted using point sensors or 523 thermal cameras, but in natural water bodies this method has primarily found success at thermal springs 524 where the temperature difference between surface waters and groundwater inflows is on the order of 10 525 °C (Briggs et al., 2016; Cardenas et al., 2011).

526 Vertical profiles of temperature can also be used to estimate vertical fluid fluxes but the application of this approach in pools with coarse alluvial sediments (commonly through-flow pools) is likely to be 527 limited by lateral flow within the subsurface when $K_h > K_v$ (Rau et al., 2010; Lautz, 2010). Analytical 528 529 solutions for temperature-based flux estimates also break-down at low flux rates where the difference 530 between convection and conduction is difficult to determine (Stallman, 1965). Recently developed instrumentation for measuring 3D flux fields (Banks et al., 2018) shows promise, but installation in 531 532 course alluvial sediments like those commonly found in arid streambeds remains a challenge. Point-533 scale measurements also require up-scaling and these methods may not be applicable in fractured hard-534 rock pools.

535 5 Application of this framework to persistent pools in the Hamersley Basin

In this section we demonstrate the application of this framework to persistent river pools in north-west Australia (Figure 5). Here we begin by providing an overview of the hydraulic mechanisms supporting persistent river-pools in the Hamersley Basin based on regional-scale tools; landscape position, geological and hydrogeological context. We then present three pool-scale case studies to demonstrate how this contextual understanding can be supported by time-series data from pools to further elucidate spatio-temporal variability in the key hydraulic mechanisms supporting pool persistence.

542 The Hamersley Basin has an arid-tropical climate with a wet season from October to April and a dry 543 season from May to September (Sturman and Tapper, 1996). Average annual rainfall is less than 300 mm yr⁻¹ with most rain falling between December and April (www.bom.gov.au). Annual rainfall 544 statistics can vary dramatically, depending on the influence of thunderstorms and cyclone activity. 545 546 Thunderstorm activity is commonly highly localised, limiting the potential for spatial interpolation of data from individual monitoring sites. Annual evaporation is around 3000 mm yr⁻¹ (www.bom.gov.au), 547 or about ten times annual rainfall, so that permanent surface water is rare. Ranges, spurs, and hills 548 549 (consisting of bedrock and dykes described below) are separated by broad alluvial valleys with 550 numerous deep gorges created by differential erosion. During large flood events, runoff creates sheet-551 flow along the main channel and the extensive floodplain can remain flooded for several weeks. In the 552 absence of cyclonic rainfall, surface water is generally limited to a series of disconnected pools along 553 the main channels. Bedrock consists of Archean basement rocks of the Weeli Wolli, Brockman, 554 Wittenoom and Marra Mamamba Formations (youngest to oldest) that are extensively folded and 555 intruded by dolerite dykes (Table 3) with unconsolidated Tertiary and Quaternary sediments overlying 556 them (Dogramaci et al., 2015). The valleys are filled with up to 100 m of consolidated and unconsolidated Tertiary detrital material consisting of clays, gravels, and chemical precipitates. The 557 558 Quaternary alluvial sediments are deposited along the creek-lines and incised channels (incised on the 559 order of metres) and consist primarily of coarse, poorly sorted gravel and cobbles (thickness of up to tens of metres, widths of up to hundreds of metres) resulting in relatively high hydraulic conductivity 560

561 (see Table 3). The region is not considered to host regionally extensive, productive aquifers for water 562 supply (Brodie et al., 2019) but fresh groundwater is abundant throughout both within the Archean basement rocks, where permeability is increased via weathering, fracturing or mineralisation, and 563 564 within the Tertiary and Quaternary sediments (Dogramaci et al., 2012). The geological basin multiple surface water catchments with drainage flowing from the headwaters in the elevated areas towards the 565 566 Fortescue, Robe or Ashburton rivers.

567

568 Table 3 Estimated horizontal hydraulic conductivities of geological units relevant to pool-scale case studies.

Age	Geological unit or formation	Description	*Hydraulic Conductivity (m d ⁻¹)
Quaternary	Alluvium	Unconsolidated clay, silt, sand, gravel and cobbles	1000
Tertiary	Alluvium/colluvium	Unconsolidated clays, silts, sands and gravels. Some chemical precipitates	0.2 - 5
Proterozoic	Dykes	Dolerite	0.001
Archean	Weeli Wolli Formation	Banded Iron Formation (BIF), mudstone, siltstone, interlayered metadoleritic sills	0.1
	Brockman Iron Formation	BIF, chert, mudstone and siltstone	0.3 - 12.4
	Wittenoom Formation	Dolomite, chert, shale, sandstone	0.001 - 3
	Marra Mamba Formation	BIF, minor shale, stiltstone, mudstone	0.001 - 10

569 values from unpublished data and Dogramaci et al. 2015



570

Figure 5 Map of the Prevalence of persistent pools on watercourses in the Hamersley Basin and selected
pools examined in detail. Persistent pools based on "Waterholes" features from Geodata Topo 250K Series
3 data set, http://pid.geoscience.gov.au/dataset/ga/63999) Black rectangle indicates extent of Figure 7.

574

575 5.1 Regional-scale assessment of persistent pools within the Hamersley Basin

576 Regional- scale mapping of known pools has provided valuable insights about the distribution of pools and the likely hydraulic mechanisms supporting their persistence. Broad national-scale mapping of 577 "waterholes" as part of the publicly available topographic data set for this region identifies many pools 578 579 along drainage lines but does not capture all of the known pools (see Figure 5). National-scale 580 groundwater dependent ecosystem mapping available is also across Australia (http://www.bom.gov.au/water/groundwater/gde/map.shtml). This data identifies the groundwater 581 dependence of some river reaches within the Hammersley Basin but does not readily allow 582 583 groundwater-dependent persistent pools to be differentiated from groundwater-dependent flowing 584 streams. Image analysis and local knowledge has allowed for the identification of additional pools that 585 were not mapped within the publicly available dataset.

586 Overlaying pool locations with topographic mapping allowed a number of pools located at points of

lateral catchment constriction to be identified suggesting that groundwater outflow (either alluvial or

588 regional groundwater) supports pool persistence. The presence of a topographic constriction was

589 confirmed using image analysis and direct observation (Figure 6).



590

587

591 Figure 6 Photo showing a river pool that persists where a surface catchment is constricted resulting in a 592 groundwater spring.

593

594 By overlaying the locations of pools with available maps of surface geology we identified pools 595 overlying elevated basement rock in the absence of an extensive alluvial channel, indicating the 596 potential for these to be perched surface water (see un-named pools at southern extent of Fig. 7 for 597 example). For other pools their location at the likely edge of a groundwater flow system where low-598 permeability basement interected intersected topography suggested regional groundwater outflow at 599 geological contacts as an important hydraulic mechanism supporting persistence (e.g. Johnny Cake 600 spring on Fig 7). A number of pools were adjacent to mapped dykes; the persistence of these pools is 601 potentially influenced by regional groundwater outflow to the surface facilitated by the dyke acting as 602 a hydraulic barrier within the subsurface. Other pools were located on mapped river- channel alluvium, 603 indicating the likelihood that through-flow of alluvial groundwater at least partially supports pool 604 persistence (e.g. pools along the contemporary flow path of Caves Creek in Fig 7). The Hammersley

Basin is a fractured-rock province that does not host aquifers that are used for water supply (GSWA 2015). As such, publicly available groundwater level data is sparse and regional-scale mapping of water table or depth to groundwater contours that could further inform an assessment of the connectivity of pools to underlying groundwater is not available. NDVI mapping was undertaken (Fig 7 inset); while this provides insights into persistence, it did not allow for the further elucidation of hydrological processes that may be driving this persistence.



Figure 7 Map showing locations of persistent pools along Caves Creek relative to bedrock, low-permeability
 bedrock, dykes and alluvial river-channel sediments (Geological mapping 50K). Inset shows NDVI (on a
 scale of 0 in blue to 100 in red).

615

In-situ observation of the landscape position of pools and the qualitative duration or pool persistence has also provided valuable insights into hydraulic mechanisms supporting pool persistence. For example, there are approximately 20 pools that reside within the ephemeral drainage lines of the Western Range that flow over hard-rock for a few days in response to rainfall and do not have extensive

alluvial deposits; a subset of these pools are deeply incised and shaded persist all year round (Figure 8a). The presence of an extensive alluvial deposits that would facilitate alluvial groundwater throughflow as a hydraulic mechanism was also able to be inferred based on surface geological mapping and direct visual observation (Figure 8b). In other cases, alluvial deposits are present, and this alluvium is shaded within a gorge, so that alluvial through-flow is a major component of the water balance and evaporation is reduced relative to the alluvium outside the gorge, allowing surface water to persist (Figure 8c).

627



Figure 8 Photos demonstrating presence or absence of alluvium indicating a) no alluvium and perched surface water, b) extensive alluvium and pool supported by through-flow of alluvial groundwater, c) alluvium within shaded gorge so that persistence of water sourced from outflow of alluvial groundwater is enhanced.

633

628

The exposure and outflow of regional groundwater as a mechanism supporting pool persistence was also able to be inferred from regional-scale data sets and direct observation in some cases. For example, some pools persist within deeply incised river gorges that do not contain extensive alluvial deposits and are therefore likely to be supported by topographically controlled outflow of regional groundwater (Figure 9a). In another case, groundwater was observed visibly seeping from an exposed rock-face above a pool (Figure 9b) inferring that the exposure of that geological unit at the surface and subsequent outflow of groundwater is important for supporting the persistence of that pool.



641

Figure 9 Photos showing a) river pool persisting within a substantially incised gorge suggesting regional
 groundwater outflow supports pool persistence (<u>*This Photo</u> by Unknown Author is licensed under <u>CC</u>
 <u>BY-ND</u>), and b) visible groundwater outflow from an exposed rock face above a persistent river pool.

645

646 **5.2 Pool-scale case studies**

647 The following three case studies demonstrate the application of this framework to three different pools 648 (or pool systems) within the Hamersley Basin. To the best of our knowledge these pools have not been 649 impacted by groundwater withdrawals or surface water diversions. These case-studies we aim to 650 demonstrate a) the value of understanding the hydrogeological setting of each pool, and b) saptio-651 temporal variability pool water balances and hydrochemistry. Each case study begins by describing our understanding of the landscape position, geological and hydrogeological context of the pool. We then 652 653 introduce time-series data; the first case study utilizes water levels and EC in the pool and groundwater; 654 the second case study adds in time-series of stable isotopes values of pool water and groundwater; the 655 third case study brings in radon-222 and temperature mapping. By combining time-series data with an understanding of landscape position and hydrogeological setting, we are able to infer hydraulic 656 mechanisms supporting pool persistence. The implications of the identified hydraulic mechanisms for 657 658 the susceptibility of the pools to groundwater withdrawals or changing climate are also discussed.

659

660 5.2.1 Case study 1: Plunge Pool

661 Plunge Pool (Fig. 10a) is located at the base of a steep topographic drop-off that exposes the Marra 662 Mamba Formation. The Wittenoom Formation and underlying Marra Mamba Formation are 663 hydraulically connected and form an unconfined regional aquifer where there has been sufficient weathering and fracturing to generate secondary porosity. This aquifer is 50-100 m thick and divided 664 665 laterally by (sub-)vertical dykes on the order of 1 km apart (but as close as 100 m) that act as hydraulic barriers within the groundwater system. The surface catchment has an area of approximately 26 km² 666 and is storage limited. Regional groundwater in the adjacent aquifer has a hydraulic head of 547 m 667 668 above sea level (asl) at a distance of 200 m from the pool, increasing to 557 m asl 600 m from the pool, 669 indicating the presence of dyke that acts as a geological barrier between these two monitoring wells. 670 Seasonal variation in groundwater hydraulic heads is minimal (on the order of 0.2 m).

671 The pool is perennial with seasonal water level fluctuation between 541 and 543 m asl driven by 672 variation in streamflow, groundwater inflow and evapotranspiration (Fig. 10b). The varying proportions 673 of the pool water balance components are reflected in the temporal variation in the salinity of water in 674 the pool. At the onset of the first wet season flood the salinity in the pool spikes (up to 4171 mS/cm), 675 reflecting the flushing of surficial salts that were deposited during the previous dry through the 676 catchment. Subsequent rainfall events then cause a rapid freshening of the pool (to as low as 124 mS/cm 677 within 1 day). In the absence of rainfall, the salinity of the pool equilibrates to that of groundwater in 678 the regional aquifer (900 mS/cm). Given the consistency of groundwater levels, this inflow rate will be 679 relatively constant, so that (in the absence of streamflow) the variability in the salinity of the pool is 680 driven by seasonal variation in temperature and evapotranspiration (Bureau of Meteorology Station 681 #007185, Paraburdoo Aero). These seasonal weather patterns drive evapo-concentration of solutes in 682 the pool as water levels fall during the dry season and freshening of the pool as water levels rise when 683 evapotranspiration decreases in winter (May-Sep). Measurement of the relationship between water 684 levels and pool water volume will allow for these pool water balance components to be quantitatively 685 resolved.

686 Based on these data, the dominant hydraulic mechanism supporting the persistence of this pool is 687 attributed to groundwater inflow from the regional aquifer that is intersected by a topographic lowy 688 (Section 2.3.2). Despite the source being a regional aquifer, the spatial extent of the groundwater 689 reservoir supporting the pool is limited by the presence of geological dykes (Fig. 10c). The pool 690 effectively acts as a "drain" on the underlying/adjacent compartment of the unconfined aquifer with the 691 inflow rate to the pool controlled by the hydraulic conductivity of the aquifer (variation in groundwater 692 levels is negligible). The pool is also hydraulically connected to the alluvial aquifer and water from the pool is likely to infiltrate into the alluvium on the down-gradient side, but this has not been measured 693 694 directly (alluvium is absent up-gradient of the pool – therefore alluvial through-flow is not a supporting 695 mechanism). The susceptibility of this pool to groundwater withdrawals is controlled by the 696 hydrogeological compartmentalization. The pool will be more susceptible to groundwater withdrawals 697 from the aquifer between the nearest dyke and the pool, and less susceptible groundwater withdrawals 698 outside of this compartment. Given that evaporation is an important component of the water balance 699 and contributes to the regulation of water levels, this pool is also susceptible to increases in 700 evapotranspiration that are predicted as temperatures increase under climate change (IPCC, 2021).



701

Figure 10 a) photo of Plunge Pool, b) pool water level and electrical conductivity (EC), c) hydrogeological setting of the
 pool.

704

705 5.2.2 Case Study 2: Howie's Hole

Howie's Hole is a pool within stream channel alluvium at the exit point of a short, narrow gorge (Fig. 11a). Immediately at the outlet of the gorge (approximately 30 m up-hydraulic gradient of the pool) there is also a seep where groundwater outflows to surface for most of the year (seep dries for approximately 2-3 months at end of dry season). The seep is supported by the regional unconfined aquifer hosted within the Marra Mamba Formation and the surficial sediments above it (including the alluvial channel sediments), which are hydraulically connected. At the seep, the Brockman 712 formation has become adjacent to the Marra Mamba due to faulting and this forms a relatively 713 impermeable hydraulic barrier approximately 700 m wide (identified by the abrupt change in water 714 table depth either side of the formation). The surface catchment upstream of Howie's Hole has an area of 33 km². The gorge restricts the stream channel from 30 m width down to a channel width of 715 716 10 m, enhancing the water depth and flow rate and resulting in scour and erosion of the Brockman formation. This area of scour during high-flow events has subsequently been filled by deposition 717 718 of unconsolidated alluvial sediments, which are now at the base of the pool (sediments speculated 719 to be 5-10 m deep).

720 The height of the regional water table is only known 1.5 km away from the seep, with seasonal 721 fluctuations of 1-2 m (Fig. 11b). We assume that the water table declines towards the seep consistent 722 with topographic elevation change (~ 20 m drop over 1.5 km), and that the seep reflects the height 723 of the water table at that location (elevation of the groundwater seep is 405 m asl). During the period 724 of observation, the groundwater seep dried up when the measured water table elevation dropped 725 below ~418.4 m asl (water sample collected when the measured water table was at 418.5 m asl on 12th Nov 2018); the seep was dry when the measured water table was at 418.3 m asl on 7th Dec 726 2018. Pool water levels track groundwater elevations above 418 m asl, but data from 2019 shows 727 the pool depth levelling off as the water table at the monitoring bore drops below 418 m asl, 728 729 suggesting the cessation of significant groundwater inputs. The pool water levels have not been surveyed to the Australian Height Datum, but pool water level is consistently below the elevation 730 of the seep (approximately 398 - 400 m asl). 731

Similar to Plunge Pool, the pool salinity spikes with the seasonal onset of rainfall, before freshening once the accumulated salts have flushed through (Fig. 11c). In the absence of rainfall, pool salinity is similar to groundwater at the water table (Marra Mamba EC 1140 uS/cm). Isotopic values were available for 2018 (which does not overlap with the data EC and water level data). During this dryseason isotope values of the seep and pool were relatively consistent until August, when the pool receded (Figure 11d).

739 Based on these data we conclude that Howie's Hole reflects the water level in the alluvial aquifer within the stream channel (Fig. 11e). The location of the groundwater seep is determined by the 740 741 geological contact between the permeable Marra Mamba Formation and impermeable Brockman 742 Iron Formation in the subsurface, which coincides with the catchment constriction (gorge) that 743 forms an outlet for surface and groundwater. As a result of the streamflow regime caused by this 744 catchment constriction, the Brockman Iron Formation has been eroded and subsequently filled with 745 unconsolidated stream channel sediments; water storage within these sediments now support the 746 persistence of this pool.

747 The water level and isotopic data indicate a threshold groundwater level for inflow of groundwater 748 to the pool, such that the pool water balance is primarily dominated by groundwater recharged 749 during the previous wet season. Below this threshold water level for groundwater inflow, the 750 persistence of the pool relies on local water storage within the streambed alluvium (supporting pool 751 depths of up to 0.2 m). The persistence of this pool is therefore susceptible to 1) wet season rainfall 752 that is inadequate to recharge the unconfined aquifer to above the threshold water level, or 2) groundwater withdrawals that reduce seasonal peak groundwater levels to below the threshold level. 753 754 In the absence of this groundwater inflow, the pool is supported by water stored locally within the 755 streambed sediments (directly beneath the pool) and would be more susceptible to drying through 756 evapotranspiration (less inflow but the same amount of water loss through evapotranspiration).





758

Figure 11 a) photo of Howie's Hole, b) groundwater elevations and pool depth, c) pool water levels and electrical conductivity of pool and groundwater, d) pool depth and δ^{18} O showing stable isotopic composition at groundwater seep and evaporative enrichment down-gradient of seep during the dry season, e) conceptual diagram of pool occurrence.

762

763 5.2.3 Case study 3: Ben's Oasis

764 Ben's Oasis is a sequence of three pools (Pool 1, 2 and 3) that are hydraulically connected during peak 765 water levels and subsequently disconnect during the dry season (Fig. 12a). The pools sit within a major drainage channel that consists of poorly sorted, fine to very coarse (gravel and boulders) unconsolidated 766 767 alluvial sediments 10's of metres wide and on the order of metres in thickness. The regional water table is within the fractured dolomite of the Wittenoom Formation, which overlies the Marra Mamba 768 769 Formation. The pool is 2 km up-hydraulic-gradient of two parallel dykes, with a regional water table 770 decline of approximately 20 m across these dykes indicating that they act as a barrier within the 771 groundwater system. Water levels in the upper pool have been monitored since 2016 and in 2019 a 772 detailed study commenced using environmental tracers to assess the spatial variability of surface water 773 - groundwater interaction along this pool sequence (Chapman, 2019).

774 Measured pool water levels show consistent seasonal trends with water level spikes of 2-3 m in response 775 to cyclonic rainfall events during summer, followed by approximately five months of relatively steady 776 water levels and then recession over approximately three months (Fig. 12b). These trends are consistent 777 with the water level variation in the adjacent alluvium, which exhibits a similar period of steady water 778 levels then recession following the cessation of summer rains. In contrast, regional groundwater levels 779 increase by about 2 m in response to summer rainfall and then immediately begin to recede. Thus, 780 although snapshot water level measurements indicate that pool water levels are consistent with the 781 regional water table, transient water level data (that includes the water level in the alluvium) 782 demonstrates that inflow of water from within the alluvial sediments within the drainage channel is the 783 dominant driver of water level fluctuations in the upper pool (where the logger was installed). Spatial trends in the persistence of surface water and surface geology are also informative at this site. The 784 785 regional Wittenoom aquifer is exposed at surface around Pools 2 (some alluvium present) and 3 (no alluvium, just bedrock), but not at Pool 1 (no bedrock, just alluvium). The upper, shallower section of 786 Pool 1 and Pool 3 dried out as the dry season progressed, but the deeper parts of Pools 1 and 2 persisted 787 788 throughout the dry-season (during 2019 and 2020). We interpret these spatial patterns of persistence as

reflecting <u>spatially variable</u> evaporation rates (i.e. more or less shading by vegetation), <u>transpiration</u>
 <u>rates</u> and <u>heterogeneity in</u> groundwater inputs (Chapman, 2019).

The results of longitudinal hydrochemical surveys (²²²Rn and δ^{18} O) along the pool sequence provide an 791 independent line of evidence to validate this interpretation (Fig. 12c). Alluvial water had a ²²²Rn activity 792 of 17.6 Bq L⁻¹ and δ^{18} O of -6.3 ‰. The regional Wittenoom aquifer had a lower ²²²Rn activity of 8.1 793 Bq L-1 and more depleted δ^{18} O of -7.26 ‰. At the top of Pool 1, ²²²Rn activity was 7 Bq L⁻¹. Given 794 795 that degassing of radon to the surface is rapid and the water level at the time of sampling was shallow, the source of water inflows must have a much higher ²²²Rn activity than 7 Bg L⁻¹ and it is therefore 796 797 most likely that inflows here are dominated by the higher-Rn alluvial water. Isotopic δ^{18} O values of around -6 ‰, are also consistent with inflow of alluvial water. ²²²Rn activities then decrease along the 798 799 pool to around 0.5 Bq L⁻¹ (indicating degassing, and the absence of further groundwater inputs) as stable isotopic values enrich to just over -5 % (reflecting evaporation and the absence of further groundwater 800 inputs). Water at the up-stream end of Pool 2 had ²²²Rn of 2 Bq L⁻¹ (greater than at the down-stream 801 end of pool 1) and δ^{18} O of -6.3 ‰ (more depleted than at the bottom of Pool 1). These data indicate 802 803 further water inflows from the subsurface, along this pool, with a lesser proportion of alluvial water, 804 and more regional groundwater, as well as through-flow from Pool 1 (inferred from relative water levels in the pools). In Pool 3, ²²²Rn remains around 2 Bq L⁻¹ indicating further groundwater inputs, but the 805 806 stable isotopic values are more enriched (possibly due to the shallow water depth allowing for enhanced 807 evaporation).

Streambed temperatures within the pools were also mapped (temperatures measured every 0.2 - 1 m along transects 1-10 m apart) in early September, when regional groundwater was 29 °C, and alluvial water was 20 °C (Fig. 12d). Measured temperatures were recorded at dawn to reduce the effect of direct solar radiation and pool depth variability (max pool depth was 0.5 m). Streambed temperatures in the pools ranged from 17-23 °C, with the warmest water (>20 °C) at the top of Pool 1, and temperatures between 19-20 °C in middle of Pool 2 and at the top of Pool 3. These results are broadly consistent with the other results, but the approach is likely to be more conclusive in the presence of larger temperature gradients. The application of vertical temperature profiles to infer water fluxes at this site was also limited by the substantial lateral component of the subsurface flow-field (i.e. violating the assumption of 1D flow) and flood events that removed or damaged monitoring infrastructure.

818 Based on these data we conclude that the persistence of Ben's Oasis throughout the dry season is 819 supported by regional groundwater inflows from the unconfined aquifer where it is exposed at surface 820 (see Section 2.3), but the water balance of Pool 1 is dominated by exchange with the alluvial water (see 821 Section 2.2). This importance of the alluvial water storage in supporting the largest of these pools is 822 only evident based on time-series water level data from the alluvium. Given only snapshot water level 823 measurements from the regional aquifer and one location in the pools, the similarity in water level 824 elevations would lead to the conclusion that regional groundwater discharge was the dominant 825 supporting mechanism. The substantial spatial variability captured in the longitudinal hydrochemical 826 survey also highlights the risks of making conclusions about surface water – groundwater interactions 827 from snapshot hydrochemistry measurements in just one location within a given pool or pool sequence. 828 Subsequent numerical modelling of the groundwater system indicates that the presence of the regional-829 scale dykes east of the pool operates as a hydraulic barrier within the groundwater system, supporting the regional water table west of the dykes, promoting regional groundwater outflow to the surface at 830 831 the pool (Jen Gleeson pers. comm).

832 These data allows us to infer that there are two hydraulic mechanisms supporting the water balance and 833 persistence of these pools; alluvial through-flow and regional groundwater discharge (Fig. 12e). The 834 persistence of these pools through the dry season is dependent on influx of water from the regional 835 unconfined aquifer. They will therefore be susceptible to groundwater withdrawals from the regional 836 aquifer if they reduce the hydraulic head to below the level of the ground surface at the pools. The water 837 balance of these pools is also controlled by the interaction with water stored in the alluvial 838 through-flow). Therefore, the pools are also susceptible to reductions in rainfall or increases in 839 temperature (and evapotranspiration) that reduce the volume of water storage (and therefore water

- 840 levels) within the streambed alluvium. A reduction in the area of the surface catchment, which can result
- from mining operations, could also similarly alter the water balance of these pools.





Figure 12 a) photo of Ben's Oasis, b) water levels in the Pool 1 (logger 1 elevation was surveyed, logger 2 elevation was approximated by matching data from logger 1), alluvium (DP1) and regional unconfined aquifer, c) spatial variation

846 in radon activities and δ^{18} O along the pool sequence, d) temperature mapping of pool sediments and e) conceptual 847 diagram of mechanisms supporting pool persistence.

848 6 Discussion

849 It has now been 100 years since groundwater springs were documented in published literature (Bryan, 850 1919; Meinzer, 1927; Meinzer, 1923). In that time, the literature on springs, surface water-groundwater 851 interactions, and non-perennial rivers have all expanded consderably. The goal of the present work has 852 been to synthesize concepts from all of those fields to aid in the identification of hydraulic mechanisms that support in-stream pools. Thus in Section 2, we identified four primary pool types, discussing 853 854 hydraulic mechanisms for each conceptually and identifying relevant background literature to support 855 each. In section 4, we then provide a toolbox for use on individual pools and at the regional scale, and show in section 5 how this toolbox can be used through a series of case studies. This identification of 856 857 the hydraulic mechanisms is essential for effective management of risks to pool ecosystems associated 858 with groundwater withdrawals, changes to the hydraulic properties of the catchment (e.g. land use 859 change) or climate change, as discussed in Section 3.

860 Across the three case studies, the persistence of all pools was related to geological contacts that resulted 861 in regional groundwater outflow. Plunge Pool and Howie's hole are both located where a low-862 permeability geological unit results in groundwater outflow to the surface; the water cannot easily 863 continue to move in the subsurface, so it emerges at the point of contact. At Ben's Oasis, there is regional 864 groundwater outflow where saturated fractured rock is exposed at the surface and the hydraulic head is above the land surface. In all of these cases, there were additional hydraulic mechanisms supporting 865 pool persistence. At plunge pool the geological contact coincides with a topographic low; at Howie's 866 Hole there is a catchment constriction; at Ben's Oasis alluvial through-flow is a key determinant of pool 867 868 water levels. Thus, the water balance of persistent pools can respond to a combination of hydraulic 869 mechanisms, and the dominant mechanisms can vary spatially and temporally within pools. In all three 870 cases, the pool(s) contain a mixture of water from streambed sediments (alluvial through-flow) and

regional groundwater during certain hydroperiods, but the pool likely wouldn't persist through the dry season in that location without groundwater discharge from the regional aquifer. Thus, the maintenance of the stream ecosystem in its current state would require preservation of in-stream water storage and regional groundwater inflows. Such pools combining alluvial through-flow pools with some regional groundwater input are likely common, but it can be difficult to definitively identify and/or quantify this regional component of the water balance.

877 Given the potential for this complexity, we advocate for the use of multiple lines of evidence in 878 determining hydraulic mechanisms, in-line with the accepted paradigm in surface water-groundwater 879 interactions literature (Kalbus et al., 2006). Regional-scale tools provide a valuable method to make a 880 first estimate of hydraulic mechanisms; however, highly instrumented sites with robust geological 881 mapping, monitoring wells, and temporal hydrologic data are required to elucidate spatiotemporal 882 variability in the pool water balance. Likewise, snapshot data from multiple pools at one point in time 883 can help distinguish perched pools vs groundwater discharge pools (i.e. pool water hydrochemically 884 similar or different to rainfall or groundwater), but in some cases water-types (or end-members) are 885 difficult to distinguish based on easily measured parameters like electrical conductivity or stable 886 isotopes of water (Bourke et al., 2015).

887 However, we also acknowledge that direct measurement of water balances in arid and semi-arid regions can be logistically difficult (Villeneuve et al., 2015). Rainfall (and therefore runoff) in arid and semi-888 889 arid environments is commonly patchy and water fluxes can be either too large to measure (streamflow 890 during a cyclone) or too small to measure directly (dry-season groundwater seepage fluxes) (Shannon 891 et al., 2002; Shanafield and Cook, 2014). There are also potential logistical constraints that can apply 892 when installing any infrastructure for sampling and monitoring in-stream pools. Persistent pools in arid 893 landscapes are commonly sites of environmental and cultural significance (Finn and Jackson, 2011; Yu, 894 2000) so that appropriate approvals and permissions typically must be obtained prior to the installation 895 of monitoring infrastructure. This may restrict the types of data that can be collected. Moreover, some 896 sites may be sacred sites, limiting who is able to access them. Surface water features in general are a draw for travellers and roaming livestock, so that any infrastructure must be secure from theft or damage. Flood events and sudden, flashy streamflows are also potential threats to infrastructure, with substantial sediment and vegetation (branches, trees) transported across the floodplain to heights of 2-3 m that can (and have) destroyed sampling equipment. Infrastructure damage by unseasonal or early rainfalls in particular can impact our ability to capture regional groundwater contributions, since this is typically a relatively small (but important) component of the water balance of pools and is most readily captured at the end of the dry season.

904 With limited resources and access to sites, trade-offs must therefore be made between detailed 905 characterization of one pool vs a minimal data set at many pools. In our experience, utilizing detailed 906 data from fewer pools, is more likely to provide a robust characterization of pool hydrology at a scale 907 required for management than snapshot data from many pools across a region, which can be open to 908 misinterpretation. For example, while there is no isotopic fractionation associated with the outflow of 909 water from a pool, there is mass removal of water (and solutes) from the pool this. As such, this water 910 loss term should be accounted for when interpreting measured isotopic values of pool. This is because the change in isotopic value (or solute concentration, C) over time $(\delta C/\delta t)$ of any water body is a 911 912 function of the water balance and the mass balance (Cook 2013, Bourke et al., 2014b). Errors in the 913 water balance will therefore propagate through to errors in the interpretation of measured concentration 914 data.

915 This point can be is easily demonstrated using a simple synthetic model of isotopic values in a pool with a surface area of 200 m² and a depth of 2 m. The change in pool volume and δ^{18} O over 112 days was 916 917 simulated using the method and parameter values of Bourke et al. (2021) for four different water balance configurations (Figure 13). In the first scenario, evapotranspiration is the only loss (or gain) term in the 918 919 water balance. Evaporation is set at 0.007 m d⁻¹ and results in isotopic fractionation; transpiration is set at 0.003 m d⁻¹ and there is no associated fractionation (total loss rate 0.01 md⁻¹). In the second scenario, 920 groundwater inflows of 2.88 m³ d⁻¹ are added with the δ^{18} O of groundwater set at -7‰. In the third 921 922 scenario, groundwater inflow and outflow are implemented (as well as evapotranspiration) with a net

groundwater inflow of 2.88 m³ d⁻¹ (groundwater inflow of 11.52 m³ d⁻¹ and outflow of 8.64 of m³ d⁻¹. 923 924 The simulated pool volumes are identical in scenarios 2 and 3, but the isotopic values are different because the water balance equations are different, and therefore the equation for dC/dt is different in 925 scenario 2, as comparted to scenario 3. Thus, if the pool water outflow term was neglected when 926 927 interpreting measured stable isotope values from the pool, the results would be inaccurate. And although the difference in isotopic enrichment may be small under different water balance scenarios, the 928 929 cumulative impact could still be important hydro-ecologically (the associated error is 8-30% of initial pool water balance in scenarios shown below). The fourth scenario has the same evapotranspiration and 930 931 groundwater inflow as scenario 2, but the pool geometry is changed so that the pool area is halved and the depth is doubled (A = 100 m^2 , d = 4 m). This scenario demonstrates that (Figure 13). The isotopic 932 evolution of this hypothetical pool is more very sensitive to the surface area to volume ratio of the pool; 933 934 and yet these geometric properties can be difficult to characterize and are rarely reported in published 935 literature (they are also are lacking in the case studies presented herein) than the individual water 936 balance components. And although the difference in isotopic enrichment may be small under different water balance scenarios, the cumulative impact could still be important hydroecologically (8-30% of 937 938 initial pool water balance in scenarios shown below). Such potential pitfalls can be found in all single methods. Thus, we suggest an initial regional-scale assessment of landscape position and 939 hydrogeological context that allows for pools to be grouped into likely hydraulic mechanisms; a 940 representative subset of these can be instrumented and sampled to provide time series of water levels 941 942 (groundwater and surface water) and hydrochemistry to understand the pool water balance.



949 Such potential pitfalls can be found in all single methods. Thus, we suggest an initial regional-scale
 950 assessment of landscape position and hydrogeological context that allows for pools to be grouped into
 951 likely hydraulic mechanisms; a representative subset of these can be instrumented and sampled to
 952 provide time series of water levels (groundwater and surface water) and hydrochemistry to understand
 953 the pool water balance.

954

All of the above points can be seen <u>This was our approach</u> in the Hammersley Basin <u>and the above</u>
 points can be seen in our results. We were able to identify key hydraulic mechanisms supporting pool

957 persistence at a number of pools at regional and local scale. However, the saptio-temporally variable 958 components of the water balance remain difficult to constrain. Although there is a lot of data in the 959 region overall, given the remote and inaccessible nature of these pools, none of them have a complete data set of the kind advocated for here. It should be noted that as with every field study, these case 960 961 studies do not represent perfect examples of the hypothetical cases but are instead limited by typical 962 considerations found in the real world and are subject to ongoing research efforts. In particular, Ben's 963 Oasis provides an example of a pool that is particularly difficult to characterise and cannot simply be 964 linked to one hydraulic mechanism. Efforts to characterise the bathymetry of Ben's Oasis have been 965 fraught with challenges, and the relationship between water level and pool volume remains uncertain, 966 limiting our efforts to confidently determine the water balance.

967 In this work, we have striven to provide a useful framework, based on a conceptual, first-principles 968 understanding, supported by both useful tools and case studies. However, this has also resulted in 969 limitations. Each of these topics could be presented as a full study. The list of field and regional-scale 970 methods is not exhaustive, but instead presents the most commonly used and accessible tools. Various 971 other tools, such as geophysical surveys and varied geochemical tracers, could easily be employed to 972 garner additional data useful in further understanding in-stream pool hydrology. Moreover, the review 973 of supporting literature, in particular from the field of groundwater-surface water interactions, has been 974 necessarily concise and more could be said. However, we feel that there is utility in presenting the basic 975 background in conjunction with field tools and considerations, allowing each reader can take the parts 976 that are most relevant to their own needs and seek out further background from the cited literature as 977 needed. We hope this work serves as a common platform for a deeper understanding of in-stream pools 978 globally, as non-perennial streams are increasingly recognised for both their importance and their 979 vulnerability in our changing world.

980 The study of persistent river pools is a developing science and much remains to be done. Policy makers 981 increasingly require accurate information on the mode of occurrence of surface water pools to put 982 forward management plans to mitigate and/or minimise the adverse impacts of human activities 983 (Leibowitz et al., 2008). This framework is subject to refinement as sufficient data becomes available 984 to fully characterise pool water balances and mode of occurrence. Extension of this framework to 985 facilitate the incorporation of biological and sedimentological processes is also desirable. Persistent river pools exist in all climates across the globe, and consistent data on geomorphology, hydrology and 986 987 ecology should be collected at multiple features so that generalized patterns and processes can be 988 elucidated. The nutrient and carbon transport between pools during flows and the effects of 989 anthropogenic disruption to groundwater inputs or surface water flushes into these pools is also not well 990 known. These disruptions can be detrimental to water quality if the anthropogenic inputs are 991 contaminated (Jackson and Pringle, 2010), but may also support seasonal connectivity that benefits the 992 ecosystem by distributing nutrients and organic matter between pools (Jaeger et al., 2014). Effects of 993 climate change (e.g. lower groundwater levels, thermal loading, and altered storm cycles) also combine 994 with geomorphological and biological factors to impact ecosystem function, but these mechanisms are 995 not yet well understood.

996 7 Conclusion

997 Persistent pools are an important feature along non-perennial rivers and these types of systems are under 998 increasing pressure from altered hydrology associated with shifting climates and anthropogenic 999 activities (Steward et al., 2012). Three dominant hydraulic mechanisms that support the persistence of 1000 river pools were identified from literature on groundwater springs and groundwater - surface water 1001 interaction; perched surface water, through-flow of alluvial water, and regional groundwater discharge. 1002 Regional groundwater discharge can be further characterized into two types of control on groundwater 1003 outflow; geological barrier vs topography. While the existing literature hints at the hydrologic and 1004 geologic constraints imperative to pool persistence, the framework presented here provides cohesive 1005 synthesis of hydraulic mechanisms supporting persistence, as required to sufficiently understand and 1006 protect persistent river pools globally. Susceptibility to hydrological change depends on the

mechanism(s) of pool persistence and the spatial distribution of stressors relative to the pool. Further
research is required to resolve the impacts hydroclimatic stressors at the scale of individual pools.

1009 A suite of diagnostic tools are available for understanding the hydrologic mechanisms that support the 1010 persistence of a given river pool. A regional-scale assessment can be made based on an understanding 1011 of the pool's landscape position and hydrogeological context, which may be supported by remote 1012 sensing or image analysis. Time-series data of water levels and hydrochemistry are required to resolve 1013 the spatiotemporal variability in pool water balances, as demonstrated in the three pool-scale case studies presented. The suitability of each of these tools to any given pool or study will depend on the 1014 1015 data and resources available, and the requirement for a coarse or highly detailed resolution of the 1016 mechanisms supporting pool persistence.

1017

1018 Data Availability

1019 The data used in Section 5 of this paper are the property of Rio Tinto. Access to these data may be

1020 requested by contacting Shawan Dogramaci (shawan.dogramaci@riotinto.com)

1021

1022 Author Contribution

1023 SB and MS prepared the text of the manuscript with input from all co-authors. PH, SC, SD and SB

1024 collected and analysed the data presented in Section 5. PH and SB prepared the figures.

1025

1026 **Competing Interests**

1027 The authors declare that they have no conflict of interest.

1028

1029 Acknowledgements

51

- 1030 This paper is based on data collection funded by Rio Tinto Iron Ore and funding from the Australian
- 1031 Research Council, grant LP120100310. Author Shanafield's contribution was supported by funding
- 1032 from the Australian Research Council, grant DE150100302. We thank the editor and our several
- 1033 thorough reviewers, as well as the colleagues who have already found this framework useful and
- 1034 encouraged us to finalise it.

1035 **References**

- Alaibakhsh, M., Emelyanova, I., Barron, O., Khiadani, M., and Warren, G. Large-scale regional delineation of
 riparian vegetation in the arid and semi-arid Pilbara region, WA, Hydrological Processes, 31, 4269-4281,
 2017.
- Alfaro, C., and Wallace, M. Origin and classification of springs and historical review with current applications,
 Environ Geol, 24, 112-124, 10.1007/bf00767884, 1994.
- Arthington, A. H., Balcombe, S. R., Wilson, G. A., Thoms, M. C., and Marshall, J. Spatial and temporal variation
 in fish-assemblage structure in isolated waterholes during the 2001 dry season of an arid-zone floodplain river,
- 1043 Cooper Creek, Australia, Mar Freshwater Res, 56, 25-35, https://doi.org/10.1071/MF04111, 2005.
- Ashley, G. M., Goman, M., Hover, V. C., Owen, R. B., Renaut, R. W., and Muasya, A. M. Artesian blister wetlands, a perennial water resource in the semi-arid rift valley of East Africa, Wetlands, 22, 686-695, 2002.
- Banks, E. W., Shanafield, M. A., Noorduijn, S., McCallum, J., Lewandowski, J., and Batelaan, O. Active heat
 pulse sensing of 3-D-flow fields in streambeds, Hydrol. Earth Syst. Sci., 22, 1917-1929, 10.5194/hess-221048 1917-2018, 2018.
- Befus, K. M., Cardenas, M. B., Ong, J. B., and Zlotnik, V. A. Classification and delineation of groundwater–lake
 interactions in the Nebraska Sand Hills (USA) using electrical resistivity patterns, Hydrogeology Journal, 20,
- 1051 1483-1495, 10.1007/s10040-012-0891-x, 2012.
- Bense, V. F., Gleeson, T., Loveless, S. E., Bour, O., and Scibek, J. Fault zone hydrogeology, Earth-Science
 Reviews, 127, 171-192, https://doi.org/10.1016/j.earscirev.2013.09.008, 2013.
- Bestland, E., George, A., Green, G., Olifent, V., Mackay, D., Whalen, M. Groundwater dependent pools in
 seasonal and permanent streams in the Clare Valley of South Australia. J. Hydrol. Regional Studies, 9, 216235. 2017.
- Bishop-Taylor, R., Tulbure, M.G.,Broich, M. Surface-water dynamics and land use influence landscape
 connectivity across a major dryland region. Ecological Applications, 27(4), 1124-1137, 2017,
 https://doi.org/10.1002/eap.1507.

- Blackburn, J., Comte, J., Foster, G., Gibbins, C. Hydrogeological controls on the flow regime of an ephemeral
 temperate stream flowing across an alluvial fan. Journal of Hydrology, 595, 125994, 2021,
 https://doi.org/10.1016/j.jhydrol.2021.125994.
- Bogan, M. T., and Lytle, D. A. Severe drought drives novel community trajectories in desert stream pools,
 Freshwater Biology, 56, 2070-2081, 10.1111/j.1365-2427.2011.02638.x, 2011.
- 1065 Bonada, N., Cañedo-Argüelles, M., Gallart, F., von Schiller, D., Fortuño, P., Latron, J., Llorens, P., Murria, C.,
- Soria, M., Vinyoles, D., Cid, N. Conservation and management of isolated pools in temporary rivers, Water,
 12 (10) 2870, https://doi.org/10.3390/w12102870, 2020.
- Boulton, A.J. Parallels and contrasts in the effects of drought on stream macroinvertebrate assemblages.
 Freshwater Biology, 48, 1173-1185. https://doi.org/10.1046/j.1365-2427.2003.01084.x, 2003
- Bourke S.A., Cook P.G., Shanafield M., Dogramaci S., Clark J.F. Characterisation of hyporheic exchange in a
 losing stream using radon-222. Journal of hydrology, 519, 94-105, 2014a
 https://doi.org/10.1016/j.jhydrol.2014.06.057
- Bourke, S. A., Harrington, G. A., Cook, P. G., Post, V. E., and Dogramaci, S. Carbon-14 in streams as a tracer of
 discharging groundwater, Journal of Hydrology, 519, 117-130, 2014b.
 http://dx.doi.org/10.1016/j.jhydrol.2014.06.056, 2014.
- Bourke, S. A., Cook, P. G., Dogramaci, S., and Kipfer, R. Partitioning sources of recharge in environments with
 groundwater recirculation using carbon-14 and CFC-12, Journal of Hydrology, 525, 418-428, 2015.
- Bourke, S.A., Degens, B., Searle, J., de Castro Tayer, T., Rother, J. Geological permeability controls streamflow
 generation in a remote, ungauged, semi-arid drainage system. J. Hydrol. Regional Studies, 38, 100956, 2021.
- Brodie, R.S., Kilgour, B., Jacobson, G., Lau, J.E. 2019. Hydrogeology Map of Australia (G.Jacobson and JE.Lau
 Hydrogeology Map). Geoscience Australia, Canberra. http://pid.geoscience.gov.au/dataset/ga/32368
- 1082 Briggs, M. A., Hare, D. K., Boutt, D. F., Davenport, G., and Lane, J. W. Thermal infrared video details multiscale
- 1083 groundwater discharge to surface water through macropores and peat pipes, Hydrological Processes, 30, 2510-
- 1084 2511, 10.1002/hyp.10722, 2016.
- Brunner, P., Cook, P., and Simmons, C. Hydrogeologic controls on disconnection between surface water and
 groundwater, Water Resources Research, 45, W01422, 2009.
- 1087 Bryan, K.: Classification of springs, The Journal of Geology, 27, 522-561, 1919.

- Bunn, S. E., Thoms, M. C., Hamilton, S. K., and Capon, S. J. Flow variability in dryland rivers: boom, bust and the bits in between, River Research and Applications, 22, 179-186, 10.1002/rra.904, 2006.
- Caldwell, T.G., Wolaver, B.D., Bongiovanni, T., Pierre, J.P., Robertson, S., Abolt, C., Scanlon, B.R. Spring
 discharge and thermal regime of a groundwater dependent ecosystem in an arid karst environment, J. Hydrol.,
 587, 124947, 2020.
- Cardenas, M. B., Neale, C. M. U., Jaworowski, C., and Heasler, H. High-resolution mapping of riverhydrothermal water mixing: Yellowstone National Park, International Journal of Remote Sensing, 32, 27652777, 10.1080/01431161003743215, 2011.
- 1096 Cardenas, M.B., Wilson, J.L. Exchange across a sediment-water interface with ambient groundwater discharge.

1097 Journal of hydrology, 346(3-4), 69-80, 2007, https://doi.org/10.1016/j.jhydrol.2007.08.019.

- Chapman, S. Groundwater discharge to persistent in-stream pools in dryland regions. Master Thesis, School of
 Earth Sciences, University of Western Australia, 2019.
- Conant, B. Delineating and quantifying ground water discharge zones using streambed temperatures, Ground
 Water, 42, 243-257, 2004.
- Cook, P. G., Jolly, I. D., Walker, G. R., & Robinson, N. I. From drainage to recharge to discharge: Some timelags
 in subsurface hydrology. Developments in water science, 50, 319-326, 2003.
- 1104 Cook, P. G., Wood, C., White, T., Simmons, C. T., Fass, T., and Brunner, P. Groundwater inflow to a shallow,
- poorly-mixed wetland estimated from a mass balance of radon, Journal of Hydrology, 354, 213-226,
 http://dx.doi.org/10.1016/j.jhydrol.2008.03.016, 2008.
- Cook, P. G. Estimating groundwater discharge to rivers from river chemistry surveys, Hydrological Processes,
 27, 3694-3707, 10.1002/hyp.9493, 2013.
- 1109 Cook, P. G., and Dogramaci, S. Estimating Recharge From Recirculated Groundwater With Dissolved Gases: An
- 1110 End-Member Mixing Analysis, Water Resources Research, 55, 5468-5486, 10.1029/2019wr025012, 2019.
- 1111 Costigan, K.H., Daniels, M.D., Dodds, W.K. Fundamental spatial and temporal disconnections in the hydrology
- of an intermittent prairie headwater network. J. Hydrol. 522, 305–316.
 https://doi.org/10.1016/j.jhydrol.2014.12.031, 2015.

- 1114 Costigan, K. H., Jaeger, K. L., Goss, C. W., Fritz, K. M., & Goebel, P. C. Understanding controls on flow
- 1115 permanence in intermittent rivers to aid ecological research: integrating meteorology, geology and land cover.
- 1116 Ecohydrology, 9(7), 1141–1153. https://doi.org/10.1002/eco.1712, 2016.
- Cranswick, R.H., Cook, P.G., Scales and magnitude of hyporheic, river-aquifer and bank storage exchange fluxes,
 Hydrological Processes, 29(14) 3084-3097, 2015.
- Cushing, C. E., and Wolf, E. G.: Primary production in Rattlesnake Springs, a cold desert spring-stream,
 Hydrobiologia, 114, 229-236, 10.1007/bf00031874, 1984.
- Cuthbert, M.O., Gleeson, T., Reynolds, S.C., Bennett, M.R., Newton, A.C., McCormack, C.J., Ashley, G.M.
 Modelling the role of groundwater hydro-refugia in East African hominin evolution and dispersal, Nature
- 1123 Communications, 8(1), 1-11, 2017.
- Cuthbert, M.O., Gleeson, T., Moosdorf, N., Befus, K.M., Schneider, A., Hartmann, J., Lehner, B. Global patters
 and dynamics of climate-groundwater interactions, Nature Climate Change, 9, 137-141, 2019.
- Davis, L., Thoms, M. C., Fellows, C., and Bunn, S.: Physical and ecological associations in dryland refugia:
 waterholes of the Cooper Creek, Australia, International Association of Hydrological Sciences, Publication,
 276, 77-84, 2002.
- Deemy, J. B., and Rasmussen, T. C. Hydrology and water quality of isolated wetlands: Stormflow changes along
 two episodic flowpaths, Journal of Hydrology: Regional Studies, 14, 23-36,
 https://doi.org/10.1016/j.ejrh.2017.10.001, 2017.
- DelVecchia A.G., Shanafield M., Zimmer M.A., Busch M.H., Krabbenhoft C.A., Stubbington R., Kaiser K.E.,
 Burrows R.M., Hosen J., Datry T., Kampf S.K. Reconceptualizing the hyporheic zone for nonperennial rivers
- 1134 and streams. Freshwater Science. 2022 Jun 1;41(2), https://doi.org/10.1086/720071.
- Doble, R., Brunner, P., McCallum, J., Cook, P.G. An analysis of river bank slope and unsaturated flow effects on
 bank storage, Groundwater, 50, 77-86, https://doi.org/10.1111/j.1745-6584.2011.00821.x, 2012
- 1137 Dogramaci, S., Skrzypek, G., Dodson, W., Grierson, P.F. Stable isotope and hydrochemical evolution of
- groundwater in the semi-arid Hamersley Basin of subtropical northwest Australia, J. Hydro., 475, 281-293,
- 1139 2012.

- Dogramaci, S., Firmani, G., Hedley, P., Skrzypek, G., & Grierson, P. F. Evaluating recharge to an ephemeral
 dryland stream using a hydraulic model and water, chloride and isotope mass balance. Journal of Hydrology,
 521, 520-532. 2015
- Dogramaci S. Springs, pools and seeps in the Hamersley Basin, NW Australia, internal report for Rio Tinto Iron
 Ore, 2016.
- 1145 Fellman, J. B., Dogramaci, S., Skrzypek, G., Dodson, W., and Grierson, P. F. Hydrologic control of dissolved
- organic matter biogeochemistry in pools of a subtropical dryland river, Water Resour. Res., 47, W06501,
 10.1029/2010wr010275, 2011.
- 1148 Fetter, C.W. Applied hydrogeology (Fourth Edition). Prentice Hall, Upper Saddle River, USA, 2001.
- 1149 Finn, M., and Jackson, S. Protecting Indigenous Values in Water Management: A Challenge to Conventional
- 1150 Environmental Flow Assessments, Ecosystems, 14, 1232-1248, 10.1007/s10021-011-9476-0, 2011.
- 1151 Fitts, C. R. Groundwater science. Elsevier, 2002.
- Gardener, W.P., Harrington, G.A., Solomon, D.K., Cook, P.G. Using terrigenic 4He to identify and quantify
 regional groundwater discharge to streams, Water Resources Research, 47, W06523,
 doi:10.1029/2010WR010276, 2011.
- Geological Survey of Western Australia (GSWA). Hydrogeological Map of Western Australia. Department of
 Mines, Industry Regulation and Safety, Government of Western Australia, 2015.
- Gibson, J.J. Short-term evaporation and water budget comparisons in shallow Arctic lakes using non-steady
 isotope mass balance. Journal of Hydrology, 264(1-4), 242-261, 2002.
- Godsey, S. E., and Kirchner, J. W. Dynamic, discontinuous stream networks: hydrologically driven variations in
 active drainage density, flowing channels and stream order, Hydrological Processes, 28, 5791-5803,
 10.1002/hyp.10310, 2014.
- Goodrich, D. C., Kepner, W. G., Levick, L. R., and Wigington Jr., P. J. Southwestern Intermittent and Ephemeral
 Stream Connectivity, JAWRA Journal of the American Water Resources Association, 54, 400-422,
 10.1111/1752-1688.12636, 2018.
- - Gutiérrez-Jurado, K.Y., Partington, D., Batelaan, O., Cook, P., Shanafield, M. What Triggers Streamflow for
 Intermittent Rivers and Ephemeral Streams in Low-Gradient Catchments in Mediterranean Climates. Water
 - 57

- 1167 Resour. Res. 55, 9926–9946. https://doi.org/10.1029/2019WR025041, 2019.
- Haas, E. M., Bartholomé, E., and Combal, B. Time series analysis of optical remote sensing data for the mapping
 of temporary surface water bodies in sub-Saharan western Africa, Journal of Hydrology, 370, 52-63,
 https://doi.org/10.1016/j.jhydrol.2009.02.052, 2009.
- 1171 Hamilton, S. K., Bunn, S. E., Thoms, M. C., and Marshall, J. C. Persistence of aquatic refugia between flow pulses
- 1172 in a dryland river system (Cooper Creek, Australia), Limnology and Oceanography, 50, 743-754, 2005.
- Harrington, G. A., Payton Gardner, W., and Munday, T. J. Tracking Groundwater Discharge to a Large River
 using Tracers and Geophysics, Groundwater, 2013.
- Herczeg, A.L. and Leaney, F.W. Environmental tracers in arid-zone hydrology. Hydrogeology Journal, 19(1), 1729, 2011, https://doi.org/10.1007/s10040-010-0652-7.
- Huang, J., Chunyu, X., Zhang, D., Chen, X., Ochoa, C.G. A framework to assess the impact of eological water
 conveyance on groundwater-dependent terrestrial ecosystems in arid inland river basins, Sci. Tot. Env., 709,
 136155, 2020.
- 1180 IPCC, 2021 Climate Change 2021: The Physical Science Basis. Contribution of Working Group I to the Sixth
- 1181 Assessment Report of the Intergovernmental Panel on Climate Change [Masson-Delmotte, V., P. Zhai, A.
- 1182 Pirani, S. L. Connors, C. Péan, S. Berger, N. Caud, Y. Chen, L. Goldfarb, M. I. Gomis, M. Huang, K. Leitzell,
- 1183 E. Lonnoy, J. B. R. Matthews, T. K. Maycock, T. Waterfield, O. Yelekçi, R. Yu and B. Zhou (eds.)].
- 1184 Cambridge University Press. In Press.
- Jackson, C.R., Pringle, C.M. Ecological benefits of reduced hydrologic connectivity in intensively developed
 landscapes. BioScience, 60(1), 37-46, 2010, https://doi.org/10.1525/bio.2010.60.1.8.
- Jaeger, K., Olden, J. Electrical resistance sensor arrays as a means to quantify longitudinal connectivity of rivers,
 River Research and Applications, 2011.
- Jaeger, K. L., Olden, J. D., and Pelland, N. A. Climate change poised to threaten hydrologic connectivity and
 endemic fishes in dryland streams, Proceedings of the National Academy of Sciences, 111, 13894-13899,
 2014.
- John, K. R. Survival of Fish in Intermittent Streams of the Chiricahua Mountains, Arizona., Ecology, 45, https://doi.org/10.2307/1937112, 1964.

- Jocque, M., Vanschoenwinkel, B. and Brendonck, L.U.C. Freshwater rock pools: a review of habitat
 characteristics, faunal diversity and conservation value. Freshwater Biology, 55(8), 1587-1602, 2010.
- Kalbus, E., Reinstorf, F., and Schirmer, M. Measuring methods for groundwater–surface water interactions: a
 review. Hydrology and Earth System Sciences, 10(6), 873-887, 2006.
- 1198 Käser, D.H., Binley, A., Heathwaite, A.L., Krause, S. Spatio-temporal variations of hyporheic flow in a riffle-
- step-pool sequence. Hydrological Processes: An International Journal, 23(15), 2138-2149, 2009,
 https://doi.org/10.1002/hyp.7317.
- Kelso, J. E., and Entrekin, S. A. Intermittent and perennial macroinvertebrate communities had similar richness
 but differed in species trait composition depending on flow duration, Hydrobiologia, 807, 189-206, 2018.
- Knighton, A. D., and Nanson, G. C. Waterhole form and process in the anastomosing channel system of Cooper
 Creek, Australia, Geomorphology, 35, 101-117, 2000.
- 1205 Kresic, N., and Stevanovic, Z. Groundwater Hydrology of Springs, Elsevier, 592 pp., 2010.
- Labbe, T. R., and Fausch, K. D. Dynamics of intermittent stream habitat regulate persistence of a threatened fish
 at multiple scales Ecological Applications, 10, 1774-1791, doi: 10.1890/10510761(2000)010[1774:doishr]2.0.co;2, 2000.
- Lamontagne, S, Kirby, J, Johnston, C. Groundwater–surface water connectivity in a chain-of-ponds semiarid
 river. Hydrological Processes. 35:e14129. <u>https://doi.org/10.1002/hyp.14129</u>, 2021.
- Lautz, L. K. Impacts of nonideal field conditions on vertical water velocity estimates from streambed temperature
 time series, Water Resour. Res., 46, W01509, 10.1029/2009wr007917, 2010.
- 1213 Leibowitz, S.G., Brooks, R.T. Hydrology and landscape connectivity of vernal pools. In Science and Conservation
- 1214 of Vernal Pools in Northeastern North America, Eds. Calhouh, A.J.K., deMaynadier, P.G., CRC Press: Boca
- 1215 Raton, FL, USA, pp. 31–53, 2008.
- 1216 Leibowitz, S. G., Wigington Jr, P. J., Rains, M. C., and Downing, D. M. Non-navigable streams and adjacent
- 1217 wetlands: addressing science needs following the Supreme Court's Rapanos decision, Frontiers in Ecology and
- 1218 the Environment, 6, 364-371, 2008.
- 1219 McCallum, J.L., Shanafield, M. Residence times of stream-groundwater exchanges due to transient stream stage
- 1220 fluctuations, Water Resour. Res., #2, 2059–2073, doi: 10.1002/2015WR017441.

- McJannet, D., Hawdon, A., Van Neil, T., Boadle, D., Baker, B., Trefry, M., Rea, I.: Measurement of evaporation
 from a mine void lake and testing of modelling apporaches, J. Hydrol. 555, 631-647, 2017.
- McMahon, T.A., Finlayson, B.L., Peel, M.C. Historical development of models for estimating evaporation using
 standard meteorological data, Wires Water, 3(6) 788-818, 2016.
- Manga, M. On the timescales characterizing groundwater discharge at springs, Journal of Hydrology(Amsterdam),
 219, 56-69, 1999.
- Marshall, S.K., Cook, P.G., Miller, A.D., Simmons, C.T., Dogramaci, S. The effect of undetected barriers on
 groundwater draw-down and recovery, Groundwater, 57(5), 718-726, 10.1111/gwat.12856, 2019.
- 1229 Mather, C. C., Nash, D. J., Dogramaci, S., Grierson, P. F., and Skrzypek, G. Geomorphic and hydrological controls
- on groundwater dolocrete formation in the semi-arid Hamersley Basin, northwest Australia, Earth Surface
 Processes and Landforms, 44, 2752-2770, 10.1002/esp.4704, 2019.
- Melly, B.L., Schael, D.M., Gama, P.T. Perched wetlands: An explanation to wetland formation in semi-arid areas,
 Journal of Arid Environments, 141, 34-39, https://doi.org/10.1016/j.jaridenv.2017.02.004, 2017.
- 1234 Meinzer, O. Outline of ground-water hydrology with definitions, US Geol Surv Water Suppl Pap, 494, 1923.
- 1235 Meinzer, O. E. Large springs in the United States, Washington, D.C., Report 557, 119, 1927.
- 1236 Messager, M.L., Lehner, B., Cockburn, C., Lamouroux, N., Pella, H., Snelder, T., Tocknew, K., Trautmann, T.,
- 1237 Watt, C., Datry, T. Global prevalence of non-perennial rivers and streams, Nature 594, 391-397, 2021.
- 1238 Ong, J. B., Lane, J. W., Zlotnik, V. A., Halihan, T., and White, E. A. Combined use of frequency-domain
- 1239 electromagnetic and electrical resistivity surveys to delineate near-lake groundwater flow in the semi-arid
- 1240 Nebraska Sand Hills, USA, Hydrogeology Journal, 18, 1539-1545, 10.1007/s10040-010-0617-x, 2010.
- Pearson, M.R., Reid, M.A., Miller, C., Ryder, D. Comparison of historical and modern river surveys reveal
 changes to waterhole characteristics in an Australian dryland river. Geomorphology, 356, 107089,
 https://doi.org/10.1016/j.geomorph.2020.107089, 2020.
- 1244 Pidwirny, M. Throughflow and Groundwater Storage, in Fundamentals of Physical Geography, 2nd Edition. 2006.
- 1245 Poeter, E., Fan, Y., Cherry, J., Wood, W., Mackay, D. Groundwater in our water cycle getting to know Earth's
- 1246 most important fresh water source, 136pp. Groundwater Project, Geulph, Ontario, Canada. 2020

- Ponder, W. F. Mound Springs of the Great Artesian Basin, in: Limnology in Australia, edited by: De Deckker, P.,
 and Williams, W. D., Springer Netherlands, Dordrecht, 403-420, 1986.
- 1249 Queensland Government, Queensland. Catchment constrictions, WetlandInfo website, accessed 16 June 2021.
- 1250 Available at: https://wetlandinfo.des.qld.gov.au/wetlands/ecology/aquatic-ecosystems-natural/groundwater-
- 1251 dependent/catchment-constrictions/, 2015.
- 1252 Rau, G. C., Andersen, M. S., McCallum, A. M., and Acworth, R. I. Analytical methods that use natural heat as a
- tracer to quantify surface water-groundwater exchange, evaluated using field temperature records,
 Hydrogeology Journal, 18, 1093-1110, 10.1007/s10040-010-0586-0, 2010.
- 1255 Rau,G.C., Halloran, L.J.S., Cuthbert, M.O., Andersen, M.S., Acworth, R.I., Tellam, J.H. Characterising the
- 1256dynamics of surface water-groundwater interactions in intermittent and ephemeral streams using streambed1257thermal signatures, Advances in Water Resources, 107, 354-369,
- 1258 https://doi.org/10.1016/j.advwatres.2017.07.005, 2017.
- Rayner, T. S., Jenkins, K. M., and Kingsford, R. T. Small environmental flows, drought and the role of refugia
 for freshwater fish in the Macquarie Marshes, arid Australia, Ecohydrology: Ecosystems, Land and Water
 Process Interactions, Ecohydrogeomorphology, 2, 440-453, 2009.
- Rhodes, K. A., Proffitt, T., Rowley, T., Knappett, P. S. K., Montiel, D., Dimova, N., ... Miller, G. R. The
 importance of bank storage in supplying baseflow to rivers flowing through compartmentalized, alluvial
- 1264 aquifers. Water Resources Research, 53, 10,539–10,557. <u>https://doi.org/10.1002/2017WR021619</u>, 2017.
- Roshier, D.A., Whetton, P.H., Allan, R.J., Robertson, A.I. Distribution and persistence of temporary wetland
 habitats in arid Australia in relation to climate change, Austral Ecology, 26(4) 371-384, 2001.
- Scanlon, B.R., Keese, K.E., Flint, A.L., Flint, L.E., Gaye, C.B., Edmunds, M., Simmers, I. Global synthesis of
 groundwater recharge in semiarid and arid regions, Hydrol. Process., 20, 3335-3370, 2006.
- Shanafield, M., Bourke, S.A., Zimmer, M.A. Costigan, K.H. An overview of the hydrology of non-perennial rivers
 and streams. Wiley Interdisciplinary Reviews: Water, 8(2), e1504, 2021.
- 1271 Shanafield, M. and Cook, P.G. Transmission losses, infiltration and groundwater recharge through ephemeral and
- 1272 intermittent streambeds: A review of applied methods. Journal of Hydrology, 511, 518-529, 2014,
- 1273 https://doi.org/10.1016/j.jhydrol.2014.01.068.

- 1274 Shannon, J., Richardson, R., Thornes, J. Modelling event-based fluxes in ephemeral streams. In: L. J. Bull, M. J.
- 1275 Kirkby (Eds.). Dryland Rivers: Hydrology and Geomorpohology of Semi-Arid Channels, 129-172, John Wiley
- 1276 and Sons, Chichester, England. 2002.Sharma, D., Kansal, A. Assessment of river quality models: a review.
- 1277 Reviews in Environmental Science and Bio/Technology, 12(3), 285-311, 2013, https://doi.org/10.1007/s11157-
- 1278 012-9285-8.
- Sheldon, F., Bunn, S. E., Hughes, J. M., Arthington, A. H., Balcombe, S. R. and Fellows, C. S. Ecological roles
 and threats to aquatic refugia in arid landscapes: Dryland river waterholes, Mar. Freshw. Res., 61(8), 885–
 895, doi:10.1071/MF09239, 2010.
- Shepard, W. D. Desert springs-both rare and endangered, Aquatic Conservation: Marine and Freshwater
 Ecosystems, 3, 351-359, 1993.
- Siebers, A. R., Pettit, N. E., Skrzypek, G., Fellman, J. B., Dogramaci, S., and Grierson, P. F. Alluvial ground
 water influences dissolved organic matter biogeochemistry of pools within intermittent dryland streams,
- 1286 Freshwater Biology, 61, 1228-1241, 10.1111/fwb.12656, 2016.
- 1287 Siegel, D. Reductionist hydrogeology: ten fundamental principles, Hydrol. Processes, 22, 4967-4970, 2008.
- 1288 Soti, V., Tran, A., Bailly, J.-S., Puech, C., Seen, D. L., and Bégué, A. Assessing optical earth observation systems
- 1289 for mapping and monitoring temporary ponds in arid areas, International Journal of Applied Earth Observation
- 1290 and Geoinformation, 11, 344-351, https://doi.org/10.1016/j.jag.2009.05.005, 2009.
- 1291 Springer, A. E., and Stevens, L. E. Spheres of discharge of springs, Hydrogeology Journal, 17, 83, 2009.
- Stallman, R. Steady one-dimensional fluid flow in a semi-infinite porous medium with sinusoidal surface
 temperature, Journal of Geophysical Research, 70, 2821-2827, 1965.
- Stanley, E. H., Fisher, S. G., and Grimm, N. B. Ecosystem Expansion and Contraction in Streams, BioScience,
 47, 427-435, 10.2307/1313058, 1997.
- Steward, A. L., von Schiller, D., Tockner, K., Marshall, J. C., Bunn, S. E. When the river runs dry: human and
 ecological values of dry riverbeds., Front. Ecol. Environ., 10, 202–209, 2012.
- 1298 Stonedahl, S.H., Harvey, J.W., Worman, A., Salehin, M., Packman, A.I. A multiscale model for integrating
- hyporheic exchange from ripples to meanders, Water Resour. Res., 46, W12539, 10.1029/2009wr008865,
- 1300 2010.

- Sturman, A. P., and Tapper, N. J. The weather and climate of Australia and New Zealand, Oxford University
 Press, USA, 1996.
- 1303 Theis, C. V. The source of water derived from wells, Civil Envineering, 10, 277-280, 1940.
- Thoms, M. C., and Sheldon, F. Lowland rivers: an Australian introduction, Regulated Rivers: Research &
 Management: An International Journal Devoted to River Research and Management, 16, 375-383, 2000.
- 1306 Townley, L. R., and Trefry, M. G. Surface water-groundwater interaction near shallow circular lakes: Flow
- 1307 geometry in three dimensions, Water Resources Research, 36, 935-948, 10.1029/1999wr900304, 2000.
- Van der Kamp, G. and Hayashi, M. Groundwater-wetland ecosystem interaction in the semiarid glaciated plains
 of North America. Hydrogeology Journal, 17(1), 203-214, 2009.
- 1310 Villeneuve, S., Cook, P.G., Shanafield, M., Wood, C. White, N. Groundwater recharge via infiltration through an
- ephemeral riverbed, central Australia. Journal of Arid Environments, 117, 47-58, 2015.
- 1312 Williams, W.D. and Siebert, B.D. The chemical composition of some surface waters in central Australia. Marine
- 1313 and Freshwater Research, 14(2), 166-175, 1963, https://doi.org/10.1071/MF9630166. Winter, T.C., Harvey,
- J.W., Franke, O.L., Alley, W.M. Groundwater and surface water: a single resource. USGS Circular 1139,
 1315 1998.
- Yu, S. Ngapa Kunangkul: living water, Report on the Indigenous cultural values of groundwater in the La Grange
 sub-basin. Perth, Western Australian Water and Rivers Commission, 2000.
- 1318 Zlotnik, V.A., Olaguera, F., Ong, J.B. An approach to assessment of flow regimes of groundwater-dominated
- 1319 lakes in arid environments, J. Hydrol. 371(1-4), 22-30, 2009.