

Influences of land use changes on the dynamics of water quantity and quality in the German lowland catchment of the Stör

Chaogui Lei, Paul D. Wagner, Nicola Fohrer

Department of Hydrology and Water Resources Management, Institute for Natural Resource Conservation, Kiel University, Olshausenstr. 75, 24118 Kiel, Germany

Correspondence: Chaogui Lei (cglei@hydrology.uni-kiel.de)

Abstract

Understanding the impacts of land use changes (LUCC) on the dynamics of water quantity and quality is necessary to identify mitigation measures favorable for sustainable watershed management. Lowland catchments are characterized by a strong interaction of streamflow and near-surface groundwater that intensifies the risk of nutrient pollution. In this study, we investigated the effects of long-term changes in individual land use classes on the water and nutrient balance in the lowland catchment of the upper Stör in Northern Germany. To this end, the hydrological model SWAT (Soil and Water Assessment Tool) and partial least squares regression (PLSR) were used. SWAT model runs for three different land use maps (1987, 2010, 2019) were conducted and the outputs were compared to derive changes in water quantity (i.e., evapotranspiration (ET), surface runoff (SQ), base flow (BF), and water yield (WYLD)) and quality variables (i.e., sediment yield (SED), total phosphorus (TP) and total nitrogen (TN) loads). These changes were related to land use changes at the subbasin scale using PLSR. The major land use changes that significantly affected water quantity and quality variables were related to a decrease of arable land and a respective increase of pasture and urban land during the period of 1987-2019. Changes of landscape indicators such as area size, shape, dominance, and aggregation of each land use class accounted for as much as 61%-88% (75% on average) of the respective variations in water quantity and quality variables. The aggregation, contiguity degrees, and area extent of arable land were found to be most important to control the variations in most water quantity variables. Increases of arable (PLAND_a) and urban land percent (PLAND_u) led to more TP and TN pollution, sediment export, and surface runoff. The cause-effect results of this study can provide a quantitative basis for targeting the most influential change in landscape composition and configuration to mitigate adverse impacts on water quality in the future.

1 Introduction

Good water quality and quantity are essential for enhancing ecological stability and diversity, and both of which play important roles in maintaining sustainable agricultural or economic development and human health (Lu et al., 2015; Singh et al., 2017; Antolini et al., 2020; Gleick, 2000; Srinivasan and Reddy, 2009). The water resources dynamics within a catchment are mainly governed by a combination of climate and land use, as other catchment characteristics (e.g., topography, soil, and lithology) usually do not change on a short term (Shuster et al., 2005; Farjad et al., 2017; Wagner et al., 2018). Vice versa, hydrology affects land use as well (Wagner and Fohrer, 2019; Wagner and Waske, 2016). In the past three decades, land use changes with respect to urbanization, deforestation, and agriculture intensification have exerted significant effects on water quality or water balance components (Wagner et al., 2016; Shrestha et al., 2018; Kändler et al., 2017). They can alter surface roughness, evapotranspiration, soil infiltration, and the interaction between surface and subsurface water (Fiener et al., 2011; Wei et al., 2007; Lei et al., 2021), and promote or hinder generation and transportation of soil particles, chemicals, or metals (Nafi'shehab et al., 2021; Taka et al., 2022; Ding et al., 2016). Given the direct and indirect effects of land use changes on hydrological processes and contaminant inputs, it is of great practical significance to identify key predictor variables, to achieve an effective catchment management of land and water resources.

Earlier studies have often aimed at analyzing land use change effects using lumped indicators of landscape composition, e.g., areal percentage of a land use class in the catchment (Kumar et al., 2022; Lei et al., 2021). However, composition indicators do not convey any details with respect to spatial settings of landscape patterns. The configuration of the spatial land use distribution is another fundamental element measured using landscape metrics (i.e., metrics to quantify the spatial structure of land use patterns within a defined geographic area). Compared to the composition indicators that refers to the abundance (e.g., areal percent) of land patches (i.e., homogenous areas of the landscape) (Hesselbarth et al., 2019) belonging to one certain class without considering their spatial characteristics, landscape configuration metrics describe spatial fragmentation or distribution of patches, e.g., the shape complexity. Landscape configuration metrics of the dominance, diversity, shape, aggregation, and interconnection of land patches play a critical part in determining the energy and matter fluxes of e.g., solar radiation, temperature, evapotranspiration, surface runoff, nutrients, and sediments from the landscape ecology perspective (Forman, 1995; Wu and Lu, 2021; Lei et al., 2019; Amiri and Nakane, 2009). They were found to be more important as descriptors of water quality than composition indicators in some case studies: E.g., Ding et al. (2016) observed that poorer water quality was not as much associated with areal percentage as with higher patch densities (PD) of cropland, orchards and grassland and a higher value of largest patch index (LPI) of urban land, in a low-order streams dominated catchment (drainage area: 35,340 km²) in southeastern China. Despite little consideration of landscape configuration in the studies of water quantity (Shrestha et al., 2018; Anand et al., 2018), the shape, dominance or connectivity degree of land patches is closely linked to the modification of the hydrological cycle. For example, more fragmented forest patches may favor funneling of precipitation (Ghimire et al., 2017); hardness and straightness of land patches of farmland, urban, and natural land uses influence streamflow rates at different magnitudes and directions (Riitters, 2019; Shi et al., 2013); more concentrated grassland patches result in greater evapotranspiration (Yu et al., 2020). Therefore, it is necessary to assess influences of changes in different aspects of a land use class to better understand their impacts on water resources dynamics.

To quantify effects of land use changes on water resources, hydrological models are widely used (Gabriels et al., 2021; Idrissou et al., 2022; Wijesekara et al., 2012), e.g., SWAT (Soil and Water Assessment Tool) (Arnold et al., 1998), HSPF (Hydrological Simulation Program-Fortran) (Bicknell et al., 2001), or DHSVM (Distributed Hydrology-Soil Vegetation Model) (Wigmosta et al., 1994). Models are particularly useful to detect historic as well as future land use change impacts applying a scenario analysis (Aredo et al., 2021; Anand et al., 2018). As a physically-based and semi-distributed hydrological model, SWAT has proven its suitability for an integrated modeling of water, sediment, and nutrient dynamics in different-sized rural catchments (Aghsaei et al., 2020; Tan et al., 2021). SWAT has been applied in many catchments worldwide to investigate the hydrological and hydro-chemical effects (Amin et al., 2020; Boongaling et al., 2018; Anand et al., 2018). In lowland areas, the transport of water and nutrients is strongly influenced by flat topography and shallow groundwater tables in addition to the spatially heterogenous land use. The hydrological model SWAT has proven its suitability to model eco-hydrological consequences of spatio-temporal land use changes in lowland catchments (Guse et al., 2014; Pott and Fohrer, 2017b). Particularly in several lowland catchments in northern Germany, SWAT was extensively tested in impact studies. E.g., Lam et al. (2012) modeled the long-term observations of daily streamflow and nitrate load in the Kielstau catchment and found that diffuse source pollution (dominated by agriculture) contributed dominantly (95%) to nitrate load; In the Upper Stör catchment, Song et al. (2015) coupled SWAT with HEC-RAS to analyze temporal dynamics of sediment loads in subbasins covered by heterogenous land use conditions. Despite a high feasibility of SWAT modelling water quantity and quality, previous studies illustrated that the original SWAT version sometimes performed relatively poor for recession limbs and low flow periods of streamflow (Guse et al., 2014; Pfannerstill et al., 2014). In lowland catchments, groundwater contributes significantly to low flows and thus becomes a dominant component of streamflow (Pott and Fohrer, 2017b). To more accurately model low flows, an enhanced version of SWAT, SWAT_{3S}, was developed in the Kielstau catchment, by conceptually separating the shallow groundwater aquifer of the original SWAT into a fast and slow shallow aquifer (Pfannerstill et al., 2014). SWAT_{3S} was successfully used for modelling daily streamflow and nitrogen loads in a few German lowland catchments (e.g., Kielstau and Treene) by improving the representation of low flow periods (Pfannerstill et

al., 2014; Haas et al., 2017). Given the aforementioned strength, SWAT_{3S} is suitable for assessing the impacts of land use changes on water resources in lowland areas dominated by groundwater recharge.


85 While the changes in landscape composition and configuration have a great potential of influencing hydrology, soil erosion or water quality dynamics at different spatial and seasonal scales (Jones et al., 2001; Kändler et al., 2017; Haidary et al., 2013), some landscape metrics may have a high probability for collinearity. The collinear landscape metrics carry redundant information and are not independent predictor variables (Hargis et al., 1998). They can therefore result in biased or even misleading results when using conventional multivariate regression techniques like ordinary least-square regression, particularly in the case of a small number of observations (Shi et al., 2013; Shawul et al., 2019). Compared to ordinary 90 multivariate statistical methods, partial least squares regression analysis (PLSR) can overcome the limitation of multicollinearity and achieve a robust performance by using techniques of multivariate statistical projection (Shi et al., 2013). Based on the powerful technique of projecting predicted and observed variables onto a new space and estimating the underlying structure between projected spaces, PLSR facilitates an unbiased analysis of “cause-effect” relationships between 95 land use changes and water resources components (Shi et al., 2013; Yan et al., 2013; Ferreira et al., 2017). Using an integrated approach of PLSR and hydrological modelling with SWAT, impacts of the land use changes on various water resources components can be effectively identified. E.g., in the Upper Du catchment, China, Yan et al., (2013) observed that the farmland positively influenced streamflow and sediment yield, whereas forest area showed negative correlation with them; besides, urban expansion would cause streamflow to increase as well. Shi et al., al (2013) indicated that the landscape 100 metrics e.g., Shannon’s diversity index (SHDI), aggregation index (AI), largest patch index (LPI), contagion (CONTAG), and patch cohesion index (COHESION) were important to control soil erosion and sediment yield, contributing 65% and 74% to their variations at subbasin level, respectively. Gashaw et al. (2018) anticipated that more shrubland would cause water yield and surface runoff to decrease while evapotranspiration and groundwater flow to rise, however, increased cultivated land would result in decreases of groundwater flow and evapotranspiration in Blue Nile Basin, Ethiopia. In summary, it has 105 been demonstrated that PLSR is efficient to distinguish the complex impacts on water quantity and quality.

The Stör River is the longest tributary of the Elbe River in the northernmost federal state of Germany, Schleswig-Holstein. Intensive agricultural activities (e.g., grazing, tillage, fertilizer, and pesticide application) are common in the catchment and increase the risk of water quality pollution (Monaghan et al., 2007). A variety of amelioration measures, e.g., tile drainage and straightening or canalizing of tributaries have been implemented in the past century to sustain agriculture productivity in 110 lowland areas dominated by shallow groundwater tables and abundant groundwater recharge. These activities brought about changes in the input and transport of nutrients and in hydrological fluxes. Meanwhile, the heterogeneity of the landscape pattern has been intensified due to artificial disturbances (Gu et al., 2007; Goldewijk and Ramankutty, 2004). We previously found significant relationships between land use patterns and water quality parameters at the landscape level in the upper Stör Catchment based on measurements (Lei et al., 2021). A modeling approach allows to model the quantitative 115 contribution of land use changes on water quality and quantity, and facilitates developing informed and practicable strategies for sustainable land and water management (Ripl et al., 1996; Pott, 2014).

To identify the key land use changes controlling the spatial and temporal variations in water quantity and quality, relationships between landscape characteristics of each land use class and water quality (represented by sediment, TP and TN) and quantity (represented by evapotranspiration, surface runoff, base flow, and water yield) were explored at the 120 subbasin scale in the upper Stör Catchment. To this end, the hydrological model SWAT and partial least squares regression (PLSR) were employed. The study aims at (1) calibrating and validating a catchment model for streamflow, sediment, TP, and TN loads; (2) quantifying the changes of landscape characteristics and water quality and quantity variables at the subbasin scale; (3) investigating the relationships (depicted by the contribution and influence) between LUCC and water quality and quantity dynamics at the subbasin scale.

2.1 Study area

The rural lowland catchment of the upper Stör is the focus of this study (Figure 1). It extends from the origin of the Stör River in Willingrade to the gauge in Willenscharen (Figure 1) and is free of tidal influence. The catchment has a drainage area of approximately 462 km², with a total length of the river network of about 221 km. Its temperate climate is characterized by an average annual precipitation of 850 mm and a mean temperature of 9.4 °C between 1990 and 2019, according to the records by weather stations Neumünster and Padenstedt (Dwd, 2020b). The average daily streamflow measured at the catchment outlet in Willenscharen is 5.8 m³ s⁻¹ between 1990 and 2019, with low flows (mean value: 3.8 m³ s⁻¹) in summer (May-October) and high flows (mean value: 7.9 m³ s⁻¹) in winter (November-April) (Lkn, 2020). Discharge occurring in the highest flow period (December-March) contributes most (around 50%) to the total annual amount of streamflow. The catchment is characterized by a flat topography, descending from nearly 60 m a.s.l. in the northeast and 85 m in the western part towards 20 m in the center and to 5-10 m in the southern part. Sandy soil (Cambisol, Gley-Podsol, Podsol) dominates the catchment, particularly in the central lowland part, while some Gley soils are mainly distributed in the east and peat soils can be found in proximity to streams and near two major wetlands (Pott and Fohrer, 2017a). The catchment is dominated by rural land use composed of arable land (36.1%) and pasture (31.3%), followed by forest (18.7%), urban areas (12.8%), and a minor fraction of water and wetland as indicated by a land use map for 2019 (Lei et al., 2021). The main cultivated crops include winter cereals (wheat, barley, and rye), corn, and rapeseed.



145 **Figure 1. Characteristics of the study area: location of the upper Stör Catchment (a), spatial distributions of topography (b) (Lverma, 2008) and soil types (c) (Finnern, 1997), of subbasins, weather and gauging stations, and waste water treatment plants (WWTPs) (d) (Pott, 2014), as well as land use maps (e) (Ripl et al., 1996; Rathjens et al., 2014; Lei et al., 2021).**

2.2 Land use data and landscape metrics

Land use maps for 1987, 2010, and 2019 were used to characterize changes in land use and landscape patterns. The earlier two maps (1987, 2010) were adapted from Ripl et al. (1996) and Rathjens et al. (2014), respectively, and were based on

Landsat TM-5 image data at 30 m resolution. The land use map for 2019 was derived from 10 m resolution Sentinel-2 satellite images (Lei et al. 2021). The land use classes were categorized uniformly as: 1) arable land (winter cereals, corn, and winter rape, and other crops), 2) pasture (meadow, field grass, and rangeland); 3) forest (deciduous and coniferous forest); 4) urban (residential, commercial and industrial areas); 5) water (rivers, ponds, and lakes) and 6) wetland (Figure 1). Water and wetland are not considered for further analysis, as they comprise only minor and mostly constant percentages. The area percentage of land use class (PLAND) is used as a measure of land use composition. Configuration metrics include the largest patch index (LPI), area-weighted mean shape index (AWMSI), area-weighted mean contiguity index (CONTIGAW), aggregation index (AI), and interspersed juxtaposition index (IJI), considering the dominance, shape, and interconnection of landscape (Ding et al., 2016; G énesi et al., 2011). Composition and configuration indices of pasture, arable land, forest and urban were selected for subsequent analysis (Table 1). They were derived with the help of the software FRAGSTATS 4.2. All indices and their changes were analyzed at subbasin scale.

Table 1. Description of the landscape metrics selected for the study.

Attributes	Metrics	Unit	Description	Abbreviation at class level	Note
Composition	Percentage of land use (PLAND)	%	Areal percentage of land use classes	PLAND _a , PLAND _p , PLAND _f , PLAND _u	
Configuration	Largest patch index (LPI)	%	Percentage of the landscape composed of the largest patch	LPI _a , LPI _p , LPI _f , LPI _u	
	Area-weighted mean shape index (AWMSI)	-	The sum of the mean shape index multiplied by the area weight of each patch type involving the corresponding class	AWMSI _a , AWMSI _p , AWMSI _f , AWMSI _u	Metrics for land use class <i>a</i> (refers to arable land), <i>p</i> (refers to pasture), <i>f</i> (refers to forest), <i>u</i> (refers to urban)
	Aggregation index (AI)	%	Number of the same patch type being adjacent divided by the maximum number of adjacencies for the corresponding land use class	AI _a , AI _p , AI _f , AI _u	
	Area-weighted mean contiguity index (CONTIGAW)	-	Measure of the patch shape based on the sum of spatial connectedness multiplied by the area weight of the patch for a certain class	CONTIGAW _a , CONTIGAW _p , CONTIGAW _f , CONTIGAW _u	
	Interspersed juxtaposition index (IJI)	%	Measure of patch adjacency and interspersed or intermixing of patch types for a class	IJI _a , IJI _p , IJI _f , IJI _u	

2.3 Hydrological and water quality modeling

2.3.1 SWAT model

The Soil and Water Assessment Tool (SWAT) is a process-based and semi-distributed hydrological model with a continuous time step (Arnold et al., 1998). It is suitable for the simulation of streamflow, sediment, nutrients, and groundwater dynamics in catchments of different sizes (Aghsaei et al., 2020; Tigabu et al., 2020; Bieger et al., 2014; Haas et al., 2016). The computation of water routing, nutrient cycles and soil erosion is based on hydrologic response units (HRUs) characterized by the same land use, soil type, and slope in the same subbasin representing the spatial heterogeneity of the catchment (Arnold et al., 2013). The HRU-based calculations for the subbasins are routed through the rivers that connect the subbasins (Neitsch et al., 2011).

To accurately represent groundwater dynamics in this lowland catchment, we applied SWAT_{3S}, an enhanced SWAT model based on SWAT 2012 Rev. 582 (Pfanterstill et al., 2014). In comparison to the standard SWAT model application that uses two aquifers, SWAT_{3S} employs three aquifers by subdividing the original shallow aquifer from SWAT into a fast and a slow aquifer. SWAT_{3S} was developed in the German lowland catchment of the Kielstau, to better represent low flow periods of streamflow and groundwater storage and flow dynamics when compared to the original SWAT version (Pfanterstill et al., 2014). It was also successfully applied to the lowland catchment of the Treene, proving its usefulness for modelling nutrients as well (Haas et al., 2016; Haas et al., 2017).

2.3.2 Model databases and setup

SWAT requires topography, soil, land use, hydro-meteorological input data. Topography data was obtained from a Digital Elevation Model (DEM) in 5 m resolution (Lverma, 2008) and used to delineate the watershed into 21 subbasins. Soil data and attributes for SWAT were derived by Pott and Fohrer (2017b) from a soil type map (Finnern, 1997). The land use map

for 2019 was used to build the model. Three-year crop rotations (winter wheat/winter wheat/corn; winter rape/winter wheat/corn; corn/corn/corn) were adapted from Oppelt et al. (2012) and implemented for the respective land use classes. Agriculture management schedules and fertilization (e.g., application rates of N, P fertilizers and manure at different crop growth stages) were determined according to the actual guidelines of agriculture practices (Lwk, 1991 and 2011; Ktbl, 1995 and 2008; Kühling, 2011). From the DEM a four slope classes (<1%, 1-2%, 2-5% and >5%) were defined. Slope, soil, and land use classes were combined to obtain 3618 HRUs in the catchment. The HRUs were generated without excluding any HRUs by thresholds for land use, soil, or slope class percentages, to allow for a better spatial representation. To accurately represent lowland hydrology, drainage tiles were considered based on the estimated distribution of drained areas in the catchment (Venohr, 2000). We adapted drainage parameter values for DEP_IMP (1200 mm), DDRAIN (875 mm), TDRAIN (24 h), and GDRAIN (61 h) from a previous modeling study in the catchment (Pott and Fohrer, 2017b). Waste water treatment plants (WWTP) were implemented as point sources using data from monthly measurement campaigns in 2009 and 2010 and WWTP data vary with space and seasons (Pott, 2014). Daily values of temperature (max. and min), solar radiation, humidity, and wind speed are available from 1990 to 2019 for the climate station Padenstedt (Dwd, 2020a). Precipitation data are available for four stations (Dwd, 2020a) (Figure 1). Daily streamflow was measured at the gauges in Padenstedt (PAD), Sarlhusen (SAR) and Willenscharen (WIL) from 1990 to 2019 (Lkn, 2020). Daily sediment and nutrient data were both obtained during two measurement campaigns, i.e., August 2009 - August 2011 and October 2018 - November 2019 in Willenscharen. Daily mixed samples were taken by an automatic and cooled sampler from a depth of 0.30 m above the river bed at the central section of the stream. They were analyzed according to German standard procedure for water analysis (DEV) (Einheitsverfahren, 1997) in the laboratory of Department of Hydrology and Water Resources Management at Kiel University. Total suspended sediment concentration was measured by filtering 1 l of water sample through 0.45 µm celluloseacetate filter paper and drying at 105 °C. The concentration of total phosphorus (TP) was determined by spectrophotometry, according to DEV H36 and DEV D11, while total nitrogen (TN) was measured by chemiluminescence detection according to DEV H3. Each measurement of TP or TN concentration from unfiltered samples was performed based on a blank comparison analysis of distilled water and triplicate analysis of subsamples. Their concentrations were determined by the arithmetic mean values of any two subsamples with smallest measurement differences (less than <10%). Based on the measurements of daily concentration and streamflow, the respective daily load of sediment, TP, and TN were calculated.

2.3.3 Model calibration and validation

The variables daily streamflow (1), sediment (2), TP (3), and TN (4) were calibrated separately and stepwise. The number in the parentheses denotes their respective calibration order, i.e., streamflow was calibrated first, followed by sediment, TP, and TN. An overview of calibration and validation details for each variable is provided in Table 2.

Preliminary parameter ranges were selected based on experiences with the SWAT model in the Stör Catchment (Pott and Fohrer, 2017b) and other German lowland catchments (i.e., Kielstau and Treene catchments) (Haas et al., 2016; Lam et al., 2012; Pfannerstill et al., 2014) as well as in relevant studies from other countries (Aghsaei et al., 2020; Boongaling et al., 2018). The final ranges of calibration parameters (Table S1) were determined based on the sensitivity of parameters to model outputs as derived from 2000 trial runs following the method used by Guse et al. (2020), in which model simulations are iteratively repeated with successively constrained parameter ranges.

Parameter sets were generated from the derived parameter ranges using Latin Hypercube Sampling in the R-package FME (Soetaert and Petzoldt, 2010). For each of these 8000 (streamflow) and 5000 (sediment, TP, and TN loads) independent parameter sets, model runs were conducted each involving a warm-up period (four years), and evaluated using multiple performance criteria to select the best parameter set. To this end, the objective functions Nash-Sutcliffe efficiency (NSE), Kling-Gupta Efficiency (KGE), and Percent Bias (PBIAS), which were proposed in Guse et al. (2014) and Moriasi et al.

(2007), were applied. For an accurate representation of all segments of the hydrograph (very high, high, middle, low, and very low periods), the additional signature measure RSR (Ratio of Root Mean Square Error to the Standard Deviation of the Observations) was used (Haas et al., 2016; Zambrano-Bigiarini, 2020). The definition of each objective function is provided in Text S1 in the supplementary materials.

First, streamflow was calibrated at three gauges. The two upstream gauges Padenstedt (PAD) and Sarlhusen (SAR) were used to select the best parameter sets for the respective sub-catchments first (Figure 1). Then, the best parameter set for the area downstream of PAD and SAR and upstream of the outlet gauge Willenscharen (WIL) was selected. For each of the three streamflow gauges, we pre-selected the parameter sets that yielded a KGE > 0.75 for the streamflow calibration period. To accurately represent streamflow dynamics during the periods of water quality measurements (Aug. 2009 - Aug. 2011 and Oct. 2018 - Nov. 2019), the mean RSR for the five flow duration curve (FDC) segments during these periods was assessed and the best 300 streamflow parameter sets indicated by a low RSR were selected. From these 300 sets, the final parameter set yielding the highest KGE in these periods was selected. Calibration and validation periods (Table 2) were defined based on an equal representation of dry, normal, and wet years according to the annual precipitation.

Second, with the derived set of best hydrological parameters, model runs for 5000 different sediment calibration parameter sets were carried out and the best model run was selected based on the highest NSE. Third, this model was run for 5000 different sets of TP calibration parameters and the best model run was similarly selected using the NSE. Finally, based on the so far derived best parameters, another 5000 model runs for TN calibration were carried out and the best model run indicated by the highest NSE was selected. To accurately represent peak loads and their dynamics, the NSE was selected as single criterion for the water quality variables. Evaluation and processing of the model data were carried out in R using the packages hydroGOF (Zambrano-Bigiarini, 2020) and zoo (Zeileis and Grothendieck, 2005).

Table 2. Overview of SWAT model calibration and validation.

	Calibration				Validation			
	Streamflow	Sediment load	TP load	TN load	Streamflow	Sediment load	TP load	TN load
Evaluation period	1990-1991; 2007-2019	30/10/2009- 7/8/2011	8/8/2009- 10/8/2011	8/8/2009- 10/8/2011	1992-2006	19/10/2018- 5/11/2019	19/10/2018- 5/11/2019	19/10/2018- 5/11/2019
Simulation period	1986-2019	2005-2011	2005-2011	2005-2011	1986-2019	2014-2019	2014-2019	2014-2019
Land use map	2019	2010	2010	2010	2019	2019	2019	2019
Gauges	PAD/SAR/WIL	WIL	WIL	WIL	PAD/SAR/WIL	WIL	WIL	WIL
Calibration runs	8000	5000	5000	5000				
Performance criteria	KGE > 0.75 in 1990-1991; 2007-2019 & best KGE among 300 best mean RSR of FDC in 8/8/2009-10/8/2011; 19/10/2018-5/11/2019	NSE	NSE	NSE				

2.3.4 Model application

Applying the best respective parameter sets, the model was run for three land use scenarios. Each scenario simulation was run from 1990 to 2019 using one of the three land use maps (in 1987, 2010, and 2019). As agriculture in 1987 was generally classified, it was split as corn (12%), rapeseed (29%), and wheat (59%) randomly distributed in the catchment in SWAT model, according to the statistical data from Schleswig-Holstein Statistical Office (1992-2012). For the three scenario simulations, all other inputs i.e. DEM, soil data, weather data, waste water quality data, management practices, and fertilization were kept constant, and the calibrated parameters were adapted. The respective differences in the mean annual value of each response variable (i.e., actual evapotranspiration (ET), surface runoff (SQ), base flow (BF), water yield (WYLD), sediment (SED), TP, or TN load) were obtained by comparing the results from two scenario model runs (see Text

S2 and S3). They can be referred to as the respective changes driven by land use changes during the corresponding periods of 1987-2010, 2010-2019, and 1987-2019. The modeled results were used to explore the influences of land use changes (LUCC) on the changes in the response variables. Furthermore, the contributions of LUCC on changes in ET, SQ, BF, and WYLD as well as in SED, TP, TN at the subbasin scale were evaluated, and key impacts from LUCC were identified.

2.4 Partial least squares regression

Combining the features of principal component and multiple linear regression analyses, partial least squares regression (PLSR) is a robust multivariate analysis method of determining the relationship between two sets of variables. It is powerful to deal with multi-collinear predictor variables. The principle of PLSR is to extract a few latent components from original predictor variables that carry as much variation as possible, and which are meanwhile most likely to predict the variation in the response variable. Detailed information on the underlying theory and algorithms of PLSR is available in Abdi (2010).

In this study, PLSR was used to reveal the contribution of changes in land use classes on the variation in ET, SQ, BF, WYLD, SED, TP, and TN across three time steps (1987, 2010, and 2019). The predictor variables were the absolute changes in area percent (PLAND) and landscape metrics (LPI, AWMSI, AI, CONTIGAW, IJI) of four main land use classes (arable land, pasture, forest, and urban). The response variables included the absolute changes in the mean annual values of ET, SQ, BF, WYLD and SED, TP, and TN loads at the subbasin scale modeled under different land use conditions in 1987, 2010, and 2019. PLSR models for all of these response variables were constructed. The absolute change in each land use indicator was calculated using equation (5)-(7) while that in each response variable was calculated using equations (8)-(10) as shown in Text S3 in the supplementary materials. A cross-validation was performed with 50 random repetitions on 10 equal segments of the data set. It was used to determine the number of optimal components of the PLSR model to obtain a desirable balance between the explained variation in the response (R^2) and predictive power of the model (measured as cross-validated goodness of the prediction: Q^2). The cumulative predictive ability (cumulative goodness of prediction: Q_{cum}^2) and the cross-validated root mean squared error (RMSECV) as the difference between actual and predicted values, were determined for each model (Yan et al., 2013). The regression coefficients (RCs) signify the direction and extent of the effect of LUCC predictor variables. The variable importance for the projection (VIP) quantifies the importance of the predictors. According to the Wold's assessment criterion, a predictor with $VIP < 0.8$ is assessed as less important (Boongaling et al., 2018; Wold et al., 2001). To achieve model parsimony, the following PLSR modelling procedures were conducted: First, an initial simulation of PLSR is run using all predictors. Next, new PLSR models are run by iteratively excluding the predictor with small variable importance (VIP) until the modelling procedure resulted in acceptable variable importance or only two predictors remained. The number of components of candidate PLSR model was determined so that the Q_{cum}^2 is maximized (Shi et al., 2013).

All the PLSR analyses were performed with the R packages pls (Mevik et al., 2020) and mdatoools (Kucheryavskiy, 2020).

3 Results and discussion

3.1 Model performances for calibration and validation periods

As shown in Table 3, for streamflow, the model obtains NSE and KGE values above 0.75, and absolute PBIAS values below or slightly above 10%. These values indicate a good to very good model performance for depicting daily streamflow in the catchment according to the criteria for model evaluation (Moriasi et al., 2007). For daily TN load, the model shows a satisfactory to very good performance, indicated by an NSE between 0.64 and 0.86 and absolute PBIAS values below 15%. For sediment load, the model achieves a satisfactory to good performance as indicated by NSE (0.54 - 0.65) and PBIAS (-22.2 - 12%) values. The model simulates TP load with an unsatisfactory (validation) to satisfactory (calibration) performance, which is assessed by NSE below and above 0.5, respectively. The worse TP model performance may be due to the short and possibly different conditions during calibration and validation periods. Nevertheless, PBIAS for TP model is still within the

acceptable performance range ($\pm 40 \leq \text{PBIAS} < \pm 70$) (Moriassi et al., 2007). It should be noted that the performance ranges
295 from Moriassi et al. (2007) refer to a monthly time step, whereas we used a finer temporal scale (daily step), on which it is
usually harder to achieve a good model representation (Tan et al., 2021; Pfannerstill et al., 2014; Pott and Fohrer, 2017a).
We therefore conclude that even for daily TP the model performance is acceptable, particularly with regard to the study
purpose of analyzing long-term changes in the water and matter balance.

Overall, modeled and measured daily values show clear consistency in their dynamics (Figure 2 and 3). Differences mainly
300 appear for low flow periods in summer and particularly for a few peak flows in winter. Specifically, a few flood peaks are
underestimated in winter, e.g. on 27-28/Feb/2002, 5-6/Jan/2012, and 24-25/Dec/2014. This might be related to an
insufficient representation of snow and deficiencies in single-event flood routing in the model (Lam et al., 2012). The
underestimation of peak streamflow in winter was also observed in other rural lowland catchments of Treene (Haas et al.,
2016) and Kielstau (Lam et al., 2010) in northern Germany. Sediment loads are overestimated during the calibration period
305 and slightly underestimated during the validation period mainly for a few peak values. The incorrect estimation might be due
to the fact that river sediment load is also influenced by tile drains and bank erosion in lowland catchments (Kiesel et al.,
2009), while SWAT primarily takes into account sheet erosion. Nevertheless, some peaks e.g. in Nov, Dec 2009, and Mar
2019 are very well depicted. A similar behavior is observed for modelling TP load, with slight overestimation of TP in
summer (April - June of 2009 and 2019) and underestimation of a few peaks in winter (November - March). TN is generally
310 well represented, except for only a few underestimations of extreme peaks in winter (e.g., early March or November 2010).
Overall, the underestimation of some peak loads of sediment, TP and TN might be attributed to the underestimation of
corresponding peak flows.





Figure 2. Comparison of measured and modeled daily streamflow during the calibration and validation periods in Willenscharen.



315

Figure 3. Comparisons between measured and modeled daily loads of sediment, total phosphorus (TP), and total nitrogen (TN), respectively for calibration (left) and validation (right) periods

Table 3. Performance metrics for the model calibration and validation periods.

Index	Calibration				Validation			
	Streamflow (PAD/SAR/WIL)	Sediment load	TP load	TN load	Streamflow (PAD/SAR/WIL)	Sediment yield	TP load	TN load
Period	1990-1991; 2007-2019	30/10/2009-7/8/2011	8/8/2009-10/8/2011	8/8/2009-10/8/2011	1992-2006	19/10/2018-5/11/2019	19/10/2018-5/11/2019	19/10/2018-5/11/2019
KGE	0.85/0.82/0.88	0.58	0.65	0.71	0.84/0.85/0.87	0.59	0.22	0.91
NSE	0.76/0.78/0.79	0.54	0.56	0.64	0.81/0.81/0.79	0.65	0.29	0.86
PBIAS (%)	5.6/-2.2/0.3	12	-4.7	-11.5	0.7/10.6/7.2	-22.2	-46.2	5

3.2 Characteristics of land use change

320

Land use changes between 1987 and 2019 vary across the catchment (Figure 4). This is indicated by the individual dynamics in the four main land use classes of arable land, pasture, forest, and settlement area. Arable land has been decreasing and primarily replaced by pasture (by 16.2% of the catchment, dark cyan in Figure 4). The decrease of arable land in the northeast (e.g., subbasins 3 and 9-11) is more pronounced than in the northwest (e.g., subbasins 2, 4, 6, 8) where pasture was sometimes converted to arable land (dark pink, Figure 4). Conversely, pasture shows an increasing trend over the period of observation. The increase in the east is stronger as compared to the west of the catchment (Figure 4 and 5). The change of pasture is in part associated with the stream restoration including stabilizing river shore and increasing riparian vegetation (Dickhaut, 2005; Gessner et al., 2010). Besides, agricultural grasses may have been included in the pasture class due to the classification approach. Forest also shows an increasing trend as indicated by green colors in Figure 4, with a strong increase in the lowlands of the middle (subbasins 6 and 13) and southern parts (subbasin 17, Figure 5). Urban area has expanded mainly around the city of Neumünster (subbasin 15 and 17) (Figure 5).

330

In addition, the subbasin-scale land use metrics varied substantially between 1987, 2010, and 2019 (Figure 6). The mean area percent (PLAND) per subbasin declined for arable land (PLAND_a) by 16% and 3% during the periods of 1987-2010 and 2010-2019, respectively. In contrast, subbasin-averaged pasture (PLAND_p) increased for the period of 1987-2010 by 12% but decreased slightly from 2010 to 2019 by 0.8%. Both forest (PLAND_f) and urban (PLAND_u) areas have steadily increased from 1987 over 2010 to 2019. Similar trends are found in the metrics of the percentage of largest patch index (LPI) and the interspersion juxtaposition index (IJI). The subbasin average of LPI for arable land has decreased by 20% from 1987 to 2019, whereas the LPI of other land use classes shows a slight and stable increase. The IJI of arable land displays an overall slight increase from 1987 to 2019, while the IJI values of other land uses have steadily and notably increased (with a net increase up to over 20%). Both the area-weighted mean contiguity (CONTIGAW) and aggregation (AI) of each land use class have decreased over time, whereas the area-weighted mean shape index (AWMSI) has continuously and slightly increased. Despite similar changing directions of the land use patterns in the periods of 1987-2010 and 2010-2019, land use has been subject to more alterations in the former period than in the latter. Additionally, CONTIGAW, AI, and IJI of arable land exhibit opposite trends in the two periods, with a decrease from 1987 to 2010, and a slight increase from 2010 to 2019.




Figure 4. Spatial distribution of land use changes between 1987 and 2019 in the Stür Catchment. Individual land use change types are marked by different colors. The percentage of each change type calculated as percentage of the catchment area is given in the parentheses. The strongest change is marked in bold.




Figure 5. Spatial distribution patterns of the changes of each land use type between 1987, 2010, and 2019.





Figure 6. Changes of land use metrics between 1987, 2010, and 2019 in the Stür Catchment.

3.3 Differences of changes in water quantity and quality

Using the results from the three different scenario model runs based on three land use maps of 1987, 2010, and 2019, we calculated changes in water quantity and quality. The spatial distribution of the variations in modeled subbasin-scale actual

355 evapotranspiration (ET), surface runoff (SQ), base flow (BF), water yield (WYLD), and loads of sediment (SED), total
phosphorus (TP), and total nitrogen (TN) between 1987, 2010, and 2019 are shown in Figure 7. ET and SQ are mostly
characterized by increases of up to 10.8 mm and 11.4 mm, respectively from 1987 to 2019, with slight decreases by up to 3.8
360 mm in several subbasins between 2010 and 2019. The most significant increase in ET occurs in subbasins which show a
larger increase in forest from 1987 to 2019, such as subbasins 8, 12 and 17 (Figure 5). SQ shows a stronger increase in the
middle-western subbasins that experienced larger expansion of urban areas (Figure 5), with the strongest increase of SQ
365 occurring in subbasins 15 and 17 that experienced the largest increase of urban area between 1987 and 2019. This might be
attributed to the increased impervious surface which facilitates the generation of surface runoff and reduces confluence time
(Anand et al., 2018; Sood et al., 2021). Contrarily, BF and WYLD have decreased by up to 20 mm and 13 mm, respectively
in most subbasins in the periods 1987-2010 and 1987-2019. However, a few subbasins in central part of the catchment
370 exhibit a slight increase in base flow, which is probably attributed to a greater contribution of shallow groundwater in the
central lowland areas to low flow periods than in the steeper eastern and western steeper areas. The loads of SED, TP, and
TN show notable decreasing trends from 1987 to 2019. Pronounced reductions of SED (7.8-18.2 t km⁻²) occur in the
relatively steeper northeastern corner (e.g., subbasins 3, 9-10) and the southwestern corner (e.g., subbasins 5 and 12) and
subbasin 17, while the decrease is weaker in the mid-west. Overall, the changes in TP and TN loads show a weak decrease in
375 the (mid) west and more pronounced decreases in the east and steeper southwest of the catchment (Figure 7). The spatial
differences may be related to the more intense exchange between groundwater and surface water and a higher contribution of
nutrients from groundwater to the stream in the lowland. The most pronounced net decrease of TP and TN loads are
observed in subbasins 12 and 17, corresponding to the largest decrease of arable land percentage (50% in subbasin 17, 30%
in subbasin 12) between 1987 and 2019. The single subbasin that has experienced a slight increase of sediment or TP load is
subbasin 1, which is characterized by the least reduction of arable land and minor decrease of forest. The most significant
decrease in nutrients and sediment has occurred in subbasins which have experienced notable increases of pasture or forest
and a decrease of arable land, e.g., subbasins 12 and 17 (Figure 5). Overall, variations in surface runoff, sediment, TP, and
TN are depicted by spatially explicit patterns on the subbasin scale. It is necessary to consider this spatial heterogeneity,
when establishing management measures in order to improve water quality.



380

Figure 7. Spatial distribution of changes in water quantity and water quality variables during the periods of 1987-2010, 2010-2019, and 1987-2019 at subbasin scale.

3.4 Influences of changes in land use metrics on water quantity and quality

3.4.1 Contributions of LUCC to changes in water quantity and quality

385

A summary of the PLSR models separately constructed for ET, SQ, BF, WYLD, SED, TP and TN, is provided in Table 4. The prediction plots for the seven variables by applying the PLSR models are shown in Figure 8. The changes in water quantity and quality could be reasonably explained by the constructed PLSR models ($0.61 < R^2 < 0.88$, $0.57 < Q^2 < 0.85$, Table 4).

390

The comparison of the actual and predicted values (in Figure 8) illustrates the accuracy of the model calibration and cross-validation. For the ET and WYLD models, the percentage of unexplained variation decreases with increasing number of components, whereas the prediction error of cross-validated observations (indicated by cross-validated root mean squared error, RMSECV) is minimal with one or two components, respectively. This indicates that adding more components does not

395

improve the correlation with the residuals of the response variables (Onderka et al., 2012). Overall, 60.5% and 68.3% of the variations in the changes in ET and WYLD can be explained by the first component and the first two components, respectively. Adding other components does not strongly increase the cumulative explained variations (only by +4.2-5.4%) in ET and WYLD changes from 1987 to 2019 (Table 4). For SQ, two components are extracted for the PLSR model, with 58.9% of variation is explained on the first component and cumulative explained variations increase to 81.3% when adding the second component. For all other variables, the minimum RMSECV is achieved with models using five components. For

base flow, 37.4% of the variation in the dynamics is explained by the first component, cumulatively 64.2% adding the second component, and ultimately 87.7% with a consecutive addition of third, fourth, and fifth component. For the changes in loads of sediment, TP, and TN, the first component of the models always explains the majority of the variation (43.7-63%, Table 4). With all water quality variables together, approximately 75% of the changes is accurately explained on average. Approximately 70-80% of the variations in water quantity and quality dynamics were explained by LUCC, underlining the importance of LUCC on catchment water resources. Better explanations (over 81%) of SQ and BF by LUCC confirmed the significant influences of landscape heterogeneity on surface runoff and groundwater dynamics (Xu et al., 2020; Kändler et al., 2017; Zhang and Schilling, 2006). Only a quarter of the variations in sediment, TP, or TN cannot be interpreted by LUCC, which demonstrates that changes of rural landscape patterns are essentially important in controlling nutrients pollution. The proportion and spatial arrangement of agriculture land play an important role in the generation and transportation of nutrient pollutants as previously reported in different catchments worldwide: e.g., Zhang et al. (2020b) found that agricultural cultivation on steeper hillsides intensified N and P entries in ponds in the hilly Tianmu Lake catchment of Eastern China. G énesi et al. (2011) identified the cohesion and contagion of cropland were more important than other land use indicators to account for the variability in TN and TP in the relatively plain Iowa Lake catchment of the central US. The minor unexplained fraction may be attributed to potential changes in waste water treatment which sometimes remained constant in our modeling approach. Lower explanation of TP may be additionally due to the lower SWAT model performance for TP, the susceptibility of P to soil or geomorphology properties (Maranguit et al., 2017; Noe et al., 2013). More than 60% of the variations in ET and WYLD are explained by LUCC. The unexplained fraction may be attributed to the different contributions from specific crops (included in SWAT) and the lumped agriculture class as well as the compensating effect of subbasins (Wagner et al., 2013).

Table 4. Summary of the PLSR models of evapotranspiration (ET), surface runoff (SQ), base flow (BF), water yield (WYLD), sediment yield (SED), total phosphorus load (TP) and total nitrogen load (TN) at subbasin scale.

Response Variable <i>Y</i>	R ²	Q ²	Component	Explained variability in <i>Y</i> (%)	Cumulative explained variability in <i>Y</i> (%)	RMSECV	Q ² _{cum}
ET	0.61	0.57	1	60.5	60.5	2.32 (mm)	0.568
			2	2.4	62.9	2.35 (mm)	0.558
			3	1.2	64.1	2.44 (mm)	0.524
			4	0.2	64.3	2.41 (mm)	0.535
			5	0.4	64.7	2.41 (mm)	0.534
SQ	0.81	0.78	1	58.9	58.9	1.70 (mm)	0.561
			2	22.4	81.3	1.20 (mm)	0.783
BF	0.88	0.85	1	37.4	37.4	4.61 (mm)	0.230
			2	26.8	64.2	3.92 (mm)	0.442
			3	9.7	73.9	3.15 (mm)	0.640
			4	8.8	82.7	2.59 (mm)	0.757
			5	5.0	87.7	2.05 (mm)	0.847
WYLD	0.68	0.61	1	64.6	64.6	2.43 (mm)	0.611
			2	3.7	68.3	2.43 (mm)	0.614
			3	0.9	69.2	2.46 (mm)	0.602
			4	0.4	69.6	2.47 (mm)	0.598
			5	0.4	70.0	2.49 (mm)	0.592
SED	0.77	0.67	1	43.7	43.7	2.76 (t km ⁻²)	0.382
			2	19.2	62.9	2.50 (t km ⁻²)	0.493
			3	11.1	74.0	2.13 (t km ⁻²)	0.630
			4	1.6	75.6	2.08 (t km ⁻²)	0.650
			5	1.0	76.6	2.03 (t km ⁻²)	0.667
TP	0.76	0.65	1	51.5	51.5	12.03 (kg km ⁻²)	0.468
			2	10.7	62.2	11.14 (kg km ⁻²)	0.544
			3	10.4	72.6	10.32 (kg km ⁻²)	0.608
			4	3.0	75.6	9.80 (kg km ⁻²)	0.647
			5	0.7	76.3	9.71 (kg km ⁻²)	0.653
TN	0.73	0.68	1	63.0	63.0	43.04 (kg km ⁻²)	0.597
			2	5.8	68.8	40.56 (kg km ⁻²)	0.643
			3	3.1	72.1	39.20 (kg km ⁻²)	0.666
			4	0.5	72.6	38.90 (kg km ⁻²)	0.671
			5	0.7	73.3	38.51 (kg km ⁻²)	0.678

Note: R² indicates the goodness of fit of the model; Q² indicates the cross-validated goodness of prediction; RMSECV indicates cross-validated root mean squared error; Q²_{cum} indicates the cumulative cross-validated goodness of prediction over all the selected PLSR components; the components selected for each model are highlighted in bold.




Figure 8. Comparison of subbasin-scale changes in evapotranspiration (ET), surface runoff (SQ), base flow (BF), water yield (WYLD), sediment (SED), total phosphorus (TP), and total nitrogen (TN) as derived from the SWAT model and the predicted values from the PLSR models. The changes were obtained based on land use changes between 1987 and 2010, 2010 and 2019, and between 1987 and 2019, respectively. Cal indicates calibration. CV indicates cross validation.

3.4.2 Effects of LUCC predictors on water quantity and quality

According to the PLSR results, each category of the landscape indices including percentage (PLAND), largest patch (LPI), shape (AWMSI), contiguity (CONTIGAW), aggregation (AI), or interspersion (IJI), plays an essential role in influencing as least one water quantity or quality variable (Table 5). The effects on the changes in ET, SQ, BF, WYLD, SED, TP, and TN are measured using weights, regression coefficients (RCs), and VIP values in the PLSR models. VIPs for predictors included into the models are greater than 0.8. For the ET model, the highest VIPs are obtained in predictors aggregation index for arable land (AIa) and contiguity index for arable land (CONTIGAWa) (VIP = 1.25, RCs = -0.122), followed by PLANDa (VIP = 1.037, RC = -0.101) and AIu (VIP = 1.03, RC = -0.1). ET tends to decrease with larger aggregation (AIa) and contiguity (CONTIGAWa) indices, and arable land percent (PLANDa) (negative RCs), whereas it increases with more pasture (PLANDp) (positive RC). In the case of surface runoff, the first and second components of the model are dominated by PLANDu on the positive side, with minor positive effect from PLANDa on the second component (Table 5). The urban area percent (PLANDu) obtains largest VIP of 1.173, and are identified as most important influencing the change in surface runoff. Surface runoff increases with an increase in arable (PLANDa) and urban areas (PLANDu) (RCs=0.403, 1.161, respectively). For base flow, in addition to arable land, pasture plays a key role in explaining its variation. Arable land (PLANDa), pasture (PLANDp) percent and area-weighted shape index of pasture (AWMSIp) obtain the largest VIPs of 1.259, 1.03, and 1.063, respectively. All show negative correlations with base flow. AIa and CONTIGAWa are important predictors for water yield with large VIPs of 1.226 and 1.218, respectively. Their higher values result in an increase of water yield. For sediment, TP or TN models, the selected components are dominated by areal percentages of arable land and pasture, in addition to the landscape metrics of arable land. The models obtain the largest regression coefficients or VIPs for PLANDa, LPIa, or PLANDp. They have VIPs of 1.0113-1.173 for sediment, 1.089-1.305 for TP, 1.005-1.232 for TN, respectively. Inferred by the RCs, an increase in sediment, TP, or TN occurs with increasing arable land (RCs: 0.602-0.884), while a decrease may occur with higher percentage of arable land in largest patches (LPIa) (RCs: -0.74 - -0.225), or with more pasture area (RCs: -0.693 - -0.122).

LPIa, AIa and CONTIGAWa are the most important landscape structure indicators affecting water quantity or quality (VIP ≥ 1 most of the time, Table 5). AIa and CONTIGAWa have positive impacts on WYLD while negative impacts on ET. By definition, AIa and CONTIGAWa would increase, respectively, when arable landscape patches are more clumped and contiguous (Shi et al., 2013; Uemaa et al., 2009). Agriculture in more clumped and connected land patches with fewer edges has been proven to show a higher capability of reducing the infiltration, compared to small scattered patches

(Boongaling et al., 2018), which may result in the increase of the water yield. Our results also corroborate with Ayivi and Jha (2018) who reported that increased water yield and base flow occur with increasing cohesive and aggregated agriculture in a moderate-altitude catchment (i.e., Reedy Fork-Buffalo Creek catchment, USA). Negative impacts on ET may be explained by the interactive changes between arable and pasture, i.e., arable land has been increased at the cost of losing pasture, and vice versa. Likewise, Shawul et al. (2019) observed that reduction in pasture would result in a decrease of ET in an agriculture-dominated and moderate-altitude catchment (the Upper Awash Catchment, Ethiopia). The negative effect of AWMSI_p on base flow implies that the coarse grass landscape has a higher capacity of absorbing and intercepting rainfall thereby resulting in lower base flow. Though landscape metrics are more often used to explain water quantity than quality variables (Table 5), the negative influences of LPI_a on sediment and nutrients, and positive influences of AWMSI_a on sediment and TP cannot be overlooked. Similar findings were observed in hilly catchments, where scattered and complicated agriculture patches are susceptible to soil erosion and thus water quality deterioration (Yan et al., 2013; Nafi'shehab et al., 2021).

The change in the percentage of arable land is most responsible for water quantity and quality dynamics, with VIP values greater than 1 for all response variables but WYLD. This may be explained by the fact that the decrease in arable land is the strongest. The negative correlations between PLAND_a and evapotranspiration (ET) and base flow (BF) imply that conversion of arable land to e.g., pasture or forest would result in increased ET and BF, due to higher capability of plant evapotranspiration and slower water transmission, which is in agreement with previous findings that perennial vegetation is more likely to increase ET (Peel et al., 2010; Li et al., 2017) and the decrease in agriculture leads to increased annual base flow (Basuki et al., 2019). Less interception by crops and additional surface runoff resulting from implementation of tillage practices (e.g., tractor road) can result in increased surface runoff (SQ). The lower ET amount of crops compared to pasture and forest is in part responsible for the increase in WYLD. Soil erosion might be accelerated due to uncovered and fragile soil by tillage practices implemented in cultivated areas as well as the increased surface runoff. N and P pollution is prone to occur in arable areas, which have a high risk of generating nutrient pollutants from excessive fertilizer or manure and eroded soil particles. The positive relationships between arable land percent and SQ, WYLD, SED TP, and TN loads are found in other studies around the world as well (Sood et al., 2021; Wang et al., 2019; Wagner et al., 2013; Mirghaed et al., 2018; Zhang et al., 2020a). Pasture shows a positive influence on ET and negative influences on sediment, TP, and TN. This also illustrates that more grassland (or rangeland) would increase plant evapotranspiration process. Pasture can improve water quality due to reduced soil erosion and nutrient transportation rate, as well as the high uptake and infiltration of nutrients by vegetation cover. Relevant studies (Li et al., 2008; Hatano et al., 2005; Ding et al., 2016; Zhang et al., 2020a) have often observed that semi-natural vegetation (e.g., forest, bushland or grassland) is beneficial for good water quality in river- or lake-dominated catchments, due to higher capability of filtering contaminants and reducing their inputs as well as decreasing surface runoff.

By applying the quantitative results that the increases in arable or pasture areas most significantly intensify or reduce the risk of soil erosion and nutrient pollution, respectively, individual subbasins can be identified as nutrient pollution “source” or “sink”. Based on these results, it is possible to develop a set of more targeted strategies to effectively control diffuse pollution at a spatial scale. At the same time, best management practices such as proper fertilization, abate of traditional tillage, crop rotation, vegetation buffer, are important to improve water quality in rural catchments (Haas et al., 2017; Pott and Fohrer, 2017a). Urban expansion is most important influencing surface runoff, the increase in urban area percent results in an increase of it (regression coefficient value > 1.16, Table 5). Similar results have been found, e.g., by Shi et al. (2007) who discovered that increased urbanized land led to increased surface runoff, by increasing flood peaks and decreasing surface runoff confluence time, in a typical urbanized region (Shenzhen) in China. Unlike previous findings (Yan et al., 2013; Wang et al., 2018), forest properties have not exerted significant influences, probably due to only minor temporal changes in some landscape metrics, e.g., area percent (PLAND), dominance (LPI), and shape (AWMSI) of forest (Figure 6).

Table 5. Regression coefficients (RCs), VIP and weight values of each PLSR model.

Predictors	ET		SQ					BF					WYLD					
	RC	VIP	W*[1]	RC	VIP	W*[1]	W*[2]	RC	VIP	W*[1]	W*[2]	W*[3]	W*[4]	W*[5]	RC	VIP	W*[1]	W*[2]
PLAND _a	-0.101	1.037	-0.017	0.403	0.790	-0.048	<i>0.189</i>	-1.654	1.259	-0.001	<i>-0.128</i>	<i>-0.135</i>	<i>-0.208</i>	<i>-0.201</i>	0.043	0.882	0.017	-0.042
PLAND _p	0.089	0.918	0.015					-1.474	1.030	-0.034	0.024	<i>-0.117</i>	<i>-0.304</i>	<i>-0.256</i>	0.011	0.866	-0.015	0.072
PLAND _f								-0.575	0.915	-0.035	-0.074	-0.072	-0.045	0.092				
PLAND _u	0.080	0.818	0.013	1.161	1.173	0.090	<i>0.173</i>											
LPI _a	-0.088	0.906	-0.015															
AWMSI _p								-0.143	1.063	-0.052	-0.058	0.059	0.093	-0.013				
AWMSI _f	0.085	0.870	0.014											-0.039	0.837	-0.016	0.041	
AI _a	-0.122	1.254	-0.020											0.187	1.226	0.024	0.025	
AI _P	-0.094	0.961	-0.016											0.100	0.924	0.018	-0.009	
AI _u	-0.100	1.030	-0.017											0.212	1.068	0.020	0.058	
CONTIGAW _a	-0.122	1.251	-0.020											0.184	1.218	0.024	0.024	
CONTIGAW _P	-0.087	0.891	-0.015											0.112	0.880	0.018	0.004	
CONTIGAW _u	-0.094	0.959	-0.016					0.281	0.805	0.040	0.029	-0.078	0.064	0.011	0.198	1.007	0.019	0.054
II _a								0.038	0.859	0.040	0.024	0.098	<i>-0.142</i>	-0.091				

Predictors	SED							TP							TN						
	RC	VIP	W*[1]	W*[2]	W*[3]	W*[4]	W*[5]	RC	VIP	W*[1]	W*[2]	W*[3]	W*[4]	W*[5]	RC	VIP	W*[1]	W*[2]	W*[3]	W*[4]	W*[5]
PLAND _a	0.602	1.165	0.027	0.038	<i>0.106</i>	0.037	0.040	0.755	1.305	0.029	0.031	<i>0.117</i>	<i>0.142</i>	0.059	0.884	1.232	0.033	<i>0.103</i>	<i>0.133</i>	<i>0.166</i>	<i>0.333</i>
PLAND _p	-0.693	1.173	-0.026	-0.022	<i>-0.124</i>	-0.096	-0.099	-0.499	1.089	-0.025	-0.007	-0.099	-0.074	0.002	-0.122	1.005	-0.030	-0.054	-0.049	0.031	<i>0.324</i>
PLAND _u	0.013	0.908	-0.022	-0.033	0.020	0.097	<i>0.116</i>	-0.045	1.038	-0.025	-0.033	0.005	0.057	<i>0.137</i>	0.028	1.013	-0.024	-0.032	0.052	<i>0.197</i>	0.093
PLAND _f								-0.009	0.821	-0.016	-0.053	0.061	0.047	0.004							
LPI _a	-0.632	1.113	0.015	-0.095	<i>-0.117</i>	-0.037	-0.070	-0.740	1.205	0.017	-0.064	-0.208	-0.091	-0.057	-0.225	0.945	0.023	-0.054	<i>-0.209</i>	0.028	0.019
LPI _p	0.397	0.819	-0.009	0.075	0.086	-0.043	0.020														
AWMSI _a	0.472	0.902	0.007	<i>0.103</i>	-0.017	0.073	0.080	0.492	0.817	0.008	0.087	0.020	0.093	0.085							
AWMSI _p	-0.445	1.087	-0.023	-0.077	-0.050	-0.022	<i>0.107</i>	-0.152	0.872	-0.019	-0.031	-0.057	<i>0.127</i>	-0.001							
CONTIGAW _a	0.039	0.877	0.023	-0.001	-0.042	-0.024	0.075	0.079	0.864	0.021	-0.027	-0.013	0.015	0.069	0.114	0.840	0.022	-0.072	0.037	0.019	0.077
AI _a	-0.053	0.876	0.022	-0.006	-0.055	-0.039	0.041	0.008	0.856	0.021	-0.030	-0.025	0.000	0.052	-0.034	0.833	0.022	-0.081	0.015	-0.024	-0.038

500 **Note:** VIP values greater than 1 were marked in bold; the absolute weights greater than 0.1 were marked in italic.

4 Conclusion

In this study, the separate contributions of changes in land use on the dynamics of seven water quantity and quality variables, i.e., actual evapotranspiration (ET), surface runoff (SQ), base flow (BF), water yield (WYLD), sediment (SED), total phosphorus (TP), and total nitrogen (TN) loads were quantified by applying an integrated approach of hydrological modelling (SWAT) and partial least squares regression (PLSR). The influences of the changes in individual land use indicators on changes in water quantity and quality were measured and identified using a scenario analysis for three different land use maps of the past.

The modelling analysis of the effects of past land use changes showed that water quality and quantity variables varied in different ways on the subbasin scale. SED, TP, and TN decreased more strongly in the eastern and western parts than in the middle lowlands, implying that a higher contribution of nutrients by groundwater can mediate the influences of land use change. Based on a PLSR analysis, about 75% of the modeled variations in water quality and quantity variables can be accurately explained by land use indicators. The change of arable land is inferred to be most important for water quality and quantity dynamics, as arable land indicators mostly showed a greater importance (measured by VIP>1) for more response variables compared to other indicators. Looking at the most significant impacts, expansion of arable land (PLAND_a) caused BF to decrease and urbanization expansion resulted in increased SQ. More aggregated and connected arable land patches led to a decrease of ET and an increase of WYLD. Arable land expansion exacerbated soil erosion and P and N pollution, whereas an increase of pasture helped to relieve nutrient pollution problems. These results underline that water quality and

quantity variables are affected by land use changes in different ways. To achieve good water quality, the dynamics in the extent and the spatial configuration of arable land require special attention. The spatial assessment of changes in water quantity and quality variables in this study provides a basis for an informed and location-specific management of land and water resources.

Code availability

SWAT is an open-source hydrological model. The source code of is freely available via <https://swat.tamu.edu/software/swat-executables/>. SWAT_{3s} is an adapted version of SWAT and the code of it was compiled by Dr. Matthias Pfannerstill (Pfannerstill et al., 2014). The code of PLSR used in this study may be available upon request to the corresponding author.

Data availability

Meteorological data can be obtained from Deutscher Wetterdienst (DWD) platform: https://opendata.dwd.de/climate_environment/CDC/. The streamflow data can be obtained from Landesbetrieb für Küstenschutz, Nationalpark und Meeresschutz Schleswig-Holstein (LKN) website: <http://www.umweltdaten.landsh.de>. Land use data are proprietary data: land use map in 1987 were adapted from Rippl et al., 1996; land use map in 2010 and in 2019 was interpreted by Kiel University. Water quality data were collected via measurements in field and the lab of Department of Hydrology and Water Resources Management at Kiel University and may be available upon request to the corresponding author.

Supplement

Author contributions

Chaogui Lei, Paul D. Wagner, and Nicola Fohrer designed the experiments and Chaogui Lei carried them out. Chaogui Lei and Paul D. Wagner developed the model codes. Chaogui Lei performed the simulations with the supervision by co-authors. Chaogui Lei worked out the results and prepared the manuscript with contributions from all co-authors.

Competing interests

The authors declare that they have no conflict of interest.

Disclaimer

Publisher's note: Copernicus Publications remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Acknowledgments

We gratefully acknowledge the funding from the China Scholarship Council (CSC) for the first author. We deeply appreciate the assistance with the field sampling and lab analysis by lab technicians Bettina Hollmann, Falko Torreck, Monika Westphal, and Imke Meyer. Special thanks go to Cristiano Andre Pott for collecting water quality data for 2009-2011 and to our students Anne-Kathrin Wendell, Henrike Risch, Jia Yuan, Josephine Loeck, Lisa Jensen, Marian Scheffler, and Tanja Boehlke for supporting the water quality measurement campaigns in 2018-2019.

This research has been supported by China Scholarship Council (grant no: 201606190222).

Review statement

This paper was edited by Yi He and reviewed by three anonymous referees.

References

- 555 Abdi, H.: Partial least squares regression and projection on latent structure regression (PLS Regression), *Wiley Interdiscip. Rev. Comput. Stat.*, 2, 97-106, <http://doi.org/10.1002/wics.51>, 2010.
- Aghsaiei, H., Dinan, N. M., Moridi, A., Asadolahi, Z., Delavar, M., Fohrer, N., and Wagner, P. D.: Effects of dynamic land use/land cover change on water resources and sediment yield in the Anzali wetland catchment, Gilan, Iran, *Sci. Total Environ.*, 712, 136449, <https://doi.org/10.1016/j.scitotenv.2019.136449>, 2020.
- 560 Amin, M. M., Veith, T. L., Shortle, J. S., Karsten, H. D., and Kleinman, P. J.: Addressing the spatial disconnect between national-scale total maximum daily loads and localized land management decisions, *J Environ Qual*, 49, 613, <http://doi.org/10.1002/jeq2.20051>, 2020.
- Amiri, B. J. and Nakane, K.: Modeling the linkage between river water quality and landscape metrics in the Chugoku district of Japan, *Water Resour. Manag.*, 23, 931-956, <http://doi.org/10.1007/s11269-008-9307-z>, 2009.
- 565 Anand, J., Gosain, A. K., and Khosa, R.: Prediction of land use changes based on Land Change Modeler and attribution of changes in the water balance of Ganga basin to land use change using the SWAT model, *Sci. Total Environ.*, 644, 503-519, <https://doi.org/10.1016/j.scitotenv.2018.07.017>, 2018.
- Antolini, F., Tate, E., Dalzell, B., Young, N., Johnson, K., and Hawthorne, P. L.: Flood risk reduction from agricultural best management practices, *J. Am. Water Resour. Assoc.*, 56, 161-179, <https://doi.org/10.1111/1752-1688.12812>, 2020.
- 570 Aredo, M. R., Hatiye, S. D., and Pingale, S. M.: Impact of land use/land cover change on stream flow in the Shaya catchment of Ethiopia using the MIKE SHE model, *Arab. J. Geosci.*, 14, 1-15, <http://doi.org/10.1007/s12517-021-06447-2>, 2021.
- Arnold, J., Kiniry, J., Srinivasan, R., Williams, J., Haney, E., and Neitsch, S.: SWAT 2012 input/output documentation, Texas Water Resources Institute, 2013.
- Arnold, J. G., Srinivasan, R., Muttiah, R. S., and Williams, J. R.: Large area hydrologic modeling and assessment part I: model development 1, *J. Am. Water Resour. Assoc.*, 34, 73-89, <https://doi.org/10.1111/j.1752-1688.1998.tb05961.x>, 1998.
- 575 Ayivi, F. and Jha, M. K.: Estimation of water balance and water yield in the Reedy Fork-Buffalo Creek Watershed in North Carolina using SWAT, *Int. Soil Water Conserv. Res.*, 6, 203-213, <https://doi.org/10.1016/j.iswcr.2018.03.007>, 2018.
- Basuki, T. M., Nugrahanto, E. B., Pramono, I. B., and Wijaya, W. W.: Baseflow and lowflow of catchments covered by various old teak forest areas, *J. Degrad. Min. Lands Manag*, 6, 1609, <https://doi.org/10.15243/JDMLM.2019.062.1609>, 2019.
- 580 Bicknell, B., Imhoff, J., Kittle, J., Donigian, A., and Johanson, R. C.: Hydrological simulation program—Fortran (HSPF): User's manual for release 12, US Environmental Protection Agency, National Exposure Research Laboratory, Athens, GA, 2001.
- Bieger, K., Hürmann, G., and Fohrer, N.: Simulation of streamflow and sediment with the soil and water assessment tool in a data scarce catchment in the three gorges region, China, *J. Environ. Qual.*, 43, 37-45, <https://doi.org/10.2134/jeq2011.0383>, 2014.
- Boongaling, C. G. K., Faustino-Eslava, D. V., and Lansigan, F. P.: Modeling land use change impacts on hydrology and the use of landscape metrics as tools for watershed management: The case of an ungauged catchment in the Philippines, *Land use policy*, 72, 116-128, <https://doi.org/10.1016/j.landusepol.2017.12.042>, 2018.
- 585 Dickhaut, W.: Fließgewässerrenaturierung Heute—Forschung zu Effizienz und Umsetzungspraxis—Abschlussbericht, Hochschule für angewandte, 2005.
- Ding, J., Jiang, Y., Liu, Q., Hou, Z., Liao, J., Fu, L., and Peng, Q.: Influences of the land use pattern on water quality in low-order streams of the Dongjiang River basin, China: a multi-scale analysis, *Sci. Total Environ.*, 551, 205-216, <https://doi.org/10.1016/j.scitotenv.2016.01.162>, 2016.
- 590 DWD: Deutscher Wetterdienst. Precipitation data 1990–2019, Precipitation stations Haale, Padenstedt, Nettelsee and Itzehoe, Climate data 1990-2019, Climate station Pony Padenstedt., https://opendata.dwd.de/climate_environment/CDC/. Accessed in July 2020., 2020a.
- DWD: Deutscher Wetterdienst. Climate data 1990–2019, Climate station Pony Padenstedt., https://opendata.dwd.de/climate_environment/CDC/. Accessed in July 2020., 2020b.
- 595 Einheitsverfahren, D.: Selected Methods of Water Analysis, Bd. I, II. VEB Gustav Fisher, Jena (in German), 1997.
- Farjad, B., Pooyandeh, M., Gupta, A., Motamedi, M., and Marceau, D.: Modelling interactions between land use, climate, and hydrology along with stakeholders' negotiation for water resources management, *Sustainability*, 9, 2022, <https://doi.org/10.3390/su9112022>, 2017.
- Ferreira, A., Fernandes, L. S., Cortes, R., and Pacheco, F.: Assessing anthropogenic impacts on riverine ecosystems using nested partial least squares regression, *Sci. Total Environ.*, 583, 466-477, <https://doi.org/10.1016/j.scitotenv.2017.01.106>, 2017.
- 600 Fiener, P., Auerswald, K., and Van Oost, K.: Spatio-temporal patterns in land use and management affecting surface runoff response of agricultural catchments—A review, *Earth-Sci. Rev.*, 106, 92-104, <https://doi.org/10.1016/j.earscirev.2011.01.004>, 2011.
- Finnern, J.: Böden und Leitbodengesellschaften des Störzungsgebietes in Schleswig-Holstein: Vergesellschaftung und Stoffaustragsprognose (K, Ca, Mg) mittels GIS., Schriftenreihe des Instituts für Pflanzenernährung und Bodenkunde der Universität Kiel, Kiel., 1997.
- 605 Forman, R. T.: Some general principles of landscape and regional ecology, *Landsc. Ecol.*, 10, 133-142, <https://doi.org/10.1007/BF00133027>, 1995.
- Gabriels, K., Willems, P., and Van Orshoven, J.: Performance evaluation of spatially distributed, CN-based rainfall-runoff model configurations for implementation in spatial land use optimization analyses, *J. Hydrol.*, 602, 126872, <https://doi.org/10.1016/j.jhydrol.2021.126872>, 2021.
- 610 Gashaw, T., Tulu, T., Argaw, M., and Worqlul, A. W.: Modeling the hydrological impacts of land use/land cover changes in the Andassa watershed, Blue Nile Basin, Ethiopia, *Sci. Total Environ.*, 619, 1394-1408, <https://doi.org/10.1016/j.scitotenv.2017.11.191>, 2018.
- Génesi, Z., Downing, J. A., Cruse, R. M., and Anderson, P. F.: Effects of watershed configuration and composition on downstream lake water quality, *J. Environ. Qual.*, 40, 517-527, <https://doi.org/10.2134/jeq2010.0133>, 2011.

- Gessner, J., Spratte, S., and Kirschbaum, F.: Störe für die Stör-Wem hilft ein lebendes Fossil, *Steinburger Jahrbuch*, 54, 247-273, 2010.
- 615 Ghimire, C. P., Bruijnzeel, L. A., Lubczynski, M. W., Ravelona, M., Zwartendijk, B. W., and van Meerveld, H. I.: Measurement and modeling of rainfall interception by two differently aged secondary forests in upland eastern Madagascar, *J. Hydrol.*, 545, 212-225, <https://doi.org/10.1016/j.jhydrol.2016.10.032>, 2017.
- Gleick, P. H.: A look at twenty-first century water resources development, *Water Int.*, 25, 127-138, <https://doi.org/10.1080/02508060008686804>, 2000.
- 620 Goldewijk, K. K. and Ramankutty, N.: Land cover change over the last three centuries due to human activities: The availability of new global data sets, *GeoJournal*, 61, 335-344, <https://doi.org/10.1007/s10708-004-5050-z>, 2004.
- Gu, D., Zhang, Y., Fu, J., and Zhang, X.: The landscape pattern characteristics of coastal wetlands in Jiaozhou Bay under the impact of human activities, *Environ. Monit. Assess.*, 124, 361-370, <https://doi.org/10.1007/s10661-006-9232-7>, 2007.
- Guse, B., Reusser, D. E., and Fohrer, N.: How to improve the representation of hydrological processes in SWAT for a lowland catchment-temporal analysis of parameter sensitivity and model performance, *Hydrol. Process.*, 28, 2651-2670, <https://doi.org/10.1002/hyp.9777>, 2014.
- 625 Haas, M. B., Guse, B., and Fohrer, N.: Assessing the impacts of Best Management Practices on nitrate pollution in an agricultural dominated lowland catchment considering environmental protection versus economic development, *J. Environ. Manage.*, 196, 347-364, <https://doi.org/10.1016/j.jenvman.2017.02.060>, 2017.
- Haas, M. B., Guse, B., Pfannerstill, M., and Fohrer, N.: A joined multi-metric calibration of river discharge and nitrate loads with different performance measures, *J. Hydrol.*, 536, 534-545, <https://doi.org/10.1016/j.jhydrol.2016.03.001>, 2016.
- 630 Haidary, A., Amiri, B. J., Adamowski, J., Fohrer, N., and Nakane, K.: Assessing the impacts of four land use types on the water quality of wetlands in Japan, *Water Resour. Manag.*, 27, 2217-2229, <https://doi.org/10.1007/s11269-013-0284-5>, 2013.
- Hargis, C. D., Bissonette, J. A., and David, J. L.: The behavior of landscape metrics commonly used in the study of habitat fragmentation, *Landsc. Ecol.*, 13, 167-186, 1998.
- 635 Hatano, R., Nagumo, T., Hata, H., and Kuramochi, K.: Impact of nitrogen cycling on stream water quality in a basin associated with forest, grassland, and animal husbandry, *Hokkaido, Japan, Ecol. Eng.*, 24, 509-515, <https://doi.org/10.1016/j.ecoleng.2005.01.011>, 2005.
- Hesselbarth, M. H., Sciaini, M., With, K. A., Wiegand, K., and Nowosad, J.: landscapemetrics: An open-source R tool to calculate landscape metrics, *Ecography*, 42, 1648-1657, <https://doi.org/10.1111/ecog.04617>, 2019.
- 640 Idrissou, M., Diekkrüger, B., Tischbein, B., Op de Hipt, F., Nächen, K., Poméon, T., Yira, Y., and Ibrahim, B.: Modeling the Impact of Climate and Land Use/Land Cover Change on Water Availability in an Inland Valley Catchment in Burkina Faso, *Hydrology*, 9, 12, <https://doi.org/10.3390/hydrology9010012>, 2022.
- Jones, K. B., Neale, A. C., Nash, M. S., Van Remortel, R. D., Wickham, J. D., Riitters, K. H., and O'Neill, R. V.: Predicting nutrient and sediment loadings to streams from landscape metrics: a multiple watershed study from the United States Mid-Atlantic Region, *Landsc. Ecol.*, 16, 301-312, <https://doi.org/10.1023/A:1011175013278>, 2001.
- 645 Kändler, M., Blechinger, K., Seidler, C., Pavlů, V., Šanda, M., Dostál, T., Krása, J., Vitvar, T., and Štich, M.: Impact of land use on water quality in the upper Nisa catchment in the Czech Republic and in Germany, *Sci. Total Environ.*, 586, 1316-1325, <https://doi.org/10.1016/j.scitotenv.2016.10.221>, 2017.
- Kiesel, J., Schmalz, B., and Fohrer, N.: SEPAL—a simple GIS-based tool to estimate sediment pathways in lowland catchments, *Adv. Geosci.*, 21, 25-32, <https://doi.org/10.5194/adgeo-21-25-2009>, 2009.
- 650 KTBL: Kuratorium für Technik und Bauwesen in der Landwirtschaft. Betriebsplanung Landwirtschaft 1995/1996 and 2008/2009, 14. Edition 21. Darmstadt: KTBL, 1995 and 2008.
- Kucheryavskiy, S.: mdatools—R package for chemometrics, *Chemom. Intell. Lab. Syst.*, 198, 103937, <https://doi.org/10.1016/j.chemolab.2020.103937>, 2020.
- 655 Kühling, I.: Modellierung und räumliche Analyse der Phosphateintragspfade im Einzugsgebiet eines norddeutschen Tieflandbaches, Master thesis, Christian-Albrechts-University Kiel, 2011.
- Kumar, S., Getirana, A., Libonati, R., Hain, C., Mahanama, S., and Andela, N.: Changes in land use enhance the sensitivity of tropical ecosystems to fire-climate extremes, *Sci. Rep.*, 12, 1-11, <https://doi.org/10.1038/s41598-022-05130-0>, 2022.
- Lam, Q., Schmalz, B., and Fohrer, N.: Modelling point and diffuse source pollution of nitrate in a rural lowland catchment using the SWAT model, *Agric. Water Manag.*, 97, 317-325, <https://doi.org/10.1016/j.agwat.2009.10.004>, 2010.
- 660 Lam, Q., Schmalz, B., and Fohrer, N.: Assessing the spatial and temporal variations of water quality in lowland areas, Northern Germany, *J. Hydrol.*, 438, 137-147, <https://doi.org/10.1016/j.jhydrol.2012.03.01>, 2012.
- Lei, C., Wagner, P. D., and Fohrer, N.: Identifying the most important spatially distributed variables for explaining land use patterns in a rural lowland catchment in Germany, *J. Geogr. Sci.*, 29, 1788-1806, <https://doi.org/10.1007/s11442-019-1690-2>, 2019.
- 665 Lei, C., Wagner, P. D., and Fohrer, N.: Effects of land cover, topography, and soil on stream water quality at multiple spatial and seasonal scales in a German lowland catchment, *Ecol. Indic.*, 120, 106940, <https://doi.org/10.1016/j.ecolind.2020.106940>, 2021.
- Li, G., Zhang, F., Jing, Y., Liu, Y., and Sun, G.: Response of evapotranspiration to changes in land use and land cover and climate in China during 2001–2013, *Sci. Total Environ.*, 596, 256-265, <https://doi.org/10.1016/j.scitotenv.2017.04.080>, 2017.
- Li, S., Gu, S., Liu, W., Han, H., and Zhang, Q.: Water quality in relation to land use and land cover in the upper Han River Basin, China, *Catena*, 75, 216-222, <https://doi.org/10.1016/j.catena.2008.06.005>, 2008.
- 670 LKN: Landesbetrieb für Küstenschutz, Nationalpark und Meeresschutz Schleswig-Holstein, Discharge data from gauges Padenstedt, Sarlhusen and Willenscharen, 2020.
- Lu, Y., Song, S., Wang, R., Liu, Z., Meng, J., Sweetman, A. J., Jenkins, A., Ferrier, R. C., Li, H., and Luo, W.: Impacts of soil and water pollution on food safety and health risks in China, *Environ. Int.*, 77, 5-15, <https://doi.org/10.1016/j.envint.2014.12.010>, 2015.
- LvermA: Digitales Geländemodell (ATKIS-DGM LiDAR), Gitterweite 5 x 5 m, 2008.
- 675 LWK: Landwirtschaftskammer Schleswig-Holstein. Richtwerte für die Düngung 1991 and 2011, 13. Edition and 21. Edition. Rendsburg: LWK, 1991 and 2011.
- Maranguit, D., Guillaume, T., and Kuzyakov, Y.: Land-use change affects phosphorus fractions in highly weathered tropical soils, *Catena*, 149, 385-393, <https://doi.org/10.1016/j.catena.2016.10.010>, 2017.
- 680 Mevik, B.-H., Wehrens, R., and Liland, K. H.: pls: Partial least squares and principal component regression, R package version, 2, 2020.
- Mirghaed, F. A., Souri, B., Mohammadzadeh, M., Salmanmahiny, A., and Mirkarimi, S. H.: Evaluation of the relationship between soil erosion and landscape metrics across Gorgan Watershed in northern Iran, *Environ. Monit. Assess.*, 190, 1-14, <https://doi.org/10.1007/s10661-018-7040-5>, 2018.
- Monaghan, R., Wilcock, R., Smith, L., Tikkisetty, B., Thorrold, B., and Costall, D.: Linkages between land management activities and water quality in an intensively farmed catchment in southern New Zealand, *Agric. Ecosyst. Environ.*, 118, 211-222, <https://doi.org/10.1016/j.agee.2006.05.016>, 2007.

- Moriasi, D. N., Arnold, J. G., Van Liew, M. W., Bingner, R. L., Harmel, R. D., and Veith, T. L.: Model evaluation guidelines for systematic quantification of accuracy in watershed simulations, *Trans. ASABE*, 50, 885-900, <https://doi.org/10.13031/2013.23153>, 2007.
- Nafi'Shehab, Z., Jamil, N. R., Aris, A. Z., and Shafie, N. S.: Spatial variation impact of landscape patterns and land use on water quality across an urbanized watershed in Bentong, Malaysia, *Ecol. Indic.*, 122, 107254, <https://doi.org/10.1016/j.ecolind.2020.107254>, 2021.
- 690 Neitsch, S. L., Arnold, J. G., Kiniry, J. R., and Williams, J. R.: Soil and water assessment tool theoretical documentation version 2009, Texas Water Resources Institute, 2011.
- Noe, G. B., Hupp, C. R., and Rybicki, N. B.: Hydrogeomorphology influences soil nitrogen and phosphorus mineralization in floodplain wetlands, *Ecosystems*, 16, 75-94, <https://doi.org/10.1007/s10021-012-9597-0>, 2013.
- Federal Statistical Office.: Statistisches Jahrbuch für die Bundesrepublik Deutschland, Wiesbaden, Statistisches Bundesamt, 1992-2012.
- 695 Onderka, M., Wrede, S., Rodný, M., Pfister, L., Hoffmann, L., and Krein, A.: Hydrogeologic and landscape controls of dissolved inorganic nitrogen (DIN) and dissolved silica (DSi) fluxes in heterogeneous catchments, *J. Hydrol.*, 450, 36-47, <https://doi.org/10.1016/j.jhydrol.2012.05.035>, 2012.
- Oppelt, N., Rathjens, H., and Dörnhöfer, K.: Integration of land cover data into the open source model SWAT, First Sentinel-2 Preparatory Symposium, Frascati, Italy, pp. 23-27, 2012.
- 700 Peel, M. C., McMahon, T. A., and Finlayson, B. L.: Vegetation impact on mean annual evapotranspiration at a global catchment scale, *Water Resour. Res.*, 46, <https://doi.org/10.1029/2009WR008233>, 2010.
- Pfannerstill, M., Guse, B., and Fohrer, N.: A multi-storage groundwater concept for the SWAT model to emphasize nonlinear groundwater dynamics in lowland catchments, *Hydrol. Process.*, 28, 5599-5612, <https://doi.org/10.1002/hyp.10062>, 2014.
- Pott, C. A.: Integrated monitoring, assessment and modeling of nitrogen and phosphorus pollution in a lowland catchment in Germany: a long-term study on water quality, Christian-Albrechts Universität Kiel, 2014.
- 705 Pott, C. A. and Fohrer, N.: Best management practices to reduce nitrate pollution in a rural watershed in Germany, *Rev. Ambiente Agua*, 12, 888-901, <https://doi.org/10.4136/ambi-agua.2099>, 2017a.
- Pott, C. A. and Fohrer, N.: Hydrological modeling in a rural catchment in Germany, *Appl. Res. Agrotech.*, 10, 07-16, <https://doi.org/10.5935/PAAET.V10.N1.01>, 2017b.
- 710 Rathjens, H., Dörnhöfer, K., and Oppelt, N.: IRSeL—An approach to enhance continuity and accuracy of remotely sensed land cover data, *Int. J. Appl. Earth Obs. Geoinf.*, 31, 1-12, <https://doi.org/10.1016/j.jag.2014.02.010>, 2014.
- Riitters, K.: Pattern metrics for a transdisciplinary landscape ecology, *Landsc. Ecol.*, 34, 2057–2063, <https://doi.org/10.1007/s10980-018-0755-4>, 2019.
- Ripl, W., Janssen, T., Hildmann, C., and Otto, I.: Entwicklung eines Land-Gewässer Bewirtschaftungskonzeptes zur Senkung von Stoffverlusten an Gewässer (Stör-Projekt I und II), Forschungsbericht, TU Berlin, 1996.
- 715 Shawul, A. A., Chakma, S., and Melesse, A. M.: The response of water balance components to land cover change based on hydrologic modeling and partial least squares regression (PLSR) analysis in the Upper Awash Basin, *J. Hydrol.: Reg. Stud.*, 26, 100640, <https://doi.org/10.1016/j.ejrh.2019.100640>, 2019.
- Shi, P.-J., Yuan, Y., Zheng, J., Wang, J.-A., Ge, Y., and Qiu, G.-Y.: The effect of land use/cover change on surface runoff in Shenzhen region, China, *Catena*, 69, 31-35, <https://doi.org/10.1016/j.catena.2006.04.015>, 2007.
- 720 Shi, Z., Ai, L., Li, X., Huang, X., Wu, G., and Liao, W.: Partial least-squares regression for linking land-cover patterns to soil erosion and sediment yield in watersheds, *J. Hydrol.*, 498, 165-176, <https://doi.org/10.1016/j.jhydrol.2013.06.031>, 2013.
- Shrestha, S., Bhattacha, B., Shrestha, M., and Shrestha, P. K.: Integrated assessment of the climate and landuse change impact on hydrology and water quality in the Songkhram River Basin, Thailand, *Sci. Total Environ.*, 643, 1610-1622, <https://doi.org/10.1016/j.scitotenv.2018.06.306>, 2018.
- 725 Shuster, W. D., Bonta, J., Thurston, H., Warnemuende, E., and Smith, D.: Impacts of impervious surface on watershed hydrology: A review, *Urban Water J.*, 2, 263-275, <https://doi.org/10.1080/15730620500386529>, 2005.
- Singh, H., Singh, D., Singh, S. K., and Shukla, D.: Assessment of river water quality and ecological diversity through multivariate statistical techniques, and earth observation dataset of rivers Ghaghara and Gandak, India, *Int. J. River Basin Manag.*, 15, 347-360, <https://doi.org/10.1080/15715124.2017.1300159>, 2017.
- 730 Song, S., Schmalz, B., and Fohrer, N.: Simulation, quantification and comparison of in-channel and floodplain sediment processes in a lowland area—A case study of the Upper Stör catchment in northern Germany, *Ecol. Indic.*, 57, 118-127, <https://doi.org/10.1016/j.ecolind.2015.03.030>, 2015.
- Sood, A., Ghosh, S., and Upadhyay, P.: Impact of land cover change on surface runoff, *Advances in Remote Sensing for Natural Resource Monitoring*, 150-169, <https://doi.org/10.1002/9781119616016.ch10>, 2021.
- 735 Srinivasan, J. T. and Reddy, V. R.: Impact of irrigation water quality on human health: A case study in India, *Ecol. Econ.*, 68, 2800-2807, <https://doi.org/10.1016/j.ecolecon.2009.04.019>, 2009.
- Taka, M., Sillanpää, N., Niemi, T., Warsta, L., Kokkonen, T., and Setälä, H.: Heavy metals from heavy land use? Spatio-temporal patterns of urban runoff metal loads, *Sci. Total Environ.*, 817, 152855, <https://doi.org/10.1016/j.scitotenv.2021.152855>, 2022.
- 740 Tan, M. L., Gassman, P. W., Liang, J., and Haywood, J. M.: A review of alternative climate products for SWAT modelling: Sources, assessment and future directions, *Sci. Total Environ.*, 795, 148915, <https://doi.org/10.1016/j.scitotenv.2021.148915>, 2021.
- Tigabu, T. B., Wagner, P. D., Hörmann, G., and Fohrer, N.: Modeling the spatio-temporal flow dynamics of groundwater-surface water interactions of the Lake Tana Basin, Upper Blue Nile, Ethiopia, *Hydrol. Res.*, 51, 1537-1559, <https://doi.org/10.2166/nh.2020.046>, 2020.
- 745 Uuemaa, E., Antrop, M., Roosaare, J., Marja, R., and Mander, Ü.: Landscape metrics and indices: an overview of their use in landscape research, *Living Rev. Landscape Res.*, 3, 1-28, <http://www.livingreviews.org/lrlr-2009-1>, 2009.
- Venohr, M.: Einträge und Abbau von Nährstoffen in Fließgewässern der oberen Stör, Diplomarbeit im Fach Geographie, Christian-Albrechts-Universität Kiel, 2000.
- Wagner, P., Kumar, S., and Schneider, K.: An assessment of land use change impacts on the water resources of the Mula and Mutha Rivers catchment upstream of Pune, India, *Hydrol. Earth Syst. Sci.*, 17, 2233-2246, <https://doi.org/10.5194/hess-17-2233-2013>, 2013.
- 750 Wagner, P. D. and Fohrer, N.: Gaining prediction accuracy in land use modeling by integrating modeled hydrologic variables, *Environ Model Softw.*, 115, 155-163, <https://doi.org/10.1016/j.envsoft.2019.02.011>, 2019.
- Wagner, P. D. and Waske, B.: Importance of spatially distributed hydrologic variables for land use change modeling, *Environ Model Softw.*, 83, 245-254, <https://doi.org/10.1016/j.envsoft.2016.06.005>, 2016.
- Wagner, P. D., Hoermann, G., Schmalz, B., and Fohrer, N.: Characterisation of the water and nutrient balance in the rural lowland catchment of the Kielstau, *Hydrol. Wasserbewirtsch.*, 62, 145-158, 2018.
- 755 Wagner, P. D., Bhallamudi, S. M., Narasimhan, B., Kantakumar, L. N., Sudheer, K., Kumar, S., Schneider, K., and Fiener, P.: Dynamic integration of land use changes in a hydrologic assessment of a rapidly developing Indian catchment, *Sci. Total Environ.*, 539, 153-164, <https://doi.org/10.1016/j.scitotenv.2015.08.148>, 2016.

- 760 Wang, Q., Xu, Y., Xu, Y., Wu, L., Wang, Y., and Han, L.: Spatial hydrological responses to land use and land cover changes in a typical catchment of the Yangtze River Delta region, *Catena*, 170, 305-315, <https://doi.org/10.1016/j.catena.2018.06.022>, 2018.
- Wang, W., Wu, X., Yin, C., and Xie, X.: Nutrition loss through surface runoff from slope lands and its implications for agricultural management, *Agric. Water Manag.*, 212, 226-231, <https://doi.org/10.1016/j.agwat.2018.09.007>, 2019.
- Wei, W., Chen, L., Fu, B., Huang, Z., Wu, D., and Gui, L.: The effect of land uses and rainfall regimes on runoff and soil erosion in the semi-arid loess hilly area, China, *J. Hydrol.*, 335, 247-258, <https://doi.org/10.1016/j.jhydrol.2006.11.016>, 2007.
- 765 Wigmosta, M. S., Vail, L. W., and Lettenmaier, D. P.: A distributed hydrology-vegetation model for complex terrain, *Water Resour. Res.*, 30, 1665-1679, <https://doi.org/10.1029/94WR00436>, 1994.
- Wijesekara, G., Gupta, A., Valeo, C., Hasbani, J.-G., Qiao, Y., Delaney, P., and Marceau, D.: Assessing the impact of future land-use changes on hydrological processes in the Elbow River watershed in southern Alberta, Canada, *J. Hydrol.*, 412, 220-232, <https://doi.org/10.1016/j.jhydrol.2011.04.018>, 2012.
- 770 Wold, S., Sjöström, M., and Eriksson, L.: PLS-regression: a basic tool of chemometrics, *Chemom. Intell. Lab. Syst.*, 58, 109-130, [https://doi.org/10.1016/S0169-7439\(01\)00155-1](https://doi.org/10.1016/S0169-7439(01)00155-1), 2001.
- Wu, J. and Lu, J.: Spatial scale effects of landscape metrics on stream water quality and their seasonal changes, *Water Res.*, 116811, <https://doi.org/10.1016/j.watres.2021.116811>, 2021.
- 775 Xu, S., Li, S.-L., Zhong, J., and Li, C.: Spatial scale effects of the variable relationships between landscape pattern and water quality: Example from an agricultural karst river basin, Southwestern China, *Agric. Ecosyst. Environ.*, 300, 106999, <https://doi.org/10.1016/j.agee.2020.106999>, 2020.
- Yan, B., Fang, N., Zhang, P., and Shi, Z.: Impacts of land use change on watershed streamflow and sediment yield: An assessment using hydrologic modelling and partial least squares regression, *J. Hydrol.*, 484, 26-37, <https://doi.org/10.1016/j.jhydrol.2013.01.008>, 2013.
- 780 Yu, D., Li, X., Cao, Q., Hao, R., and Qiao, J.: Impacts of climate variability and landscape pattern change on evapotranspiration in a grassland and landscape mosaic, *Hydrol. Process.*, 34, 1035-1051, <https://doi.org/10.1002/hyp.13642>, 2020.
- Zhang, W., Li, H., Hyndman, D. W., Diao, Y., Geng, J., and Pueppke, S. G.: Water quality trends under rapid agricultural expansion and enhanced in-stream interception in a hilly watershed of Eastern China, *Environ. Res. Lett.*, 15, 084030, <https://doi.org/10.1088/1748-9326/ab8981>, 2020a.
- 785 Zhang, W., Li, H., Pueppke, S. G., Diao, Y., Nie, X., Geng, J., Chen, D., and Pang, J.: Nutrient loss is sensitive to land cover changes and slope gradients of agricultural hillsides: evidence from four contrasting pond systems in a hilly catchment, *Agric. Water Manag.*, 237, 106165, <https://doi.org/10.1016/j.agwat.2020.106165>, 2020b.
- Zhang, Y.-K. and Schilling, K.: Increasing streamflow and baseflow in Mississippi River since the 1940s: Effect of land use change, *J. Hydrol.*, 324, 412-422, <https://doi.org/10.1016/j.jhydrol.2005.09.033>, 2006.