

Application of an improved distributed hydrological model based on soil – gravel structure in the Niyang River basin, Qinghai – Tibet Plateau

5 Pengxiang Wang^{1,2,3}, Zuhao Zhou^{1*}, Jiajia Liu¹, Chongyu Xu^{3,7}, Kang Wang³, Yangli Liu⁴, Jia Li⁵, Yuqing Li⁶, Yangwen Jia¹, Hao Wang¹

¹State Key Laboratory of Simulation and Regulation of Water Cycle in River Basin, China Institute of Water Resources and Hydropower Research, Beijing 100038, China

²China Three Gorges Corporation, Beijing 100038, China

³State Key Laboratory of Water Resources and Hydropower Engineering Science, Wuhan University, Wuhan 430072, China

10 ⁴China Power Construction Group Guiyang Engineering Corporation Limited, Guiyang 550081, China

⁵Bureau of South to North Water Transfer of Planning, Designing and Management, Ministry of Water Resources, Beijing 100038, China

⁶Department of Water Resources and Civil Engineering, Tibet Agriculture and Animal Husbandry College, Nyingchi 860000, China

15 ⁷Department of Geosciences, University of Oslo, Oslo, Norway

Correspondence to: Zuhao Zhou (zhzh@iwhr.com)

Abstract: Runoff formation and hydrologic regulation mechanisms in mountainous cold regions are the basis for investigating the response patterns of hydrological processes under climate change. Owing to plate movements and climatic effects, the surface soils of bare lands and grasslands on the Qinghai–Tibet Plateau (QTP) are thin, and the soil below the surface contains abundant gravel. This unique geological structure, combined with snow and frozen soil, affects the water cycle in this region. To investigate the influence of the underlying surface structure on water–heat transport and water circulation processes on the QTP, we performed a comprehensive study combining water–heat transfer field experiments and developed a water and energy transfer processes model for the QTP (WEP–QTP) based on the original water and energy transfer processes model in cold regions (WEP–COR). The Niyang River basin, located on the QTP, was selected as the study area to evaluate the consistency between theoretical hypotheses, observations, and modeling results. The model divided the uniform soil profile into a dualistic soil–gravel structure. When no phase change was present in the ground, two infiltration models based on the dualistic soil–gravel structure were developed, these used the Richards equation to model a non-heavy rain scenario and the multi-layer Green–Ampt model for a heavy rain scenario. During the freeze–thaw period, a water–heat coupling model based on the continuum of the snow–soil–gravel layer was constructed. By considering gravel, the improved model corrected the overestimation of the moisture content below the surface soil predicted by the original model and reduced the moisture content relative error (RE) from 33.74% to 12.11%. The addition of the snow layer not only reduced the temperature fluctuation of the surface soil, but also revised the overestimation of the freeze–thaw speed predicted by the original model with the help of the gravel. The temperature root-mean-square error was reduced from 1.16 °C to 0.86 °C. In the fully thawed period, the dualistic soil–gravel structure improved the regulation effect of

删除: a new

删除: Basin

删除: The

删除: -

删除: has a

删除: layer on top of a thick soil-

删除: mixture (SGM) layer.

删除: the

删除:

删除: area, significantly affect water circulation in the entire

删除: the

删除: -

删除: process in

删除: and

20

删除: Water

删除: Energy

删除: Processes

25

删除: in

删除: -

删除:),

删除: Water

30

删除: Energy

删除: Processes

删除: Cold Regions

删除: -

删除: Basin

删除: hypothesis, observation

删除: divides

35 groundwater on flow, thus stabilizing the flow process. The maximum RE at the flow peak and trough decreased by 88.2% and 21.3%, respectively. In the freeze-thaw period, by considering the effect of the snow-soil-gravel layer continuum, the freezing and thawing processes of WEP-QTP lagged those of WEP-COR by approximately one month. The groundwater simulated by WEP-QTP had more time to recharge the river, which better represented the observed "tailing" process from September onwards. The flow simulated by the WEP-QTP model was more accurate and closer to the actual measurements, 40 with a Nash-Sutcliffe efficiency > 0.75 and |RE| < 10%. The improved model reflects the effects of the unique QTP environment on water-heat transport and water cycling and can thus be used for hydrological simulation on the QTP.

1 Introduction

The Qinghai-Tibet Plateau (QTP), also known as the "Asian Water Tower," is a major cold mountainous area located at low latitude and high altitude. This region has unique geology and landforms, is sensitive to climate change (Liu et al., 2019), 45 and is vital for the water resource security of China and southeast Asia (Yu et al., 2012). The extensive glaciers, snow cover, and permanently and seasonally frozen soil in the area have major impacts on the water cycle (Li et al., 2016; Ding et al., 2020). Unraveling the mechanisms of runoff formation and hydrological regulation in this region is the basis for studying the response patterns of hydrological processes under a changing climate.

In both permafrost and permafrost-free areas, the ground undergoes seasonal freezing and thawing, which has received a lot 50 of attention regarding hydrological research because of the great variety of biological and physical processes occurring on the surface and subsurface (Chen et al., 2014; Kurylyk et al., 2014). During soil freezing, ice in the seasonally thawed layer blocks most of the pores in the soil, hinders infiltration, and thus affects water movement in the soil (Cheng and Jin, 2013). In terms of the hydrological cycle, the frozen soil layer prevents rainfall and snowmelt infiltration, forcing surface runoff down slope, which may lead to severe flash floods. In addition, frozen soil affects the quantity of groundwater recharge 55 supplemented by infiltration and the distribution ratio of water resources allocated between rivers and lakes (Ireson et al., 2013; Larsbo et al., 2019). The simulation accuracy of water and heat transport in the seasonally thawed layer directly affects the evaluation of water resources and analysis of runoff evolution in the QTP area. However, soil water and heat transfer processes are relatively complex and influenced by several factors (Watanabe and Kugisaki, 2017), such as soil structure (Dai et al., 2019; Franzluebbers, 2002) and heat conduction under snow cover (Lundberg et al., 2016).

60 During the continuous uplift of the QTP, a series of ascending areas (loci of denudation) and descending areas (loci of deposition) were formed. Quaternary deposits are generally thinner in denuded areas and thicker in depositional areas (e.g., valleys and plains). As a result of the collision of the Indian and Eurasian plates, there are many gravel and rock fragments within QTP Quaternary sediments (Chen et al., 2015; Deng et al., 2019). The abundance of gravel allows the formation of many interconnected pore channels within these sediments, thus increasing their saturated hydraulic conductivity (Beibei et al., 2009). The greater thermal conductivity and heat capacity of gravel compared to those of dry soil also affect the heat transfer process (Yi et al., 2013). In addition, in the cold alpine regions of the QTP, the decomposition of biomass occurs

删除: valley

删除: -

删除: -

删除: -

删除: process

删除: -

删除: that

删除: -

删除: -

删除: showed

删除: after

删除: -

删除:

删除: -

删除: cycle process

删除: in

删除: -

删除: with

删除: landform

删除: resources

删除: Southeast

删除: mechanisms

删除: change conditions

删除: the

删除: at

删除: seasonal thaw

删除: As for

删除: the

mostly in the surface layers of Quaternary sediments owing to the low temperatures, resulting in the formation of a thin soil layer that is more highly developed and accumulates more organic matter than deeper layers (Sun, 1996). This soil stratification is particularly evident in alpine meadows (Yang et al., 2009; Pan et al., 2017).

The existing hydrological models for cold regions, such as the SHAWDHM model (Zhang et al., 2013), GEOTop model (Rigon et al., 2006), cold regions hydrological model (CRHM) (Pomeroy et al., 2007), and variable infiltration capacity (VIC) model (Cherkauer and Lettenmaier, 2003), consider the processes of water and heat transport in the soil and can simulate water cycling in cold regions to a certain extent. However, these models define the simulated object of the water-heat coupled transport process as a homogeneous medium, while overlooking the stratified soil structure of the QTP.

By calibrating certain parameters, the effect of gravel on water and heat transfer can be hidden to some extent, and the simulation effect can be improved. However, some errors remain in the simulation, and it is difficult to objectively reflect the influence of the stratified geological structure on water-heat transport and the hydrological cycle.

It is particularly important to consider the influence of the unique underlying surface of the QTP on water-heat transport and water circulation, especially in the context of global climate change and frozen soil degradation. The objectives of the present study were to: (1) develop infiltration models based on the dualistic soil-gravel structure under fully thawed conditions; (2) develop a modeling framework representing coupled water and heat transfer in the ground based on the snow-soil-gravel layer continuum through field water and heat monitoring experiments during the freeze-thaw period (the temperature of the calculation unit was lower than 0 °C); and (3) investigate the effect of the dualistic soil-gravel structure on the hydrological cycle by building a water and energy transfer processes model of the QTP (WEP-QTP) for the Niyang River basin, a tributary of the Yarlung Zangbo River on the QTP.

2 Materials and methods

2.1 Study sites and data

2.1.1 Study area

The Niyang River is located on the left bank of the lower reaches of the Yarlung Zangbo River, between 29°28'–30°38' N and 92°10'–94°35' E in the Linzhi area of southeastern Tibet. It originates from Cuomoliang Mountain on the west side of the Mila Mountain in the Tibet Autonomous Region of China at an altitude of approximately 5000 m above sea level (a.s.l.). The Niyang River flows from west to east through Gongbujiangda County and Bayi Town and finally flows into the Yarlung Zangbo River in the Bayi District of Nyingchi City; it has a vertical drop of 2080 m with an average slope of 0.73%. The basin is approximately 230 km long from east to west, and 110 km wide from north to south. The area of the watershed is 17,535 km², ranking fourth among the five tributaries of the Yarlung Zangbo River, and its runoff is second only to that of Palungzangbu River. The Niyang River basin is located at the intersection of the east-west and north-south mountain ranges of Tibet. The basin sediments consist of greywacke and litharenite with low-moderate textural and mineralogical maturity

删除: in

删除: Cold Regions Hydrological Model

删除: Variable Infiltration Capacity

删除: in cold regions

删除: the

删除: cycle processes

删除: generally

删除: -

删除: one-dimensional

删除: upper and lower layered

删除: the

删除: difference in

删除: between SGM and soil

删除: there remain

删除: upper and lower

删除: structures

删除: -

删除: the

删除: -

删除: the

删除: ,

删除: heat and

删除: transfers

删除: soil/SGM layer

删除:),

删除: the distributed

删除: cycle

删除: -

(Huyan et al., 2022). The terrain in the watershed is complex, with staggered large and small mountains and large elevation fluctuations. The elevation of the river valley is generally 3000–4000 m a.s.l. The elevation of most mountain peaks on both sides of the valley is approximately 5000 m a.s.l, reaching a maximum of 6870 m a.s.l. The Niyang River basin belongs to the plateau temperate monsoon climate zone. The multi-year average precipitation is affected by the Indian Ocean tropical ocean monsoon. Under the effect of the Indian low pressure, the southwest monsoon pushes a large quantity of warm and humid air from the Bay of Bengal along the Yarlung Zangbo River valley to the Niyang River basin, causing precipitation in the basin; rainfall is often heavy and varies markedly with elevation. The average elevation of the basin is 4688.6 m a.s.l, the average annual precipitation is 1416 mm, and the average annual temperature is approximately 8 °C. Evident temperature changes occur from east to west with changing elevation. The frozen soil in the study area is mainly seasonal. Permafrost accounts for approximately 24% of the basin area, mainly distributed in the upper reaches of the basin and high-altitude areas on both sides of the main stream.

In the present study, a water-heat coupling process monitoring experiment was carried out during the freeze-thaw period on the side of Sejila Mountain in the lower reaches of the Niyang River basin. The latitude and longitude of the study site are 29°27'12" N and 94°21'45" E, respectively, and the altitude is 4607 m a.s.l. The annual average temperature of the experimental site, a seasonally frozen soil area, is 5.28 °C. The experimental period was from 2016 to 2017, during which the freeze-thaw period was from November 2016 to March 2017. The distribution of stations within the watershed and location of the experimental area are shown in Fig. 1. Before the field experiment, nuclear magnetic resonance was used to calibrate the water and heat transport monitoring instruments under seasonal freezing and thawing soil conditions on the plateau. A working area with a length of 1.0 m, width of 1.0 m, and depth of 2.0 m was excavated at the experimental site. A time-domain reflectometry sensor was used to monitor the liquid water content, a PT100 sensor was used to measure the temperature, and a TensionMark sensor was used to measure the soil water potential; each were installed every 10 cm vertically in the experimental pit to a depth of 1.6 m. Following installation, the pit was backfilled with undisturbed soil and data were collected automatically. During the experiment, the monitoring instrument was inspected regularly and the snow thickness was measured at the same time.

删除: 3,000–4,000

删除: 5,000

删除: up to 6,870

删除: Basin

删除: amount

删除: Valley

删除: Basin

删除: with heavy

删除: large vertical changes.

删除: 1,416

删除: Obvious

删除: the

删除: mainstream

删除: -

删除: -

删除: mountainside

删除: the

删除: Basin

删除: and latitude

删除: and 29°27'12" N

删除: 4,607

删除: is 5.28 °C, which is

删除: -

删除: while

删除: station

删除: the

删除: points

删除: Figure




Figure 1: Overview of the Niyang River basin including the distribution of stations, sampling points, and experimental site.

2.1.2 Data description

The data required for this study were mainly divided into two categories: 1) data required for model construction (including meteorology, geology and landforms, terrain, soil type, land-use type, vegetation index, and glacier data); and 2) data used to verify the model results (including historical and experimental monitoring data).

Meteorological data, including temperature, relative humidity, sunshine hours, and wind speed, were collected by the Nyingchi Meteorological Station within the basin and the Jiali Meteorological Station outside the basin, from 1961 to 2018.

These data were obtained from the China Meteorological Data Network (<http://data.cma.cn>). In addition to the two meteorological stations in Nyingchi and Jiali, the rainfall data sources also included six rainfall stations (Gongbujiangda, Gengzhang, Baheqiao, Niqu, Kelaqu, and Zengba; data from 2013 to 2015) from the watershed and the contour map of annual precipitation in the Tibet Water Resources Bulletin (2012–2017). The temperature, precipitation, relative humidity, sunshine duration, and wind speed in the basin were interpolated from the meteorological station data using the reversed distance squared method. Temperature and precipitation were additionally corrected for elevation. The temperature correction factor was $-6\text{ }^{\circ}\text{C}/\text{km}$. For the precipitation data, the precipitation-elevation relationship was determined according to the contour map of annual precipitation in the Tibet Water Resources Bulletin and the precipitation station data.

删除: Basic situation and station

删除: the Niyang River Basin

删除: the first were

删除: mainly

删除: landform

删除:), while the second were

删除: :

删除: data

删除: in

删除: -

删除: The

删除: 2013–2015) including

删除: in

删除: by

删除: -

删除: As for

删除: -

Subsequently, the daily precipitation data were obtained for the basin through elevation interpolation (Wang et al., 2017) of the precipitation data from six rainfall stations and two meteorological stations to avoid precipitation errors at high altitudes caused by altitude limitations of precipitation stations.

Geology and landform data: owing to plate movements and climatic effects, the surface soils of bare land and grassland on the QTP are thin and the underlying soils contain abundant gravel (Fig. 2). According to the geological characteristics of the QTP, we selected 24 sampling points at different altitudes, from the source to the estuary of the Niyang River basin, for field investigation of soil texture (Fig. 1). Among these, points 1–16 were located along the river, while points 17–24 were distributed from the foot of the mountain to the peak. The soil thicknesses and compositions at the 24 sampling points were measured and analyzed. The surface soil of the Niyang River basin was mainly sandy loam, with average sand, silt, and clay contents of 55.89%, 31.2%, and 12.91%, respectively. The underlying mixture of soil and gravel mainly comprised rounded gravel containing pebbles; the gravel content was approximately 50%–65%, while the clay content was 5%–10%, and pores were filled with medium- and fine-grained sand. The thickness of the surface soil gradually decreased from the foot to the peak of the mountain; it was greater than 100 cm in the valley and decreased with higher altitude to approximately 40 cm on the upper hillside.



Figure 2: Soil and gravel structure of the Niyang River basin (pictures taken near the experimental site labeled in Fig. 1).

Terrain data: elevation data (Digital Elevation Model, DEM) used in this study were obtained from the SRTM90 (Shuttle Radar Topography Mission), jointly measured by the National Aeronautics and Space Administration and National Imagery and Mapping Agency with an accuracy of 90 m.

Soil data: soil-type data were obtained from the second national soil census and “Chinese Soil Records”. Land-use data were obtained from the Resource Environment Science and Database Center, Institute of Geographic Sciences and Natural Resources Research, Chinese Academy of Sciences (<http://www.resdc.cn>); the data resolution was 30 m.

Vegetation index: moderate-resolution imaging spectroradiometer data (<https://ladsweb.modaps.eosdis.nasa.gov/search/>) from 2000 to 2017 were selected as the data source. Among these data, the leaf area index accuracy was 500 m and

删除: in

删除: : Due

删除: the combined

删除: plate tectonics, weathering, and erosion, a unique

删除: with a

删除: soil layer on the top and a thick SGM layer on the

删除: on

删除: them

删除: layer

删除: Basin is

删除: ,

删除: ,

删除: SGM layer is

删除: round

删除: –

删除: –

删除: the

删除: are

删除: layer

删除: decreases

删除: , and is

删除: with higher altitude and increases to more than 10



normalized difference vegetation index accuracy was 250 m; these were mainly used to calculate evaporation and vegetation interception processes, respectively.

Glacier data: the glacier data included the second glacial catalogue data set of China (1:100,000) and Landsat TM/ETM+/OLI remote sensing images. The second glacier inventory data were obtained from the China Cold and Arid Regions Science Data Center (<http://westdc.westgis.ac.cn/>). Landsat data were obtained from the data sharing platform of the United States Geological Survey (<http://glovis.usgs.gov/>). ENVI software was used to extract glaciers, and the boundaries of the glaciers were finally determined with reference to Google Earth imagery. The glaciers in the basin were classified according to China's second glacier cataloging rules and the glacier area was calculated. The volume of each glacier was calculated using the area-volume empirical formula (Grinsted, 2013; Radić and Hock, 2010).

The distribution of the main hydrologically relevant features of the basin used in the model construction is shown in Appendix A. Model verification data included historical and experimental monitoring data. Historical data included daily measured flow data from the Gongbujiangda Hydrological Station (2013–2016, 2018), Baheqiao Hydrological Station (2013–2014), and Duobu Station (2013–2018). Experimental monitoring data included snow thickness, soil temperature and volumetric water content of the experimental site from 2016 to 2017.

2.2 Model improvement

Based on the water and energy transfer processes in cold regions (WEP-COR) model (Li et al., 2019), this study developed the improved WEP-QTP model. The WEP-COR model is a distributed hydrological model. To consider the impact of the topography and land cover on the water cycle in large basins, the calculation unit of the WEP-COR model is contour bands (i.e., bands at different elevation intervals) inside small sub-basins. Each unit is classified into five classes: water body, soil-vegetation, irrigated farmland, non-irrigated farmland, and impervious area. The water body class includes rivers, lakes, and glaciers. The soil-vegetation class includes bare land, grassland, and woodland. The impervious area class consists of urban buildings and impervious surfaces. The calculation result of the water and heat flux in each class is weighted by area to obtain the water and heat flux of the contour band. An introduction to the WEP-COR model structure and simulation method is provided in Appendix B.

In contrast to the cold areas where the WEP-COR model is generally applied, the seasonally thawed layer above the impervious boundary (in permafrost regions, the impervious boundary is the permafrost layer) on the QTP is mostly a dualistic soil-gravel structure, which closely interacts with surface hydrological processes and is a key link affecting the QTP hydrological cycle. Therefore, we took the seasonally thawed layer above the impermeable boundary as the research object and improved the water and heat simulation methods for the fully thawed and freeze-thaw periods in soil-vegetation, irrigated farmland, and non-irrigated farmland areas.

Under fully thawed conditions, the calculation object of water movement was defined as the dualistic soil-gravel structure (Fig. 3a). The upper layers were soil (s-layers), whose thickness was determined by the location of the calculation unit, and which gradually decreased from the foot to the peak of the mountain (Fig. 3b). The lower layers were a mixture of gravel and

删除: The

删除: China's

删除: glacier inventory

删除: (USGS)

删除: the

删除: by

删除: -

删除: -

删除:

删除: data

删除: the

删除: the

删除: station

删除: The experimental

删除: the

删除: -

删除: Water

删除: Energy

删除: Processes

删除: Cold Regions

删除: -

删除: Water and Energy transfer Processes in the

删除: (WEP-QTP)

删除: -

删除: -

删除: (

删除: -

删除: Impervious


195 soil (g-layers), dominated by gravel, the thickness of which was the total thickness of the aquifer and vadose zone above the impermeable boundary minus the surface soil thickness.

删除: SGM layer.


During the freeze-thaw period, in addition to considering the impact of gravel on water-heat transfer, the contribution of snow to thermal insulation was also considered. A snow layer was added on top of the dualistic soil-gravel structure. The water-heat coupling simulation object was defined as the snow-soil-gravel layer continuum (Fig. 3c).

删除: and its higher reflectivity to shortwave solar radiation were


200



(a)



(b)



(c)

Figure 3: Layered calculation structure of the dualistic soil-gravel structure (a), snow-soil-gravel layered structure (b), and snow-soil-gravel layer continuum (c).

Snow was treated as a single layer (layer 0) in the model, and its thickness was determined by the snow water equivalent and snow density. As the surface soil is more sensitive to changes in atmospheric temperature, the thicknesses of layers 1 and 2 were each set to 10 cm, while the thicknesses of the other s-layers and g-layers were set to 20 cm. Considering the active range of seasonally frozen soil, the depth of the water-heat numerical simulation in the model was set as 2 m. When the depth of groundwater is < 2 m, the depth of the water-heat numerical simulation equates to the depth of groundwater, and when the depth of groundwater is > 2 m, the part below 2 m is treated as the transition layer. The lower boundary was the impermeable layer, and the depth from the surface to the impermeable layer was an adjustable parameter in the model that can be adjusted based on the actual basin conditions. In regions with seasonally frozen soil, the model considered the entire freezing and bidirectional thawing processes of the soil. For the permafrost regions, the surface layer freezing and thawing processes were considered, while the lower permafrost layer was used as the lower boundary condition.

2.2.1 Fully thawed period

In the non-heavy rain infiltration scenario, the basic equation describing water movement remained the same and is Darcy's law. However, the high gravel percentage of the g-layer, changes its water retention curves and affects its matrix suction under different moisture conditions (Cousin et al., 2003). Therefore, a revised formula for water retention properties of the soil-gravel mixture was used to describe the water retention curves of the lower g-layers (Wang et al., 2013):

- 删除: "
- 删除: "
- 删除:)
- 删除: the "
- 删除: "
- 删除:)
- 删除: the first and second
- 删除: each
- 删除: third through
- 删除: eleventh
- 删除: divided evenly, each with a thickness of
- 删除: Considering the active range of seasonal frozen soil ...
- 删除: equations
- 删除: were
- 删除: as the WEP-COR model.
- 删除: in
- 删除: unsaturated state, since
- 删除: can neither conduct nor store water, the gravel, whi ...
- 删除: SGM
- 删除: , hinders the movement of water and affects the
- 删除: the
- 删除: lower gravel layer

$$\frac{\theta_l - \theta_r}{\theta_s - \theta_r} = A_m h^{-\lambda} (1 - B_m \omega_{gravel}) \quad (1)$$

where A_m and B_m are empirical parameters, h is the **matrix** suction (cm), λ is the pore-size distribution parameter ($\lambda < 1$), and ω_{gravel} is the volume ratio of **gravel in the g-layer**. Wang et al. (2013) provided a full description of the factors and parameters used in Equation (1) ($A_m = 1.45$, $B_m = 0.2$, $\lambda = 0.18$) in this study.

230 In the heavy rain infiltration scenario, the multi-layer Green–Ampt equation (Jia and Tamai, 1998) was used to calculate the infiltration process when the infiltration front (INF) was in the **s-layers**, which is the same as in WEP_–COR (Equations B4 to B11 in Appendix B). **As** the INF moves to the interface of the **s-layer** and **g-layer** (layer *itf*), the front movement slows down because the water suction of the **g-layer** is less than that of the **s-layer**. **When** the water has the same potential energy in the **s-layer** and **g-layer**, the INF breaks through the critical surface, and then the infiltration rate stabilizes (Fig. 4). Therefore, a

235 new infiltration model was proposed by improving the method of infiltration rate in the multi-layer Green–Ampt equation (Equation B4 in Appendix B). The stable infiltration rate after **the** INF **breaks** through **layer itf** was calculated as follows:

$$f_{gravel} = k_{soil} \left(1 + \frac{A_{itf}}{B_{itf} + F_{itf}} \right) \quad (2)$$


where f_{gravel} is the stable infiltration rate after breaking through **layer itf**; k_{soil} is the saturated hydraulic conductivity of the **s-layer** (mm/h); F_{itf} is the cumulative infiltration when the front breaks through layer *itf* (mm); A_{itf} is the total water capacity of the **s-layers** above the interface (mm); **and** B_{itf} is the error caused by the different soil moisture content of the **s-layers** above the interface (mm). **A full description of the two parameters A_{itf} and B_{itf} has been provided by Jia and Tamai (1998), and their calculation is shown in Appendix B by Equations B5 and B6.**

The gravel increases the porosity in the **g-layers**, and the pores connect to form a fast channel for transporting water during heavy **rain**. After the INF breaks through the interface, the **infiltrating** water preferentially recharges the groundwater through

245 **macropores**. The accumulated infiltration quantity is as follows:

$$F = F_{itf} + Q_{gd} \quad (3)$$

where Q_{gd} is the quantity of groundwater **recharged** by infiltration, $Q_{gd} = f_{gravel}(t - t_{itf})$, and t_{itf} is the time when the INF breaks through the interface.



删除: matric

删除: the gravel in the SGM layer

删除: soil layer

删除: -

删除: Equation

删除: When

删除: soil

删除: SGM (Layer

删除: SGM

删除: soil (Mao and Shang, 2010). Until the

删除: soil

删除: the SGM

删除: breaking

删除: Layer

删除: Layer

删除: soil

删除: soil

删除: soil

删除:); F_{itf} is the cumulative infiltration when the front


删除: SGM

删除: rains

删除: infiltration

删除: the

删除: recharge



250 **Figure 4: Cumulative infiltration process of the WEP-QTP model.**

Under fully thawed conditions, all the water is in a liquid state, and heat conduction has only a minor effect on the water migration process. Therefore, for simulation efficiency, only moisture simulation was performed during this period.

2.2.2 Freeze-thaw period

255 During the freeze-thaw period, the water-heat coupling simulation object was defined as the snow-soil-gravel layer continuum (Fig. 3b). On the QTP, variations in temperature and precipitation caused by altitude differences result in more snow accumulation and less melting at higher altitudes. Therefore, avalanches are common in this region. In this model, we established a snow thickness threshold. When the difference in snow thickness between two adjacent calculation units (the contour bands) exceeds this threshold, an avalanche will occur. The snow in the higher-altitude calculation unit slides into
260 the next unit until the two units have the same snow thickness. The daily variation of snow water equivalent was calculated as follows:

$$S = S_p - S_d - S_m \quad (4)$$

where S is the daily variation of snow water equivalent (mm/d); S_p is the snow water equivalent from precipitation (mm/d), S_p is equal to the daily precipitation when the average atmospheric temperature of the day is < 2 °C, otherwise $S_p = 0$; S_d is the snow water equivalent variation owing to avalanches (mm/d); and S_m is the quantity of snow melting equivalent (mm/d)
265 calculated using the degree-day factor method (Hock, 1999) as follows:

$$S_m = d_f(T_a - T_s) \quad (5)$$

where d_f is the degree-day factor (mm/[°C·day]); T_a is the atmospheric temperature (°C); and T_s is the critical temperature of snow melting (°C), assuming snow melting begins when $T_a > T_s$. S_m was treated as precipitation in the model.

270 The simulation method of water transport under the snow layer was the same as that in the fully thawed period. However, the saturated hydraulic conductivity (K_s) was corrected by temperature and calculated as follows (Chen et al., 2008; Jansson, 2004):

$$K_s = \begin{cases} K & T > 0 \\ K(0.54 + 0.023T) & T_f \leq T \leq 0, \\ K_0 & T < T_f \end{cases} \quad (6)$$

275 where K is the initial saturated hydraulic conductivity (cm/s) and K_0 is the minimum hydraulic conductivity (cm/s) under freezing conditions. Considering the difference in the hydrodynamic properties of the s-layer and g-layer, the K_0 value for the s-layer was 0 cm/s. For the g-layer, owing to the larger pores, K_0 has a value > 0 cm/s. T is the temperature of the s-layer or g-layer (°C), while T_f is the critical temperature (°C) corresponding to the minimum hydraulic conductivity.

280 For the heat transfer process, we assumed that the upper boundary of the heat transfer system is the atmosphere, which controls the input and output of energy in the system. The temperature difference between the atmosphere and the surface is the source of heat conduction. In the presence of snow on the surface, the atmosphere first exchanges energy with the snow.

删除: -

删除: the

删除: was

删除: the

删除: had

删除: the

删除: -

删除: A snow layer was added on top of the dualistic soil ...

删除: differences

删除: cause the calculation units (the contour bands) at hi ...

删除: . Conversely, calculation units with lower elevation ...

删除: snow thickness

删除: exceeded

删除: snow meltdown occurred

删除: was less than

删除: due

删除: snow sliding down

删除:), when the difference in snow thickness between tv ...

删除:),

删除: melt starts

删除: is

删除: But

删除: of the soil or SGM layer

删除: can be

删除: soil

删除: SGM

删除: soil

删除: SGM

then the snow exchanges energy with the soil, while in the absence of snow, the atmosphere exchanges energy directly with the soil. The heat transferred to the underlying surface can be calculated from the climate forcing using the following equation (Hu and Islam, 1995):

$$C_{vu}\delta \frac{dT_u}{dt} = G(0, t) - G(\delta, t) \quad (7)$$

285 where C_{vu} is the volumetric heat capacity of the underlying surface ($\text{MJ}/\text{m}^3/^\circ\text{C}$); T_u is the temperature of the underlying surface; δ is the thickness of the underlying surface; and $G(\delta, t)$ is the heat flux at depth δ and moment t .

When δ is equal to the damping depth of the diurnal temperature wave (d_u) ($d_u = (2k/\omega)^{1/2}$) (Hu and Islam, 1995), where k is the thermal diffusivity of underlying surface (m^2/s), and ω is the fundamental frequency), $G(d_u, t)$ can be neglected, and the daily average heat flux conducted into the underlying surface (G) can be obtained by discretizing Equation (7) as

290 follows:

$$G = C_{vu}d_u\Delta T_u \quad (8)$$

where ΔT_u is the daily temperature variation of the underlying surface ($^\circ\text{C}$), which is approximated by the difference in temperature between the atmosphere and the underlying surface.

295 The lowermost boundary is the impermeable layer, and it is assumed that this maintains a constant temperature (seasonally frozen soil regions $> 0^\circ\text{C}$, permafrost regions $< 0^\circ\text{C}$).

The heat flux and temperature for each layer of the snow-soil-gravel layer continuum were calculated using the following equation (Shang et al., 1997; Wang et al., 2014):

$$C_v \frac{\partial T}{\partial t} = \frac{\partial}{\partial z} \left[\lambda \frac{\partial T}{\partial z} \right] + L_f \rho_l \frac{\partial \theta_l}{\partial t} \quad (9)$$

300 where C_v and λ are the volumetric heat capacity ($\text{J}/[\text{m}^3 \cdot ^\circ\text{C}]$) and thermal conductivity ($\text{W}/[\text{m} \cdot ^\circ\text{C}]$) of the s-layer or g-layer, respectively; L_f is the latent heat of ice melting ($3.35 \times 10^5 \text{ J/kg}$); T is the temperature ($^\circ\text{C}$) of the s-layer or g-layer; ρ_l is the ice density (kg/m^3); θ_l is the ice content by volume (cm^3/cm^3); and z is the layer thickness (m).

For the snow layer added to improve the model, the main water-heat parameters include thermal conductivity, volumetric heat capacity, and snow density. The calculation formulas of each parameter are as follows:

Snow density was calculated via Equation (10) (Hedstrom and Pomeroy, 1998):

305
$$\rho_s = \begin{cases} 67.9 + 51.3e^{T_a/2.6} & T_a \leq 0 \\ 119.2 + 20T_a & T_a > 0 \end{cases} \quad (10)$$

The thermal conductivity and volumetric heat capacity of snow were calculated as follows (Goodrich, 1982; Ling and Zhang, 2006):

$$\lambda_s = \begin{cases} 0.138 - \frac{1.01\rho_s}{1000} + 3.233\left(\frac{\rho_s}{1000}\right)^2 & 156 < \rho_s \leq 600 \\ 0.023 + \frac{0.234\rho_s}{1000} & \rho_s \leq 156 \end{cases} \quad \text{and} \quad (11)$$

$$C_{vs} = 2.09\rho_s \times 10^3, \quad (12)$$

- 删除: layer
- 删除: . Conversely,
- 删除: exchanges energy
- 删除: , and
- 删除: energy fluxes
- 删除: based on
- 删除: .
- 删除: lower
- 删除: at the bottom
- 删除: assuming
- 删除: it
- 删除: seasonal
- 删除: The heat transferred to the underlying surface is
- 删除: $$
- 删除: 8
- 删除: soil
- 删除: SGM
- 删除: soil
- 删除: SGM
- 删除: volumetric
- 删除: of ice in the soil or SGM layer
- 删除: equation (11)
- 删除: 9
- 删除: 10
- 删除: 11

310 where ρ_s is the snow density (kg/m³); T_a is the atmospheric temperature (°C); λ_s is the thermal conductivity of the snow (W/[m·°C]); and C_{V_s} is the volumetric heat capacity of the snow (J/[m³·°C]).

~~In contrast to the uniform soil profile, gravel in the g-layer has a great influence on the heat conduction. The main thermal parameters of the g-layer include volumetric heat capacity and thermal conductivity. The calculation formulas for each parameter were as follows:~~

315 Volumetric heat capacity was calculated via Equation (13) (Chen et al., 2008):

$$C_V = (1 - \theta_s) \times C_s + \theta_l \times C_l + \theta_i \times C_i, \quad (13)$$

where θ_s , θ_l , and θ_i are the saturated volumetric water content, volumetric liquid water content, and volumetric ice content, respectively; C_s , C_l , and C_i are the volumetric heat capacity (J/[m³·°C]) of the s-layer/g-layer, water, and ice, respectively. At 0 °C, the s-layer and g-layer have values of 1.93×10^6 J/[m³·°C] and 3.1×10^6 J/[m³·°C], respectively, and water and ice

320 have values of 4.213×10^6 J/[m³·°C] and 1.94×10^6 J/[m³·°C], respectively.

The thermal conductivity calculation referred to the IBIS model, as follows (Foley et al., 1996):

$$\lambda = \lambda_{st} \times (56^{\theta_l} + 224^{\theta_l}), \quad (14)$$

$$\lambda_{st} = \omega_{gravel} \times 1.5 + \omega_{sand} \times 0.3 + \omega_{silt} \times 0.265 + \omega_{clay} \times 0.25, \quad (15)$$

where λ and λ_{st} are the thermal conductivity of the s-layer/g-layer in the actual state and dry state (W/[m·°C]), respectively,

325 and ω_{gravel} , ω_{sand} , ω_{silt} , and ω_{clay} are the volume ratios of gravel, sand, silt, and clay, respectively.

2.3 Model evaluation criteria

Data from January 2013 to December 2018 were used to evaluate the simulation results of daily flow rates at Gongbujiangda, Baheqiao, and Duobu stations. The performance of the model was first evaluated using a qualitative assessment via graphing

330 and then assessed quantitatively using statistical metrics including the root-mean-square error (RMSE), Nash–Sutcliffe efficiency (NSE), and relative error (RE). The RMSE, NSE, and RE were calculated as follows:

$$RMSE = \sqrt{\frac{1}{N} \sum_{i=1}^N [(O_i - S_i)^2]} \quad (16)$$

$$NSE = 1 - \frac{\sum_{i=1}^N [(O_i - S_i)^2]}{\sum_{i=1}^N (O_i - \bar{O})^2} \quad (17)$$

$$RE = \frac{\sum_{i=1}^N S_i - \sum_{i=1}^N O_i}{\sum_{i=1}^N O_i} \times 100\% \quad (18)$$

335 where N is the number of observations; O_i is the observed value; \bar{O} is the mean observed value; and S_i is the simulated value.

删除: As opposed

删除: the presence of

删除: also

删除: of the soil–gravel layer.

删除: soil–gravel

删除: were

删除: equation (14)

删除: 12

删除: of the soil or SGM layer

删除: soil or SGM

删除: ; at

删除: soil

删除: SGM layers

删除: ×

删除: ×

删除: ;

删除: ×

删除: ×

删除: 13

删除: 14

删除: actual

删除: soil or SGM

删除: and the thermal conductivity

删除: the

删除: graphs

删除:

删除: squared

删除: the

3 Results and discussion

3.1 Model calibration and validation

The Niyang River basin was divided into 217 sub-basins, and each sub-basin was divided into 1–10 contour bands according to elevation as the basic calculation unit. The basin was divided into a total of 871 contour bands. The average area of the contour band was 20 km². The sub-basins of the watershed and the division of the contour bands are shown in Appendix A.

We calibrated and verified the daily flow processes of Gongbujiangda, Baheqiao, and Duobu stations—located upstream, on the largest tributary, and downstream, respectively—from 2013 to 2018. The data from Duobu Station were split into two parts: data from 2013 to 2015, which were used for calibration, and data from 2016 to 2018, which were used for validation.

Discontinuous, measured flow data from Gongbujiangda and Baheqiao stations from 2013 to 2018 were used to verify the model.

The parameters of the model were divided into four categories: underlying surface parameters, vegetation parameters, soil parameters, and aquifer parameters. All parameters have physical meaning and can be estimated based on observed experimental data or remote sensing data. The sensitivities of these four types of parameters were analyzed (Jia et al., 2006), and categorized as one of three levels: high, medium, or low. Highly sensitive parameters included soil thickness, soil saturated hydraulic conductivity, and riverbed material permeability coefficient. These parameters were calibrated using actual measurements: the saturated hydraulic conductivity of the s-layer was 0.648 m/d, that of the g-layer was 4.32 m/d, and the riverbed conductivity was approximately 5.184 m/d. The thicknesses of the s-layers on the mountaintop, mountainside, and at the foot of the mountain were 0.4 m, 0.6 m, and 1.0 m, respectively. In addition, for model improvement, the main parameter calibration results were as follows: the degree-day factor of snow was 4 mm/[°C·day], the critical temperature of snow melting was −1 °C, and the critical value of non-heavy versus heavy rain periods was 15 mm/day.

Daily flow data from Duobu Station during the calibration and verification periods, and from Gongbujiangda and Baheqiao stations during the verification period, are shown in Figure 5 and Table 1. The simulation results of the WEP-QTP model from all three stations were consistent with the measured flow data. During the verification period, compared with the WEP-COR model, the WEP-QTP model showed an increased NSE and decreased RE, thereby considerably improving the simulation. The WEP-QTP simulation flow process was smoother, and a large flow peak was not easily formed. However, we also found that WEP-QTP underestimated the river discharge during the frozen period; this may be attributed to the model not explicitly considering the outflow of sub-permafrost water, which could supplement the river discharge in the frozen period through macropores in the bedrock fracture zone. In general, the WEP-QTP model delivered an acceptable performance for the Niyang River basin and achieved an NSE > 0.75 and RE < 10% for the validation period. Hence, the improved model could be used for further analysis.

删除: Basin

删除: ~

删除: according to the elevation.

删除: bands is

删除: process

删除: station

删除: while those

删除: The discontinuous

删除: namely

删除: observational

删除: the above

删除: ,

删除: the sensitivities

删除: the parameters were divided into

删除: namely

删除: and

删除: with

删除: measurement, and

删除: results were as follows. The

删除: soil

删除: SGM

删除: soil

删除: at

删除: are

删除: and


删除: Figure 5 and Table 1 present

删除: results of both


删除: of the daily flow data from Duobu station and only

Table 1: Model validation results for Gongbujiangda, Baheqiao, and Duobu stations


Model	Duobu				Gongbujiangda		Baheqiao	
	Calibration		Validation		Validation		Validation	
	NSE	RE	NSE	RE	NSE	RE	NSE	RE
WEP-QTP	0.89	-5.8%	0.76	3.4%	0.79	0.01%	0.75	-5.47%
WEP-COR	0.69	-4.65%	0.31	0.01%	0.67	1.66%	0.40	-2.38%



(a)



(b)



(c)

Figure 5: Verification results of the WEP-QTP and WEP-COR models at (a) Duobu, (b) Gongbujiangda, and (c) Baheqiao stations.

删除: -

删除: -

3.2 Simulation and comparison of soil–gravel water–heat data at test sites

Figure 6 shows the air temperature together with the simulated and measured snow thicknesses during freezing and thawing at the experimental site. Snow began to accumulate on 3 December, 2016 and was completely melted by 4 April, 2017. The maximum snow thickness was 12.4 cm, and the simulated snow thickness was consistent with the measured value.




Figure 6: Snow thickness and air temperature during freezing and thawing at the experimental site.

3.2.1 Soil–gravel temperature

The soil–gravel temperature simulation results from the WEP-QTP and WEP-COR models are shown in Figure 7. The surface soil thickness at the experimental site was approximately 40 cm. For the 10 cm s-layer, because the simulation parameters of the WEP-QTP and WEP-COR models were the same, the simulated temperature results were consistent, except for during the snow cover period (i.e., the period when the snow thickness was > 5 cm, between 27 December, 2016–20 March, 2017). Owing to the insulation effect of snow, the heat transfer and temperature fluctuations of the surface soil were reduced. The RMSE of WEP-QTP in the 10 cm s-layer was 1.09 °C during the snow cover period; this was much less than the 2.12 °C of WEP-COR. The simulation results of the two models in the 20 cm layer did not differ considerably. For the 40 cm layer and below, the soil in the WEP-COR model had a higher water content than the g-layer in the WEP-QTP model during the early stage of freezing, masking the difference in simulated temperature between the two models (the volumetric heat capacity of water is higher than that of gravel and soil). However, as the temperature decreased, the moisture in the s-layer was converted into ice with a smaller heat capacity; thus, the difference in thermodynamic properties between the s-layer and the g-layer increased gradually. During this period, the simulated difference between the two models reached a maximum of 1.41 °C (40 cm layer, 26 January, 2017).

删除: and

删除: thickness

删除: test point. The snow

删除: The temperature and moisture of the soil–gravel la ...

删除: thicknesses

删除: temperatures

删除: sites from observations and the WEP-QTP model ...

删除: of

删除: -QTP and WEP-

删除: test

删除: -

删除: -

删除: simulation

删除: Due

删除: -

删除: soil

删除: , which

删除: -

删除: -

删除: SGM

删除: -

删除: at

删除: greater

删除: soil

删除: SGM

删除: soil

删除: simulation

380

385

390

395





Figure 7: Simulated (WEP-QTP and WEP-COR models) and observed temperatures of the soil–gravel layer at different depths.

We also compared the simulation results of the scenario considering only the g-layer (GL Scenario) with those of the scenario considering only snow cover (SC Scenario) to quantitatively analyze how snow and gravel affect the simulation results (Table 2). From Table 2, for the average RMSE: $WEP_QTP < GL\ Scenario < SC\ Scenario < WEP_COR$. Compared with the WEP-COR model, both snow and gravel improved the accuracy of temperature simulation, but the locations of their main effects on heat transfer were different. The RMSE of the SC Scenario at depths of 10–20 cm was smaller than that of the GL Scenario. Snow cover reduces the heat transfer and temperature fluctuations of the surface layer, which improves the simulation accuracy of the surface soil temperature. For depths of 40 cm and below, the RMSE of the GL Scenario was smaller than that of the SC Scenario, and the influence of the g-layer was dominant. Overall, the addition of the snow layer reduced the temperature fluctuations in the surface soil and, in conjunction with the g-layer, corrected the overestimation of the freeze-thaw rate present in the original model. The temperature RMSE was reduced from 1.16 to 0.86 °C.

删除: 2016/11/10 2016/12/10 2017/1/9 2017/2/8 2017/3/10 2017/4/9

删除: SGM (SGM)

删除: and

删除: the

删除: it can be found that

删除: -

删除: SGM

删除: -

删除: to

删除: -

删除: SGM

删除: location

删除: was

删除: in the

Table 2: RMSE values for the simulation of temperature (°C).

Depth (cm)	WEP-QTP	WEP-COR	GL Scenario	SC Scenario
10	1.53	1.89	1.79	1.64
20	1.00	0.93	0.95	0.88
40	0.63	0.87	0.65	0.75
60	0.59	1.03	0.65	0.92
80	0.63	1.06	0.70	0.96
100	0.79	1.20	0.87	1.12
Mean	0.86	1.16	0.94	1.05

删除: soil

删除: simulation

删除:)

删除: SGM

410 3.2.2 Soil-gravel moisture

Figure 8 shows a comparison between the simulated and measured values of the liquid water content during the freeze-thaw period of the WEP-QTP and WEP-COR models at the experimental site in 2016–2017. During the freezing period (December–March), the liquid water content of the upper layer first decreased owing to the decrease in temperature; this was followed by a decrease in liquid water content in the lower g-layer, which stabilized in January–February. When the temperature increased in March, the upper layer initially began to melt, thereby increasing the liquid water content and subsequent melting of the lower layer. At the end of the freeze-thaw period, the upper part of the soil-gravel layer had a higher water content than that in the lower part owing to the infiltration of snow melt; this water content was also higher than that prior to freezing.

删除:

删除: in

删除: -

删除: -

删除: points

删除: upper layer

删除: dropped due

删除: drop,

删除: drop



删除: SGM

删除: the

删除: due

删除: , and

删除: before



420 **Figure 8: Simulated (WEP-QTP and WEP-COR models) and observed moisture contents of the soil-gravel layer during the freezing and thawing periods.**

425 Over the entire freeze-thaw period, the lower g-layer did not affect the simulation of soil moisture content at a depth of 10 cm. For the 20 and 40 cm depth s-layers, their water holding capacity was greater than that of the g-layer; hence, their moisture simulated by the WEP-QTP model was greater than that simulated by the WEP-COR model. Below 40 cm depth, the simulation difference between the two models began to emerge more clearly. The simulated moisture of the WEP-COR model varies linearly in the vertical direction and was greater than the measured values, while the moisture simulated by the WEP-QTP model was lower and more similar to the measured values. This can be attributed to the fact that the thickness of the s-layer at the experimental site was 40 cm, and below it was the g-layer with higher hydraulic conductivity and lower water holding capacity. The WEP-COR model did not take into account the influence of the stratified geological structure on water migration. However, because the actual condition of the underlying surface cannot be homogeneous as assumed in the model generalization, there was a discrepancy in the model simulation results. Soil with a low gravel content may be present at depth of approximately 160 cm. In March and April after the snow melts, the snowmelt water infiltrated to this

- 删除: -
- 删除: -
- 删除: During
- 删除: SGM
- 删除: in the
- 删除: layer;
- 删除: -
- 删除: soil
- 删除: in the WEP-QTP model
- 删除: SGM
- 删除: under it, so that the
- 删除: -
- 删除: of
- 删除: -

depth and was more likely to reside here, and the measured water content value of this layer was between the simulated values of the WEP-QTP and WEP-COR models. The average RE of WEP-COR was 33.74%, and that of WEP-QTP was smaller at 12.11%. Hence, the WEP-QTP model could reflect the influence of gravel on the vertical migration of water.

3.3 Analysis of the snow-soil-gravel layer continuum effects on the process of water cycling

To explore the influence of the snow-soil-gravel layer continuum on the process of water cycling and the reasons behind the improvement of the model simulation, 2014 (a year for which all measured data were available) was selected as a typical year to compare and analyze the simulation results before and after model improvement (Fig. 9). The simulation difference between the two models appeared from June to October. Compared to the whole year, the difference between the RMSEs of the two models was largest from June to September, and that between the REs of the two models was largest in October (Table 3). For the Gongbujiangda, Baheqiao, and Duobu stations, the RMSEs of WEP-QTP decreased by 14.44, 62.81, and 149.12 m³/s, respectively, from June to September, and the absolute values of RE decreased by 4.08%, 32.67%, and 45.50%, respectively, in October. The simulation performance of the WEP-QTP model was better than that of the WEP-COR in three aspects: the peak value of the flood season was not too high; the trough value of the flow process was higher than that of WEP-COR; and the WEP-QTP model showed a better "tailing" process from September onwards.

删除: layer

删除: there

删除: values

删除: -

删除: -

删除: -

删除: -

删除: -

删除: -

删除: **Simulation and comparison**

删除: **watershed flow**

删除: To further

删除: improved WEP-QTP compared with the original W

删除: was

删除: RMSE

删除: the

删除: the difference

删除: RE

删除: the

删除: stations

删除: -

删除: m³/s

删除: m³/s

删除:

删除:

删除:

删除: -

删除: -




Figure 9: Simulated (WEP-QTP and WEP-COR models) and observed flow rates at (a) Gongbujiangda, (b) Baheqiao, and (c) Duobu stations in 2014.

450 Table 3. Statistical values of the WEP-QTP and WEP-COR models for flow simulation in different periods.

Statistical value	Gongbujiangda		Duobu		Baheqiao	
	WEP-QTP	WEP-COR	WEP-QTP	WEP-COR	WEP-QTP	WEP-COR
RMSE (m ³ /s)	88.47/ 148.32/35.99 ^a	96.27/ 162.76/30.19	106.48/ 175.61/79.05	145.05/ 238.42/140.55	244.39/ 416.74/45.64	335.56/ 565.86/211.33
RE (%)	2.20/7.78/19.86	13.12/8.72/23.94	-1.95/7.06/ -31.72	7.29/-3.06/64.39	-3.78/-0.11/1.25	12.71/7.31/46.76

^a Values of the whole year, June to September, and October, respectively.

删除: -

删除: -

删除: -

删除: -

删除: soil temperature

By comparing the hydrological cycle fluxes simulated by the two models, the influence of gravel on hydrological processes and the contribution of gravel to enhancing the simulation can be revealed, to some extent. Figure 10 shows the comparison and analysis of hydrological cycle flux changes across the basin simulated using the WEP-QTP and WEP-COR models.

From June to September, the surface runoff from precipitation simulated by WEP-QTP decreased by 31.79% when compared with that simulated by WEP-COR; correspondingly, groundwater recharge and groundwater discharge increased by 249.16% and 280.41%, respectively. Precipitation during heavy rainfall events in the WEP-QTP model preferentially recharged groundwater via macropores in the g-layer, and then recharged the river through groundwater discharge. However, in the WEP-COR model, most of this precipitation contributed to the peak flow during the flood season by the way of surface runoff, which far exceeded the measured value of the flow (Fig. 9). This may be the main reason for the better performance of the WEP-QTP model in the peak and trough flow simulations during the flood season.




Figure 10: Monthly changes in hydrological cycle flux simulated by WEP-QTP and WEP-COR.

The addition of the snow layer not only reduced the temperature fluctuation of the surface soil, but also, aided by the g-layers, revised the overestimation of the freeze-thaw speed present in the original model. In the lower elevation valleys (< 4600 m a.s.l.), the percentage of area having a snow thickness ≥ 0.5 m reached its maximum (18.36%) in February and then decreased to 0% by June. However, in high-altitude areas (> 4600 m a.s.l.), where the temperature was lower than that in the valleys, the percentage of area having a snow thickness ≥ 0.5 m reached its maximum (51.26%) in April and then dropped to a minimum of 0.60% in July (Fig. 11). The WEP-COR model did not consider snow cover, the upper boundary was the atmosphere, and the soil responded quickly to changes in atmospheric temperature. From January to December, the proportion of area with a frozen thickness ≥ 1 m simulated by WEP-COR model decreased and then increased with changing temperature (maximum in January, minimum in August). In contrast, the proportion of area with a frozen soil thickness > 1 m simulated by the WEP-QTP model reached the maximum in February and minimum in September (Fig. 12). The inconsistency in the spatiotemporal variation of the frozen soil led to discrepancies in groundwater recharge and discharge processes between the two models. The change in frozen soil area simulated by the WEP-QTP model lagged that simulated by the WEP-COR model, as did the groundwater discharge process (the groundwater discharge of WEP-QTP reached its maximum in September, while that of WEP-COR occurred in August (Fig. 10)). Water in the WEP-QTP model

删除: the changes in

删除: by

删除: -

删除: -

删除: -

删除: -

删除: The precipitation

删除: can recharge

删除: more rapidly during heavy rains through

删除: SGM layer, while flow peaks are not easily formed.

删除: -

删除: part of water mostly formed

删除: Therefore,

删除: WEP-QTP performed

删除: simulation

删除: , and could simulate more groundwater discharge to ...

删除: change process of

删除: -

删除: -

删除: with

删除: help of the SGM

删除: original model's

删除: -

删除: .

删除: 4,600


删除: with

删除: greater than

删除:

had more time to complete groundwater and river recharge, and thus exhibited a better observed “tailing” process than that in the WEP_COR model.

- 删除: for
- 删除: recharge
- 删除: showing
- 删除: compared with
- 删除: -



480

Figure 11: Spatiotemporal variation in snow cover thickness during 2014.

- 删除: . Temporal and spatial
- 删除: of
- 删除: in




Figure 12: Monthly changes in frozen soil area proportion within the basin.

In cold regions, climate change affects high and low flows in different ways. As warming and wetting progresses, changes in high flows show spatial heterogeneity, while low flows show a consistently increasing trend (Song et al., 2021). Warming enhances subsurface flow connectivity and increases groundwater flow by increasing the thickness of the active layer (St. Jacques and Sauchyn, 2009; Walvoord and Kurylyk, 2016). As the medium connecting groundwater and surface water, the water-heat transport of the active layer has a substantial influence on the process of water cycling in cold regions (Chen et al., 2014; Kurylyk et al., 2014). Our study demonstrates that the soil-gravel layer structure on the QTP is different from the soil structure in other cold regions. In terms of heat transfer, snow and gravel block heat conduction and slow down the freezing and thawing rates of aquifers. For water transfer, the large pores of the lower g-layer increase the regulation effect of groundwater on flow processes. Under future climate conditions, the participation of groundwater in the water cycle of the QTP may be greater than we expected. Ignoring the snow-soil-gravel layer structure will affect hydrological forecasting, reservoir regulation, and water resource utilization.

4 Conclusions

This study took the Niyang River basin as the study area and constructed the WEP-QTP model on the basis of the original WEP-COR model. The improved WEP-QTP model focuses on the geological structural characteristics of the QTP, dividing a uniform soil profile into two types of media: the upper s-layer and lower g-layer. When no phase change occurred in the ground, two infiltration models based on a dualistic soil-gravel structure were developed, using the Richards equation for non-heavy rain scenarios, and the multi-layer Green-Ampt model for heavy rain scenarios. During the freeze-thaw period, a water-heat coupling model based on a snow-soil-gravel continuum was constructed. This model was used to simulate the process of water cycling within the Niyang River basin, and the improvement of the model was analyzed via comparison with the WEP-COR model.

删除: change process of the

删除: in

删除: differently.

删除: the

删除: continue

删除: flow shows

删除: consistent

删除: great

删除: water cycle

删除: in

删除: layer

删除: general

删除: SGM

删除: and storage

删除: of the

删除: the

删除: higher

删除: the

删除: forecast

删除: combined the geological characteristics of the thin: ...

删除: Basin

删除: research

删除: , the WEP-QTP model was

删除: based

删除: -

删除: model divides the

删除: soil

删除: the

505 Compared with the simulation results prior to improvement, the addition of snow not only reduced the surface soil temperature fluctuations, but also interacted with the **g-layers** to reduce the soil freezing and thawing speed. The **underestimation** of temperature by WEP-COR was corrected, while the temperature RMSE was reduced from 1.16 °C to 0.86 °C. **Furthermore**, the WEP-QTP model **was able to** reflect the impact of the **g-layer** on the vertical movement of water and accurately describe the dynamic changes in moisture in the **s-** and **g-layers**; the RE of the moisture content was reduced from 33.74% to -12.11%.

510 According to the comparison of the WEP-QTP simulation and measured **data from** the main stations in the Niyang River **basin**, the daily flow process simulated by the **improved** model **was more accurate** ($NSE > 0.75$ and $|RE| < 10\%$), **representing** a considerable improvement **over** the WEP-COR model. **During** the fully thawed period, the dualistic soil-gravel structure increased the recharge and discharge of groundwater and improved the regulation effect of groundwater on flow, thereby stabilizing the water flow process. The maximum RE at the flow peak and **trough** decreased by 88.2% and 21.3%, respectively. **During** the freeze-thaw period, by considering the effect of the snow-soil-gravel layer continuum on soil freezing and thawing processes, changes in frozen soil depth simulated by WEP-QTP lagged those **simulated by** WEP-COR by approximately one month. **As a result, there** was more time for the river **to be recharged** by groundwater, **as indicated by** a better observed “tailing” process **from September onwards**.

520 In contrast to **typical** cold **regions**, the unique geological structure and climatic characteristics of the QTP change the **process** of water **cycling** in the basin. Ignoring the influence of the dualistic soil-gravel structure greatly impacts **hydrological forecasting** and water resource assessment.

Data and code availability

The datasets and model code relevant to the current study are available from the corresponding author on reasonable request.

Author contribution

525 PW performed the model programming and simulations. ZZ, KW, and YL conducted the field experiments. ZZ, JL, YL, and JL contributed to the model programming. PW and ZZ performed the writing. CX, YJ and HW contributed to the writing of the paper.

Competing interests

The authors declare that they have no conflict of interest.

- 删除: SGM layer
- 删除: low estimation
- 删除: -
- 删除: At the same time
- 删除: -
- 删除: can
- 删除: SGM
- 删除: under the soil
- 删除: soil
- 删除: SGM
- 删除: -
- 删除: results of
- 删除: Basin
- 删除: is in line with the actual status, while the flow
- 删除: Nash
- 删除: which is
- 删除: compared with
- 删除: In
- 删除: valley
- 删除: In
- 删除: -
- 删除: of
- 删除: -
- 删除: There
- 删除: recharge
- 删除: the
- 删除: which showed
- 删除: after

530 Acknowledgements

This work was partly supported by grants from the National Natural Science Foundation of China (91647109, 51879195) and the National Key Research and Development Program of China (2016YFC0402405).

References

535 Arocena, J., Hall, K., and Zhu, L. P.: Soil formation in high elevation and permafrost areas in the Qinghai Plateau (China), Spanish Journal of Soil Science, 2, 34-49, 2012.

Beibei, Z., Ming'an, S., and Hongbo, S.: Effects of rock fragments on water movement and solute transport in a Loess Plateau soil, Comptes Rendus Geoscience, 341, 462-472, 2009.

540 Chen, B., Luo, S., Lü, S., Zhang, Y., and Ma, D.: Effects of the soil freeze-thaw process on the regional climate of the Qinghai-Tibet Plateau, Climate research, 59, 243-257, 2014.

Chen, H., Nan, Z., Zhao, L., Ding, Y., Chen, J., and Pang, Q.: Noah modelling of the permafrost distribution and characteristics in the West Kunlun area, Qinghai-Tibet Plateau, China, Permafrost and Periglacial Processes, 26, 160-174, 2015.

545 Chen, R.-s., Lu, S.-h., Kang, E.-s., Ji, X.-b., Zhang, Z., Yang, Y., and Qing, W.: A distributed water-heat coupled model for mountainous watershed of an inland river basin of Northwest China (I) model structure and equations, Environmental Geology, 53, 1299-1309, 2008.

Cheng, G. and Wu, T.: Responses of permafrost to climate change and their environmental significance, Qinghai-Tibet Plateau, Journal of Geophysical Research: Earth Surface, 112, 2007.

550 Cheng, G. and Jin, H.: Permafrost and groundwater on the Qinghai-Tibet Plateau and in northeast China, Hydrogeology Journal, 21, 5-23, 2013.

Cherkauer, K. A. and Lettenmaier, D. P.: Simulation of spatial variability in snow and frozen soil, Journal of Geophysical Research: Atmospheres, 108, 2003.

Cousin, I., Nicoullaud, B., and Coutadeur, C.: Influence of rock fragments on the water retention and water percolation in a calcareous soil, Catena, 53, 97-114, 2003.

555 Dai, L., Guo, X., Zhang, F., Du, Y., Ke, X., Li, Y., Cao, G., Li, Q., Lin, L., and Shu, K.: Seasonal dynamics and controls of deep soil water infiltration in the seasonally-frozen region of the Qinghai-Tibet plateau, Journal of Hydrology, 571, 740-748, 2019.

Deng, D., Wang, C., and Peng, P.: Basic Characteristics and Evolution of Geological Structures in the Eastern Margin of the Qinghai-Tibet Plateau, Earth Sciences Research Journal, 23, 283-291, 2019.

560 Ding, Y., Zhang, S., Wu, J., Zhao, Q., Li, X., and Qin, J.: Recent progress on studies on cryospheric hydrological processes changes in China, Advances in Water Science, 31(5), 690-702, 2020.

删除: Childs, S. W. and Flint, A. L.: Physical properties of forest soils containing rock fragments, Forestry Publications, 95-121, 1990.

- Douville, H., Royer, J.-F., and Mahfouf, J.-F.: A new snow parameterization for the Meteo-France climate model, *Climate Dynamics*, 12, 21-35, 1995.
- 565 Dutra, E., Viterbo, P., Miranda, P. M., and Balsamo, G.: Complexity of snow schemes in a climate model and its impact on surface energy and hydrology, *Journal of Hydrometeorology*, 13, 521-538, 2012.
- Foley, J. A., Prentice, I. C., Ramankutty, N., Levis, S., Pollard, D., Sitch, S., and Haxeltine, A.: An integrated biosphere model of land surface processes, terrestrial carbon balance, and vegetation dynamics, *Global Biogeochemical Cycles*, 10, 603-628, 1996. | 删除: biogeochemical cycles
- 570 Franzluebbers, A. J.: Water infiltration and soil structure related to organic matter and its stratification with depth, *Soil and Tillage Research*, 66, 197-205, 2002. | 删除: research
- Goodrich, L. E.: The influence of snow cover on the ground thermal regime, *Canadian Geotechnical Journal*, 19, 421-432, 1982. | 删除: geotechnical journal
- Grinsted, A.: An estimate of global glacier volume, *The Cryosphere*, 7, 141, 2013.
- Hedstrom, N. and Pomeroy, J.: Measurements and modelling of snow interception in the boreal forest, *Hydrological Processes*, 12, 1611-1625, 1998.
- 575 Hock, R.: A distributed temperature-index ice-and snowmelt model including potential direct solar radiation, *Journal of Glaciology*, 45, 101-111, 1999.
- Hu, Z., Islam, S.: Prediction of ground surface temperature and soil moisture content by the force-restore method. *Water Resources Research*, 31(10): 2531-2539, 1995.
- 580 Huyan, Y., Yao, W., Xie, X., and Wang, L.: Provenance, source weathering, and tectonics of the Yarlung Zangbo River overbank sediments in Tibetan Plateau, China, using major, trace, and rare earth elements, *Geological Journal*, 57, 37-51, 2022.
- Ireson, A., Van Der Kamp, G., Ferguson, G., Nachshon, U., and Wheeler, H.: Hydrogeological processes in seasonally frozen northern latitudes: understanding, gaps and challenges, *Hydrogeology Journal*, 21, 53-66, 2013.
- 585 Jansson, P. and Karlberg, L.: Coupled heat and mass transfer model for soil-plant-atmosphere systems, Royal Institute of Technology, Dept of Civil and Environmental Engineering, Stockholm, 2011.
- Jia, Y. and Tamai, N.: Integrated analysis of water and heat balances in Tokyo metropolis with a distributed model, *Journal of Japan Society of Hydrology and Water Resources*, 11, 150-163, 1998.
- Jia, Y., Ding, X., Qin, C., and Wang, H.: Distributed modeling of landsurface water and energy budgets in the inland Heihe river basin of China, *Hydrology and Earth System Sciences*, 13, 1849, 2009.
- 590 Jia, Y., Ni, G., Kawahara, Y., and Suetsugi, T.: Development of WEP model and its application to an urban watershed, *Hydrological Processes*, 15, 2175-2194, 2001.
- Jia, Y., Wang, H., Zhou, Z., Qiu, Y., Luo, X., Wang, J., Yan, D., and Qin, D.: Development of the WEP-L distributed hydrological model and dynamic assessment of water resources in the Yellow River basin, *Journal of Hydrology*, 331, 606-629, 2006.
- 595

Kurylyk, B. L., MacQuarrie, K. T., and McKenzie, J. M.: Climate change impacts on groundwater and soil temperatures in cold and temperate regions: Implications, mathematical theory, and emerging simulation tools, *Earth-Science Reviews*, 138, 313-334, 2014.

Larsbo, M., Holten, R., Stenrød, M., Eklo, O. M., and Jarvis, N.: A [dual-permeability approach](#) for [modeling soil water flow](#) and [heat transport](#) during [freezing](#) and [thawing](#), *Vadose Zone Journal*, 18, 2019.

删除: Dual-Permeability Approach

Li, J., Zhou, Z., Wang, H., Liu, J., Jia, Y., Hu, P., and Xu, C.-Y.: Development of WEP-COR model to simulate land surface water and energy budgets in a cold region, *Hydrology Research*, 50, 99-116, 2019.

删除: Modeling Soil Water Flow

Li, Z., Yu, G., Xu, M., Hu, X., Yang, H., and Hu, S.: Progress in studies on river morphodynamics in Qinghai-Tibet Plateau. *Advances in Water Science*, 27(4), 617-628, 2016.

删除: Heat Transport

删除: Freezing

Ling, F. and Zhang, T.: Sensitivity of ground thermal regime and surface energy fluxes to tundra snow density in northern Alaska, *Cold Regions Science and Technology*, 44, 121-130, 2006.

删除: Thawing

Liu, X., Yang, W., Zhao, H., Wang, Y., and Wang, G.: Effects of the freeze-thaw cycle on potential evapotranspiration in the permafrost regions of the Qinghai-Tibet Plateau, China, *Science of the Total Environment*, 687, 257-266, 2019.

删除:):

删除: regions science

Lundberg, A., Ala-Aho, P., Eklo, O., Klöve, B., Kværner, J., and Stumpp, C.: Snow and frost: implications for spatiotemporal infiltration patterns—a review, *Hydrological Processes*, 30, 1230-1250, 2016.

删除: technology

MAO, X.-m. and SHANG, S.-h.: Method of minimum flux in saturation layer for calculating stable water infiltration through layered soil, *Journal of Hydraulic Engineering*, 7, 2010.

删除: total environment

删除: processes

Monteith, J.: *Principles of Environmental Physics*, Edward Arnold, London, 214p, 1973.

Mualem, Y.: Hydraulic conductivity of unsaturated soils: Prediction and formulas. *Methods of Soil Analysis: Part 1 Physical and Mineralogical Methods*, 5: 799-823, 1986.

删除: Mehuys, G., Stolzy, L., Letey, J., and Weeks, L.: Effect of stones on the hydraulic conductivity of relatively dry desert soils, *Soil Science Society of America Journal*, 39, 37-42, 1975.

[Niu, G., Yang, Z.: Effects of frozen soil on snowmelt runoff and soil water storage at a continental scale. *Journal of Hydrometeorology*, 7\(5\), 937-952, 2006.](#)

删除: environmental physics

Pan, Y., Lyu, S., Li, S., Gao, Y., Meng, X., Ao, Y., and Wang, S.: Simulating the role of gravel in freeze–thaw process on the Qinghai–Tibet Plateau, *Theoretical and Applied Climatology*, 127, 1011-1022, 2017

删除: .

Pitman, A., Yang, Z., and Henderson-Sellers, A.: Description of bare essentials of surface transfer for the Bureau of Meteorology Research Centre AGCM, Bureau of [Meteorology](#), 1991.

删除: applied climatology

Pomeroy, J., Gray, D., Brown, T., Hedstrom, N., Quinton, W., Granger, R., and Carey, S.: The cold regions hydrological process representation and model: A platform for basing model structure on physical evidence, *Hydrological Processes*, 21, 2650-2667, 2007.

删除: Meteorology1991

Radić, V. and Hock, R.: Regional and global volumes of glaciers derived from statistical upscaling of glacier inventory data, *Journal of Geophysical Research: Earth Surface*, 115, 2010.

Rigon, R., Bertoldi, G., and Over, T. M.: GEOtop: A distributed hydrological model with coupled water and energy budgets, *Journal of Hydrometeorology*, 7, 371-388, 2006.

Shang, S.-h., Lei, Z., and Yang, S.: Numerical simulation improvement of coupled moisture and heat transfer during soil freezing, *Journal-Tsinghua University*, 37, 62-64, 1997.

Song, C., Wang, G., Sun, X., and Hu, Z.: River runoff components change variably and respond differently to climate change in the Eurasian Arctic and Qinghai-Tibet Plateau permafrost regions, *Journal of Hydrology*, 601, 126653, 2021.

St. Jacques, J. M. and Sauchyn, D. J.: Increasing winter baseflow and mean annual streamflow from possible permafrost thawing in the Northwest Territories, Canada, *Geophysical Research Letters*, 36, 2009.

635 Sun, H., *Formation and Evolution of Qinghai-Xizang Plateau*. Shanghai Science and Technology Press, 1996.

Van Genuchten, M. T.: A closed-form equation for predicting the hydraulic conductivity of unsaturated soils, *Soil Science Society of America Journal*, 44, 892-898, 1980.

Walvoord, M. A. and Kurylyk, B. L.: Hydrologic impacts of thawing permafrost—A review, *Vadose Zone Journal*, 15, 2016.

Wang, A., Xie, Z., Feng, X., Tian, X., and Qin, P.: A soil water and heat transfer model including changes in soil frost and thaw fronts, *Science China Earth Sciences*, 57, 1325-1339, 2014.

640 Wang, H., Xiao, B., and Wang, M.: Modeling the soil water retention curves of soil-gravel mixtures with regression method on the Loess Plateau of China, *PLoS One*, 8, e59475, 2013.

Wang, Y., Yang, H., Yang, D., Qin, Y., Gao, B., and Cong, Z.: Spatial interpolation of daily precipitation in a high mountainous watershed based on gauge observations and a regional climate model simulation, *Journal of Hydrometeorology*, 18, 845-862, 2017.

645 Watanabe, K. and Kugisaki, Y.: Effect of macropores on soil freezing and thawing with infiltration, *Hydrological Processes*, 31, 270-278, 2017.

Yang, K., Chen, Y.-Y., and Qin, J.: Some practical notes on the land surface modeling in the Tibetan Plateau, *Hydrology and Earth System Sciences*, 13, 687-701, 2009.

650 Yi, S., Chen, J., Wu, Q., and Ding, Y.: Simulating the role of gravel on the dynamics of permafrost on the Qinghai-Tibetan Plateau, *The Cryosphere Discussions*, 7, 4703-4740, 2013.

Yu, L., Feng C.: Recent progress in climate change over Tibetan Plateau. *Plateau and Mountain Meteorology Research*, 32(3): 84-88, 2012.

Zaradny, H.: *Groundwater Flow in Saturated and Unsaturated Soil*. Balkema Press, Rotterdam, 1993.

655 Zhang, Y., Cheng, G., Li, X., Han, X., Wang, L., Li, H., Chang, X., and Flerchinger, G.: Coupling of a simultaneous heat and water model with a distributed hydrological model and evaluation of the combined model in a cold region watershed, *Hydrological Processes*, 27, 3762-3776, 2013.

Zhang, Z. F., Ward, A. L., and Keller, J. M.: Determining the porosity and saturated hydraulic conductivity of binary mixtures, *Vadose Zone Journal*, 10, 313-321, 2011.

删除: JOURNAL-TSINGHUA UNIVERSITY

删除: The formation

删除: evolution

删除: the

删除: Tibet

删除: science society

删除: journal

删除: flow

删除: saturated

删除: unsaturated soil

删除: .

Zhang, Z. F., Ward, A. L., and Keller, J. M.: Determining the porosity and saturated hydraulic conductivity of binary mixtures, *Vadose Zone Journal*, 10, 313-321, 2011.

删除: -




Figure A1: Annual precipitation contour map (mm/year).

删除: .





Figure A2: Mean annual temperature (°C).

删除: .



665

Figure A3: Glacier and permafrost distributions.

删除: .




Figure A4: Division of contour bands.

删除: . The division

删除: the

删除: -

删除: -

删除: Water

删除: Energy

删除: Processes

删除: Cold Regions

删除: -

删除: For

删除: -

Appendix B. Introduction of the WEP_{QTP}-COR model

670 The WEP_{QTP} model was developed based on the water and energy transfer processes in cold regions (WEP_{QTP}-COR) model.


To allow better understanding and comparison, the WEP_{QTP}-COR model is briefly introduced in this section.

Model structure

The WEP-COR model is a distributed hydrological model. In terms of the horizontal structure, the WEP-COR model uses the contour bands inside small sub-basins as the basic calculation unit (Fig. B1a), and fully considers the vertical changes in vegetation, soil, air temperature, precipitation, and other factors in the basin with changing elevation. Each unit was classified as one of five types according to the type of land-use: water body, soil-vegetation, irrigated farmland, non-irrigated farmland, and impervious area. Evapotranspiration of water and soil was calculated using the Penman formula, and the vegetation canopy evaporation was calculated using the Penman-Monteith formula (Monteith, 1973). For soil moisture, the Green-Ampt infiltration model was used for heavy rain periods (Jia and Tamai, 1998), and non-heavy rain periods were simulated using the Richards equation (Jia et al., 2009). The subsurface runoff was calculated based on slope and soil hydraulic conductivity, and groundwater movement was calculated using Boussinesq's equation (Zaradny, 1993). The groundwater outflow was calculated according to the hydraulic conductivity of the riverbed material and difference between the river water stage and groundwater level (Jia et al., 2001). For glacier-covered areas, the "degree-day factor method" (Hock, 1999) was used to calculate the quantity of glacier melting, and the runoff from the melting of glaciers was directly added to the corresponding hydrological calculation unit.

The vertical structure of WEP-COR was divided into the vegetation canopy or building interception layer, surface depression storage layer, aeration layer, transition zone layer, and groundwater layer. To accurately simulate the changes in soil moisture and heat from the surface to the deep layers, and to reflect the influence of soil depth on the evaporation of bare soil and water absorption and transpiration of vegetation roots, the aerated zone soil was divided into 11 layers (Fig. B1b).

The thickness of the first and second layers was set to 10 cm, and the thickness of layers 3-11 was set to 20 cm.



(a)

删除: -

删除: -

删除: is divided into

删除: type

删除: The calculation result of the water and heat flux in each type was weighted by area to obtain the water and heat flux of the contour band.

删除: during the

删除: period

删除: the

删除: period was

删除: by

删除: by the

删除: -


删除: the

删除: the

删除: the

删除: the

删除: the



(b)

695 **Figure B1: Horizontal (a) and vertical (b) structure of the WEP-COR model.**

Water-heat transport simulation

The WEP-COR model divides soil infiltration into two scenarios: heavy rain infiltration and non-heavy rain infiltration, according to the different runoff generation mechanisms. In the non-heavy rain infiltration scenario, the runoff is generated by saturation-excess, and the soil vertical water flux transfer can be written as follows (Shang et al., 1997; Wang et al., 2014):

$$\frac{\partial \theta_l}{\partial t} = \frac{\partial}{\partial z} \left[D(\theta_l) \frac{\partial \theta_l}{\partial z} - K(\theta_l) \right] - \frac{\rho_l}{\rho_l} \frac{\partial \theta_l}{\partial t} \quad (B1)$$

where θ_l is the volumetric content of liquid water in the soil layer (cm^3/cm^3); $D(\theta_l)$ and $K(\theta_l)$ are the unsaturated soil hydraulic diffusivity (cm^2/s) and hydraulic conductivity (cm/s), respectively; t and z are the time and space coordinates (positive vertically downward), respectively; and ρ_l is the water density (kg/m^3).

705 The Van Genuchten function (Van Genuchten, 1980) was used to describe the upper soil water retention curves:

$$\frac{\theta_l - \theta_r}{\theta_s - \theta_r} = \frac{1}{[1 + (\alpha h)^n]^m} \quad (B2)$$

where θ_s is the saturated water content (cm^3/cm^3); θ_r is the residual water content (cm^3/cm^3); h is the matric suction (cm); α is an empirical parameter (cm^{-1}); n and m are empirical parameters affecting the shape of the retention curve; and $m = 1 - 1/n$.

The hydraulic conductivity was calculated using the Mualem model (Mualem, 1986):

删除: -Heat Transport Simulation

删除: -

删除: ,

删除:);

删除: -

删除: by

删除: Y

$$710 \quad K(\theta_l) = \begin{cases} K_s & \theta_l = \theta_s \\ K_s \left(\frac{\theta_l - \theta_r}{\theta_s - \theta_r} \right)^\Omega & \theta_l \neq \theta_s \end{cases}, \quad (B3)$$

where $K(\theta_l)$ is the hydraulic conductivity (cm/s) of the soil layer when the liquid water content is θ_l ; K_s is the saturated hydraulic conductivity of the soil temperature correction (cm/s); ~~and Ω~~ is Mualem's constant.

删除: Ω

In the heavy rain infiltration scenario, the runoff is generated by infiltration-excess. The multi-layer unsteady rainfall Green-Ampt model proposed by Jia and Tamai ~~was~~ used (Jia and Tamai, 1998) to calculate the infiltration process. When the infiltration front (INF) reached the m -th layer of soil, the soil infiltration capacity was calculated ~~using~~ the following formulas:

删除: is

删除: by

$$f = k_m \left(1 + \frac{A_{m-1}}{B_{m-1} + F} \right) \quad (B4)$$

$$A_{m-1} = \left(\sum_1^{m-1} L_i - \sum_1^{m-1} \frac{L_i k_m}{k_i} + SW_m \right) \Delta \theta_m \quad (B5)$$

$$B_{m-1} = \left(\sum_1^{m-1} \frac{L_i k_m}{k_i} \right) \Delta \theta_m - \sum_1^{m-1} L_i \Delta \theta_i \quad (B6)$$

720 where f is the infiltration capacity (mm/h); A_{i-1} is the total water capacity of the soil above the i layer (mm); B_{i-1} is the error caused by the different soil moisture contents of the soil above the i layer (mm); F is the cumulative infiltration (mm); k_i is the hydraulic conductivity of the i -th soil layer (mm/h); L_i is the soil thickness of the i -th layer (mm); SW_m is the capillary suction pressure at the INF of the m -th layer (mm); ~~and $\Delta \theta_i = \theta_s - \theta_l$~~ .

删除: -

删除: -

The cumulative infiltration quantity F when the INF ~~reached~~ the m -th layer ~~was~~ calculated based on whether there ~~was~~ water accumulation on the ground surface. If the ground surface ~~had~~ accumulated water when the INF ~~reached~~ the ~~$m-1$ -th~~ layer, Eq. (B7) was used; otherwise, Eq. (B8) was used:

删除: reaches

删除: is

删除: is

删除: has

删除: reaches

$$725 \quad F - F_{m-1} = k_m (t - t_{m-1}) + A_{m-1} \ln \left(\frac{A_{m-1} + B_{m-1} + F}{A_{m-1} + B_{m-1} + F_{m-1}} \right) \quad (B7)$$

$$F - F_p = k_m (t - t_p) + A_{m-1} \ln \left(\frac{A_{m-1} + B_{m-1} + F}{A_{m-1} + B_{m-1} + F_p} \right) \quad (B8)$$

$$F_{m-1} = \sum_1^{m-1} L_i \Delta \theta_i \quad (B9)$$

$$730 \quad F_p = A_{m-1} \left(\frac{I_p}{k_m} - 1 \right) - B_{m-1} \quad (B10)$$

删除: 1th

$$t_p = t_{m-1} + (F_p - F_{n-1}) / I_p \quad (B11)$$

where t is the time; t_{m-1} is the time when the INF reaches the interface between the $m-1$ and m layers; t_p is the start time of the water accumulation; F_p is the cumulative infiltration quantity at t_p ; ~~and I_p~~ is the precipitation intensity at t_p .

删除: -

The relationship between the water and heat transport of frozen soil is mainly manifested in the dynamic balance of the moisture content of the unfrozen water and the negative temperature of the soil. According to the principle of energy balance, the energy change of each layer in the freeze-thaw system was used for the soil temperature change and water phase change in the system. The heat flux conducted into the soil was calculated using the forced recovery method (Douville et al., 1995;

735

Pitman et al., 1991). The heat flux and temperature of each layer were calculated using the following equations (Chen et al., 2008):

$$740 \quad H_{i,i+1} = 0.1782 \frac{(\lambda_i Z_i + \lambda_{i+1} Z_{i+1})(T_i - T_{i+1})}{(Z_i + Z_{i+1})^2} \quad \text{and} \quad (B12)$$

$$T_i = \frac{H_{i-1,i} - H_{i,i+1}}{C_{vi} Z_i}, \quad (B13)$$

where i is the number of soil layers; $H_{i,i+1}$ represents the sensible heat flux between the i layer and the $i+1$ layer (MJ/m^2); λ represents the thermal conductivity ($\text{W}/[\text{m}\cdot^\circ\text{C}]$); Z is the thickness (cm); C_v is the soil volume heat capacity ($\text{J}/[\text{m}^3\cdot^\circ\text{C}]$); and T is the temperature ($^\circ\text{C}$).

745 Temperature is the driving force of the water phase change. The relationship between the water and heat transport of frozen soil is mainly manifested in the dynamic balance of the moisture content of the unfrozen water and the negative temperature of the soil (Wang et al., 2014; Niu et al., 2006):

$$\theta_l = \theta_m(T) \quad (B14)$$

where $\theta_m(T)$ is the maximum unfrozen water moisture content corresponding to a negative soil temperature.

750 For further details of the WEP-COR model, please refer to Li et al. (2019).