

1 **Investigation of the functional relationship between antecedent rainfall and the probability**
2 **of debris flow occurrence in Jiangjia Gully, China**

3 Shaojie Zhang¹, Xiaohu Lei^{1,4}, Hongjuan Yang¹, Kaiheng Hu¹, Juan Ma², Dunlong Liu³, Fanqiang Wei⁴

4 1.State Key Laboratory of Mountain Hazards and Engineering Safety, Institute of Mountain Hazards and
5 Environment, Chinese Academy of Sciences, Chengdu 610041, China

6 2.China Institute for Geo-Environment Monitoring, Beijing, 100081

7 3.College of Software Engineering, Chengdu University of Information and Technology, Chengdu, 610225, China

8 4.Chongqing Institute of Green and Intelligent Technology, Chinese Academy of Sciences, Chongqing 400714,
9 China

10 Correspondence to: Shaojie Zhang, E-mail: sj-zhang@imde.ac.cn; Kaiheng Hu, E-mail: khhu@imde.ac.cn

11 **Abstract**

12 A larger antecedent effective precipitation (AEP) indicates a higher probability of a debris flow
13 (P_{df}) being triggered by subsequent rainfall. Scientific topics surrounding this qualitative conclusion
14 that can be raised, including what kinds of variation rules do they follow, and whether there is a
15 boundary limit. To answer these questions, Jiangjia Gully in Dongchuan, Yunnan province, China,
16 is chosen as the study area, and a numerical calculation, rainfall scenario simulation, and Monte
17 Carlo integration method have been used to calculate the occurrence probability of debris flow under
18 different AEP conditions and derive the functional relationship between P_{df} and AEP. The
19 relationship between P_{df} and AEP can be quantified by a piecewise function. P_{df} is equal to 15.88%
20 even AEP reaches 85 mm indicating that debris flow in nature has an extremely small probability
21 compared to the rainfall frequency. Data from 1094 rainfall events and 37 historical debris flow

22 events are collected to verify the reasonability of the functional relationship. The results indicate
23 that the piecewise function are highly correlated with the observation results. Our study confirms
24 the correctness of the qualitative description of the relationship between AEP and P_{df} , clarifies that
25 debris flow is a small probability event compared to rainfall frequency, and quantitatively reveals
26 the evolution law of debris flow occurrence probability with AEP, which can provide a clear
27 reference for the early warning of debris flows.

28 **Keywords:** Debris flow, antecedent effective rainfall, Dens-ID, Monte Carlo method

29

30 **1 Introductions**

31 The antecedent effective precipitation (AEP) likes a Trojan horse lurking inside a loose soil
32 mass, which can cooperate with subsequent rainfall at any time to trigger debris flow in a debris-
33 flow gully. The AEP is equivalent to the precipitation preserved in soil mass before the triggering
34 rainfall process; it represents the saturation degree of loose soil mass (Segoni et al., 2018a;
35 Leonarduzz and Molnar, 2020). Therefore, the soil moisture that has accumulated from antecedent
36 rainfall since the beginning of a rainfall season has a significant influence on how new storm rainfall
37 interacts with the loose soil mass within a gully (Fiorillo and Wilson, 2004; Long et al., 2020). The
38 increase in AEP can decrease the shear strength of a loose solid material provided by shallow
39 landslides or channel erosion (Papa, et al., 2013; Senthilkumar et al., 2017; Liu et al., 2020), as a
40 consequence, the supply rate of solid material resources can be significantly enhanced in the
41 subsequent rainfall process (Wei et al., 2008; Bennett et al., 2014; Zhang et al., 2020). Additionally,
42 increased AEP and moisture content have been shown to enhance rainfall-induced surface runoff in
43 a variety of environments (Tisdall, 1951; Luk, 1985; Le Bissonnais et al., 1995; Castillo et al., 2003;

44 Jones et al., 2017; Hirschberg et al., 2021). Thus, AEP plays an important role in the formation of
45 debris flows (Hong et al., 2018).

46 Rainfall thresholds represent the difficulty degree of debris flow triggered by rainfall (Marra
47 et al., 2017). Investigations including the influence of AEP on the rainfall threshold can be helpful
48 to examining the relationship between AEP and debris flow occurrence. Currently, the relationship
49 between the AEP and rainfall threshold indicates that there is a negative correlation between the
50 AEP and rainfall conditions that trigger debris flows (Huang, 2013). AEP also represents the
51 saturation degree of loose soil mass (Zhao et al., 2019a; Abraham et al., 2021), and integrating soil
52 moisture with rainfall thresholds has been proven effective in improving prediction performance
53 (Segoni et al., 2018a; Zhao et al., 2019b; Abraham et al., 2020). Scholars also have attempted to
54 analyze the influence of antecedent soil moisture on the rainfall threshold triggering debris flow
55 (Cui et al., 2007; Hu et al., 2015), and there is still a negative correlation between antecedent soil
56 moisture and triggering rainfall conditions (Chen et al., 2017) just like the relationship between AEP
57 and rainfall threshold. The above investigations show that increasing in AEP can significantly
58 decrease the rainfall conditions for triggering a debris flow, which in turn means that debris flow is
59 more likely to occur. Generally, the qualitative description of ‘the greater the AEP, the higher the
60 probability (P_{df}) of subsequent rainfall triggering the debris flow (De Vita et al., 2000; Bel et al.,
61 2017)’ has gradually become a consensus. Therefore, discovering a specific function to describe this
62 qualitative description is helpful to further demonstrating the above consensus, revealing a certain
63 evolutionary law of debris flow with rainfall in nature.


64 To quantify the evolution law of P_{df} with the changing AEP, a numerical model denoted as the
65 Dens-ID can correlate the rainfall parameters (I and D) with the debris flow density (Zhang et al.,

2020; Long et al., 2020; Zhang et al., 2023), and it has been used to construct the rainfall intensity-duration (ID) threshold curves under different AEP conditions. The ID threshold curves with upper and lower bounds can delineate the closed region in the ID coordinate system, which represents the set of all rainfall conditions that can trigger debris flow at a certain AEP. Consequently, the probability of natural rainfall falling into a closed region is equivalent to P_{df} , which can then be calculated based on Monte Carlo integration. The next section introduces the basic information of study area including the rainfall and debris flow event data collected from the study area. The third section addresses how to establish the functional relationship between the AEP and Pdf using the Dens-ID and Monte Carlo integration method. Section 4, 5 and 6 discuss the results and state the conclusions of this study, respectively.

2 Study areas

The Jiangjia Gully (JJG) is a primary tributary of the Xiaojiang River, which is located in the Dongchuan District of Kunming City, Yunnan Province, China (Fig.1). As shown in Fig.1, JJG has a drainage area of 48.6 km² with elevations ranging from 1040 to 3260 m. In this gully, the relative relief from the ridge to the valley reaches 500 m, and most of the slope gradient is greater than 25°. Slopes within JJG are covered by abundant loose soil with a thickness of more than ten meters. Shallow landslides are frequently triggered by intense rainfall processes in JJG, providing a large number of solid materials for debris flow (Yang et al., 2022). Before 1979, the Menqian and Duozhao gullies are the two main tributaries of JJG, accounting for 64.7% of the entire drainage area. The upstream areas of the two main tributaries are the initiation zones of the debris flows, and the channels of the upstream tributaries are narrow and V-shaped (Zhang et al., 2020). However, several check dams have been constructed in the Duozhao gully since 1979, which have significantly reduced debris flow activity in this sub-gully (Zeng et al., 2009). Currently, Menqian Gully with the area of 13.2 km² is the primary source area. The slope gradient of its both sides is very steep, e.g., the mean slope in Menqian Gully is 32° and the maximum slope can reach 70°.

91 Bedrock that mainly consists of slates formed in lower Proterozoic crops out in the unvegetated or
92 sparsely vegetated lower part. The bedrock is fragmented and mostly disintegrates into clasts with
93 the size more than 20 mm. The upper part of the bedrock is lain by soil mantles with thicknesses of
94 0.5–20 m, which are covered by grasses and shrubs, or are used for terrace farming. The soil mantle
95 is poorly sorted and composed of particles from clay to boulder. The translational zone from the
96 upper to the lower parts of the slope is prone to shallow landslides. Some landslides directly evolve
97 into debris flows, while the others release sediment to the channel, which is mobilized by runoff in
98 debris flow events (Yang et al., 2022).



99

Fig.1 Location of JJG

100

101 Steep terrain provides a beneficial potential energy condition for transporting a large amount
102 of loose solid materials from JJG to Xiaojiang River. Consequently, debris flows in JJG can be easily
103 triggered by high-intensity rainstorm or long-duration rainfall processes (Zhang et al., 2020). The
104 solid material necessary for a debris flow in a gully may be from shallow landslides (Iverson et al.,
105 1997; Gabet and Mudd, 2006; Zhang et al., 2020; Long et al., 2020) or runoff-induced bed erosions
106 (Berti and Simoni, 2005; Coe et al., 2008; Tang et al., 2020; Bernard and Gregoretti, 2021). In JJG,
107 shallow landslides are the main sources for the solid material supply (Zhang et al., 2014; Liu et al.,
108 2016; Yang et al., 2022), which is consistent with the assumptions of Dens-ID (Zhang et al., 2020).
109 Thus, JJG is used as the study zone for deriving the function that describes the relationship between

110 AEP and P_{df} .

111 **3 Methods and data**

112 **3.1 Dens-ID**

113 Debris flow gullies characterized by a solid source supply from landslides are widely
114 distributed in southwest China (Zhang et al., 2014). For this type of debris flow gully, our previous
115 study proposed Dens-ID aiming at correlating debris-flow density to rainfall parameters based on
116 water-soil coupling mechanism (Zhang et al., 2020; Long et al., 2020). Den-ID assumes debris flow
117 to be a water-soil mixture, it contains three core simulating contents including hydrological
118 simulation, water-soil coupling to calculate the water-soil-mixture density, and correlating density
119 to rainfall parameters.

120 (1) Simulating hydrological process: the purpose is to provide parameters for estimating
121 rainfall-induced runoff and the supply volume of rainfall-induced loose solid materials. Based on
122 the digital elevation model (DEM) of a gully, Den-ID can simulate the rainfall-induced runoff and
123 water diffusion in the vertical direction within the soil mass. The rainfall infiltration border is
124 controlled by Equation 1.

$$125 \quad -D(\theta) \frac{\partial \theta}{\partial z} + K(\theta) = I(t) \quad (1)$$

126 where θ is the soil water content; $D(\theta) = K(\theta)/(d\theta/d\psi)$, which represents the soil water
127 diffusivity; z is the soil depth, which is positive downwards along the soil depth as the topsoil is
128 taken as the origin point; $K(\theta)$ is the hydraulic conductivity; $I(t)$ is the rainfall intensity; and ψ is
129 the soil matrix suction. When the rainfall intensity is less than the surface infiltration capacity,
130 Equation 1 is used to represent this physical process; whereas the case of precipitation intensity
131 exceeding the infiltration capacity of topsoil means that the surface is saturated, and the excess

132 precipitation from the topsoil is converted into runoff. Therefore, the pressure infiltration of each
 133 grid cell is not considered.

$$134 \quad \frac{\partial \theta}{\partial t} = \frac{\partial}{\partial z} \left[D(\theta) \frac{\partial \theta}{\partial z} \right] - \frac{\partial K(\theta)}{\partial z} \quad (2)$$

135 Equation 2 is the Richard differential infiltration equation (Richards, 1931), which is used to
 136 describe the water movement along the vertical direction within soil mass after precipitation
 137 infiltrates into topsoil. Dens-ID uses the finite-difference method to solve Eqs. 1 and 2 and can
 138 provide the runoff depth (denoted as $dw(i, t)$), soil water content, and soil matrix suction for each
 139 grid cell. Dens-ID then calculates the runoff volume using runoff depth $dw(i, t)$ in Equation 3.

$$140 \quad V_w(t) = \sum_{t=1}^T \sum_{i=1}^n S_g * dw(i, t) \quad (3)$$

141 where n represents the total number of grid cells that can generate runoff at time t , $V_w(t)$ represents
 142 the total volume of runoff within a gully at time t , S_g represents the area of the grid cell generating
 143 runoff, and T represents the total duration of a rainfall process.

144 (2) Calculating supply amount of loose solid materials and density of the water-soil mixture:
 145 taking hydrological parameters such as soil water content and soil matrix suction as inputs, Dens-
 146 ID uses Equations 4 and 5 to estimate the supply amount of rainfall-induced loose solid materials
 147 within a gully. Equation 4 calculates safety factor F_s of each grid cell as a function of the matrix
 148 suction and soil moisture. $F_s > 1$ indicates that the grid cell is stable and cannot supply solid material
 149 to the gully, whereas a grid with $F_s < 1$ can provide solid material in the form of a shallow landslide.

$$150 \quad F_s = \frac{\tan \varphi}{\tan \beta} + \frac{c + \psi \tan(\varphi^b)}{\gamma_t d_s \cos \beta \sin \beta} \quad (4)$$

151 where F_s represents the safety factor of each grid cell, c is the soil cohesion force, φ is the internal
 152 friction angle, φ^b is related to the matrix suction and is approximately equal to φ as the low matrix
 153 suction is small, d_s is the soil depth, and ψ is the matrix suction which is a function of soil water

154 content and can be described by the Van Genuchten model (Van Genuchten, 1980).

155 Equation 4 is used to estimate the total volume of solid materials from all the unstable grid
156 cells during a rainfall process.

$$157 \quad V_s(t) = \sum_{t=1}^T \sum_{j=1}^m S_g * ds(j, t) \quad (5)$$

158 where m represents the number of grid cells that can provide solid material at time t and $V_s(t)$ is the
159 total volume of solid material within a gully at time t . At time t , the density of the water-soil mixture
160 after full coupling between runoff and solid material can be calculated using Equation 6.

$$161 \quad \rho_{mix}(t) = \frac{\rho_w V_w(t) + \rho_s V_s(t)}{V_{mix}(t)} \quad (6)$$

162 where $\rho_{mix}(t)$ is the density of the water-soil mixture, ρ_w is the water density, ρ_s is the density of
163 the soil particles, and $V_{mix}(t)$ is the volume of the water-soil mixture, which is the sum of $V_w(t)$
164 and $V_s(t)$. $V_w(t)$ and $V_s(t)$ are the key variables that can be derived using Eqs. 3 and 5.

165 (3) Correlating density to rainfall parameters including rainfall intensity and duration: after
166 firstly presetting the density of the water-soil mixture as ρ_{mix} , Dens-ID also needs to simulate many
167 rainfall scenarios including long durations with low-intensity rainfall and short durations with high-
168 intensity rainfall in order to obtain a sufficient number of $[D_i, I_i]$. Using each $[D_i, I_i]$ as input, Dens-
169 ID then can calculate the density using Equation 6. If the calculated density is equal to ρ_{mix} , the $[D_i,$
170 $I_i]$ combination is saved by Dens-ID. After Dens-ID completes the trial calculations, all combination
171 data of $[D_i, I_i]$ that satisfy the constraints of the preset density (ρ_{mix}) can be collected as a dataset.
172 Each collected $[D_i, I_i]$ within the dataset corresponds to the preset ρ_{mix} , accordingly, Dens-ID can
173 correlate rainfall parameters (D and I) to debris flow density (Long et al., 2020). Dens-ID can derive
174 ID threshold curves by fitting the selected $[D_i, I_i]$ data, and each ID curve corresponds to a debris
175 flow density value (Zhang et al., 2020). As the density of debris flow in JJG varies in a specific

176 interval of $1.2\text{--}2.3\text{g/cm}^3$ (Zhang et al., 2014; Zhuang et al., 2015; Long et al., 2020), the threshold
177 curve that corresponds to the boundary value can form a closed area with the I- and D-axes in the
178 ID coordinate system. The case of monitoring or forecasting rainfall falling into this closed area
179 indicates that the rainfall condition may trigger debris flow. The verification results in JJG show
180 that Dens-ID can effectively describe the mechanism and process of debris flow formation, and its
181 prediction accuracy is approximately 80.5%, which is 27.7% higher than that of statistical models
182 (Zhang et al., 2020). Such a high prediction accuracy can further indicate that the closed area formed
183 by the derived ID curves has a very reasonable location and coverage in the ID coordinate system,
184 providing extremely reliable analytical data in this study.

185 **3.2 JJG data for model Dens-ID**

186 The JJG datasets for Dens-ID are terrain data, hydrological parameters, and soil mechanical
187 parameters. The DEM is the basal data for deriving other terrain data, including slope length,
188 gradient, and river channels; the spatial resolution of the DEM is 0.5 m, and a DEM with a grid size
189 of 10 m was generated using the resampling technology in ArcGIS. The hydrological parameters
190 are related to the soil types within JJG; the five key parameters are the saturated soil water content,
191 residual soil water content, the two parameters of soil water characteristic curve including n and m ,
192 and the infiltration rate of topsoil. The soil mechanical parameters are the soil cohesion force and
193 internal friction angle obtained through direct shear tests on the soil samples. Detailed data are
194 available in Zhang et al. (2020) and Long et al. (2020).

195 **3.3 Historical rainfall and debris flow data**

196 Rainfall data for the rainy seasons between 2006 and 2020 have been collected from the JJG
197 observation station, and it is necessary to identify each rainfall process from the long-term rainfall
198 sequences. Inter-event time (IET) is defined as the minimum time interval between two consecutive
199 rainfall pulses (Adams et al., 1986). IET has a strong influence on the rainfall event starting and
200 ending times (Bel et al., 2017), and Peres et al. (2018) has identified that IET depends on whether
201 the mean daily potential evapotranspiration (MDPE) is larger than precipitation within the IET. The
202 long observation of evaporation within JJG showed that MDPE is about 4 mm; precipitation during
203 IET >0.5 mm is considered the end of a rainfall process. Under this standard, 1094 rainfall events
204 and 37 debris flow events have been identified during the sampling period. Detailed rainfall data
205 information can be found in “appendix 1-1094 rainfall and 37 debris flow data.xlsx”. The AEP listed
206 in this appendix is considered the weighted sum of the rainfall periods before the occurrence of
207 debris flow (Long et al., 2020) and it can be calculated using Equation 7.

$$208 \qquad \qquad \qquad AEP = \sum_{i=1}^n K^n R_i \qquad (7)$$

209 where AEP is the antecedent effective rainfall; K is the attenuation coefficient, which is equal to
210 0.78 based on the field test in JJG (Zhang et al., 2020); and n is the number of days preceding the
211 debris flow occurrence.

212 Based on the observed rainfall data, the 1094 AEPs are calculated using Equation 7 and listed
213 in Appendix 1. The AEP corresponding to each rainfall event varies from 0–88 mm. Taking this
214 variation range as a reference, the variation range of the AEP input in the Dens-ID model is set
215 between 10 and 85 mm. Since AEP in JJG ranges in 0-88 mm according to the measured rainfall
216 data, Dens-ID presets several AEP values including 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70,
217 75, 80, 85. The cases of AEP=0 and AEP=5 mm are excluded, because the two cases represents such

218 a low initial rainfall condition that any ID curve cannot derived from Dens-ID. The purpose of
 219 increasing AEP by an interval of size 5 is to get adequate ID curves, which will be helpful to
 220 calculate P_{df} under different AEP conditions.

221 **3.4 Monte Carlo method for calculating the definite integral**

222 Because of the boundary of the debris-flow density in JJG (1.2–2.3g/cm³), Dens-ID produces
 223 the corresponding upper and lower boundary curves under a specific AEP condition. The two
 224 boundary curves can be described using the power function.

$$225 \begin{cases} f(D)_{up} = I_{up} = \alpha_1 D^{\beta_1} & D \in [a_1, b_1] \\ f(D)_{low} = I_{low} = \alpha_2 D^{\beta_2} & D \in [a_2, b_2] \end{cases} \quad (8)$$

226 These two threshold curves can delineate an enclosed area in the ID coordinate system, denoted
 227 as W_{ID} . The independent variable (D) and dependent variable (I) in Equation 8 also form a closed
 228 rectangular region in the ID coordinate system, denoted as R_{ID} . In the ID coordinate system, the
 229 coverage of R_{ID} is larger than that of W_{ID} , as will be shown in detail in Section 4.1. Limited within
 230 R_{ID} , any rainfall processes located in W_{ID} can trigger debris flow. If the probability of rainfall
 231 process falling into the range of W_{ID} under random conditions is determined, the occurrence
 232 probability of debris flow can be estimated. Many physical phenomena are stochastic in nature and
 233 governed by stochastic partial differential equations with nondeterministic initial/boundary
 234 conditions or integral equations (Peres and Cancelliere, 2014; Yan and Hong, 2014). Albert (1956)
 235 proposed the Monte Carlo method for solving integral equations. This method is subsequently used
 236 to estimate the peak flow and volume of debris flow (Donovan and Santi, 2017; Paola et al., 2017),
 237 entrainment of the underlying bed sediment (Han et al., 2015), and risk assessment (Calvo and Savi,
 238 2009; Li et al., 2021). The rainfall process is randomly selected within the R_{ID} , and the probability

239 of the chosen one falling into the W_{ID} can be determined using W_{ID}/R_{ID} . The physical meaning of
 240 the Monte Carlo solving definite integral lies on calculating the area enclosed by the function curve
 241 and horizontal axis. Therefore, the area of W_{ID} can be calculated by the difference in the definite
 242 integral formula of the two equations in Equation 8.

$$243 \quad W_{ID} = S_{up} - S_{low} = \int_{a_1}^{b_1} f(D)_{up} dD - \int_{a_2}^{b_2} f(D)_{low} dD \quad (9)$$

244 where S_{up} and S_{low} represent the area enclosed by the two threshold curves and the horizontal axis,
 245 respectively, and a_1 , b_1 , a_2 , and b_2 are the boundary values of D in the two curves. For the upper
 246 boundary line (or lower boundary), if the probability distribution function of D between $[a_1, b_1]$ is
 247 $p(D)$, Equation 10 can be derived by substituting $p(D)$ into Equation 9.

$$248 \quad \begin{cases} S_{up} = \int_{a_1}^{b_1} f(D)_{up} dD = \int_{a_1}^{b_1} \frac{f(D)_{up}}{p(D)} p(D) dD \approx \frac{1}{n} \sum_{k=1}^n \frac{f(D_i)_{up}}{p(D_i)} \\ S_{low} = \int_{a_2}^{b_2} f(D)_{low} dD = \int_{a_2}^{b_2} \frac{f(D)_{low}}{p(D)} p(D) dD \approx \frac{1}{n} \sum_{k=1}^n \frac{f(D_i)_{low}}{p(D_i)} \end{cases} \quad (10)$$

$$249 \quad W_{ID} = \frac{1}{n} \sum_{k=1}^n \frac{f(D_i)_{up}}{p(D_i)} - \frac{1}{n} \sum_{k=1}^n \frac{f(D_i)_{low}}{p(D_i)} \quad (11)$$

250 where n represents the number of random samples drawn from the variation range of D , and $p(D_i)$
 251 is the probability density distribution function of D in the interval $[a_1, b_1]$ or $[a_2, b_2]$. The key to
 252 solving Equation 10 depends on sampling from $p(D)$. The following steps are used to explain how
 253 samples were taken using $p(D_i)$.

254 Step 1: Based on the probability density distribution function $p(D)$, the cumulative probability
 255 distribution function can be derived by $cdf(D) = \int_{-\infty}^D f(D) dD$;

256 Step 2: Assume that $U^{(i)}$ obeys a uniform distribution within $[0, 1]$, which can be randomly collected
 257 from this interval and denoted as $U^{(i)} \sim U(0, 1)$.

258 Step 3: Substitute $U^{(i)}$ into the inverse function of the cumulative probability distribution $cdf(D)$ to
 259 obtain random sample $D^{(i)}$, denoted by $D^{(i)} = cdf^{-1}(U^{(i)})$. Then, a dataset composed of n data
 260 points of $D^{(i)}$ is obtained.

261 Step 4: W_{ID} can be calculated by substituting n data points of $D^{(I)}$ into Equation 10, and the P_{df}
 262 ($P_{df} = \frac{R_{ID}}{W_{ID}}$) corresponding to a specific AEP is determined. P_{df} represents the probability that the
 263 subsequent precipitation process may trigger debris flow for a certain AEP. Thus, the influence of
 264 the AEP on the occurrence probability of debris flows can be quantified.

265 3.5 Correlation analysis between numerical and observation results

266 The relationship between the AEP- P_{df} fitted through the observational data is used as a
 267 reference standard, and the correlation analysis method is used to verify the function of the AEP- P_{df}
 268 derived by Dens-ID. Correlation analysis is used to study the degree of linear correlation between
 269 variables, which is represented by correlation coefficient r :

$$270 \quad r = \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum_{i=1}^n (x_i - \bar{x})^2 \sum_{i=1}^n (y_i - \bar{y})^2}} \quad (12)$$

271 where x represents the P_{df} derived from the observed data, y represents the P_{df} derived from Dens-
 272 ID, \bar{x} and \bar{y} represent the averages, r represents the correlation coefficient, and n represents the
 273 number of samples. $|r| \geq 0.8$ can be regarded as a high correlation between two variables; $0.5 \leq |r| < 0.8$
 274 represents a moderate correlation; $0.3 \leq |r| < 0.5$ represents a low correlation; and $|r| < 0.3$ indicates the
 275 degree of correlation between the two variables is weak and can be regarded as uncorrelated.

276 4 Results

277 4.1 ID threshold curves and warning zone closed by the derived curves


278 Dens-ID yields the upper and lower boundary lines of the ID threshold in each condition of a
 279 preset AEP, and these two boundary lines are characterized by different debris flow density and
 280 listed in Table 1. It can be seen from Table 1 that the maximum density corresponding to the ID
 281 threshold curve cannot reach 2.2, when AEP is less than 15 mm. A small AEP indicates the supply
 282 rate of solid resources in JJG is far less than the runoff generation rate during a subsequent rainfall

283 process. In this situation, runoff is dominated in the water-soil coupling process yielding a water-
 284 soil mixture with low density value.

285 Table 1 ID threshold curve database under different AEP


AEP (mm)	ID threshold curve function for JJG	
	1.2 g/cm ³	2.2 g/cm ³
10	$I_{1.2} = 19.85D^{-0.54} D \in [1, 269] (R^2 = 0.991)$	$I_{1.8} = 15.85D^{-0.48} D \in [1, 263] (R^2 = 0.990)$
15	$I_{1.2} = 21.69D^{-0.55} D \in [1, 236] (R^2 = 0.993)$	$I_{2.0} = 16.10D^{-0.50} D \in [1, 229] (R^2 = 0.995)$
20	$I_{1.2} = 23.22D^{-0.58} D \in [1, 203] (R^2 = 0.996)$	$I_{2.2} = 17.20D^{-0.53} D \in [1, 192] (R^2 = 0.995)$
25	$I_{1.2} = 24.47D^{-0.60} D \in [1, 171] (R^2 = 0.997)$	$I_{2.2} = 16.92D^{-0.53} D \in [1, 160] (R^2 = 0.998)$
30	$I_{1.2} = 26.24D^{-0.64} D \in [1, 143] (R^2 = 0.996)$	$I_{2.2} = 18.09D^{-0.57} D \in [1, 132] (R^2 = 0.995)$
35	$I_{1.2} = 35.47D^{-0.65} D \in [1, 123] (R^2 = 0.958)$	$I_{2.2} = 19.55D^{-0.58} D \in [1, 112] (R^2 = 0.985)$
40	$I_{1.2} = 40.59D^{-0.78} D \in [1, 103] (R^2 = 0.966)$	$I_{2.2} = 22.15D^{-0.64} D \in [1, 92] (R^2 = 0.984)$
45	$I_{1.2} = 41.12D^{-0.78} D \in [1, 83] (R^2 = 0.932)$	$I_{2.2} = 23.19D^{-0.69} D \in [1, 72] (R^2 = 0.981)$
50	$I_{1.2} = 41.26D^{-0.86} D \in [1, 65] (R^2 = 0.981)$	$I_{2.2} = 23.50D^{-0.74} D \in [1, 55] (R^2 = 0.980)$
55	$I_{1.2} = 38.63D^{-0.88} D \in [1, 53] (R^2 = 0.950)$	$I_{2.2} = 23.31D^{-0.70} D \in [1, 42] (R^2 = 0.932)$
60	$I_{1.2} = 31.49D^{-0.92} D \in [1, 40] (R^2 = 0.992)$	$I_{2.2} = 20.73D^{-0.86} D \in [1, 30] (R^2 = 0.977)$
65	$I_{1.2} = 29.14D^{-0.95} D \in [1, 32] (R^2 = 0.957)$	$I_{2.2} = 18.10D^{-0.91} D \in [1, 22] (R^2 = 0.893)$
70	$I_{1.2} = 23.05D^{-0.96} D \in [1, 25] (R^2 = 0.998)$	$I_{2.2} = 13.04D^{-0.93} D \in [1, 15] (R^2 = 0.995)$
75	$I_{1.2} = 21.13D^{-0.97} D \in [1, 22] (R^2 = 0.994)$	$I_{2.2} = 10.90D^{-0.95} D \in [1, 12] (R^2 = 0.995)$
80	$I_{1.2} = 18.72D^{-0.98} D \in [1, 20] (R^2 = 0.997)$	$I_{2.2} = 9.96D^{-0.95} D \in [1, 11] (R^2 = 0.999)$
85	$I_{1.2} = 18.47D^{-0.99} D \in [1, 18] (R^2 = 0.999)$	$I_{2.2} = 8.17D^{-0.95} D \in [1, 9] (R^2 = 0.999)$

286 Under the condition of $AEP < 10$ mm, Dens-ID cannot derive the threshold curve
 287 corresponding to even the minimum density value of 1.2 g/cm^3 , which indicates that the subsequent
 288 rainfall can hardly trigger debris flow JJG. Table 1 also shows that the AEP ranging from 10 to 85
 289 mm can significantly affect the ID threshold curve, because the parameters including α and β
 290 regularly respond to the change in AEP.




291

292



293

294



295

296 Fig.2 ID threshold curves derived by Dens-ID (the blue dotted line corresponds to 1.2 g/cm^3 , and


297 the orange dotted line corresponds to 2.2 g/cm^3)

298 There are two ID threshold curves in each subplot of Fig. 2, which correspond to 1.2 g/cm^3 and
299 2.2 g/cm^3 , respectively. Because the debris flow density in JJG varies within a certain range from
300 $1.2\text{--}2.3 \text{ g/cm}^3$, the two ID threshold curves shown in each subplot can be regarded as the upper and
301 lower boundary lines for determining the occurrence of debris flow (Zhang et al., 2020). Within the
302 ID coordinate system, the two derived curves together with the I- and D-axes delineate a closed area
303 shown in Fig.2c. Any subsequence rainfall represented by the combination of I and D falling into
304 W_{ID} may trigger a debris flow. As shown in each subplot, the threshold curve can be represented by
305 the power function $I=\alpha D^\beta$. The variation intervals of the independent (D) and dependent (I) variables
306 of the power function are $[1, D_{\max}]$ and $[1, I_{\max}]$, respectively, where D_{\max} represents the rainfall
307 duration required to trigger debris flow when $I= 1 \text{ mm/h}$, and I_{\max} represents the rainfall intensity
308 required for debris flow formation for $D=1 \text{ h}$. As shown in Fig.2c, independent variable D and
309 dependent variable I can delineate a larger rectangular area (AOBC) in the ID plane than W_{ID} , which
310 is denoted as R_{ID} . The coverage area of R_{ID} is much larger than that of W_{ID} indicating that the
311 proportion of rainfall conditions that can trigger debris flows is low. Therefore, even for AEP=85
312 mm, the occurrence probability of debris flows remains low. As shown in each subplot, each AEP
313 corresponds to a different W_{ID} and R_{ID} , which provides basic data for the quantitative evaluation of
314 the effect of different AEPs on the occurrence probability of debris flows.

315 **4.2 Occurrence probability of debris flow under different AEP**

316 Based on the Monte Carlo method of calculating the definite integral, it is necessary to explore
317 the probability density function of rainfall duration (D) to calculate the occurrence probability of
318 debris flow under different AEP conditions. For the 1094 rainfall events listed in Appendix 1, we

319 found that the probability distribution of rainfall duration D in JJG can be described by a power
 320 function (Fig. 3). As shown in Fig.3, the number of samples with $D < 1$ accounted for 37.7%, $1 < D < 3$
 321 for 23.5%, $3 < D < 5$ for 14.7%, and $5 < D < 10$ for 16.9%; the number of rainfall events with D
 322 exceeding 10 h accounted for only 6.7%.



323

324 Fig. 3 Probability density function of $f(D)$

325 Based on the probability density distribution function $f(D)=0.2312D^{-1.617}$, the cumulative
 326 probability function $cdf(D)$ can be obtained through integration. In $cdf(D)$, denoted as Equation 13,
 327 the integration constant C needs to be determined.

328
$$cdf(D) = \int_{-\infty}^D f(D) dD = -0.3747 * D^{-0.617} + C \quad (13)$$

329 The range of 0–40 h is evenly divided into 56 statistical intervals (the second column in
 330 Appendix 2, titled “appendix 2-f(D)and CFD(D).xlsx”), and each statistical interval is separated by
 331 0.5 h. The proportion of the sample size in each interval among the 1094 samples can be calculated
 332 and listed in the second column in Appendix 2; the cumulative proportion that increases with D is
 333 also derived and listed in the third column in Appendix 2. The data in the first and third columns of
 334 Appendix 2 are substituted into Equation 13 to calculate C . The results show that C increases with
 335 D but gradually stabilizes at approximately 1.04 (the fifth column in Appendix 2). Therefore, C is

336 set to 1.04.

337 Based on the process of calculating P_{df} under different AEP conditions in Section 3.4, the P_{df}
338 corresponding to each AEP in Table 1 is obtained, and the function $P_{df} = f(AEP)$ for describing
339 their relationship has been fitted using the AEP and P_{df} data.

$$340 \quad P_{df} = 0.3442e^{0.0457AEP} \quad (14)$$

341 As shown in Equation 14, the relationship of AEP and P_{df} obeys the rule of exponential function
342 as AEP changes from 10 to 85 mm, whereas $P_{df} = 0$ when AEP is less than 10 mm. The evolution
343 of P_{df} with AEP variation can be divided into two stages (Fig. 4). Two key issues must be stated
344 before discussing the two stages in depth: (1) Based on the calculation results of the Dens-ID model,
345 an upper limit volume of the rainfall-induced solid material supply is derived in JJG, which is the
346 basic condition for determining the scale of debris flow in JJG (Zhang et al., 2020). (2) Based on
347 the principle of water balance, AEP is defined as the rainfall that is preserved in the soil before the
348 triggering rainfall process (Kohler and Linsley, 1951); field observations in JJG show that the AEP
349 is positively correlated with the soil water content (Cui et al., 2007), and the field observations of
350 the Liudaogou catchment in the northern Loess Plateau of China have the same result (Zhu and
351 Shao, 2008); therefore, the AEP is typically used to estimate soil water content (Crozier, 1986; Chen
352 et al., 2018; Zhao et al., 2019b). The water soil content before the triggering rainfall process can be
353 characterized by AEP (Thomas et al., 2019; Schoener and Stone, 2020).




Fig.4 Relationship of P_{df} and AEP derived from Dens-ID

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

Stage 1: The probability of debris flow occurrence in JJG is equal to 0 when the AEP is < 10 mm. Dens-ID estimates the solid material volume by simulating rainfall-induced shallow landslides. According to Equation 4, the key hydrological process that triggers shallow landslides is the continuous increase in soil water content caused by rainfall infiltration. The increase in soil moisture content reduces soil matrix suction and eventually contributes to shallow landslides. The soil water content of the loose soil mass in JJG is low when the AEP < 10 mm (Long et al., 2020), and a long duration of rainfall infiltration is needed to increase the soil water content. However, based on the infiltration border of Dens-ID (Equation 1), limited by the infiltration capacity of the topsoil in JJG, the portion of precipitation that exceeds the infiltration capacity is be converted into runoff; therefore, when the water content of the soil layer in JJG is low, the surface runoff can be rapidly generated. Therefore, the runoff generation rate can be much higher than the supply rate of solid material in the condition of AEP < 10 mm. In this hydrological scenario, Dens-ID determines that even a soil-water mixture with a density of 1.2 g/cm³ is difficult to generate in JJG; thus, the probability of debris flow is 0.

370 Stage 2: When AEP varies within the interval of 10 mm-85mm, the subsequent rainfall is
371 capable of triggering debris flow in JJG. Compared to AEP < 10 mm in Stage 1, the soil water
372 content within JJG increased significantly. Therefore, the solid material from shallow landslides can
373 be immediately ready without a long rainfall infiltration duration, and a large water content of
374 topsoil is beneficial to the rapid generation of runoff (Jones et al., 2017; Hirschberg et al., 2021).
375 When there is a sufficient supply of solid material and runoff, the probability of debris flow
376 occurrence in Stage 2 is significantly increased by the increasing AEP. The relationship between
377 $P_{df} \sim AEP$ can be described by an exponential function of $P_{df} = 0.3442e^{0.0457AEP}$. The exponential
378 function and its boundary show that the increasing tendency of P_{df} is a little sluggish before AEP is
379 equal to 50 mm. The occurrence probability of debris flow in JJG is only 15.88% even when AEP
380 is equal to 85 mm.

381 **5 Discussions**

382 **5.1 Correlation analysis of the two curves derived from Dens-ID and observation data**

383 The AEP in Appendix 1 varied from 0–87.9 mm, according to this range, we can test the
384 reasonability of the relationship between $P_{df} \sim AEP$ shown in Fig. 4. We introduce how to use the
385 rainfall and debris flow data recorded in Appendix 1 to calculate P_{df} : (1) The original AEP value is
386 rounded to one decimal place, and the rounded AEP are listed in the 8th column of Appendix 1,
387 which were sorted from largest to smallest; (2) the maximum AEP_i was set to 85 mm, and [AEP_i,
388 AEP_i-5] was used as the search window to collect the rainfall events and debris flow events; and (3)
389 we count the number of debris flow events N_{df} and the number of rainfall events N_{rain} in each search
390 window and then calculate $P_{df} = N_{df}/N_{rain}$. Based on the above steps, the collected data and calculated


391 P_{df} are listed in Table 2. As shown in Table 2, a positive correlation between the probability of debris
 392 flow occurrence and AEP in JJG was determined. When AEP < 10 mm, a total of 205 rainfall
 393 processes were recorded; however, no debris flow events were observed, and the debris flow
 394 occurrence probability was 0, which is consistent with the results of Stage 1 derived from Dens-ID.

395

Table 2 Collected and calculated P_{df} in each search window

	Field observation data and calculated P_{df}										
AEP	10	15	20	25	30	35	40	45	50	75	80
N_{df}	0	3	2	7	7	4	4	5	3	1	1
N_{rain}	205	133	111	127	124	106	106	49	31	8	5
$P_{df}(\%)$	0	2.3	1.8	5.5	5.6	3.8	3.8	10.2	9.7	12.5	20

396 Based on P_{df} and AEP listed in Table 2, their relationship can be described by the exponential
 397 function denoted as $P_{df} = 1.5917e^{0.031AEP}$, which is similar to Equation 14 drawn in Fig.4. The
 398 two curves were nearly parallel. Equation 12 was used to analyze the correlation of the two curves,
 399 and r is equal to 0.93, suggesting they have a very high correlation. Therefore, the function of $P_{df} =$
 400 $f(AEP)$ derived from Dens-ID, which is used to describe the evolution trend of debris flow
 401 occurrence probability with AEP variation, is reasonable.



402

403 Fig.5 Relationship of AEP and P_{df} obtained from field observation data and Dens-ID model (the blue line is

404 derived from field observation data, and the black line is derived from Dens-ID)

405 We can also see from Fig.5 that although the variation tendencies of the two curves are

406 consistent, a significant bias existed between them. Basically, the probability value derived from the

407 field observation data is larger than that from the Dens-ID model in the condition of a given AEP.

408 As shown in Fig.5, the blue line fitted through the observation data is above the black line derived

409 from Dens-ID, indicating that Dens-ID underestimated the probability of debris flow occurrence if

410 the observation data were used as the reference. Taking the probability value in the 6th row of Table

411 2 as references, the error of the Equation14 was calculated using the AEP in Table 2 as inputs and

412 listed in Table 3.

413 Table 3 Error estimation on the Equation 14

AEP	15	20	25	30	35	40	45	50	75	80
Error	0.70	0.53	0.81	0.76	0.63	0.44	0.67	0.57	0.17	0.35

414 It can be seen that very large bias of Equation12 is listed in Table 2. However, we cannot

415 conclude that there is a precision problem in the calculation results of the Dens-ID. Because (1)
416 Although 1094 rainfall processes and 37 debris flow events are the field observation data, there are
417 many uncertain factors in Equation 7 for calculating AEP using these rainfall data (Kim et al., 2021),
418 such as the subjectivity existing in K and n of Equation 7, which render uncertainty in the calculated
419 AEP. In this case, if the data in Appendix 1 are used as the real value for evaluating the precision of
420 Dens-ID, the error evaluation result may be unfair to Dens-ID. In this case, it is unfair to evaluate
421 the Dens-ID error by using the calculated AEP in Appendix 1 as the true value. However, this
422 uncertainty can show consistent directional deviations because of the fixed values of K and n in
423 Equation 7; therefore, the uncertainty has no effect on the correlation analysis. (2) To establish the
424 functional relationship between P_{df} -AEP, many rainfall scenarios were simulated using the Dens-ID
425 model. Dens-ID simulated 3376, 3182, 2677, and 2677 rainfall processes with AEP = 20, 40, 45,
426 and 50 mm, respectively. The total number of simulated rainfall processes was significantly larger
427 than that of the 1094 observed rainfall events. The collected 1094 rainfall events still cannot fully
428 reflect all rainfall conditions in nature; that is, the amount of the observed 1094 rainfall data is still
429 inadequate when used as the denominator for calculating the probability of debris flow occurrence
430 in JJG. Therefore, the P_{df} calculated using the field observation data may be generally higher than
431 that calculated using Dens-ID. With the accumulation of rainfall observation data of JJG, it is
432 believed that the Pdf derived from field observation data will gradually decrease until it is close to
433 the calculated value of Dens-ID model. (3) Dens-ID cannot fully and accurately describe the
434 formation process of the debris flow in JJG because of the simplification in theory and boundaries.
435 Dens-ID is also affected by the accuracy of the input parameters (Zhang et al., 2020), which may
436 eventually lead to deviations between the simulation results and field observations.

437 5.2 Potential application and limitation

438 Deriving a quantified functional relationship of P_{df} and AEP would be more conducive to
439 examining the correspondence between these two parameters. Using mathematical physics method,
440 the function of $P_{df} = f(AEP)$ was firstly derived which can help us to learn more from the derived
441 $P_{df} = f(AEP)$.

442 Firstly, AEP is indeed an important factor affecting debris flow. Generally, there is the
443 following consensus in the field of debris flow: the greater the AEP, the higher the probability (P_{df})
444 of subsequent rainfall triggering the debris flow (De Vita et al., 2000; Bel et al., 2017). However,
445 this fuzzy qualitative description cannot explain the influence degree of AEP on the probability of
446 debris flow induced by subsequent rainfall. It can be seen from $P_{df} = f(AEP)$ that there are two
447 key value nodes of AEP affecting P_{df} : (1) point 10 mm: the case of $AEP < 10$ mm indicates that
448 any subsequent rainfall cannot trigger debris flow in JJG. Because the supply rate of solid material
449 is much lower than the runoff generation rate during subsequent rainfall in JJG, the water-soil
450 mixture within tends to be a hyperconcentrated flow rather than a debris flow (Long et al., 2020);
451 (2) Point 50 mm: the case of $10 \text{ mm} \leq AEP \leq 50 \text{ mm}$ means that the soil water content increases
452 significantly compared to $AEP < 10$ mm, but a necessary infiltration time to increase it to the critical
453 state for triggering shallow landslides is still required. Therefore, limited by the supply rate of the
454 solid material, the increasing rate of P_{df} is sluggish. The case of $50 \text{ mm} < AEP \leq 85 \text{ mm}$ represents
455 the soil water content is relatively larger, the solid material from shallow landslides can be
456 immediately ready without a long rainfall infiltration duration, and a large soil water content of
457 topsoil is beneficial to the rapid generation of runoff (Jones et al., 2017; Hirschberg et al., 2021).
458 When there is a sufficient supply of provenance and runoff, the probability of debris flow occurrence

459 in this subprocess is significantly enhanced by the increasing AEP.

460 Secondly, Rainfall-induced debris flow is a small probability event compared with the rainfall
461 frequency in nature. JJG is well-known due to its high-frequency debris flow event. However, the
462 formation probability of debris flow in JJG induced by subsequence rainfall is only 15.88% even
463 the AEP reaches to 85 mm. Therefore, debris flow induced by rainfall in JJG is a small probability
464 event compared with the rainfall frequency. The figure of 15.88% means that the efficiency of rain-
465 induced debris flow is extremely low, which also indicates that the formation of debris flow is an
466 extremely complex physical process, in which rainfall is only one of the motivating factors, and
467 there are other more important internal factors affecting the formation of debris flow, such as
468 topography, source recharge and fluid characteristics of debris flow (Zhang et al., 2020). Thirdly, in
469 practical application, when the AEP in JJG is calculated according to Equation 7, the derived
470 exponential function can help us to assess the probability of debris flow in JJG triggered by
471 subsequent rainfall, according to which debris flow warning information can be issued in advance
472 to provide technical support for disaster prevention and reduction.

473 Our study also has its own limitations and needs to be listed for providing directions for
474 subsequent investigation. (1) Long-term observation data should be used to deduce the functions of
475 $P_{df} = f(AEP)$, however, the number of debris flow gullies with long-term observational data
476 worldwide is less than 10 (Hürlimann et al., 2019), accordingly, the function of $P_{df} = f(AEP)$
477 cannot yet be derived in other debris-flow gullies. (2) Dens-ID model assumes that the solid
478 material mainly comes from shallow landslides. However, the formation mechanism and solid
479 source supply mode of runoff-induced debris flow are different. Therefore, the functional of $P_{df} =$
480 $f(AEP)$ for runoff-induced debris flow still needs to be studied with the help of other physical

481 models. (3) The calculation result of $P_{df} = f(AEP)$ derived from Dens-ID model has a large bias
482 from the observation data, the authors think that the main reason is insufficient field observation
483 data especially inadequate rainfall data. Basically, even for high-frequency debris flow gullies like
484 JJG, the success rate of debris flow induced by rainfall is still very low. Continuous increase of
485 rainfall and debris flow observation data will make the growth rate of N_{rain} in Table 2 much higher
486 than that of N_{df} . Therefore, with the accumulation of rainfall observation data of JJG, it is believed
487 that the P_{df} derived from field observation data will gradually decrease until it is close to the
488 calculated result of Dens-ID model. Therefore, the authors will continue to collect field observation
489 data of JJG in the later period, and constantly verify the accuracy of Equation 14 derived from Dens-
490 ID.

491 **5 Conclusions**

492 The Dens-ID model and Monte Carlo integral equation is used to derive function of $P_{df} =$
493 $f(AEP)$. The functional relationship is verified using a large amount of field observation data from
494 JJG. The following conclusions are drawn as follows.

495 The positive relationship between P_{df} and AEP is now described by a clear mathematical
496 equation in this study. the effective range of AEP that can affect debris flow formation verifies within
497 10–85 mm. Based on the simulation results, the probability of debris flow occurrence in JJG is 0 in
498 the condition of $AEP < 10$ mm, and the relationship between P_{df} and AEP can be described by an
499 exponential function when $10 \text{ mm} \leq AEP \leq 85 \text{ mm}$. The plausibility of the first two evolution stages
500 of the P_{df} -AEP piecewise function is effectively confirmed by the field observation data because the
501 P_{df} -AEP relationship obtained from field observation data is highly correlated with the simulation
502 results of Dens-ID. However, the reasonability of the last two stages of the P_{df} -AEP piecewise

503 function cannot be tested because of the lack of field observation data, and the errors of the P_{df} -AEP
504 piecewise function cannot be verified because of the uncertainty of the AEP derived from the
505 observation rainfall data.

506 This study mathematically confirms that "the greater the AEP, the higher the probability of
507 subsequent rainfall triggering debris flow" and quantifies this qualitative conclusion using piecewise
508 functions. This can effectively reveal the essential relationship between the two natural events of
509 rainfall and debris flow, quantitatively describe the impact of different AEPs on the probability of
510 debris flow occurrence, and provide key technical support for the early warning of debris flows.

511 **Code/Data availability**

512 Some or all data, models, or code generated or used during the study are available from the
513 corresponding author by request.

514 **Author Contribution**

515 SJZ, XHL, HJY, JM, and DLL conceptualized the work; developed the methodology; and carried
516 out the data curation, formal analysis, validation, and writing of the original draft. FQW and KHH
517 reviewed the initial manuscript.

518 **Competing interests**

519 The contact author has declared that none of the authors has any competing interests.

520 **Acknowledgement:**

521 This work was supported by the National Key Research and Development Program of China
522 (2023YFC3007205), the West Light Foundation of The Chinese Academy of Science, National
523 Natural Science Foundation of China (No. 42271013, No. 42001100), Project of the Department of
524 Science and Technology of Sichuan Province (No. 2023ZHCG0012).

525 **References**

- 526 Abraham, M.T., Satyan, N., Rosi, A., Pradhan, B., Segoni, S.: Usage of antecedent soil moisture for
527 improving the performance of rainfall thresholds for landslide early warning. *Catena*, 200,
528 105147, 2021.
- 529 Abraham, M.T., Satyam, N., Pradhan, B., Alamri, A.M.: Forecasting of landslides using rainfall
530 severity and soil wetness: A probabilistic approach for Darjeeling Himalayas. *Water (Switzerland)*
531 12, 1–19, 2020.
- 532 Adams, B., Fraser, H., Howard, C., Hanafy, M.: Meteorological data analysis for drainage system
533 design. *J. Environ. Eng.* 112, 1986.
- 534 Albert, G.E.: A general theory of stochastic estimates of the Neumann series for solution of certain
535 Fredholm integral equations and related series, in: M.A. Meyer (Ed.), *Symposium of Monte Carlo*
536 *Methods*, Wiley, New York, 1956.
- 537 Bel, C., Liébault, F., Navratil O., Eckert N., Bellot H., Fontaine, F., Laigle, D.: Rainfall control of
538 debris-flow triggering in the Réal Torrent, Southern French Prealps, 291, 17-32, 2017.
- 539 Bennett, G.L., Molnar, P., Mcardell, B.W., Burlando, P.: A probabilistic sediment cascade model of
540 sediment transfer in the Illgraben. *Water Resources Research*, 50, 1225-1244, 2014.
- 541 Bernard, M., Gregoretti, C.: The use of rain gauge measurements and radar data for the model-based
542 prediction of runoff-generated debris flow occurrence in early warning systems. *Water Resources*
543 *Research*, 57, e2020WR027893, 2021.
- 544 Berti, M., Simoni, A.: Experimental evidences and numerical modelling of debris flow initiated by
545 channel runoff. *Landslides*, 3, 171-182, 2005.
- 546 Calvo, B., Savi, F.: A real-world application of Monte Carlo procedure for debris flow risk

547 assessment, *Computers and Geosciences*, 35(5), 967-977, 2009.

548 Castillo, V.M., Gómez-Plaza, A., Martínez-Mena, M.: The role of antecedent soil water content in
549 the runoff response of semiarid catchments: a simulation approach. *Journal of Hydrology*, 284,
550 114-130, 2003.

551 Chen, C.W., Oguchi, T., Chen, H., Lin, G.W. Estimation of the antecedent rainfall period for mass
552 movements in Taiwan, *Environmental Earth Sciences*, 77, 184, 2018.

553 Chen, C.W., Saito, H., Oguchi, T.: Analyzing rainfall-induced mass movements in Taiwan using the
554 soil water index, *Landslides*, 14, 1031-1041, 2017.

555 Coe, J.A., Kinner, D.A., Godt, J.W. Initiation conditions for debris flows generated by runoff at
556 Chalk Cliffs, central Colorado. *Geomorphology*, 3, 270-297, 2008.

557 Crozier, M.J.: *Landslides: causes, consequences & environment*. Croom Helm, London, p 25, 1986.

558 Cui, P., Zhu, Y.Y., Chen, J., Han, Y.S., Liu, H.J.: Relationships between antecedent rainfall and
559 debris flows in Jiangjia Ravine, China. In: Chen & Major, eds., *Debris-Flow Hazards Mitigation:*
560 *Mechanics, Prediction, and Assessment*, Millpress, Netherlands, 3-10, 2007.

561 De Vita, P.: Fenomeni d'instabilita' delle coperture piroclastiche dei Monti Lattari, di Sarno e di
562 Salerno (Campania) ed analisi degli eventi pluviometrici determinanti. *Quad. Geol. Appl.*, 7, 213–
563 239, 2000.

564 Donovan, I.P., Santi, P.M. A probabilistic approach to post-wildfire debris-flow volume modeling,
565 *Landslides*, 14(4): 1345-1360, 2017.

566 Fiorillo, F., Wilson, R.C. Rainfall induced debris flows in pyroclastic deposits, Campania (southern
567 Italy). *Engineering Geology*, 75, 263-289, 2004.

568 Gabet, E.J., Mudd, S.M.: The mobilization of debris flows from shallow landslides. *Geomorphology*

569 1, 207-218, 2006.

570 Han, Z., Chen, G.Q., Li, Y.G., He, Y.: Assessing entrainment of bed material in a debris-flow event:
571 a theoretical approach incorporating Monte Carlo method: Assessing Entrainment of Bed
572 Material by Debris Flow, *Earth surface processes and landforms*, 40(14): 1877-1890, 2015.

573 Hirschberg, J., Badoux, A., McArdell, B.W., Leonarduzzi, E., Molnar, P.: Evaluating methods for
574 debris-flow prediction based on rainfall in an Alpine catchment. *Nat. Hazards Earth Syst. Sci.*,
575 21, 2773-2789, 2021.

576 Hong, M., Kim, J., Jeong, S.: Rainfall intensity-duration thresholds for landslide prediction in South
577 Korea by considering the effects of antecedent rainfall. *Landslides*, 15, 523–534, 2018.

578 Hu, W., Xu, Q., Wang, G.H., van Asch, T.W.J., Hicher, P.Y.: Sensitivity of the initiation of debris
579 flow to initial soil moisture. *Landslides* 12, 1139–1145, 2015.

580 Huang, C.H.: Critical rainfall for typhoon-induced debris flows in the Western Foothills, Taiwan.
581 *Geomorphology*, 185, 87-95, 2013.

582 Hürlimann, M. Coviello, V., Bel, C., Guo, X.J., Berti, M., Graf, C., Hübl, J., Miyata, S., Smith, J.B.,
583 Yin, H.Y.: Debris-flow monitoring and warning, Review and examples. *Earth-Science Reviews*,
584 199, 102981, 2019.

585 Iverson, R. M., Reid, M. E., LaHusen, R. G.: Debris Flow Mobilization from Landslides. *Annu. Rev.*
586 *Earth Planet*, 25: 85-138, 1997.

587 Jones, R., Thomas, R.E., Peakall, J., Manville, V.: Rainfall-runoff properties of tephra: Simulated
588 effects of grain-size and antecedent rainfall. *Geomorphology*, 282, 39-51, 2017.

589 Kim, S.W., Chun, K.W., Kim, M., Catani, F., Choi, B., Seo, J.: Effect of antecedent rainfall
590 conditions and their variations on shallow landslide-triggering rainfall thresholds in South Korea.

591 Landslides, 18, 569-582, 2021.

592 Kohler, M.A., Linsley, R.K.: Predicting the runoff from Storm Rainfall. US Department of
593 Commerce, Weather Bureau, Washington, D.C, 1951.

594 Le Bissonnais, Y., Renaux, B., Delouche, H. Interactions between soil properties and moisture
595 content in crust formation, runoff and interrill erosion from tilled loess soils. *Catena*, 25(1), 33-
596 46, 1995.

597 Li, L., Zhang, S.X., Li, S.H., Qiang, Y., Zheng, Z., Zhao, D.S.: Debris Flow Risk Assessment
598 Method Based on Combination Weight of Probability Analysis, *Advances in civil engineering*,
599 2021, 1-12, 2021.

600 Liu, D.L., Zhang, S.J., Yang, H.J., Zhao, L.Q., Jiang, Y.H., Tang, D., Leng, X.P.: Application and
601 analysis of debris-flow early warning system in Wenchuan earthquake-affected area. *Nat. Hazards*
602 *Earth Syst. Sci.*, 16, 483-496, 2016.

603 Liu, X.L., Wang, F., Nawnit, K., Lv, X.F., Wang, S.J. Experimental study on debris flow initiation.
604 *Bulletin of Engineering Geology and the Environment*, 79, 1565-1580, 2020.

605 Long, K., Zhang, S.J., Wei, F.Q., Hu, K.H., Zhang, Q., Luo, Y. A hydrology-process based method
606 for correlating debris flow density to rainfall parameter and its application on debris flow
607 prediction. *Journal of Hydrology*, 589, 125124, 2020.

608 Luk, S.H.: Effect of antecedent soil moisture content on rainwash erosion. *Catena*, 12, 129-139,
609 1985.

610 Marra, F., Destro, E., Nikolopoulos, E.I., Zocatelli, D., Creutin, J.D., Guzzetti, F., Borga, M.:
611 Impact of rainfall spatial aggregation on the identification of debris flow occurrence thresholds.
612 *Hydrol. Earth Syst. Sci.*, 21, 4525-4532, 2017.

613 Paola, F.De., Risi, R.De., Crescenzo, G. Di, Giugni, M., Santo, A., Speranza, G.: Probabilistic
614 Assessment of Debris Flow Peak Discharge by Monte Carlo Simulation, *Journal of Risk and*
615 *Uncertainty in Engineering Systems, Part A: Civil Engineering*, 3(1), A4015002, 2017.

616 Papa, M.N., Medina, V., Ciervo, F., Bateman, A.: Derivation of critical rainfall thresholds for
617 shallow landslides as a tool for debris flow early warning systems. *Hydrol. Earth Syst. Sci.* 17,
618 4095-4107, 2013.

619 Peres, D.J., Cancelliere, A.: Derivation and evaluation of landslide-triggering thresholds by a Monte
620 Carlo approach. *Hydrol. Earth Syst. Sci.*, 18, 4913-4931, 2014.

621 Peres, D.J., Cancelliere, A.: Modeling impacts of climate change on return period of landslide
622 triggering. *Journal of Hydrology*, 567, 420-434, 2018.

623 Richards, L.A. Capillary condition of liquids in porous mediums. *Physics* 1, 318–333, 1931.

624 Schoener, G., Stone, M.C.: Monitoring soil moisture at the catchment scale-A novel approach
625 combining antecedent precipitation index and radar-derived rainfall data, *Journal of Hydrology*,
626 589, 125155, 2020.

627 Segoni, S., Piciullo, L., Gariano, S.L.: A review of the recent literature on rainfall thresholds for
628 landslide occurrence, *Landslides*, 15:1483-1501, 2018b.

629 Segoni, S., Rosi, A., Lagomarsino, D., Fanti, R., Casagli, N.: Brief communication: Using averaged
630 soil moisture estimates to improve the performances of a regionalscale landslide early warning
631 system. *Nat. Hazards Earth Syst. Sci.* 18, 807–812, 2018a.

632 Senthilkumar, V., Chandrasekaran, S.S., Maji, V.B.: Geotechnical characterization and analysis of
633 rainfall-induced 2009 landslide at Marappalam area of Nilgiris district, Tamil Nadu state, India.
634 *Landslides*, 14, 1803-1814, 2017.

635 Tang, H., Mcguire, L.A., Kean, J.W., Smith, J.B.: The impact of sediment supply on the initiation
636 and magnitude of runoff-generated debris flows. *Geophysical Research Letters*, 47,
637 e2020GL087643, 2020.

638 Thomas, M.A., Collins, B.D., Mirus, B.B.: Assessing the feasibility of satellite-based thresholds for
639 hydrologically driven landsliding. *Water Resource Research*, 55, 9006-9023, 2019.

640 Tisdall, A.: Antecedent soil moisture and its relation to infiltration. *Aust. J. Agric. Res.*, 2 (3), 342–
641 348, 1951.

642 Van Genuchten, M.: A closed form equation for predicting the hydraulic conductivity of unsaturated
643 soils. *Soil Sci. Soc. Am. J.* 44, 892–898, 1980.

644 Wei, F.Q., Hu, K.H., Zhang, J., Jiang, Y.H., Chen, J.: Determination of effective antecedent rainfall
645 for debris flow forecast based on soil moisture content observation in Jiangjia Gully, China. In:
646 DeWrachien, D., Brebbia, C.A., Lenzi, M.A., eds., *Monitoring, Simulation, Prevention and*
647 *Remediation of dense debris flows II*. WIT Transactions on Engineering Sciences, England. 13-
648 22, 2008.

649 Yan, Z.Z., Hong, Z.M.: Using the Monte Carlo method to solve integral equations using a modified
650 control variate. *Applied mathematics and computation*, 242,764-777, 2014.

651 Yang, H.J., Zhang, S.J., Hu, K.H., Wei, F.Q., Wang, K., Liu S.: Field observation of debris flow
652 activities in the initiation area of Jiangjia Gully, Yunnan Province, China, *Journal of Mountain*
653 *Science*, 19(6): 1602-1617, 2022.

654 Zeng, Q.L., Yue, Z.Q., Yang, Z.F., Zhang, X.J.: A case study of long-term field performance of
655 check-dams in mitigation of soil erosion in Jiangjia stream, China. *Environ Geol* 58:897–911,
656 2009.

657 Zhang, S.J., Xu, C.X., Wei, F.Q., Hu, K.H., Xu, H., Zhao, L.Q., Zhang, G.P.: A physics-based model
658 to derive rainfall intensity-duration threshold for debris flow. *Geomorphology*, 351, 106930, 2020.

659 Zhang, S.J., Yang, H.J., Wei, F.Q., Jiang, Y.H., Liu, D.L.: A model of debris flow forecast based on
660 the water-soil coupling mechanism. *Journal of Mountain Science*, 25, 757-763, 2014.

661 Zhang, S.J., Xia, M.Y., Li, L., Yang, H.J., Liu, D.L., Wei, F.Q.: Quantify the effect of antecedent
662 effective precipitation on rainfall intensity-duration threshold of debris flow. *Landslides*, 20,
663 1719-1730, 2023.

664 Zhao, B.R., Dai, Q., Han, D.W., Dai, H.C., Mao, J.Q., Zhuo, L.: Probabilistic thresholds for
665 landslides warning by integrating soil moisture conditions with rainfall thresholds. *Journal of*
666 *Hydrology*, 574, 276-287, 2019a.

667 Zhao, B.R., Dai, Q., Han, D., Dai, H., Mao, J., Zhuo, L., Rong, G.: Estimation of soil moisture using
668 modified antecedent precipitation index with application in landslide predictions. *Landslides* 16,
669 2381–2393, 2019b.

670 Zhu, Y.J., Shao, M.G.: Variability and pattern of surface moisture on a small-scale hillslope in
671 Liudaogou catchment on the northern Loess Plateau of China, *Geoderma*, 147, 185-191, 2008.

672 Zhuang, J.Q., Cui, P., Wang, G.H., Chen, X.Q., Iqbal, J., Guo, X.J.: Rainfall thresholds for the
673 occurrence of debris flows in Jiangjia Gully, Yunnan Province, China. *Eng. Geol.* 195, 335–346,
674 2015.