

Advancing measurements and representations of subsurface heterogeneity and dynamic processes: towards 4D hydrogeology

Thomas Hermans¹, Pascal Goderniaux², Damien Jougnot³, Jan [H. Fleckenstein](#)⁴, Philip Brunner⁵, Frédéric Nguyen⁶, Niklas Linde⁷, Johan Alexander Huisman⁸, Olivier Bour⁹, Jorge Lopez Alvis^{6,a}, Richard Hoffmann^{6,8}, Andrea Palacios^{10,b}, Anne-Karin Cooke^{11,12,c}, Álvaro Pardo-Álvarez⁵, Lara Blazevic^{3,d}, Behzad Pouladi^{9,e}, Peleg Haruzi^{8,13}, [Alejandro Fernandez Visentini](#)^{7,f}, [Guilherme E. H. Nogueira](#)⁴, [Joel Tirado-Conde](#)^{14,g}, [Majken C. Looms](#)¹⁴, Meruyert Kenshlikova⁹, Philippe Davy⁹, Tanguy Le Borgne⁹

¹ Department of Geology, Ghent University, 9000 Gent, Belgium

10 ² Department of Geology and Applied Geology, University of Mons, 7000 Mons, Belgium

³ [Sorbonne Université, CNRS, EPHE, UMR 7619 METIS, 75005 Paris, France](#)~~MR 7619 METIS, Sorbonne Université, UPMC Université Paris 06, CCNRS, EPHE, F-75005 Paris, France~~

⁴ Department of Hydrogeology, Helmholtz Centre for Environmental Research, 04318 Leipzig, Germany

⁵ Laboratory of Hydrogeological Processes, University of Neuchâtel, 2000 Neuchâtel, Switzerland

15 ⁶ Urban and Environmental Engineering, Liege University, 4000 Liege, Belgium

⁷ Institute of Earth Sciences, University of Lausanne, 1015 Lausanne, Switzerland

⁸ Agrosphere (IBG 3), Institute of Bio- and Geosciences, Forschungszentrum Jülich GmbH, 52425 Jülich, Germany

⁹ [Univ Rennes, CNRS, Géosciences Rennes, UMR 6118, 35000 Rennes, France](#)~~Géosciences Rennes, UMR 6118, Université de Rennes 1, CNRS, 35000 Rennes, France.~~

20 ¹⁰ Institute of Environmental Assessment and Water Research (IDAEA), Consejo Superior de Investigaciones Científicas (CSIC), Barcelona, 08034, Spain

¹¹ Géosciences Montpellier, University of Montpellier, CNRS, Univ. des Antilles, 34095 Montpellier, France

¹² Institut d'Optique d'Aquitaine, Muquans, 33400 Talence, France

¹³ Department of Environmental Physics and Irrigation, Agricultural Research Organization – Volcani Institute, 7505101

25 Rishon LeZion, Israel

¹⁴ [Department of Geosciences and Natural Resource Management, University of Copenhagen, 1350 Copenhagen, Denmark.](#)

^a Now at Centro de Geociencias-, Universidad Nacional Autonoma de Mexico, 76230 Querétaro, Mexico.

^b Now at Amphos 21 Consulting, 08019 Barcelona, Spain.

^c Now at Federal Institute for Geosciences and Natural Resources (BGR), 13593 Berlin, Germany

30 ^d Now at Ruden SA, 0349 Oslo, Norway

^e Now at Silixa Ltd, London, UK.

^f [Now at BRGM, 45060 Orléans Cedex 02, France](#)

^g [Now at COWI A/S, 2800 Kongens Lyngby, Denmark](#)

35 Correspondence to: Thomas Hermans (Thomas.hermans@ugent.be)

Abstract. Essentially all hydrogeological processes are strongly influenced by the subsurface spatial heterogeneity and the temporal variation of environmental conditions, hydraulic properties, and solute concentrations. This spatial and temporal variability generally leads to effective behaviors and emerging phenomena that cannot be predicted from conventional approaches based on homogeneous assumptions and models. However, it is not always clear when, why, how and at what scale the 4D (3D + time) nature of the subsurface needs to be considered in hydrogeological monitoring, modelling and applications needs to be considered when studying hydrogeological processes in order to employ adequate mechanistic models or perform upscaling. The scale at which a hydrogeological system should be characterized in terms of its spatial heterogeneity and temporal dynamics depends on the studied process(es); and it is not always necessary to consider the full complexity. In this paper, we ~~identify~~ discuss the interest and potential for the monitoring and characterization of spatial and temporal variability, including 4D imaging, in a series of hydrogeological processes ~~for which an approach coupling the monitoring of spatial and temporal variability, including 4D imaging, is often necessary~~ recommended: (1) groundwater fluxes, that control (2) solute transport, ~~mixing~~ and reaction processes, (3) vadose zone dynamics, and (4) surface-subsurface water interaction occurring at the interface between different subsurface compartments. We first identify the main challenges related to the coupling of spatial and temporal fluctuations for these processes. ~~WThen, we then~~ highlight some recent innovations that have led to significant breakthroughs in high resolution space-time imaging and modelling the characterization, monitoring and modelling of these is domain. We finally discuss how spatial and temporal fluctuations. We finally propose a classification of processes and applications at different scales according to their need and potential for high-resolution space-time imaging. affect our ability to accurately model them and predict their behavior. We thus advocate a more systematic characterization of the dynamic and three-dimensional nature of the subsurface for a series of critical subsurface processes and emerging applications. ~~and~~ This calls for the validation of 4D imaging techniques at highly instrumented observatories, and the ~~the~~ harmonization ~~of of~~ open databases to share store hydrogeological data sets in their four-dimensional components, ~~for answering emerging scientific questions and addressing key societal issues.~~

60 **Short summary.** Although invisible, groundwater plays an essential role for the society as a source of drinking water or for ecosystems by providing baseflow to rivers, but is also facing important challenges in term of contaminations. Characterizing groundwater reservoirs with their spatial heterogeneity and their temporal evolution is therefore crucial for their sustainable management. In this paper, we review some important challenges and recent innovations in imaging and modelling the groundwater reservoirs 4D nature of the hydrogeological systems.

While the surface components of continental water, such as streams, lakes and glaciers, are a very familiar part of our landscape, the vast majority of continental water resources resides and flows in the subsurface, and is thus generally inaccessible to direct observation (McDonnell, 2017). Growing societal needs imply that subsurface environments, which form part of the critical zone of the Earth (Brantley et al., 2007; Fan et al., 2019), are increasingly subject to pressure and multiple (possibly competing) uses for water resources such as groundwater abstraction, artificial recharge and storage (Dillon et al., 2019; Russo and Lall, 2017; Aeschbach-Hertig and Gleeson, 2012), nuclear waste storage (e.g., Ewing, 2015, Butler, 2010), geothermal energy (Rivera et al., 2017; Fleuchaus et al., 2018; Lu, 2018), oil and gas extraction (e.g., Wang et al., 2014) and climate change mitigation such as energy storage (Arbabzadeh et al., 2019) and CO₂ sequestration (Hamza et al., 2021, Kumar et al., 2020) while being threatened by anthropogenic contamination (e.g., Riedel et al., 2020). As a result, subsurface systems are experiencing profound modifications that affect their basic environmental functions and ecosystem services (Erostate et al., 2020; Fattorini et al., 2020; Luijendijk et al., 2020). These modifications include, both at the local and the catchment scales, water level depletion (Jasechko et al., 2021), which affects baseflow of many rivers and associated ecosystem services (Conant et al., 2019), a growing input of chemicals and pathogens, which threaten water quality (e.g., Szymczycha et al., 2020), seawater intrusion (Werner et al., 2013) and soil salinization (Litalien and Zeeb, 2020; Singh, 2021) threatening soil- and water resources as well as food security in many arid and semi-arid regions of the world, and massive fluid injections at depth related to CO₂ sequestration or gas extraction, which may lead to increased seismicity (Rathnaweera et al., 2020; Schultz et al., 2020; Keranen and Weingarten, 2018).

The last decade has seen great advances in stochastic subsurface hydrology (e.g., Scheidt et al., 2018), microscale imaging (e.g., Gouze et al. 2008, Blunt et al. 2013, Heyman et al. 2020), and geophysical characterization (e.g., Binley et al., 2015; Singha et al., 2015). Although geological heterogeneity has been long recognized, these advances have made it even more clear that the subsurface is highly heterogeneous at multiple scales and that this heterogeneity substantially controls many flow, transport and biochemical processes (e.g., Hartmann et al., 2017; Comte et al., 2019; Zamrsky et al., 2020). Recent efforts have led to an improved ability for monitoring surface-water dynamics or characterizing the state of aquatic systems, but this has not been matched by a significant increase in our ability to quantify the dynamics of fluxes and processes in the subsurface (e.g., Schilling et al., 2018). A wide gap between common modelling approaches (e.g., homogeneous or multi-Gaussian representations of parameters, steady state or transient simulations, upscaling approaches) and field reality prevails. On the one hand, data sets often have a very limited 3D spatial extent and are characterized by a low sampling density, preventing a full description of the complex nature of the aquifer (e.g., Xu and Valocchi, 2015). On the other hand, studies concerning the temporal dynamics of hydrological processes and structures are generally based on point data typically acquired in wells ~~in~~ hydrogeology, potentially missing the underlying spatial variability (e.g., Johnson et al., 2012).

The persistent observation gap between data points ~~results in a lack of knowledge and~~ contributes significantly to the current lack of understanding of subsurface processes and our ~~(in)~~ability to accurately predict the evolution of subsurface systems.

~~This deficiency in the characterization of aquifers limits our ability to answer critical scientific questions of significant societal and industrial impacts such as. For example, the magnitude, spatial distribution and temporal dynamics of fluxes between subsurface and surface compartments of the Earth are relevant for the management of water quantity, quality and ecology at the interface between the surface and the subsurface (Fleckenstein et al., 2006, 2010; Brunner et al., 2017; Conant et al., 2019).~~ the fate of contaminant. Similarly, the dispersion and residence time distribution of dissolved chemical species in heterogeneous porous and fractured media, as well as the coupling between fluid mixing and reactions and the localization of hotspots of subsurface biogeochemical reactions, are key aspects to study the fate of contaminations through mixing, reactions and the development of biogeochemical hotspots (e.g., Wallis et al., 2020; Pannecoucke et al., 2020; Robinson and Hasenmueller, 2017; Bailey, 2017), or understand the contribution of subsurface processes to global cycles of carbon (Zhang and Planavsky, 2020; Liu et al., 2014) and nitrogen (Marzadi et al., 2012) (Figure 1). ~~The above mentioned processes are both highly dynamical and strongly influenced by small-scale and across-scale heterogeneity (e.g., Salehikhoo et al., 2013, Dentz et al., 2011). In particular, the location and reactivity of biogeochemical hot spots (e.g. McClain et al. 2003), which are thought to have a disproportionate influence on macroscale critical zone processes relative to their size, may be largely influence by spatial heterogeneity coupled to temporal fluctuations (e.g., Rolle and Le Borgne 2019).~~ The potential of a characterization for coupled spatio-temporal monitoring of parameters and state variables and their temporal evolution, including 4D imaging, to understand these processes remains largely unexplored. This temporal component should not only include the evolution of state variables under transient conditions, but also the evolution of system properties because of coupled processes such as hydromechanical effects impacting the pore space or fracture apertures (Davy et al., 2018), ~~colmatation clogging~~ and erosion processes in streambeds (Partington et al., 2017) or reactive transport inducing changes in the pore space (Izumoto et al., 2020). A grand challenge of subsurface imaging methods for dynamic hydrogeological processes (Figure 1) is to deal with systems characterized by pronounced structure and process heterogeneity, including preferential flow paths, evolving properties or geometry, unsaturated flow processes, fluctuating redox conditions, and multifunctional microbial communities. Recent breakthroughs in hydrogeophysical imaging techniques (e.g., Binley et al., 2015; Singha et al., 2015) and the emergence of interdisciplinary approaches combining new sensors such as fiber optics (Bense et al., 2016; Zhan, 2020), new experimental methodologies like ambient seismic noise correlation (Garambois et al., 2019) and coupled modelling techniques (e.g., Hinnell et al., 2010; Jardani et al., 2013; Linde and Doetsch, 2016) may profoundly change our vision and representation of the dynamics of processes that take place in these environments (Binley et al., 2015; St. Clair et al., 2015). However, monitoring and characterizing dynamical fluxes, transport, reactions and hydromechanical processes that evolve spatially in 3D with geophysical imaging is still in its infancy in environmental sciences and engineering. The efficiency of those new methods and the full complexity that emerges from their coupling can only be revealed through in-situ exploration with interdisciplinary approaches. In that sense, field observatories and case studies constitute a key component of the current research effort (e.g., Folch et al., 2020, Palacios et al., 2020, [Table 2.B.6](#)).

~~Although heterogeneity influences all the processes occurring in the subsurface, an exhaustive characterization of the subsurface is not always necessary and strongly depends on the objective of the studies. Large-scale water balance approaches,~~

average advection velocity or aquifer recharge through the vadose zone might be approximated with scarce hydrogeological data. However, the integration of recent advances in imagining the spatial and temporal variability in hydrological model is still in its early stage and has a huge potential to improve the mechanistic understanding of hydrological processes, the upscaling of models and the assessment of model simplifications. The objective of this opinion review paper is, therefore, to identify and discuss when, why, and for which processes and applications the characterization of dynamic hydrogeological processes is crucial. Although heterogeneity influences all the processes occurring in the subsurface, an exhaustive characterization of the subsurface is not always necessary and strongly depends on the objective of the studies, the scale and the available budget. We identify three categories of processes according to their need for coupled temporal and spatial monitoring, including 4D imaging (see Table 1 and Figure 8): –A. Processes that require high-resolution space-time imaging to develop accurate upscaled models applicable to less instrumented sites –the mechanistic understanding of hydrological processes for which the integration of recent advances in imagining the spatial and temporal variability brings a potential for improvement. B. applications for which spatial and temporal monitoring is critical and desirable at the local scale, such as the monitoring of contamination, the assessment of soil moisture for precision agriculture, or induced seismicity. C. applications for which limited hydrogeological data are often sufficient for a first approximation –such as large scale water balance, average transit time or aquifer recharge. More specifically, We discuss the potential and value of exploring and monitoring high resolution space-time imaging in hydrogeology, including 4D imaging, for understanding monitoring and modelling groundwater fluxes, transport, mixing and reactions processes, soil moisture dynamics in the vadose zone and surface-subsurface water interactions (Figure 1). Based on a non-exhaustive overview of recent advances, we identify key scientific challenges and their relation to the heterogeneous and dynamic nature of the subsurface for each of the above-mentioned processes. We then highlight some recent breakthroughs which allowed to advance our understanding of these processes. We also discuss the feasibility, advances and challenges of numerical modelling of the identified processes in terms of 4D complexity. We finally highlight as well as the important central role of instrumented field observatories and corresponding case studies to tackle the scientific challenges and evaluate the performance and scope of recent innovations.

2 Key processes in hydrogeology and their 4D nature

In this section, we highlight hydrogeological processes at different scales for which the considerations of coupled spatial heterogeneity and temporal dynamics are important, present the main challenges related to the representation and inference of spatial and temporal variability and point towards a few recent innovations that could help to address these challenges in the future (Figure 1).

2.1 Groundwater fluxes

Inferring and modeling groundwater Darcy fluxes and fluid velocities is crucial in most hydrogeological processes and related applications, both for quantitative water quantity (e.g., water storage, groundwater discharge, residence transit time

[distribution](#)) and [qualitative quality](#) (e.g., contaminant transport, reaction and mixing processes, [see also section 2.3](#)) purposes ([Figure 1](#)). Pore-scale advection flow, along with the other transport processes and the influence of the macro-scale geological heterogeneity, controls propagation and spreading of natural or contaminant solutes, from fast transfers to late time tailing s (e.g. Dentz et al. 2011; Hoffmann et al., 2020; [Table 2.E.2](#); Kang et al., 2015). In the context of risk assessment, measuring natural solutes or contaminant concentrations may be of limited value if not supported by quantitative flux rates allowing to estimate solute mass transfers (Brouyère et al., 2008). Groundwater fluxes drive mixing processes prevailing at aquifer interfaces such as subsurface-surface interactions in hyporheic zones ([see also section 2.4](#)) or transition zones along coastal saltwater intrusion (e.g. Werner et al. 2013, Hester et al. 2017, [Nogueira et al., 2019](#)). They also influence hydrogeochemical and biogeochemical reactions by transporting reactants, such as nutrients, to these interfaces. They impact the feasibility of storage applications including the injection and recovery of heat or CO₂ in the subsurface (Niemi et al. 2017, Fleuchaus et al. 2018) and control [residence-transit](#) times distributions across watersheds (Goderniaux et al., 2013).

The range of variation of expected groundwater fluxes may be very large, making them difficult to image, with their spatial and temporal variation. For decades, the basic approach consisted in first measuring the hydraulic conductivity and then predict fluxes, based on the hydraulic gradient. This approach however presents the serious disadvantage to average local variations and offers a limited understanding of the groundwater flux spatial distribution in heterogeneous media (Palmer, 1993; Brouyère et al., 2008; Jamin et al., 2015). In addition, many subsurface processes are time-dependent and exhibit an inherent periodicity. If deep systems are not expected to vary rapidly, shallow aquifers can exhibit fluctuations ranging from lower (e.g. multi-annual or seasonal recharge fluctuations) to higher frequencies (e.g. tide dependent saltwater intrusion, aquifer exploitation or artificial storage applications, [reaction to rainfall](#)). The accurate quantification of groundwater flux rates including their spatial distribution and transient conditions is, therefore, needed to understand and manage these processes. This should be performed at the relevant scale(s), with the appropriate resolution, in adequation with the objectives of the study and the geological context (Jimenez-Martinez et al., 2013).

Recent research efforts have focused on the development of direct or indirect methods allowing for a more accurate assessment of groundwater fluxes, including their amplitude, spatial distribution and temporal dynamics, with application [s](#) in highly heterogeneous media. ~~As groundwater fluxes influence many processes, Specific approaches, based on thermal methods for instance, have been developed for certain contexts, such as surface-subsurface interactions (section 2.4), while approaches based on solute transport (e.g., tracer experiments), are allowing only indirect quantification of the fluxes (Popp et al., 2021, see section 2.2)~~ ~~some approaches, discussed in the next sections, have been developed for specific contexts, such as surface-subsurface interactions or solute transport, allowing indirect quantification of the fluxes, for example through tracer experiments (Popp et al., 2021).~~ Some ~~o~~Other techniques are more general and available to directly and accurately measure local groundwater fluxes (e.g., Jamin et al., 2015; Le Borgne et al., 2006–; Brouyère et al., 2008–; Burnett et al., 2006). For instance, point measurements of [Darcy-Darcy](#) fluxes are classically done from dilution methods (Drost et al., 1968; Klotz et al., 1980; Pitrak et al., 2007; Novakowski et al., 2006; Jamin et al., 2015). Well-points velocity probes have been also recently developed (Labaky et al., 2009; Devlin, 2020) to provide promising and complementary velocity measurements although

ranges of measurements are still limited. A key aspect of some recent approaches is to allow the monitoring of groundwater fluxes dynamics (Jamin and Brouyère, 2018).

Important challenges, also depending on the media type, however, remain. The number of available methods for direct measurement is limited and most methods are suited for porous media rather than fractured aquifers where fluxes are expected to show stronger spatial variations (Pouladi et al., 2021). Current methods are still deficient in providing ~~full 3D~~ high-resolution ~~3D~~ datasets as they must be performed in wells. Current geophysical imaging techniques are still unable to directly estimate fluxes, as they are mostly based on the contrast in water properties induced through tracers. Nevertheless, very promising results were obtained ~~through the combination~~ combining of ambient noise surface wave tomography (~~ANSWT~~), and self-potential (SP) measurements to image the ~~complex hydrogeology~~ hydrogeological structure and associated groundwater flow paths ~~at a coastal site~~ (Grobbe et al., 2021). ~~The joint interpretation of the SP and seismic data permits to show that groundwater flow occurs in the identified paleo-channels at the erosional surface of the basaltic bedrock (Grobbe et al., 2021).~~ Despite these improvements, monitoring the dynamics of fluxes remains resource expensive. Accurate measurements, which often imply complex experimental needs and designs, must be repeated regularly, with an adequate time resolution, for example to understand ~~ing~~ cyclic process evolution. Passive flux methods (e.g., Hatfield et al., 2004) integrate flux measurements over specific periods, providing mean representative value while avoiding repetitive field operations, but do not capture the dynamics.

Fiber Optic Distributed Temperature Sensing (DTS) allows for the measurement of temperature with high spatial and temporal resolution over large distances from a few ~~hundreds~~-m up to several km, using buried or borehole cables (Selker et al., 2006; Bense et al., 2016; Simon et al., 2020, see ~~table 1~~ Table 2.C.2). By estimating the rates of temperature change along the cable, this kind of system allows an indirect estimation of groundwater fluxes intercepting the cable, provided that conditions are changing fast enough and that the temperature change is large enough to be detected (~~Read et al., (2013),~~ ~~for example resolved groundwater fluxes in fractured granite, by combining DTS measurements and hot water injections in a borehole.~~ Long-term changes can also be detected by using DTS systems as permanent monitoring tools (Susanto et al., 2017; McCobb et al., 2018). A new generation of active fiber-optics with heated cables designed for hydrogeological investigations is currently being developed and is a promising approach for inferring borehole or in-situ groundwater fluxes (Read et al., 2014; des Tombes et al., 2019; Maldaner et al., 2019; Simon et al., 2021; Del Val et al., 2021). The thermal response during the active heating of the cable and the subsequent cooling period is monitored ~~as it depends strongly on the water fluxes intercepting the cable,~~ allowing an accurate groundwater flux assessment (Simon et al., 2021). Although challenges still remain to deploy such set-ups on the field, possible DTS applications extend to various domains, including 3D hydraulic tomography (Pouladi et al., 2021) or groundwater-surface water interactions (see section 2.4).

In summary, ~~The development of innovative in-situ methods to characterize the spatial and temporal variability of groundwater flow opens a range of new opportunities for understanding, modelling and monitoring hydrogeological systems. These advances may provide much more accurate estimation of subsurface velocity statistics in space and time in highly instrumented site to establish upscaled transport models, for porous and fracture media, at the decameter scale that capture~~

~~these dynamics fluxes is an important element, unravelling the 4D distributions of fluxes remains a major challenge in hydrogeology for process understanding or environment characterization. the spatial distribution and dynamics of fluxes constitute a key component to many hydrogeological processes but are still poorly resolved. In particular, imaging fluxes at high resolution, in particular for characterizing macro-dispersion at the decameter scale remains a huge challenge (see next section and table 1.A and Figure 8). In critical applications such as subsurface energy (thermal affected zone, induced seismicity related to fluid injection) or waste storage, these novel methods will likely be increasingly used to reduce the risks involved. Spatially distributed fluxes measurements are also needed to better understand transit times distribution from the local to the catchment scale (table 1.B and Figure 8). Finally, in more standard hydrogeological applications, such as However, detailed fluxes measurements as well as heterogeneity characterization do not seem necessary for water balance studies, aquifer recharge or average residence time estimation, such a level of characterization is generally not required (table 1.C and Figure 8). Although integrating 4D aspects in flux assessment might not be needed in larger scale water balance studies, they still influence residence time at the catchment scale. The development of innovative in-situ methods to characterize fluxes is an important element, unravelling the 4D distributions of fluxes remain a major challenge in hydrogeology for process understanding or environment characterization.~~

235

240

245 2.2 Transport, mixing and reaction

Three-dimensional heterogeneity and temporal fluctuations of fluxes have a first-order impact on transport and reaction processes (e.g. Dentz et al. 2011, Rolle and Le Borgne 2019, Valocchi et al. 2019, [Figure 1](#)). The inherent heterogeneity of subsurface environments leads to ~~strong dispersion dynamics~~, which do not follow the conventional ~~Fickian macrodispersion framework based on Fickian dispersion dispersion framework~~ (e.g. Berkowitz et al. 2006, Neuman and Tartakovsky 2009). Furthermore, mixing ~~dynamics rates in 3D systems~~ can be fundamentally different than predicted from 2D or steady representations of the subsurface (Lester et al. 2013). At the pore scale, recent 3D imaging techniques (Figure 2) have shown that 3D flow topologies driven by pore scale flow patterns lead to chaotic flows that strongly enhance mixing rates (Heyman et al. 2020, Souzy et al. 2020). At the Darcy scale, anisotropic permeability fields can generate helical flow that play a similar role (Ye et al. 2015). In fractured media, intersection of fractures with fluids of different chemical compositions can create microbial hot spots with intermittent activity (Bochet et al. 2020). In coastal aquifers, mixing between freshwater and saline water trigger reactions, including rock dissolution that leads to increased permeability and karst formation, which develop a hot spots due to medium heterogeneity (De Vriendt et al., 2020). Modelling and laboratory investigations have shown that these transport and reaction rates can be further altered by temporal fluctuations in head levels (Pool and Dentz, 2018) and variable water content (Jiménez-Martínez et al., 2017). Modelling studies have provided evidence that heterogeneity and temporal fluctuations can exert a strong control on biogeochemical reaction rates (Li et al., 2010; Sanz-Prat et al., 2016). However, there is increasing evidence that reactive transport processes are not well captured by the macrodispersion framework (Gramling et al. 2002, de Anna et al. 2014). Yet, in the absence of an alternative upscaling framework, ~~the macrodispersion model~~ is still the main reference for field applications.

250

255

260

265 Characterizing and imaging transport and reaction dynamics in the field is a critical challenge for a range of fundamental and applied questions, such as designing efficient remediation strategies for contaminated sites (Kitanidis and McCarty, 2012) or characterizing transport and reaction dynamics in mixing zones (Rolle and Le Borgne, 2019). ~~Such reactive hot spots, that concentrate a disproportionate amount of reaction relative to their size,~~ tend to develop at the interfaces between surface and subsurface compartments (McClain et al. 2003), which include ~~s~~ the vadose zone (Jimenez-Martinez et al., 2017, see section 2.3), the hyporheic zone (Hester et al., 2017, [Nogueira et al., 2022](#), see section 2.4) or the groundwater-seawater interface
270 (Pool and Dentz, 2018; [Duque et al., 2019](#)).

Classical artificial tracer tests are commonly used to estimate solute transport properties and related parameters. Their use in highly heterogeneous media is, however, challenging due to the difficulty of positioning a limited amount of recovering points leading to low mass recovery (Kemna et al., 2002; Sanford et al., 2006). When interpreting or inverting ~~the tracer~~ breakthrough data, with little information on the spatial heterogeneity, the range of possible interpretation in terms of parameter values can
275 be quite large or misleading (e.g. [Hoffmann et al., 2019, Table 2.A.1](#)). Combining tracer test recovery with other monitoring methods, such as geophysics (e.g., [Robert et al., 2012](#); [Hermans et al., 2015b, Table 2.A.1](#)), and model inversion provides complementary information (e.g., ~~Robert et al., 2012~~) that can narrow down the uncertainty in the interpretation. Combining multiple tracers ([Klepikova et al., 2016](#); [Hoffmann et al., 2019, 2021a,b, Figure 3, Table 2.A.1, and 2.E](#)~~Table 2.E~~) or tracers with flux measurements such as seepage meters ([Tirado-Conde et al., 2019, Table 2.C.7](#); [Duque et al., 2019](#)) can also provide
280 more constraints on tracer test interpretation, ~~exchanges fluxes estimation or heterogeneity~~. (~~Hoffmann et al., 2019, 2021a,b, table 1.E~~). ~~Tirado-Conde et al. (2019) combined 180 seepage meter measurements with heat used as a tracer in 30 locations, to study and characterize surface water-groundwater interactions and saltwater intrusion around a coastal lagoon inlet. Hoffmann et al. (2019), Klepikova et al. (2016) combined classical tracers with heat injection, taking advantage of heat conduction processes in rocks and sediments to better image the heterogeneity (Figure 3). They coupled these different tracer experiments with electrical imaging (ERT) and fiber optics (Hermans et al., 2015b, table 1.A.1) to image highly heterogeneous alluvial deposits with high resolution (3), in the context of experimental pumping operations performed at short time scale.~~
285 DTS fiber optics techniques provide the opportunity for spatial monitoring of thermal tracers (de La Bernardie et al., 2018; Klepikova et al., 2016, see also section 2.1 and ~~table 1~~[Table 2.C.3 and 1.C.7](#)). The combination of tracer experiments under different configurations (convergent, push pull, ~~etc.,...~~) provides new constraints on transport models, ~~highlighting the possibility providing the opportunity~~ to capture the effect of complex 3D fracture networks architectures in effective transport models (Kang et al., 2015; Guilhéneuf et al., 2017).
290

New mobile mass spectrometers have opened up new opportunities to use dissolved gas as tracers and measure them continuously in the field (Brennwald et al., 2016; Chatton et al., 2017; Popp et al., 2021). Dissolved gases, such as Helium, ~~or~~ Argon ~~and Xenon~~, are conservative tracers with larger diffusivity compared to solute tracers, thus, allowing the exploration of
295 diffusive processes such as fracture-matrix or mobile-immobile water interactions (~~Hoffmann et al. (2020), combined dye tracers with dissolved gases (Helium, Argon, Xenon) to study preferential flowpaths and mobile-immobile water effects within~~

~~a dual porous/fractured rock chalk aquifer (table 4Table 2.E.2).~~ Reactive tracers have offered new methods for characterizing transport dynamics, including hyporheic exchange (Knapp et al., 2017, see also section 2.4).

The use of time-lapse geophysical techniques provides a promising avenue to characterize the spatial distribution and temporal evolution of transport and reaction processes, at scale up to a few hundred meters (e.g. Binley et al. 2015, ~~table 4Table 2~~). Extensive geophysical imaging of transport processes has mainly been performed using Electrical Resistivity Tomography (ERT) and Ground Penetrating Radar (GPR) even if immediate successes have often been hampered by issues of mass recovery due to unresolved concentration gradients (Slater et al., 2002; Singha and Gorelick, 2005; Müller et al., 2010; Doetsch et al., 2012; Dorn et al., 2012b, Fernandez-Visentini et al. 2020). A major challenge is, thus, to upscale the non-stationary and non-ergodic solute concentration fields as well as the macroscopic heterogeneity unresolved by geophysics (Gueting et al., 2015, 2017, ~~table 4Table 2.D.2~~) to derive relevant petrophysical relationships. Accounting for realistic heterogeneity patterns in inversion remains difficult (both flow and transport) and upscaling is not straightforward (Singha et al., 2015). In smoothness-constrained tomography inversion, there is usually underprediction of magnitudes and overprediction of target sizes (Day-Lewis et al., 2006). Overcoming this challenge requires advanced hydrogeophysical imaging (e.g., Hermans et al., 2016b, 2018, Oware et al., 2019), adapted regularization consistent with the studied process (e.g., Karaoulis et al., 2014; Hermans et al., 2016a, Nguyen et al., 2016; Lopez-Alvis et al., 2021), geostatistical post-processing (Moyssey et al., 2005; Nussbaumer et al. 2019) or coupled inversion (e.g., Hinnel et al. 2010). Recent modelling results suggest that key geostatistical properties of permeability fields may be inferred from time-lapse ERT imaging (Fernandez Visentini et al., 2020). New geophysically sensitive tracers, allowing density matching with the resident fluid (Shakas et al., 2017, ~~table 4Table 2.B.3~~), provide images of tracer pathways that are not influenced by density effects, ~~a key limitation of geophysical techniques based on dense saline tracers~~. Theoretical work has suggested that tracers that change their electrical conductivity when reacting could be imaged by electrical methods, providing new opportunities to characterize mixing processes in situ (Ghosh et al., 2018). This idea remains to be tested in the laboratory and field.

Geophysical techniques that have the potential to map and monitor reactive processes, such as Spectral Induced Polarization (SIP), which consists in measuring the phase shift of an alternating electrical signal occurring because of polarization phenomena in the electrical double layer, by mineral precipitation (Leroy et al., 2017), or by the activity of microorganisms (Kessouri et al., 2019) are highly sensitive to pore scale processes and concentration distributions (Izumoto et al., 2020, 2022), which make their interpretation challenging but potentially very rewarding. The coupling of geophysical techniques with pore scale imaging techniques, including micro and millifluidics (Jougnot et al., 2018; Fernandez Visentini et al., 2021, Izumoto et al., 2022) and X-ray computed tomography (Johansson et al., 2019;), represents a new avenue of research to understand and quantify the geophysical signature of unresolved pore scale processes (Jougnot et al., 2018; Fernandez Visentini et al., 2021, Izumoto et al., 2022).

Geophysical methods are ~~also thus~~ increasingly used for mapping biogeochemical processes (Atekwana and Slater, 2009; Knight et al., 2010). Self-potential (SP) signals ~~have, under specific conditions, been shown to be~~ sensitive to redox conditions in contaminated groundwater (Naudet et al., 2003; Revil et al., 2009; Arora et al., 2007). Laboratory studies have

shown the correlation between SIP and bacteria activity using column experiments (Davis et al., 2006; Abdel Aal et al., 2010; Zhang et al., 2014) and the SIP method has been applied to detect biogeochemical reactions or root activities in the field (Wainwright et al., 2016; Flores Orozco et al., 2012; Ehosioko et al., 2020). However, current interpretations are largely qualitative or empirical through correlation. It remains challenging to mechanistically relate the SIP signal to biological and physiological processes or simply to the biomass itself. For many applications, the underlying mechanisms of the observed polarization are still subject of active research and debate (see e.g., Leroy et al. 2017, Ehosioko et al., 2020), while field applications remain limited (Flores Orozco et al., 2021).

The coupling of heterogeneity, transport and reaction often lead to scale effects influencing effective reactive transport parameters (Dentz et al., 2011, Salehikhoo et al., 2013, ~~Dentz et al., 2011~~), ~~making leading to a major~~ upscaling a major challenge in transport characterization and reactive transport modelling at the catchment scale (Li et al., 2017). Improved time and space resolution of geophysical and inversion techniques, and the development of systems capable of surveying large areas repeatedly with multiple hydrogeophysical methods open new perspectives for mapping and monitoring these dynamics in the field (Folch et al., 2020; Palacios et al., 2020, Table 2.B.6). -As discussed above, hydrogeophysical imaging of transport and reaction processes is very attractive, but it requires upscaling the effects of sub-scale transport dynamics to the scales resolved by geophysical techniques (Fernandez Visentini et al., 2020). Processes occurring at unresolved scales require imaging by combining multiple methods across scales, different tracers, and use of integrating data with geostatistics, modeling and inversion (Linde and Doetsch, 2016). Similar challenges occur when imaging the water content distribution in the vadose zone as discussed in section 2.3.

~~Recent innovations have demonstrated promising research avenues for overcoming the above-mentioned challenges. Recent modelling and field work have provided a new understanding of the role of heterogeneity and temporal fluctuations in the development of mixing and reaction hot spots and hot moments. In fractured rocks, three-dimensional fracture patterns trigger localized mixing of fluids of different chemical compositions, leading to highly reactive hot spots at fracture intersections that develop intermittently depending on hydrological fluctuations (Bochet et al., 2020). In coastal aquifers, mixing between freshwater and saline water trigger reactions, including rock dissolution that leads to increased permeability and karst formation, which develop as hot spots due to medium heterogeneity (De Vriendt et al., 2020). Improved time and space resolution of geophysical and inversion techniques, inverse modeling advances to monitor time-dependent processes, and the development of systems capable of surveying large areas repeatedly with multiple hydrogeophysical methods open new perspectives for mapping and monitoring these dynamics in the field (Folch et al., 2020; Palacios et al., 2020, table 1Table 2.B.6).~~

In summary, there is increasing evidence that conventional sampling monitoring techniques and models are not able to capture mechanisms underlying the 3D heterogeneity and temporal fluctuations playing a key role in controlling transport and reaction processes. 4D imaging of transport and reaction at laboratory and field scale is critical to define new effective models able to upscale these dynamics and predict them in less instrumented sites (table 1.A and Figure 8). Furthermore, recent Laboratory experiments identifying tracer behaviors at the pore scale and linking them to upscaling properties such as geophysical signal

365 ~~will help to enable the development of new mechanistic models that effectively capture these dynamics and allow for accurate~~
~~upscaling approaches. Applied at the field scale, these Recent recent~~ advances ~~combined within~~ 4D imaging ~~discussed here~~
will open new opportunities for ~~the exploration of transport and reaction processes from lab to field scales, which monitoring~~
~~the fate of contaminants when risk management requires it (e.g. contamination remediation and monitoring, nuclear waste~~
~~disposal storage, table 1.B and Figure 8). Current monitoring techniques and models may be sufficient only in applications~~
370 ~~where accurate predictions of transport dynamics are less critical (table 1.C and Figure 8). while it will remain unnecessary~~
~~for lower impact activities (e.g. natural attenuation of soil contamination)~~ will help to enable the development of new
~~mechanistic models that effectively capture these dynamics and allow for accurate upscaling approaches.~~

2.3 Water content dynamics in the vadose zone

The vadose or unsaturated zone is the upper part of the critical zone. The distribution of fluid phases and their evolution with
375 time makes it a very complex media, where root systems and soil micro-organisms further complexify this dynamic
environment (Figure 1). Understanding, monitoring and predicting the quantity (i.e. water content) and movement (i.e., water
flow) of water are needed to address water quality and availability issues (e.g., Vereecken et al., 2015). Vadose zone hydrology
usually relies on punctual measurements of physical variables with established sensors: TDR (Time-Domain Reflectometry,
to infer the water content from dielectric permittivity) or tensiometers (to determine the matric potential). Vadose zone
380 hydrology is still too often viewed by hydrogeologists as a vertical 1D transit compartment with homogeneous sources
(rainwater infiltration) and sinks (evaporation or evapotranspiration) on the way to the aquifer. If such approach might be
sufficient to estimate average aquifer recharge rate, punctual measurements and 1D modelling approaches provide limited
information for the characterization of this strongly 3D environment and its dynamics ~~and; thus it is not sufficient for~~
~~applications such as precision agriculture~~. The varying water content (in time and space) and biological interactions (e.g. with
385 the roots) are adding a layer of complexity compared to the saturated zone, making its spatial and dynamical characterization
even more challenging.

While geophysical methods can provide fast and integrated measurements to characterize the spatial heterogeneity of the
vadose zone and imaging the water content distribution (within the limitation of their resolution: e.g., ~~Daily et al. 1992,~~ Day-
Lewis et al. 2005), the quantifications of dynamic processes related to water flow and (reactive) transport still remain an
390 important challenge.

In vadose zone hydrogeophysics, the most promising approaches to tackle these challenges rely on using multiple methods
and integrating the measured data in 4D numerical simulations with joint inversion strategies together with appropriate
petrophysical knowledge (e.g., Hubbard and Linde, 2011, ~~table 1~~Table 2). Surface-based and cross-borehole imaging of the
water content in the vadose zone through measurements of the electrical conductivity or dielectric permittivity distribution is
395 well established (e.g., Carrière et al., 2015, 2022, ~~table 1~~Table 2.B.5). The electrical conductivity can be obtained using low-
frequency electrical and electromagnetic methods such as Electrical Resistivity Tomography and Induced Polarization (e.g.,
Kemna et al., 2012; Revil et al., 2012). Higher frequency methods such as the Time Domain or Frequency Domain

Electromagnetics can also be employed from the surface (e.g., Pelerin, 2002) or the air (Auken et al., 2020) allowing to cover large areas in a limited amount of time, but show generally a poor vertical resolution at the scale of the vadose zone. Electrical and electromagnetic methods are well established in static conditions but also in monitoring applications (e.g., Singha et al. 2015). The main limitation of these methods is the ~~downside of their integrative nature: a limited resolution that masks~~ heterogeneities and can mislead quantitative estimation of water content or solute concentration using petrophysical relationships established in the laboratory (Day-Lewis et al., 2005; Jougnot et al., 2018) as already discussed in section 2.2. Combining several methods (e.g., Blazevic et al., 2020, ~~table 4Table 2.B.1~~) and improving the petrophysical-based approaches (e.g., Day-Lewis et al., 2017) is needed to move towards a more quantitative use of electrical and electromagnetic methods.

Ground-Penetrating Radar (GPR) is the most developed geophysical method to obtain the water content at high spatio-temporal resolution through the dielectric permittivity (e.g., Huisman et al., 2003, Roth et al. 1990; Klotzsche et al., 2018; Looms et al., 2008). Time-lapse studies using GPR to monitor water infiltration can provide insights about the hydrodynamic (e.g., Léger et al., 2014; Klotzsche et al., 2019a) and transport properties (e.g., Haarder et al. 2015) of the vadose zone, ~~and reveal-~~ ~~Commonly, geophysical studies of vadose zone processes use 1D approximations although~~ the 3D nature of ~~the heterogeneous vadose zone can obviously result in lateral flow processes, including lateral flow~~ (Scholer et al., 2012).

Nuclear Magnetic Resonance (NMR) ~~allows to obtain a signal that is~~ ~~directly related sensitive~~ to the quantity of water in the subsurface. It is based on the resonance of the magnetic moment of the protons from water molecules. NMR can be used from the surface or boreholes to infer the water content in the vadose zone (e.g., Schmidt and Rempe, 2020). Recent works have also shown its value for monitoring the water dynamics through time-lapse measurements (e.g., Mazzili et al. 2020, Lesparre et al. 2020, ~~Table 2.C.1~~).

From established P-wave velocity tomography (e.g., Bradford, 2002) to more recent imaging of surface wave velocities and Poisson ratios (e.g., Pasquet et al., 2015, ~~table 4Table 2.B.4~~), active seismic methods are developing toward a much more quantitative characterization of the water content distribution (e.g., Pride, 2005). Surface waves appear promising for monitoring of water content dynamics ~~in the vadose zone~~ (Dangeard et al., 2018, ~~table 4Table 2.B.4~~) and combining time-lapse imaging of seismic tomography and ERT will allow providing a more quantitative imaging (Blazevic et al., 2020, ~~Figure 4 table 4Table 2.B.1~~). ~~Figure 4Figure a shows the acquisition set up used by Blazevic et al. (2020) to jointly monitor the infiltration of water in a delimited area above a pit instrumented with TDR (Fig. ure 4Figure b). Figure 4 Figure c and Figure 4Figure d show the developments of the relative changes in ERT and seismic inversions results during the infiltration along the North-South line, respectively. One can see the preferential water flow from North to South, indicating lateral flow in the vadose zone.~~ This use of complementary methods, in terms of resolution and sensitivity to properties (electrical conductivity and mechanical properties), opens up new perspective such as joint inversion (e.g., Doetsch et al., 2010) and petrophysical-based inversion (e.g., Wagner et al., 2019).

Passive seismic is also receiving increasing attention as ambient noise can be used as a source to monitor hydrosystems. Recent works on seismic noise monitoring have been conducted using ballistic waves to monitor water table variations (Garambois et

al., 2019). The development of distributed acoustic sensing will allow the acquisition of denser and larger-scale monitoring data in this direction (e.g., Zhan, 2020).

Another passive method that is increasingly used in the vadose zone is the self-potential method (e.g., Revil and Jardani, 2013). It consists in measuring naturally occurring electrical voltages that results from various coupling mechanisms, for instance, electrokinetic coupling when water flows in a porous medium or in a fractured system (e.g., Jougnot et al. 2020; Robert et al, 2011). A promising approach ~~to monitor water movement in the vadose zone~~ is to implant the SP electrodes in the ground at different locations and depths, the measured signal is then integrated over the volume delimited by the electrodes, allowing vertical and lateral monitoring. Recent works of SP monitoring have shown the usefulness of SP to monitor infiltration (Jougnot et al. 2015, Hu et al., 2020, see ~~table 1~~ [Table 2.C.6](#)) and root water uptake (Voytek et al., 2019). These works have shown the need for further improving petrophysical models to shift the use of SP towards a more quantitative paradigm.

Lastly, gravity is a well-established passive geophysical method that is suitable to monitor water movement ~~in the vadose zone~~ (Fores et al., 2017, 2018, ~~table 1~~ [Table 2.C.4](#)). Due to its very large footprint that integrate the density distribution from the center of the Earth, there is a crucial need for more accurate and sensitive gravimeters, such as e.g. quantum absolute gravimeters (Cooke et al., 2021, [Table 2.C.5](#)). The non-uniqueness of gravity signals requires the inclusion of complementary information (e.g. geodetic or hydrological data) for signal separation. Time-lapse gravimetry has been used to identify and constrain subsurface water storage changes, e.g. in artificial recharge facilities (Kennedy et al., 2016), to separate precipitation and groundwater mass signals (Delobbe et al., 2019), to locate karst storage dynamics (Pivetta et al., 2021) and identify evapotranspiration patterns (Carrière et al., 2021). [Time-lapse gravity data have also been successfully used to improve the calibration of groundwater models \(Christiansen et al., 2011a, 2011b\)](#). Further data acquisition procedures and treatments that enhance sensitivity to local processes (e.g., gravity gradients and hydrological modelling coupled with gravity measurements (Cooke et al., 2020, ~~table 1~~ [Table 2.C.5](#)) are needed to provide more quantitative interpretations.

In summary, the 3D nature of the subsurface is made even more complex in the vadose zone by its partial saturation and the evolution of the water phase, both in term of saturation and spatial distribution, as well as by the presence of root systems and microorganisms. ~~While quantitative assessments of aquifer recharge can often be achieved by integrative approaches, the spatial and temporal distribution of the water content in the vadose zone is crucial for assessing water available to the plants through their roots, to identify preferential flow paths for contaminants or infiltration in karstic aquifers, or for optimizing irrigation practices. Careful Detailed studies of processes in the vadose zone at highly instrumented sites open new opportunities for the quantification of transport and reaction processes from lab to field scales (e.g., for tracer loss, see Jougnot et al., 2018 table 1.A and Figure 8). At a more intermediate scale, the 4D imaging unveils preferential flow paths for infiltration or contaminant and transport processes and water availability for plants through their root system allowing to optimize irrigation systems (table 1.B and Figure 8) (see Blazevic et al. 2020). While, aAt a much larger scale, such precise imaging is rendered impossible due to the subsurface complexity, in which case simple 1D hypothesis can lead to quantitatively interesting reliable results (e.g., for quantitative assessment of mass balance or aquifer recharge, table 1.C and Figure 8; mass balance, see Carrière et al., 2021).~~

465 2.4 Groundwater – surface water interactions

The interface between groundwater (GW) and surface water (SW) is a structurally complex, dynamic transition zone that modulates fluxes of water, solutes and heat between the two adjoining compartments (Lewandowski et al., 2019, [Figure 1](#)). These fluxes in turn affect several processes that are relevant for the management of water quantity (e.g. water supply via bank filtration, groundwater recharge), quality (e.g. pollutant attenuation, nutrient transformations – eutrophication) and aquatic ecology (e.g. environmental flows, habitat and refugia) (Fig. 5).

Exchange and turnover patterns in the GW-SW transition zone are defined by nested spatial controls ranging from regional topography and geology (Winter 1999) to local variability of streambed permeability (Kalbus et al. 2009, Irvine et al. 2012; Tang et al., 2017) and morphology evolution (Trauth et al. 2015; Partington et al., 2017), the spatial arrangement of subsurface hydrofacies (Fleckenstein et al. 2006, Frei et al. 2009; Carrier et al., 2018) and their anisotropy (Gianni et al., 2018) and reactive zones (Frei et al. 2012, Loschko et al. 2016). Temporal dynamics are mainly imposed by the surface water system (Dudley–Southern and Binley 2015, Trauth and Fleckenstein 2017, Song et al. 2020), as SW heads can change significantly over short – event – time scales while head changes in GW occur more gradually (e.g. at seasonal time scales). The resulting fluctuations in hydraulic gradients affect subsurface mixing (Hester et al. 2017, Bandopadhyay et al. 2018, [Nogueira et al., 2022](#)), as well as transit times and reactive turnover (Zarnetske et al. 2012, Trauth and Fleckenstein 2017).

~~While a sufficient, mechanistic understanding of the linkages and feedbacks between spatial and temporal controls of flow and turnover processes at small spatial and temporal scales is will clearly be needed for a sound management of water quality and ecosystem services of in coupled GW-SW systems and their ecosystem services (Hester and Gooseff 2010, Morén et al. 2017, Hester et al. 2018), the same level of process detail may not be required to evaluate conjunctive use of GW and SW for the management of larger-scale water quantity (Scanlon et al. 2016). In other words, the level of detail needed will also depend on the scale of the problem and the questions asked. This understanding clearly hinges on innovative methods and the ability to test them at dedicated field sites. The insights gained at these sites may provide a basis for simplifications and generalizations, which can be used to improve modeling concepts for management of GW-SW systems beyond the specific field sites.~~

Recent years have seen significant advances in methods and technologies for the [small-scale](#) characterization and simulation of coupled GW-SW systems. Methods particularly suited for the study of GW-SW interactions, to name a few, include in situ and high resolution sensing of temperatures (Constantin 2008, Vogt et al. 2010) and solute concentrations (Blaen et al. 2016, Brandt et al. 2017), tracer techniques to characterize exchange flows (Mallard et al. 2014; Schilling et al., 2017a; Popp et al., 2021), transit times and reactions (Schmidt et al. 2012, Knapp and Cirpka 2017), as well as process-based, integrated modeling of coupled GW-SW systems (Schilling et al. 2017b, Trauth and Fleckenstein 2017, Broecker et al. 2019, [Nogueira et al., 2021b, Table 2.E.3](#)) and geophysics (McGarr et al., 2021, [Table 2.A.2](#)). Here, we briefly discuss some key research fields related to the heterogeneous and dynamical nature of ~~the~~ GW-SW [interactions systems](#), which have, and likely will continue to contribute to an improved understanding of GW-SW interactions.

The use of heat as a natural tracer has become a popular tool to characterize GW-SW exchange patterns due to the natural temperature differences between GW and SW and the relative ease and accuracy of temperature measurements using standard sensors. This field has evolved significantly since some of the earlier seminal works (Stonestrom and Constantz 2003, Schmidt et al. 2006) and has embraced novel technologies such as DTS (Krause et al. 2012, Rose et al. 2013) and hand-held (Glaser et al. 2016, Marruedo Arricibita et al. 2018) or airborne infrared imagery (Lewandowski et al. 2013). The suite of methods available today allows for high-resolution assessment of temperatures in space and time for a qualitative mapping of GW-SW exchange patterns (Anibas et al. 2011, Krause et al. 2012) or a quantification of exchange fluxes (Schornberg et al. 2010, Munz and Schmidt 2017). Temperature data can ~~further be used to~~ constrain and improve numerical models of coupled GW-SW systems (Munz et al. 2017). Due to their relative ease of use, heat-based methods have become a robust and standard tool to characterize GW-SW exchange patterns. New opportunities may arise from a smart combination of different techniques (Tirado-Conde et al. 2019, [Table 2.C.7](#)) or the use of actively heated fiber optics (Simon et al. 2021), a technique (see also section 2.1) that has been used punctually to quantify streambed flow dynamics in zones of groundwater upwelling (Briggs et al. 2016), and which is in current development for quantifying GW-SW exchange patterns along stream sections (Simon et al., 2022, [Table 2.C.2](#)).

The concentration of oxygen is a key variable that defines the redox state of the transition zone between GW and SW and with that the potential for important reactions like denitrification (Zarnetske et al. 2012). Understanding the dynamics of oxygen consumption is therefore important for evaluating nutrient turnover in hyporheic and riparian zones (Marzadri et al. 2012, Trauth et al. 2015, 2018). A key reaction consuming oxygen in these zones is aerobic respiration, which has been shown to depend on transit times (Zarnetzke et al. 2011a, Diem et al. 2014) and the availability of labile organic carbon as the main electron donor (Zarnetske et al. 2011b). Field deployable optode-based oxygen sensors have enabled high-resolution measurements of oxygen concentrations in time (Diem et al. 2014, Vieweg et al. 2016) and space (Brandt et al. 2017) allowing for robust assessments of respiration dynamics at the GW-SW interface (Vieweg et al. 2016). Based on such data, the strong temperature dependence of aerobic respiration rates has been demonstrated (Diem et al. 2014), which may dominate turnover rates compared to the effects of variable transit times (Nogueira et al., 2021a, [Table 2.E.3](#)). Similar effects were found to affect complex spatio-temporal patterns of riparian denitrification, which seem to be jointly controlled by hydraulically driven variability in exchange fluxes and transit times, supply of organic carbon as an electron donor from stream water and riparian sediments and seasonal temperature variations (Trauth et al. 2018, Lutz et al. 2020, Nogueira et al. 2021b, [Table 2.E.3](#)). Besides high-resolution data sets of key variables like oxygen concentration, it is often the combination of these rich data sets with innovative methods for analysis and modeling (e.g., Diem et al. 2014, Lutz et al. 2020, Nogueira et al. 2021a, 2021b, [Table 2.E.3](#)) that advances our mechanistic understanding of the processes and feedbacks that define the functionality of GW-SW interfaces.

Another promising and still evolving field in the area of GW-SW interactions has been the use of mechanistic models in explorative mode to test hypotheses and to investigate process interactions and feedbacks (Fleckenstein et al. 2010, Brunner et al. 2017). Important insights into physics of flow, transport and turnover processes in the hyporheic zone (HZ) have been

gained based on such modeling studies. This includes the effects of ambient groundwater flow on hyporheic exchange (Cardenas and Wilson 2007, Trauth et al. 2013, 2015), intermeander and parafluvial flows (Boano et al. 2006), reactions and turnover in the HZ (Boano et al. 2010, Trauth et al. 2014, 2015), effects of geologic heterogeneity on hyporheic flows and reactions (Laube et al. 2018, Bardini et al. 2013) as well as the influence of stream flow dynamics on hyporheic exchange and turnover (Trauth and Fleckenstein 2017, Singh et al. 2020). Similar modeling studies have been conducted for riparian zones and river corridors addressing aspects such as the effects of streamflow variations on riparian solute turnover (Gu et al. 2012), effects of bank filtration processes on solute mobilization from riparian zones (Mahmood et al. 2019), the effects of riverbed heterogeneity on GW-SW exchange patterns (Tang et al. 2017) or the presence and dynamics of unsaturated conditions at the stream-aquifer interface (Schilling et al. 2017). Some studies have also used modeling experiments to address mixing processes at GW-SW interfaces, which are important for mixing-dependent reactions (Hester et al. 2017). These studies have addressed effects of flow geometries and hydraulics on mixing in hyporheic and riparian zones (Bandopadhyay et al. 2018; Lee et al., 2021, Nogueira et al., 2022)—or effects of geologic heterogeneity at the groundwater-seawater interface on calcite dissolution and karstification (De Vriendt et al. 2020) as discussed in more detail in section 2.2. Advances in modeling capabilities, including a seamless, integral simulation of flow and reactive transport in of GW-SW systems (Broeker et al. 2019; Li et al., 2020), together with rich data sets from highly instrumented field sites to confront test these models ~~with~~, will help to improve our mechanistic understanding of small-scale GW-SW interactions. ~~Such approach will provide a solid basis for generalizing and developing new concepts allowing the use of more parsimonious models, focusing on the dominant processes, which could be more largely applied for management-relevant scales (Gomez-Velez and Harvey, 2014).~~

550 In summary, ~~the many functionality-functionalities~~ of the GW-SW interface related to water quality (e.g. hyporheic attenuation of nutrients and pollutants) and aquatic ecology (provision of habitat and refugia for aquatic organisms) are ~~is~~ clearly defined by small-scale processes operating in 4D ~~and need to be characterized and evaluated accordingly~~. ~~A~~ suite of field methods and modeling tools exists to characterize the relevant process patterns and dynamics in sufficient detail to develop new conceptual ideas about system functioning or to advise solutions to site-specific problems (table 1.A and Figure 8). ~~New methodological developments as well as innovative improvements to existing methods, and their systematic use at dedicated field sites, will open up new opportunities to advance our mechanistic understanding of GW-SW interactions and to develop more parsimonious models, which are needed to develop appropriate measures for the management of coupled GW-SW systems. Although the heterogeneity of the SW-GW interface leads to a large variability in the exchange fluxes at (deca)metric scale (e.g., Ghysels et al., 2019, table 1.B and Figure 8). In contrast, larger-scale assessments of GW-SW exchange for water~~

560 quantity (e.g. conjunctive use scenarios) or base flow management (e.g. environmental flows) can often be achieved with much simpler, integral approaches (table 1.C and Figure 8).

3 Numerical methods development for 4D data integration and inversion

Numerical representation methods and numerical techniques have become essential tools in both understanding and forecasting subsurface models (e.g., Karatzas, 2017). Most common software suites in hydrogeology allow to model the subsurface using properties distributed in 3D. The temporal derivatives being an essential component of underlying physical equations, the transient character of hydrogeological processes is most often already included. When a mathematical formulation of the process exists, numerical methods allow simulating the response to any scenarios as long as the distribution of the involved hydrogeological parameters is provided. Specific models can handle non-linearity related to time-varying properties as illustrated by coupled models for unsaturated flow or geomechanics (Simunek et al., 2018; Davy et al., 2018). However, next to accuracy related to solvers and their parameterization (numerical dispersion, instability, non-convergence), numerical models remain dependent on the accuracy of the underlying mathematical representation of the modelled process. Previous sections have highlighted that experimental work remains necessary to characterize complex processes such as mixing and transport or GW-SW interactions (Heyman et al., 2020).

Nevertheless, several challenges remain to properly simulate heterogeneous groundwater reservoirs and their dynamics with numerical models. [As highlighted in the previous sections, a key aspect is to feed the models with the appropriate data input](#) (e.g., Schilling et al., 2019). Subsurface processes are influenced by the heterogeneity in subsurface properties. If the latter is essential for the purpose of the model, this should be reflected in the data input [through sufficiently dense spatially distributed data](#) (e.g., Guillaume et al., 2019). Even with powerful computers, simulating the transient response of a catchment-scale model with limited resolution might still take several hours, days or even weeks (e.g., Hayley et al., 2014). The same is true for high-resolution geophysical models such as full-waveform GPR or 3D electromagnetics (e.g., Oldenburg et al., 2013; Klotzsche et al., 2019b; Zhou et al., 2020; Haruzi et al., 2022) and coupled approaches (Coulon et al., 2021). Including geophysical data in hydrogeological models is thus even more challenging. Surrogate models can be used to speed up simulation processes, but their accuracy remains dependent on the training process, which can be problematic in highly heterogeneous media (Linde et al. 2017; Köpke et al., 2018; Mo et al., 2020). Small-scale heterogeneity is present in many geological contexts (e.g., Bayer et al., 2011). Even if it is relevant for the objective of the model, it must thus often be neglected due to limited computational resources. This sometimes leads to unrealistic outputs, in particular for transport processes (e.g., Hoffmann et al., 2019, [Table 2.A.1](#)). This may be addressed by upscaling heterogeneous systems and defining equivalent properties at larger scale, but this is very challenging for transport processes with multiple physical scales and non-equilibrium phenomena (Li et al., 2017; Icardi et al., 2019).

Even if simulating small-scale heterogeneity would become possible, the actual distribution of properties is always unknown. The limited amount of noise-contaminated data does not allow to unequivocally recover this distribution through inverse modeling (Zhou et al., 2014), even when distributed geophysical data is available (Hermans et al., 2015a; Mari et al., 2009, [table 1-Table 2.D.1](#)). On the one hand, deterministic approaches have to simplify the parameter estimation problem to make it well-posed (e.g., smoothing, zonation or pilot-points) and are therefore, limited, for tackling uncertainty related to 4D

595 processes. On the other hand, stochastic approaches such as Markov chain Monte Carlo (McMC) methods (e.g., Vrugt et al., 2013), using more or less complex and realistic geostatistical representations of the heterogeneity and more or less wide prior distribution (Linde et al., 2015b), often require thousands to millions of simulations to converge, especially when spatial uncertainty is included (e.g., De Pasquale et al., 2019). The transient aspects are also commonly simplified, due to a lack of data or the simplification of boundary conditions. In most applications, resolving numerically a time-~~dependant~~-~~dependent~~ system of partial derivative equations based on spatially distributed parameters in 3D with a high spatial and temporal resolution ~~to represent a relatively large system~~ remains utopic. It is therefore of uttermost importance to understand which simplifying assumptions can be applied without degrading the predictive capability of the model (Schilling et al., 2019).

Fractured aquifers are even more complicated to model. Fracture networks have complex 3D geometries and are, therefore, difficult to characterize from mostly 1D or 2D data (Le Goc et al., 2017; Day-Lewis et al., 2017). Modeling flow in fractures ~~requires another scale compared to matrix flow~~ occurs at a ~~smaller~~ scale, which brings additional challenges in terms of gridding (Schädle et al., 2019) and inversion (Ringel et al., 2019). Combined with a higher degree of heterogeneity and uncertainty than in porous media, it increases the above-mentioned issues preventing efficient modeling.

Nevertheless, recent advances shed light on some innovative solutions to tackle those problems. For fractured aquifers, recent studies in fracture modeling such as realistic flow characterization and mechanical coupling using discrete fracture networks (Davy et al., 2018; Maillot et al., 2016; Lei et al., 2017), innovative inverse methodologies (Pieraccini, 2020) and characterization techniques (Dorn et al., 2013; Shakas and Linde, 2017; Molron et al., 2020, 2021, ~~table 4~~ Table 2.B.2) pushed forward our ability to account for the complexity of fractured media.

More generally, Cloud-cloud computing combined with increasing computational power ~~should allow to~~ is one avenue to allow modelling the subsurface at a higher 4D resolution for an increasing number of applications in the future, ~~including for (small) consulting companies and field practitioners~~ (Hayley, 2017; Kurtz et al., 2017). The ongoing efforts for coupling different simulators, both in hydrogeology and hydrogeophysics will also favor the incorporation of larger, more informative data sets ~~in modelling efforts~~ (e.g., Commer et al., 2020). The incorporation of geophysical data, especially at the large-scale has remained limited for a long time by the use of empirical and local petrophysical relationship (Rubin and Hubbard, 2005). The combination of large-scale airborne electromagnetic data combined with advanced machine learning approaches for their integration will likely contribute to the broader use of 3D and 4D data sets in hydrogeology accounting for the inherent uncertainty at that scale (e.g., Vilhelmsen et al., 2019; Gottschalk et al., 2022).

Although Bayesian methods such as McMC are widely recognized in the scientific literature for inversion, prediction and uncertainty quantification (Ferré, 2020), they have not been widely adopted by practitioners because of their computational burdens, especially for complex ~~uncertain~~ geometries. Recent developments in machine learning such as deep neural networks (DNN) have shown that complex spatial patterns can be efficiently reduced to a manageable number of dimensions. DNNs allow to simplify complex subsurface models with millions of cells to a few tens of dimensions, while maintaining their geometrical complexity represented by a prior parameter distribution. This opens the possibility to apply McMC or global optimization methods at a reasonable cost as recently demonstrated by Laloy et al. (2018) and Lopez-Alvis et al., (2021) (see

630 [Figure 6](#) (Figure-). Since the parameterization of the prior is a key to obtain realistic solutions, the identification of realistic geological scenarios through falsification techniques (e.g., Hermans et al., 2015a; Linde et al., 2015a; Lopez-Alvis et al., 2019; [2022](#)) or assembled prior (Lopez-Alvis et al., 2022) can further improve stochastic inversion by reducing the range of the prior. Another recent innovation is to propose physically-based geostatistical upscaling allowing to translate the small-scale spatial uncertainty at a larger scale (Benoit et al., 2021). Combining those recent advances with accurate fast approximations of the forward model (Linde et al., 2017) should allow for more accurate representations of spatial variability within affordable 635 computational time. As an alternative, approximations of the inverse problems using Ensemble Kalman generator (e.g., Nowak, 2009, Bobe et al., 2020, Tso et al., 2021) or normalization and linearization approaches (e.g., Holm-Jensen and Hansen, 2019) can also provide a relatively fast, though realistic, approximation of the solution to the inverse problem. Alternatively, recent studies have proposed to investigate more prediction-oriented strategies to simulate complex hydrogeological systems (Sun and Sun, 2015; Ferré, 2017; Scheidt et al., 2018). For example, Bayesian Evidential Learning 640 (BEL) proposes to use a set of simulations from realistic numerical models including the 4D complexity to learn a statistical relationship between a predictor (data set) and a target (model output, see [Figure 7](#) (Figure-), making it a model-driven machine-learning approach, circumventing the challenges of non-linear inversion while providing a proxy for global sensitivity analysis (Hermans et al., 2018). The statistical learning requires reducing the dimensionality of the problem, so that part of the complexity may remain unresolved (Park and Caers, 2020). If such a statistical relationship exists, this approach has the 645 advantage to require only a limited amount of simulations to derive the posterior distribution of the prediction, typically only a few hundreds to a few thousands. The latter are independent and can be fully parallelized. Propagating noise in the statistical relationship is also straightforward (Hermans et al., 2016). Such direct forecasting is possible because predictions often have a much-lower dimensionality than models. [The efficiency of such an approach makes it particularly interesting for experimental and optimum design studies under uncertainty \(Thibaut et al., 2021\).](#) Nevertheless, when the data-prediction 650 relationship is complex and highly non-linear, BEL might overestimate uncertainty (Michel et al., 2020a), for instance when the prior uncertainty is large (Hermans et al., 2019). In such a case, classical inversion might still be needed (Scheidt et al., 2018). Recent advances have shown that BEL can also estimate the model parameter distributions and be used as a more traditional inversion technique (Yin et al., 2020; Michel et al., 2020a). However, such more advanced applications require further development of appropriate tools to identify highly non-linear relationships (Park and Caers, 2020) which will 655 inevitably come at a larger computational cost (Michel et al., 2020b). Although these recent developments are promising solutions to integrate large 4D data sets within efficient simulation and inversion framework to forecast the behavior of aquifers, they still need to be more widely evaluated and used, including for complex field cases. [New mechanistic models developed based on 4D data sets will need to be integrated in numerical models. The validation with case studies in different contexts will demonstrate if new inversion and prediction methods, including machine learning approaches are adapted to the incorporation of the 4D complexity of hydrogeological processes. Synthetic numerical studies and global sensitivity analysis should help us to identify which simplifications can be reasonably made in applications at the large scale and/or with limited budget preventing the acquisition of dense data sets.](#)

4 When is a 4D coupled spatial and temporal characterization needed ?

665 Although spatial heterogeneity and temporal variations by default influence all the processes occurring in the subsurface, a full 4D characterization coupled with a numerical model is not always necessary. Throughout the paper, we identified three levels of applications requiring a decreasing amount of resolution. Table 1 and Figure 8 summarize and classifies the different scales and processes according to their requirement for spatio-temporal monitoring, including 4D imaging.

670 A. Processes for which high-resolution space-time data are needed to improve mechanistic models. Previous sections have discussed how the acquisition of spatially and temporally distributed data is crucial for hydrological processes understanding. Observation gaps severely impede our ability to understand, model and predict a series of critical subsurface processes (see table 1.A and Figure 8). The acquisition of dense 4D data sets is needed to obtain new insights into internal mechanisms and process hierarchies, identify the dominant processes, which govern a specific response of the system, and ultimately develop upscaled models that capture these dynamics. High-resolution space-time data can thus help us to characterize the influence of heterogeneity and temporal dynamics, and ~~to~~ thus understand and quantify how the small-scale processes must be upscaled to larger scales, or to which level they can be simplified. This is crucial to develop new conceptual ideas about system functioning, to advise solutions to site-specific problems or to design accurate numerical models.

680 B. Processes for which high-resolution space-time monitoring is desirable at the scale of individual sites. This is for example the case for precision agriculture for which knowing the spatio-temporal distribution of the soil moisture is ~~crucial~~ a central element to implement efficient irrigation solutions or for site-risk management to avoid the spreading of contaminations. The oil industry has been aware of the importance of the spatio-temporal variations of their reservoirs for decades, and related research has been supported by economic interests. It has less been the case for hydrogeology, except ~~maybe~~ for the characterization of storage site for nuclear waste, or more recently induced seismicity related to geothermal exploitations. An increase in the number of applications including 4D investigations and monitoring (see table 1.B and Figure 8). Hydrology has been using remote sensing data for decades, and a similar trend is now visible with airborne electromagnetic data in hydrogeology. This is a first step towards the generalization of the integration, to some extent, of 3D and 4D data in groundwater models, even at the catchment scale and beyond. A key challenge will be to determine which resolution and which sampling rate is necessary to properly account for the underlying subsurface complexity, which requires testing and validating these methods at highly instrumented observatories and sharing the produced space-time datasets.

690 C. Processes for which 4D data– may not be necessary. In some such cases, the principle of parsimony applies, and simple models can be calibrated explaining sparse data (see table 1.C and Figure 8). For example, the management of water resources based on meteorological and production data using simple water balance approaches has been applied successfully in many contexts for decades. We may obtain reasonable estimates of groundwater volumes and

fluxes from sparse hydrogeological data, so that a fine scale characterization of the heterogeneity might not be needed or working in steady-state conditions might be sufficient. Estimating an average recharge rate for by-passing the complex processes occurring in the vadose zone has been proved to be efficient in many contexts. ~~In such cases, the principle of parsimony applies, and simple models can be calibrated explaining sparse data.~~

700 In summary, although a few large-scale applications do not require a high level of spatial characterization and temporal monitoring, a large spectrum of processes are highly sensitive to 4D dynamics. We identify two complementary strategies to deal with this challenge. The first consists in developing upscaled models that capture the effect of spatial and temporal fluctuations. This requires first acquiring and sharing high resolution space-time datasets at highly instrumented observatories (see section 5). The second is to implement a site-specific 4D imaging strategy in critical applications that require it and have
705 the corresponding budget. This requires as a first step to validate recent 4D imaging techniques in some dedicated observatories, where the degree of knowledge is sufficient to establish the relevant space-time resolution depending on the targeted process and application (see section 5).

It is not evident to know *a priori* if 4D imaging is desirable. If a more systematic use of global sensitivity analysis and the multiplication of case studies should help the community to reveal when this is actually necessary, we also propose to consider
710 some key elements when evaluating the need for a thorough spatio-temporal characterization of the reservoir at the three envisaged scales:

- Is there evidence for small-scale heterogeneity influencing the considered phenomenon ?
- Are there any existing mechanistic models explaining the observed phenomena ? Are these effective models in agreement with available observations at highly instrumented sites ?
- 715 - Is there a technology available to monitor the desired 4D variations ? ~~Is there evidence for small-scale heterogeneity influencing the considered phenomenon ?~~
- Do transient phenomena have an influence on the results ?
- Does the lack of data has an influence on the decision to ignore spatial heterogeneity or temporal variations ?
- Is there evidence in the literature (e.g. global sensitivity analysis) that the processes at hand are not sensitive to the
720 heterogeneity ?

4-5 The added value of need for highly instrumented and long term instrumented field sites hydrogeological observatories

725 Over the last decades, highly instrumented field sites have been equipped to explore ~~and~~ monitor and model subsurface processes ~~often with detailed geological models available~~ (e.g. Bogaen et al. 2018). Long-term observations of subsurface environments, typically more than ten years, are motivated by the broad range of responses and residence-transit times of these systems that provide resilience to hydrological systems to environmental changes. When characterizing processes beyond the laboratory scales, the exhaustive 4D characterization of processes becomes a ~~challenging n insurmountable~~ task. While it is
730 illusory and not necessary to equip all subsurface systems with 4D imaging techniques, the use of high spatial and temporal resolution techniques in few highly instrumented field observatories during passive monitoring and active experiments is a key step to establish effective models that capture the effect of 3D heterogeneity and temporal dynamics and can be used and parametrized in other less instrumented sites. ~~may be a key step to upscale laboratory observations to a scale relevant for practical applications.~~ The insights gained at these sites may provide is thus a basis for simplifications and generalizations,
735 which can be used to improve modeling concepts for management beyond the specific field sites. In particular, these datasets should allow unraveling the importance of 4D dynamics and the influence of different processes on hydrogeophysical signals. Furthermore, these field observatories provide platforms to test and validate emerging 4D imaging techniques, evaluate their accuracy and potential, and establish the required space-time resolution depending on the targeted process. We thus argue that ~~these field hydrogeological~~ observatories provide a key step between theory and laboratory experiments on one side and
740 practical field applications on the other side.

Available datasets related to such sites often combine fixed geophysical and hydrogeological sensing systems for the short-term monitoring of experimental campaigns, but also for the long-term monitoring of natural systems required to characterize physical and chemical heterogeneity and target hotspots, which cannot be easily accessed by classical observations. Related studies often provide parametrized hydrological models for the interpretation.

745 A non-exhaustive list of time-lapse hydrogeological and hydrogeophysical datasets ~~available online~~, selected based on their on-line availability and ~~relevance for illustrating this study~~ space-time resolution, is given in ~~Table 1~~ Table 2. As can be seen, 4D data openly available are still scarce given the large variability of geological systems and applications. Because such extensive spatially and temporally resolved imaging can only be achieved on few sites, we argue that it is important to archive and share such datasets in open databses. In particular, these data are critical to i) test and validate model hypotheses and
750 predictive capabilities, ii) to develop appropriate inverse modeling approaches adapted to the high level of heterogeneity of subsurface environments, iii) evaluate the added value of different imaging techniques in order to optimize the design of monitoring strategies on other sites. ~~Table 1~~ Table 2 will be made available through the website

<https://hplus.ore.fr/en/database/4d-hydrogeology-dataset>, which will be open to contributions to enrich the datasets with new data.

755 **5-6 Concluding remarks**

In this paper, we have illustrated that advances in our understanding of complex subsurface processes hinge on our ability to observe/image key parameters and state variables with the relevant spatial and temporal resolution. ~~Key applications where the coupling of spatial heterogeneity and temporal fluctuations might be essential include flow heterogeneity and dynamics, transport and reaction, unsaturated flow and transport, and surface-groundwater interactions, heat and solute transport, mixing and reaction processes occurring in the subsurface and at the interface between the subsurface and rivers. Identifying spatial and temporal fluctuations of groundwater flow is, thus, key to unravel important processes such as the transport of contaminant or the biodegradation of pollutants. In specific applications, data availability is always limited, due to budget, time and space constraints, and conceptual simplifications are required. In this context, field observatories linked to open database and techniques dedicated to the acquisition of spatially and temporally resolved data sets are essential to~~ i) build appropriate models based on spatially and temporally resolved measurements and ii) test and validate relevant sensors and methodologies.

~~Although spatial heterogeneity and temporal variations by default influence all the processes occurring in the subsurface, a full 4D characterization coupled with a numerical model is not always necessary. For example, the management of water resources based on meteorological and production data using simple water balance approaches has been applied successfully in many contexts for decades. We may obtain reasonable estimates of groundwater volumes and fluxes from sparse hydrogeological data, so that a fine scale characterization of the heterogeneity might not be needed or working in steady state conditions might be sufficient. Estimating an average recharge rate for by passing the complex processes occurring in the vadose zone has been proved to be efficient in many contexts.~~

~~Nevertheless, key applications where the coupling of spatial heterogeneity and temporal fluctuations might be essential include heat and solute transport, mixing and reaction processes occurring in the subsurface and at the interface of rivers. Identifying spatial and temporal fluctuations of groundwater flow is, thus, key to unravel important processes such as the transport of contaminant or the biodegradation of pollutants. In specific applications, data availability is always limited, due to budget, time and space constraints, and conceptual simplifications are required. In this context, field observatories linked to open database and techniques dedicated to the acquisition of spatially and temporally resolved data sets are essential to build~~ appropriate models based on spatially and temporally resolved measurements.

New technologies are advancing our ability to close observation gaps and image the subsurface heterogeneity and dynamics for processes of relevance in hydrogeology. ~~The development of techniques and sensors directly sensitive to transient fluxes (finite volume point dilution method, active-DTS), constitutes a major advance towards understanding the complex processes taking place in the subsurface, although further developments are still needed to combine these techniques with classical~~

785 ~~geophysical methods to allow full 4D imaging. Similarly, the combination of classical salt and dye tracer with heat and~~
~~dissolved gasses has the potential to further discriminate the different transport processes and to understand the exchanges~~
~~between mobile and immobile water, both in porous and fractured media, but also for surface subsurface interactions.~~ Such
data collected across scales and with dense networks could lead to a better description of the processes and the development
of new mechanistic models as well as the proper definition of effective parameters and upscaling approaches to do away with
790 the complexity at larger scales.

Considering the spatial heterogeneity of the subsurface quickly requires the use of efficient and reliable numerical models.
Including small-scale heterogeneity automatically calls for high-resolution models with refined grids leading to high if not
unacceptable computation times. In addition, the uncertainty inherent to subsurface systems can only be properly dealt with
by stochastic approaches that require many simulations to characterize the ensemble of possible outcomes. The current
795 computational power available for the scientific community, and for practitioners in the industry, is not sufficient to
systematically tackle groundwater reservoirs with their full 4D complexity.

Simplifications, such as ignoring the small-scale heterogeneity or ignoring some transient processes, are always needed and
can in many cases provide useful results for groundwater management. Nevertheless, the hydrogeological community is still
often facing model predictive outcomes that are not consistent when validation data become available. Even though the 4D
800 complexity is not always the cause, it can probably explain why some models have poor predictive capability. Ideally,
hydrogeological conceptual models should initially consider the 4D complexity of the system, and only deviate from this
rigorous description when there is no significant effect on the prediction or decision-making process. Such conceptual
simplifications of hydrogeological systems should be based on strong experimental or numerical evidences, and should not
constitute the default hypothesis because of lack of data or computational power. [High-resolution space-time observations are](#)
805 [needed for improve mechanistic models of hydrological processes and for their upscaling, as well as for the monitoring at the](#)
[field-scale when significant risks for humans or the environment are associated. Although 4D data are less needed at larger](#)
[scales for which averaging models are often satisfactory, we expect they will become more crucial at this scale as well in the](#)
[future to tackle the challenges of sustainable development linked to water availability.](#)

In that sense, the existence of large 4D data sets linked to field observatories and models can only be beneficial for the
810 community. Similarly, the more systematic use of Monte Carlo simulations, prediction-oriented approaches or global
sensitivity analyses, although computationally expensive, can provide the necessary background information, at least for
processes that can be properly characterized by mathematical models.

[Author contribution](#)

[Investigation and Formal analysis: TH, PG. Concetualization and writing - original draft preparation: TH, PG, DJ, JF,](#)
815 [TLB. Resources: TH, PG, DJ, JF, TLB, JLA, RH, AP, AKC, APA, LB, BP, PH, AFV, GN, JTC, MK. Funding acquisition,](#)

Acknowledgement

This work has received funding from the European Union’s Horizon 2020 research and innovation program under the Marie Skłodowska-Curie grant agreement number 722028 (ENIGMA ITN). We thank all the ENIGMA beneficiaries and partners for their direct and indirect contributions to this article.

References

- Abdel Aal, G. Z., Atekwana, E. A., and Atekwana, E. A. Effect of bioclogging in porous media on complex conductivity signatures. *Journal of Geophysical Research: Biogeosciences*, 115(G3), G00G07, 2010.
- 825 Aeschbach-Hertig, W., and Gleeson, T. Regional strategies for the accelerating global problem of groundwater depletion. *Nature Geoscience*, 5(12), 853–861, 2012. <https://doi.org/10.1038/ngeo1617>
- Anibas, C., K. Buis, R. Verhoeven, P. Meire, and O. Batelaan. A simple thermal mapping method for seasonal spatial patterns of groundwater-surface water interaction, *J Hydrol*, 397(1-2), 93-104, 2011.
- Arbabzadeh, M., Sioshansi, R., Johnson, J. X., and Keoleian, G. A. The role of energy storage in deep decarbonization of electricity production. *Nature Communications*, 10(1), 3413, 2019. <https://doi.org/10.1038/s41467-019-11161-5>
- 830 Arora, T., Linde, N., Revil, A., and Castermant, J. Non-intrusive characterization of the redox potential of landfill leachate plumes from self-potential data. *Journal of contaminant hydrology*, 92(3-4), 274-292, 2007.
- Atekwana, E. A., and Slater, L. D. Biogeophysics: A new frontier in Earth science research. *Reviews of Geophysics*, 47(4), RG4004, 2009.
- 835 Auken, E., Foged, N., Andersen, K. R., Nyboe, N. S., and Christiansen, A. V. On-time modelling using system response convolution for improved shallow resolution of the subsurface in airborne TEM. *Exploration Geophysics*, 51(1), 4-13, 2020.
- Bailey, R. T. Review: Selenium contamination, fate, and reactive transport in groundwater in relation to human health. *Hydrogeology Journal*, 25(4), 1191–1217, 2017. <https://doi.org/10.1007/s10040-016-1506-8>
- 840 Bandopadhyay, A., P. Davy, and T. Le Borgne. Shear Flows Accelerate Mixing Dynamics in Hyporheic Zones and Hillslopes, *Geophys Res Lett*, 45(21), 11659-11668, 2018.
- Bardini, L., Boano, F., Cardenas, M. B., Sawyer, A. H., Revelli, R., and Ridolfi, L. Small-scale permeability heterogeneity has negligible effects on nutrient cycling in streambeds. *Geophysical Research Letters*, 40(6), 1118–1122, 2013. <https://doi.org/10.1002/grl.50224>

- 845 Bayer, P., Huggenberger, P., Renard, P., and Comunian, A. Three-dimensional high resolution fluvio-glacial aquifer analog: Part 1: Field study. *Journal of Hydrology*, 405, 1–9, 2011.
- Benoit, N., Marcotte, D., Molson, J. Stochastic correlated hydraulic conductivity tensor calibration using gradual deformation. *Journal of Hydrology*, 594, 125880, 2021.
- Bense, V. F., Read, T., Bour, O., Le Borgne, T., Coleman, T., Krause, S., et al. Distributed Temperature Sensing as a downhole
850 tool in hydrogeology. *Water Resources Research*, 52(12), 9259–9273, 2016. <https://doi.org/10.1002/2016WR018869>
- Berkowitz, B., Cortis, A., Dentz, M., and Scher, H. Modeling non-Fickian transport in geological formations as a continuous time random walk. *Reviews of Geophysics*, 44(2), RG2003, 2006.
- Binley, A., Hubbard, S. S., Huisman, J. A., Revil, A., Robinson, D. A., Singha, K., and Slater, L. D. The emergence of hydrogeophysics for improved understanding of subsurface processes over multiple scales. *Water resources research*,
855 51(6), 3837-3866, 2015.
- Blaen, P. J., K. Khamis, C. E. M. Lloyd, C. Bradley, D. Hannah, and S. Krause. Real-time monitoring of nutrients and dissolved organic matter in rivers: Capturing event dynamics, technological opportunities and future directions, *Sci Total Environ*, 569, 647-660, 2016.
- Blazevic, L., L. Bodet, S. Pasquet, N. Linde, D. Jougnot, and L. Longuevergne. Time-Lapse Seismic and Electrical Monitoring
860 of the Vadose Zone during a Controlled Infiltration Experiment at the Ploemeur Hydrological Observatory, France. *Water* 12, 1230, 2020. <https://doi.org/10.3390/w12051230>
- Blunt, M. J., Bijeljic, B., Dong, H., Gharbi, O., Iglauer, S., Mostaghimi, P., et al. Pore-scale imaging and modelling. *Advances in Water Resources*, 51, 197–216, 2013. <https://doi.org/10.1016/j.advwatres.2012.03.003>
- Boano, F., A. Demaria, R. Revelli, and L. Ridolfi. Biogeochemical zonation due to intrameander hyporheic flow, *Water Resour*
865 *Res*, 46, W02511, 2010.
- Boano, F., C. Camporeale, R. Revelli, and L. Ridolfi. Sinuosity-driven hyporheic exchange in meandering rivers, *Geophys Res Lett*, 33(18), L18406, 2006.
- Bobe, C., Hanssens, D., Hermans, T., and Van De Vijver, E. Efficient Probabilistic Joint Inversion of Direct Current Resistivity and Small-Loop Electromagnetic Data. *Algorithms*, 13(6), 144, 2020. <https://doi.org/10.3390/a13060144>
- 870 Bochet, O., Bethencourt, L., Dufresne, A., Farasin, J., Pédrot, M., Labasque, T., et al. Iron-oxidizer hotspots formed by intermittent oxic–anoxic fluid mixing in fractured rocks. *Nature Geoscience*, 13(2), 149-155, 2020.
- Bogena, H. R., White, T., Bour, O., Li, X., and Jensen, K. H. Toward better understanding of terrestrial processes through long-term hydrological observatories. *Vadose Zone Journal*, 17(1), 1-10, 2018.
- Bradford, J. H. Depth characterization of shallow aquifers with seismic reflection, Part I—The failure of NMO velocity
875 analysis and quantitative error prediction. *Geophysics*, 67(1), 89-97, 2002.
- Brandt, T., M. Vieweg, G. Laube, R. Schima, T. Goblirsch, J. H. Fleckenstein, and C. Schmidt. Automated in Situ Oxygen Profiling at Aquatic-Terrestrial Interfaces, *Environ Sci Technol*, 51(17), 9970-9978, 2017.

- Brantley, S.L., M.B. Goldhaber and K.V. Ragnarsdottir. Crossing Disciplines and Scales to Understand the Critical Zone, *Elements*, 3, 307-314, 2007.
- 880 Brennwald, M. S., M. Schmidt, J. Oser, and R. Kipfer. A portable and autonomous mass spectrometric system for on-site environmental gas analysis, *Environ. Sci. Technol.*, 50 (24), 13455–13463, 2016.
- Briggs, M. A., S. F. Buckley, A. C. Bagtzoglou, D. D. Werkema, and J. W. Lane. Actively heated high-resolution fiber-optic-distributed temperature sensing to quantify streambed flow dynamics in zones of strong groundwater upwelling, *Water Resour Res*, 52(7), 5179-5194, 2016.
- 885 Broecker, T., K. Teuber, V. S. Gollo, G. Nutzmann, J. Lewandowski, and R. Hinkelmann. Integral Flow Modelling Approach for Surface Water-Groundwater Interactions along a Rippled Streambed, *Water*, 11(7), 1517, 2019.
- Brouyère, S., Batlle-Aguilar, J., Goderniaux, P., Dassargues, A. A new tracer technique for monitoring groundwater fluxes: the Finite Volume Point Dilution Method. *J. Contam. Hydrol.* 95, 121–140, 2008.
- Brunner, P., R. Therrien, P. Renard, C. T. Simmons, and H. J. H. Franssen. Advances in understanding river-groundwater
890 interactions, *Rev Geophys*, 55(3), 818-854, 2017.
- Burnett, W.C., Aggarwal, P.K., Aureli, A., Bokuniewicz, H., Cable, J.E., Charette, M.A., Kontar, E., Krupa, S., Kulkarni, K.M., Loveless, A., Moore, W.S., Oberdorfer, J.A., Oliveira, J., Ozyurt, N., Povinec, P., Privitera, A.M.G., Rajar, R., Ramessur, R.T., Scholten, J., Stieglitz, T., Taniguchi, M., Turner, J.V. Quantifying submarine groundwater discharge in the coastal zone via multiple methods. *Science of the Total Environment* 367, 498–543, 2006.
895 <https://doi.org/10.1016/j.scitotenv.2006.05.009>
- Butler, D. France digs deep for nuclear waste. *Nature*, 466(7308), 804–805, 2010. <https://doi.org/10.1038/466804a>
- Cardenas, M. B., and J. L. Wilson. Exchange across a sediment-water interface with ambient groundwater discharge, *J Hydrol*, 346(3-4), 69-80, 2007.
- Carlier, C., Wirth, S. B., Cochand, F., Hunkeler, D., and Brunner, P. Geology controls streamflow dynamics. *Journal of*
900 *Hydrology*, 566, 756–769, 2018. <https://doi.org/10.1016/j.jhydrol.2018.08.069>
- Carrière S.D., Chalikakis K., Danquigny C., Clément R., Emblanch C. Feasibility and Limits of Electrical Resistivity Tomography to Monitor Water Infiltration Through Karst Medium During a Rainy Event. In: Andreo B., Carrasco F., Durán J., Jiménez P., LaMoreaux J. (eds) *Hydrogeological and Environmental Investigations in Karst Systems*. Environmental Earth Sciences, vol 1. Springer, Berlin, Heidelberg, 2015. https://doi.org/10.1007/978-3-642-17435-3_6
- 905 Carrière, S. D., Loiseau, B., Champollion, C., Ollivier, C., Martin-StPaul, N. K., Lesparre, N., et al. First evidence of correlation between evapotranspiration and gravity at a daily time scale from two vertically spaced superconducting gravimeters. *Geophysical Research Letters*, 48, e2021GL096579, 2022. <https://doi.org/10.1029/2021GL096579>
- Chatton, E., Labasque, T., de La Bernardie, J, Guihéneuf, N., Bour, O. and L. Aquilina. Field continuous measurement of dissolved gases with a CF-MIMS: Applications to the physics and biogeochemistry of groundwater flow, *Environmental Science and Technology*, Volume: 51 (2), pp 846-854, 2017. doi: 10.1021/acs.est.6b03706
910

- Christiansen, L., Binning, P.J., Rosbjerg, D., Andersen, O.B., and Bauer-Gottwein, P. Using time-lapse gravity for groundwater model calibration: An application to alluvial aquifer storage. *Water Resources research*, 47, W06503, 2011a. doi:10.1029/2010WR009859.
- 915 Christiansen, L., Haarder, E.B., Hansen, A.B., Looms, M.C., Binning, P.J., Rosbjerg, D., Andersen, O.B., and Bauer-Gottwein P. Calibrating Vadose Zone Models with Time-Lapse Gravity Data. *Vadose Zone Journal*, 10, 1034-1044, 2011b. <https://doi.org/10.2136/vzj2010.0127>
- Commer, Finsterle, S., Hoversten, G.M. Three-dimensional fracture continuum characterization aided by urface time-domain electromagnetics and hydrogeophysical joint inversion – proof-of-concept. *Computational Geosciences*, 24, 1895-1909, 2020. <https://doi.org/10.1007/s10596-020-09942-9>.
- 920 Comte, J.-C., Offerdinger, U., Legchenko, A., Caulfield, J., Cassidy, R., and Mézquita González, J. A. Catchment-scale heterogeneity of flow and storage properties in a weathered/fractured hard rock aquifer from resistivity and magnetic resonance surveys: Implications for groundwater flow paths and the distribution of residence times, *Geological Society, London, Special Publications*, 479(1), 35, 2019. <https://doi.org/10.1144/SP479.11>
- Conant, B., Robinson, C. E., Hinton, M. J., and Russel, H. A. J. A framework for conceptualizing groundwater-surface water interactions and identifying potential impacts on water quality, water quantity, and ecosystems. *Journal of Hydrology*, 19, 609-627, 2019.
- 925 Constantz, J. Heat as a tracer to determine streambed water exchanges. *Water Resources Research*, 44(4), W00D10, 2008. <https://doi.org/10.1029/2008WR006996>
- Cooke, A. K., Champollion, C., Vermeulen, P., Janvier, C., Desruelle, B., Le Moigne, N., and Merlet, S. Detection of subsurface water storage dynamics with combined gravity-vertical gravity gradient monitoring and hydrological simulation. In *EGU General Assembly Conference Abstracts*, 9020, 2020.
- 930 Cooke, A. K., Champollion, C., and Le Moigne, N. First evaluation of an absolute quantum gravimeter (AQG# B01) for future field experiments. *Geoscientific Instrumentation, Methods and Data Systems*, 10(1), 65-79, 2021.
- Coulon, C. Pryet, A., Lemieux, J.-M., Ble, J.F.Y., Bouchedda, A., Gloaguen, E. Comte, J.C., Dupuis, J.C., Banton, O. A framework for parameter estimation using sharp-interface seawater intrusion models, *Journal of Hydrology*, 600, 126509, 2021. [10.1016/j.jhydrol.2021.126509](https://doi.org/10.1016/j.jhydrol.2021.126509)
- 935 ~~Daily, W., Ramirez, A., LaBrecque, D., and Nitao, J. Electrical resistivity tomography of vadose water movement. *Water Resources Research*, 28(5), 1429-1442, 1992.~~
- Dangeard, M., Bodet, L., Pasquet, S., Thiesson, J., Guérin, R., Jougnot, D., and Longuevergne, L. Estimating picking errors in near-surface seismic data to enable their time-lapse interpretation of hydrosystems. *Near Surface Geophysics*, 16(6), 613-625, 2018.
- 940 Davis, C.A., E. Atekwana, E. Atekwana, L.D. Slater, S. Rossbach, and M.R. Mormile. Microbial growth and biofilm formation in geologic media is detected with complex conductivity measurements, *Geophys. Res. Lett.* 33, L18403, 2006.

- 945 Davy, P., Darcel, C., Le Goc, R., and Mas Ivars, D. Elastic properties of fractured rock masses with frictional properties and power law fracture size distributions. *J. Geophys. Res.: Solid Earth*, 123(8), 6521-6539, 2018. doi:<https://doi.org/10.1029/2017JB015329>
- Day-Lewis, F. D., Lane, J. W., and Gorelick, S. M. Combined interpretation of radar, hydraulic, and tracer data from a fractured-rock aquifer near Mirror Lake, New Hampshire, USA. *Hydrogeology Journal*, 14(1-2), 1-14, 2006.
- 950 Day-Lewis, F. D., Linde, N., Haggerty, R., Singha, K., and Briggs, M. A. Pore network modeling of the electrical signature of solute transport in dual-domain media. *Geophysical Research Letters*, 44(10), 4908-4916, 2017.
- Day-Lewis, F. D., Singha, K., and Binley, A. Applying petrophysical models to radar travel time and electrical resistivity tomograms: Resolution-dependent limitations. *Journal of Geophysical Research*, 110, B08206, 2005. <https://doi.org/10.1029/2004JB003569>
- 955 Day-Lewis, F. D., Slater, L. D., Robinson, J., Johnson, C. D., Terry, N., and Werkema, D. An overview of geophysical technologies appropriate for characterization and monitoring at fractured-rock sites. *Journal of Environmental Management*, 204, 709-720, 2017. <https://doi.org/10.1016/j.jenvman.2017.04.033>
- de Anna, P., Jimenez-Martinez, J., Tabuteau, H., Turuban, R., Le Borgne, T., Derrien, M., and Méheust, Y. Mixing and reaction kinetics in porous media: An experimental pore scale quantification. *Environmental science and technology*, 48(1), 508-516, 2014.
- 960 de La Bernardie, J., Bour, O., Le Borgne, T., Guihéneuf, N., Chatton, E., Labasque, T. et al. Thermal attenuation and lag time in fractured rock: theory and field measurements from joint heat and solute tracer tests. *Water Resources Research*, 54(12), 10-053, 2018.
- Delobbe, L., Watlet, A., Wilfert, S., and Camp, M. V. Exploring the use of underground gravity monitoring to evaluate radar estimates of heavy rainfall. *Hydrology and Earth System Sciences*, 23(1), 93-105, 2019.
- 965 de Pasquale, G., Linde, N., Doetsch, J., and Holbrook, W. S. Probabilistic inference of subsurface heterogeneity and interface geometry using geophysical data. *Geophysical Journal International*, 2(217), 816-831, 2019.
- De Vriendt, K., M. Pool, and M. Dentz. Heterogeneity-Induced Mixing and Reaction Hot Spots Facilitate Karst Propagation in Coastal Aquifers, *Geophys Res Lett*, 47(10), e2020GL087529, 2020.
- 970 Del Val, L., Carrera, J., Pool, M., Martinez, L., Casanovas, C., Bour, O. and Folch, A. Heat dissipation test with fiber-optic distributed temperature sensing to estimate groundwater flux. *Water Resources Research*, 57, e2020WR027228, 2021.
- Dentz, M., Le Borgne, T., Englert, A., and Bijeljic, B. Mixing, spreading and reaction in heterogeneous media: A brief review. *Journal of contaminant hydrology*, 120, 1-17, 2011.
- des Tombe, B. F., Bakker, M., Smits, F., Schaars, F., and van der Made, K.-J. Estimation of the variation in specific discharge over large depth using distributed temperature sensing (DTS) measurements of the heat Pulse response. *Water Resources*
- 975 *Research*, 55, 811-826, 2019.
- Devlin, J.F. *Groundwater Velocity. The Groundwater Project*, Guelph, Ontario, Canada, 2020.

- Diem, S., O. A. Cirpka, and M. Schirmer. Modeling the dynamics of oxygen consumption upon riverbank filtration by a stochastic-convective approach (vol505, pg 352, 2013), *J Hydrol*, 509, 631-631, 2014.
- Dillon, P., Stuyfzand, P., Grischek, T., Lluria, M., Pyne, R. D. G., Jain, R. C., et al. Sixty years of global progress in managed
980 aquifer recharge. *Hydrogeology Journal*, 27(1), 1–30, 2019. <https://doi.org/10.1007/s10040-018-1841-z>
- Doetsch, J., Linde, N., Coscia, I., Greenhalgh, S. A., and Green, A. G. Zonation for 3D aquifer characterization based on joint inversions of multimethod crosshole geophysical data. *Geophysics*, 75(6), G53-G64, 2010.
- Doetsch, J., Linde, N., Vogt, T., Binley, A., and Green, A. G. Imaging and quantifying salt-tracer transport in a riparian groundwater system by means of 3D ERT monitoring. *Geophysics*, 77(5), B207-B218, 2012.
- 985 Dorn C., Linde N., Le Borgne T., O. Bour and L. Baron. Single-hole GPR reflection imaging of solute transport in a granitic aquifer, *Geophysical Research Letters*, Vol.38, L08401, 2011.
- Dorn, C., Linde, N., Doetsch, J., Le Borgne, T., Bour, O. Fracture imaging within a granitic rock aquifer using multiple-offset single-hole and cross-hole GPR reflection data, *Journal of Applied Geophysics*, 78, 123-132, 2012a.
- Dorn, C., Linde, N., Le Borgne, T., Bour, O., and de Dreuzy, J. R. Conditioning of stochastic 3-D fracture networks to
990 hydrological and geophysical data. *Adv Water Resour*, 62, 79-89, 2013. doi:
<https://doi.org/10.1016/j.advwatres.2013.10.005>
- Dorn, C., Linde, N., Le Borgne, T., Bour, O., and Klepikova, M. Inferring transport characteristics in a fractured rock aquifer by combining single-hole ground-penetrating radar reflection monitoring and tracer test data. *Water Resources Research*, 48(11), W11521, 2012b.
- 995 Drost, W., Klotz, D., Koch, A., Moser, H., Neumaier, F., Rauert, W. Point dilution methods of investigating ground water flow by means of radioisotopes. *Water Resour. Res.* 4 (1), 125–146, 1968.
- Dudley-Southern, M., and A. Binley. Temporal responses of groundwater-surface water exchange to successive storm events, *Water Resour Res*, 51(2), 1112-1126, 2015.
- [Duque, C., Jessen, S., Tirado-Conde, J., Karan, S., Engesgaard, P. Application of stable isotopes of water to study coupled
1000 submarine groundwater discharge and nutrient delivery. *Water*, 11, 1842, 2019. doi: 10.2290/w11091842](#)
- Ehosioko, S., Nguyen, F., Rao, S., Kremer, T., Placencia-Gomez, E., Huisman, J. A., et al. Sensing the electrical properties of roots: A review. *Vadose Zone Journal*, 19(1), e20082, 2020. <https://doi.org/10.1002/vzj2.20082>
- Erostate, M., Huneau, F., Garel, E., Ghiotti, S., Vystavna, Y., Garrido, M., and Pasqualini, V. Groundwater dependent ecosystems in coastal Mediterranean regions: Characterization, challenges and management for their protection. *Water
1005 Research*, 172, 115461, 2020. <https://doi.org/10.1016/j.watres.2019.115461>
- Ewing, R. C. Long-term storage of spent nuclear fuel. *Nature Materials*, 14(3), 252–257, 2015. <https://doi.org/10.1038/nmat4226>
- Fan, Y., Grant, G., and Anderson, S. P. Water within, moving through, and shaping the Earth's surface: Introducing a special issue on water in the critical zone. *Hydrological Processes*, 33(25), 3146-3151, 2019.

- 1010 Fattorini, S., Fiasca, B., Di Lorenzo, T., Di Cicco, M., and Galassi, D. M. P. A new protocol for assessing the conservation priority of groundwater-dependent ecosystems. *Aquatic Conservation: Marine and Freshwater Ecosystems*, 30(8), 1483–1504, 2020. <https://doi.org/10.1002/aqc.3411>
- Fernandez Visentini, A., N. Linde, T. Le Borgne, M. Dentz. Inferring geostatistical properties of hydraulic conductivity fields from saline tracer tests and equivalent electrical conductivity time-series. *Advances in Water Resources*, 146, 103758, 1015 2020.
- Fernandez Visentini, A., de Anna, P., Jougnot, D. Le Borgne T., Méheust Y. and Linde N. Electrical Signatures of Diffusion-Limited Mixing: Insights from a Milli-fluidic Tracer Experiment. *Transp Porous Med.*, 2021. <https://doi.org/10.1007/s11242-021-01607-0>
- Ferre, T. P. A. Revisiting the Relationship Between Data, Models, and Decision-Making. *Groundwater*, 55(5), 604–614, 2017. 1020 <https://doi.org/10.1111/gwat.12574>
- Ferre, T. P. A. Being Bayesian: Discussions from the Perspectives of Stakeholders and Hydrologists. *Water*, 12(2), 461, 2020. <https://doi.org/10.3390/w12020461>
- Fleckenstein, J. H., R. G. Niswonger, and G. E. Fogg. River-aquifer interactions, geologic heterogeneity, and low-flow management, *Ground Water*, 44(6), 837-852, 2006.
- 1025 Fleckenstein, J. H., S. Krause, D. M. Hannah, and F. Boano. Groundwater-surface water interactions: New methods and models to improve understanding of processes and dynamics, *Adv Water Resour*, 33(11), 1291-1295, 2010.
- Fleuchaus, P., Godschalk, B., Stober, I., and Blum, P. Worldwide application of aquifer thermal energy storage – A review. *Renewable and Sustainable Energy Reviews*, 94, 861–876, 2018. <https://doi.org/10.1016/j.rser.2018.06.057>
- Flores Orozco, A., A. Kemna, C. Oberdörster, L. Zschornack, C. Leven, P. Dietrich, and H. Weiss. Delineation of subsurface 1030 hydrocarbon contamination at a former hydrogenation plant using spectral induced polarization imaging *J. Contam. Hydrol.* 136–137, 131, 2012.
- Flores Orozco, A., Ciampi, P., Katona, T., Censini, M., Petrangeli Papini, M., Deidda, 507 G.P., Cassiani, G. Delineation of hydrocarbon contaminants with multi-frequency complex conductivity imaging. *Science of the Total Environment*, 768, 144997, 2021.
- 1035 Folch, A., del Val, L., Luquot, L., Martínez-Pérez, L., Bellmunt, F., Le Lay, H., et al. Combining fiber optic DTS, cross-hole ERT and time-lapse induction logging to characterize and monitor a coastal aquifer. *Journal of Hydrology*, 588, 125050, 2020.
- Fores B., C. Champollion, N. Le Moigne, R. Bayer, J. Chéry. Assessing the precision of the iGrav superconducting gravimeter for hydrological models and karstic hydrological process identification, *Geophysical Journal International*, 208, 269–280, 1040 2017. <https://doi.org/10.1093/gji/ggw396>
- Fores, B., Champollion, C., Mainsant, G., Albaric, J., and Fort, A. Monitoring saturation changes with ambient seismic noise and gravimetry in a karst environment. *Vadose Zone Journal*, 17(1), 1-12, 2018.

- Frei, S., J. H. Fleckenstein, S. J. Kollet, and R. M. Maxwell. Patterns and dynamics of river-aquifer exchange with variably-saturated flow using a fully-coupled model, *J Hydrol*, 375(3-4), 383-393, 2009.
- 1045 Frei, S., Knorr, K. H., Peiffer, S., and Fleckenstein, J. H. Surface micro-topography causes hot spots of biogeochemical activity in wetland systems: A virtual modeling experiment. *Journal of Geophysical Research: Biogeosciences*, 117(G4), G00N12, 2012. <https://doi.org/10.1029/2012JG002012>
- Garambois, S., Voisin, C., Romero Guzman, M. A., Brito, D., Guillier, B., and Réfloch, A. Analysis of ballistic waves in seismic noise monitoring of water table variations in a water field site: added value from numerical modelling to data understanding. *Geophysical Journal International*, 219(3), 1636-1647, 2019.
- 1050 Ghosh, U., Borgne, T. L., Jougnot, D., Linde, N., and Méheust, Y. Geoelectrical signatures of reactive mixing: a theoretical assessment. *Geophysical Research Letters*, 45(8), 3489-3498, 2018.
- [Ghysels, G., Anibas, C., Awol, H., Tolche, A., Schneidewind, U., and Huysmans, M. The Significance of Vertical and Lateral Groundwater–Surface Water Exchange Fluxes in Riverbeds and Riverbanks: Comparing 1D Analytical Flux Estimates with 3D Groundwater Modelling. *Water*, 13\(3\), 306, 2021. https://doi.org/10.3390/w13030306](https://doi.org/10.3390/w13030306)
- 1055 [Gianni, G., Doherty, J., and Brunner, P. Conceptualization and Calibration of Anisotropic Alluvial Systems: Pitfalls and Biases. *Groundwater*, 57\(3\), 409-419, 2018.](https://doi.org/10.3390/w13030306)
- Glaser, B., J. Klaus, S. Frei, J. Frentress, L. Pfister, and L. Hopp. On the value of surface saturated area dynamics mapped with thermal infrared imagery for modeling the hillslope-riparian-stream continuum, *Water Resour Res*, 52(10), 8317-8342, 1060 2016.
- Godemiaux, P., Davy, P., Bresciani, E., De Dreuzy, J.R., [and](#) Le Borgne, T. Partitioning a regional groundwater flow system into shallow local and deep regional flow compartments. *Water Resour. Res.* 49, 2274–2286, 2013.
- [Gomez-Velez, J. D., and J. W. Harvey. A hydrogeomorphic river network model predicts where and why hyporheic exchange is important in large basins, *Geophys Res Lett*, 41\(18\), 6403–6412, 2014. Gottschalk, I., and Knight, R. The development of a machine-learning approach to construct a field-scale rock-physics transform. *Geophysics*, 87\(2\), MR35–MR48, 2022. https://doi.org/10.1190/geo2020-0811.1](https://doi.org/10.1190/geo2020-0811.1)
- 1065 [Gouze, P., Melean, Y., Le Borgne, T., Dentz, M., and Carrera, J. Non-Fickian dispersion in porous media explained by heterogeneous microscale matrix diffusion. *Water Resources Research*, 44\(11\), WR006690, 2008. https://doi.org/10.1029/2007WR006690](https://doi.org/10.1190/geo2020-0811.1)
- 1070 Gramling, C. M., Harvey, C. F., and Meigs, L. C. Reactive transport in porous media: A comparison of model prediction with laboratory visualization. *Environmental science and technology*, 36(11), 2508-2514, 2002.
- Grobbe, N., Mordret, A., Barde-Cabusson, S., Ellison, L., Lach, M., Seo, Y.-H., et al. A multi-hydrogeophysical study of a watershed at Kaiwi Coast (O’ahu, Hawai’i), using seismic ambient noise surface wave tomography and self-potential data. *Water Resources Research*, 57, e2020WR029057, 2021.
- 1075 Gu, C., Anderson, W., and Maggi, F. Riparian biogeochemical hot moments induced by stream fluctuations. *Water Resources Research*, 48(9), W09546, 2012. <https://doi.org/10.1029/2011WR011720>

- Gueting, N., Klotzsche, A., van der Kruk, J., Vanderborght, J., Vereecken, H., & Englert, A. Imaging and characterization of facies heterogeneity in an alluvial aquifer using GPR full-waveform inversion and cone penetration tests, *Journal of hydrology*, 524, 680-695, 2015.
- 1080 Gueting, N., Vienken, T., Klotzsche, A., van der Kruk, J., Vanderborght, J., Caers, J., et al. High resolution aquifer characterization using crosshole GPR full-waveform tomography: Comparison with direct-push and tracer test data. *Water Resources Research*, 53(1), 49–72, 2017. <https://doi.org/10.1002/2016WR019498>
- Guihéneuf, N., Bour, O., Boisson, A., Le Borgne, T., Becker, M. W., Nigon, B., et al. Insights about transport mechanisms and fracture flow channeling from multi-scale observations of tracer dispersion in shallow fractured crystalline rock. *Journal of contaminant hydrology*, 206, 18-33, 2017.
- 1085 Guillaume, J.H.A., Jakeman, J.D., Marsii-Libelli S., Asher, M., Brunner P., Croke, B., Hill M.C., Jakeman, A.J., Keesman, K.J., Razavi, S., Stigter J.D. Introductory overview of identifiability analysis: A guide to evaluating whether you have the right type of data for your modeling purpose. *Environmental Modelling and Software*, 119, 418-432, 2019.
- Haarder, E. B., Jensen, K. H., Binley, A., Nielsen, L., Uglebjerg, T. B., and Looms, M. C. Estimation of recharge from long-term monitoring of saline tracer transport using electrical resistivity tomography. *Vadose Zone Journal*, 14(7), 1-13, 2015.
- 1090 Hamza, A., Hussein, I. A., Al-Marri, M. J., Mahmoud, M., Shawabkeh, R., and Aparicio, S. CO2 enhanced gas recovery and sequestration in depleted gas reservoirs: A review. *Journal of Petroleum Science and Engineering*, 196, 107685, 2021. <https://doi.org/10.1016/j.petrol.2020.107685>
- Hartmann, A., Gleeson, T., Wada, Y., and Wagener, T. Enhanced groundwater recharge rates and altered recharge sensitivity to climate variability through subsurface heterogeneity. *Proceedings of the National Academy of Sciences of the United States of America*, 114(11), 2842–2847, 2017. <https://doi.org/10.1073/pnas.1614941114>
- 1095 Haruzi, P., Schmäck, J., Zhou, Z., van der Kruk, J., Vereecken, H., Vanderborght, J., Klotzsche, A. [Detection of tracer plumes using full-waveform inversion of time-lapse ground penetrating radar data: a numerical study in a high-resolution aquifer model. *Water Resources Research*, e2021WR030110, 2022. <https://doi.org/10.1029/2021WR030110>. ~~Detection of tracer plumes using full-waveform inversion of time-lapse ground penetrating radar data: a numerical study in a high-resolution aquifer model, *Water Resources Research*, 2022, in review.~~](https://doi.org/10.1029/2021WR030110)
- 1100 Hatfield, K., Annable, M., Cho, J., Rao, P.S.C., Klammler, H. A direct passive method for measuring water and contaminant fluxes in porous media. *J. Cont. Hydrol.* 75, 155–181, 2004.
- Hayley, K. The Present State and Future Application of Cloud Computing for Numerical Groundwater Modeling. *Groundwater*, 55(5), 678–682, 2017. <https://doi.org/10.1111/gwat.12555>
- 1105 Hayley, K., Schumacher, J., MacMillan, G.J., Boutin, L.C. Highly parameterized model calibration with cloud computing: an example of regional flow model calibration in northeast Alberta, Canada. *Hydrogeology Journal*, 22, 729-737, 2014.
- Hermans, T., Kemna, A., and Nguyen, F. Covariance-constrained difference inversion of time-lapse electrical resistivity tomography data. *Geophysics*, 81(5), E311–E322, 2016a. <https://doi.org/10.1190/geo2015-0491.1>

- 1110 Hermans, T., Lesparre, N., De Schepper, G., and Robert, T. Bayesian evidential learning: a field validation using push-pull tests. *Hydrogeology Journal*, 27(5), 1661–1672, 2019. <https://doi.org/10.1007/s10040-019-01962-9>
- Hermans, T., Nguyen, F., Klepikova, M., Dassargues, A., and Caers, J. Uncertainty quantification of medium-term heat storage from short-term geophysical experiments using Bayesian Evidential Learning. *Water Resources Research*, 54, 2931–2948, 2018. <https://doi.org/10.1002/2017WR022135>
- 1115 Hermans, T., Oware, E. K., and Caers, J. Direct prediction of spatially and temporally varying physical properties from time-lapse electrical resistance data. *Water Resources Research*, 52, 7262–7283, 2016b.
- Hermans, T., Wildemeersch, S., Jamin, P., Orban, P., Brouyère, S., Dassargues, A., Nguyen, F. Quantitative temperature monitoring of a heat tracing experiment using cross-borehole ERT. *Geothermics* 53, 14–26, 2015b. <https://doi.org/10.1016/j.geothermics.2014.03.013>
- 1120 Hermans, Thomas, Nguyen, F., and Caers, J. Uncertainty in training image-based inversion of hydraulic head data constrained to ERT data: Workflow and case study. *Water Resources Research*, 51(7), 5332–5352, 2015a. <https://doi.org/10.1002/2014WR016460>
- Hester, E. T., and M. N. Gooseff. Moving Beyond the Banks: Hyporheic Restoration Is Fundamental to Restoring Ecological Services and Functions of Streams, *Environ Sci Technol*, 44(5), 1521-1525, 2010.
- 1125 Hester, E. T., K. E. Brooks, and D. T. Scott Comparing reach scale hyporheic exchange and denitrification induced by instream restoration structures and natural streambed morphology, *Ecol Eng*, 115, 105-121, 2018.
- Hester, E. T., M. B. Cardenas, R. Haggerty, and S. V. Apte. The importance and challenge of hyporheic mixing, *Water Resour Res*, 53(5), 3565-3575, 2017.
- Heyman, J., Lester, D. R., Turuban, R., Méheust, Y., and Le Borgne, T. Stretching and folding sustain microscale chemical gradients in porous media. *Proceedings of the National Academy of Sciences*, June 2016, 117(24), 13359-13365, 2020.
- 1130 Hinnell, A. C., Ferré, T. P. A., Vrugt, J. A., Huisman, J. A., Moysey, S., Rings, J., and Kowalsky, M. B. Improved extraction of hydrologic information from geophysical data through coupled hydrogeophysical inversion. *Water Resources Research*, 46, W00D40, 2010. <https://doi.org/10.1029/2008WR007060>
- Hoffmann, R., Dassargues, A., Goderniaux, P., and Hermans, T. Heterogeneity and prior uncertainty investigation using a joint heat and solute tracer experiment in alluvial sediments. *Frontiers in Earth Sciences - Hydrosphere*, 7, 108, 2019.
- 1135 Hoffmann, R., Goderniaux, P., Jamin, P., Chatton, E., de La Bernardie, J., Labasque, T., Le Borgne, T., Dassargues, A., Continuous dissolved gas tracing of fracture-matrix exchanges. *Geophysical Research Letters*, 47, e2020GL088944, 2020.
- Hoffmann, R., Maréchal, J.C., Selles, A., Dassargues, A., Goderniaux, P. Heat tracing in a fractured aquifer with injection of hot and cold water, *Groundwater*, 2021b. <https://doi.org/10.1111/gwat.13138>
- 1140 Hoffmann, R., Goderniaux, P., Jamin, P., Orban, P., Brouyère, S., Dassargues, A.. Differentiated influence of the double porosity of the chalk on solute and heat transport. In: Farrell, R. P., Massei, N., Foley, A. E., Howlett, P. R. and West, L. J. (eds) *The Chalk Aquifers of Northern Europe*. Geological Society, London, Special Publications, 517, 2021a. <https://doi.org/10.1144/SP517-2020-170>.

- Holm-Jensen, T., and Hansen, T. M. Linear Waveform Tomography Inversion Using Machine Learning Algorithms. *Mathematical Geosciences*, 52, 31-50, 2019. <https://doi.org/10.1007/s11004-019-09815-7>
- 1145 Hu, K., Jougnot, D., Huang, Q., Looms, M.C., and Linde, N. Advancing quantitative understanding of self-potential signatures in the critical zone through long-term monitoring, *Journal of Hydrology*, 585, 124771, 2020. <https://doi.org/10.1016/j.jhydrol.2020.124771>.
- Hubbard, S. S., and Linde, N. Hydrogeophysics. In: *Treatise on Water Science* (Ed.: Peter Wilderer), Vol 2, Elsevier, 2011.
- 1150 Huisman, J. A., Hubbard, S. S., Redman, J. D., and Annan, A. P. Measuring soil water content with ground penetrating radar: A review. *Vadose zone journal*, 2(4), 476-491, 2003.
- Icardi, M., Boccardo, G., and Dentz, M. Upscaling Flow and Transport Processes. In F. Toschi and M. Sega (Eds.), *Flowing Matter* (pp. 137–176). Cham: Springer International Publishing, 2019. https://doi.org/10.1007/978-3-030-23370-9_5
- Irvine, D. J., P. Brunner, H. J. H. Franssen, and C. T. Simmons. Heterogeneous or homogeneous? Implications of simplifying heterogeneous streambeds in models of losing streams, *J Hydrol*, 424, 16-23, 2012.
- 1155 Izumoto, S., Huisman, J. A., Wu, Y., and Vereecken, H. Effect of solute concentration on the spectral induced polarization response of calcite precipitation. *Geophysical Journal International*, 220(2), 1187-1196, 2020.
- Izumoto, S., Huisman, J.A., Zimmermann, E., Heyman, J., Gomez, F., Tabuteau, H., Laniel, R., Vereecken, H., Méheust, Y., and Le Borgne, T., Pore-Scale Mechanisms for Spectral Induced Polarization of Calcite Precipitation Inferred from Geo-
Electrical Millifluidics. *Environmental Science & Technology*, 56(8), pp.4998-5008, 2022.
- 1160 Jamin, P., Brouyère, S. Monitoring transient groundwater fluxes using the Finite Volume Point Dilution Method. *Journal of Contaminant Hydrology* 218, 10-18, 2018.
- Jamin, P., Goderniaux, P., Bour, O., Le Borgne, T., Englert, A., Longuevergne, L., Brouyère, S. Contribution of the finite volume point dilution method for measurement of groundwater fluxes in a fractured aquifer. *Journal of Contaminant Hydrology* 182, 244–255, 2015. <https://doi.org/10.1016/j.jconhyd.2015.09.002>
- 1165 Jardani, A., Revil, A., and Dupont, J. P. Stochastic joint inversion of hydrogeophysical data for salt tracer test monitoring and hydraulic conductivity imaging. *Advances in water resources*, 52, 62-77, 2013.
- Jasechko, S., Seybold, H., Perrone, D., Fan, Y., and Kirchner, J. W. Widespread potential loss of streamflow into underlying aquifers across the USA. *Nature*, 591(7850), 391–395, 2021. <https://doi.org/10.1038/s41586-021-03311-x>
- 1170 [Johansson, S., Rossi, M., Hall, S. A., Sparrenbom, C., Hagerberg, D., Tudisco, E., et al. Combining spectral induced polarization with X-ray tomography to investigate the importance of DNAPL geometry in sand samples. *Geophysics*, 84\(3\), E173–E188, 2019. https://doi.org/10.1190/geo2018-0108.1](https://doi.org/10.1190/geo2018-0108.1)
- Jiménez-Martínez J., L. Longuevergne, T. Le Borgne, P. Davy, A. Russian, and O. Bour. Temporal and spatial scaling of hydraulic response to recharge in fractured aquifers: Insights from a frequency domain analysis, *Water Resour. Res.*, 49, 2013. doi:10.1002/wrcr.20260.
- 1175

- Jiménez-Martínez, J., Le Borgne, T., Tabuteau, H., and Méheust, Y. Impact of saturation on dispersion and mixing in porous media: Photobleaching pulse injection experiments and shear-enhanced mixing model. *Water Resources Research*, 53(2), 1457-1472, 2017.
- Johnson, T. C., Slater, L. D., Ntarlagiannis, D., Day-Lewis, F. D., and Elwaseif, M. Monitoring groundwater-surface water interaction using time-series and time-frequency analysis of transient three-dimensional electrical resistivity changes. *Water Resources Research*, 48(7), W07506, 2012. <https://doi.org/10.1029/2012WR011893>
- Jougnot, D., Jiménez-Martínez, J., Legendre, R., Le Borgne, T., Méheust, Y., and Linde, N. Impact of small-scale saline tracer heterogeneity on electrical resistivity monitoring in fully and partially saturated porous media: Insights from geoelectrical milli-fluidic experiments. *Advances in Water Resources*, 113, 295-309, 2018.
- Jougnot, D., Linde, N., Haarder, E. B., and Looms, M. C. Monitoring of saline tracer movement with vertically distributed self-potential measurements at the HOBE agricultural test site, Voulund, Denmark. *Journal of Hydrology*, 521, 314-327, 2015.
- Jougnot, D., Roubinet, D., Guarracino, L., and Maineult, A. Modeling streaming potential in porous and fractured media, description and benefits of the effective excess charge density approach. In *Advances in Modeling and Interpretation in Near Surface Geophysics* (pp. 61-96). Springer, Cham, 2020.
- Kalbus, E., C. Schmidt, J. W. Molson, F. Reinstorf, and M. Schirmer Influence of aquifer and streambed heterogeneity on the distribution of groundwater discharge, *Hydrol Earth Syst Sc*, 13(1), 69-77, 2009.
- Kang, P. K., Le Borgne, T., Dentz, M., Bour, O., and Juanes, R. Impact of velocity correlation and distribution on transport in fractured media: Field evidence and theoretical model. *Water Resources Research*, 51(2), 940-959, 2015.
- Karaoulis, M., Tsourlos, P., Kim, J.-H., and Revill, A. 4D time-lapse ERT inversion: Introducing combined time and space constraints. *Near Surface Geophysics*, 12(1), 25–34, 2014. <https://doi.org/10.3997/1873-0604.2013004>
- Karatzas, G. P. Developments on Modeling of Groundwater Flow and Contaminant Transport. *Water Resources Management*, 31(10), 3235–3244, 2017. <https://doi.org/10.1007/s11269-017-1729-z>
- Kemna, A., Binley, A., Cassiani, G., Niederleithinger, E., Revil, A., Slater, L., et al. An overview of the spectral induced polarization method for near-surface applications. *Near Surface Geophysics*, 10(1957), 453–468, 2012. <https://doi.org/10.3997/1873-0604.2012027>
- Kemna, A., Kulessa, B., and Vereecken, H. Imaging and characterisation of subsurface solute transport using electrical resistivity tomography (ERT) and equivalent transport models. *Journal of Hydrology*, 267(3–4), 125–146, 2002.
- Kennedy, J., Ferré, T. P., and Creutzfeldt, B. Time-lapse gravity data for monitoring and modeling artificial recharge through a thick unsaturated zone. *Water Resources Research*, 52(9), 7244-7261, 2016.
- Keranen, K. M., and Weingarten, M. Induced Seismicity, *Annual Review of Earth and Planetary Sciences*. 46, 149-174, 2018. <https://doi.org/10.1146/annurev-earth-082517-010054>
- Kessouri, P., A. Furman, J.A. Huisman, T. Martin, A. Mellage, D. Ntarlagiannis, M. Bucker, S. Ehosioke, P. Fernandez, A. Flores-Orozco, A. Kemna, F. Nguyen, T. Pilawski, S. Saneiyani, M. Schmutz, N. Schwartz, M. Weigand, Y. Wu, C. Zhang,

- 1210 and E. Placencia-Gomez. Induced polarization applied to biogeophysics: recent advances and future prospects. *Near Surf. Geophys.* 17, 595, 2019.
- Kitanidis, P. K., and McCarty, P. L. (Eds.). *Delivery and Mixing in the Subsurface: Processes and Design Principles for in Situ remediation* (Vol. 4). Springer Science and Business Media, 2012.
- Klepikova, M., Wildemeersch, S., Hermans, T., Jamin, P., Orban, P., Nguyen, F., Brouyère, S., Dassargues, A. Heat tracer test
1215 in an alluvial aquifer: Field experiment and inverse modelling. *Journal of Hydrology* 540, 812–823, 2016.
<https://doi.org/10.1016/j.jhydrol.2016.06.066>
- Klotz, D., Seiler, K.P., Moser, H., Neumaier, F. Dispersivity and velocity relationship from laboratory and field experiments. *J. Hydrol.* 45 (3–4), 169–184, 1980.
- Knapp, J. L. A., and O. A. Cirpka. Determination of hyporheic travel time distributions and other parameters from concurrent
1220 conservative and reactive tracer tests by local-in-global optimization, *Water Resour Res*, 53(6), 4984–5001, 2017.
- Knapp, J. L., González-Pinzón, R., Drummond, J. D., Larsen, L. G., Cirpka, O. A., and Harvey, J. W. Tracer-based characterization of hyporheic exchange and benthic biolayers in streams. *Water Resources Research*, 53(2), 1575–1594, 2017.
- Knight, R., Pyrak-Nolte, L. J., Slater, L., Atekwana, E., Endres, A., Geller, J. et al. Geophysics at the interface: Response of
1225 geophysical properties to solid-fluid, fluid-fluid, and solid-solid interfaces. *Reviews of Geophysics*, 48(4), RG4002, 2010.
- Köpke, C., Irving, J., and Elsheikh, A. H. Accounting for model error in Bayesian solutions to hydrogeophysical inverse problems using a local basis approach. *Advances in Water Resources*, 116, 195–207, 2018.
<https://doi.org/10.1016/j.advwatres.2017.11.013>
- Krause, S., T. Blume, and N. J. Cassidy. Investigating patterns and controls of groundwater up-welling in a lowland river by
1230 combining Fibre-optic Distributed Temperature Sensing with observations of vertical hydraulic gradients, *Hydrol Earth Syst Sc*, 16(6), 1775–1792, 2012.
- Kumar, S., Foroozesh, J., Edlmann, K., Rezk, M. G., and Lim, C. Y. A comprehensive review of value-added CO2 sequestration in subsurface saline aquifers. *Journal of Natural Gas Science and Engineering*, 81, 103437, 2020.
<https://doi.org/10.1016/j.jngse.2020.103437>
- 1235 Kurtz, W., Lapin, A., Schilling, O. S., Tang, Q., Schiller, E., Braun, T., et al. Integrating hydrological modelling, data assimilation and cloud computing for real-time management of water resources. *Environmental Modelling and Software*, 93, 418–435, 2017. <https://doi.org/10.1016/j.envsoft.2017.03.011>
- Labaky, W., J. F. Devlin, and R. W. Gillham. Field comparison of the point velocity probe with other groundwater velocity measurement methods, *Water Resour. Res.*, 45, W00D30, 2009. doi:10.1029/2008WR007066
- 1240 Laloy, E., Héroult, R., Jacques, D., and Linde, N. Training-Image Based Geostatistical Inversion Using a Spatial Generative Adversarial Neural Network. *Water Resources Research*, 54(1), 381–406, 2018. <https://doi.org/10.1002/2017WR022148>
- Laube, G., C. Schmidt, and J. H. Fleckenstein. The systematic effect of streambed conductivity heterogeneity on hyporheic flux and residence time, *Adv Water Resour*, 122, 60–69, 2018.

- Le Borgne, T., Bour, O., Paillet, F.L., Caudal, J.-P. Assessment of preferential flow path connectivity and hydraulic properties at single-borehole and cross-borehole scales in a fractured aquifer. *Journal of Hydrology* 328, 347–359, 2006. <https://doi.org/10.1016/j.jhydrol.2005.12.029>
- Lee, A., Aubeneau, A., Liu, X., and Cardenas, M. B. Hyporheic exchange in sand dunes under a freely deforming river water surface. *Water Resources Research*, 57, e2020WR028817, 2021. <https://doi.org/10.1029/2020WR028817>
- Le Goc, R., Darcel, C., and Davy, P. Advanced DFN models from multi-support data for underground facilities. *Procedia engineering*, 191, 1015-1022, 2017. doi: <https://doi.org/10.1016/j.proeng.2017.05.274>
- Léger, E., Saintenoy, A., and Coquet, Y. Hydrodynamic parameters of a sandy soil determined by ground-penetrating radar inside a single ring infiltrometer. *Water Resources Research*, 50(7), 5459-5474, 2014.
- Lei, Q., Latham, J.-P., and Tsang, C.-F. The use of discrete fracture networks for modelling coupled geomechanical and hydrological behaviour of fractured rocks. *Comput. Geotech.*, 85, 151-176, 2017.
- 1255 Leroy, P., Li, S., Jougnot, D., Revil, A., and Wu, Y. Modelling the evolution of complex conductivity during calcite precipitation on glass beads. *Geophysical Journal International*, 209(1), 123-140, 2017.
- Lesparre, N., Girard, J.-F., Jeannot, B., Weill, S., Dumont, M., Boucher, M., et al. Magnetic resonance sounding dataset of a hard-rock headwater catchment for assessing the vertical distribution of water contents in the subsurface. *Data in Brief*, 31, 105708, 2020. <https://doi.org/10.1016/j.dib.2020.105708>
- 1260 Lester, D. R., Metcalfe, G., and Trefry, M. G. Is chaotic advection inherent to porous media flow?. *Physical review letters*, 111(17), 174101, 2013.
- Lewandowski, J., K. Meinikmann, T. Ruhtz, F. Poschke, and G. Kirillin. Localization of lacustrine groundwater discharge (LGD) by airborne measurement of thermal infrared radiation, *Remote Sens Environ*, 138, 119-125, 2013.
- Lewandowski, J., Arnon, S., Banks, E., Batelaan, O., Betterle, A., Broecker, T., Coll, C., Drummond, J. D., Gaona Garcia, J., Galloway, J., Gomez-Velez, J., Grabowski, R. C., Herzog, S. P., Hinkelmann, R., Höhne, A., Hollender, J., Horn, M. A., Jaeger, A., Krause, S. et al. Is the Hyporheic Zone Relevant beyond the Scientific Community? *Water*, 11(11), 2230, 2019. <https://doi.org/10.3390/w11112230>
- 1265
- Li, B., Liu, X., Kaufman, M. H., Turetaia, A., Chen, X., and Cardenas, M. B. Flexible and modular simultaneous modeling of flow and reactive transport in rivers and hyporheic zones. *Water Resources Research*, 56, e2019WR026528, 2020. <https://doi.org/10.1029/2019WR026528>
- 1270
- Li, L., Maher, K., Navarre-Sitchler, A., Druhan, J., Meile, C., Lawrence, C. et al. Expanding the role of reactive transport models in critical zone processes. *Earth-science reviews*, 165, 280-301, 2017.
- Li, L., Steefel, C. I., Kowalsky, M. B., Englert, A., and Hubbard, S. S. Effects of physical and geochemical heterogeneities on mineral transformation and biomass accumulation during biostimulation experiments at Rifle, Colorado. *Journal of contaminant hydrology*, 112(1-4), 45-63, 2010.
- 1275
- Linde, N., and Doetsch, J. Joint inversion in hydrogeophysics and near-surface geophysics. In: *Integrated imaging of the Earth: Theory and applications* (Eds. M. Moorkamp, P. Lelievre, N. Linde, and A. Khan), 218, 119-135, 2016.

- Linde, N., Ginsbourger, D., Irving, J., Nobile, F., and Doucet, A. On uncertainty quantification in hydrogeology and hydrogeophysics. *Advances in Water Resources*, 110, 166–181, 2017. <https://doi.org/10.1016/j.advwatres.2017.10.014>
- 1280 Linde, N., Lochbühler, T., Dogan, M., and Van Dam, R. L. Tomogram-based comparison of geostatistical models: Application to the Macrodispersion Experiment (MADE) site. *Journal of Hydrology*, 531, 543–556, 2015a. <https://doi.org/10.1016/j.jhydrol.2015.10.073>
- Linde, N., Renard, P., Mukerji, T., and Caers, J. Geological realism in hydrogeological and geophysical inverse modeling: A review. *Advances in Water Resources*, 86, 86–101, 2015b. <https://doi.org/10.1016/j.advwatres.2015.09.019>
- 1285 Litalien, A., and Zeeb, B. Curing the earth: A review of anthropogenic soil salinization and plant-based strategies for sustainable mitigation. *Science of the Total Environment*, 698, 134235, 2020. <https://doi.org/10.1016/j.scitotenv.2019.134235>
- Liu, Q., Charette, M. A., Henderson, P. B., McCorkle, D. C., Martin, W., and Dai, M. Effect of submarine groundwater discharge on the coastal ocean inorganic carbon cycle. *Limnology and Oceanography*, 59(5), 1529–1554, 2014. <https://doi.org/10.4319/lo.2014.59.5.1529>
- 1290 Looms, M. C., Jensen, K. H., Binley, A., & Nielsen, L. Monitoring unsaturated flow and transport using cross-borehole geophysical methods, *Vadose Zone Journal*, 7, 227-237, 2008.
- Lopez-Alvis, J., Hermans, T., Looms, M., and Nguyen, F. Geophysical inversion using a variational autoencoder to model an assembled spatial prior uncertainty. *Journal of Geophysical Research: Solid Earth*, 2022. 10.1029/2021JB022581
- 1295 Lopez-Alvis, J., Hermans, T., and Nguyen, F. (2019). A cross-validation framework to extract data features for reducing structural uncertainty in subsurface heterogeneity. *Advances in Water Resources*, 133, 103427.
- Lopez-Alvis, J., Laloy, E., Nguyen, F., and Hermans, T. Deep generative models in inversion: The impact of the generator's nonlinearity and development of a new approach based on a variational autoencoder. *Computers and Geosciences*, 152, 104762, 2021. <https://doi.org/10.1016/j.cageo.2021.104762>
- 1300 Loschko, M., Woehling, T. Rudolph, D.L., and Cirpka, O.A. Cumulative relative reactivity: A concept for modeling aquifer-scale reactive transport, *Water Resour. Res.*, 52, 8117–8137, 2016. doi:10.1002/2016WR019080.
- Lu, S.-M. A global review of enhanced geothermal system (EGS). *Renewable and Sustainable Energy Reviews*, 81, 2902–2921, 2018. <https://doi.org/10.1016/j.rser.2017.06.097>
- Luijendijk, E., Gleeson, T., and Moosdorf, N. Fresh groundwater discharge insignificant for the world's oceans but important for coastal ecosystems. *Nature Communications*, 11(1), 1260, 2020. <https://doi.org/10.1038/s41467-020-15064-8>
- 1305 Lutz, S. R., N. Trauth, A. Musolff, B. M. Van Breukelen, K. Knoller, and J. H. Fleckenstein. How Important is Denitrification in Riparian Zones? Combining End-Member Mixing and Isotope Modeling to Quantify Nitrate Removal from Riparian Groundwater, *Water Resour Res*, 56(1), 2020.
- Klotzsche, A., Jonard, F., Looms, M. C., van der Kruk, J., & Huisman, J. A. Measuring soil water content with ground penetrating radar: A decade of progress. *Vadose Zone Journal*, 17(1), 1-9, 2018.
- 1310

- Klotzsche, A., Lärm, L., Vanderborght, J., Cai, G., Morandage, S., Zörner, M., et al. Monitoring soil water content using time-lapse horizontal borehole GPR data at the field-plot scale, *Vadose zone journal*, 18(1), 190044, 2019a.
- Klotzsche, A., Vereecken, H., & van der Kruk, J. Review of crosshole ground-penetrating radar full-waveform inversion of experimental data: Recent developments, challenges, and pitfalls. *Geophysics*, 84(6), H13-H28, 2019b.
- 1315 Mahmood, M. N., C. Schmidt, J. H. Fleckenstein, and N. Trauth. Modeling the Impact of Stream Discharge Events on Riparian Solute Dynamics, *Groundwater*, 57(1), 140-152, 2019.
- Maldaner, C. H., Munn, J. D., Coleman, T. I., Molson, J. W., and Parker, B. L. Groundwater flow quantification in fractured rock boreholes using active distributed temperature sensing under natural gradient conditions. *Water Resources Research*, 55, 3285–3306, 2019.
- 1320 Maillot, J., Davy, P., Le Goc, R., Darcel, C., and de Dreuzy, J. R. Connectivity, permeability, and channeling in randomly distributed and kinematically defined discrete fracture network models. *Water Resources Research*, 52(11), 8526–8545, 2016. <https://doi.org/10.1002/2016WR018973>
- Mallard, J., B. McGlynn, and T. Covino. Lateral inflows, stream-groundwater exchange, and network geometry influence stream water composition, *Water Resour Res*, 50(6), 4603-4623, 2014.
- 1325 Mari, J.L., G. Porel and B. Bourbiaux. From 3D Seismic to 3D Reservoir Deterministic Model Thanks to Logging Data: the Case Study of a Near Surface Heterogeneous Aquifer. *Oil and Gas Science and Technology - Rev. IFP*, 64, pp. 119-131, 2009.
- Marruedo Arricibita, A. I., S. J. Dugdale, S. Krause, D. M. Hannah, and J. Lewandowski. Thermal infrared imaging for the detection of relatively warm lacustrine groundwater discharge at the surface of freshwater bodies, *J Hydrol*, 562, 281-289, 1330 2018.
- Marzadri, A., D. Tonina, and A. Bellin. Morphodynamic controls on redox conditions and on nitrogen dynamics within the hyporheic zone: Application to gravel bed rivers with alternate-bar morphology, *J Geophys Res-Biogeophys*, 117, G00N10, 2012.
- Mazzilli, N., Chalikakis, K., Carrière, S. D., and Legchenko, A. Surface Nuclear Magnetic Resonance Monitoring Reveals 1335 Karst Unsaturated Zone Recharge Dynamics during a Rain Event. *Water*, 12(11), 3183, 2020.
- McClain, M. E., Boyer, E. W., Dent, C. L., Gergel, S. E., Grimm, N. B., Groffman, P. M. et al. Biogeochemical hot spots and hot moments at the interface of terrestrial and aquatic ecosystems. *Ecosystems*, 6, 301-312, 2003.
- McCobb, T. D., Briggs, M. A., LeBlanc, D. R., Day-Lewis, F. D., and Johnson, C. D. Evaluating long-term patterns of decreasing groundwater discharge through a lake-bottom permeable reactive barrier. *Journal of environmental 1340 management*, 220, 233-245, 2018.
- McDonnell, J. J. Beyond the water balance. *Nature Geoscience*, 10(6), 396, 2017. <https://doi.org/10.1038/ngeo2964>
- McGarr, J. T., Wallace, C. D., Ntarlagiannis, D., Sturmer, D. M., and Soltanian, M. R. Geophysical mapping of hyporheic processes controlled by sedimentary architecture within compound bar deposits. *Hydrological Processes*, 35(9), e14358, 2021. <https://doi.org/10.1002/hyp.14358>

- 1345 ~~Michel, H., Nguyen, F., Kremer, T., Elen, A., and Hermans, T. 1D geological imaging of the subsurface from geophysical data with Bayesian Evidential Learning. Computers and Geosciences, 138, 104456, 2020a. <https://doi.org/10.1016/j.cageo.2020.104456>~~
- Michel, H., Nguyen, F., and Hermans, T. Improving Bayesian Evidential Learning 1D imaging (BEL1D) accuracy through iterative prior resampling. American Geophysical Union, 2020b. <https://doi.org/10.1002/essoar.10501770.1>
- 1350 ~~Michel, H., Nguyen, F., Kremer, T., Elen, A., and Hermans, T. 1D geological imaging of the subsurface from geophysical data with Bayesian Evidential Learning. Computers and Geosciences, 138, 104456, 2020a. <https://doi.org/10.1016/j.cageo.2020.104456>~~
- Mo, S., Zabarar, N., Shi, X., and Wu, J. Integration of Adversarial Autoencoders With Residual Dense Convolutional Networks for Estimation of Non-Gaussian Hydraulic Conductivities. Water Resources Research, 56(2), e2019WR026082, 2020.
- 1355 <https://doi.org/10.1029/2019WR026082>
- Molron, J., Linde, N., Baron, L., Selroos, J.-O., Darcel, C., and Davy, P. Which fractures are imaged with Ground Penetrating Radar? Results from an experiment in the Äspö Hardrock Laboratory, Sweden. Engineering Geology, 273, 105674, 2020. <https://doi.org/10.1016/j.enggeo.2020.105674>
- Molron, J., Linde, N., Davy, P., Baron, L., Darcel, C., Selroos, J.-O., Le Borgne, T. and Doolaege, D. GPR-inferred fracture aperture widening in response to a high-pressure tracer injection test at the Äspö Hard Rock Laboratory, Sweden, Eng. Geol., 292, 106249, 2021.
- 1360
- Morén, I., Worman, A., and Riml, J. Design of remediation actions for nutrient mitigation in the hyporheic zone. Water Resources Research, 53, 8872–8899, 2017. <https://doi.org/10.1002/2016WR020127>
- Moysey, S., Singha, K., and Knight, R. A framework for inferring field-scale rock physics relationships through numerical simulation. Geophysical Research Letters, 32(8), L08304, 2005. <https://doi.org/10.1029/2004GL022152>
- 1365
- Müller, K., Vanderborght, J., Englert, A., Kemna, A., Huisman, J. A., Rings, J., & Vereecken, H. Imaging and characterization of solute transport during two tracer tests in a shallow aquifer using electrical resistivity tomography and multilevel groundwater samplers. Water Resources Research, 46(3), W03502, 2010.
- Munz, M., and C. Schmidt. Estimation of vertical water fluxes from temperature time series by the inverse numerical computer program FLUX-BOT, Hydrol Process, 31(15), 2713-2724, 2017.
- 1370
- Munz, M., S. E. Oswald, and C. Schmidt. Coupled Long-Term Simulation of Reach-Scale Water and Heat Fluxes Across the River-Groundwater Interface for Retrieving Hyporheic Residence Times and Temperature Dynamics, Water Resour Res, 53(11), 8900-8924, 2017.
- Naudet, V., Revil, A., Bottero, J. Y., and Bégassat, P. Relationship between self-potential (SP) signals and redox conditions in contaminated groundwater. Geophysical research letters, 30(21), 2091, 2003.
- 1375
- Neuman, S. P., and Tartakovsky, D. M. Perspective on theories of non-Fickian transport in heterogeneous media. Advances in Water Resources, 32(5), 670-680, 2009.

- Nguyen, F., Kemna, A., Robert, T., and Hermans, T. Data-driven selection of the minimum-gradient support parameter in time-lapse focused electric imaging. *Geophysics*, 81(1), A1–A5, 2016. <https://doi.org/10.1190/GEO2015-0226.1>
- 1380 Niemi, A., Bear, J., and Bensabat, J.. Geological storage of CO₂ in deep saline formations. Dordrecht, Netherlands: Springer, 2017.
- Nogueira G., Stigter T.Y., Zhou Y., Mussa F., Juizo D. Understanding groundwater salinization mechanisms to secure freshwater resources in the water-scarce city of Maputo, Mozambique. *Science of the Total Environment* 661: 723–736, 2019: <https://doi.org/10.1016/j.scitotenv.2018.12.343>
- 1385 Nogueira, G.E.H., Schmidt, C., Brunner, P., Graeber, D. Fleckenstein, J.H. Transit-time and temperature control the spatial patterns of aerobic respiration and denitrification in the riparian zone, *Water Resources Research*, e2021WR030117, 2021a. <https://doi.org/10.1029/2021WR030117>
- Nogueira, G.E.H., Schmidt, C., Trauth, N., Fleckenstein, J.H. Seasonal and short-term controls of riparian oxygen dynamics and the implications for redox processes, *Hydrological Processes*, 25(2), e14055, 2021b. <https://doi.org/10.1002/hyp.14055>
- 1390 [Nogueira G.E.H., Schmidt C., Partington D., Brunner P., Fleckenstein J.H. Spatiotemporal variations in water sources and mixing spots in a riparian zone. *Hydrology and Earth System Sciences* 26\(7\), 1883–1905, 2022. https://doi.org/10.5194/hess-26-1883-2022](https://doi.org/10.5194/hess-26-1883-2022)
- Nowak, W. Best unbiased ensemble linearization and the quasi-linear Kalman ensemble generator. *Water Resour. Res.* 45, W04431 doi:10.1029/2008WR007328, 2009.
- 1395 Novakowski, K., Bickerton, G., Lapcevic, P., Voralek, J., Ross, N. Measurements of groundwater velocity in discrete rock fractures. *J. Contam. Hydrol.* 82 (1–2), 44–60, 2006.
- Nussbaumer R, Benoit L, Mariethoz G, Liechti F, Bauer S, Schmid B. A Geostatistical Approach to Estimate High Resolution Nocturnal Bird Migration Densities from a Weather Radar Network. *Remote Sensing*. 11(19):2233, 2019. <https://doi.org/10.3390/rs11192233>
- 1400 Oldenburg, D. W., Haber, E., and Shekhtman, R. Three dimensional inversion of multisource time domain electromagnetic data. *GEOPHYSICS*, 78(1), E47–E57, 2013. <https://doi.org/10.1190/geo2012-0131.1>
- Oware, E., Irving, J., and Hermans, T. Basis-Constrained Bayesian-MCMC Difference Inversion for Geoelectrical Monitoring of Hydrogeological Processes. *Geophysics*, 84(4), A37–A42, 2019.
- Palacios, A., Ledo, J. J., Linde, N., Luquot, L., Bellmunt, F., Folch, A., et al. Time-lapse cross-hole electrical resistivity tomography (CHERT) for monitoring seawater intrusion dynamics in a Mediterranean aquifer. *Hydrology and Earth System Sciences*, 24(4), 2121–2139, 2020. <https://doi.org/10.5194/hess-24-2121-2020>
- 1405 Palmer, C.D. Borehole dilution tests in the vicinity of an extraction well. *J.Hydrol.*, 146:245–266, 1993.
- Pannecoucke, L., Le Coz, M., Freulon, X., and de Fouquet, C. Combining geostatistics and simulations of flow and transport to characterize contamination within the unsaturated zone. *Science of the Total Environment*, 699, 134216, 2020.
- 1410 <https://doi.org/10.1016/j.scitotenv.2019.134216>

- Park, J., and Caers, J. Direct forecasting of global and spatial model parameters from dynamic data. *Computers and Geosciences*, 143, 104567, 2020. <https://doi.org/10.1016/j.cageo.2020.104567>
- Partington, D., Therrien, R., Simmons, C. T., and Brunner, P. Blueprint for a coupled model of sedimentology, hydrology, and hydrogeology in streambeds: Coupling Sedimentology, Hydrology, and Hydrogeology. *Reviews of Geophysics*, 55(2), 287–309, 2017. <https://doi.org/10.1002/2016RG000530>
- 1415 Pasquet, S., Bodet, L., Dhemaied, A., Mouhri, A., Vitale, Q., Rejiba, F. et al. Detecting different water table levels in a shallow aquifer with combined P-, surface and SH-wave surveys: Insights from VP/VS or Poisson's ratios. *Journal of Applied Geophysics*, 113, 38-50, 2015.
- Pellerin, L. Applications Of Electrical And Electromagnetic Methods For Environmental And Geotechnical Investigations. *Surveys in Geophysics* 23, 101–132, 2002. <https://doi.org/10.1023/A:1015044200567>
- 1420 Pieraccini, S. Uncertainty quantification analysis in discrete fracture network flow simulations. *GEM - International Journal on Geomathematics*, 11(1), 12, 2020. <https://doi.org/10.1007/s13137-020-0148-0>
- Pittrak, M., Mares, S., Kobr, M. A simple borehole dilution technique in measuring horizontal ground water flow. *Groundwater* 45 (1), 89–92, 2007.
- 1425 Pivetta, T., Braitenberg, C., Gabrovšek, F., Gabriel, G., and Meurers, B. Gravity as a tool to improve the hydrologic mass budget in karstic areas. *Hydrology and Earth System Sciences*, 25(11), 6001-6021, 2021.
- Pool, M., and Dentz, M. Effects of heterogeneity, connectivity, and density variations on mixing and chemical reactions under temporally fluctuating flow conditions and the formation of reaction patterns. *Water Resources Research*, 54(1), 186-204, 2018.
- 1430 Popp, A. L., Pardo-Álvarez, Á., Schilling, O. S., Scheidegger, A., Musy, S., Peel, M., et al. A Framework for Untangling Transient Groundwater Mixing and Travel Times. *Water Resources Research*, 57(4), e2020WR028362, 2021. <https://doi.org/10.1029/2020WR028362>
- Pouladi B., N. Linde, L. Longuevergne and O. Bour, Individual and joint inversion of head and flux data by geostatistical hydraulic tomography, *Advances in Water resources* 154 (2021) 103960, 2021.
- 1435 Pride, S. R. Relationships between seismic and hydrological properties. In *Hydrogeophysics* (pp. 253-290). Springer, Dordrecht, 2005.
- Rathnaweera, T. D., Wu, W., Ji, Y., and Gamage, R. P. Understanding injection-induced seismicity in enhanced geothermal systems: From the coupled thermo-hydro-mechanical-chemical process to anthropogenic earthquake prediction. *Earth-Science Reviews*, 205, 103182, 2020. <https://doi.org/10.1016/j.earscrev.2020.103182>
- 1440 Read, T., Bour, O., Bense, V., Le Borgne, T., Goderniaux, P., Klepikova, M.V., Hochreutener, R., Lavenant, N., Boschero, V. Characterizing groundwater flow and heat transport in fractured rock using fiber-optic distributed temperature sensing. *Geophysical Research Letters* 40, 2055–2059, 2013.

- Read, T., Bour, O., Selker, J.S., Bense, V.F., Le Borgne, T., Hochreutener, R., Lavenant, N. Active-distributed temperature sensing to continuously quantify vertical flow in boreholes. *Water Resources Research* 50, 3706–3713, 2014.
1445 <https://doi.org/10.1002/2014WR015273>
- Revil, A., and Jardani, A. *The self-potential method: Theory and applications in environmental geosciences*. Cambridge University Press, New York, 2013.
- Revil, A., Karaoulis, M., Johnson, T., and Kemna, A. Some low-frequency electrical methods for subsurface characterization and monitoring in hydrogeology. *Hydrogeology Journal*, 20(4), 617-658, 2012.
- 1450 Revil, A., Trolard, F., Bourrie, G., Castermant, J., Jardani, A., and Mendonça, C. A. Ionic contribution to the self-potential signals associated with a redox front. *Journal of Contaminant Hydrology*, 109(1-4), 27-39, 2009.
- Riedel, T., Weber, T.K.D. Review: The influence of global change on Europe's water cycle and groundwater recharge. *Hydrogeology Journal*, 28 (6), 1939-1959, 2020.
- Ringel, Somogyvári, Jalali, and Bayer. Comparison of Hydraulic and Tracer Tomography for Discrete Fracture Network
1455 Inversion. *Geosciences*, 9(6), 274, 2019. <https://doi.org/10.3390/geosciences9060274>
- Rivera, J. A., Blum, P., and Bayer, P. Increased ground temperatures in urban areas: Estimation of the technical geothermal potential. *Renewable Energy*, 103, 388–400, 2017. <https://doi.org/10.1016/j.renene.2016.11.005>
- Robert, T., Dassargues, A., Brouyère, S., Kaufmann, O., Hallet, V., and Nguyen, F. Assessing the contribution of electrical resistivity tomography (ERT) and self-potential (SP) methods for a water well drilling program in fractured/karstified
1460 limestones. *Journal of Applied Geophysics*, 75(1), 42–53, 2011. <https://doi.org/10.1016/j.jappgeo.2011.06.008>
- Robert, T., Caterina, D., Deceuster, J., Kaufmann, O., Nguyen, F. A salt tracer test monitored with surface ERT to detect preferential flow and transport paths in fractured/karstified limestones. *Geophysics* 77, B55–B67, 2012.
<https://doi.org/10.1190/geo2011-0313.1>
- Robinson, H. K., and Hasenmueller, E. A. Transport of road salt contamination in karst aquifers and soils over multiple
1465 timescales. *Science of the Total Environment*, 603–604, 94–108, 2017. <https://doi.org/10.1016/j.scitotenv.2017.05.244>
- Rolle, M., and Le Borgne, T. Mixing and reactive fronts in the subsurface. *Reviews in Mineralogy and Geochemistry*, 85(1), 111-142, 2019.
- Rose, L., S. Krause, and N. J. Cassidy. Capabilities and limitations of tracing spatial temperature patterns by fiber-optic distributed temperature sensing, *Water Resour Res*, 49(3), 1741-1745, 2013.
- 1470 Roth, K., Schulin, R., Flühler, H., and Attinger, W. Calibration of time domain reflectometry for water content measurement using a composite dielectric approach. *Water resources research*, 26(10), 2267-2273, 1990.
- Russo, T. A., and Lall, U. Depletion and response of deep groundwater to climate-induced pumping variability. *Nature Geoscience*, 10(2), 105–108, 2017. <https://doi.org/10.1038/ngeo2883>
- Salehikhoo, F., Li, L., and Brantley, S. L. Magnesite dissolution rates at different spatial scales: The role of mineral spatial
1475 distribution and flow velocity. *Geochimica et Cosmochimica Acta*, 108, 91-106, 2013.

- Sanford, W. E., Cook, P. G., Robinson, N. I., and Weatherill, D. Tracer mass recovery in fractured aquifers estimated from multiple well tests. *Groundwater*, 44(4), 564-573, 2006.
- Sanz-Prat, A., Lu, C., Amos, R. T., Finkel, M., Blowes, D. W., and Cirpka, O. A. Exposure-time based modeling of nonlinear reactive transport in porous media subject to physical and geochemical heterogeneity. *Journal of contaminant hydrology*, 192, 35-49, 2016.
- 1480 [Scanlon, B. R., R. C. Reedy, C. C. Faunt, D. Pool, and K. Uhlman, Enhancing drought resilience with conjunctive use and managed aquifer recharge in California and Arizona, *Environ Res Lett*, 11\(3\), 2016](#)
- Schädle, P., Zulian, P., Vogler, D., Bhopalam, S. R., Nestola, M. G. C., Ebigo, A., et al. 3D non-conforming mesh model for flow in fractured porous media using Lagrange multipliers. *Computers and Geosciences*, 132, 42–55, 2019.
- 1485 <https://doi.org/10.1016/j.cageo.2019.06.014>
- Scheidt, C., Li, L., and Caers, J. *Quantifying Uncertainty in Subsurface Systems*. Hoboken, NJ and Washington D.C.: John Wiley and Sons and American Geophysical Union, 2018.
- Schilling, O. S., C. Gerber, D. J. Partington, R. Purtschert, M. S. Brennwald, R. Kipfer, D. Hunkeler, and P. Brunner. Advancing Physically-Based Flow Simulations of Alluvial Systems Through Atmospheric Noble Gases and the Novel Ar-37 Tracer Method, *Water Resour Res*, 53(12), 10465-10490, 2017a.
- 1490
- Schilling, O. S., Irvine, D. J., Hendricks Franssen, H.-J., and Brunner, P. Estimating the spatial extent of unsaturated zones in heterogeneous river-aquifer systems. *Water Resources Research*, 53, 10,583–10,602, 2017b.
- <https://doi.org/10.1002/2017WR020409>
- Schilling, O.S., Cook, P.G., Brunner, P. Beyond classical observations in hydrogeology: The advantages of including exchange flux, temperature, tracer concentration, residence time, and soil moisture observations in groundwater model calibration. *Reviews of Geophysics*, 57, 146–182, 2018. <https://doi.org/10.1029/2018RG000619>
- 1495
- Schmidt, C., A. Musolff, N. Trauth, M. Vieweg, and J. H. Fleckenstein. Transient analysis of fluctuations of electrical conductivity as tracer in the stream bed, *Hydrol Earth Syst Sc*, 16(10), 3689-3697, 2012.
- Schmidt, C., M. Bayer-Raich, and M. Schirmer. Characterization of spatial heterogeneity of groundwater-stream water interactions using multiple depth streambed temperature measurements at the reach scale, *Hydrol Earth Syst Sc*, 10(6), 849-859, 2006.
- 1500
- Schmidt, L., and Rempe, D. Quantifying Dynamic Water Storage in Unsaturated Bedrock with Borehole Nuclear Magnetic Resonance. *Geophysical Research Letters*, 47(22), e2020GL089600, 2020.
- Scholer, M., Irving, J., Looms, M. C., Nielsen, L., and Holliger, K. Bayesian Markov-chain-Monte-Carlo inversion of time-lapse crosshole GPR data to characterize the vadose zone at the Arrenaes Site, Denmark. *Vadose Zone Journal*, 11(4), vzt2011-0153, 2012.
- 1505
- Schornberg, C., Schmidt, C., Kalbus, E., and Fleckenstein, J. H. Simulating the effects of geologic heterogeneity and transient boundary conditions on streambed temperatures — Implications for temperature-based water flux calculations. *Advances in Water Resources*, 33(11), 1309–1319, 2010. <https://doi.org/10.1016/j.advwatres.2010.04.007>


- 1510 Schultz, R., Skoumal, R. J., Brudzinski, M. R., Eaton, D., Baptie, B., and Ellsworth, W. Hydraulic fracturing-induced seismicity. *Reviews of Geophysics*, 58(3), 1–43, 2020. <https://doi.org/10.1029/2019RG000695>
- Selker, J.S., Thévenaz, L., Huwald, H., Mallet, A., Luxemburg, W., van de Giesen, N., Stejskal, M., Zeman, J., Westhoff, M., Parlange, M.B. Distributed fiber-optic temperature sensing for hydrologic systems. *Water Resources Research* 42, W12202, 2006. <https://doi.org/10.1029/2006WR005326>
- 1515 Shakas, A., and Linde, N. Apparent apertures from ground penetrating radar data and their relation to heterogeneous aperture fields. *Geophys. J. Int.*, 209(3), 1418-1430, 2017. doi: <https://doi.org/10.1093/gji/ggx100>
- Shakas, A., Linde, N., Baron, L., Bochet, O., Bour, O., and Le Borgne, T. Hydrogeophysical characterization of transport processes in fractured rock by combining push-pull and single-hole ground penetrating radar experiments. *Water Resources Research*, 52(2), 938-953, 2016.
- 1520 Shakas, A., Linde, N., Baron, L., Selker, J., Gerard, M. F., Lavenant, N. et al. Neutrally buoyant tracers in hydrogeophysics: Field demonstration in fractured rock. *Geophysical Research Letters*, 44(8), 3663-3671, 2017.
- Simon, N., Bour, O., Lavenant, N., Porel, G., Nauleau, B., Pouladi, B., Longuevergne, L. A comparison of different methods to estimate the effective spatial resolution of FO-DTS measurements achieved during sandbox experiments. *Sensors (Switzerland)* 20, 570, 2020. <https://doi.org/10.3390/s20020570>
- 1525 Simon, N., Bour, O., Lavenant, N., Porel, G., Nauleau, B., Pouladi, B., et al. Numerical and experimental validation of the applicability of active-DTS experiments to estimate thermal conductivity and groundwater flux in porous media. *Water Resources Research*, 57, e2020WR028078, 2021.
- Simon, N., Bour, O., Faucheux, M., Lavenant, N., Le Lay, H., Fovet, O., Thomas, Z., and Longuevergne, L. Combining passive- and active-DTS measurements to locate and quantify groundwater discharge into streams, *Hydrol. Earth Syst. Sci.*, 2022. <https://doi.org/10.5194/hess-2021-293>.
- Šimůnek, J., M. Šejna, and M. Th. van Genuchten, New Features of the Version 3 of the HYDRUS (2D/3D) Computer Software Package, *Journal of Hydrology and Hydromechanics*, 66(2), 133-142, 2018. doi: 10.1515/johh-2017-0050,
- Singh, A. Soil salinization management for sustainable development: A review. *Journal of Environmental Management*, 277, 111383, 2021. <https://doi.org/10.1016/j.jenvman.2020.111383>
- 1535 Singh, T., Gomez-Velez, J. D., Wu, L., Wörman, A., Hannah, D. M., and Krause, S. Effects of successive peak flow events on hyporheic exchange and residence times, *Water Resour Res*, 56, e2020WR027113, 2020.
- Singha, K., and Gorelick, S. M. Saline tracer visualized with three-dimensional electrical resistivity tomography: Field-scale spatial moment analysis. *Water Resources Research*, 41(5), W05023, 2005.
- Singha, K., Day-Lewis, F. D., Johnson, T., and Slater, L. Advances in interpretation of subsurface processes with time-lapse electrical imaging. *Hydrological Processes*, 29(6), 1549–1576, 2015.
- 1540 Slater, L., Binley, A., Versteeg, R., Cassiani, G., Birken, R., and Sandberg, S. A 3D ERT study of solute transport in a large experimental tank. *Journal of Applied Geophysics*, 49(4), 211-229, 2002.

- 1545 Song, X., Chen, X., Zachara, J. M., Gomez-Velez, J. D., Shuai, P., and Ren, H., et al. River dynamics control transit time distributions and biogeochemical reactions in a dam-regulated river corridor. *Water Resources Research*, 56, e2019WR026470, 2020.
- Souzy, M., Lhuissier, H., Méheust, Y., Le Borgne, T., and Metzger, B. Velocity distributions, dispersion and stretching in three-dimensional porous media. *Journal of Fluid Mechanics*, 891, A16, 2020. doi:10.1017/jfm.2020.113
- St. Clair, J., Moon, S., Holbrook, W. S., Perron, J. T., Riebe, C. S., Martel, S. J. et al. Geophysical imaging reveals topographic stress control of bedrock weathering. *Science*, 350(6260), 534-538., *Science*, 350, 2015.
- 1550 Stonestrom, D.A. and Constantz, J. Heat as a tool for studying the movement of ground water near streams. *US Geol Surv Circ.* 1260, 2003.
- Sun, N.-Z., and Sun, A. Model calibration and parameter estimation: for environmental and water resource systems. New York: Springer, 2015.
- Susanto, K., Malet, J. P., Gance, J., and Marc, V. Fiber Optics Distributed Temperature Sensing (FO-DTS) for Long-term
1555 Monitoring of Soil Water Changes in the Subsoil. In *EAGE/DGG Workshop 2017* (pp. cp-508). European Association of Geoscientists and Engineers, 2017.
- Szymczycha, B., Borecka, M., Białk-Bielińska, A., Siedlewicz, G., and Pazdro, K. Submarine groundwater discharge as a source of pharmaceutical and caffeine residues in coastal ecosystem: Bay of Puck, southern Baltic Sea case study. *Science of The Total Environment*, 713, 136522, 2020. <https://doi.org/10.1016/j.scitotenv.2020.136522>
- 1560 Tang, Q., W. Kurtz, O. S. Schilling, P. Brunner, H. Vereecken, and H. J. H. Franssen. The influence of riverbed heterogeneity patterns on river-aquifer exchange fluxes under different connection regimes, *J Hydrol*, 554, 383-396, 2017.
- [Thibaut, R., Laloy, E., and Hermans, T. A new framework for experimental design using Bayesian Evidential Learning: The case of wellhead protection area. *Journal of Hydrology*, 603, 126903, 2021. https://doi.org/10.1016/j.jhydrol.2021.126903](https://doi.org/10.1016/j.jhydrol.2021.126903)
- Tirado-Conde, J., P. Engesgaard, S. Karan, S. Muller, and C. Duque. Evaluation of Temperature Profiling and Seepage Meter
1565 Methods for Quantifying Submarine Groundwater Discharge to Coastal Lagoons: Impacts of Saltwater Intrusion and the Associated Thermal Regime, *Water*, 11(8), 1648, 2019.
- Trauth, N., A. Musolff, K. Knoller, U. S. Kaden, T. Keller, U. Werban, and J. H. Fleckenstein. River water infiltration enhances denitrification efficiency in riparian groundwater, *Water Res*, 130, 185-199, 2018.
- Trauth, N., and J. H. Fleckenstein. Single discharge events increase reactive efficiency of the hyporheic zone, *Water Resour*
1570 *Res*, 53(1), 779-798, 2017.
- Trauth, N., C. Schmidt, M. Vieweg, S. E. Oswald, and J. H. Fleckenstein. Hydraulic controls of in-stream gravel bar hyporheic exchange and reactions, *Water Resour Res*, 51(4), 2243-2263, 2015.
- Trauth, N., C. Schmidt, M. Vieweg, U. Maier, and J. H. Fleckenstein. Hyporheic transport and biogeochemical reactions in pool-riffle systems under varying ambient groundwater flow conditions, *J Geophys Res-Bioge*, 119(5), 910-928, 2014.



- 1575 Trauth, N., C. Schmidt, U. Maier, M. Vieweg, and J. H. Fleckenstein. Coupled 3-D stream flow and hyporheic flow model under varying stream and ambient groundwater flow conditions in a pool-riffle system, *Water Resour Res*, 49(9), 5834-5850, 2013.
- Tso C.H.M., Iglesias M., Wilkinson P., Kuras O., Chambers J., and Binley A. 2021. Efficient multi-scale imaging of subsurface resistivity with uncertainty quantification using ensemble Kalman inversion. *Geophysical journal International*, 225, 887-1580 905, 2021.
- Valocchi, A. J., Bolster, D., and Werth, C. J. Mixing-limited reactions in porous media. *Transport in Porous Media*, 130(1), 157-182, 2019.
- Vereecken, H., J.A. Huisman, H.-J. Hendricks Franssen, N. Bruggemann, H.R. Bogaen, S. Kollet, M. Javaux, J. van der Kruk, and J. Vanderborght. Soil hydrology: recent methodological advances, challenges and perspectives. *Water Resources Research*, 51(4), 2616 – 2633, 2015.
- 1585 Vieweg, M., M. J. Kurz, N. Trauth, J. H. Fleckenstein, A. Musloff, and C. Schmidt. Estimating time-variable aerobic respiration in the streambed by combining electrical conductivity and dissolved oxygen time series, *J Geophys Res -Biogeo*, 121(8), 2199-2215, 2016.
- [Vilhelmsen, T., Marker, P., Foged, N., Wernberg, T., Auken, E., Christiansen, A. V., et al. A Regional Scale Hydrostratigraphy Generated from Geophysical Data of Varying Age, Type, and Quality. *Water Resources Management*, 33, 539-553, 2019. https://doi.org/10.1007/s11269-018-2115-1](https://doi.org/10.1007/s11269-018-2115-1)
- 1590
- Vogt, T., E. Hoehn, P. Schneider, A. Freund, M. Schirmer, and O. A. Cirpka. Fluctuations of electrical conductivity as a natural tracer for bank filtration in a losing stream, *Adv Water Resour*, 33(11), 1296-1308, 2010.
- Voytek, E. B., Barnard, H. R., Jougnot, D., and Singha, K. Transpiration-and precipitation-induced subsurface water flow 1595 observed using the self-potential method. *Hydrological Processes*, 33(13), 1784-1801, 2019.
- Vrugt, J. A., ter Braak, C. J. F., Diks, C. G. H., and Schoups, G. Hydrologic data assimilation using particle Markov chain Monte Carlo simulation: Theory, concepts and applications. *Advances in Water Resources*, 51, 457–478, 2013. <https://doi.org/10.1016/j.advwatres.2012.04.002>
- 1600 Wagner, F. M., Mollaret, C., Günther, T., Kemna, A., and Hauck, C. Quantitative imaging of water, ice and air in permafrost systems through petrophysical joint inversion of seismic refraction and electrical resistivity data. *Geophysical Journal International*, 219(3), 1866-1875, 2019.
- Wainwright, H.M., A. Flores Orozco, M. Bucker, B. Dafflon, J. Chen, S.S. Hubbard, and K.H. Williams. Hierarchical Bayesian method for mapping biogeochemical hotspots using induced polarization imaging *Water Resour. Res.* 52, 533-551, 2016.
- Wallis, I., Prommer, H., Berg, M., Siade, A. J., Sun, J., and Kipfer, R. The river–groundwater interface as a hotspot for arsenic 1605 release. *Nature Geoscience*, 13(4), 288–295, 2020. <https://doi.org/10.1038/s41561-020-0557-6>
- Wang, Q., Chen, X., Jha, A. N., and Rogers, H. Natural gas from shale formation - The evolution, evidences and challenges of shale gas revolution in United States. *Renewable and Sustainable Energy Reviews*, 30, 1–28, 2014. <https://doi.org/10.1016/j.rser.2013.08.065>

- Werner, A. D., Bakker, M., Post, V. E. A., Vandenbohede, A., Lu, C., Ataie-Ashtiani, B., et al. Seawater intrusion processes, investigation and management: Recent advances and future challenges. *Advances in Water Resources*, 51, 3–26, 2013. <https://doi.org/10.1016/j.advwatres.2012.03.004>
- Winter, T. C. Relation of streams, lakes, and wetlands to groundwater flow systems, *Hydrogeol J*, 7(1), 28-45, 1999.
- Xu, T., and Valocchi, A. J. A Bayesian approach to improved calibration and prediction of groundwater models with structural error. *Water Resources Research*, 51(11), 9290–9311, 2015. <https://doi.org/10.1002/2015WR017912>
- Ye, Y., Chiogna, G., Cirpka, O. A., Grathwohl, P., and Rolle, M. Experimental evidence of helical flow in porous media. *Physical review letters*, 115(19), 194502, 2015.
- Yin, Z., Strebelle, S., and Caers, J. Automated Monte Carlo-based Quantification and Updating of Geological Uncertainty with Borehole Data (AutoBEL v1.0). *Geosci. Model Dev*, 2020. <https://doi.org/10.5194/gmd-2019-232>
- Zamrsky, D., Karssenberg, M. E., Cohen, K. M., Bierkens, M. F. P., and Oude Essink, G. H. P. Geological Heterogeneity of Coastal Unconsolidated Groundwater Systems Worldwide and Its Influence on Offshore Fresh Groundwater Occurrence. *Frontiers in Earth Science*, 7, 2020. <https://doi.org/10.3389/feart.2019.00339>
- Zametske, J. P., R. Haggerty, S. M. Wondzell, and M. A. Baker. Labile dissolved organic carbon supply limits hyporheic denitrification, *J Geophys Res-Bioge*, 116, 2011a.
- Zametske, J. P., R. Haggerty, S. M. Wondzell, and M. A. Baker. Dynamics of nitrate production and removal as a function of residence time in the hyporheic zone, *J Geophys Res-Bioge*, 116, 2011b.
- Zametske, J. P., R. Haggerty, S. M. Wondzell, V. A. Bokil, and R. González-Pinzón. Coupled transport and reaction kinetics control the nitrate source-sink function of hyporheic zones, *Water Resour. Res.*, 48, 2012. W11508, doi:10.1029/2012WR011894
- Zhan, Z. Distributed acoustic sensing turns fiber-optic cables into sensitive seismic antennas. *Seismological Research Letters*, 91(1), 1-15, 2020.
- Zhang, C., A. Revil, Y. Fujita, J. Munakata-marr, and G. Redden. Quadrature conductivity: A quantitative indicator of bacterial abundance in porous media *Geophysics* 79(6), D363-D375, 2014.
- Zhang, S., and Planavsky, N. J. Revisiting groundwater carbon fluxes to the ocean with implications for the carbon cycle. *Geology*, 48(1), 67–71, 2020. <https://doi.org/10.1130/G46408.1>
- Zhou, H., Gómez-Hernández, J. J., and Li, L. Inverse methods in hydrogeology: Evolution and recent trends. *Advances in Water Resources*, 63, 22–37, 2014. <https://doi.org/10.1016/j.advwatres.2013.10.014>
- Zhou, Z., Klotzsche, A., Hermans, T., Nguyen, F., Schmäck, J., Haruzi, P., and Vereecken, H. 3D aquifer characterization of the Hermalle-sous-Argenteau test site using crosshole ground-penetrating radar amplitude analysis and full-waveform inversion, *Geophysics*, 85(6), H133-H148, 2020.

1640




Flux measurement and DTS




1645 **Figure 1: Illustration of the 4D nature of hydrogeological processes inaccessible from punctual data only: a) imaging subsurface fluxes and their contribution to surface fluxes through the combination of borehole and surface imaging; b) monitoring water content and temperature fluctuations for quantifying preferential flows and heat transfer; c) characterizing tracer motion to elucidate transport processes and related parameters; d) analyzing and upscaling pore-scale signals produced by microscale reactive transport processes.**

A. Darcy scale helical flow in anisotropic permeability fields (centimeter to meter scale)



B. Chaotic flow dynamics at the pore scale in granular media (millimeter to centimeter scale)



1650

1655

Figure 2: A. Experimental evidence of helical flow at Darcy scale (top, modified from Ye et al., 2015): the black lines show simulated streamlines, the colored surfaces iso-pressure surfaces and the red dots are experimental sampling points. B. Experimental evidence of chaotic mixing at the pore scale in three-dimensional porous media (bottom modified from Heyman et al., 2020): the color field shows the concentration of a continuously injected fluorescent dye, the red line is the intersection of the plume with a 2D plane transverse to the mean flow, which shows the stretching and folding patterns that produce chaotic mixing, the grey spheres represent selected grains in the bead pack that create the first successive folding of the plume.







Figure 3. Hydraulic conductivity fields (A-B) and related simulations (C-D) obtained by inversion of temperature (A-C) and solute tracer concentration data (B – D) from heat and solute tracer experiments (modified from Hoffmann et al., 2019, [table 1 Table 2.A.1](#)).




1660

Figure 4. (A) Acquisition set-up used by Blazevic et al. (2020) to jointly monitor the infiltration of water with ERT and seismic, lines that cross in the infiltration area. (B) Picture of the infiltration test, above a pit instrumented with TDR. Temporal evolution of relative change in properties inferred from (C) the ERT and (D) the seismic data along the North-South profile at different times (i.e., successive acquisitions) during the infiltration, respectively (modified after Blazevic et al., 2020, table 1-Table 2.B.1). One can see the preferential water flow from North to South, indicating lateral flow in the vadose zone.

1665



1670 Figure 5. Conceptual depiction of the GW-SW interface and the nested controls of spatio-temporal patterns of exchange and solute turnover in the transition zone between GW and SW (using a river-aquifer system as an example). A: primary spatial controls defined by regional topography and geology, B: secondary spatial controls defined by local aquifer and stream bed geologic heterogeneities as well as streambed morphology, C: temporal controls caused by river flow dynamics. Processes and management aspects that are affected by these exchange and turnover patterns are shown in light blue.



1675 | **Figure 6: Adapted deep neural network (DNN) based inversion scheme using a variational autoencoder (VAE) to represent complex geological structure in a latent space represented by sparse variable in which a stochastic gradient-descent (SGD) can be applied to converge towards the a more geologically realistic solution modified from Lopez-Alvis et al., (2022).**





Figure 7: Framework of Bayesian Evidential Learning applied to the prediction of heat storage in an aquifer from a tracer experiment monitored by geophysics. 1. A prior model of the spatial heterogeneity is defined and sampled. 2. Both the predictor (data set such as a tracer experiment) and the target (prediction of heat storage) are simulated. For the predictor, a petrophysical transform is used to generate the corresponding geophysical data. 3. Dimension reduction techniques are applied to both data and prediction. 4. A statistical relationship between data and prediction is learned. 5. The posterior distribution of the prediction for field observed data is generated using the statistical relationship. 6. The posterior is back-transformed in the physical space (modified from Hermans et al., 2018).

1680



1685

Figure 8: Indicative temporal and spatial scales of some processes in hydrogeology for which accurate mechanistic models are still lacking (in reddish colors), for which 4D monitoring might be crucial (blueish and greenish colors), and for which 4D might be unnecessary (greyish colors), see also Table 1.

1690

1695

Table 1. Classification of ~~Non-exhaustive list of processes requiring~~ according to their need for high resolution 4D data space-time imaging

<u>Type of processes</u>	<u>Typical Scales</u>	<u>Examples</u>
<u>A. Processes for which high resolution space-time imaging is needed for developing mechanistic models that upscale these dynamics</u>	From the pore-scale to (deca)metric scale Seconds to hours or days	<ul style="list-style-type: none"> - <u>Subsurface velocity statistics and dynamics</u> - <u>Fracture dominated flow</u> - <u>Transport, mixing and reactive transport</u> - <u>Geophysical characterization of biogeochemical processes</u> - <u>Preferential infiltration and lateral unsaturated flow</u> - <u>Transport and reaction in the unsaturated zone</u> - <u>Conceptual models of interface exchanges</u> - <u>Upscaling mechanistic models</u>
<u>B. Processes for which high resolution space-time monitoring is desirable or crucial in applications</u>	From metric scale to kilometric scale A few hours to years	<ul style="list-style-type: none"> - <u>Soil moisture characterization for precision agriculture</u> - <u>Monitoring of contaminations (natural attenuation, in-situ bioremediation, reactive barriers)</u> - <u>Thermal affected zone for energy storage</u> - <u>Storage of nuclear waste</u> - <u>Induced seismicity resulting from geothermal exploitation or fluid injections in the subsurface</u> - <u>Variability in groundwater-river exchanges</u>
<u>C. Processes for which space-time characterization may not be critical</u>	From decametric scale to catchment and global scale Months to centuries	<ul style="list-style-type: none"> - <u>Water balance at the catchment scale</u> - <u>Average transit and residence time</u> - <u>Average recharge towards aquifer</u> - <u>Evaluation of the fate of contaminants when the risk for receptors is limited</u> - <u>River baseflow</u>

700

Table 12: Selection of datasets available on-line for multi-dimensional hydrogeological system characterization and monitoring. Datasets were selected based on their on line availability, their link with a dynamic component of the subsurface and their relevance for illustrating the paper. This table will be available on line <https://hplus.ore.fr/en/database/4d-hydrogeology-dataset> with the possibility to contribute to enrich the datasets with new data.

Dimension	Dataset	Site	Link to dataset	Publications
A + 3D + time	A.1 Time-lapse geophysical monitoring of heat transport: 2D time-lapse ERT cross-sections + 3D multiple nested wells data during heat tracer test	Hermalle, Belgium	https://hplus.ore.fr/en/associated-sites/enigma/data-hermalle	Hermans et al., (2015b, 2018) (Hoffmann et al. 2019)
	A.2 Time-lapse geophysical monitoring of hyporheic zone processes: 2D surface Electromagnetic Induction + 2D time-lapse ERT (section)	Theis site, Ohio, USA	https://doi.org/10.4211/hs.69204f1ee49c4176a8aab5f4832c7b76	McGarr et al., (2021)
B. 2D + time	B.1 Time-lapse geophysical monitoring of water infiltration in the vadose zone: 2D time-lapse ERT and seismic cross-sections + TDR monitoring of water content during irrigation	Ploemeur, France	http://hplus.ore.fr/en/blazevic-et-al-2020-water-data ¹	Blazevic et al. (2020)

¹ with login and password provided upon request

	<p>B.2 GPR imaging of fracture opening during hydraulic test: borehole and surface GPR+ optical televiewer + core logging during high pressure injection test</p>	<p>Aspö hard rock laboratory, Sweden</p>	<p>http://hplus.ore.fr/en/molron-et-al-2021-eg-data¹ http://hplus.ore.fr/en/molron-et-al-2020-eg-data¹</p>	<p>Molron et al. (2020, 2021)</p>
	<p>B.3 GPR imaging of tracer transport in fractured media: borehole GPR + conductivity and fluorescence monitoring during tracer test</p>	<p>Ploemeur, France</p>	<p>http://hplus.ore.fr/en/shakas-et-al-2017-grl-data¹</p>	<p>Shakas et al. (2017, 2016)</p>
	<p>B.4 Use of V_p/V_s ratio to monitor subsurface water content: 2D time-lapse seismic cross-sections P- and surface-wave survey, SH-wave refraction acquisition, travel-time tomography</p>	<p>Ploemeur, France</p>	<p>http://hplus.ore.fr/en/pasquet-et-al-2015-nsg-data</p>	<p>Pasquet et al. (2015) Dangeard et al. (2018)</p>
	<p>B.5 Time-lapse geophysical monitoring of water infiltration in karstic environment: 2D time-lapse ERT cross-sections during rainfall events</p>	<p>LSBB, France</p>	<p>https://hplus.ore.fr/en/carriere-et-al-2022-dib-data</p>	<p>Carrière et al. (2015, 2022)</p>

	B.6 Time-lapse geophysical monitoring of seawater intrusion: 2D time-lapse cross-hole ERT in coastal aquifer	Argentona, Spain	http://hplus.ore.fr/en/palacios-et-al-2020-hess-data ¹	Palacios et al. (2020)
C: 1D + time	C.1 Nuclear Magnetic resonance monitoring of water in a headwater catchments: Time-lapse magnetic resonance sounding	Strengbach, France	http://hplus.ore.fr/en/lesparre-et-al-2020-joh-data	Lesparre et al. (2020)
	C.2 Fiber optic DTS monitoring for estimating thermal conductivity and groundwater flux in porous media: fiber optic DTS and heat tracer experiments in a sand tank	Poitiers, France	http://hplus.ore.fr/en/simon-et-al-2020-wrr-data	Simon et al. (2020, 2022)
	C.3 Fiber-optic monitoring of heat transfer in fractured media: Fiber optic-DTS monitoring during thermal and solute tracer tests,	Ploemeur, France	http://hplus.ore.fr/en/delabernardie-et-al-2018-wrr-data ¹	De La Bernardie et al. (2018)
	C.4 Use of gravimeter time series for hydrological model calibration in a karst aquifer: Ten years gravimetry time series using iGrav superconducting gravimeter	Larzac, France	https://hplus.ore.fr/en/igrav-gravity-dataset	Fores et al. (2018, 2017)

	C.5 Time-lapse absolute quantum gravity measurements to monitor water storage in karstic environments: gravimeter time series	Larzac, France	https://zenodo.org/record/4279110#.YdlFqWCZOM8	(Cooke et al, 2021)
	C.6 Self-potential monitoring of natural rainfall and saline tracer infiltrations at the agricultural test site of Voulund, Denmark (HOBE network): Self-potential, time series	Voulund, Denmark	https://data.mendeley.com/datasets/6r8898657w/1	(Hu et al., 2020)
	C.7. Fiber-optic and borehole temperature monitoring of heat transfer in stream valleys: Fiber optic-DTS and borehole temperature monitoring of naturally occurring temperature fluctuations in groundwater upwelling areas in wetlands.	Holtum stream lowlands, Denmark.	https://water.columbia.edu/people/upmanu-lall https://hplus.ore.fr/en/associated-sites/enigma/data-evi-1	Tirado-Conde et al. (2019)
D. High resolution imaging of heterogeneity	D.1 3D Seismic imaging of a karstic aquifer combined with multiple cross	Poitiers, France	http://hplus.ore.fr/en/mari-et-al-2009-ogst-data ¹ https://hplus.ore.fr/en/poitiers/data-poitiers ¹	Mari et al. (2009)

	borehole tracer tests: 3D seismic bloc and tracer tests			
	D.2 GPR Imaging of sand layered aquifer with multiple 2D profiles and tracer tests: Crosshole GPR and tracer tests	Krauthausen, Germany	https://teodoor.icg.kfa-juelich.de/geonetwork/aaps/search/?uuid=a4d404c9f-419a-4b14-b6e0-6ee9acd8f80e ¹	Gueting et al. (2015, 2017)
E. Multiple tracer experiments	E.1 solute and heat tracer tests for characterizing heat transfer in fractured granite: Convergent and push-pull tests with injection of hot water, cold water and salt	Choutuppal, India	http://hplus.ore.fr/en/hoffmann-et-al-2021-groundwater-data	Hoffmann et al. (2021b)
	E.2 solute and dissolved gas tracer tests for characterizing transport in Chalk: Convergent and push-pull tests with heat, helium, argon, xenon and uranine	Mons, Belgium	https://hplus.ore.fr/en/hoffmann-et-al-2020-hydrogeology-of-the-chalk-data ¹ http://hplus.ore.fr/en/hoffmann-et-al-2020-grl-data ¹	Hoffmann et al. (2020, 2021a)
	E.3 salt and dissolved oxygen tracer tests for characterizing transport and transit-times in a riparian zone: time-series of	Selke River, Falkenstein, Germany	https://www.hydroshare.org/resource/51b3933c4987427e94e51e3339237755/ https://www.hydroshare.org/resource/476a188d9f894a77a3ed404949680cab/	Nogueira et al. (2021a, 2021b)

1705

	EC, dissolved oxygen, and water temperature and stage			
--	--	--	--	--