Manuscript Number: hess-2023-96

**Revision notes:** 

We would like to thank the editor and reviewers for the valuable and comments,

which were very helpful for the further improvement of the manuscript. We have

looked through each comment the editor and reviewers raised and responded and

incorporate it in the revised manuscript. For your review, we have attached the

revised PDF manuscript at the end. The following is the detailed response:

Reviewer #1:

The article is presenting an interesting set of data and applied some solid

methodologies in order to show the impact of urban activities (broad sense).

The angle taken by the article is very interesting. However, there are more

assumptions than scientific demonstration partly because the authors have long

temporal series at a few SW sampling points when the scientific demonstration is

more looking for spatial variability than temporal variability. The GW data is not

really used. The article should be strengthened by a better use of the collected data

and additional and more self-explanatory figures.

No figure is really convincing as the explanation factors remains quite "vague", land

cover (which type? What variability through the basin?), soil permeability (data on

that is not provided). Spatial information on these parameters is missing.

**Response:** Thank you for your valuable comments and suggestions on our manuscript.

Based on your comments and suggestions, we have enhanced the analysis and

discussion of the isotope data, strengthened the groundwater analysis, redescribed the

spatial variability of the results, illustrated our results with more figures, and analyzed

in detail the influencing factors of the MRT, with the revised sections shown in blue.

In addition, for your review, we have included a PDF of the revised manuscript at the end of this document.

## **Specific comments:**

1. Line 43: the reference (Cho) is a very specific case and most probably not appropriate to be cited here.

**Response:** We agree with your suggestion and have modified the expression here. We have changed "Urbanization has led to a dramatic increase in water consumption, significantly impacting groundwater quality (Cho et al., 2009)." to "Urbanization exacerbates water depletion and has far-reaching impacts on groundwater (Flörke et al., 2018; McDonough et al., 2020)."

2. Line 62: it is not clear why these three references were cited here. There are many other studies on GW-SW studies so may be better cite local studies or global ones.

**Response:** We have modified the study cited here, we have changed "Isotopes that are stable of hydrogen and oxygen are very useful tools for investigating hydrological issues that are connected to surface water and groundwater sources (Gat,1996, Tetzlaff et al.,2007, Sanda et al.,2017)." to "Isotopes that are stable of hydrogen and oxygen are very useful tools for investigating hydrological issues that are connected to surface water and groundwater sources (Förstel and Hützen, 1983; Fekete et al., 2006; Vystavna et al., 2021)."

3. Line 132: the *river* sampling location

**Response:** We have revised the expression in response to your comments,we have changed "The sampling location" to "the river sampling location".

4. Line 135: Are all GW bodies sampled ? or a selection of GW bodies ? please specify

**Response:** We have provided a detailed description of groundwater collection, with detailed revisions below. We have changed "Samples of groundwater bodies were obtained at 7 sampling stations around the basin" to "Artesian well water was collected as groundwater samples at seven sampling locations around the basin", and is indicated in Fig. 1.




Figure 1 (a) The location of the study area, (b) Comprehensive observation system for the study area, (c) Urban surface water sampling points(from Google Maps), (d) Common urban landscape dams in SYR Basin.

5. Line 191: remove big cap for The

**Response:** We have modified the formulation here.

Specifically: Periodic regression analysis and the mean residence time (MRT)

6. Line 193-195: paragraph to be changed in order to highlight the method and not the specific Slovenian case

**Response:** We have revised the expression in response to your comments. We have changed "Precipitation and surface water samples were collected from a variety of locations across Slovenia, as well as from Belgrade, Serbia, for the Sava and Danube

rivers. Seasonal fluctuations in  $\delta^{18}$ O levels were analyzed using periodic regression analysis to determine how these levels changed over time. This method entailed fitting seasonal sine wave curves to annual  $\delta^{18}$ O variations using least squares optimization (Rodgers et al.,2005)" to "Seasonal fluctuations in  $\delta^{18}$ O levels were analyzed using periodic regression analysis to determine how these levels changed over time. This method entailed fitting seasonal sine wave curves to annual  $\delta^{18}$ O variations using least squares optimization (Rodgers et al.,2005)."

7. Line 219: what is the seasonal variation of isotopes? Is the effect of dam similar in all season? Only average means are given and fig 3 is difficult to read as all water were represented

**Response:** I'm sorry that this sentence was not clearly expressed, which has caused you a misunderstanding. According to your suggestion, we have described the seasonal variations of isotopes, according to our results, the effect of urban landscape dams on river water and groundwater is similar, and some degree of evaporation occurs in both river water and groundwater, and we have modified Figure 3 to make it easier to understand, and the following is the detailed information of our modification. Specifically:

In both surface water and groundwater,  $\delta D$  and  $\delta^{18}O$  showed significant seasonal variations (Fig. 3). Seasonal variations were more pronounced in surface water than in groundwater, with surface water showing the largest amplitude in spring and the smallest amplitude in fall, while groundwater showed closer amplitudes in all seasons, which also indicates that groundwater is less disturbed.




Figure 3 Relationship between  $\delta D$  and  $\delta^{18}O$  in various water bodies in the SYR Basin during different seasons (a) Spring, (b) Summer, (c) Autumn, (d) The contrast between RWL, GWL, LMWL and GMWL throughout the sampling period.

8. Fig2: Where the GW points were taken comparing to the distance to surface water and dam? No location is given in the paper. This is also most probably the reason why GW variability is not discussed in the chapter 4.1

**Response:** In response to your suggestion that we also increase the distance to dams near groundwater, we have modified Figure 2 and added some groundwater isotope data to make it easier to understand. The revised Figure 2 is shown below.




Figure 2 Longitudinal variation of  $\delta D$  and  $\delta^{18}O$  in river water and groundwater in the SYR Basin.

## 9. Line 249: Global meteoric

**Response:** Due to our negligence, this error was caused, and we have revised the content, We have changed "global geteoric water line" to "global meteoric water line".

10. Fig3: very small figures and difficult to read. Not all explanation in the text can be confirmed by the figure due to too many information in very small size figures.

**Response:** According to your suggestion, we have modified Fig 3. The detailed revisions are as follows.




Figure 3 Relationship between  $\delta D$  and  $\delta^{18}O$  in various water bodies in the SYR Basin during different seasons (a) Spring, (b) Summer, (c) Autumn, (d) The contrast between RWL,GWL,LMWL and GMWL throughout the sampling period.

11. Line 252-255: the sampling points are not so close to the LML, some are even quite far. Also possible GW discharge to the surface water and possible recharge mechanism looks possible for the GW. More discussion would be needed

Response: Yes, there are some surface water sampling sites far from the LMWL, and after we rechecked the data, we eliminated some of the isotopic anomalies that may have been caused by experimental and other factors, and re-plotted Figure 3.In case the response is too cumbersome and inconvenient to view and read, the revisions to Figure 3 are described in Response 10 above, and I thank you for your help. In addition, we have described in detail the interactions between surface water and groundwater and provided detailed information on the revisions.

Specifically:

We compared monthly variations in isotopic values of groundwater near the city with monthly variations in river water from a landscaped dam and found that the monthly variations in groundwater near the city were closely related to river water from a landscaped dam. The concentration of groundwater sampling sites near the city near the sampling sites of the dam water indicates that the groundwater around the city has similar isotopic signatures to the dam and river water. This suggests that groundwater near the city is recharged by river water during the summer months. In addition, we demonstrated this by comparing the data of the dam river water with the groundwater level. In addition, a portion of the groundwater sampling sites around the city are located in the lower right corner of the LMWL, which suggests that the groundwater around the city may also experience some degree of evaporation.




Figure 4 (a) Relationship between  $\delta^{18}O$  and  $\delta D$  of groundwater around city and urban river water; (b) Monthly variations of  $\delta^{18}O$  in groundwater around city; (c) Monthly variations of  $\delta D$  in groundwater around city.

In addition, we also compared and analyzed the changes of groundwater isotope values with those of groundwater around the city in the whole basin, and found that there was a close correlation between the changes of groundwater around the city and

those of the river, while the other groundwater isotope values did not have a strong correlation with the river. In the urban area, the mean values of  $\delta D$  and  $\delta^{18}O$  of the dammed river water were -8.26% and -49.88%, respectively, while the mean values of  $\delta D$  and  $\delta^{18}O$  of the groundwater around the city were -8.44% and -50.36%, respectively, which indicated that the  $\delta D$  and  $\delta^{18}O$  values of the groundwater around the city were similar to those of the river water in the dammed city. In addition, the isotopic mean values of  $\delta D$  and  $\delta^{18}O$  of groundwater throughout the SYR basin were -8.73% and -54.78%, which are significantly different from the isotopic values of river water in the urban dams.




Figure 5 (a) Monthly variations of  $\delta^{18}$ O in groundwater around city, (b) Monthly variations of  $\delta D$  in groundwater around city.

# 12. Line 257: it is not because of the different correlation line that we can conclude in a variation of IC from up to down.

**Response:** I'm sorry that this sentence was not clearly expressed, which has caused you a misunderstanding. we have revised the narrative, and here is the detailed revision information.

We have changed "The SYR Basin surface water samples that were collected exhibited a linear regression of  $\delta D$ =5.63 $\delta^{18}O$ -6.11, which revealed a spatial variation in isotopic composition from upstream to downstream. Where the river water line (RWL) intercept and slope show a trend that is first decreasing and then increasing as one moves from upstream to downstream. This demonstrated the presence of

significant isotopic differences in the water." to "Overall, the H-O isotopic composition of surface water samples from the SYR showed a linear regression of  $\delta D$  =  $5.63\delta^{18}O$  - 6.11, and the slope of RWL was the largest in the autumn (slope = 6.65) and the smallest in the summer (slope = 5.56), which indicated that the river water evaporated the weakest in the autumn and the strongest in the summer."

#### 13. Line 258-261: Sentence not clear

**Response:** We apologize for the reading difficulty caused by the lack of clarity of presentation here. We have revised the sentence and the changes are listed in point 12 of the response, thank you for your help.

14. Line 262-265: location of GW points and variation in comportment is missing here. It looks that there is a large IC variations between one GW point to another **Response:** Based on your comments, we have revised the presentation. Specifically:

And it is interesting to note that groundwater also shows significant enrichment near the urban landscape dams (Fig. 2), indicating that groundwater is also affected by evapotranspiration, mainly because the Wuwei urban area is in the region of a large alluvial fan in front of the mountains, the sand and gravel aquifers are very permeable, and the depth of groundwater burial is shallow, making the groundwater more susceptible to the effects of evaporation.

- 15. Line 267-271: this is theoretical but does not give much information to the reader **Response:** Based on your suggestion, we have decided to remove this erroneous and confusing statement.
- 16. Line 285 and fig4: is it evaporation loss calculated for each points for the whole period? Is a) and b) environment explained somewhere in the text? Which SW point in each category?

**Response:** Yes, we calculated evaporation losses for each surface water sampling site

in the upstream and midstream for the entire sampling period. For the a) and b) environments, we made relevant interpretations, and detailed modification information is provided below.

#### Specifically:

Differences contributing to evaporation losses from the river in the upstream and midstream urban areas can be explained mainly by the landscape characteristics of the basin. In the upstream of the Shiyang River, higher vegetation cover and atmospheric humidity in the mountainous areas result in weaker evaporation losses, while the midstream are dominated by urban land, and urban landscapes increase the watershed area and slow down the river, exacerbating evaporation losses losses from the river.

## 17. Line 308: assumptions, not demonstrated, a ref would be needed

**Response:** Based on your suggestion, we have added the relevant literature here, and the following is the detailed revision information.

# Specifically:

We have changed "The  $\delta^{18}$ O levels of precipitation reported in the SYR Basin have an excellent regularity (R<sup>2</sup>=0.46) and a seasonal patterns trend that effectively depicts the nfluence of the monsoon climate on the local environment" to "The  $\delta^{18}$ O levels of precipitation reported in the SYR Basin have an excellent regularity (R<sup>2</sup>=0.46) and a seasonal patterns trend that effectively depicts the nfluence of the monsoon climate on the local environment (Zhu et al., 2019)."

#### References:

Zhu, G., Guo, H., Qin, D., Pan, H., Zhang, Y., Jia, W., and Ma, X.: Contribution of recycled moisture to precipitation in the monsoon marginal zone: Estimate based on stable isotope data, Journal of Hydrology, 569, 423 – 435, https://doi.org/10.1016/j.jhydrol.2018.12.014, 2019.

18. Line 311: Variability in GW should also be showed, as it is first necessary to demonstrate the GW IC is stable with time before telling that SW is presenting seasonal variation due to direct precipitation. And to be compared with seasonal

## variability of precipitation?

**Response:** The stability of the groudwater isotope composition over time has been demonstrated in Figures 2 and 3. The main focus of this study is on the surface runoff in the urban area, so it is assumed that groundwater does not contribute to the runoff.In addition, we calculated the sinusoidal regression period for precipitation and streamflow in the SYR basin separately, in order to reveal the cyclic variation of runoff and precipitation in the urban area. As described in our previous methods regarding MRT, the sinusoidal exponential regression model amplitude, A, is an important parameter in calculating MRT for river water, and applying MRT to river water data on longer time scales and larger basins is problematic. The model generally assumes certain steady-state conditions in the catchment function, which is clearly unrealistic (McGuire et al., 2005), and in order to minimize errors, in this case we weighted precipitation  $\delta^{18}$ O in an attempt to characterize recharge, especially in basins with pronounced climatic seasonality (Uhlenbrook et al., 2002). Nonetheless, studies elsewhere have shown that the model remains a reliable tool for estimating MRT (Stewart and McDonnell, 1991; Soulsby et al., 2001; Asano et al., 2002; Tekleab et al., 2014; Wang et al., 2022), thank you for your Help.

#### Reference:

- McGuire, K. J., DeWalle, D. R., and Gburek, W. J.: Evaluation of mean residence time in subsurface waters using oxygen-18 fluctuations during drought conditions in the mid-Appalachians, J. Hydrol., 261, 132–149, 2002.
- Uhlenbrook, S., Frey, M., Leibundgut, C., and Maloszewski, P.: Hydrograph separations in a mesoscale mountainous basin at event and seasonal timescales, Water Resour. Res., 38, 1096–1110, 2002.
- Stewart, M. K. and McDonnell, J. J.: Modelling base flow soil water residence times from deuterium concentrations, Water Resour. Res., 27, 2681–2693, 1991.
- Asano, Y., Uchida, T., and Ohte, N.: Residence times and flow paths of water in steep unchannelled catchments, Tanakami, Japan, J. Hydrol., 261, 173–192, 2002.
- Tekleab, S., Wenninger, J., and Uhlenbrook, S.: Characterisation of stable isotopes to identify residence times and runoff components in two meso-scale catchments in

the Abay/Upper Blue Nile basin, Ethiopia, Hydrol. Earth Syst. Sci., 18, 2415–2431, 2014.

Wang, S., He, X., Kang, S., Fu, H., and Hong, X.: Estimation of stream water components and residence time in a permafrost catchment in the central Tibetan Plateau using long-term water stable isotopic data, The Cryosphere, 16, 5023–5040, 2022.

19. Line 326-339: Again many assumptions on the reason of the variability of seasonal variation between the different SW points but nothing is demonstrated **Response:** We have made changes to the presentation here based on your suggestions, and here are the details of the changes.

Specifically:

The reasons for differences in isotope periodicity in different regions may be attributed to local water management systems, topographic features and urban development. At points S1, S2, and S10, the correlation of model simulations was low, which could be attributed to the presence of Xiying Reservoir in the upstream as well as Hongyashan Reservoir in the downstream (Sang et al., 2023), where seasonal variations in the isotope values of the river water are interfered by the reservoir dispatching activities. At points S3 to S5, the correlation of the model simulation is higher, which is because in the middle reaches of the SYR basin, the expansion of urban built-up areas leads to a significant increase in surface runoff during the rainy season, and according to the land use data, the land area of the towns in Wuwei City has continued to increase by 134.38 km<sup>2</sup> from 2010 to 2018, resulting in the surface water showing a cyclical trend comparable to that of the precipitation. Since the 1950s, in order to better utilize water resources, 13 small and medium-sized reservoirs with a total storage capacity of 900,000 m<sup>3</sup> were constructed during this period (Ma et al., 2010), increasing the proportion of rainfall in the runoff constituents as a result of The correlation of the model simulation is at a high level at points S6~S9, where, in contrast to the high-elevation areas in the upper reaches, the terrain in the middle and lower reaches of the SYR basin is relatively flat, mainly with cultivated land and

deserts, and is less disturbed by human activities (Sun et al., 2021), which further reflects the responsiveness to recent precipitation inputs.

20. Line 344: How MRT is influenced by the factors influencing the IC discussed in the previous chapter? And influence of dams? What is the uncertainty of such calculation? Are MRT significantly different for each SW?

**Response:** According to your suggestion, we have analyzed the factors affecting MRT specifically, about the uncertainty of MRT calculation we have mentioned in the previous 18 points, thank you for your help below is the specific modification information.

# Specifically:

The Dunnett's test revealed a significant difference (P < 0.05) between the MRT of the river and the annual magnitude of  $\delta^{18}$ O of the river. We further investigated the relationship between the estimated mean residence time and basin landscape features such as topography (Fig. 8). Using the digital elevation model (DEM) to calculate the mean slope of the SYR basin, we found that the mean residence time was also strongly correlated with the mean basin slope (R<sup>2</sup> = 0.63), and that the upper reaches of the Shiyang River basin are mainly high-elevation mountainous areas, where the topography is sloped, but where the vegetation cover is high and dominated by alpine meadows, subalpine scrub and Qinghai spruce (Zhang et al. 2023), the greater slope leads to a higher gravitational potential, which tends to result in a negative correlation with mean residence time (McGuire et al., 2005), which also contributes to the potentially higher MRT values in the upstream mountains. In our study, catchment area (CA) had a low correlation with MRT (R<sup>2</sup> = 0.40), and a weak relationship between catchment area and MRT has been observed in other studies (McGlynn et al., 2003; McGuire et al., 2005).




Figure 8 Correlation between mean slope of the basin (a), catchment area (b), sand clay loam ratio (c), ratio of residential and industrial areas to total basin area (d) and MRT.

Soil is an important component of basin hydrology, and the physical properties of soil, such as water-holding capacity and pore space distribution, have an important influence on the response to precipitation in the basin, and the sand-clay-loam soil ratio is used here to investigate the possible relationship with MRT. The results showed that the content of sand clay loam ratio showed a strong positive correlation with MRT (R²=0.62). Wuwei City is located in the pre-mountain flood-fan belt, and the soil is dominated by sandy soil (Zhang et al., 2023), which is loose in texture, has good permeability and good water retention properties, and is mainly used for agricultural cultivation. Its good permeability increases the vertical movement of water and the length of flow paths, leading to a longer MRT. There is a strong negative correlation between the MRT and the ratios of resident and industrial areas (RI), which also indicates that as urbanization progresses, with the increase of urban land, this undoubtedly leads to a significant shortening of the MRT. However, the MRT in the mid-river urban area is not much shorter as compared to the downstream,

which may be attributed to the fact that the mid-river The large number of landscape dams constructed in the urban areas, currently 51 urban landscape dams have been built in the peri-urban areas of Wuwei City, and the considerable number of landscape dams may have counteracted the impact of the urban land use, resulting in a lengthening of the MRT in the middle reaches as well.

#### Reference:

McGlynn, B., McDonnell, J., Stewart, M., and Seibert, J.: On the relationships between catchment scale and streamwater mean residence time, Hydrol. Process., 17, 175–181, https://doi.org/10.1002/hyp.5085, 2003.

McGuire, K. J., DeWalle, D. R., and Gburek, W. J.: Evaluation of mean residence time in subsurface waters using oxygen-18 fluctuations during drought conditions in the mid-Appalachians, J. Hydrol., 261, 132–149, 2002.

Zhang, W., Wan, Q., Zhu, G., and Xu, Y.: Distribution of soil organic carbon and carbon sequestration potential of different geomorphic units in Shiyang river basin, China, Environ Geochem Health, 45, 4071 – 4086, https://doi.org/10.1007/s10653-022-01472-w, 2023.

#### 21. Line 359: ref are missing

**Response:** We have added the relevant references here, here is the detailed revision information, thank you for your help.

We have changed "Recent studies have suggested that the development of dam-reservoir systems may result in river fragmentation and modifications in flow regimes in terms of their volume, frequency, and duration." to "Recent studies have suggested that the development of dam-reservoir systems may result in river fragmentation and modifications in flow regimes in terms of their volume, frequency, and duration (Négrel et al., 2016; Murgulet et al., 2016; Peñas and Barquín, 2019; Maavara et al., 2020)."

22. Line 372: what is "accumulation of isotope tracer"? enrichment? Changes? Accumulation is not the correct term most probably

**Response:** We apologize for any reading difficulties caused by the lack of clarity in the presentation here. We have modified the presentation, and the following is the detailed modification information.

Specifically: We have changed "In the metropolitan coast of Wuwei, a number of landscape dams have led to the accumulation of isotopic tracers in the surface water." to "In the metropolitan coast of Wuwei, many landscape dams have led to isotopic enrichment in surface water."

23. Line 377-380 and fig6a: S8 and S7 specific values and variability of dexcess after the urban dams are not explained

**Response:** In response to your suggestion, we have interpreted the d-excess variations at S7 and S8 as detailed below.

Specifically: In contrast, due to the confluence of tributaries prior to the S7 sampling point, the river water has lower isotopic values, resulting in elevated *d-excess* values between S6 and S8.

# 24. Line 385-387: ref is missing

**Response:** We have added relevant references here, the The added references are as follows.

#### Specifically:

Localized microclimates in urban areas allow for changes in precipitation and evapotranspiration processes, while urbanization alters the pristine subsurface, complicating water cycle processes in the basin (Jacobson, 2011; Westra et al., 2014; Oudin et al., 2018).

#### Reference:

Jacobson, C. R.: Identification and quantification of the hydrological impacts of imperviousness in urban catchments: A review, Journal of Environmental Management, 92, 1438–1448, https://doi.org/10.1016/j.jenvman.2011.01.018, 2011.

Oudin, L., Salavati, B., Furusho-Percot, C., Ribstein, P., and Saadi, M.: Hydrological

impacts of urbanization at the catchment scale, Journal of Hydrology, 559, 774–786, https://doi.org/10.1016/j.jhydrol.2018.02.064, 2018.

Westra, S., Fowler, H. J., Evans, J. P., Alexander, L. V., Berg, P., Johnson, F., Kendon, E. J., Lenderink, G., and Roberts, N. M.: Future changes to the intensity and frequency of short-duration extreme rainfall, Rev. Geophys., 52, 522–555, https://doi.org/10.1002/2014RG000464, 2014.

25. Line 388 to 423: it is only assumptions but no data to show that or not related to any of previously demonstrated variability and no data on water quality acquired in this study. Therefore this should better be placed in a concluding part

**Response:** In response to your suggestions, we have revised the presentation of this section, and here are the details of the revisions.

#### Specifically:

In terms of the impact on runoff, it is mainly reflected in the increase of surface impermeability due to urbanization, the land use area of Wuwei urban land increased by about 134.38 km2 from 2010 to 2018, which greatly weakened the infiltration process in urban areas, and the rainfall runoff process simulated by sinusoidal cyclic regression method showed that there were significant differences in the river metro in different parts of the Shiyang River Basin, and that the middle reaches of the river had the highest degree of urbanization, and the time of the metro was the shortest, which further increases the contribution of rainfall to runoff. Regarding the effect of urbanization on evapotranspiration, a large number of dams were constructed on the Shiyang River and flowed through the urban area of Wuwei, causing significant evapotranspiration losses, in addition, these landscape dams also led to hydrogen and oxygen isotope enrichment (Fig. 10), and the numerous reservoirs that were constructed for the construction and development of the city (Ma et al., 2010), and these reservoirs also contributed to a significant evapotranspiration losses effect, which has been previously confirmed in our study was also confirmed (Sang et al., 2023). On the other hand, our study found that the isotopic compositions and trends of urban nearshore groundwater were similar to those of surface water, which suggests

that there is a close correlation between urban nearshore groundwater and river water, and that the difference in water levels between river water and groundwater may be the main reason for river recharge of urban nearshore groundwater (Fig. 4). In the rainy season, the river level gradually rises, which decreases the difference between the water levels of urban nearshore groundwater and river water, and the river water recharges the groundwater, and in the dry season, the river level decreases, and the urban nearshore groundwater, which is buried at a shallow depth, in turn recharges the river.

In addition, the growth of urbanization has had a dramatic impact on the water environment in cities, where water problems occur frequently (Giri and Qiu, 2016; Ma et al., 2022). Urbanization has increased impervious surfaces such as parking lots, rooftops, roads, and sidewalks, leading to increased runoff, which creates additional pathways for pollutants to be transported from landscapes to water bodies ((Ren et al., 2014; Wilson and Weng, 2020; Nolan et al., 2023). On the other hand, agricultural activities have increased some of the fertilizers, pesticides, herbicides and dairy manure in the farmland into the nearest water bodies, which can directly and indirectly affect will reduce water quality (Yu et al., 2020). The Shiyang River Basin in the Northwest Arid Zone is an inland river basin with the highest development intensity and the sharpest conflict between water supply and demand in the region. The Liangzhou district in the central part of the Shiyang River basin is the most densely populated artificial oasis with the largest scale of water demand in the entire basin. Our previous study found that direct discharge of industrial and community domestic wastewater into the river led to deterioration of surface water quality around the Shiyang River basin (Ma et al., 2021). In addition agricultural activities have less impact on the upper reaches of the Shiyang River and relatively more impact on the middle and lower reaches, and the application of nitrogen-based fertilizers during agricultural cultivation is the main cause of high NH4<sup>+</sup> and NO3<sup>-</sup> concentrations in the area (Ma et al., 2021), which may also lead to increased salinity and accelerated eutrophication of the river, threatening the safety of the basin's water environment. Overall, human activities (urbanization) may alter the water cycle processes inherent in inland river basins, and the implications of such changes need to be further explored.

#### 26. Line 425-439: these are processes seen with data – OK

**Response:** I'm sorry that this sentence was not clearly expressed, which has caused you a misunderstanding. We have revised the presentation of this section and the details of the revisions are provided below.

## Specifically:

In this study, we investigated the hydrometeorological and isotopic data of the Shiyang River Basin from 2017 to 2021, and our investigations showed that urbanization had a significant impact on the water cycle of the basin. The results showed that the isotopic values of the river water showed a significant enrichment from upstream to downstream, but facilities such as landscape dams and reservoirs in the urban area significantly altered this natural pattern, and the isotopic values of the river water in the urban area ( $\delta D$ =-48.31%;  $\delta^{18}O$ =-7.49%) were higher than those of the natural river water ( $\delta D=-55.77\%$ ;  $\delta^{18}O=-8.98\%$ ), and landscape dams aggravated the evaporation losses of river water, due to the increase of urban land area, which accelerated the rainfall-runoff conversion process, the residence time of surface water in different regions of the Shiyang River Basin had obvious differences, and the MRT from the upstream to the downstream showed a fluctuating downward process, which was shortened from 1,126 days in the upper reaches to 941 days in the lower reaches, and the MRT was mainly controlled by the basin's landscape features. In addition, there was a strong relationship between the isotopic composition of the reservoir and the surrounding groundwater. Overall, urbanization has a profound impact on the hydrological system of the basin, and the results of this study can provide some references for future research on urbanization and the water cycle, and improve our understanding of the hydrological processes of basins in arid zones.

27. Line 440-443: not really demonstrated but could be done with the available data most probably

**Response:** Based on your suggestions, we have modified the presentation here, and the modified information has been responded to in question 26 above, thank you for your help.

#### 28. Line 443-445: assumption only

**Response:** Based on your suggestions, we have modified the presentation here, and the modified information has been responded to in question 26 above, thank you for your help.

## 29. Many references are not properly cited in the text:

**Response:** I am very sorry for our negligence. We have re-cited the references, thank you for your help.

## 30. Line 508: small caps

**Response:** Based on your suggestions, we have modified the references here.

### 31. Line 521: small caps

**Response:** Based on your suggestions, we have modified the references here.

#### Reference:

Gibson, J. J. and Edwards, T. W. D.: Regional water balance trends and evaporation-transpiration partitioning from a stable isotope survey of lakes in northern Canada, Global Biogeochem. Cycles, 16, 10-1-10 – 14, https://doi.org/10.1029/2001GB001839, 2002.

# 32. Line 601 : some information is missing

**Response:** Based on your suggestions, we are citing the research results updated here. Reference:

Négrel, P., Petelet-Giraud, E., and Millot, R.: Tracing water cycle in regulated basin using stable  $\delta^{18}O-\delta^2H$  isotopes: The Ebro river basin (Spain), Chemical Geology, 422, 71–81, https://doi.org/10.1016/j.chemgeo.2015.12.009, 2016.

# Effects of Urbanization on the water cycle in the Shiyang River

# 2 Basin: Based on stable isotope method

- Rui Li<sup>a,b</sup>, Guofeng Zhu<sup>a,b,\*</sup>, Siyu Lu<sup>a,b</sup>, Liyuan Sang<sup>a,b</sup>, Gaojia Meng<sup>a,b</sup>, Longhu Chen<sup>a,b</sup>,
- 4 Yinying Jiao<sup>a,b</sup>, Qinqin Wang<sup>a,b</sup>

#### 5 Affiliations:

- 6 a College of Geography and Environmental Science, Northwest Normal University, Lanzhou
- 7 730070. Gansu. China
- 8 <sup>b</sup> Shiyang River Ecological Environment Observation Station, Northwest Normal University,
- 9 Lanzhou 730070, Gansu, China
- 10 \*Corresponding author. Email: zhugf@nwnu.edu.cn.
- Abstract: In water-scarce arid areas, the water cycle is affected by urban 11 development and natural surface changes, and urbanization has a profound impact on 12 the hydrological system of the basin. Through an ecohydrological observation system 13 14 established in the Shiyang River basin in the inland arid zone, we studied the impact of urbanization on the water cycle of the basin using isotope methods. The results 15 16 showed that urbanization significantly changed the water cycle process in the basin, and accelerated the rainfall-runoff process due to the increase of urban land area, and 17 the mean residence time (MRT) of river water showed a fluctuating downward trend 18 19 from upstream to downstream, and was shortest in the urban area in the middle reaches, and the MRT was mainly controlled by the landscape characteristics of the 20 basin. In addition, our study showed that river water and groundwater isotope data 21 were progressively enriched from upstream to downstream due to the construction of 22 metropolitan landscape dams, which exacerbated evaporative losses of river water, 23

- and also strengthened the hydraulic connection between groundwater and river water around the city. Our findings have important implications for local water resource management and urban planning and provide important insights into the hydrologic dynamics of urban areas.
- 28 **Keywords:** Urbanization; Water cycle; Stable isotopes; River Connectivity

#### 1 Introduction

24

25

26

27

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

According to the "2020 Global Cities Report," urban areas are currently home to more than half of the worldwide people, which amounts to 56.2%. This pattern is expected to continue over the course of the next decade, culminating in an urbanization rate of 60.4% by the year 2030. In addition, the study forecasts that by the year 2050, approximately seventy percent of the world's population would reside in urban areas (Chen et al., 2020; UN, 2019; UN-Habitat, 2020). Unlike other regions, urban regions have a substantial influence on the hydrological system, resulting in significant consequences on water balance and the water cycle (Gillefalk et al., 2021). To meet the diverse household and industrial requirements in metropolitan areas, where the population is concentrated and water demands are high, a complex interplay between natural and manmade components of the water cycle is required. These components include both natural features such as streams and groundwater, as well as human-made systems like drinking water and drainage networks (Gessner et al., 2014). Urbanization exacerbates water depletion and has far-reaching impacts on groundwater (Flörke et al., 2018; McDonough et al., 2020), affecting the environment and water availability (Bhaskar and Welty, 2015). Rapid urbanization will seriously

pressure the structure, function and water quality degradation of basin ecosystems (Grimm et al., 2008; Sun and Lockaby, 2012; Sun et al., 2015).

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

Urbanization's effects on basin hydrology and the related processes have complex and varying consequences (Caldwell et al., 2012; Martin et al., 2017). In the past few decades, with the continuous acceleration of urbanization, human activities in urban areas have become more frequent, and the hydrological effects of urbanization have become more intense, attracting widespread attention worldwide (Salvadore et al., 2015). The rise of impervious surfaces in urbanized regions increases the rate of urban water runoff, which raises the danger of urban floods (Wing et al., 2018). In addition, high-intensity human activities have led to increased discharge of domestic sewage and industrial wastewater, deteriorating water quality and ecological environment (Pickett et al., 2011). Meanwhile, basin water cycle processes are influenced by a combination of meteorological and subsurface factors. It has been found that urbanization has led to significant increases in runoff and peak flows in rivers (Liu et al., 2018; Han et al., 2022) and has resulted in shorter runoff response times (Anderson et al., 2022), which also exacerbates the intensity and frequency of flooding in basins (De Niel and Willems, 2019; Blum et al., 2020). On the other hand, the urbanization process leads to an increase in the amount of rainfall in the basin as well as an increase in the frequency of extreme rainfall events (Shastri et al., 2015; Fu et al., 2019; Yang et al., 2021), whereas in dryland inland river basins in arid zones that are dependent on water resources for development, the impacts of urbanization on the water cycle processes of the basins are still not clear, and they

need to be explored in depth the effects of urbanization on basin water cycle processes.

Hence, study into how human activities alter the features of river runoff and the water cycle within a basin is essential for the prudent use and sustainable development of

water resources.

68

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

Isotopes that are stable of hydrogen and oxygen are very useful tools for investigating hydrological issues that are connected to surface water and groundwater sources (Fekete et al., 2006; Förstel and Hützen, 1983; Vystavna et al., 2021). Researchers have been conducting studies using stable isotopes as tracers over the course of the past few years in order to explore the impact that urbanization has had on the water cycle. Urbanization has the potential to trigger and intensify convective activity and warm-season rainfall in both urban areas and their surrounding regions (Burian and Shepherd, 2005). Researchers generally agree that urbanization reduces depressions on the underlying surface, weakens water permeability and increases runoff. At the same time, the lower roughness of the underlying surface shortens the confluence time (Guan et al., 2015; Oudin et al., 2018). Moreover, against the backdrop of swift urbanization, the swift proliferation of urban regions has resulted in a sharp surge in impermeable areas, alterations to regional microclimates, and the erection of a vast number of infrastructures (including overpasses, subways, and so on), all of which have significantly impacted the water cycle process in urban areas (Jacobson, 2011; Westra et al., 2014). The complex connection between the permeable and impermeable zones influences the surface confluence processes (Bruwier et al., 2020). The construction of urban water conservation projects, such as rubber dams

and pumping stations, also affects the confluence process of urban areas to a certain extent (Zhu et al., 2021). Limited long-term and continuous monitoring has hampered accurate depiction of urbanization's spatiotemporal effects on basin hydrology. Furthermore, the scientific research till lacks sufficient research on arid regions that heavily depend on mountain river runoff for sustenance and development.

Against the background of increasing urbanization, it is particularly important to study the hydrological impacts of urbanization on basins and their corresponding countermeasures, especially in arid inland river basins, where the impacts of human activities in urban areas on rivers may be more prominent. Therefore, the Shiyang River Basin (SYR), located in the inland arid zone of Northwest China, was used as an example to study the impact of urbanization on the hydrology of the basin using the stable isotope method. The following problems are proposed to be solved: (1) An examination of the mechanisms underlying evaporation and infiltration of surface water within urban aquatic ecosystems; (2) Assessing the effects of urbanization on water body connectivity through a comprehensive analysis; (3) The influence of urbanization on the precipitation-runoff process is analyzed. This provides us with essential information on how to maintain and manage the water resources found in inland river basins, which is especially useful in light of the fact that the rate of urbanization is growing.

#### 2 Systems, Data, and Methods of Observation

The SYR Basin is located in Gansu Province, China, to the east of the He-xi Corridor. Its coordinates are  $101^{\circ}22' \sim 104^{\circ}16'$  E and  $36^{\circ}29' \sim 39^{\circ}27'$  N. The SYR

Basin is bounded to the west by the Wushaoling Mountain and to the north by the foothills of the Qilian Mountain (Zhu et al., 2019). The basin in question is situated within the continental temperate belt, characterized by a parched climate and diverse topography. Annual precipitation hovers within the range of 100 to 600 mm, while pan evaporation levels exhibit greater variability, ranging from 700 to 2600 mm annually. The majesty of the Qilian Mountains is where the SYR begins its journey, and the Qilian Mountains are the source of its eight main tributaries. The SYR is principally supported by the convergence of precipitation, snowmelt, and glacier runoff (Wei et al., 2013).

The Wuwei City is crossed by four important rivers, namely the Xiying, Zamu, Huangyang and Jinta, which cover a catchment area of 3986 km². As the principal water source for the entire region, the SYR Basin is one of the most highly utilized inland river basins in terms of water resource development and consumption worldwide. The dams in the SYR basin are predominantly situated in close proximity to the urbanized regions of Liangzhou District, located within Wuwei City. Liangzhou District, situated in the middle of the basin, boasts of a relatively high population density and a notable commercial concentration. At the turn of the millennium, Wuwei City only boasted a paltry five landscape dams positioned on its rivers. As of 2019, this figure has surged dramatically, with a staggering total of 51 urban landscape dams now gracing both urban and peri-urban areas of the city. These dams are primarily composed of man-made landscape waterfalls and rubber dams, fulfilling their core function of creating public landscape water bodies within the urban expanse.

#### 134 (Zhu et al., 2021).




Figure 1 (a) The location of the study area, (b) Comprehensive observation system for the study area, (c) Urban surface water sampling points (from Google Maps), (d) Common urban landscape dams in SYR Basin.

#### 3 Sampling and data analysis

Since 2017, a comprehensive observation system has been established in the SYR Basin, and stable isotope observations and hydrometeorological observations have been carried out on surface water, shallow groundwater and rainfall. Continuous sampling in the SYR Basin was carried out from April 2017 to March 2021, different water bodies were sampled, and we collected a total of 943 samples from 24 sampling points (Table 1). The river sampling location ought to be selected such that it is physically possible to go as close to the middle of the river as possible, with the goal of minimizing the impact of areas with standing water and sewage. Artesian well water was collected as groundwater samples at 7 sampling locations around the basin. The automated weather station was used to measure meteorological factors such as

temperature and relative humidity while collecting precipitation samples. Water samples were sealed in high-density polyethylene bottles to avoid evaporation and leakage during transit and storage, precipitation samples were collected using weather station standard rain gauges. These samples were then frozen and wrapped with plastic tape.

Table 1 Basic information on precipitation, surface water and groundwater sampling sites

Parameter	Compling Doint	Number	Compling posied	Collection	
rarameter	Sampling Point	Number	Sampling period	Channels	
Precipitation	P1, P2, P3, P4, P5,P6,	207	D	Rain tube collection	
	P7,	387	Precipitation events		
Surface Water	\$1,\$2,\$3,\$4,\$5,\$6, \$7,	270	M 41	Sampling in river water	
	S8, S9, S10	270	Monthly		
Groundwater	G1、G2、G3、G4、G5、	100	M 41	Sampling from wells	
	G6、G7	189	Monthly		

Analysis of the water samples is conducted through liquid water isotope analysis utilizing the DLT-100 (Los Gatos Research) in the Stable Isotope Laboratory at Northwest Normal University. Each water sample and isotope standard are injected six times in succession to assure reliable findings, with the first two injection values eliminated and the average of the last four injections used for final analysis, thereby avoiding any potential isotope analysis memory effect. The isotope measurements were denoted by the symbol " $\delta$ ," which indicates the deviation in thousandths from the Vienna Standard Mean Ocean Water:

164 
$$\delta_{\text{sample}}(\%) = \left[ \left( \frac{R_s}{R_{v-smow}} \right) - 1 \right] \times 1000$$
 (1)

where  $R_s$  is the ratio of  $^{18}\text{O}/^{16}\text{O}$  or  $^{2}\text{H}/^{1}\text{H}$  in the collected sample, Rv-smow is the

ratio of  $^{18}\text{O}/^{16}\text{O}$  or  $^{2}\text{H}/^{1}\text{H}$  of the Vienna standard sample, and the analytical accuracy of  $\delta D$  and  $\delta^{18}O$  is  $\pm 0.6\%$  and  $\pm 0.2\%$ , respectively.

# 3 Analysis methods

#### 3.1 Calculation and indication of *d-excess*

Dansgaard (1964) introduced the concept of deuterium excess (d-excess) as the difference in isotopic composition between global precipitation and the Vienna Standard Mean Ocean Water ( $V_{SMOW}$ ) reference water, which corresponds to a value of 10‰. This parameter reflects the average isotopic composition of air masses associated with precipitation and is widely used to identify atmospheric source regions (Deng et al., 2016). d-excess was proposed by Dansgaard (Dansgaard, 1964) and is defined as:

$$d\text{-}excess = \delta D - 8\delta^{18}O \tag{2}$$

# 3.2 Calculation of evaporation losses of surface water

The losses of surface water through evaporation and the resulting fluctuations in water levels of rivers, lakes, and wetlands are key aspects of the terrestrial water cycle that merit significant attention (Gammons et al., 2006; Hamilton et al., 2005). Evaporation is the primary mechanism of water losses in the water cycle. For river water in dry regions and urban river water that flows slowly due to manmade constraints, evaporation cannot be ignored. Thus, it is vital to address the alteration of urban landscape dam water caused by non-equilibrium isotope fractionation during evaporation. The provided formula (3) can be used to estimate the rate of evaporative water losses from the body of water in question (Skrzypek et al., 2015):

$$f = 1 - \left[ \frac{(\delta - \delta^*)}{(\delta_0 - \delta^*)} \right]^{\frac{1}{m}}$$
(3)

The variables in the equation are as follows: f represents the ratio of water lost to evaporation,  $\delta$  denotes the measured values of the water body located in the urban dam area of Wuwei City, situated in the middle reaches of the SYR and  $\delta_{\theta}$  represents the initial value of the hydrogen and oxygen stable isotope of the water body. It is widely assumed that the point of intersection between the local meteoric water line (LMWL) and the local evaporation line (LEL) represents the average isotopic composition of the input water body within the basin (Gibson et al., 2005). In the current investigation, the intersection point marked by  $\delta^{18}O = -7.24\%$  and  $\delta D = -46.9\%$  has been designated as the  $\delta_{\theta}$  value, while  $\delta^*$  denotes the maximum isotope enrichment factor and m corresponds to the enrichment slope. The calculation of the above parameters in this paper is realized in Hydrocalculator software (Skrzypek et al., 2015) (http://hydrocalculator.gskrzypek.com). According to studies (Qian et al., 2007), it is more accurate to use  $\delta^{18}O$  when calculating the evaporation losses ratio, so this study calculates the f value of SYR water using  $\delta^{18}O$  value.

## 3.3 Periodic regression analysis and the mean residence time (MRT)

Seasonal fluctuations in  $\delta^{18}$ O values were analyzed using periodic regression analysis to determine how these values changed over time. This method entailed fitting seasonal sine wave curves to annual  $\delta^{18}$ O variations using least squares optimization (Rodgers et al.,2005):

$$\delta^{18}O = \delta^{18}O_{ave} + A \cdot \left[\cos(c \cdot t - \theta)\right] \tag{4}$$

The modelled  $\delta^{I8}O$  values and the mean weighted annual measured  $\delta^{I8}O_{ave}$  values were both utilized in the analysis of seasonal fluctuations in  $\delta^{I8}O$  levels. Additionally, the measured  $\delta^{I8}O$  annual amplitude (A), the radial frequency of annual fluctuations (c), and the time in days after the start of the sampling period (t) were also considered in this analysis. Furthermore, the phase lag or time of the annual peak  $\delta^{I8}O$  in radians ( $\theta$ ) was determined through this approach.

An exponential model was used for the purpose of estimating the mean residence time (MRT). This model operates on the presumption that precipitation inputs quickly mix with resident water. In order to do this, the following equation was used (Maloszewski et al., 1983; Rodgers et al., 2005):

$$MRT = c^{-1} \cdot \left[ (A_{Z2} / A_{Z1})^{-2} - 1 \right]^{0.5}$$
 (5)

The amplitude of precipitation  $(A_{ZI})$ , the amplitude of the surface water outputs  $(A_{Z2})$ , and the radial frequency of the annual fluctuation (c) as defined in Eq. (4) were taken into consideration to estimate the mean residence time (MRT).

#### 4 Results

#### 4.1 Spatiotemporal distribution of isotopes in different water bodies

The isotopes values of the surface water in the SYR Basin show a clear enrichment from upstream to downstream when viewed from space. It is worth noting that landscape dams and reservoirs in urban areas alter this pattern significantly, producing markedly higher isotopic compositions of surface water around such structures (Fig. 2). To be more specific, the surface water throughout the entire basin had average isotope values that were lower than those of the sampling points in the dams region, which had values that were greater (Table 2). In addition, the dams

slowed the flow of the river, this resulted in isotope enrichment of the river water. Notably, these values exhibit spatial and temporal variability, with the largest  $\delta D$  and  $\delta^{18}O$  values observed in river water, and the lowest in groundwater.




Figure 2 Longitudinal variation of  $\delta D$  and  $\delta^{18}O$  in river water and groundwater in the SYR Basin.

To be more specific, over the course of time, these values shift seasonally from spring to autumn (Table 2, Fig. 3). There was a range of values from -75.43‰ to -40.62‰ for the  $\delta D$  values of surface water, with an average of -53.53‰. The  $\delta^{18}O$  values display a varied range, from -10.43‰ to -5.53‰, with an average of -8.54‰, whereas the *d-excess* values demonstrate variability ranging from 10.26‰ to 29.72‰, with 15.28‰ as the average value. A broad spectrum of  $\delta D$  values are observed during the summer season, ranging from -61.27‰ to -31.16‰, with an average -48.90‰. Meanwhile,  $\delta^{18}O$  values fluctuate between -9.52‰ and -3.41‰, with an average -8.12‰. The phenomenon that was observed can be traced back primarily to

the aftereffects of the Hongyashan Reservoir built downstream. Because the reservoir has such a large capacity for water retention, it causes significant amounts of river water to evaporate in summer, which ultimately results in a discernible enrichment of the isotopic composition. In both surface water and groundwater,  $\delta D$  and  $\delta^{18}O$  showed significant seasonal variations (Fig. 3). Seasonal variations were more pronounced in surface water than in groundwater, with surface water showing the largest amplitude in spring and the smallest amplitude in fall, while groundwater showed closer amplitudes in all seasons, which also indicates that groundwater is less disturbed.

Table 2 Isotopic composition statistics of surface water in SYR Basin

Sampling Point	$\delta^{18}{ m O}$			δD			d-excess		
	Mean	Min.	Max.	Mean	Min.	Max.	Mean	Min.	Max.
<b>S</b> 1	-9.35	-9.86	-9.06	-57.16	-59.46	-52.47	17.2	12.33	23.91
S2	-9.22	-10.02	-8.78	-56.62	-63.85	-10.02	16.46	15.53	19.28
S3	-7.74	-9.03	-7.75	<b>-</b> 49.84	-50.76	-46.66	15.42	13.59	19.48
S4	-7.29	-8.79	-7.65	-46.22	-53.29	-46.26	14.9	11.01	18.03
S5	-7.43	-9.11	-5.53	-48.84	-56.66	-40.62	14.29	14.21	29.72
<b>S</b> 6	-9.54	-10.43	-8.29	-60.14	-75.43	-54.40	14.31	10.26	17.62
S7	-9.04	-9.54	-8.21	-54.23	-70.04	-48.03	16.54	12.81	21.16
S8	-9.15	-10.35	-8.64	-56.37	-63.35	-52.22	16.84	14.56	19.54
<b>S</b> 9	-8.41	-9.70	-6.02	-53.95	-65.33	-45.54	13.33	12.31	19.50
S10	-8.18	-8.84	-6.58	-51.92	-58.05	-45.39	13.48	12.21	21.72

4.2 The Relationship between  $\delta D$  and  $\delta^{18}O$  values

As shown by the linear fitting equation  $\delta D = 7.52\delta^{18}O + 7.58$ , there is a significant linear positive correlation ( $R^2 = 0.96$ ) between  $\delta D$  and  $\delta^{18}O$  in atmospheric precipitation in the SYR Basin (Fig. 3). It is clear that the slope (7.52) and intercept (7.58) of the local meteoric water line (LMWL) are smaller than the global meteoric water line (GMWL), which can be attributed to the basin's location in an inland arid region, where precipitation disturbances are less frequent and evaporative

fractionation of precipitation is stronger. On the other hand, compared with the slopes of the LMWL, the slopes of the surface water line (SWL) and the groundwater line (GWL) are relatively close (Fig. 3), indicating that there is a strong hydraulic connection between groundwater and river water in the SYR basin, and the slopes of GWL and RWL show GWL > RWL in all seasons, suggesting that the river water is most affected by evaporation and groundwater is less affected by evaporation. In addition, both surface water and groundwater sampling points were distributed near the LMWL, indicating that both river water and groundwater receive recharge from precipitation. Overall, the H-O isotopic composition of surface water samples from the SYR showed a linear regression of  $\delta D = 5.63 \delta^{18}O - 6.11$ , and the slope of RWL was the largest in the autumn (slope = 6.65) and the smallest in the summer (slope = 5.56), which indicated that the river water evaporated the weakest in the autumn and the strongest in the summer.




Figure 3 Relationship between  $\delta D$  and  $\delta^{18}O$  in various water bodies in the SYR Basin during different seasons (a) Spring, (b) Summer, (c) Autumn, (d) The contrast between RWL, GWL, LMWL and GMWL throughout the sampling period.

Isotopic analysis of groundwater samples reveals a range of  $\delta D$  and  $\delta 18O$  values spanning from -50.7‰ to -71.9‰ and from -7.23‰ to -10.4‰, respectively. Moreover, the groundwater samples analyzed in the study displayed a linear regression of  $\delta D$ =6.3 $\delta^{18}O$ -2.15 (R<sup>2</sup>=0.86). And it is interesting to note that groundwater also shows significant enrichment near the urban landscape dams (Fig. 2), indicating that groundwater is also affected by evapotranspiration, mainly because the Wuwei urban area is in the region of a large alluvial fan in front of the mountains, the sand and gravel aquifers are very permeable, and the depth of groundwater burial

is shallow, making the groundwater more susceptible to the effects of evaporation.

# 4.3 Impact of urbanization on groundwater

We compared monthly variations in isotopic values of groundwater near the city with monthly variations in river water from a landscaped dam and found that the monthly variations in groundwater near the city were closely related to river water from a landscaped dam. The concentration of groundwater sampling sites near the city near the sampling sites of the dam water indicates that the groundwater around the city has similar isotopic signatures to the dam and river water (Fig. 4). This suggests that groundwater near the city is recharged by river water during the summer months. In addition, we demonstrated this by comparing the data of the dam river water with the groundwater level. In addition, a portion of the groundwater sampling sites around the city are located in the lower right corner of the LMWL, which suggests that the groundwater around the city may also experience some degree of evaporation.




Figure 4 (a) Relationship between  $\delta^{18}O$  and  $\delta D$  of groundwater around city and urban river water; (b) Monthly variations of  $\delta^{18}O$  in groundwater around city; (c) Monthly variations of  $\delta D$  in groundwater around city.

In addition, we also compared and analyzed the changes of groundwater isotope values with those of groundwater around the city in the whole basin, and found that there was a close correlation between the changes of groundwater around the city and those of the river, while the other groundwater isotope values did not have a strong correlation with the river (Fig. 5). In the urban area, the mean values of  $\delta D$  and  $\delta^{18}O$  of the dammed river water were -8.26% and -49.88%, respectively, while the mean values of  $\delta D$  and  $\delta^{18}O$  of the groundwater around the city were -8.44% and -50.36%, respectively, which indicated that the  $\delta D$  and  $\delta^{18}O$  values of the groundwater around the city were similar to those of the river water in the dammed city. In addition, the isotopic mean values of  $\delta D$  and  $\delta^{18}O$  of groundwater throughout the SYR basin were

-8.73‰ and -54.78‰, which are significantly different from the isotopic values of river water in the urban dam.




Figure 5 (a) Monthly variations of  $\delta^{18}$ O in urban river water and groundwater around city, (b) Monthly variations of  $\delta$ D in urban river water and groundwater around city.

# 4.4 Temporal and spatial variation of surface water evaporation losses in the urban area of Wuwei

In addition to being an essential part of the hydrological cycle, evaporation is widely recognized as one of the most significant factors driving climate change in semi-arid regions and in telluric ecosystems (Gibson et al., 2002; Gibson and Edwards, 2002). An obviously spatial and temporal fluctuation can be seen in the amount of surface water that is lost to evaporation in the upper mountain area as well as the intermediate urban area of the SYR basin (Fig. 6). Analyzed from a time-varying perspective, there is significant seasonal variation in surface water evaporation losses both in the upstream mountainous region and the midstream urban area of Wuwei, with the highest rates occurring during summer and the lowest during winter (Fig.6). Additionally, a spatial comparison reveals that surface water evaporation losses in the midstream urban area of Wuwei are significantly greater than those in the upstream

#### mountainous area.




Figure 6 Evaporation losses from surface water in different areas of the SYR (a) Upper reaches mountainous area, (b) Middle reaches urban areas.

Differences contributing to evaporation losses from the river in the upstream and midstream urban areas can be explained mainly by the landscape characteristics of the basin. In the upstream of the Shiyang River, higher vegetation cover and atmospheric humidity in the mountainous areas result in weaker evaporation losses, while the midstream are dominated by urban land, and urban landscapes increase the watershed area and slow down the river, exacerbating evaporation losses from the river.

## **5 Discussion**

## 5.1 Effects of Urbanization on the Rainfall-Runoff Process

Fig. 7 depicts the regression model of rainfall events in the SYR Basin, represented by a sine wave, and the fitting of surface water  $\delta^{18}$ O across the research season. The  $\delta^{18}$ O levels of precipitation reported in the SYR Basin have an excellent regularity (R<sup>2</sup>=0.46) and a seasonal patterns trend that effectively depicts the nfluence of the monsoon climate on the local environment (Zhu et al., 2019). Seasonal variations are seen in the generally steady  $\delta^{18}$ O and  $\delta^{18}$ O values of the upstream water.

These results indicate that the predominant component of the river water is the baseflow resulting from recent precipitation runoff. Throughout the duration of the study, the majority of the lowest  $\delta^{18}$ O values in the 10 surface water sample points were recorded during the winter, whilst the highest values were recorded during the summer. These trends coincide with both the temporal variation of precipitation isotopes in the SYR Basin, indicating that precipitation input is the underlying cause of isotope changes in river water. Nevertheless, variations in the isotopes of river water differ in range across various regions within the SYR Basin, with significant variation in the degree of fit for the regression curve. The fitting degree of surface water in the upper and lower reaches is relatively low (R<sup>2</sup>=0.37, R<sup>2</sup>=0.28, R<sup>2</sup>=0.23), implying limited seasonal isotopic variability in these regions. The midstream surface water exhibits a notably higher degree of conformity as compared to its upstream and downstream counterparts (R<sup>2</sup>=0.38, R<sup>2</sup>=0.48, R<sup>2</sup>=0.62, R<sup>2</sup>=0.78, R<sup>2</sup>=0.54, R<sup>2</sup>=0.48, R<sup>2</sup>=0.52). Moreover, the isotopic composition of surface water throughout this area exhibits notable cyclic variations.

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365




Figure 7 Fits the annual regression model of  $\delta^{18}$ O in SYR Basin precipitation and river water (time: 2019/4/17—2020/4/23; S1-S10 are surface water sampling points).

The reasons for differences in isotope periodicity in different regions may be attributed to local water management systems, topographic features and urban development. At points S1, S2, and S10, the correlation of model simulations was low, which could be attributed to the presence of Xiying Reservoir in the upstream as well as Hongyashan Reservoir in the downstream (Sang et al., 2023), where seasonal

variations in the isotope values of the river water are interfered by the reservoir dispatching activities. At points S3 to S5, the correlation of the model simulation is higher, which is because in the middle reaches of the SYR basin, the expansion of urban built-up areas leads to a significant increase in surface runoff during the rainy season, and according to the land use data, the land area of the towns in Wuwei City has continued to increase by 134.38 km<sup>2</sup> from 2010 to 2018, resulting in the surface water showing a cyclical trend comparable to that of the precipitation. Since the 1950s, in order to better utilize water resources, 13 small and medium-sized reservoirs with a total storage capacity of 900,000 m<sup>3</sup> were constructed during this period (Ma et al., 2010), increasing the proportion of rainfall in the runoff constituents as a result of The correlation of the model simulation is at a high level at points S6~S9, where, in contrast to the high-elevation areas in the upper reaches, the terrain in the middle and lower reaches of the SYR basin is relatively flat, mainly with cultivated land and deserts, and is less disturbed by human activities (Sun et al., 2021), which further reflects the responsiveness to recent precipitation inputs.

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

The Dunnett's test revealed a significant difference (P < 0.05) between the MRT of the river and the annual magnitude of  $\delta^{18}$ O of the river. We further investigated the relationship between the estimated mean residence time and basin landscape features such as topography (Fig. 8). Using the digital elevation model (DEM) to calculate the mean slope of the SYR basin, we found that the mean residence time was also strongly correlated with the mean basin slope (R<sup>2</sup> = 0.63), and that the upper reaches of the Shiyang River basin are mainly high-elevation mountainous areas, where the

topography is sloped, but where the vegetation cover is high and dominated by alpine meadows, subalpine scrub and Qinghai spruce (Zhang et al. 2023), the greater slope leads to a higher gravitational potential, which tends to result in a negative correlation with mean residence time (McGuire et al., 2005), which also contributes to the potentially higher MRT values in the upstream mountains. In our study, catchment area (CA) had a low correlation with MRT ( $R^2 = 0.40$ ), and a weak relationship between catchment area and MRT has been observed in other studies (McGlynn et al., 2003; McGuire et al., 2005).




Figure 8 Correlation between mean slope of the basin (a), catchment area (b), sand clay loam ratio (c), ratio of residential and industrial areas to total basin area (d) and MRT.

Soil is an important component of basin hydrology, and the physical properties of soil, such as water-holding capacity and pore space distribution, have an important

influence on the response to precipitation in the basin and the sand-clay-loam soil ratio is used here to investigate the possible relationship with MRT. The results showed that the content of sand clay loam ratio showed a strong positive correlation with MRT (R<sup>2</sup>=0.62). Wuwei City is located in the pre-mountain flood-fan belt, and the soil is dominated by sandy soil (Zhang et al., 2023), which is loose in texture, has good permeability and good water retention properties, and is mainly used for agricultural cultivation. Its good permeability increases the vertical movement of water and the length of flow paths, leading to a longer MRT. There is a strong negative correlation between the MRT and the ratios of resident and industrial areas (RI) (R<sup>2</sup>=0.49), which also indicates that as urbanization progresses, with the increase of urban land, this undoubtedly leads to a significant shortening of the MRT. However, the MRT in the mid-river urban area is not much shorter as compared to the downstream, which may be attributed to the fact that the mid-river The large number of landscape dams constructed in the urban areas, currently 51 urban landscape dams have been built in the peri-urban areas of Wuwei City, and the considerable number of landscape dams may have counteracted the impact of the urban land use, resulting in a lengthening of the MRT in the middle reaches as well.

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

#### 5.2 Effects of Water Conservancy Projects in Urban Areas on Isotope Dynamics

Recent studies have suggested that the development of dam-reservoir systems may result in river fragmentation and modifications in flow regimes in terms of their volume, frequency, and duration (Négrel et al., 2016; Murgulet et al., 2016; Peñas and Barquín, 2019; Maavara et al., 2020). Furthermore, chemical-containing nutrient

migration, such as phosphorus, may occur during sediment movement, resulting in widespread eutrophication problems (Yang et al., 2007; Duan et al., 2019). As of 2019, a total of 51 urban landscape dams, primarily consisting of artificial landscape waterfalls and rubber dams, have been constructed in and around Wuwei city (Zhu et al., 2021). In the metropolitan coast of Wuwei, many landscape dams have led to isotopic enrichment in surface water. This damping effect has been observed in numerous dammed rivers across the globe, including the Rio Grande in the southwestern United States (Vitvar et al., 2007) and the Ebro River in Spain (Négrel et al., 2016), as evidenced by isotopic tracers. In the metropolitan coast of Wuwei, a number of landscape dams have led to the enrichment of isotopic tracers in the surface water. The results indicate that the  $\delta D$  and  $\delta^{18}O$  levels of the surface water at the outflow of Wuwei City are greater than those at the inflow (Fig. 2). Moreover, the influence of evaporation on isotopic composition should not be overlooked, as it can lead to a decrease in *d-excess* values (Peng et al., 2012). Consistent with previous studies (Wang et al., 2019), we observed that the *d-excess* of influent water was higher than that of urban river water. This observation further supports the accumulation of heavy H-O isotopes in the surface waters of the dam areas, as shown in Fig. 6a. In contrast, due to the confluence of tributaries prior to the S7 sampling point, the river water has lower isotopic values, resulting in elevated *d-excess* values between S6 and S8.

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450




Figure 9 (a) The longitudinal variation of the surface water *d-excess* of the SYR, (b) The longitudinal variation of the surface water MRT of the SYR.

## 5.3 Effects of Urbanization on the Water Cycle of basins

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467


468

Localized microclimates in urban areas allow for changes in precipitation and evapotranspiration processes, while urbanization alters the pristine subsurface, complicating water cycle processes in the basin (Jacobson, 2011; Westra et al., 2014; Oudin et al., 2018). In terms of the impact on runoff, it is mainly reflected in the increase of surface impermeability due to urbanization, the land use area of Wuwei urban land increased by about 134.38 km<sup>2</sup> from 2010 to 2018, which greatly weakened the infiltration process in urban areas, and the rainfall runoff process simulated by sinusoidal cyclic regression method showed that there were significant differences in the river metro in different parts of the Shiyang River Basin, and that the middle reaches of the river had the highest degree of urbanization, and the time of the metro was the shortest, which further increases the contribution of rainfall to runoff. Regarding the effect of urbanization on evapotranspiration, a large number of dams were constructed on the Shiyang River and flowed through the urban area of Wuwei, causing significant evapotranspiration losses, in addition, these landscape

dams also led to hydrogen and oxygen isotope enrichment (Fig. 10), and the numerous reservoirs that were constructed for the construction and development of the city (Ma et al., 2010), and these reservoirs also contributed to a significant evapotranspiration loss effect, which has been previously confirmed in our study was also confirmed (Sang et al., 2023). On the other hand, our study found that the isotopic compositions and trends of urban nearshore groundwater were similar to those of surface water, which suggests that there is a close correlation between urban nearshore groundwater and river water, and that the difference in water levels between river water and groundwater may be the main reason for river recharge of urban nearshore groundwater (Fig. 4). In the rainy season, the river level gradually rises, which decreases the difference between the water levels of urban nearshore groundwater and river water, and the river water recharges the groundwater, and in the dry season, the river level decreases, and the urban nearshore groundwater, which is buried at a shallow depth, in turn recharges the river.

In addition, the growth of urbanization has had a dramatic impact on the water environment in cities, where water problems occur frequently (Giri and Qiu, 2016; Ma et al., 2022). Urbanization has increased impervious surfaces such as parking lots, rooftops, roads, and sidewalks, leading to increased runoff, which creates additional pathways for pollutants to be transported from landscapes to water bodies (Ren et al., 2014; Wilson and Weng, 2010; Nolan et al., 2023). On the other hand, agricultural activities have increased some of the fertilizers, pesticides, herbicides and dairy manure in the farmland into the nearest water bodies, which can directly and

indirectly affect will reduce water quality (Yu et al., 2013). The Shiyang River Basin in the Northwest Arid Zone is an inland river basin with the highest development intensity and the sharpest conflict between water supply and demand in the region. The Liangzhou district in the central part of the Shiyang River basin is the most densely populated artificial oasis with the largest scale of water demand in the entire basin. Our previous study found that direct discharge of industrial and community domestic wastewater into the river led to deterioration of surface water quality around the Shiyang River basin (Ma et al., 2021). In addition agricultural activities have less impact on the upper reaches of the Shiyang River and relatively more impact on the middle and lower reaches, and the application of nitrogen-based fertilizers during agricultural cultivation is the main cause of high NH4<sup>+</sup> and NO3<sup>-</sup> concentrations in the area (Ma et al., 2021), which may also lead to increased salinity and accelerated eutrophication of the river, threatening the safety of the basin's water environment. Overall, human activities (urbanization) may alter the water cycle processes inherent in inland river basins, and the implications of such changes need to be further explored.



491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

Figure 10 Schematic diagram of the effect of urbanization on river isotope dynamics.

#### **6 Conclusions**

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

In this study, we investigated the hydrometeorological and isotopic data of the Shiyang River Basin from 2017 to 2021, and our investigations showed that urbanization had a significant impact on the water cycle of the basin. The results showed that the isotopic values of the river water showed a significant enrichment from upstream to downstream, but facilities such as landscape dams and reservoirs in the urban area significantly altered this natural pattern, and the isotopic values of the river water in the urban area ( $\delta D$ =-48.31%;  $\delta^{18}O$ =-7.49%) were higher than those of the natural river water ( $\delta D$ =-55.77%;  $\delta^{18}O$ =-8.98%), and landscape dams aggravated the evaporation losses of river water, due to the increase of urban land area, which accelerated the rainfall-runoff conversion process, the residence time of surface water in different regions of the Shiyang River Basin had obvious differences, and the MRT from the upstream to the downstream showed a fluctuating downward process, which was shortened from 1,126 days in the upstream to 941 days in the downstream, and the MRT was mainly controlled by the basin's landscape features. In addition, there was a strong relationship between the isotopic composition of the reservoir and the surrounding groundwater. Overall, urbanization has a profound impact on the hydrological system of the basin, and the results of this study can provide some references for future research on urbanization and the water cycle, and improve our understanding of the hydrological processes of basin in arid zones.

#### Acknowledgements

This research was financially supported by the National Natural Science Foundation of China (41971036, 41867030).

## **Data availability Statement**

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

551

The isotopic data that support the findings of this study are openly available in Zhu, Guofeng (2022), "Stable water isotope monitoring network of different water bodies in SYR Basin, a typical arid river in China", Mendeley Data, V1, doi: 10.17632/vhm44t74sy.1. The source of soil data comes from the Harmonized World Soil Database (HWSD) constructed by the Food and Agriculture Organization of the United Nations (FAO) and the International Institute for Applied Systems (IIASA) on 2009. The land-use and land-cover change data of the Shiyang River Basin were obtained from Chinese Academy of Sciences, the data centre of resources and environmental science (http://www.resdc.cn).

## **Competing Interests**

We undersigned declare that this manuscript entitled "Effects of Urbanization on the water cycle in the SYR Basin: Based on stable isotope method" is original, has not been published before and is not currently being considered for publication elsewhere.

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

### Reference

Anderson, B. J., Slater, L. J., Dadson, S. J., Blum, A. G., and Prosdocimi, I.: 550 Statistical Attribution of the Influence of Urban and Tree Cover Change on Streamflow: A Comparison of Large Sample Statistical Approaches, Water 552

- Resources Research, 58, e2021WR030742,
- https://doi.org/10.1029/2021WR030742, 2022.
- Asano, Y., Uchida, T., and Ohte, N.: Residence times and flow paths of water in steep
- unchannelled catchments, Tanakami, Japan, Journal of Hydrology, 261, 173–192,
- 557 https://doi.org/10.1016/S0022-1694(02)00005-7, 2002.
- Baker, A.: Land Use and Water Quality, in: Encyclopedia of Hydrological Sciences,
- edited by: Anderson, M. G. and McDonnell, J. J., John Wiley & Sons, Ltd,
- 560 Chichester, UK, hsa195, https://doi.org/10.1002/0470848944.hsa195, 2005.
- Bhaskar, A. S. and Welty, C.: Analysis of subsurface storage and streamflow
- generation in urban basins, Water Resour. Res., 51, 1493–1513,
- 563 https://doi.org/10.1002/2014WR015607, 2015.
- Blum, A. G., Ferraro, P. J., Archfield, S. A., and Ryberg, K. R.: Causal Effect of
- Impervious Cover on Annual Flood Magnitude for the United States,
- Geophysical Research Letters, 47, e2019GL086480,
- 567 https://doi.org/10.1029/2019GL086480, 2020.
- Bruwier, M., Maravat, C., Mustafa, A., Teller, J., Pirotton, M., Erpicum, S.,
- Archambeau, P., and Dewals, B.: Influence of urban forms on surface flow in
- 570 urban pluvial flooding, Journal of Hydrology, 582, 124493,
- 571 https://doi.org/10.1016/j.jhydrol.2019.124493, 2020.
- Burian, S. J. and Shepherd, J. M.: Effect of urbanization on the diurnal rainfall pattern
- in Houston, Hydrol. Process., 19, 1089–1103, https://doi.org/10.1002/hyp.5647,
- 574 2005.

- 575 Caldwell, P. V., Sun, G., McNulty, S. G., Cohen, E. C., and Moore Myers, J. A.:
- Impacts of impervious cover, water withdrawals, and climate change on river
- flows in the conterminous US, Hydrol. Earth Syst. Sci., 16, 2839–2857,
- 578 https://doi.org/10.5194/hess-16-2839-2012, 2012.
- 579 Chen, G., Li, X., Liu, X., Chen, Y., Liang, X., Leng, J., Xu, X., Liao, W., Qiu, Y., Wu,
- Q., and Huang, K.: Global projections of future urban land expansion under
- shared socioeconomic pathways, Nat Commun, 11, 537,
- 582 https://doi.org/10.1038/s41467-020-14386-x, 2020.
- Dansgaard, W.: Stable isotopes in precipitation, Tellus, 16, 436–468,
- 584 https://doi.org/10.1111/j.2153-3490.1964.tb00181.x, 1964.
- De Niel, J. and Willems, P.: Climate or land cover variations: what is driving observed
- changes in river peak flows? A data-based attribution study, Hydrol. Earth Syst.
- 587 Sci., 23, 871–882, https://doi.org/10.5194/hess-23-871-2019, 2019.
- Deng, K., Yang, S., Lian, E., Li, C., Yang, C., and Wei, H.: Three Gorges Dam alters
- the Changjiang (Yangtze) river water cycle in the dry seasons: Evidence from
- 590 H-O isotopes, Science of The Total Environment, 562, 89–97,
- 591 https://doi.org/10.1016/j.scitotenv.2016.03.213, 2016.
- 592 Duan, W., Hanasaki, N., Shiogama, H., Chen, Y., Zou, S., Nover, D., Zhou, B., and
- Wang, Y.: Evaluation and Future Projection of Chinese Precipitation Extremes
- Using Large Ensemble High-Resolution Climate Simulations, Journal of Climate,
- 595 32, 2169–2183, https://doi.org/10.1175/JCLI-D-18-0465.1, 2019.

- Fekete, B. M., Gibson, J. J., Aggarwal, P., and Vörösmarty, C. J.: Application of
- isotope tracers in continental scale hydrological modeling, Journal of Hydrology,
- 330, 444–456, https://doi.org/10.1016/j.jhydrol.2006.04.029, 2006.
- 599 Flörke, M., Schneider, C., and McDonald, R. I.: Water competition between cities and
- agriculture driven by climate change and urban growth, Nat Sustain, 1, 51–58,
- 601 https://doi.org/10.1038/s41893-017-0006-8, 2018.
- 602 Förstel, H. and Hützen, H.: Oxygen isotope ratios in German groundwater, Nature,
- 603 304, 614–616, https://doi.org/10.1038/304614a0, 1983.
- 604 Fu, X., Yang, X., and Sun, X.: Spatial and Diurnal Variations of Summer Hourly
- Rainfall Over Three Super City Clusters in Eastern China and Their Possible
- 606 Link to the Urbanization, JGR Atmospheres, 124, 5445–5462,
- 607 https://doi.org/10.1029/2019JD030474, 2019.
- 608 Gammons, C. H., Poulson, S. R., Pellicori, D. A., Reed, P. J., Roesler, A. J., and
- Petrescu, E. M.: The hydrogen and oxygen isotopic composition of precipitation,
- evaporated mine water, and river water in Montana, USA, Journal of Hydrology,
- 328, 319–330, https://doi.org/10.1016/j.jhydrol.2005.12.005, 2006.
- 612 Gessner, M. O., Hinkelmann, R., Nützmann, G., Jekel, M., Singer, G., Lewandowski,
- J., Nehls, T., and Barjenbruch, M.: Urban water interfaces, Journal of Hydrology,
- 514, 226–232, https://doi.org/10.1016/j.jhydrol.2014.04.021, 2014.
- 615 Gibson, J. J., Edwards, T. W. D., Birks, S. J., St Amour, N. A., Buhay, W. M.,
- McEachern, P., Wolfe, B. B., and Peters, D. L.: Progress in isotope tracer

- 617 hydrology in Canada, Hydrol. Process., 19, 303–327,
- 618 https://doi.org/10.1002/hyp.5766, 2005.
- 619 Gibson, J. J. and Edwards, T. W. D.: Regional water balance trends and
- evaporation-transpiration partitioning from a stable isotope survey of lakes in
- 621 northern Canada: REGIONAL WATER BALANCE USING STABLE
- 622 ISOTOPES, Global Biogeochem. Cycles, 16, 10-1-10-14,
- https://doi.org/10.1029/2001GB001839, 2002.
- 624 Gibson, J. J., Prepas, E. E., and McEachern, P.: Quantitative comparison of lake
- throughflow, residency, and catchment runoff using stable isotopes: modelling
- and results from a regional survey of Boreal lakes, Journal of Hydrology, 2002.
- 627 Gillefalk, M., Tetzlaff, D., Hinkelmann, R., Kuhlemann, L.-M., Smith, A., Meier, F.,
- Maneta, M. P., and Soulsby, C.: Quantifying the effects of urban green space on
- water partitioning and ages using an isotope-based ecohydrological model,
- 630 Hydrol. Earth Syst. Sci., 25, 3635–3652,
- https://doi.org/10.5194/hess-25-3635-2021, 2021.
- 632 Giri, S. and Qiu, Z.: Understanding the relationship of land uses and water quality in
- Twenty First Century: A review, Journal of Environmental Management, 173,
- 41–48, https://doi.org/10.1016/j.jenvman.2016.02.029, 2016.
- 635 Grimm, N. B., Faeth, S. H., Golubiewski, N. E., Redman, C. L., Wu, J., Bai, X., and
- Briggs, J. M.: Global Change and the Ecology of Cities, Science, 319, 756–760,
- https://doi.org/10.1126/science.1150195, 2008.

- 638 Guan, M., Sillanpää, N., and Koivusalo, H.: Storm runoff response to rainfall pattern,
- magnitude and urbanization in a developing urban catchment: Storm Runoff
- Response to Rainfall Pattern, Magnitude and Urbanization, Hydrol. Process.,
- n/a-n/a, https://doi.org/10.1002/hyp.10624, 2015.
- Hamilton, S. K., Bunn, S. E., Thoms, M. C., and Marshall, J. C.: Persistence of
- aquatic refugia between flow pulses in a dryland river system(Cooper Creek,
- 644 Australia), Limnol. Oceanogr., 50, 743–754,
- https://doi.org/10.4319/lo.2005.50.3.0743, 2005.
- Han, S., Slater, L., Wilby, R. L., and Faulkner, D.: Contribution of urbanisation to
- non-stationary river flow in the UK, Journal of Hydrology, 613, 128417,
- 648 https://doi.org/10.1016/j.jhydrol.2022.128417, 2022.
- Jacobson, C. R.: Identification and quantification of the hydrological impacts of
- imperviousness in urban catchments: A review, Journal of Environmental
- Management, 92, 1438–1448, https://doi.org/10.1016/j.jenvman.2011.01.018,
- 652 2011.
- 653 Liu, J., Shen, Z., and Chen, L.: Assessing how spatial variations of land use pattern
- affect water quality across a typical urbanized basin in Beijing, China,
- Landscape and Urban Planning, 176, 51–63,
- https://doi.org/10.1016/j.landurbplan.2018.04.006, 2018.
- Ma, H., Zhu, G., Zhang, Y., Sang, L., Wan, Q., Zhang, Z., Xu, Y., and Qiu, D.: Ion
- migration process and influencing factors in inland river basin of arid area in

- 659 China: a case study of Shiyang River Basin, Environ Sci Pollut Res, 28,
- 56305–56318, https://doi.org/10.1007/s11356-021-14484-3, 2021.
- Ma, J., Pan, F., Chen, L., Edmunds, W. M., Ding, Z., He, J., Zhou, K., and Huang, T.:
- Isotopic and geochemical evidence of recharge sources and water quality in the
- Quaternary aquifer beneath Jinchang city, NW China, Applied Geochemistry, 25,
- 996–1007, https://doi.org/10.1016/j.apgeochem.2010.04.006, 2010.
- Ma, X., Li, N., Yang, H., and Li, Y.: Exploring the relationship between urbanization
- and water environment based on coupling analysis in Nanjing, East China,
- 667 Environ Sci Pollut Res, 29, 4654–4667,
- https://doi.org/10.1007/s11356-021-15161-1, 2022.
- Maavara, T., Chen, Q., Van Meter, K., Brown, L. E., Zhang, J., Ni, J., and Zarfl, C.:
- River dam impacts on biogeochemical cycling, Nat Rev Earth Environ, 1,
- 671 103–116, https://doi.org/10.1038/s43017-019-0019-0, 2020.
- Małoszewski, P., Rauert, W., Stichler, W., and Herrmann, A.: Application of flow
- 673 models in an alpine catchment area using tritium and deuterium data, Journal of
- 674 Hydrology, 66, 319–330, https://doi.org/10.1016/0022-1694(83)90193-2, 1983.
- Martin, K. L., Hwang, T., Vose, J. M., Coulston, J. W., Wear, D. N., Miles, B., and
- Band, L. E.: basin impacts of climate and land use changes depend on magnitude
- and land use context, Ecohydrology, 10, e1870, https://doi.org/10.1002/eco.1870,
- 678 2017.
- McDonough, L. K., Santos, I. R., Andersen, M. S., O'Carroll, D. M., Rutlidge, H.,
- Meredith, K., Oudone, P., Bridgeman, J., Gooddy, D. C., Sorensen, J. P. R.,

- Lapworth, D. J., MacDonald, A. M., Ward, J., and Baker, A.: Changes in global
- groundwater organic carbon driven by climate change and urbanization, Nat
- 683 Commun, 11, 1279, https://doi.org/10.1038/s41467-020-14946-1, 2020.
- McGlynn, B., McDonnell, J., Stewart, M., and Seibert, J.: On the relationships
- between catchment scale and streamwater mean residence time, Hydrol. Process.,
- 686 17, 175–181, https://doi.org/10.1002/hyp.5085, 2003.
- McGuire, K. J., McDonnell, J. J., Weiler, M., Kendall, C., McGlynn, B. L., Welker, J.
- M., and Seibert, J.: The role of topography on catchment-scale water residence
- time: CATCHMENT-SCALE WATER RESIDENCE TIME, Water Resour. Res.,
- 690 41, https://doi.org/10.1029/2004WR003657, 2005.
- Murgulet, D., Murgulet, V., Spalt, N., Douglas, A., and Hay, R. G.: Impact of
- 692 hydrological alterations on river-groundwater exchange and water quality in a
- semi-arid area: Nueces River, Texas, Science of The Total Environment, 572,
- 694 595–607, https://doi.org/10.1016/j.scitotenv.2016.07.198, 2016.
- Négrel, P., Petelet-Giraud, E., and Millot, R.: Tracing water cycle in regulated basin
- using stable  $\delta^{18}O-\delta^2H$  isotopes: The Ebro river basin (Spain), Chemical Geology,
- 697 422, 71–81, https://doi.org/10.1016/j.chemgeo.2015.12.009, 2016.
- Nolan, T. M., Reynolds, L. J., Sala-Comorera, L., Martin, N. A., Stephens, J. H.,
- 699 O'Hare, G. M. P., O'Sullivan, J. J., and Meijer, W. G.: Land use as a critical
- determinant of faecal and antimicrobial resistance gene pollution in riverine
- 701 systems, Science of The Total Environment, 871, 162052,
- 702 https://doi.org/10.1016/j.scitotenv.2023.162052, 2023.

- Oudin, L., Salavati, B., Furusho-Percot, C., Ribstein, P., and Saadi, M.: Hydrological
- impacts of urbanization at the catchment scale, Journal of Hydrology, 559,
- 705 774–786, https://doi.org/10.1016/j.jhydrol.2018.02.064, 2018.
- 706 Peñas, F. J. and Barquín, J.: Assessment of large-scale patterns of hydrological
- alteration caused by dams, Journal of Hydrology, 572, 706–718,
- 708 https://doi.org/10.1016/j.jhydrol.2019.03.056, 2019.
- 709 Peng, T.-R., Huang, C.-C., Wang, C.-H., Liu, T.-K., Lu, W.-C., and Chen, K.-Y.:
- Using oxygen, hydrogen, and tritium isotopes to assess pond water's contribution
- 711 to groundwater and local precipitation in the pediment tableland areas of
- 712 northwestern Taiwan, Journal of Hydrology, 450–451, 105–116,
- 713 https://doi.org/10.1016/j.jhydrol.2012.05.021, 2012.
- Pickett, S. T. A., Cadenasso, M. L., Grove, J. M., Boone, C. G., Groffman, P. M.,
- Irwin, E., Kaushal, S. S., Marshall, V., McGrath, B. P., Nilon, C. H., Pouyat, R.
- V., Szlavecz, K., Troy, A., and Warren, P.: Urban ecological systems: Scientific
- foundations and a decade of progress, Journal of Environmental Management, 92,
- 718 331–362, https://doi.org/10.1016/j.jenvman.2010.08.022, 2011.
- 719 Qian, H., Dou, Y., Li, X.J., Yang, B.C., and Zhao, Z.H.: Changes of δ<sup>18</sup>O and δD
- along Dousitu River and its indication of river water evaporation. Hydrogeol.
- 721 Eng. Geol. 34 (1), 107–112,
- 722 https://doi.org/10.16030/j.cnki.issn.1000-3665.2007.01.024,2007.

- Ren, L., Cui, E., and Sun, H.: Temporal and spatial variations in the relationship
- between urbanization and water quality, Environ Sci Pollut Res, 21,
- 725 13646–13655, https://doi.org/10.1007/s11356-014-3242-8, 2014.
- Rodgers, P., Soulsby, C., Waldron, S., and Tetzlaff, D.: Using stable isotope tracers to
- assess hydrological flow paths, residence times and landscape influences in a
- nested mesoscale catchment, Hydrol. Earth Syst. Sci., 9, 139–155,
- 729 https://doi.org/10.5194/hess-9-139-2005, 2005.
- 730 Salvadore, E., Bronders, J., and Batelaan, O.: Hydrological modelling of urbanized
- catchments: A review and future directions, Journal of Hydrology, 529, 62–81,
- 732 https://doi.org/10.1016/j.jhydrol.2015.06.028, 2015.
- Sang, L., Zhu, G., Xu, Y., Sun, Z., Zhang, Z., and Tong, H.: Effects of Agricultural
- 734 Large-And Medium-Sized Reservoirs on Hydrologic Processes in the Arid
- Shiyang River Basin, Northwest China, Water Resources Research, 59,
- 736 e2022WR033519, https://doi.org/10.1029/2022WR033519, 2023.
- 737 Shastri, H., Paul, S., Ghosh, S., and Karmakar, S.: Impacts of urbanization on Indian
- summer monsoon rainfall extremes, J. Geophys. Res. Atmos., 120, 496–516,
- 739 https://doi.org/10.1002/2014JD022061, 2015.
- Skrzypek, G., Mydłowski, A., Dogramaci, S., Hedley, P., Gibson, J. J., and Grierson,
- P. F.: Estimation of evaporative loss based on the stable isotope composition of
- 742 water using Hydrocalculator, Journal of Hydrology, 523, 781–789,
- 743 https://doi.org/10.1016/j.jhydrol.2015.02.010, 2015.

- Sun, G., Caldwell, P. V., and McNulty, S. G.: Modelling the potential role of forest
- 745 thinning in maintaining water supplies under a changing climate across the
- conterminous United States: Response of Water Yield to Forest Thinning and
- 747 Climate Change, Hydrol. Process., 29, 5016–5030,
- 748 https://doi.org/10.1002/hyp.10469, 2015.
- Sun, G. and Lockaby, B. G.: Water Quantity and Quality at the Urban-Rural Interface,
- in: Urban-Rural Interfaces, edited by: Laband, D. N., Lockaby, B. G., and
- 751 Zipperer, W. C., American Society of Agronomy, Soil Science Society of
- America, Crop Science Society of America, Inc., Madison, WI, USA, 29–48,
- 753 https://doi.org/10.2136/2012.urban-rural.c3, 2012.
- 754 Sun, Z., Zhu, G., Zhang, Z., Xu, Y., Yong, L., Wan, Q., Ma, H., Sang, L., and Liu, Y.:
- 755 Identifying surface water evaporation loss of inland river basin based on
- evaporation enrichment model, Hydrological Processes, 35, e14093,
- 757 https://doi.org/10.1002/hyp.14093, 2021.
- 758 Talma, S, Woodborne, S. and Lorentz, S.: South African Contribution to the Rivers
- 759 CRP, 2012.
- 760 UN-Habitat: World cities report 2020: the value of sustainable urbanization,
- 761 UN-Habitat, Nairobi, Kenya, 377 pp., 2020.
- United Nations Department of Economic and Social Affairs: World Urbanization
- Prospects 2018: Highlights, United Nations,
- 764 https://doi.org/10.18356/6255ead2-en, 2019.
- Vitvar, T., Aggarwal, P. K., and Herczeg, A. L.: Global network is launched to

- monitor isotopes in rivers, Eos Trans. AGU, 88, 325–326,
- 767 https://doi.org/10.1029/2007EO330001, 2007.
- Vystavna, Y., Harjung, A., Monteiro, L. R., Matiatos, I., and Wassenaar, L. I.: Stable
- isotopes in global lakes integrate catchment and climatic controls on evaporation,
- 770 Nat Commun, 12, 7224, https://doi.org/10.1038/s41467-021-27569-x, 2021.
- Wang, B., Zhang, H., Liang, X., Li, X., and Wang, F.: Cumulative effects of cascade
- dams on river water cycle: Evidence from hydrogen and oxygen isotopes,
- 773 Journal of Hydrology, 568, 604–610,
- https://doi.org/10.1016/j.jhydrol.2018.11.016, 2019.
- Wei, W., Shi, P., Zhou, J., Feng, H., Wang, X., and Wang, X.: Environmental
- suitability evaluation for human settlements in an arid inland river basin: A case
- study of the Shiyang River Basin, J. Geogr. Sci., 23, 331–343,
- 778 https://doi.org/10.1007/s11442-013-1013-y, 2013.
- Westra, S., Fowler, H. J., Evans, J. P., Alexander, L. V., Berg, P., Johnson, F.,
- Kendon, E. J., Lenderink, G., and Roberts, N. M.: Future changes to the intensity
- and frequency of short-duration extreme rainfal, Rev. Geophys., 52, 522–555,
- 782 https://doi.org/10.1002/2014RG000464, 2014.
- Wilson, C. and Weng, Q.: Assessing Surface Water Quality and Its Relation with
- Urban Land Cover Changes in the Lake Calumet Area, Greater Chicago,
- 785 Environmental Management, 45, 1096–1111,
- 786 https://doi.org/10.1007/s00267-010-9482-6, 2010.

- Wing, O. E. J., Bates, P. D., Smith, A. M., Sampson, C. C., Johnson, K. A., Fargione,
- J., and Morefield, P.: Estimates of present and future flood risk in the
- 789 conterminous United States, Environ. Res. Lett., 13, 034023,
- 790 https://doi.org/10.1088/1748-9326/aaac65, 2018.
- 791 Yang, L., Ni, G., Tian, F., and Niyogi, D.: Urbanization Exacerbated Rainfall Over
- European Suburbs Under a Warming Climate, Geophysical Research Letters, 48,
- 793 e2021GL095987, https://doi.org/10.1029/2021GL095987, 2021.
- 794 Yang, S. L., Zhang, J., and Xu, X. J.: Influence of the Three Gorges Dam on
- downstream delivery of sediment and its environmental implications, Yangtze
- River, Geophys. Res. Lett., 34, L10401, https://doi.org/10.1029/2007GL029472,
- 797 2007.
- 798 Yu, D., Shi, P., Liu, Y., and Xun, B.: Detecting land use-water quality relationships
- from the viewpoint of ecological restoration in an urban area, Ecological
- 800 Engineering, 53, 205–216, https://doi.org/10.1016/j.ecoleng.2012.12.045, 2013.
- 801 Zhang, W., Wan, Q., Zhu, G., and Xu, Y.: Distribution of soil organic carbon and
- 802 carbon sequestration potential of different geomorphic units in Shiyang river
- basin, China, Environ Geochem Health, 45, 4071–4086,
- https://doi.org/10.1007/s10653-022-01472-w, 2023.
- Zhu, G., Guo, H., Qin, D., Pan, H., Zhang, Y., Jia, W., and Ma, X.: Contribution of
- recycled moisture to precipitation in the monsoon marginal zone: Estimate based
- on stable isotope data, Journal of Hydrology, 569, 423–435,
- 808 https://doi.org/10.1016/j.jhydrol.2018.12.014, 2019.

Zhu, G., Sang, L., Zhang, Z., Sun, Z., Ma, H., Liu, Y., Zhao, K., Wang, L., and Guo,
H.: Impact of landscape dams on river water cycle in urban and peri-urban areas
in the Shiyang River Basin: Evidence obtained from hydrogen and oxygen
isotopes, Journal of Hydrology, 602, 126779,
https://doi.org/10.1016/j.jhydrol.2021.126779, 2021.